



●Endurance : 3,000 hours at 105℃

●Rated voltage 400V, Capacitance 2.2 to 4.7µF






### **♦**SPECIFICATIONS

Items	Characteristics							
Category Temperature Range	-40 to +105℃							
Rated Voltage Range	400V <sub>dc</sub>							
Capacitance Tolerance	±20%(M) (20°C, 120Hz							
Leakage Current	I=0.04CV+100(max.)							
	Where, I : Max. leaka	Max. leakage current (μA), C : Nominal capacitance (μF), V : Rated voltage (V) (at 20°C after 1 m						
<b>Dissipation Factor</b>	Rated voltage(Vdc)	400V						
(tanô)	tanδ (Max.)	0.25		(20°C, 120Hz)				
Low Temperature	Rated voltage(Vdc)	400V						
Characteristics	Z(-25°C)/Z(+20°C)	6						
(Max. impedance Ratio)	Z(-40°C)/Z(+20°C)	10		(120Hz)				
Endurance	The following specific	ecifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage is applied for 3,000 hours						
	at 105°C.							
	Capacitance change	≦±20	% of the initial value					
	D.F. (tanδ)	≦2009	% of the initial specified value					
	Leakage current	≦The	initial specified value					
Shelf life	The following specifications shall be satisfied when the capacitors are restored to 20℃ after exposing them for 500 hours at 105℃ without							
	voltage applied. Before the measurement, the capacitor shall be preconditioned by applying voltage according to Item 4.1 of JIS C 5							
	Capacitance change	≦±20	% of the initial value					
	D.F. (tanδ)	≦2009	% of the initial specified value					
	Leakage current	≦The	initial specified value					

## **◆DIMENSIONS** [mm]




**♦PART NUMBERING SYSTEM** 

Size code	D	L	Α	В	С	w	Р
HA0	8	10.0	8.3	8.3	9.0	0.7 to 1.1	3.1
JA0	10	10.0	10.3	10.3	11.0	0.7 to 1.1	4.5

## MARKING

EX) 400V3.9µF





1 2 3 4 5 6	7 8 9 10 11 1	13 14 15 16 17 18	
EMKB 40	1 A D A 🗌		
			Supplement code Size code Capacitance tolerance code Capacitance code (ex. 2.2µF:2R2)
			Taping code
			Terminal code
			Voltage code
			Series code
			Category

Please refer to "Product code guide (surface mount type)"

#### **♦STANDARD RATINGS**

WV (Vdc)	Cap (μF)	Size code	ES (Ωmax/	SR (120Hz)	Rated ripple current (mArms/105℃,120Hz)	Part No.	
			20°C	-40℃	(IIIAIIIIS/1050,12012)		
	2.2	HA0	20	1,000	26	EMKB401ADA2R2MHA0G	
400	3.3	JA0	10	500	37	EMKB401ADA3R3MJA0G	
400	3.9	JA0	10	500	38	EMKB401ADA3R9MJA0G	
	4.7	JA0	10	500	39	EMKB401ADA4R7MJA0G	

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Aluminium Electrolytic Capacitors - SMD category:

Click to view products by United Chemicon manufacturer:

Other Similar products are found below :

 EEV-FK1E332W
 22927
 MAL214099813E3
 HUB1800-S
 34610
 RYK-50V101MG5TT-FL
 107AXZ016MQ5
 EMF1EM101E83D00R

 EMK1AM221E83D00R
 EMK1EM471GB0D00R
 EMK1VM101E83D00R
 EMVY350ARA221MHA0G
 UV2G3R3M0810VG

 RVT2A4R7M0605
 MAL214097402E3
 MAL215375471E3
 MAL224699909E3
 MAL224699813E3
 MAL215099017E3
 MAL215099117E3

 MAL215099818E3
 HV100M100E077ETR
 RC0J226M04005VR
 RC0J476M05005VR
 RC1A227M08010VR
 RC1C476M6L005VR

 MAL214099111E3
 50SEV1M4X5.5
 50SKV1M4X5.5
 TYEH1A336E55MTR
 UCD1V100MCQ1GS
 UCX1H471MNQ1MS

 35SEV47M6.3X8
 35SGV220M10X10.5
 35SLV10M5X6.1
 VES2R2M1HTR-0405
 VZH102M1ATR-1010
 50SEV10M6.3X5.5

 50SGV1M4X6.1
 107SML016M
 EDK226M035A9DAA
 EEV-HA1A471UP
 SC1C476M05005VR
 UCX1H471MNS1MS
 VZH331M1ETR-0810

 0810
 VES101M1CTR-0605
 6.3SEV42M4X5.5
 6.3SEV47M4X5.5
 EEVEB2V4R7Q
 EEEFK1H151GP