

# 10-40GHz Frequency Multiplier

## GaAs Monolithic Microwave IC

### Description

The CHX2092a is a cascaded by 4 frequency multiplier monolithic circuit.



It is designed for a wide range of applications, from military to commercial communication systems. The backside of the chip is both RF and DC grounded. This helps to simplify the assembly process.

The circuit is manufactured with a pHEMT process, 0.25µm gate length, via holes through the substrate, air bridges and electron beam gate lithography.

It is available in chip form

### Main Features

- Broadband performances: 9-10GHz
- 11dBm output power for +12dBm input power
- DC bias:  $V_d=3.5\text{Volt}@I_d=80\text{mA}$
- Chip size: 2.31 x 0.97 x 0.10mm



### Main Characteristics

Tamb. = 25°C

Symbol	Parameter	Min	Typ	Max	Unit
Fin	Input frequency range	9		10	GHz
Fout	Output frequency range	36		40	GHz
Pin	Input power		12		dBm
Pout_4xFin	4xFin Output power @ +12dBm input power	9	11		dBm

ESD Protection : Electrostatic discharge sensitive device. Observe handling precautions !

## Electrical Characteristics

Tamb = +25°C, Vd= 3.5V

Symbol	Parameter	Min	Typ	Max	Unit
Fin	Input frequency range	9		10	GHz
Fout	Output frequency range	36		40	GHz
Pin	Input power	11	12	14	dBm
Pout_4xFin	4Xfin Output power for +12dBm input power	9	11		dBm
Pout_Fin	Fin level at the output	-18	-22		dBm
Pout_2xFin	2x Fin level at the output		-16		dBm
Pout_3xFin	3x Fin level at the output		-4		dBm
VSWRin	Input VSWR			2:1	
VSWRout	Output VSWR			2:1	
Id	Bias current		80	130	mA

## Absolute Maximum Ratings

Tamb = +25°C


Symbol	Parameter	Values	Unit
Vd	Drain bias voltage	4	V
Id	Drain bias current	140	mA
Pin	Maximum Input power	16	dBm
Vg	Gate bias voltage	-2 to +0.4	V
Ta	Operating temperature range	-40 to +85	°C
Tstg	Storage temperature range	-55 to +155	°C

(1) Operation of device above any one of these parameters may cause permanent damage.


**Typical on Jig Measurements.**

Bias conditions:  $V_d = 3.5V$ ,  $V_{g12} = -0.8V$ ,  $V_{g3} = -0.2V$


**Harmonic Output power versus frequency @  $P_{in} = 11dBm$**




**Output power versus Input power @  $F_{in} = 10GHz$**




### 4x Fin Output power versus temperature @ Pin= 12dBm



Chip Assembly and Mechanical data



Note: Supply feed should be capacitively bypassed. 25µm diameter gold wire is to be preferred.  
Pad Size: 100 x 100µm




**Bonding pad positions**  
(Chip thickness: 100µm. All dimensions are in micrometers)

## Ordering Information

Chip form : CHX2092a99F/00

Information furnished is believed to be accurate and reliable. However **United Monolithic Semiconductors S.A.S.** assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of **United Monolithic Semiconductors S.A.S.** Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. **United Monolithic Semiconductors S.A.S.** products are not authorised for use as critical components in life support devices or systems without express written approval from **United Monolithic Semiconductors S.A.S.**



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Signal Conditioning](#) category:*

*Click to view products by [United Monolithic Semiconductors](#) manufacturer:*

Other Similar products are found below :

[MAPDCC0004](#) [PD0409J5050S2HF](#) [880157](#) [HHS-109-PIN](#) [DC1417J5005AHF](#) [DC4859J5005AHF](#) [AFS14A30-2185.00-T3](#) [AFS14A35-1591.50-T3](#) [DS-323-PIN](#) [DSS-313-PIN](#) [B39321R801H210](#) [B39321R821H210](#) [B39921B4317P810](#) [1A0220-3](#) [2089-6207-00](#) [JP510S](#) [LFB212G45SG8C341](#) [LFB322G45SN1A504](#) [LFL182G45TC3B746](#) [SF2159E](#) [30057](#) [1P510S](#) [CER0813B](#) [3A325](#) [40287](#) [41180](#) [ATB3225-75032NCT](#) [B69842N5807A150](#) [BD0810N50100AHF](#) [BD2326L50200AHF](#) [BD2425J50200AHF](#) [HMC189AMS8TR](#) [C5060J5003AHF](#) [JHS-114-PIN](#) [JP503AS](#) [DC0710J5005AHF](#) [DC2327J5005AHF](#) [DC3338J5005AHF](#) [43020](#) [LFB2H2G60BB1C106](#) [LFL15869MTC1B787](#) [X3C19F1-20S](#) [XC3500P-20S](#) [10013-20](#) [SF2081E](#) [SF2194E](#) [SF2238E](#) [CDBLB455KCAX39-B0](#) [RF1353C](#) [PD0922J5050D2HF](#)