


Description

United Silicon Carbide, Inc. offers the xR series of high performance SiC Schottky diodes. With zero reverse recovery charge and 175°C maximum junction temperature, USCI's diodes are ideally suited for high frequency and high efficiency power systems with minimum cooling requirements.



| Part Number | Package | Marking |
|-------------|-----------|------------|
| UJD06504TS | TO-220-2L | UJD06504TS |

Features

- ◆ Positive temperature coefficient for safe operation and ease of paralleling
- ◆ 175°C maximum operating junction temperature
- ◆ Extremely fast switching not dependent on temperature
- ◆ Essentially no reverse or forward recovery
- ◆ Enhanced surge capability
- ◆ RoHS compliant
- ◆ Power converters
- ◆ Industrial motor drives
- ◆ Switching-mode power supplies
- ◆ Power factor correction modules

Typical Applications

Maximum Ratings

| Parameter | Symbol | Test Conditions | Value | Units |
|---|----------------|---|------------|-------|
| DC blocking voltage | V_R | | 650 | V |
| Repetitive peak reverse voltage, $T_j=25^\circ\text{C}$ | V_{RRM} | | 650 | V |
| Surge peak reverse voltage | V_{RSM} | | 650 | V |
| Maximum DC forward current | I_F | $T_C = 156^\circ\text{C}$ | 4 | A |
| Non-repetitive forward surge current sine halfwave | I_{FSM} | $T_C = 25^\circ\text{C}, t_p = 10\text{ms}$ | 30 | A |
| | | $T_C = 110^\circ\text{C}, t_p = 10\text{ms}$ | 24 | |
| Repetitive forward surge current sine halfwave, D=0.1 | I_{FRM} | $T_C = 25^\circ\text{C}, t_p = 10\text{ms}$ | 21.5 | A |
| | | $T_C = 110^\circ\text{C}, t_p = 10\text{ms}$ | 12.4 | |
| Non-repetitive peak forward current | $I_{F,max}$ | $T_C = 25^\circ\text{C}, t_p = 10\mu\text{s}$ | 235 | A |
| | | $T_C = 110^\circ\text{C}, t_p = 10\mu\text{s}$ | 212 | |
| Non-repetitive avalanche energy | E_{AS} | $T_j = 25^\circ\text{C}, L = 5\text{mH}, I_{pk}=3.55\text{A}, V_{DD}=100\text{V}$ | 33 | mJ |
| Power dissipation | P_{Tot} | $T_C = 25^\circ\text{C}$ | 71 | W |
| | | $T_C = 156^\circ\text{C}$ | 9 | |
| Maximum junction temperature | $T_{j,max}$ | | 175 | °C |
| Operating and storage temperature | T_j, T_{STG} | | -55 to 175 | °C |
| Soldering temperatures, wavesoldering only allowed at leads | T_{sold} | 1.6mm from case for 10s | 260 | °C |

Electrical Characteristics

$T_J = +25^\circ\text{C}$ unless otherwise specified

| Parameter | Symbol | Test Conditions | Value | | | Units |
|--|--------|--|-------|-----|------|---------------|
| | | | Min | Typ | Max | |
| Forward voltage | V_F | $I_F = 4\text{A}, T_J = 25^\circ\text{C}$ | - | 1.5 | 1.7 | V |
| | | $I_F = 4\text{A}, T_J = 150^\circ\text{C}$ | - | 1.8 | 2.1 | |
| | | $I_F = 4\text{A}, T_J = 175^\circ\text{C}$ | - | 2 | 2.25 | |
| Reverse current | I_R | $V_R = 650\text{V}, T_J = 25^\circ\text{C}$ | - | 10 | 170 | μA |
| | | $V_R = 650\text{V}, T_J = 175^\circ\text{C}$ | - | 20 | 550 | |
| Total capacitive charge ⁽¹⁾ | Q_C | $V_R = 400\text{V}$ | | 9.3 | | nC |
| Total capacitance | C | $V_R = 1\text{V}, f = 1\text{MHz}$ | | 125 | | pF |
| | | $V_R = 300\text{V}, f = 1\text{MHz}$ | | 16 | | |
| | | $V_R = 600\text{V}, f = 1\text{MHz}$ | | 13 | | |
| Capacitance stored energy | E_C | $V_R = 400\text{V}$ | | 1.3 | | μJ |

(1) See Figure 8, Q_c is independent on T_j , di_F/dt , and I_F as shown in the application note USCI_AN0011.

Thermal characteristics

| Parameter | symbol | Test Conditions | Value | | | Units |
|--------------------|-----------|-----------------|-------|------|-----|--------------------|
| | | | Min | Typ | Max | |
| Thermal resistance | R_{0JC} | | | 1.57 | 2.1 | $^\circ\text{C/W}$ |

Typical Performance




Figure 1 Typical reverse characteristics








Figure 2 Typical forward characteristics

**Figure 3 Power dissipation****Figure 4 Diode forward current****Figure 5 Capacitance vs. reverse voltage****Figure 6 Maximum transient thermal impedance**




Figure 7 Typical capacitance stored energy vs. reverse voltage




Figure 8 Typical capacitive charge vs. reverse voltage

Disclaimer

United Silicon Carbide, Inc. reserves the right to change or modify any of the products and their inherent physical and technical specifications without prior notice. United Silicon Carbide, Inc. assumes no responsibility or liability for any errors or inaccuracies within.

Information on all products and contained herein is intended for description only. No license, express or implied, to any intellectual property rights is granted within this document.

United Silicon Carbide, Inc. assumes no liability whatsoever relating to the choice, selection or use of the United Silicon Carbide, Inc. products and services described herein.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Schottky Diodes & Rectifiers category:

Click to view products by UnitedSiC manufacturer:

Other Similar products are found below :

[MA4E2039](#) [D1FH3-5063](#) [MBR10100CT-BP](#) [MBR1545CT](#) [MMBD301M3T5G](#) [RB160M-50TR](#) [RB551V-30](#) [BAS16E6433HTMA1](#) [BAT54-02LRH](#) [E6327](#) [NSR05F40QNXT5G](#) [NTE555](#) [JANS1N6640](#) [SB07-03C-TB-H](#) [SB1003M3-TL-W](#) [SK310-T](#) [SK32A-LTP](#) [SK33A-TP](#) [SK34B-TP](#) [SS3003CH-TL-E](#) [GA01SHT18](#) [CRS10I30A\(TE85L,QM](#) [MA4E2501L-1290](#) [MBRA140TRPBF](#) [MBRB30H30CT-1G](#) [SB007-03C-TB-E](#) [SK32A-TP](#) [SK33B-TP](#) [SK35A-TP](#) [SK38B-TP](#) [NRVBM120LT1G](#) [NTE505](#) [NTSB30U100CT-1G](#) [SS15E-TP](#) [VS-6CWQ10FNHM3](#) [ACDBA1100LR-HF](#) [ACDBA1200-HF](#) [ACDBA140-HF](#) [ACDBA2100-HF](#) [ACDBA3100-HF](#) [CDBQC0530L-HF](#) [CDBQC0240LR-HF](#) [ACDBA340-HF](#) [ACDBA260LR-HF](#) [ACDBA1100-HF](#) [SK310B-TP](#) [MA4E2502L-1246](#) [MA4E2502H-1246](#) [NRVBM120ET1G](#) [NSR01L30MXT5G](#) [NTE573](#)