



1. Material:
 - Contaeis: Phosphone
 - Bronze
 - insulater: PBT+30%
 - G. F. UL 94V-0
 - Shell: SPCC
2. Mechanical:
 - Mating: 35N max.
 - Withdrowa Force: 10N min.
 - Darabirity: 1500 cycles min.
3. Elecetical:
 - Current-max (amps) 1.5A
 - Voitage-max (volls) 30V
 - Withstanding Voltage 750V AC
 - Contact Resistance (ohms) 30 milliohms max insulation
 - Resistance (ohms) 1000 Megogms min.
4. Plating:
 - Contacts: Gold And Tin Over
 - Nickel Ploled
 - Shell: Nickel over all plating.
5. Environmental:
 - temperature Range: -55 to 85 .

>0.5~2	±0.05	±0.10	±0.15	第一视角 ☉	设计 Jack Jin	图面 单位	A4 MM	东莞市美韩电子科技有限公司 Dongguan Usakro Electronic Technology Co., Ltd.			
>2~5	±0.15	±0.20	±0.25		审核 Jacky Zhong	比例 重量		1:1	DWG NO.	型号: USB AF 侧插短体卷边	SIZE A4
>5~10	±0.25	±0.28	±0.30		批准 Tony Meng	页码 版次	1/1 A/0	1 of 1	PART NO.	规格: 13.7*7.02*16.75	VER R
角度 ANGLE				±0.5°	未注尺寸公差 (mm)						

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [USAKRO](#) manufacturer:

Other Similar products are found below :

[10033527-N3112MLF](#) [17-210561](#) [GMCB05B11124H1EU](#) [17-200931](#) [65-647-8-BK-BU](#) [690-010-295-484](#) [73725-1191BLF](#) [950](#) [E8144-B01021-L](#) [A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBB15131](#) [MUSBC111M5](#) [MUSBD11135](#) [217450-1](#) [CA 6 W LD](#) [896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#) [KUSBX-SMTAS1NBTR](#) [KUSBX-SMTBS1NBTR](#) [30-498-6](#) [SK-60A-2](#) [17-200261](#) [17-210051](#) [1734082-1](#) [FK-37-32SL](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [30-9503](#) [M9177/2-1](#) [MAB 5 S](#) [MIKROE-1451](#) [33UBBR-04SW11R](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [USBFTVSCCG](#) [KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SLAS1N-W30](#) [1-1734084-2](#) [E8110-001-01](#) [MUSBC11135](#) [NK-27-32SL](#)