


US-Lasers: 635nm-5mW - Red Laser Diode

[Back to Laser Diodes](#)

VISIBLE LASER DIODE DATA SHEET

ABSOLUTE MAXIMUM RATINGS - (Tc=25 °C)

TECHNICAL DATA for LASER DIODE		 Pin Out Diagram - Style A
Visible laser diode light output	635nm	
Optical power output	5mW CW	
Package Type	5.6mm	
Built-in photo diode for monitoring laser output		

Items	Symbols	Values	Unit
Optical output power	Po	5	mW
Laser diode reverse voltage	VLDR	2	V
Photo diode reverse voltage	VPDR	30	V
Operating temperature	Topr	-10 ~ +40	°C
Storage temperature	Tstg	-40 ~ +85	°C

OPTICAL and ELECTRICAL CHARACTERISTICS - (Tc=25 °C)

Items	Symbols	Min.	Typ.	Max.	Unit	Test Condition
Optical output power	Po	-	5	-	mW	-
Threshold current	Ith	30	40	60	mA	-
Operating current	Iop	40	50	70	mA	Po=5mW
Operating voltage	Vop	2.0	2.4	2.7	V	Po=5mW
Lasing wavelength	λ D	630	635	645	nm	Po=5mW
Beam divergence	θ F	8	10	11	deg	Po=5mW
Beam divergence	θ z	25	31	40	deg	Po=5mW
Slope Efficiency (mW/mA)	0	0.4	0.5	0.7		-
Monitor current	Im	10	50	90	μ A	Po=5mW, Vr=5V
Astigmatism	As	-	11	-	μ m	Po=5mW
MTTF		3000-5,000 hrs.				Po=5mW, NA=0.4
Emitter Distance to Cap Lens		0.3mm				
Emitter Size		1 x 4 Microns				
Structure		Index Guided				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for us-lasers manufacturer:

Other Similar products are found below :

[HK-10.4](#) [D8085I](#) [HK-6.4](#) [VOL7805I](#) [MM8505I](#) [NS102-200K](#) [THAD 5.6-9MM](#) [VOL6505I](#) [M8085I](#) [D8505I](#) [M7805I](#) [AD 5.6-9MM](#)
[NS102A-200K](#) [M6355I](#) [D6355I](#) [M8505I](#) [M6505I](#) [D405-120](#) [D7805I](#) [D405-20](#) [MM6505I](#)