

US-Lasers: 808nm-5mW - Infrared Laser Diodes and Infrared Diode Laser Modules

[Back To Laser Modules](#)

TECHNICAL DATA for LASER MODULE		
Barrel Specs:	Collect Specs:	Lens Housing Specs:
<ul style="list-style-type: none"> • 3/8 - 56 Thread Size • Dia: 10.4mm • Length: 17mm 	<ul style="list-style-type: none"> • 3/8 - 56 Thread Size • 4.3mm Aperature • Half Hard Brassbbb 	<ul style="list-style-type: none"> • 3/8 - 56 Thread Size • 3.7mm Aperture • 7mm Plastic Lens

INFRARED DIODE LASER DATA SHEETS

ABSOLUTE MAXIMUM RATINGS - (Tc=25 °C)

TECHNICAL DATA for LASER DIODE		Pin Out Diagram - Style A
<ul style="list-style-type: none"> • Index Guided MQW Structure • Wavelength: 808nm (Typ.) • Optical Power: 5mW CW • Threshold Current: 25mA (Typ.) • Standard Package: 5.6mm 		
Infrared light output	808nm	
Optical power output	5mW CW	
Package Type	5.6mm	
Built-in photo diode for monitoring laser output		

Items	Symbols	Values	Unit			
Optical output power	Po	5	mW			
Laser diode reverse voltage	VLDR	2	V			
Photo diode reverse voltage	VPDR	30	V			
Operating temperature	Topr	-10 ~ +40	°C			
Storage temperature	Tstg	-40 ~ +85	°C			
OPTICAL and ELECTRICAL CHARACTERISTICS - (Tc=25 °C)						
Items	Symbols	Min.	Typ.	Max.	Unit	Test Condition
Optical output power	Po	-	5	-	mW	-
Threshold current	Ith	10	20	35	mA	-
Operating current	Iop	15	25	45	mA	Po=5mW
Operating voltage	Vop	1.9	2.1	2.5	V	Po=5mW
Lasing wavelength	8 D	800	808	820	nm	Po=5mW
Beam divergence	θ F	8	11	15	deg	Po=5mW
Beam divergence	θ z	20	35	45	deg	Po=5mW
Slope Efficiency (mW/mA)	0	0.1	0.3	0.6	-	-
Monitor current	Im	10	100	200	μ A	Po=5mW,Vr=5V
Astigmatism	As	-	11	-	μ m	Po=5mW
MTTF		3000-5,000 hrs.				Po=5mW,NA=0.4
Emitter Size		1 x 4 Microns				
Emitter Distance to Cap Lens		0.3mm				
Structure		Index Guided				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for us-lasers manufacturer:

Other Similar products are found below :

[HK-10.4](#) [D8085I](#) [HK-6.4](#) [VOL7805I](#) [MM8505I](#) [NS102-200K](#) [THAD 5.6-9MM](#) [VOL6505I](#) [M8085I](#) [D8505I](#) [M7805I](#) [AD 5.6-9MM](#)
[NS102A-200K](#) [M6355I](#) [D6355I](#) [M8505I](#) [M6505I](#) [D405-120](#) [D7805I](#) [D405-20](#) [MM6505I](#)