

Features

- N-Channel, 5V Logic Level Control
- Enhancement mode
- Very low on-resistance $R_{DS(on)}$ @ $V_{GS}=4.5$ V
- VitoMOS® Technology
- 100% Avalanche test
- Pb-free lead plating; RoHS compliant



Halogen-Free

V_{DS}	65	V
$R_{DS(on),TYP} @ V_{GS}=10$ V	19	mΩ
$R_{DS(on),TYP} @ V_{GS}=4.5$ V	22	mΩ
I_D	30	A

PDFN3333


Pin1

Part ID	Package Type	Marking	Tape and reel information
VS6412AE	PDFN3333	6412AE	5000PCS/Reel



Maximum ratings, at $T_A = 25^\circ\text{C}$, unless otherwise specified

Symbol	Parameter		Rating	Unit
$V_{(BR)DSS}$	Drain-Source breakdown voltage		65	V
I_s	Diode continuous forward current	$T_c = 25^\circ\text{C}$	30	A
I_D	Continuous drain current@ $V_{GS}=10\text{V}$	$T_c = 25^\circ\text{C}$	30	A
		$T_c = 100^\circ\text{C}$	19	A
I_{DM}	Pulse drain current tested ①	$T_c = 25^\circ\text{C}$	120	A
EAS	Avalanche energy, single pulsed ②		121	mJ
P_D	Maximum power dissipation	$T_c = 25^\circ\text{C}$	32	W
V_{GS}	Gate-Source voltage		± 20	V
$T_{STG} T_J$	Storage and operating temperature range		-55 to 150	°C

Thermal Characteristics

Symbol	Parameter	Typical	Unit
$R_{\theta JC}$	Thermal Resistance-Junction to Case	3.9	°C/W
$R_{\theta JA}$	Thermal Resistance-Junction to Ambient	35	°C/W

Symbol	Parameter	Condition	Min.	Typ.	Max.	Unit
Static Electrical Characteristics @ $T_j=25^\circ\text{C}$ (unless otherwise stated)						
$V_{(\text{BR})\text{DSS}}$	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}, I_{\text{D}}=250\mu\text{A}$	65	--	--	V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{\text{DS}}=65\text{V}, V_{\text{GS}}=0\text{V}$	--	--	0.1	μA
	Zero Gate Voltage Drain Current($T_j=125^\circ\text{C}$)	$V_{\text{DS}}=65\text{V}, V_{\text{GS}}=0\text{V}$	--	--	100	μA
I_{GSS}	Gate-Body Leakage Current	$V_{\text{GS}}=\pm 20\text{V}, V_{\text{DS}}=0\text{V}$	--	--	± 100	nA
$V_{\text{GS}(\text{TH})}$	Gate Threshold Voltage	$V_{\text{DS}}=V_{\text{GS}}, I_{\text{D}}=250\mu\text{A}$	1.0	1.8	2.5	V
$R_{\text{DS}(\text{ON})}$	Drain-Source On-State Resistance ^③	$V_{\text{GS}}=10\text{V}, I_{\text{D}}=15\text{A}$	--	19	24	$\text{m}\Omega$
$R_{\text{DS}(\text{ON})}$	Drain-Source On-State Resistance ^③	$V_{\text{GS}}=4.5\text{V}, I_{\text{D}}=10\text{A}$	--	22	26	$\text{m}\Omega$
Dynamic Electrical Characteristics @ $T_j = 25^\circ\text{C}$ (unless otherwise stated)						
C_{iss}	Input Capacitance	$V_{\text{DS}}=30\text{V}, V_{\text{GS}}=0\text{V}, f=1\text{MHz}$	--	1240	--	pF
C_{oss}	Output Capacitance		--	95	--	pF
C_{rss}	Reverse Transfer Capacitance		--	85	--	pF
R_g	Gate Resistance	$f=1\text{MHz}$	--	2.4	--	Ω
Q_g	Total Gate Charge	$V_{\text{DS}}=30\text{V}, I_{\text{D}}=5\text{A}, V_{\text{GS}}=10\text{V}$	--	21	--	nC
Q_{gs}	Gate-Source Charge		--	6	--	nC
Q_{gd}	Gate-Drain Charge		--	8.5	--	nC
Switching Characteristics						
$t_{\text{d}(\text{on})}$	Turn-on Delay Time	$V_{\text{DD}}=30\text{V}, I_{\text{D}}=5\text{A}, R_{\text{G}}=6.8\Omega, V_{\text{GS}}=10\text{V}$	--	12	--	nS
t_r	Turn-on Rise Time		--	8.5	--	nS
$t_{\text{d}(\text{off})}$	Turn-Off Delay Time		--	42	--	nS
t_f	Turn-Off Fall Time		--	6	--	nS
Source- Drain Diode Characteristics@ $T_j = 25^\circ\text{C}$ (unless otherwise stated)						
V_{SD}	Forward on voltage	$I_{\text{SD}}=15\text{A}, V_{\text{GS}}=0\text{V}$	--	0.8	1.2	V
t_{rr}	Reverse Recovery Time	$T_j=25^\circ\text{C}, I_{\text{sd}}=5\text{A}, V_{\text{GS}}=0\text{V}$ $dI/dt=100\text{A}/\mu\text{s}$	--	22	--	nS
Q_{rr}	Reverse Recovery Charge			86		nC

NOTE:

- ① Repetitive rating; pulse width limited by max. junction temperature.
- ② Limited by $T_{j\text{max}}$, starting $T_j = 25^\circ\text{C}$, $L = 0.5\text{mH}$, $R_G = 25\Omega$, $I_{AS} = 22\text{A}$, $V_{GS} = 10\text{V}$. Part not recommended for use above this value
- ③ Pulse width $\leq 300\mu\text{s}$; duty cycle $\leq 2\%$.

Typical Characteristics




Fig1. Typical Output Characteristics




Fig2. $V_{GS(TH)}$ Gate -Source Voltage Vs. T_j




Fig3. Typical Transfer Characteristics




Fig4. Normalized On-Resistance Vs. T_j




Fig5. Typical Source-Drain Diode Forward Voltage




Fig6. Maximum Safe Operating Area

Typical Characteristics




Fig7. Typical Capacitance Vs.Drain-Source Voltage




Fig8. Typical Gate Charge Vs.Gate-Source Voltage




Fig9. Normalized Maximum Transient Thermal Impedance




Fig10. Unclamped Inductive Test Circuit and waveforms





Fig11. Switching Time Test Circuit and waveforms

PDFN3333 Package Outline Data



DIMENSIONS (unit : mm)

Symbol	Min	Typ	Max	Symbol	Min	Typ	Max
A	0.70	0.75	0.80	b	0.25	0.30	0.35
C	0.10	0.15	0.25	D	3.25	3.35	3.45
D1	3.00	3.10	3.20	D2	1.78	1.88	1.98
D3	--	0.13	--	E	3.20	3.30	3.40
E1	3.00	3.15	3.20	E2	2.39	2.49	2.59
e	0.65BSC			H	0.30	0.39	0.50
L	0.30	0.40	0.50	L1	--	0.13	--
θ	--	10°	12°	M	*	*	0.15

*Not specified

Customer Service

Sales and Service:

sales@vgsemi.com

Vanguard Semiconductor CO., LTD

TEL: (86-755) -26902410

FAX: (86-755) -26907027

WEB: www.vgsemi.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for MOSFET category:

Click to view products by Vanguard manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FDPF9N50NZ](#) [FW216A-TL-2W](#) [FW231A-TL-E](#) [APT5010JVR](#) [NTNS3A92PZT5G](#)
[IRF100S201](#) [JANTX2N5237](#) [2SK2464-TL-E](#) [2SK3818-DL-E](#) [FCA20N60_F109](#) [FDZ595PZ](#) [STD6600NT4G](#) [FSS804-TL-E](#) [2SJ277-DL-E](#)
[2SK1691-DL-E](#) [2SK2545\(Q,T\)](#) [D2294UK](#) [405094E](#) [423220D](#) [MCH6646-TL-E](#) [TPCC8103,L1Q\(CM](#) [367-8430-0972-503](#) [VN1206L](#)
[424134F](#) [026935X](#) [051075F](#) [SBVS138LT1G](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [751625C](#) [873612G](#) [IRF7380TRHR](#)
[IPS70R2K0CEAKMA1](#) [RJK60S3DPP-E0#T2](#) [RJK60S5DPK-M0#T0](#) [APT5010JVFR](#) [APT12031JFLL](#) [APT12040JVR](#) [DMN3404LQ-7](#)
[NTE6400](#) [JANTX2N6796U](#) [JANTX2N6784U](#) [JANTXV2N5416U4](#) [SQM110N05-06L-GE3](#) [SIHF35N60E-GE3](#)