



6U Overall, VME64x J1/J2 (without J0) with 5-row, 160 positions DIN 4161 connectors

### Features

- VME64J1 Extender on top & VME64J2 Extender on Bottom attached with mending plate to create VME64J1J2 Extender
- Excellent performance with a multi layer design
- Individual signal tracking with interruption jumpers
- Voltage & Current measuring facilities
- Full ground plane
- Signal pin-out identification silkscreen onto outer PCB layers
- Jumper Blocks provided to allow signal line interrogation
- Max. current per contact @ nominal 50°C = 1.75A
- Controlled impedance, Signal trace shielding
- Voltage rating 200 RMS or 300 VDC

### Ordering Info

- Part Number : **VME64J1J2**

### Mechanical specifications

- Board Height 6U ( 9.00")
- Board Length 11.75"
- PCB Thickness 0.062"
- Card Extender bracket (P/N : 5210211, may)

### Board specifications

- Material : FR-4 Epoxy
- PCB UL94V-0, PCB R
- 6 Internal 1oz. copper
- PCB exposed Copper

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Data Logging & Acquisition](#) category:*

*Click to view products by [Vector](#) manufacturer:*

Other Similar products are found below :

[PCI-6208A](#) [DAQe-2502](#) [PXI-2208](#) [ACL-8112DG](#) [SpotBotBLE](#) [LPCI-7230](#) [USB-4761-BE](#) [SE028](#) [PCI-1761-BE](#) [AR207/8/S1/PPPP/IP65](#)  
[PCI-1711UL-CE](#) [USB-4702-AE](#) [USB-4704-AE](#) [USB-4716-AE](#) [USB-4750-BE](#) [USB-4751-AE](#) [PCIE-1810-AE](#) [PCI-1710U-DE](#) [PCI-](#)  
[1710HGU-DE](#) [AR207/8/S1/PPPP/IP30](#) [U2781A](#) [4610](#) [EL-USB-5](#) [AR407/S1/P/P/P/P](#) [AR207/8/S2/PPPP/IP30](#) [ACL-8112PG](#) [cPCI-7248](#)  
[cPCI-7433](#) [DAQ-2213](#) [ND-6053](#) [ND-6060](#) [PCI-7230](#) [PCI-7432](#) [PCI-7442](#) [PCI-9112](#) [PCI-9112A](#) [PCI-9113A](#) [PCI-9221](#) [PCM-7248+](#) [USB-](#)  
[1903](#) [USB-2401](#) [PCIE-1813-AE](#) [PCIE-1816-AE](#) [PCIE-1816H-AE](#) [PCIE-1884-AE](#) [USB-5856-AE](#) [USB-5862-AE](#) [AR654/S1/P/P/P/P/IP30](#)  
[AR654/S2/P/P/P/P/IP30](#) [DAS30](#)