


## PVMI-2TE-10.6-1x1-TO8-wZnSeAR-36

### 2.0 – 12.0 μm HgCdTe two-stage thermoelectrically cooled, optically immersed photovoltaic multiple junction detector

**PVMI-2TE-10.6-1x1-TO8-wZnSeAR-36** is two-stage thermoelectrically cooled IR photovoltaic multiple junction detector based on sophisticated HgCdTe heterostructure for the best performance and stability. The device is designed for the maximum performance at 10.6 μm. Detector element is monolithically integrated with hyperhemispherical GaAs microlens in order to improve performance of the device. 3° wedged zinc selenide anti-reflection coated (wZnSeAR) window prevents unwanted interference effects.

#### Spectral response ( $T_a = 20^\circ\text{C}$ )



Exemplary spectral detectivity, the spectral response of delivered devices may differ.

#### Specification ( $T_a = 20^\circ\text{C}$ )

Parameter	Detector type
	PVMI-2TE-10.6-1x1-TO8-wZnSeAR-36
Active element material	epitaxial HgCdTe heterostructure
Cut-on wavelength $\lambda_{\text{cut-on}}$ (10%), μm	≤2.0
Peak wavelength $\lambda_{\text{peak}}$ , μm	8.5±1.5
Optimum wavelength $\lambda_{\text{opt}}$ , μm	10.6
Cut-off wavelength $\lambda_{\text{cut-off}}$ (10%), μm	≥12.0
Detectivity $D^*(\lambda_{\text{peak}})$ , $\text{cm}\cdot\text{Hz}^{1/2}/\text{W}$	≥1.5×10 <sup>9</sup>
Detectivity $D^*(\lambda_{\text{opt}})$ , $\text{cm}\cdot\text{Hz}^{1/2}/\text{W}$	≥1.0×10 <sup>9</sup>
Current responsivity $R_i(\lambda_{\text{peak}})$ , A/W	≥0.15
Current responsivity $R_i(\lambda_{\text{opt}})$ , A/W	≥0.1
Time constant $\tau$ , ns	≤3
Resistance R, Ω	≥90
Active element temperature $T_{\text{det}}$ , K	~230
Optical area $A_o$ , mm×mm	1×1
Package	TO8
Acceptance angle $\Phi$	~36°
Window	wZnSeAR

#### Features

- Wide spectral range from 2.0 to 12.0 μm
- No bias required
- No flicker noise
- Operation from DC to high frequency
- Sensitive to IR radiation polarisation
- Versatility
- Quantity discounted price
- Fast delivery

#### Applications

- CO<sub>2</sub> laser (10.6 μm) measurements
- Laser power monitoring and control
- Laser beam profiling and positioning
- Laser calibration
- Dentistry


#### Related product

- UM-I-10.6 detection module


#### Two-stage thermoelectric cooler parameters

Parameter	Value
$T_{\text{det}}$ , K	~230
$V_{\text{max}}$ , V	1.3
$I_{\text{max}}$ , A	1.2
$Q_{\text{max}}$ , W	0.36


#### Thermistor characteristics




#### Spectral transmission of wZnSeAR window (typical example)



### Mechanical layout, mm



$\Phi$  – acceptance angle  
 A – distance from the bottom of the 2TE-TO8 header to the focal plane  
 R – hyperhemisphere microlens radius



Function	Pin number
Detector	1, 3
Thermistor	7, 9
TE cooler supply	2(+), 8(-)
Chassis ground	11
Not used	4, 5, 6, 10, 12

### Precautions for use and storage

- Heatsink with thermal resistance of  $\sim 2$  K/W is necessary to dissipate heat generated by 2TE cooler.
- Operation in 10% to 80% humidity and -20°C to 30°C ambient temperature.
- Beam power limitations for optically immersed detector:
  - irradiance with CW or single pulse longer than 1  $\mu$ s irradiance on the apparent optical active area must not exceed 2.5 W/cm<sup>2</sup>,
  - irradiance of the pulse shorter than 1  $\mu$ s must not exceed 10 kW/cm<sup>2</sup>.
- Storage in dark place with 10% to 90% humidity and -20°C to 50°C ambient temperature.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Photoelectric Sensors](#) category:*

*Click to view products by [Vigo System](#) manufacturer:*

Other Similar products are found below :

[7442AD2X5FRX](#) [EX-19B-LP](#) [EX-19SB-PN](#) [7443AR0X5FRX](#) [7452AD4D4NNX](#) [7694ADE04DS2X](#) [FE7C-FRC6S-M](#) [FX-305](#) [PM-R24-R](#)  
[Q45VR2FPQ](#) [13104RQD07](#) [E3JUXM4MN](#) [E3L2DC4](#) [E3S3LE21](#) [E3SCT11M1J03M](#) [E3SDS20E21](#) [E3VDS70C43S](#) [E3XNM16](#) [BR23P](#)  
[HOA6563-001](#) [OJ-3307-30N8](#) [OS-311A-30](#) [P32013](#) [P34036](#) [P43004](#) [P60001](#) [PB10CNT15PO](#) [S14132](#) [935286-000](#) [S52101](#) [S56258](#) [FD-](#)  
[SN500](#) [FE7B-FDRB6-M](#) [SU-79](#) [T36342](#) [T40300](#) [T60001](#) [PD60CNX20BP](#) [FX-302-HY](#) [FZS](#) [PM-T64W](#) [PZ2-51P](#) [CX-491-P-J](#) [CYNUTX10](#)  
[UZB802](#) [UZB803](#) [UZFRG1](#) [UZFRG4](#) [UZFRT4](#) [UZFTT8](#)