





Plug-in motion detector, 120°, IP20, 280W, Schuko

Marka: Virone | Symbol: MS-1(GS) | Ean: 5908254817243





PRODUCT DESCRIPTION

An electrical device that is installed in a standard wall socket. Thanks to the use of a PIR sensor, the device helps to automate the switching on and off of electrical devices after motion detection. The receivers are switched on at the appropriate daylight intensity.







TECHNICAL DATA

General information:

Type of sensor:	Infrared
Detection angle:	120°
Detection range:	9 m
Nominal voltage:	230V~, 50Hz
Max. load:	1200 W
Max. load of the LED light source:	300 W
Degree of protection (IP):	20
Colour:	white
Adjustable daylight sensor (LUX):	Yes
Adjustable time setting (TIME):	Yes
Adjustment of motion detection range (SENS):	Yes
Relay output:	No
Presence detector:	No
Working temperature:	-20[~+40]
Installation:	To the Schuko socket
Dimensions - width:	45 mm
Dimensions - height:	98.3 mm
Dimensions - depth:	81.5 mm
Lighting time adjustment range (TIME):	min.: 10 sek. ± 3 sek., max.: 15min.±2min
Daylight sensor adjustment range (LUX):	<3-2000lux
Other features:	SENS detection range adjustment: 2-9M



























X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Specialist Controllers category:

Click to view products by Virone manufacturer:

Other Similar products are found below:

CV500SLK21 H2CRSAC110B R88ARR080100S E53E01 E53E8C E5GNQ03PFLKACDC24 B300LKL21 NSCXDC1V3

NT20SST122BV1 C40PEDRA K31S5 K31S6 K3TX-AD31A L595020 26546803 26546805 H7HP-C8D PWRA440A CPM1AETL03CH

3G2A5BI081 3G2A5IA122 3G2A5OD211 3G2A5RM001EV1 3G2A5RT002EV1 3G2A6-ID217 3G2A6LK202EV1 3G2A9AL004E

C200HETL01E C200PCPD024 3G2A5AD001 3G2A5BI051 3G2A5IA121 3G2A5ID112 3G2A5ID213 3G2A5ID219 3G2A5MR431

3G2A5OC221 3G2A5PS222E 3G2A6IM213 3G2A6-OD412 3G2A9AL001 3G2C7LK202EV1 3G5A2OC221E LDP2TA2B115

3G3DV130B4294 E53E04 E53Q4Q4 E54E8CT C200HWCOM06EV1 NT30KBA04