

BY206GP THRU BY207GP

SUPER RECTIFIER

GENERAL INSTRUMENT

FEATURES


- High temperature metallurgically bonded constructed rectifiers
- For use in high frequency rectifier circuits
- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Fast switching for high efficiency
- Glass passivated cavity-free junction in DO-41 package
- 0.4 ampere operation at $T_A = 55^\circ\text{C}$ with no thermal runaway
- Typical I_n less than $1 \mu\text{A}$
- Capable of meeting environmental standards of MIL-S-19500
- High temperature soldering guaranteed: $350^\circ\text{C}/10$ seconds / .375" (9.5mm) lead length / 5 lbs., (2.3kg) tension

MECHANICAL DATA

Case: Molded plastic over glass
 Terminals: Axial leads, solderable per MIL-STD-202, Method 208
 Polarity: Color band denotes cathode
 Mounting Position: Any
 Weight: 0.012 ounce, .3 gram

VOLTAGE RANGE
350 to 600 Volts

CURRENT
0.4 Amperes



PATENTED

Glass-plastic encapsulation technique is covered by Patent No. 3,806,802 of 1976; brazed-lead assembly to Patent No. 3,930,306 of 1976 and glass composition by Patent No. 3,752,701 of 1973

Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
 Resistive or inductive load.
 For capacitive load, derate current by 20%.

	BY206GP	BY207GP	UNITS
Maximum Recurrent Peak Reverse Voltage	350	600	V_{RRM}
Maximum RMS Voltage	210	350	V_{RMS}
Maximum DC Blocking Voltage	300	500	V_{DC}
Maximum Average Forward Rectified Current .375" (.95mm) Lead Lengths at $T_A = 55^\circ\text{C}$	0.4		A_{FM}
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	15		A_{PK}
Maximum Instantaneous Forward Voltage at 2.0A $T_J = 150^\circ\text{C}$	1.5		V_{PK}
Maximum Full Load Reverse Current Full Cycle Average at $T_A = 55^\circ\text{C}$ $T_J = 125^\circ\text{C}$	2.0 200	2.0 125	μA
Maximum Reverse Recovery Time (Note 1)	1.0		μS
Typical Junction Capacitance (Note 2)	15		pF
Operating and Storage Temperature Range T_J, T_{STG}	-65 to +175		$^\circ\text{C}$

NOTES:
 1. Reverse Recovery Test Conditions: $I_f = 0.4\text{A}$, $V_R = 50\text{V}$ $di/dt = 0.4\text{AAJS}$
 2. Measured at 1.0 MHz and applied reverse voltage of 4.0 VDC.

RATING AND CHARACTERISTIC CURVES
BY206GP THRU BY207QP

FIG. 1 — FORWARD CURRENT DERATING CURVE




FIG. 2 — TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 3 — MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 4 — TYPICAL JUNCTION CAPACITANCE




FIG. 5 — REVERSE RECOVERY TIME CHARACTERISTIC





FIG. 6 — SUPERCTIFIER



GENERAL INSTRUMENT CORPORATION

Power Semiconductor Division Headquarters 600 West John Street, CS620, Hicksville, N.Y. 11802-1620, (516) 933-3333 • TWX: 310-376-8690 • FAX: 516-933-8238
 North Eastern Regional Sales Office: 120 Andrews Road, Hicksville, N.Y. 11801-1702, (516) 933-3200 • FAX: 516-433-4412 • TWX: 310-376-7238
 South Eastern Regional Sales Office: 3030 Holcomb Bridge Road, Suite F, Norcross, GA 30071, (404) 448-1285 • TWX: 510-101-3222 • FAX: 404-448-1266
 Central Regional Sales Office: 2355 S. Arlington Hts. Road, Arlington Hts., IL 60005, (312) 364-5850 • TWX: 910-222-0431 • FAX: 312-364-0849
 Western Regional Sales Office: 21601 Vanowen Street, Suite 205, Canoga Park, CA 91308, (818) 992-0682 • TWX: 910-322-1980 • FAX: 818-992-1958

INTERNATIONAL SALES OFFICES

Germany, Austria and Switzerland General Instrument Deutschland GmbH, Froleichstr. 98, 8000 München 81, Tel: (089) 959 97-0 • Telex: 524 523 • FAX: (089) 957 04 89
 France General Instrument France, 9 Rue E. Enesco, 94006 Créteil Cédex, Tel: 93 (1) 43771283 • Telex: 262435 • FAX: 33 (1) 43991524
 Italy General Instrument Italia, Semiconductor Div., Via Cantù 11, 20092 Cinisello Balsamo (Milano), Tel: (02) 86010444 • FAX: (02) 86010324
 United Kingdom General Instrument (UK) Ltd., Time House, Ruislip, Middlesex, England, Tel: 8958-33358 & 8956-35670 • Telex: 23272 • FAX: 9-011-44-89-58-393
 Taiwan General Instrument of Taiwan, Ltd., 233 Pao Chiao Road, Hsin Tien, Taipei, Taiwan, Tel: 9113860 • FAX: 9-011-8882-817-6901
 Japan General Instrument International Corp., Fudde Building, 5th Floor, 1-13 Toranomon 4-Chrome, Minato-Ku, Tokyo 105, Japan, Tel: (03) 437-0261 (GIC) • FAX: 9-011-81-3434-3938
 Hong Kong General Instrument Hong Kong Ltd., Rm. 1104-1107, Tower B, Mandarin Plaza, 14 Science Museum Rd., Tsimshatsui East, Kowloon, Hong Kong, Tel: 3-7226577 • Telex: 54606 GIKH HX • FAX: (852) 3-7239239

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Rectifiers](#) category:

Click to view products by [Vishay](#) manufacturer:

Other Similar products are found below :

[70HFR40](#) [RL252-TP](#) [150KR30A](#) [1N5397](#) [NTE5841](#) [NTE6038](#) [SCF5000](#) [1N4002G](#) [1N4005-TR](#) [JANS1N6640US](#) [481235F](#)
[RRE02VS6SGTR](#) [067907F](#) [MS306](#) [70HF40](#) [T110HF60](#) [T85HFL60S02](#) [US2JFL-TP](#) [A1N5404G-G](#) [CRS04\(T5L,TEMQ\)](#) [ACGRA4007-HF](#)
[ACGRB207-HF](#) [CLH03\(TE16L,Q\)](#) [ACGRC307-HF](#) [ACEFC304-HF](#) [NTE6356](#) [NTE6359](#) [NTE6002](#) [NTE6023](#) [NTE6039](#) [NTE6077](#)
[85HFR60](#) [40HFR60](#) [1N1186RA](#) [70HF120](#) [85HFR80](#) [D126A45C](#) [SCF7500](#) [D251N08B](#) [SCHJ22.5K](#) [SM100](#) [SCPA2](#) [SCH10000](#) [SDHD5K](#)
[VS-12FL100S10](#) [ACGRA4001-HF](#) [D1821SH45T PR](#) [D1251S45T](#) [NTE5990](#) [NTE6358](#)