Dual Flat No Lead Molded Precision Thin Film Divider, Surface Mount Resistor Network



The DFN series of thin film precision dividers surface mount resistor networks offer a wide ratio range that is listed in the standard resistance offering table. The 4 mm x 4 mm 0.8 mm pitch dual flat no lead package feature 50 % savings in board space over traditional SOIC packages. The DFN dividers are ideal for applications that require tight TC tracking and ratio tolerances over temperature.

FEATURES

- 0.8 mm lead pitch
- MSL level 1 per J-STD-020
- Low profile 1 mm seated height
- Small size 4 mm x 4 mm size 50 % board savings over SOIC packages
- Low TCR ± 25 ppm, TCR tracking to ± 5 ppm
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

Pb-free

RoHS COMPLIANT

TYPICAL PERFORMANCE

	ABSOLUTE	TRACKING
TCR	25	5
	ABSOLUTE	RATIO
TOL.	0.1	0.05

SCHEMATIC



STANDARD RESISTANCE OFFERING (R_1/R_2)		
RATIO	R_1	R_2
100:1	100K	1K
50:1	50K	1K
25:1	25K	1K
20:1	20K	1K
10:1	10K	1K
5:1	10K	2K
2:1	10K	5K

STANDARD ELECTRICAL SPECIFICATIONS		
TEST	SPECIFICATIONS	CONDITIONS
Material	Passivated nichrome	-
Pin/Lead Number	8	-
Resistance Range	1000 Ω to 100 kΩ per element	-
TCR: Absolute	± 25 ppm/°C	-55 °C to +125 °C
TCR: Tracking	± 5 ppm/°C	-55 °C to +125 °C
Tolerance: Absolute	± 0.1 %	+25 °C
Tolerance: Ratio	± 0.05 %	+25 °C
Power Rating: Resistor	100 mW	Maximum at +70 °C
Power Rating: Package	100 mW x number of resistors	Maximum at +70 °C
Stability: Absolute	ΔR ± 0.05 %	2000 h at +70 °C
Stability: Ratio	ΔR ± 0.015 %	2000 h at +70 °C
Voltage Coefficient	< 0.1 ppm/V	-
Working Voltage	100 V max. not to exceed $\sqrt{P \times R}$	-
Operating Temperature Range	-55 °C to +125 °C	-
Storage Temperature Range	-55 °C to +150 °C	-
Noise	< - 30 dB	-
Thermal EMF	< 0.08 µV/°C	-
Shelf Life Stability: Absolute	ΔR ± 0.01 %	1 year at + 25 °C
Shelf Life Stability: Ratio	ΔR ± 0.002 %	1 year at + 25 °C

DIMENSIONS AND IMPRINTING in millimeters



A	Max.	0.900
	Nom.	0.850
	Min.	0.800

Notes

(1) 100-1 resistance ratio part marking to be 100-

(2) Contact factory for package outlines for higher pin count or custom configurations

MECHANICAL SPECIFICATIONS

Resistive Element	Passivated nichrome
Substrate Material	Ceramic
Body	Molded epoxy
Terminals	Copper alloy
Plating	100 % matte tin
Marking Resistance to Solvents	Per MIL-PRF-914

GLOBAL PART NUMBER INFORMATION

D	F	N	A	5	-	1	U	F

GLOBAL MODEL (4 digits)	RESISTANCE (3, 4 or 5 digits)	PACKAGING
DFNA (Lead (Pb)-free) (e3)	**2-1** **5-1** **10-1** **20-1** **25-1** **50-1** **100-1**	TAPE AND REEL **T0** = 100 min., 100 mult **T1** = 1000 min., 1000 mult (3) **T3** = 300 min., 300 mult **T5** = 500 min., 500 mult **TF** = Full reel 3000 **TS** = 100 min., 1 mult **UF** = TUBED

Note

(3) Preferred packaging code

Vishay Dale Thin Film Land Patterns

1. Scope

This technical note provides sample land patterns for Vishay Dale Thin Film SMT resistive products. The following drawings are based on IPC-SM-782 Surface Mount Design and Land Pattern Standard. These drawings are for reference only Vishay Thin Film recommends that the user contacts their PC board supplier for actual land patterns required. The pads are intended for lead (Pb)-free and tin / lead solder types.

2. Product Series

Thin Film Surface Mount Chip Resistors (FC, L, P, PTN, PLT, PLTT. PLTU, PAT, PATT, PNM, M/D55342 QPL Series)

0402 Land Pattern



0502 Land Pattern



0505 Land Pattern



0603 Land Pattern



0705 Land Pattern



1005 Land Pattern



1010 Land Pattern



1206 Land Pattern



1505 Land Pattern



2010 Land Pattern



2208 Land Pattern



2512 Land Pattern



Thin Film Surface Mount Chip Resistors (PHP, PCAN Series)

0603 Land Pattern



1206 Land Pattern



0805 Land Pattern



2512 Land Pattern



Thin Film Surface Mount Chip Resistors Long Axis Termination (L Series)

0508 Land Pattern



0612 Land Pattern



1020 Land Pattern



1225 Land Pattern



Surface Mount Networks (MPM, MP3, MP4 Series)

SOT-23 (MPM, MPMA)



SC70-3 (MP3)



SC70-4 (MP4)



Surface Mount Networks SOIC Narrow Body 150 mils (ORN, CSO, MOMC, HTRN, AORN, MORN Series)

SOIC-8
(ORN, HTRN, AORN, CSO-8)



SOIC-14
(NOMC-14, NOMCA-14, CSO-14)



SOIC-16
(NOMC-16, NOMCA-16, CSO-16, VSOR-16)



MORN MSOP MO-187AA
(MORN-8)



Surface Mount Networks SOIC Medium Body 220 mils (TOMC Series)

SOIC-16 (TOMC)



Surface Mount Networks SOIC Wide Body 300 mils (WOMC Series)

SOIC-16 (WOMC-16)



SOIC-20 (WOMC-20)



Surface Mount Networks High Density SSOP, TSOP (VSSR, VTSR Series)

SSOP MO-137

OSOP-16, VSSR-16



OSOP-20, VSSR-20



OSOP-24, VSSR-24, HD-CSO-24



TSSOP MO-153

VTSR-16



VTSR-20



VTSR-24



Surface Mount Leadless Networks (LCC Series)

16 Pin LCC



20 Pin LCC



Surface Mount Leadless Networks (MPH Series)

4 Pin LCC



Surface Mount Leadless Packages DUAL/ QUAD Flat No Lead (DFN, QFN Series)

DFN MLP

DFN-8 4 x 5 mm Sq



QFN MLP

QFN-20 5 x 5 mm Sq



Surface Mount Leadless Resistor Arrays (PR Series)

PR 100 (2 to 8 resistors)



PR 135 (2 to 8 resistors)



PR 182 (2 to 8 resistors)



Note

- All dimensions in inches (mm)

Flatpack

14 Pin Bottom Brazed Flatpack



16 Pin Bottom Brazed Flatpack



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay’s knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer’s technical experts. Product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Resistor Networks & Arrays ***category:***

Click to view products by Vishay ***manufacturer:***

Other Similar products are found below :

M8340105K1002FGD03 M8340105K3301JCD03 M8340106M2002GCD03 M8340107K1471FGD03 M8340107K2002GCD03 M8340107K2261FGD03 M8340107M1501GGD03 M8340108K1001FCD03 M8340108K3240FGD03 M8340108K4991FGD03 M8340108K6192FGD03 M8340109K2872FCD03 M8340109MA010GHD03 EXB-24N121JX EXB-24N330JX EXB-24N470JX 744C083101JTR EXB-U14360JX EXB-U18390JX 744C083270JTR 745C102472JP 767161104G 770101223 ACAS06S0830339P100 ACAS06S0830343P100 ACAS06S0830344P100 RM2012A-102/104-PBVW10 RM2012A-102503-PBVW10 8B472TR4 268-15K ACAS06S0830341P100 ACAS06S0830342P100 ACAS06S0830345P100 EXB-U14470JX EXB-U18330JX 266-10K M8340102K1051FBD04 M8340105M1001JCD03 M8340106K4701GGD03 M8340107K1004GGD03 M8340108K1000GGD03 M8340108K1202GGD03 M8340108K3901GGD03 M8340108K4992FGD03 M8340108K5111FGD03 M8340109K2202GCD03 RKC8BD104J DFNA100-1TS 745X101473JP RMKD408-10KBW