



Optocoupler, Phototransistor Output, With Base Connection



H179005



FEATURES

- Current transfer ratio (see order information)
- Isolation test voltage 4420 V_{RMS}
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


RoHS
COMPLIANT

AGENCY APPROVALS

- [UL / cUL](#) 1577
- [CSA](#)
- [CQC GB4943.1-2011](#)
- [CQC GB8898-2011](#)
- [FIMKO](#)

LINKS TO ADDITIONAL RESOURCES



DESCRIPTION

The IL2 is an optically coupled isolated pairs employing GaAs infrared LEDs and silicon NPN phototransistor. Signal information, including a DC level, can be transmitted by the drive while maintaining a high degree of electrical isolation between input and output. The IL2 is especially designed for driving medium-speed logic and can be used to eliminate troublesome ground loop and noise problems. This coupler can be used also to replace relays and transformers in many digital interface applications such as CRT modulation.

| ORDERING INFORMATION | |
|--|-----------------|
| <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid black; padding: 2px 5px;">I</div> <div style="border: 1px solid black; padding: 2px 5px;">L</div> <div style="border: 1px solid black; padding: 2px 5px;">2</div> <div style="border: 1px solid black; padding: 2px 5px;">-</div> <div style="border: 1px solid black; padding: 2px 5px;">X</div> <div style="border: 1px solid black; padding: 2px 5px;">0</div> <div style="border: 1px solid black; padding: 2px 5px;">0</div> <div style="border: 1px solid black; padding: 2px 5px;">9</div> <div style="border: 1px solid black; padding: 2px 5px;">T</div> </div> <p style="text-align: center;">PART NUMBER PACKAGE OPTION PACKAGE OPTION</p> | |
| AGENCY CERTIFIED / PACKAGE | CTR (%) |
| UL, cUL, CSA, CQC, FIMKO | > 100 |
| SMD-6, option 9 | IL2-X009T |

Note

- Additional options may be possible, please contact sales office

| ABSOLUTE MAXIMUM RATINGS (T _{amb} = 25 °C, unless otherwise specified) | | | | |
|---|----------------|-------------------|-------|-------|
| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
| INPUT | | | | |
| Reverse voltage | | V _R | 6 | V |
| Forward current | | I _F | 60 | mA |
| Surge current | | I _{FSM} | 2.5 | A |
| Power dissipation | | P _{diss} | 100 | mW |
| Derate linearly from 25 °C | | | 1.33 | mW/°C |



| ABSOLUTE MAXIMUM RATINGS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | |
|--|-------------------------|------------|-------------|-------|
| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
| OUTPUT | | | | |
| Collector emitter breakdown voltage | | BV_{CEO} | 70 | V |
| Emitter base breakdown voltage | | BV_{EBO} | 7 | V |
| Collector base breakdown voltage | | BV_{CBO} | 70 | V |
| Collector current | | I_C | 50 | mA |
| | $t < 1.0\text{ ms}$ | I_C | 400 | mA |
| Power dissipation | | P_{diss} | 200 | mW |
| Derate linearly from 25 °C | | | 2.6 | mW/°C |
| COUPLER | | | | |
| Package power dissipation | | P_{tot} | 250 | mW |
| Derate linearly from 25 °C | | | 3.3 | mW/°C |
| Storage temperature | | T_{stg} | -40 to +150 | °C |
| Operating temperature | | T_{amb} | -40 to +100 | °C |
| Junction temperature | | T_j | 125 | °C |
| Soldering temperature ⁽¹⁾ | 2.0 mm from case bottom | T_{sld} | 260 | °C |

Notes

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability
- ⁽¹⁾ Refer to reflow profile for soldering conditions for surface mounted devices (SMD). Refer to wave profile for soldering conditions for through hole devices (DIP)

| ELECTRICAL CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | | |
|--|--|-------------|------|-----------|------|---------------|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| INPUT | | | | | | |
| Forward voltage | $I_F = 60\text{ mA}$ | V_F | - | 1.25 | 1.65 | V |
| Breakdown voltage | $I_R = 10\text{ }\mu\text{A}$ | V_{BR} | 6 | 30 | - | V |
| Reverse current | $V_R = 6.0\text{ V}$ | I_R | - | 0.01 | 10 | μA |
| Capacitance | $V_R = 0\text{ V}$, $f = 1.0\text{ MHz}$ | C_O | - | 40 | - | pF |
| Thermal resistance junction to lead | | R_{thjl} | - | 750 | - | K/W |
| OUTPUT | | | | | | |
| Collector emitter capacitance | $V_{CE} = 5.0\text{ V}$, $f = 1.0\text{ MHz}$ | C_{CE} | - | 6.8 | - | pF |
| Collector base capacitance | $V_{CB} = 5.0\text{ V}$, $f = 1.0\text{ MHz}$ | C_{CB} | - | 8.5 | - | pF |
| Emitter base capacitance | $V_{EB} = 5.0\text{ V}$, $f = 1.0\text{ MHz}$ | C_{EB} | - | 11 | - | pF |
| Collector emitter leakage voltage | $V_{CE} = 10\text{ V}$ | I_{CEO} | - | 5 | 50 | nA |
| Collector emitter saturation voltage | $I_{CE} = 1.0\text{ mA}$, $I_B = 20\text{ }\mu\text{A}$ | V_{CEsat} | - | 0.25 | - | V |
| Base emitter voltage | $V_{CE} = 10\text{ V}$, $I_B = 20\text{ }\mu\text{A}$ | V_{BE} | - | 0.65 | - | V |
| DC forward current gain | $V_{CE} = 10\text{ V}$, $I_B = 20\text{ }\mu\text{A}$ | h_{FE} | 200 | 650 | 1800 | |
| DC forward current gain saturated | $V_{CE} = 0.4\text{ V}$, $I_B = 20\text{ }\mu\text{A}$ | h_{FEsat} | 120 | 400 | 600 | |
| Thermal resistance junction to lead | | R_{thjl} | - | 500 | - | K/W |
| COUPLER | | | | | | |
| Capacitance (input to output) | $V_{I-O} = 0\text{ V}$, $f = 1.0\text{ MHz}$ | C_{IO} | - | 0.6 | - | pF |
| Insulation resistance | $V_{I-O} = 500\text{ V}$ | R_S | - | 10^{14} | - | Ω |

Note

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements



| CURRENT TRANSFER RATIO | | | | | | |
|--|---|---------------|------|------|------|------|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Current transfer ratio (collector emitter saturated) | $I_F = 10 \text{ mA}, V_{CE} = 0.4 \text{ V}$ | CTR_{CEsat} | - | 170 | - | % |
| Current transfer ratio (collector emitter) | $I_F = 10 \text{ mA}, V_{CE} = 10 \text{ V}$ | CTR_{CE} | 100 | 200 | 500 | % |
| Current transfer ratio (collector base) | $I_F = 10 \text{ mA}, V_{CB} = 9.3 \text{ V}$ | CTR_{CB} | - | 0.25 | - | % |

| SWITCHING CHARACTERISTICS | | | | | | |
|---------------------------|---|-----------|------|------|------|---------------|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| NON-SATURATED | | | | | | |
| Current time | $V_{CE} = 5 \text{ V}, R_L = 75 \Omega$, t_p measured at 50 % of output | I_F | - | 4 | - | mA |
| Delay time | $V_{CE} = 5 \text{ V}, R_L = 75 \Omega$, t_p measured at 50 % of output | t_D | - | 1.7 | - | μs |
| Rise time | $V_{CE} = 5 \text{ V}, R_L = 75 \Omega$, t_p measured at 50 % of output | t_r | - | 2.6 | - | μs |
| Storage time | $V_{CE} = 5 \text{ V}, R_L = 75 \Omega$, t_p measured at 50 % of output | t_s | - | 0.4 | - | μs |
| Fall time | $V_{CE} = 5 \text{ V}, R_L = 75 \Omega$, t_p measured at 50 % of output | t_f | - | 2.2 | - | μs |
| Propagation H to L | $V_{CE} = 5 \text{ V}, R_L = 75 \Omega$, t_p measured at 50 % of output | t_{PHL} | - | 1.2 | - | μs |
| Propagation L to H | $V_{CE} = 5 \text{ V}, R_L = 75 \Omega$, t_p measured at 50 % of output | t_{PLH} | - | 2.3 | - | μs |
| SATURATED | | | | | | |
| Current time | $V_{CE} = 0.4 \text{ V}, R_L = 1.0 \text{ k}\Omega$, $V_{CL} = 5 \text{ V}, V_{TH} = 1.5 \text{ V}$ | I_F | - | 5 | - | mA |
| Delay time | $V_{CE} = 0.4 \text{ V}, R_L = 1.0 \text{ k}\Omega$, $V_{CL} = 5 \text{ V}, V_{TH} = 1.5 \text{ V}$ | t_D | - | 1 | - | μs |
| Rise time | $V_{CE} = 0.4 \text{ V}, R_L = 1.0 \text{ k}\Omega$, $V_{CL} = 5 \text{ V}, V_{TH} = 1.5 \text{ V}$ | t_r | - | 2 | - | μs |
| Storage time | $V_{CE} = 0.4 \text{ V}, R_L = 1.0 \text{ k}\Omega$, $V_{CL} = 5 \text{ V}, V_{TH} = 1.5 \text{ V}$ | t_s | - | 5.4 | - | μs |
| SATURATED | | | | | | |
| Fall time | $V_{CE} = 0.4 \text{ V}, R_L = 1.0 \text{ k}\Omega$, $V_{CL} = 5 \text{ V}, V_{TH} = 1.5 \text{ V}$ | t_f | - | 13.5 | - | μs |
| Propagation H to L | $V_{CE} = 0.4 \text{ V}, R_L = 1.0 \text{ k}\Omega$, $V_{CL} = 5 \text{ V}, V_{TH} = 1.5 \text{ V}$ | t_{PHL} | - | 5.4 | - | μs |
| Propagation L to H | $V_{CE} = 0.4 \text{ V}, R_L = 1.0 \text{ k}\Omega$, $V_{CL} = 5 \text{ V}, V_{TH} = 1.5 \text{ V}$ | t_{PLH} | - | 7.4 | - | μs |

| COMMON MODE TRANSIENT IMMUNITY | | | | | | |
|-----------------------------------|---|----------|------|------|------|------------------------|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Common mode rejection output high | $V_{CM} = 50 \text{ V}_{P-P}, R_L = 1 \text{ k}\Omega, I_F = 10 \text{ mA}$ | $ CM_H $ | - | 5000 | - | $\text{V}/\mu\text{s}$ |
| Common mode rejection output low | $V_{CM} = 50 \text{ V}_{P-P}, R_L = 1 \text{ k}\Omega, I_F = 10 \text{ mA}$ | $ CM_L $ | - | 5000 | - | $\text{V}/\mu\text{s}$ |
| Common mode coupling capacitance | | C_{CM} | - | 0.01 | - | pF |




| SAFETY AND INSULATION RATINGS | | | | |
|--|--|-------------------|--------------------|-------------------|
| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
| Climatic classification | According to IEC 68 part 1 | | 40 / 100 / 21 | |
| Comparative tracking index | | CTI | 175 | |
| Maximum rated withstanding isolation voltage | t = 1 min | V _{ISO} | 4420 | V _{RMS} |
| Maximum transient isolation voltage | | V _{IOTM} | 10 000 | V _{peak} |
| Maximum repetitive peak isolation voltage | | V _{IORM} | 890 | V _{peak} |
| Isolation resistance | V _{IO} = 500 V, T _{amb} = 25 °C | R _{IO} | ≥ 10 ¹² | Ω |
| | V _{IO} = 500 V, T _{amb} = 100 °C | R _{IO} | ≥ 10 ¹¹ | Ω |
| Output safety power | | P _{SO} | 400 | mW |
| Input safety current | | I _{SI} | 275 | mA |
| Safety temperature | | T _S | 175 | °C |
| Creepage distance | | | ≥ 7 | mm |
| Clearance distance | | | ≥ 7 | mm |
| Insulation thickness | | DTI | ≥ 0.4 | mm |

Note


- As per IEC 60747-5-5, § 7.4.3.8.2, this optocoupler is suitable for “safe electrical insulation” only within the safety ratings. Compliance with the safety ratings shall be ensured by means of protective circuits

TYPICAL CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)




iii1_01

Fig. 1 - Non-Saturated Switching Schematic




iii1_04

Fig. 4 - Saturated Switching Timing




iii1_02

Fig. 2 - Saturated Switching Schematic




iii1_05

Fig. 5 - Forward Voltage vs. Forward Current



iii1_03

Fig. 3 - Non-Saturated Switching Timing



iii1_06

Fig. 6 - Normalized Non-Saturated and Saturated CTR vs. LED Current




Fig. 7 - Normalized Non-Saturated and Saturated CTR vs. LED Current




Fig. 10 - Collector Emitter Current vs. Temperature and LED Current




Fig. 8 - Normalized Non-Saturated and Saturated CTR vs. LED Current




Fig. 11 - Collector Emitter Leakage Current vs. Temperature




Fig. 9 - Normalized Non-Saturated and Saturated CTR, T_{amb} = 100 °C vs. LED Current




Fig. 12 - Normalized CTR_{cb} vs. LED Current and Temperature




Fig. 13 - Collector Base Photocurrent vs. LED Current




Fig. 16 - Normalized Saturated h_{FE} vs. Base Current and Temperature




Fig. 14 - Normalized Photocurrent vs. I_F and Temperature




Fig. 17 - Propagation Delay vs. Collector Load Resistor







Fig. 15 - Normalized Non-Saturated h_{FE} vs. Base Current and Temperature



PACKAGE DIMENSIONS in millimeters



Option 9





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Transistor Output Optocouplers](#) category:

Click to view products by [Vishay](#) manufacturer:

Other Similar products are found below :

[LTV-814S-TA](#) [LTV-824HS](#) [LTV-852S](#) [66095-001](#) [6N136-X017T](#) [MCT6-X007](#) [MOC8101-X017T](#) [PS2561A-1-W-A](#) [PS2561B-1-L-A](#)
[PS2561L-1-V-A](#) [MRF658](#) [IL755-1X007](#) [ILD74-X001](#) [ILQ615-2X017](#) [ILQ615-3X016](#) [LDA102S](#) [LDA110S](#) [PS2561-1-V-W-A](#) [PS2561AL-1-V-A](#) [PS2561L1-1-L-A](#) [PS2701A-1-F3-P-A](#) [PS2801-1-F3-P-A](#) [PS2911-1-L-AX](#) [CNY17-2X017](#) [CNY17-4X001](#) [CNY17-4X017](#) [CNY17F-1X007](#) [CNY17F-2X017](#) [CNY17F-4X001](#) [CNY17G-1](#) [LTV-214](#) [LTV-702VB](#) [LTV-733S](#) [LTV-816S-TA](#) [LTV-825S](#) [TCET1113](#) [TCET2100](#)
[4N25-X007T](#) [IL215AT](#) [ILD615-1X007](#) [ILQ2-X007](#) [VOS615A-2T](#) [WPPC-A11066AA](#) [WPPC-A11066AD](#) [WPPC-A11084ASS](#) [WPPC-A21068AA](#) [WPPC-D11066AA](#) [WPPC-D21068ED](#) [WPPC-D410616EA](#) [WPPC-D410616ED](#)