



Optocoupler, Phototransistor Output, with Base Connection



I179004



FEATURES

- Isolation test voltage (1.0 s), 5300 V_{RMS}
- V_{CEsat} 0.25 (≤ 0.4) V, I_F = 10 mA, I_C = 2.5 mA
- Built to conform to VDE requirements
- Highest quality premium device
- Long term stability
- Storage temperature, - 55 ° to + 150 °C
- Lead (Pb)-free component
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC


RoHS
COMPLIANT

DESCRIPTION

The SFH601 is an optocoupler with a gallium arsenide LED emitter which is optically coupled with a silicon planar phototransistor detector. The component is packaged in a plastic plug-in case 20 AB DIN 41866. The coupler transmits signals between two electrically isolated circuits.

AGENCY APPROVALS

- UL1577, file no. E52744 system code H or J, double protection
- DIN EN 60747-5-5 (VDE 0884) available with option 1
- CSA 93751
- BSI IEC 60950; IEC 60065

| ORDER INFORMATION | |
|-------------------|--|
| PART | REMARKS |
| SFH601-1 | CTR 40 % to 80 %, DIP-6 |
| SFH601-2 | CTR 63 % to 125 %, DIP-6 |
| SFH601-3 | CTR 100 % to 200 %, DIP-6 |
| SFH601-4 | CTR 160 % to 320 %, DIP-6 |
| SFH601-1X006 | CTR 40 % to 80 %, DIP-6 400 mil (option 6) |
| SFH601-1X007 | CTR 40 % to 80 %, SMD-6 (option 7) |
| SFH601-1X009 | CTR 40 % to 80 %, SMD-6 (option 9) |
| SFH601-2X006 | CTR 63 % to 125 %, DIP-6 400 mil (option 6) |
| SFH601-2X007 | CTR 63 % to 125 %, SMD-6 (option 7) |
| SFH601-2X009 | CTR 63 % to 125 %, SMD-6 (option 9) |
| SFH601-3X006 | CTR 100 % to 200 %, DIP-6 400 mil (option 6) |
| SFH601-3X007 | CTR 100 % to 200 %, SMD-6 (option 7) |
| SFH601-3X009 | CTR 100 % to 200 %, SMD-6 (option 9) |
| SFH601-4X006 | CTR 160 % to 320 %, DIP-6 400 mil (option 6) |
| SFH601-4X007 | CTR % 160 to 320 %, SMD-6 (option 7) |
| SFH601-4X009 | CTR % 160 to 320 %, SMD-6 (option 9) |

Note

For additional information on the available options refer to option information.

| ABSOLUTE MAXIMUM RATINGS (1) | | | | |
|------------------------------|----------------|-------------------|-------|------|
| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
| INPUT | | | | |
| Reverse voltage | | V _R | 6 | V |
| DC forward current | | I _F | 60 | mA |
| Surge forward current | t = 10 μs | I _{FSM} | 2.5 | A |
| Total power dissipation | | P _{diss} | 100 | mW |

| ABSOLUTE MAXIMUM RATINGS ⁽¹⁾ | | | | |
|---|--|------------|----------------|------------------|
| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
| OUTPUT | | | | |
| Collector emitter voltage | | V_{CE} | 100 | V |
| Emitter base voltage | | V_{EBO} | 7 | V |
| Collector current | | I_C | 50 | mA |
| | $t = 1.0 \text{ ms}$ | I_C | 100 | mA |
| Power dissipation | | P_{diss} | 150 | mW |
| COUPLER | | | | |
| Isolation test voltage between emitter and detector | $t = 1.0 \text{ s}$ | V_{ISO} | 5300 | V_{RMS} |
| Isolation resistance | $V_{IO} = 500 \text{ V}, T_{amb} = 25 \text{ }^\circ\text{C}$ | R_{IO} | $\geq 10^{12}$ | Ω |
| | $V_{IO} = 500 \text{ V}, T_{amb} = 100 \text{ }^\circ\text{C}$ | R_{IO} | $\geq 10^{11}$ | Ω |
| Storage temperature range | | T_{stg} | - 55 to + 150 | $^\circ\text{C}$ |
| Ambient temperature range | | T_{amb} | - 55 to +100 | $^\circ\text{C}$ |
| Junction temperature | | T_j | 100 | $^\circ\text{C}$ |
| Soldering temperature ⁽²⁾ | max. 10 s, dip soldering: distance to seating plane $\geq 1.5 \text{ mm}$ | T_{sld} | 260 | $^\circ\text{C}$ |

Notes

⁽¹⁾ $T_{amb} = 25 \text{ }^\circ\text{C}$, unless otherwise specified.

Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.

⁽²⁾ Refer to reflow profile for soldering conditions for surface mounted devices (SMD). Refer to wave profile for soldering conditions for through hole devices (DIP).

| ELECTRICAL CHARACTERISTICS | | | | | | | |
|--------------------------------------|---|----------|-------------|------|------|------|---------------|
| PARAMETER | TEST CONDITION | PART | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| INPUT | | | | | | | |
| Forward voltage | $I_F = 60 \text{ mA}$ | | V_F | | 1.25 | 1.65 | V |
| Breakdown voltage | $I_R = 10 \text{ } \mu\text{A}$ | | V_{BR} | 6 | | | V |
| Reverse current | $V_R = 6 \text{ V}$ | | I_R | | 0.01 | 10 | μA |
| Capacitance | $V_F = 0 \text{ V}, f = 1 \text{ MHz}$ | | C_O | | 25 | | pF |
| Thermal resistance | | | R_{thja} | | 750 | | K/W |
| OUTPUT | | | | | | | |
| Collector emitter capacitance | $f = 1 \text{ MHz}, V_{CE} = 5 \text{ V}$ | | C_{CE} | | 6.8 | | pF |
| Collector base capacitance | $f = 1 \text{ MHz}, V_{CB} = 5 \text{ V}$ | | C_{CB} | | 8.5 | | pF |
| Emitter base capacitance | $f = 1 \text{ MHz}, V_{EB} = 5 \text{ V}$ | | C_{EB} | | 11 | | pF |
| Thermal resistance | | | R_{thja} | | 500 | | K/W |
| Collector emitter leakage current | $V_{CE} = 10 \text{ V}$ | SFH601-1 | I_{CEO} | | 2 | 50 | nA |
| | | SFH601-2 | I_{CEO} | | 2 | 50 | nA |
| | | SFH601-3 | I_{CEO} | | 5 | 100 | nA |
| | | SFH601-4 | I_{CEO} | | 5 | 100 | nA |
| COUPLER | | | | | | | |
| Saturation voltage collector emitter | $I_F = 10 \text{ mA}, I_C = 2.5 \text{ mA}$ | | V_{CEsat} | | 0.25 | 0.4 | V |
| Capacitance (input to output) | $V_{I-O} = 0, f = 1 \text{ MHz}$ | | C_{IO} | | 0.6 | | pF |

Note

$T_{amb} = 25 \text{ }^\circ\text{C}$, unless otherwise specified.


Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements.

| CURRENT TRANSFER RATIO | | | | | | | |
|--------------------------------------|----------------------|----------|--------|------|------|------|------|
| PARAMETER | TEST CONDITION | PART | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| I_C/I_F at $V_{CE} = 5.0\text{ V}$ | $I_F = 10\text{ mA}$ | SFH601-1 | CTR | 40 | | 80 | % |
| | | SFH601-2 | CTR | 63 | | 125 | % |
| | | SFH601-3 | CTR | 100 | | 200 | % |
| | | SFH601-4 | CTR | 160 | | 320 | % |
| | $I_F = 1\text{ mA}$ | SFH601-1 | CTR | 13 | 30 | | % |
| | | SFH601-2 | CTR | 22 | 45 | | % |
| | | SFH601-3 | CTR | 34 | 70 | | % |
| | | SFH601-4 | CTR | 56 | 90 | | % |

Note


Current transfer ratio and collector emitter leakage current by dash number.

| SWITCHING CHARACTERISTICS | | | | | | | |
|---------------------------|---|----------|-----------|------|------|------|---------------|
| PARAMETER | TEST CONDITION | PART | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| NON-SATURATED | | | | | | | |
| Current | $V_{CC} = 5\text{ V}, R_L = 75\ \Omega$ | | I_F | | 10 | | mA |
| Rise time | $V_{CC} = 5\text{ V}, R_L = 75\ \Omega$ | | t_r | | 2 | | μs |
| Fall time | $V_{CC} = 5\text{ V}, R_L = 75\ \Omega$ | | t_f | | 2 | | μs |
| Turn-on time | $V_{CC} = 5\text{ V}, R_L = 75\ \Omega$ | | t_{on} | | 3 | | μs |
| Turn-off time | $V_{CC} = 5\text{ V}, R_L = 75\ \Omega$ | | t_{off} | | 2.3 | | μs |
| SATURATED | | | | | | | |
| Current | | SFH601-1 | I_F | | 20 | | mA |
| | | SFH601-2 | I_F | | 10 | | mA |
| | | SFH601-3 | I_F | | 10 | | mA |
| | | SFH601-4 | I_F | | 0.5 | | mA |
| Rise time | | SFH601-1 | t_r | | 2 | | μs |
| | | SFH601-2 | t_r | | 3 | | μs |
| | | SFH601-3 | t_r | | 3 | | μs |
| | | SFH601-4 | t_r | | 4.6 | | μs |
| Fall time | | SFH601-1 | t_f | | 11 | | μs |
| | | SFH601-2 | t_f | | 14 | | μs |
| | | SFH601-3 | t_f | | 14 | | μs |
| | | SFH601-4 | t_f | | 15 | | μs |
| Turn-on time | | SFH601-1 | t_{on} | | 3 | | μs |
| | | SFH601-2 | t_{on} | | 4.2 | | μs |
| | | SFH601-3 | t_{on} | | 4.2 | | μs |
| | | SFH601-4 | t_{on} | | 6 | | μs |
| Turn-off time | | SFH601-1 | t_{off} | | 18 | | μs |
| | | SFH601-2 | t_{off} | | 23 | | μs |
| | | SFH601-3 | t_{off} | | 23 | | μs |
| | | SFH601-4 | t_{off} | | 25 | | μs |



isfh601_01

Fig. 1 - Linear Operation (without Saturation)



isfh601_02

Fig. 2 - Switching Operation (with Saturation)

| SAFETY AND INSULATION RATINGS | | | | | | |
|--|------------------------|--------|------|-----------|------|------|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Climatic classification (according to IEC 68 part 1) | | | | 55/100/21 | | |
| Comparative tracking index | | CTI | 175 | | 399 | |
| V_{IOTM} | | | 8000 | | | V |
| V_{IORM} | | | 890 | | | V |
| P_{SO} | | | | | 700 | mW |
| I_{SI} | | | | | 400 | mA |
| T_{SI} | | | | | 175 | °C |
| Creepage distance | standard DIP-6 | | 7 | | | mm |
| Clearance distance | standard DIP-6 | | 7 | | | mm |
| Creepage distance | 400 mil DIP-6 | | 8 | | | mm |
| Clearance distance | 400 mil DIP-6 | | 8 | | | mm |
| Insulation thickness, reinforced rated | per IEC 60950 2.10.5.1 | | 0.4 | | | mm |

Note

As per IEC 60747-5-2, § 7.4.3.8.1, this optocoupler is suitable for "safe electrical insulation" only within the safety ratings. Compliance with the safety ratings shall be ensured by means of protective circuits.

TYPICAL CHARACTERISTICS

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified




Fig. 3 - Current Transfer Ratio vs. Diode Current




Fig. 4 - Current Transfer Ratio vs. Diode Current




Fig. 5 - Current Transfer Ratio vs. Diode Current




Fig. 8 - Current Transfer Ratio vs. Diode Current




Fig. 6 - Current Transfer Ratio vs. Diode Current




Fig. 9 - Transistor Characteristics




Fig. 7 - Current Transfer Ratio vs. Diode Current




Fig. 10 - Output Characteristics




Fig. 11 - Forward Voltage




Fig. 14 - Saturation Voltage vs. Collector Current and Modulation Depth SFH601-2




Fig. 12 - Collector Emitter Off-state Current




Fig. 15 - Saturation Voltage vs. Collector Current and Modulation Depth SFH601-3




Fig. 13 - Saturation Voltage vs. Collector Current and Modulation Depth SFH601-1






Fig. 16 - Saturation Voltage vs. Collector Current and Modulation Depth SFH601-4




isfh601_17

Fig. 17 - Permissible Pulse Load




isfh601_19

Fig. 19 - Permissible Forward Current Diode



isfh601_18

Fig. 18 - Permissible Power Dissipation for Transistor and Diode

PACKAGE DIMENSIONS in inches (millimeters)


i178004


SFH601

Vishay Semiconductors Optocoupler, Phototransistor
Output, with Base Connection




PACKAGE DIMENSIONS in inches (millimeters)


Option 6



Option 7



Option 9



18450

**OZONE DEPLETING SUBSTANCES POLICY STATEMENT**

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively.
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA.
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design
and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Transistor Output Optocouplers](#) category:

Click to view products by [Vishay](#) manufacturer:

Other Similar products are found below :

[LTV-814S-TA](#) [LTV-824HS](#) [LTV-852S](#) [66095-001](#) [6N136-X017T](#) [MCT6-X007](#) [MOC8101-X017T](#) [PS2561A-1-W-A](#) [PS2561B-1-L-A](#)
[PS2561L-1-V-A](#) [MRF658](#) [IL755-1X007](#) [ILD74-X001](#) [ILQ615-2X017](#) [ILQ615-3X016](#) [LDA102S](#) [LDA110S](#) [PS2561-1-V-W-A](#) [PS2561AL-1-V-A](#) [PS2561L1-1-L-A](#) [PS2701A-1-F3-P-A](#) [PS2801-1-F3-P-A](#) [PS2911-1-L-AX](#) [CNY17-2X017](#) [CNY17-4X001](#) [CNY17-4X017](#) [CNY17F-1X007](#) [CNY17F-2X017](#) [CNY17F-4X001](#) [CNY17G-1](#) [LTV-214](#) [LTV-702VB](#) [LTV-733S](#) [LTV-816S-TA](#) [LTV-825S](#) [TCET1113](#) [TCET2100](#)
[4N25-X007T](#) [IL215AT](#) [ILD615-1X007](#) [ILQ2-X007](#) [VOS615A-2T](#) [WPPC-A11066AA](#) [WPPC-A11066AD](#) [WPPC-A11084ASS](#) [WPPC-A21068AA](#) [WPPC-D11066AA](#) [WPPC-D21068ED](#) [WPPC-D410616EA](#) [WPPC-D410616ED](#)