


Neon Circuit Component Lamps

| Configuration | Part Number | Old Ref. Number | Design Current mA | Initial DC Breakdown Voltage | Initial DC Maintaining Voltage |
|---|-------------|-----------------|-------------------|------------------------------|--------------------------------|
| Wire Terminal | | | | | |
|  | 2AA | NE-99 | 0.30 | 60-80 | 52-62 |
| | 2AC | | 1.50 | 125 Max. | - |
| | 3AD | NE-98 | 0.30 | 65-80 | Avg.>50 |
| | 3AG | | 0.40 | 60-90 | Avg.>58 |
| | 3AG-B | | 0.40 | 65-73 | 52-62 |
| | 3AG-C | | 0.40 | 68-76 | 52-62 |
| | 3AG-F | | 0.40 | 65-73 | 64 Max. |
| | 3AH | | 2.00 | 75-135 | Avg.70 |
| | 3AJ | | 5.00 | 60-100 | Avg.>59 |
| | 3AJ-C | | 5.00 | 60-100 | Avg.>59 |
| | 4AD | | 0.50 | 105-135 | 60-80 |
| | 4AE | | 0.50 | 120-150 | 60-80 |
| | 5AB | NE-23 | 0.30 | 60-90 | Avg.59 |
| | 5AB-A | | 0.30 | 60-80 | 50-65 |
| | 5AB-B | | 0.30 | 62-72 | 50-60 |
| | 5AB-BT | | 0.30 | 62-72 | 50-60 |
| | 5AB-T | | 0.30 | 60-90 | Avg.59 |
| | 5AC | NE-68 | 0.30 | 60-90 | 52-65 |
| | 5AG | NE-81 | 0.10 | 64-80 | 50-58 |
| | 5AG-A | NE-76 | 0.40 | 68-76 | 50-60 |
| | 5AH | NE-83 | 5.00 | 60-100 | Avg.>59 |
| | 5AH-A | | 5.00 | 60-85 | 50-65 |
| | 5AH-B | | 5.00 | 75-85 | 55-66 |
| | 5AH-D | | 3.00 | 60-85 | 50-70 |
| | 5AH-E | | 5.00 | 60-100 | Avg.>61 |
| | 5AJ | NE-86 | 1.50 | 55-90 | Avg.>57 |
| | 5AJ-A | | 1.50 | 55-75 | 45-65 |
| | 5AJ-B | | 1.50 | 70-90 | 55-75 |

| Average Life to Indicate Change | | | | Dimensions | | |
|-----------------------------------|--------|------------------|-------|------------|----------|----------|
| Breakdown Voltage | | Maintain Voltage | | inches | | |
| Chg. | Hrs. | Chg. | Hrs. | A (Max.) | B (Max.) | C (Min.) |
| Wire Terminal-Standard Brightness | | | | | | |
| - | - | 6.0 | 7,500 | .244 | .500 | 1.00 |
| - | 25,000 | - | - | .244 | .500 | 1.00 |
| 5.0 | 6,000 | 5.0 | 6,000 | .244 | .750 | 2.00 |
| 5.0 | 2,000 | 5.0 | 2,000 | .244 | .750 | 2.00 |
| 5.0 | 2,000 | 5.0 | 2,000 | .244 | .750 | 2.00 |
| 5.0 | 2,000 | 5.0 | 2,000 | .244 | .750 | 2.00 |
| 5.0 | 2,000 | 5.0 | 2,000 | .244 | .750 | 1.00 |
| 10.0 | 2,000 | 10.0 | 2,000 | .244 | .750 | 2.00 |
| 5.0 | 500 | 5.0 | 500 | .244 | .750 | 1.00 |
| 5.0 | 500 | 5.0 | 500 | .244 | .750 | 2.00 |
| 10.0 | 3,000 | 10.0 | 3,000 | .244 | .844 | 1.00 |
| 10.0 | 3,000 | 10.0 | 3,000 | .244 | .844 | 1.00 |
| 5.0 | 6,000 | 5.0 | 6,000 | .244 | 1.000 | 1.00 |
| 5.0 | 6,000 | 5.0 | 6,000 | .244 | 1.000 | 1.00 |
| 5.0 | 6,000 | 5.0 | 6,000 | .244 | 1.000 | 1.00 |
| 5.0 | 6,000 | 5.0 | 6,000 | .244 | 1.000 | 1.00 |
| 5.0 | 6,000 | 5.0 | 6,000 | .244 | 1.000 | 1.00 |
| - | - | 5.0 | 2,000 | .244 | 1.000 | 1.00 |
| 5.0 | 2,000 | 5.0 | 2,000 | .244 | 1.000 | 1.00 |
| - | 1,000 | 5.0 | 2,000 | .244 | 1.000 | 1.00 |
| 5.0 | 5,000 | 5.0 | 5,000 | .244 | .938 | 1.00 |
| 5.0 | 5,000 | 5.0 | 5,000 | .244 | .938 | 1.00 |
| 5.0 | 5,000 | 5.0 | 5,000 | .244 | .938 | 1.00 |
| 5.0 | 5,000 | 5.0 | 5,000 | .244 | .938 | 1.00 |
| 5.0 | 5,000 | 5.0 | 5,000 | .244 | .938 | 2.00 |
| 5.0 | 2,000 | 5.0 | 2,000 | .244 | .938 | 1.00 |
| 5.0 | 2,000 | 5.0 | 2,000 | .244 | .938 | 1.00 |
| 5.0 | 2,000 | 5.0 | 2,000 | .244 | .938 | 1.00 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Lamps category](#):

Click to view products by [Visual Communications manufacturer](#):

Other Similar products are found below :

[5911-086-13](#) [5AB](#) [6180](#) [7009](#) [8623](#) [909](#) [912](#) [1224](#) [1230](#) [DE603](#) [DNW21-DW10/BLA](#) [BF20100-11B](#) [1892](#) [NL177WL2A](#) [NL276C2A](#)
[IFL-LX2162-16T](#) [C2A-T](#) [C9A](#) [301](#) [303](#) [A1C](#) [A2B](#) [19](#) [268](#) [GT-NE6H1225T](#) [CM1820](#) [CM5004WW](#) [303](#) [32-2211T](#) [36EN-2113](#) [407](#)
[4916S1](#) [521-7332](#) [5314N1](#) [5314N2](#) [311](#) [WWT1-EW10/GRN](#) [4925H1](#) [DW07](#) [MS25231-313](#) [5603437](#) [5603851](#) [CM2](#) [7683EBP](#) [8553](#)
[XE135B](#) [WWT2-EW34BLA](#) [5705H7](#) [NL2951WL2G](#) [1301910036](#)