


## 1091M Series Non-Relampable LED Indicator Lights





Solid-state indicator lights complete with built-in current-limiting resistor and rectifier diode.

Mounting: Will snap-fit into Ø.500/.505 hole in panels .020/.100 thick. Push-on speednut SN0461 also available. Mounting hole pattern on page SP2.

Wire Leads: No. 22 AWG (105°C) 4.40/4.80 long, stripped .430/.570

Lens: Polycarbonate

Anode(+): Red lead

Bezel: Polished stainless steel.

Housing: White Nylon

To use 24V model: Beyond 32VAC add 30 ohms per volt; beyond 24 VDC add 50 ohms per volt.

Use 1/2W resistor up to 50V; 1W resistor for 50V to 70V; 2W resistor for 75V to 125V. Do not use beyond 125V.

	LED Solid State Indicator			
Lens Color	Model No.	Model No.	Model No.	Model No.
	(6V)	(12V)	(24V)	(105-125 VAC*)
Red	1091M1-6V	1091M1-12V	1091M1-24V	1091M1-125VAC
Green	1091M5-6V	1091M5-12V	1091M5-24V	1091M5-125VAC
Yellow	-	1091M7-12V	1091M7-24V	1091M7-125VAC
Internal Resistor	150	390	1000	(2) 3.9K 1/2W*
(ohms)				(One Internal)

\*125 VAC supplied with 6" white wire, stripped 1/2" with external 3.9K 1/2 watt resistor attached to one lead, covered with shrink tubing insulation.

Voltage Table				
Nominal	VAC	VDC		
6V	5 to 11	3.5 to 6.5		
12V	10 to 20	6 to 13.5		
24V	22 to 32	12 to 24		
125 VAC	105 to 125	-		

Lens Color	Incorporates LED*
Red	4304H1
Green	4304H5
Yellow	4304H7

\* Also incorporates 1N4004 (400 P.I.V.) rectifier diode.

## **Compliance & Approvals**



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Panel Mount Indicators category:

Click to view products by Visual Communications Company manufacturer:

Other Similar products are found below :

607-3232-140F 821-0331-503 FL2870C8R FL2950WL7B FL2950WL8G FL589WL8R FL67C8R H8630FBBA3 NL177WL2A NL177WL3G NL276C2A NL2950BWL3G NL589WL2R NL67C2C NL67C3R C480AABG3 PB22BM41K PB22SIM40Y PB22SKRS31KC L32R-R2-2311 L3353-MWRG L39UR-R24-2111 L58D-G2-W L58D-Y2-W L59D-R12-W L59UD-R12-W L625DG L625DR LE177WL39007 LH1048BSWL3702 LH1048BWL3702 LH382A LH677G LHM628A FL276WL7R FL2950BWL7R FL2950WL7R FL2950WL8R FL2950WL8R-12 FL2951WL8G FL2951WL8R FL589C7R FL67WL8G MPC5BCW18.0 556-1605-808F 556-1705-809F 556-3008-839F 558-0201-818F 559-0001-813F 559-1301-801F