



REVISIONS			
LTR.	DESCRIPTION	DATE	APP.

NOTES:

- FILAMENT SHAPE MUST BE UNIFORM WITH COILS EVENLY SPACED AND FREE OF TWIST OR SHORTING.
- BULB SHALL BE CLEAN WITH NO FOREIGN MATERIALS OR GLASS CHIPS INSIDE.
- CENTER OF FILAMENT SHALL BE WITHIN THE CENTER 1/3 OF THE BULB.
- LAMPS SHALL BE CAPABLE OF OPERATION AND STORAGE AT TEMPERATURES FROM -65 °C TO +100 °C WITHOUT DEGRADATION.
- LAMPS SHALL BE PACKAGED IN CONTAINERS SUITABLE TO PREVENT BREAKAGE DURING SHIPMENT.
- LAMP BASE TO BE NICKEL PLATED D.C. BAYONET.

JAN 20 2001

1/29/98

Superseded by Drawing # A14726 Rev A

ELECTRICAL CHARACTERISTICS					
VOLTS	WATTS	AMPS	MSCP NOM.	LIFE HOURS (AVG.)	FILAMENT SHAPE
24.0	6.5	.271 ± .027	2.50	1500	C-2V



CHICAGO MINIATURE
 WHERE INNOVATION COMES TO LIGHT

1080 Johnson Drive
 Buffalo Grove, Illinois 60089

Telephone: (708) 459-3400
 Fax: (708) 459-2708

DRAWN BY JK MURPHY	DATE 5/17/96	TOLERANCES UNLESS OTHERWISE SPECIFIED	DESCRIPTION T-6 D.C. BAYONET BASE LAMP	PART NUMBER CM8-A234
CHECKED BY DE FORSMAN	5/17/96	3 PLACE ± .XXX		
APPROVED BY DON MACCRINDLE	5/17/96	2 PLACE ± .XX		
PREVIOUSLY WAS X-4756		ANGULAR ± .X		
		FRACTIONAL ± X/X		
DIMENSIONS IN PARENTHESES ARE IN mm		SCALE		
		NTS		
			REVISION	SHEET 1 OF 1

A14726 REV. A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Lamps category](#):

Click to view products by [Visual Communications Company](#) manufacturer:

Other Similar products are found below :

[5AB](#) [6180](#) [8111](#) [8623](#) [912](#) [120PS](#) [1224](#) [DE603](#) [DW50](#) [IFL-LX2162-16T](#) [C9A](#) [C9A](#) [3015](#) [303](#) [19](#) [PR13](#) [268](#) [GT-NE6H1225T](#)
[CM5004WW](#) [32-2211T](#) [323](#) [509K](#) [5314N1](#) [5314N2](#) [WWT1-EW10/GRN](#) [4925H1](#) [DW07](#) [10C7DC-120V](#) [1141](#) [MS25231-313](#) [E73](#) [CM2](#)
[7683EBP](#) [8553](#) [XE135B](#) [WWT2-EW34BLA](#) [6S6/30V](#) [7367](#) [1301910036](#) [7A1H](#) [8630FBBB](#) [85](#) [106](#) [105](#) [BGF717-UV1](#) [1974D](#) [1495](#) [373](#)
[400](#) [502](#)