

Low Profile, Panel Flush Light Pipe

Light pipe transmits from SMD LED to the front of a panel

Applications

- security cameras
- entertainment systems
- telephone systems

Key features

- allows easy panel removal
- low profile, panel flush design blends in until light is emitted
- mates to any PCB using SMD 4 (sold separately)
- optical grade acrylic for maximum light transmission

- panel and cabinet illumination
- medical devices
- efficient production assembly
- available in standard lengths of .300" to 1.20"
- custom lengths available upon request
- RoHS compliant

Product specifications

Materials				
LPCM (litepipe)	clear optical grade acrylic, UL rating 94-HB			
SMD 4 (PCB mount)	nylon, (black) UL rating 94-V2			

Installation specification				
mounting hole	.173" [4.4mm] min to .183" [4.6mm] max without retaining ring RTN 150			
	.173" [4.4mm] min to .200" [5.1mm] max with retaining ring RTN 150			
panel thickness	MAX : DIM A300" [7.62mm]			


Ordering data

LPCM lightpipe ordering code (example)	LPCM XXX CTP	LITEPIPE ORDERING CALCULATIONS: DIM A - DIM B (.200" [5.1mm]) = MIN LIGHTPIPE LENGTH
(Min 030 =. 300") (Max 120	= 1.20")	DIM A - DIM C (.100" [2.5mm]) = MAX LIGHTPIPE LENGTH

XXX = length in inches							
Standard sizes*							
030	040	050	060	070			
080	090	100	110	120			

*Custom Lengths Available Upon Request





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Light Pipes category:

Click to view products by Visual Communications Company manufacturer:

Other Similar products are found below :

 1367627-1
 SLP3-300-450-F
 SLP3-400-450-R
 LPA-C011301S-6
 LPF-C011306S
 FLP25-1.95
 VLP-640-F
 LPA-C011301S-5.4
 LPA

 R051171S-12
 LPA-S011331S
 515-1027-803F
 515-1217F
 SLP3-150-300-R
 SLP3-500-450-R
 515-1064-810F
 FLPV-SG
 BDL-1187

 7511A41
 7511A87-500
 FLPV-SBC
 5151064802F
 5151-192-0055-0DF
 LPF-R011340S
 515-1166-801F
 FLPF-6.0
 PM4-C1522-3.70
 LC

 11.25
 CLP-1214
 515-1064-808F
 FLX3_05
 515-1192-0025-0DF
 HS LC-H-D2/R2XC1-2 54
 515-1192-80-3DF
 1282.2600
 1296.2004

 PBLP-1001-1
 SZ1-10.00-A220-F4P54
 SZ1-10.00-A220-F4P
 LC2-4.1
 1296.7042
 SF4-2.5-F5P
 PLP5-2-625-54
 FLP25-13.5
 1271.2002

 1272.0030
 1276.2004
 1281.1001-8MM
 1282.1300
 1296.2022