


Power Wirewound Resistors
radial, fibre glass core, coated




Specifications

Type		KP290	KP292	KP294	KP296	KP298
Styles		0518	0523	0533	0543	0553
Power rating P_{70}	W	2,0	4,0	5,0	6,5	8,0
Resistance range	Ω	0R1 ... 7K5	0R15 ... 11K	0R27 ... 20K	0R39 ... 27K	0R47 ... 36K
E-Series		E 24/E 12	E 24/E 12	E 24/E 12	E 24/E 12	E 24/E 12
Tolerances	%	± 10 $\pm 5 \geq 0R2$	± 10 $\pm 5 \geq 0R3$	± 10 $\pm 5 \geq 0R47$	± 10 $\pm 5 \geq 0R68$	± 10 $\pm 5 \geq 0R91$
Temperature coefficient	$10^{-6} \cdot K^{-1}$		- 80 ... + 500			
max. cont. work. voltage	V_{RMS}		$\sqrt{P_{70} \cdot R}$ for all styles			
Insulation voltage (1min.)	V_{RMS}		max 75			
Insulation resistance	Ω		not insulated			
Derating linear	$^{\circ}C$		70 ... 350 (0W)			
Climatic category			55/200/56			
Temperature range	$^{\circ}C$		- 55 ... 350			
Thermal resistance	KW^{-1}	110	70	60	50	40
Failure rate (Total, ϑ_0 , max., 60% conf. lev.)	$10^{-9} \cdot h^{-1}$		appr. 100, depends on value			
Endurance (P_{70} , 70 $^{\circ}C$, 1000)	$\left[\frac{\Delta R}{R}\right] \%$		$\pm 3,0$ average			
Damp heat, steady state (40 $^{\circ}C$, 93% r.h., 56d)	$\left[\frac{\Delta R}{R}\right] \%$		$\pm 2,0$			
Climatic sequence	$\left[\frac{\Delta R}{R}\right] \%$		$\pm 2,0$			
Terminal strength	$\left[\frac{\Delta R}{R}\right] \%$		$\pm 1,0$			
Terminal tensile strength	N		40			
Resistance to soldering heat (260 $^{\circ}C$, 10s)	$\left[\frac{\Delta R}{R}\right] \%$		$\pm 0,2$ typ.			
Solderability	s	solderable according to IEC 60068-2-20 Ta				
Marking		on termination; value 3 digits, Tolerance, Production date code				


Dimensions in mm:



Type 290-0... 298-0









Type 290-1... 298-1



Type	L	RM
KP290-0/1	18,2	10
KP292-0/1	23,3	15
KP294-0/1	33,4	25
KP296-0/1	43,5	35
KP298-0/1	53,7	45

Type	RM Tolerance	Xmax.
KP29x-0	+1,0	3,0
KP29x-1	+0,8	1,7

Temperature rise:
(solder joints)



Packaging:

Type	Packaging	Pieces	Pack.-Code
KP290-0	bulk	500	B
KP290-1	bulk	1000	B
KP292-0	bulk	500	B
KP292-1	bulk	1000	B
KP294-0	bulk	250	B
KP294-1	bulk	500	B
KP296-0	bulk	250	B
KP296-1	bulk	500	B
KP298-0	bulk	250	B
KP298-1	bulk	250	B

Ordering example: KP294-1 5 B 1K3
 Type Tolerance Pack.-Code R-Value

Revision 200807

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Wirewound Resistors - Through Hole category](#):

Click to view products by [Vitrohm manufacturer](#):

Other Similar products are found below :

[75822-2K4](#) [90J56R](#) [AC03000001208JAC00](#) [EP3WS47RJ](#) [C1010KJL](#) [C1015RJL](#) [C3A10KJT](#) [27J1K0](#) [ES3W47RJ](#) [AC04000001500JAC00](#)
[AC10000002208JAB00](#) [AC10000004708JAB00](#) [SQMW5R39J](#) [SQPW5R22J](#) [SQPW5R33J](#) [1879927-3](#) [FCB2100RJ](#) [T505](#) [FSQ5WR47J](#)
[FW10A33R0JA](#) [CPCC03R5000JB31](#) [CPCC0510R00JE32](#) [CPCC051R000JB31](#) [CPCP10500R0JE32](#) [CPW05700R0JE143](#)
[CPW152K500JE313](#) [C1010RJL](#) [C10R47JL](#) [C141K0JL](#) [C144R7JL](#) [ES05W100RJ](#) [SQMW1047RJ](#) [SQMW210RJ](#) [CPCC03R2000JB31](#)
[CPCC0515R00JE01](#) [CPW055R000JB143](#) [CPW103K300JE143](#) [CPW202R000JB14](#) [ULW5-39R0JT075](#) [W31-R47JA1](#) [ULW5-68RJT075](#)
[SQBW401K0JFASTON](#) [SPH1001JLF](#) [65888-3R3](#) [CPCC10R5100JE66](#) [SQP500JB-400R](#) [SQBW403R3JFASTON](#) [280-PRM7-4.7-RC](#)
[CW02B9R100JE73](#) [CPCP05R1000JE32](#)