


Power Wirewound Resistors
radial, fibre glass core, coated




Specifications

Type		KP290	KP292	KP294	KP296	KP298
Styles		0518	0523	0533	0543	0553
Power rating P_{70}	W	2,0	4,0	5,0	6,5	8,0
Resistance range	Ω	0R1 ... 7K5	0R15 ... 11K	0R27 ... 20K	0R39 ... 27K	0R47 ... 36K
E-Series		E 24/E 12	E 24/E 12	E 24/E 12	E 24/E 12	E 24/E 12
Tolerances	%	± 10 $\pm 5 \geq 0R2$	± 10 $\pm 5 \geq 0R3$	± 10 $\pm 5 \geq 0R47$	± 10 $\pm 5 \geq 0R68$	± 10 $\pm 5 \geq 0R91$
Temperature coefficient	$10^{-6} \cdot K^{-1}$		- 80 ... + 500			
max. cont. work. voltage	V_{RMS}		$\sqrt{P_{70} \cdot R}$ for all styles			
Insulation voltage (1min.)	V_{RMS}		max 75			
Insulation resistance	Ω		not insulated			
Derating linear	$^{\circ}C$		70 ... 350 (0W)			
Climatic category			55/200/56			
Temperature range	$^{\circ}C$		- 55 ... 350			
Thermal resistance	KW^{-1}	110	70	60	50	40
Failure rate (Total, ϑ_0 , max., 60% conf. lev.)	$10^{-9} \cdot h^{-1}$		appr. 100, depends on value			
Endurance (P_{70} , 70 $^{\circ}C$, 1000)	$\left[\frac{\Delta R}{R}\right] \%$		$\pm 3,0$ average			
Damp heat, steady state (40 $^{\circ}C$, 93% r.h., 56d)	$\left[\frac{\Delta R}{R}\right] \%$		$\pm 2,0$			
Climatic sequence	$\left[\frac{\Delta R}{R}\right] \%$		$\pm 2,0$			
Terminal strength	$\left[\frac{\Delta R}{R}\right] \%$		$\pm 1,0$			
Terminal tensile strength	N		40			
Resistance to soldering heat (260 $^{\circ}C$, 10s)	$\left[\frac{\Delta R}{R}\right] \%$		$\pm 0,2$ typ.			
Solderability	s		solderable according to IEC 60068-2-20 Ta			
Marking			on termination; value 3 digits, Tolerance, Production date code			


Dimensions in mm:



Type 290-0... 298-0









Type 290-1... 298-1



Type	L	RM
KP290-0/1	18,2	10
KP292-0/1	23,3	15
KP294-0/1	33,4	25
KP296-0/1	43,5	35
KP298-0/1	53,7	45

Type	RM Tolerance	Xmax.
KP29x-0	+1,0	3,0
KP29x-1	+0,8	1,7

Temperature rise:
(solder joints)



Packaging:

Type	Packaging	Pieces	Pack.-Code
KP290-0	bulk	500	B
KP290-1	bulk	1000	B
KP292-0	bulk	500	B
KP292-1	bulk	1000	B
KP294-0	bulk	250	B
KP294-1	bulk	500	B
KP296-0	bulk	250	B
KP296-1	bulk	500	B
KP298-0	bulk	250	B
KP298-1	bulk	250	B

Ordering example: KP294-1 5 B 1K3
 Type Tolerance Pack.-Code R-Value

Revision 200807

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Metal Oxide Resistors](#) category:

Click to view products by [Vishay](#) manufacturer:

Other Similar products are found below :

[009260C](#) [FA87/180R/5%](#) [ROX1SJ4R7](#) [R0229](#) [M012CT52R220J](#) [WK80922003900J5C00](#) [434529B](#) [WMO5S-100KJA05](#) [ROX1SJ12K](#)
[ROX1SJ270K](#) [054084X](#) [054211G](#) [054220E](#) [095734G](#) [RS02B887R0FE73](#) [RSS2W470RJTB](#) [RSS3470RJTB](#) [WK202070A1003JD500](#)
[ROX3SJR22](#) [WR404140A2208JFE00](#) [RSS551KJ](#) [RSS3150RJTB](#) [ROX5SJ39K](#) [MOSX1CT528R2R20F](#) [RSF-25JT-52-120R](#) [RSF50SJT-52-](#)
[330K](#) [RSF2WSJT-52-60R](#) [RSF-25JT-52-2M](#) [RSF50SJT-52-1M](#) [RSF100JT-52-360K](#) [RSF50SJT-52-22R](#) [RSF50SJT-52-15R](#) [RSF200JT-73-](#)
[280R](#) [RSF50SJT-52-0R5](#) [RSF-25JT-52-1M2](#) [RSF200JT-73-0R2](#) [RSF-50JT-52-2K5](#) [MO1W-150R±5%-TT63](#) [MO3W-200R±5%-9T73](#)
[ROX2SJ4K3](#) [ROX5SJ120R](#) [ROX3SJR10](#) [ROX2SJ200K](#) [CPF2200R00JKRE6](#) [LVR01R0200FE73](#) [HR1206J47RP05](#) [HR1206J1MP05](#)
[HR1206F430KP05](#) [HR1206F680KP05](#) [HR1206J100RP05](#)