



# VIS30039

## 30V N-Channel Power Trench MOSFET

### General Description

- Trench Power MOSFET Technology
- Low  $R_{DS(ON)}$
- Optimized for High Reliable Switch Application
- High Current Capability
- RoHS and Halogen-Free Compliant

### Applications


- Motor Drive
- Load Switch
- Battery Protection
- General DC/DC Converters

### Product Summary


$V_{DS}$		30V
$I_D$	(at $V_{GS}=10V$ )	32A
$R_{DS(ON)}$	(at $V_{GS}=10V$ , typ)	3.7m $\Omega$
$R_{DS(ON)}$	(at $V_{GS}=4.5V$ , typ)	4.9m $\Omega$

100% UIS Tested


100% RG Tested



Top View




Top View



DFN3.3X3.3

Bottom View



### Orderable Part Number

VIS30039

### Package Type

DFN3.3x3.3

### Form

Tape & Reel

### Minimum Order Quantity

5000

### Absolute Maximum Ratings $T_A=25^\circ C$ unless otherwise noted

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	$V_{DS}$	30	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current <sup>(5)</sup>	$T_C=25^\circ C$	32	A
	$T_C=100^\circ C$	32	A
Pulsed Drain Current <sup>(3)</sup>	$I_{DM}$	250	A
Continuous Drain Current	$T_A=25^\circ C$	21	A
	$T_A=100^\circ C$	17	A
Avalanche Current <sup>(3)</sup>	$I_{AS}$	33.3	A
Avalanche Energy $L=0.1mH$ <sup>(3)</sup>	$E_{AS}$	55	mJ
Power Dissipation <sup>(2)</sup>	$T_C=25^\circ C$	36	W
	$T_C=100^\circ C$	13	W
Power Dissipation <sup>(1)</sup>	$T_A=25^\circ C$	3.1	W
	$T_A=100^\circ C$	1.25	W
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150	$^\circ C$

### Thermal Characteristics

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient <sup>(1)</sup>	$R_{\theta JA}$	30	40	$^\circ C/W$
Maximum Junction-to-Ambient <sup>(1,4)</sup>		Steady-State	60	75
Maximum Junction-to-Case	$R_{\theta JC}$	2.8	3.4	$^\circ C/W$



# VIS30039


## 30V N-Channel Power Trench MOSFET

### Electrical Characteristics (T<sub>J</sub>=25°C unless otherwise noted)


Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	I <sub>D</sub> =250μA, V <sub>GS</sub> =0V	30			V
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> =30V, V <sub>GS</sub> =0V T <sub>J</sub> =55°C			1 5	μA
I <sub>GSS</sub>	Gate-Body leakage current	V <sub>DS</sub> =0V, V <sub>GS</sub> =±20V			±100	nA
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA	1.4	1.8	2.2	V
R <sub>DS(ON)</sub>	Static Drain-Source On-Resistance	V <sub>GS</sub> =10V, I <sub>D</sub> =20A T <sub>J</sub> =125° V <sub>GS</sub> =4.5V, I <sub>D</sub> =20A		3.7 5.3 4.9	4.5 6.7	mΩ
g <sub>FS</sub>	Forward Transconductance	V <sub>DS</sub> =5V, I <sub>D</sub> =20A		71		S
V <sub>SD</sub>	Diode Forward Voltage	I <sub>S</sub> =1A, V <sub>GS</sub> =0V		0.71		V
I <sub>S</sub>	Maximum Body-Diode Continuous Current				48	A
<b>DYNAMIC PARAMETERS</b>						
C <sub>iss</sub>	Input Capacitance	V <sub>GS</sub> =0V, V <sub>DS</sub> =15V, f=1MHz		2366		pF
C <sub>oss</sub>	Output Capacitance			350		pF
C <sub>rss</sub>	Reverse Transfer Capacitance			225		pF
R <sub>g</sub>	Gate resistance	f=1MHz		0.7		Ω
<b>SWITCHING PARAMETERS</b>						
Q <sub>g</sub> (10V)	Total Gate Charge	V <sub>GS</sub> =10V, V <sub>DS</sub> =15V, I <sub>D</sub> =20A		45.5		nC
Q <sub>g</sub> (4.5V)	Total Gate Charge			21.6		nC
Q <sub>gs</sub>	Gate Source Charge			9.7		nC
Q <sub>gd</sub>	Gate Drain Charge			9.4		nC
t <sub>D(on)</sub>	Turn-On Delay Time	V <sub>GS</sub> =10V, V <sub>DS</sub> =15V, R <sub>L</sub> =0.75Ω, R <sub>GEN</sub> =3Ω		12.3		ns
t <sub>r</sub>	Turn-On Rise Time			9.4		ns
t <sub>D(off)</sub>	Turn-Off Delay Time			28.5		ns
t <sub>f</sub>	Turn-Off Fall Time			9.8		ns
t <sub>rr</sub>	Body Diode Reverse Recovery Time	I <sub>F</sub> =20A, di/dt=200A/μs		6.8		ns
Q <sub>rr</sub>	Body Diode Reverse Recovery Charge	I <sub>F</sub> =20A, di/dt=200A/μs		10.2		nC

- 1) R<sub>θJA</sub> is measured with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with T<sub>A</sub>=25°C. The Power dissipation P<sub>DSM</sub> is based on R<sub>θJA</sub> ≤ 10s and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.
- 2) The power dissipation P<sub>D</sub> is based on T<sub>J(MAX)</sub>=150°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.
- 3) Single pulse width limited by junction temperature T<sub>J(MAX)</sub>=150°C.
- 4) R<sub>θJA</sub> is the sum of the thermal impedance from junction to case R<sub>θJC</sub> and case to ambient.
- 5) The maximum current rating is package limited.


### TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




**Fig 1.** Typical Output Characteristics




**Fig 2.** Typical Transfer Characteristics




**Fig 3.** Normalized On-Resistance vs. Temperature



**Fig 4.** Typical Capacitance vs.  $V_{DS}$




**Fig 5.** Typical Gate Charge vs.  $V_{GS}$




**Fig 6.** Typical Source-Drain Diode Forward Voltage


### TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




**Fig 7.** Maximum Safe Operating Area



**Fig 8.** Maximum Drain Current vs. Case Temperature




**Fig 9.** Normalized Maximum Transient Thermal Impedance, Junction-to-Case




**Fig 10.** Normalized Maximum Transient Thermal Impedance, Junction-to-Ambient


### TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




**Fig 11.** Single Pulse Power Rating Junction-to-Case




**Fig 12.** Single Pulse Power Rating Junction-to-Ambient



**Fig 13.** Maximum Power Rating vs. Temperature




**Fig 14.** On-Resistance vs.  $V_{GS}$




**Fig 15.** On-Resistance vs. Drain Current


### TEST CIRCUIT




**Fig16.** Unclamped Inductive Test Circuit




**Fig17.** Unclamped Inductive Waveform




**Fig18.**  $Q_g$  Test Circuit



**Fig19.**  $Q_g$  Waveform



**Fig18.** Resistive Switching Test Circuit



**Fig19.** Switching Time Waveform



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [MOSFET](#) category:*

*Click to view products by [VOLTAIC](#) manufacturer:*

Other Similar products are found below :

[614233C](#) [648584F](#) [IRFD120](#) [IRFF430](#) [JANTX2N5237](#) [2N7000](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [AOD464](#) [2SK2267\(Q\)](#) [2SK2545\(Q,T\)](#)  
[405094E](#) [423220D](#) [MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [SSM6J414TU,LF\(T](#) [751625C](#) [PSMN4R2-30MLD](#)  
[TK31J60W5,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#)  
[NTE2384](#) [NTE2969](#) [NTE6400A](#) [DMN2080UCB4-7](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [SSM6P54TU,LF](#) [DMP22D4UFO-](#)  
[7B](#) [IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#) [STF5N65M6](#) [STU5N65M6](#) [C3M0021120D](#) [DMN13M9UCA6-7](#)  
[BSS340NWH6327XTSA1](#) [MCM3400A-TP](#) [DMTH10H4M6SPS-13](#) [IRF40SC240ARMA1](#) [IPS60R1K0PFD7SAKMA1](#)  
[IPS60R360PFD7SAKMA1](#) [IPS60R600PFD7SAKMA1](#)