

Printview: Triple-deck terminal block; 6-conductor through terminal block; L; without marker carrier; gray housing; internal commoning; conductor entry with violet marking; suitable for Ex e II applications - Item No.: 2002-3208

**WAGO**® online catalog / eShop

**Triple-deck terminal block; 6-conductor through terminal block; L; without marker carrier; gray housing; internal commoning; conductor entry with violet marking; suitable for Ex e II applications**

Item No.: 2002-3208



*Triple-deck terminal block; 6-conductor through terminal block; L; without marker carrier; gray housing; internal commoning; conductor entry with violet marking; suitable for Ex e II applications*

## Marking

RoHS ✓  
Compliant

## Business data

Supplier	WAGO
Item no.	2002-3208
GTIN / EAN	4044918691246
Content	1
Order amount	50
Customer item number	

## Notes

## Technical data



### Miscellaneous


Total number of connection points	6
Total number of potentials	1
Potentialkennzeichnung	L
Number of levels	3
Color	gray
Ratings according to 1	IEC/EN 60947-7-1
Pollution degree (1)	3
Rated voltage EN (1) [V]	500 [V]

Printview: Triple-deck terminal block; 6-conductor through terminal block; L; without marker carrier; gray housing; internal commoning; conductor entry with violet marking; suitable for Ex e II applications - Item No.: 2002-3208

<b>Technical data</b>	
<i>Rated surge voltage (1) [kV]</i>	<i>6 [kV]</i>
<i>Nominal current [A]</i>	<i>24 [A]</i>
<i>Nominal current (2) [A]</i>	<i>28 [A]</i>
<i>Rated voltage EN (Ex e II) [V]</i>	<i>440 [V]</i>
<i>Nominal current (Ex e II) [A]</i>	<i>19 [A]</i>
<i>Nominal current (Ex e II) with jumper [A]</i>	<i>17 [A]</i>
<i>Connection technology (1)</i>	<i>Push-in CAGE CLAMP®</i>
<i>Nominal cross section 1</i>	<i>2.5 mm<sup>2</sup></i>
<i>Solid sizes 1</i>	<i>0.25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG</i>
<i>solid, directly pluggable 1</i>	<i>0.75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG</i>
<i>Fine-stranded wires 1</i>	<i>0.25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG</i>
<i>min. fine-stranded with insulated ferrule, push-in terminati</i>	<i>0.75 mm<sup>2</sup> / 18 AWG</i>
<i>Strip length 1</i>	<i>10 ... 12 mm / 0.39 ... 0.47 in</i>
<i>Type of wiring</i>	<i>Front-entry wiring</i>
<i>Design</i>	<i>horizontal</i>
<i>Marking level</i>	<i>Center/Side marking</i>
<i>Insulating material</i>	<i>Polyamide 66 (PA 66)</i>
<i>Fire load [MJ]</i>	<i>0.321 [MJ]</i>
<i>Weight [g]</i>	<i>17.745 [g]</i>
<i>Width</i>	<i>5.2 mm / 0.205 in</i>
<i>Height from upper-edge of DIN-rail [mm]</i>	<i>69.5 [mm]</i>
<i>Height from upper-edge of DIN-rail</i>	<i>69.5 mm / 2.736 in</i>
<i>Length</i>	<i>93.3 mm / 3.673 in</i>
<i>Type of mounting</i>	<i>DIN 35 rail</i>

Images & drawings





#### Address

WAGO Kontakttechnik GmbH & Co. KG

Hansastr. 27

32423 Minden

Telefon: 0571/887-0

Fax: 0571/887-169

<http://www.wago.com>

© WAGO Kontakttechnik GmbH & Co. KG

Technische Änderungen und Irrtümer vorbehalten.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [wago manufacturer](#):*

Other Similar products are found below :

[750-460](#) [231-118/026-000](#) [231-303/026-000](#) [231-620/019-000](#) [257-403](#) [280-438](#) [280-831](#) [284-624](#) [210-111](#) [231-303/037-000](#) [231-446/001-000\\_NR](#) [232-216/026-000](#) [234-510](#) [264-726](#) [280-339](#) [0283-0671](#) [830-800/000-305](#) [750-512](#) [750-455](#) [51251782](#) [286-312](#) [713-1428/107-000](#) [731-138/048-000](#) [750-459](#) [750-517](#) [750-602](#) [793-3505](#) [826-172](#) [859-304](#) [280-335](#) [231-535/001-000](#) [2604-1105](#) [2604-1106](#) [2604-1504](#) [2606-1103/020-000](#) [2624-1103](#) [2626-3103/020-000](#) [821-104](#) [713-1107](#) [852-1411](#) [2106-1307](#) [2116-5307](#) [832-1205](#) [832-3604](#) [2009-110](#) [281-512/281-501](#) [286-336](#) [750-421](#) [750-838](#) [753-559](#)