


技术参数:

- 插芯:
- 插针数: 4+屏蔽
  - 额定电流: 10A
  - 额定电压: 50V
  - 额定脉冲电压: 0.8kV
  - 污染等级: 3
  - 绝缘阻抗:  $>10^{10}\Omega$
- 材料:
- 绝缘体: 聚碳酸酯
  - 外导体: 锌合金
- 接触电阻:  $\leq 4m\Omega$
  - 温度范围:  $-40^{\circ}C - +85^{\circ}C$
  - 依据UL 94的阻燃等级: V0
  - 外导体表面: 镀
  - 电缆直径: 3-9.5mm
  - 可插拔次数:  $>500$
- 插针:
- 接线方式: 冷压连接
  - 材料: 铜合金
  - 表面处理: 镀金
  - 接触电阻:  $\leq 3m\Omega$
  - 线径范围: 0.14-2.5mm<sup>2</sup>(26-14 AWG)
- 工具:
- 冷压钳: TL02G
  - 退针器: TL00
- 备注: 内包括直径为3-6和6-9.5mm的卡簧

Technical specification:

- Inserts:
- No. of contact: 4+shielding
  - Rated current: 10A
  - Rated voltage: 50V
  - Rated impulse voltage: 0.8kV
  - Pollution degree: 3
  - Insulation resistance:  $>10^{10}\Omega$
- Material:
- Insulator: polycarbonate
  - Outer conductor: zinc alloy
- Contact resistance:  $\leq 4m\Omega$
  - Temperature range:  $-40^{\circ}C - +85^{\circ}C$
  - Flammability acc.to UL 94: V0
  - Outer surface finish: nickel
  - Cable diameter: 3-9.5mm
  - Mating cycles:  $>500$
- Contacts:
- Terminal: crimp terminal
  - Material: copper alloy
  - Surface: hard-silver plated
  - Contact resistance:  $\leq 3m\Omega$
  - Wire gauge: 0.14-2.5mm<sup>2</sup>(26-14 AWG)
- Tools:
- Crimp contact tool: TL02G
  - Contact removal tool: TL00
- Note: 2 clamps for cable diameter 3-6 and 6-9.5mm included in the delivery range



						表面处理 Finish		-		图号 Drawing No.		-		
						材料 Material		-		产品代号 Part Code		EMC-004-FC		
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date					产品料号 Part No.		1290040200082	
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name				
绘图 Drawn	BQ LUO	18.10.2010	标准化 Stand.	-	-	1:1	V1.0	28g	-	-				
审核 Checked	P RAO	18.10.2010												
工艺 Process	-	-	批准 Approved	YY LIN	18.10.2010	All Dimensions in mm Original Size DIN A 4		 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD						

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [DC Power Connectors](#) category:*

*Click to view products by [WAIN](#) manufacturer:*

Other Similar products are found below :

[KLDX-SMT-0202-BPTR](#) [171-0722-E](#) [K596](#) [KLD-0201-BC](#) [4C6831AX](#) [10073976-112LF](#) [LCB60PW-M](#) [LCB30PW-M](#) [LCB60PB-M](#)  
[LCC30PB-M](#) [LCB50PW-M](#) [LCB50-M](#) [LCB60-F](#) [LCC30-M](#) [LCB40PW-M](#) [LCC30PW-M](#) [LCB50-F](#) [LCB40-F](#) [LCB30-F](#) [LCC40-M](#)  
[LCC40PB-M](#) [LCB40PB-M](#) [LCC40-F](#) [LCB60-M](#) [LCC40PW-M](#) [LCB50PB-M](#) [DC-002-100](#) [DC-031A-130](#) [DC-031A-100](#) [DC-003A-130](#)  
[DC-045-130](#) [DC-192-130](#) [DC-033-130](#) [DC-011-100](#) [DC-002F-130](#) [DC-002-130](#) [DB-14-2F](#) [DC-183B](#) [DC-060-04A](#) [DC-099-200](#) [DC-015-](#)  
[250-A](#) [DC-016-200-A](#) [DC-005A-200](#) [DC-044A-200](#) [DC-088-200](#) [DC-022A-200](#) [DC-038-150](#) [DC-012A-250](#) [DC-005C-130](#) [DC-012A-200](#)