



技术参数:

插芯:

- 插针数: 1
 - 额定电流:
 - 不带适配器: 650A
 - 额定电压: 4000V
 - 额定脉冲电压: 18kV
 - 污染等级: 3
 - 绝缘阻抗: $> 10^{10}\Omega$
 - 材料: 聚酰胺
 - 颜色: RAL 9002 (浅白色)
 - 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - 依据UL 94的阻燃等级: V0
 - 可插拔次数: > 500
- 插针:
- 接线方式: 轴向螺栓连接
 - 材料: 铜合金
 - 表面处理: 镀银
 - 接触电阻: $\leq 0.2\text{m}\Omega$
 - 电缆绞线依据: IEC 60 228-5
- 轴向螺栓连接:
- 横截面: $70-120\text{mm}^2/150-185\text{mm}^2$
 - 剥线长度: 23-25mm
 - 最大电缆直径: 26.5mm
- 拧紧力矩:
- mm^2 : 70 95 120 150 185
 - $\text{N}\cdot\text{m}$: 12 14 16 17 18

螺栓连接:

- 螺纹: M12
 - 拧紧力矩: $16-18\text{N}\cdot\text{m}$
- 固定框架:
- 材料: 不锈钢
 - 外壳固定螺丝的拧紧力矩: $0.5\text{N}\cdot\text{m}$

Technical specification:

Insters:

- No. of contact: 1
 - Rated current:
 - Without adapter: 650A
 - Rated voltage: 4000V
 - Rated impulse voltage: 18kV
 - Pollution degree: 3
 - Insulation resistance: $> 10^{10}\Omega$
 - Material: polyamide
 - Colour: RAL 9002(grey white)
 - Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - Flammability acc.to UL 94: V0
 - Mating cycles: > 500
- Contacts:
- Terminal: axial screw terminal
 - Material: copper alloy
 - Surface: hard-silver plated
 - Contact resistance: $\leq 0.2\text{m}\Omega$
 - For stranded wire acc. to: IEC 60 228-5
- Axial screw termination:
- Wire gauge: $70-120\text{mm}^2/150-185\text{mm}^2$
 - Stripping length: 23-25mm
 - Max. cable diameter: 26.5mm
- Tightening torque:
- mm^2 : 70 95 120 150 185
 - $\text{N}\cdot\text{m}$: 12 14 16 17 18
- Screw terminal:
- Thread: M12
 - Tightening torque: $16-18\text{N}\cdot\text{m}$
- Frame:
- Material: stainless steel
 - Tightening torque of the fixing screws: $0.5\text{N}\cdot\text{m}$

						表面处理 Finish	-			图号 Drawing No.	-
						材料 Material	-			产品代号 Part Code	HC650.185-F
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date				产品料号 Part No.	1310010210202
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	-
绘图 Drawn	BQ LUO	18.03.2019	标准化 Stand.	-	-	2:3	V1.2	261.57g	-		
审核 Checked	HZ LAN	18.03.2019									
工艺 Process	-	-	批准 Approved	HQ ZHANG	18.03.2019	All Dimensions in mm Original Size DIN A 4			厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DC Power Connectors](#) category:

Click to view products by [WAIN](#) manufacturer:

Other Similar products are found below :

[KLDX-SMT-0202-BPTR](#) [171-0722-E](#) [K596](#) [KLD-0201-BC](#) [4C6831AX](#) [10073976-112LF](#) [LCB60PW-M](#) [LCB30PW-M](#) [LCB60PB-M](#)
[LCC30PB-M](#) [LCB50PW-M](#) [LCB50-M](#) [LCB60-F](#) [LCC30-M](#) [LCB40PW-M](#) [LCC30PW-M](#) [LCB50-F](#) [LCB40-F](#) [LCB30-F](#) [LCC40-M](#)
[LCC40PB-M](#) [LCB40PB-M](#) [LCC40-F](#) [LCB60-M](#) [LCC40PW-M](#) [LCB50PB-M](#) [DC-002-100](#) [DC-031A-130](#) [DC-031A-100](#) [DC-003A-130](#)
[DC-045-130](#) [DC-192-130](#) [DC-033-130](#) [DC-011-100](#) [DC-002F-130](#) [DC-002-130](#) [DB-14-2F](#) [DC-183B](#) [DC-060-04A](#) [DC-099-200](#) [DC-015-](#)
[250-A](#) [DC-016-200-A](#) [DC-005A-200](#) [DC-044A-200](#) [DC-088-200](#) [DC-022A-200](#) [DC-038-150](#) [DC-012A-250](#) [DC-005C-130](#) [DC-012A-200](#)