



- 技术参数:
- 插芯:
    - 插针数: 4/2+PE
    - 额定电流:
      - 电力区: 40A
      - 信号区: 10A
    - 额定电压:
      - 电力区: 400V (相对地额定电压)
      - 690V (相间额定电压)
      - 信号区: 250V
    - 额定脉冲电压:
      - 电力区: 6kV
      - 信号区: 4kV
    - 污染等级: 3
    - 依据UL/CSA的额定电压: 600/250V
    - 绝缘阻抗:  $> 10^{10}\Omega$
    - 材料: 聚碳酸酯
    - 颜色: RAL 7032 (浅灰色)
    - 温度范围:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
    - 依据UL 94的阻燃等级: V0
    - 可插拔次数:  $> 500$
  - 插针:
    - 接线方式: 冷压连接
    - 材料: 铜合金
    - 表面处理:
      - 镀银
      - 镀金
    - 接触电阻:  $< 0.3\text{m}\Omega$
    - 线径范围:
      - 强电针: 1.5-6mm<sup>2</sup>(16-10 AWG)
      - 信号针: 0.14-2.5mm<sup>2</sup>(26-14 AWG)
    - 最大绝缘直径:
      - 强电针: 5mm
  - 塑料外壳:
    - 材料: 热塑性塑料
    - 联锁元件: 聚酰胺 (尼龙)
    - 外壳密封: 丁腈橡胶
    - 温度范围:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
    - 依据UL 94的阻燃等级: V0
    - 防护等级: IP65 (联锁状态, IEC 60529)
  - 工具:
    - 冷压钳:
      - TL02G(0.5-4mm<sup>2</sup>)
      - TL02-0G(1.5-6mm<sup>2</sup>)
    - 退针器:
      - TL00 (10A退针器)
      - TL06G (40A退针器)

- Technical specification:
- Insters:
- No. of contact: 4/2+PE
  - Rated current:
    - Power side: 40A
    - Signal side: 10A
  - Rated voltage:
    - Power side: 400V(rated voltage conductor - ground)
    - 690V(rated voltage conductor - conductor)
    - Signal side: 250V
  - Rated impulse voltage:
    - Power side: 6kV
    - Signal side: 4kV
  - Pollution degree: 3
  - Rated voltage acc.to UL/CSA: 600/250V
  - Insulation resistance:  $> 10^{10}\Omega$
  - Material: polycarbonate
  - Colour: RAL 7032(light grey)
  - Temperature range:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
  - Flammability acc.to UL 94: V0
  - Mating cycles:  $> 500$
- Contacts:
- Terminal: crimp terminal
  - Material: copper alloy
  - Surface:
    - Hard-silver plated
    - Hard-gold plated
  - Contact resistance:  $< 0.3\text{m}\Omega$
  - Wire gauge:
    - Power contacts: 1.5-6mm<sup>2</sup>(16-10 AWG)
    - Signal contacts: 0.14-2.5mm<sup>2</sup>(26-14 AWG)
  - Max. insulation diameter: 5mm
- Plastic hoods/housings:
- Material: thermoplastic
  - Locking element: polyamide
  - Hoods/Housings seal: NBR
  - Temperature range:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
  - Flammability acc.to UL 94: V0
  - Degree of protection: IP65 (acc.to IEC 60529 for coupled connector)
- Tools:
- Crimping tool:
    - TL02G(0.5-4mm<sup>2</sup>)
    - TL02-0G(1.5-6mm<sup>2</sup>)
  - Contact removal tool:
    - TL00(for crimp contacts 10A)
    - TL06G(for crimp contacts 40A)

						表面处理 Finish		-		图号 Drawing No.		-	
						材料 Material		-		产品代号 Part Code		HQ-004/2-MC	
标记 Mark	处数 Number	变更描述/Description		签名 Signature	日期 Date	比例 Scale		版本 REV.	重量 Weight	数量 Qty.	产品料号 Part No.		1300060100001
绘图 Drawn	BQ LUO	姓名/Name	日期/Date	姓名/Name	日期/Date	1:1	V1.0	12.5g	-		产品名称 Part Name		-
审核 Checked	P RAO		18.10.2010										
工艺 Process	-			批准 Approved	YY LIN	18.10.2010	All Dimensions in mm Original Size DIN A 4		厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD				

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [DC Power Connectors](#) category:*

*Click to view products by [WAIN](#) manufacturer:*

Other Similar products are found below :

[KLDX-SMT-0202-BPTR](#) [171-0722-E](#) [K596](#) [KLD-0201-BC](#) [4C6831AX](#) [10073976-112LF](#) [LCB60PW-M](#) [LCB30PW-M](#) [LCB60PB-M](#)  
[LCC30PB-M](#) [LCB50PW-M](#) [LCB50-M](#) [LCB60-F](#) [LCC30-M](#) [LCB40PW-M](#) [LCC30PW-M](#) [LCB50-F](#) [LCB40-F](#) [LCB30-F](#) [LCC40-M](#)  
[LCC40PB-M](#) [LCB40PB-M](#) [LCC40-F](#) [LCB60-M](#) [LCC40PW-M](#) [LCB50PB-M](#) [DC-002-100](#) [DC-031A-130](#) [DC-031A-100](#) [DC-003A-130](#)  
[DC-045-130](#) [DC-192-130](#) [DC-033-130](#) [DC-011-100](#) [DC-002F-130](#) [DC-002-130](#) [DB-14-2F](#) [DC-183B](#) [DC-060-04A](#) [DC-099-200](#) [DC-015-](#)  
[250-A](#) [DC-016-200-A](#) [DC-005A-200](#) [DC-044A-200](#) [DC-088-200](#) [DC-022A-200](#) [DC-038-150](#) [DC-012A-250](#) [DC-005C-130](#) [DC-012A-200](#)