HSF

NOTES:
Rated Current: 3.0AMP.
Contact Resistance: 20mΩ Max.
Withstand Voltage: 1000V AC/DC
Insulation Resistance: 1000MΩ Min.
Operation Temperature: −40℃ to +105℃

Contact Material: Brass
Contact Plating: Au or Sn Over Ni
Insulator Material: PA9T+33%G.F UL94V−0 BK
A3

Recommended P.C.B Layout (Top Side)
(PCB BOARD TOLERANCE±0.05)





Ordering Information

1125-12 XX XX S XXX C 0 XX A2
(C: A3)

No.of Pins	Contact Plating	Pin Length	Insulator Material	Packing	Series No.
Per Row:02~40	G0=Gold Flash G3=10u"Gold G4=15u"Gold G5=30u"Gold S0=Gold Flash/Tin S3=10u"Gold/Tin S4=15u"Gold/Tin S5=30u"Gold/Tin SN=Tin SM=Matte Tin	L=A+B+2.5 Standard:085=8.5 095=9.5 105=10.5 116=11.6 118=11.8 135=13.5	C=PA9T	0=PE Bag T=Tube	01~99





Item	Pin Lenght	A	B	Mating
Standard	8.50	3.00	3.00	2135
	9.50	3.00	4.00	2145
	10.50	3.00	5.00	2150
	11.60	3.00	6.10	2171 2185 A1
	11.80	2.40	6.90	2171 2185
	13.50	3.00	8.00	
Alternate				

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A3	2018/06/02	Cancel PBT & Modify P/N	A3
A2	2018/01/22	Modify P/N	A2
A1	2016/02/19	MODIFY DRAWING	------
A0	2012/05/28	NEW	------

OPERATION	
X.X	±0.40
X.XX	±0.25
X.XXX	±0.15
Angle	± 3°
DIM	TOL

DRAW	Surong Xu	DATE	2018/06/02
CHECK		DATE	
APPROVE		DATE	
SCALE	Fit		
UNIT	mm [inch]		
SIZE	A4		
SHEET	1/1		
PROJ.			

PART NO. 1125−12XXXXSXXXC0XX A2 A3

TITLE: PH2.54 DUAL ROW S/T H=2.5

Customer NO.

WCON
Http: www.wcon.com

WCON−Dongguan
Tel: +86 769 85358920
Fax: +86 769 85358915
E-mail: sales@wcon.com

WCON−Kunshan
Tel: +86 512 57468408
Fax: +86 512 57468468
E-mail: salesks@wcon.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings ***category:***

Click to view products by Wcon ***manufacturer:***

Other Similar products are found below :

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 891-007-9SS-BST1T 000-34000 0008550134 0009482033 0009507031 57102-F02-18ULF 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 CSU011177004 636-1427 638009-1 641938-9 641991-4 644168-1 644827-2 647662-1 65039-019ELF 65692-001LF 65781-018 65781-047