

# HSF

**NOTES:**

Rated Current: 2.0AMP.  
 Contact Resistance: 20mΩ Max.  
 Withstand Voltage: 500V AC/DC  
 Insulation Resistance: 1000MΩ Min.  
 Operation Temperature: -40℃ to +125℃(GOLD)  
 -40℃ to +105℃(TIN)



Contact Material: Brass  
 Contact Plating: Au or Sn Over Ni  
 Insulator Material: PA9T+33%GF UL94V-0 BK

## Ordering Information



1215-12 XX G0 S XXX C 0 XX

No. of Pins Contact Plating Pin Length Insulator Packing Series No.  
 Per Row: 02-40 G0=Gold Flash L=A+B+1.5 Material 0=PE Bag 01-99  
 G3=10u"Gold Standard 063=6.3 C=PA9T T=Tube  
 G4=15u"Gold 073=7.3  
 G5=30u"Gold 083=8.3  
 S0=Gold Flash/Tin  
 S3=10u"Gold/Tin  
 S4=15u"Gold/Tin  
 S5=30u"Gold/Tin  
 SN=Tin Plated  
 SM=Matte Tin

Item	Pin Length	A	B	Mating
Standard	6.30	2.80	2.00	2220T 2221 2227T 2228
	7.30	2.80	3.00	2235
	8.30	2.80	4.00	2240 2243 2263 2272
	6.50	2.50	2.50	
	7.80	2.80	3.50	
	8.00	2.50	4.00	
	8.20	2.70	4.00	
	8.50	3.00	4.00	
	10.00	2.40	6.10	



Recommended P.C.B Layout (Top Side)  
 (PCB BOARD TOLERANCE±0.05)



REV	DATE	MODIFICATION DESCRIPTION
A0	2012/04/18	NEW
A1	2018/01/18	Modify P/N
A2	2019/02/28	Modify
A3	2020/06/11	Modify Pin 02~40P

OPERATION	DRAW	DATE	SCALE	Fit
XX ±0.40	2x King	2020/06/11	mm	A4
XXX ±0.25	CHECK	DATE	UNIT	mm
XXXX ±0.15	APPREVE	DATE	SIZE	A4
Angle ± 3'	DATE	DATE	SHEET	1/1
DIM TOL	DATE	DATE	PROJ.	1/1

PART NO. 1215-12XXXXXXC0XX  
 TITLE: PH2.00 DUAL ROW 180° H=1.5  
 Customer NO.

**WCON**  
 Http: www.wcon.com

WCON-Dongguan  
 Tel: +86 769 85358920  
 Fax: +86 769 85358915  
 E-mail: sales@wcon.com

WCON-Kunshan  
 Tel: +86 512 57468408  
 Fax: +86 512 57468468  
 E-mail: sales@wcon.com

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Wcon](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)