

HSF

NOTES:

Current Rating: 3AMP
 Contact Resistance: 20mΩ max
 Withstand Voltage: 500V AC/DC
 Insulation Resistance: 1000MΩ min
 Operation Temperature: -40°C to +105°C

Contact Material: Brass
 Contact plating: Au or Sn Over Ni
 Insulator Material: PBT+30%G.F.(U194V-0) $\Delta\Delta$


Ordering Information

3112-XX R XX B K00 X 1

No. of Pins	Contact Plating	Color Insulator	Packaging
10P 30P	CO=Gold Flash	B=Black	A=Tray
14P 34P	G1=3μ"Gold	U=Blue	T=Tube
16P 40P	G2=5μ"Gold	G=Gray(427C)	
20P 50P	G3=10μ"Gold	F=Gray(413C)	
24P 60P	G4=15μ"Gold		
26P 64P	G5=30μ"Gold		
	SP=Gold Flash/Tin		
	SI=3μ"Gold/Tin		
	S2=5μ"Gold/Tin		
	S3=10μ"Gold/Tin		
	S4=15μ"Gold/Tin		
	S5=30μ"Gold/Tin		
	SN=Tin		

A (TOLERANCE) $\Delta\Delta$

ITEM	≤ 20P	> 20P
A	± 0.20	± 0.30



REV	DATE	MODIFICATION DESCRIPTION	CHANGE	OPERATION	DRAW	DATE	SCALE	FIT	PART NO.	TITLE:	WCON--Dongguan	WCON--Kunshan
A2	2014/05/05	MODIFY	$\Delta\Delta$	X.X	Allen	2014/05/05	mm	A4	3112-XXXXXXBK00X1	2.54 BOX HEADER 90° H=13.6	Tel: +86 769 85358920	Tel: +86 512 57468408
A1	2012/05/10	MODIFY	$\Delta\Delta$	X.XXX	CHECK	DATE	SIZE	A4			Fax: +86 769 85358915	Fax: +86 512 57468468
A0	2008/05/08	NEW		X.XXX	APPROVE	DATE	SHEET	1/1	Customer NO.		E-mail: sales@wcon.com	E-mail: sales@wcon.com
				Angle			PROJ.					
				± 3'								
				TOL								

WCON

Http: www.wcon.com

WCON--Dongguan
 Tel: +86 769 85358920
 Fax: +86 769 85358915
 E-mail: sales@wcon.com

WCON--Kunshan
 Tel: +86 512 57468408
 Fax: +86 512 57468468
 E-mail: sales@wcon.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [I/O Connectors](#) category:

Click to view products by [Wcon](#) manufacturer:

Other Similar products are found below :

[571763P](#) [61-168618-12P](#) [D20419-211](#) [72.250.1628.2](#) [72.250.2428.2](#) [76.350.0729.0](#) [76871-1403](#) [PCR-E36PM](#) [PCS-XE26LKA](#) [PCS-XES68MS+](#) [G38A71314B](#) [9776-18-6](#) [1571250010](#) [157-22500-3](#) [MS3471L14-19P L/C](#) [192991-0703](#) [91-644626-35P](#) [172501-6002](#) [FCN-260C008-A/L0](#) [FCN-260C024-AL0](#) [FCN-261Z008](#) [2000314-1](#) [200331-1](#) [PCS-E28FS+](#) [PCS-XE26SLFD+](#) [PCS-XE26SLFDT+](#) [G730VID08BDC24](#) [HDMR-29-01-S-SM-TR](#) [HDRA-E68W1LFDTC-SL+](#) [54182-0605](#) [UE86K842720321](#) [38113800006](#) [DP3AR020WQ1R200](#) [Z4.102.0680.0](#) [500-1040](#) [500-1052](#) [500-1054](#) [ZP-4008-66L](#) [10-565995-597N](#) [10-584459-12P](#) [5554841-1](#) [SM3106F14S-7S-LC](#) [SM3106R18-18S](#) [U90B3054061110](#) [U65-E04-4020](#) [ZPF000000000097891](#) [557-262M2-06C](#) [PCS-96LFD+](#) [60-042222-02S](#) [10099439-003C-TRLF](#)