

HSF

Recommended P. C. B Layout (Top Side)
(PCB BOARD TOLERANCE ± 0.05)

NOTE:


1. MATERIAL:
 - 1.1 INSULATOR: LCP+30%G.F, UL94V-0; BLACK.
 - 1.2 CAP: LCP+30%G.F, UL94V-0; BLACK.
 - 1.3 CONTACT: PHOSPHOR BRONZE.
 - 1.4 MOUNTING EAR: PHOSPHOR BRONZE.
2. FINISH:
 - 2.1 CONTACT: 3u" OR 5u" MIN. GOLD PLATED IN CONTACT AREA
 Δ 80u" MIN. TIN PLATED IN SOLDER AREA
 50u" MIN. NICKEL UNDERPLATED OVERALL.
 - 2.2 MOUNTING EAR: 100u" MIN. TIN PLATED OVER
 50u" MIN. NICKEL UNDERPLATED OVERALL.
3. ELECTRICAL CHARACTERISTICS
 - 3.1 CURRENT RATING: 0.5A.
 - 3.2 CONTACT RESISTANCE: 65m Ω MAX.
 - 3.3 INSULATION RESISTANCE: 1000M Ω MIN DC500V.
 - 3.4 DIELECTRIC WITHSTANDING VOLTAGE: 250V AC PER MINUTE.
 - 3.5 OPERATING TEMPERATURE: -40°C ~ +105°C.
 - 3.6 OPERATING: 100 CYCLES MIN.
 - 3.7 INSERTION FORCE: 90g MAX. Per PIN PAIR.
 - 3.8 WITHDRAWAL FORCE: 10g MIN. Per PIN PAIR.
 - 3.9 CONTACT RETENTION FORCE: 250g MIN. PER CONTACT
 - 3.10 STORAGE TEMPERATURE: -10°C ~ +40°C.

Flatness: <80Pins The "M" Is 0.10mm MAX
 Δ \geq 80Pins The "M" Is 0.15mm MAX

Ordering Information

3614- P XXX - XXX XX R 01

No. of Pins	High "H"	Contact Plating	Packing
		Δ S1=3u"Gold/Tin S3=10u"Gold/Tin S4=15u"Gold/Tin S5=30u"Gold/Tin	R=Tape&Reel+CAP



No. of Pins	Dimension				
	A	B	C	D	E
20	15.30	8.60	7.20	12.20	12.80
30	19.30	12.60	11.20	16.20	16.80
40	23.30	16.60	15.20	20.20	20.80
50	27.30	20.60	19.20	24.20	24.80
60	31.30	24.60	23.20	28.20	28.80
80	39.30	32.60	31.20	36.20	36.80
100	47.30	40.60	39.20	44.20	44.80
120	55.30	48.60	47.20	52.20	52.80
160	71.30	64.60	63.20	68.20	68.80

B3	2018/05/24	Modify	Δ	OPERATION	DRAW	DATE	SCALE	FIT	PART NO. 3614-PXXX-XXXXR01
B2	2016/11/18	Modify CAP Length	Δ	x.x ± 0.40	Ding	2018/05/24	UNIT	mm	
B1	2016/08/08	ADD 50Pin	Δ	x.xx ± 0.25	CHECK	DATE	SIZE	inch	
A0	2010/03/09	NEW	---	x.xxx ± 0.15	APPROVE	DATE	SHEET	1/1	
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	Angle $\pm 3^\circ$			PROJ.	ϕ	

WCON
 Http: www.wcon.com

WCON-Dongguan
 Tel: +86 769 85358920
 Fax: +86 769 85358915
 E-mail: sales@wcon.com

WCON-Kunshan
 Tel: +86 512 57468408
 Fax: +86 512 57468468
 E-mail: salesks@wcon.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:

Click to view products by [Wcon](#) manufacturer:

Other Similar products are found below :

[589158040000018](#) [MDF7C-18P-2.54DSA\(55\)](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [FCN-723J004/1](#) [MIS-048-01-F-D-DP-K](#) [832-10-034-10-001000](#) [FX4C-80S-1.27DSA](#) [93696-330](#) [224393](#) [FCN-235D050-G/C](#) [210-93-314-41-105000](#) [2-22603-0](#) [MDF7-40DP-2.54DSA\(55\)](#) [5031084030](#) [MIT-114-03-F-D-K](#) [55323-1519](#) [45970-4130](#) [YFT-20-05-H-03-SB-K](#) [503308-3040](#) [026-6203-PDB](#) [027-6203-PDB](#) [069159702701000](#) [101A10019X](#) [105061100000861+](#) [55650-0588-C](#) [75140-7012](#) [87471-650](#) [YTW-30-07-H-Q-410-140](#) [YTT-112-01-H-Q](#) [063209](#) [0717420006](#) [FCN-268F024-G0D](#) [10124054-515LF](#) [68685-603](#) [8-1616154-3](#) [MIS-019-01-F-D](#) [YTQ-11201HQ](#) [IL-WX-10PB-HF-B-E1000E](#) [YFT-50-05-H-10-SB-K](#) [FCN-268M024-G/3D](#) [MDF7-16DP-2.54DSA\(55\)](#) [AXE810124](#) [FCN-214J100-G/0](#) [FCN-230C068-E/S](#) [AXE812124](#) [74220-001](#) [354184](#) [P50-028-DDS-TG](#)