

Recommended P.C.B Layout (Top Side)
(PCB BOARD TOLERANCE ± 0.05)

NOTES:

- Current Rating: 5.0AMP
- Contact Resistance: 20mΩ Max
- Insulation Resistance:
- Withstand Voltage: 1000V AC/minute
- Operation Temperature: -25°C to +85°C

Contact Material: Brass
Contact plating: Au Or Sn Over Ni
Insulator Material: PA66 Or PA46

Ordering Information

WF3961-WR HXX W 0 X


H=PA46
Blank=PA66
No. of pins S4=15"/Gold/Tin
02-1SP S5=50"/Gold/Tin
G0=Gold Flash
G3=10u"/Gold
G4=15u"/Gold
G5=30u"/Gold
Blank=Tin

Contact Plating
S0=Gold Flash/Tin
S3=10u"/Gold/Tin
S4=15u"/Gold/Tin
S5=50u"/Gold/Tin

Color
B=Black
W=White

Series No.
1=Type 1
2=Type 2

Packing
0=PE Bag



Specification & Ordering Information:

Circuit	Part No.	Dimension		Q'Ty/ bag
		A	B	
02	WF3961-WR02W0X	3.96	7.92	700
03	WF3961-WR03W0X	7.92	11.88	600
04	WF3961-WR04W0X	11.88	15.84	450
05	WF3961-WR05W0X	15.84	19.80	350
06	WF3961-WR06W0X	19.80	23.76	300
07	WF3961-WR07W0X	23.76	27.72	250
08	WF3961-WR08W0X	27.72	31.68	200
09	WF3961-WR09W0X	31.68	35.64	180
10	WF3961-WR10W0X	35.64	39.60	150
11	WF3961-WR11W0X	39.60	43.56	120
12	WF3961-WR12W0X	43.56	47.52	90
13	WF3961-WR13W0X	47.52	51.48	70
14	WF3961-WR14W0X	51.48	55.44	50
15	WF3961-WR15W0X	55.44	59.40	30

OPERATION	±0.40	DRAW	JYHuang	DATE	2012/09/11	SCALE	FIT
CHECK	±0.25	CHECK		DATE		UNIT	mm
ANGLE	±0.15	APPROVE		DATE		SIZE	A4
DIM	± 3°	PROJ.		SHEET	1/1	CUSTOMER NO.	

PART NO.	SEE TAB
TITLE:	"M"TYPE 3.96 WAFBR 90°



Http: www.wcon.com

WCON-Dongguan
Tel: +86 769 85358920
Fax: +86 769 85358915
E-mail: sales@wcon.com

WCON-Kunshan
Tel: +86 512 57468408
Fax: +86 512 57468468
E-mail: sales@wcon.com

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
AO	2012/09/11	NEW	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Wcon](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)