

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Product image





Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

Version	SAK Series, Feed-through terminal, Rated cross- section: 10 mm ² , Screw connection, beige
Order No.	<u>0110060000</u>
Туре	SAK 10
GTIN (EAN)	4008190027056
Qty.	100 pc(s).

Creation date January 8, 2022 2:57:34 AM CET

Technical data

SAK 10



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Dimensions and weights			
Depth	49 mm	Depth (inches)	1.929 inch
Height	40 mm	Height (inches)	1.575 inch
Width	10 mm	Width (inches)	0.394 inch
Net weight	18.95 g		
Temperatures			
Storage temperature	-25 °C55 °C	Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex- Certificate of Conformity
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	100 °C
Material data			
Material	PA 66	Colour	beige / yellow
UL 94 flammability rating	V-2		
Rating data IECEx/ATEX			
	THEN (4 O ATE) (000 711		
Certificate No. (ATEX)	TUEV18ATEX8207U	Certificate No. (IECEX)	IECEXTUR18.0017U
Max. voltage (ATEX)	550 V	Current (ATEX)	57 A
Wire cross section max. (ATEX)	16 mm ²	Max. voltage (IECEX)	550 V
Current (IECEX)			16 mm²
Operating temperature range For operating temperature range see EC Design Test Certificate / IEC Ex- Certificate of Conformity		Marking EN 60079-7	Ex eb II C Gb
Ex 2014/34/EU label	ll 2 G D		
System specifications			
Version	Course composition	End environmente verovived	
version	Screw connection, for screwable cross- connection, One end	End cover plate required	
	without connector		Yes
Number of potentials	1	Number of levels	1
Number of clamping points per level	2	Number of potentials per tier	1
Levels cross-connected internally	No	PE connection	No
Rail PE function	TS 32 No	N-function PEN function	No No
			NO
Additional technical data			
Explosion-tested version	No	Number of similar terminals	1
Open sides	right	Type of mounting	Snap-on
CSA rating data			
Cartificate No. (CCA)	154695 1501714		GE A
Certificate No. (CSA)	154685-1501714	Current size C (CSA)	65 A
Voltage size C (CSA)	600 V	Wire cross section max. (CSA)	6 AWG
Wire cross section min. (CSA)	14 AWG		

Technical data



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Conductors for clamping (additional connection)

Conductor cross-section, flexible plus plastic collar DIN 46228/1, further connection, max. 10 mm²

Conductors for clamping (rated connection)

Blade size	1.0 x 5.5 mm	Clamping range, max.	16 mm ²
Clamping range, min.	1.5 mm ²	Clamping screw	M 4
Connection cross-section, stranded,		Connection cross-section, stranded, min	ז.
max.	16 mm²		1.5 mm²
Connection direction	on side	Gauge to IEC 60947-1	B6
Number of connections	2	Stripping length	12 mm
Tightening torque, max.	2.64 Nm	Tightening torque, min.	2 Nm
Twin wire-end ferrules, max.	6 mm²	Twin wire-end ferrules, min.	0.75 mm ²
Type of connection		Wire connection cross section AWG,	
	Screw connection	max.	AWG 6
Wire connection cross section AWG,		Wire connection cross section, finely	
min.	AWG 14	stranded, max.	16 mm²
Wire connection cross section, finely stranded, min.		Wire connection cross-section, finely stranded with wire-end ferrules DIN	10
	1.5 mm ²	46228/1, max.	10 mm²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	1.5 mm²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	10 mm²
Wire connection cross-section, finely stranded with wire-end ferrules DIN		Wire connection cross-section, solid core, max.	
46228/4, min.	1.5 mm ²		10 mm²
, ,			
Wire connection cross-section, solid core, min.	1.5 mm²		
Wire connection cross-section, solid	1.5 mm²		
Wire connection cross-section, solid core, min.	1.5 mm ² TS 32	Standards	IEC 60947-7-1
Wire connection cross-section, solid core, min.		Standards Wire connection cross section AWG, min.	IEC 60947-7-1 AWG 14
Wire connection cross-section, solid core, min. General Rail Wire connection cross section AWG,	TS 32	Wire connection cross section AWG,	
Wire connection cross-section, solid core, min. General Rail Wire connection cross section AWG, max. Rating data	TS 32 AWG 6	Wire connection cross section AWG, min.	AWG 14
Wire connection cross-section, solid core, min. General Rail Wire connection cross section AWG, max. Rating data Rated cross-section	TS 32 AWG 6 10 mm ²	Wire connection cross section AWG, min. Rated voltage	AWG 14 800 V
Wire connection cross-section, solid core, min. General Rail Wire connection cross section AWG, max. Rating data Rated cross-section Rated current	TS 32 AWG 6	Wire connection cross section AWG, min. Rated voltage Current at maximum wires	AWG 14
Wire connection cross-section, solid core, min. General Rail Wire connection cross section AWG, max. Rating data Rated cross-section Rated current Standards	TS 32 AWG 6 10 mm ²	Wire connection cross section AWG, min. Rated voltage Current at maximum wires Volume resistance according to IEC 60947-7-x	AWG 14 800 V
Wire connection cross-section, solid core, min. General Rail Wire connection cross section AWG, max. Rating data Rated cross-section Rated current	TS 32 AWG 6 10 mm ² 57 A IEC 60947-7-1	Wire connection cross section AWG, min. Rated voltage Current at maximum wires Volume resistance according to IEC 60947-7-x Power loss in accordance with IEC	AWG 14 800 V 76 A 0.56 mΩ
Wire connection cross-section, solid core, min. General Rail Wire connection cross section AWG, max. Rating data Rated cross-section Rated current Standards Rated impulse withstand voltage	TS 32 AWG 6 10 mm ² 57 A IEC 60947-7-1 8 kV	Wire connection cross section AWG, min. Rated voltage Current at maximum wires Volume resistance according to IEC 60947-7-x	AWG 14 800 V 76 A
Wire connection cross-section, solid core, min. General Rail Wire connection cross section AWG, max. Rating data Rated cross-section Rated current Standards	TS 32 AWG 6 10 mm ² 57 A IEC 60947-7-1	Wire connection cross section AWG, min. Rated voltage Current at maximum wires Volume resistance according to IEC 60947-7-x Power loss in accordance with IEC	AWG 14 800 V 76 A 0.56 mΩ
Wire connection cross-section, solid core, min. General Rail Wire connection cross section AWG, max. Rating data Rated cross-section Rated current Standards Rated impulse withstand voltage	TS 32 AWG 6 10 mm ² 57 A IEC 60947-7-1 8 kV	Wire connection cross section AWG, min. Rated voltage Current at maximum wires Volume resistance according to IEC 60947-7-x Power loss in accordance with IEC	AWG 14 800 V 76 A 0.56 mΩ
Wire connection cross-section, solid core, min. General Rail Wire connection cross section AWG, max. Rating data Rated cross-section Rated current Standards Rated impulse withstand voltage Pollution severity UL rating data	TS 32 AWG 6 10 mm ² 57 A IEC 60947-7-1 8 kV 3	Wire connection cross section AWG, min. Rated voltage Current at maximum wires Volume resistance according to IEC 60947-7-x Power loss in accordance with IEC 60947-7-x	AWG 14 800 V 76 A 0.56 mΩ 1.82 W
Wire connection cross-section, solid core, min. General Rail Wire connection cross section AWG, max. Rating data Rated cross-section Rated current Standards Rated impulse withstand voltage Pollution severity UL rating data Certificate No. (UR)	TS 32 AWG 6 10 mm ² 57 A IEC 60947-7-1 8 kV 3 E60693	Wire connection cross section AWG, min. Rated voltage Current at maximum wires Volume resistance according to IEC 60947-7-x Power loss in accordance with IEC 60947-7-x Conductor size Factory wiring max. (UR	AWG 14 800 V 76 A 0.56 mΩ 1.82 W) 6 AWG
Wire connection cross-section, solid core, min. General Rail Wire connection cross section AWG, max. Rating data Rated cross-section Rated current Standards Rated impulse withstand voltage Pollution severity UL rating data Certificate No. (UR) Conductor size Factory wiring min. (UR	TS 32 AWG 6 10 mm ² 57 A IEC 60947-7-1 8 kV 3 E60693) 14 AWG	Wire connection cross section AWG, min. Rated voltage Current at maximum wires Volume resistance according to IEC 60947-7-x Power loss in accordance with IEC 60947-7-x Conductor size Factory wiring max. (UR Conductor size Field wiring max. (UR)	AWG 14 800 V 76 A 0.56 mΩ 1.82 W) 6 AWG 6 AWG
Wire connection cross-section, solid core, min. General Rail Wire connection cross section AWG, max. Rating data Rated cross-section Rated current Standards Rated impulse withstand voltage Pollution severity UL rating data Certificate No. (UR)	TS 32 AWG 6 10 mm ² 57 A IEC 60947-7-1 8 kV 3 E60693	Wire connection cross section AWG, min. Rated voltage Current at maximum wires Volume resistance according to IEC 60947-7-x Power loss in accordance with IEC 60947-7-x Conductor size Factory wiring max. (UR	AWG 14 800 V 76 A 0.56 mΩ 1.82 W) 6 AWG

Classifications

Technical data



Weidmüller Interface GmbH & Co. KG Klingenbergstraße 26

D-32758 Detmold Germany

www.weidmueller.com

ETIM 6.0	EC000897	ETIM 7.0	EC000897
ETIM 8.0	EC000897	ECLASS 9.0	27-14-11-20
ECLASS 9.1	27-14-11-20	ECLASS 10.0	27-14-11-20
ECLASS 11.0	27-14-11-20		

Approvals

Approvals

ROHS	Conform		
UL File Number Search	E60693		
Downloads			
Approval/Certificate/Document of	Attestation Of Conformity		
Conformity	<u>cfat sak !=</u>		
	<u>CB Certificate</u>		
	CB Test Certificate EAC certificate		
	DNVGL certificate		
	Lloyds Register Certificate		
	MARITREG Certificate		
	EAC EX Certificate		
	IECEx Certificate		
	ATEX Certificate		
	Declaration of Conformity		
	CE Declaration of Conformity all terminals		
Engineering Data	CAD data – STEP		
Engineering Data	EPLAN, WSCAD		
Product Change Notification	20210308 Technical Change SAK PA 32		
User Documentation	StorageConditionsTerminalBlocks NTI SAK 10/32		
Catalogues	Catalogues in PDF-format		

Accessories

Blank

Y	DEFENSION
C	SECONDERED
	CEREBELLE I.
Ľ	STREETERED
Ľ	TTTTTTTTTTTTTT
T	
C	
	TITITITI I.
Ľ	
r	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

	0	
Туре	DEK 5/5 MC NE WS	Version
Order No.	<u>1609801044</u>	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397111	Weidmueller, white
Qty.	1,000 pc(s).	

Plus

T	1	1	L	L	L	1_	L	ļ
h	1	1	Ŀ	Ŀ	1.	Ŀ	1.	ļ
	li		L	Ŀ	Ŀ	Ŀ	1	ļ
F	I.	T.	Ŀ	Ŀ	Ŀ	Ŀ	1	ļ
	1	1	Ŀ	1	Ŀ	1	1	ļ
P	1		Ŀ	Ŀ	h	1		l
P	1	1	Ŀ	h	I.	1	1	I
F	1	1	1	I.	1	1	1	I
P	1		Ľ	1	T	1	1	1
				T	T	1	1	İ

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

	•	
Туре	DEK 5/8 PLUS MC NE WS	Version
Order No.	<u>1046350000</u>	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
GTIN (EAN)	4032248782055	Weidmueller, white
Qty.	800 pc(s).	

Creation date January 8, 2022 2:57:34 AM CET



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

SAK-Series

SAK Series Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

General ordering data

Туре	EW 35	Version
Order No.	0383560000	Accessories, End bracket
GTIN (EAN)	4008190181314	
Qty.	50 pc(s).	

SAK-Series



Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

General	ordering data	
Туре	STA 1/ZA SAK4-10	Version
Order No.	<u>1632450000</u>	SAK Series, Test adapte
GTIN (EAN)	4008190209636	
Qty.	25 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Connection sleeves



General ordering data

Туре	VH 19/5/3.5 SAK4-16	Version
Order No.	0285100000	SAK Series, Connecting sleeve, for cross-connection link, Number of
GTIN (EAN)	4008190189297	poles: 1
Qty.	50 pc(s).	

SAK-Series



A partition plate is used for the optical separation of circuits or used for electrical isolation from neighbouring cross-connectors. In contrast to the end plate, the contour can be larger than the adjacent terminal blocks. However, it should not be smaller, as otherwise the required clearance and creepage distances within the application can no longer be maintained.

General	General ordering data				
Туре	TW SAK4-10 HP/DBR/0.5	Version			
Order No.	<u>0197100000</u>	SAK Series, Partition plate, 0.5 mm, brown, dark beige, Direct			
GTIN (EAN)	4008190146627	mounting			
Qty.	20 pc(s).				
Туре	TW 4 SAK4-10	Version			
Order No.	<u>0130160000</u>	SAK Series, Partition plate, 1.5 mm, beige			
GTIN (EAN)	4008190096335				
Qty.	20 pc(s).				
Туре	TW 4 SAK4-10 BL	Version			
Order No.	<u>0130180000</u>	SAK Series, Partition plate, 1.5 mm, blue			
GTIN (EAN)	4008190114138				
Qty.	20 pc(s).				
Туре	TSCH 1	Version			
Order No.	<u>0319160000</u>	SAK Series, Small partition, beige, 2 mm			
GTIN (EAN)	4008190097219				
Qty.	100 pc(s).				



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Screws



Depending on the terminal block or also accessories, we offer different types of screws as additional items or also spare parts.

General ordering data

Туре	BFSC M3X25	Version
Order No.	0292500000	Accessories, Mounting screw, for cross-connection link
GTIN (EAN)	4008190177027	
Qty.	100 pc(s).	

Blank

	L	L	L	Ŀ	Ľ	L	1
	1	L	Ŀ	Ŀ	L	L	
	1	Γ.	1.	E	E		
	1	1	1	1	E		
	1	1	Γ.	1	E	E	
		1	Γ.,	Ι.,	1.		1
		Ι.		1	1.		
0		1				Ε.	
		1	1	1	1		

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data Type DEK 5/8 MC NE WS Version Order No. 1856740000 Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00 GTIN (EAN) 4032248400850 Weidmueller, white Oty. 800 pc(s). Version



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Q / SAK



Screwable cross-connections are easy to mount and de mount. Thanks to the big contact surface, even high currents can be transmitted with maximum contact reliability.

General	ral ordering data				
Туре	Q 3 SAK10	Version			
Order No.	<u>0457200000</u>	SAK Series, Cross-connector, for cross-connection link, Number of			
GTIN (EAN)	4008190135379	poles: 3			
Qty.	50 pc(s).				
Туре	Q 10 SAK10	Version			
Order No.	<u>0457400000</u>	SAK Series, Cross-connector, for cross-connection link, Number of			
GTIN (EAN)	4008190016166	poles: 10			
Qty.	20 pc(s).				
Туре	Q 4 SAK10	Version			
Order No.	0457300000	SAK Series, Cross-connector, for cross-connection link, Number of			
GTIN (EAN)	4008190129750	poles: 4			
Qty.	50 pc(s).				
Туре	Q 2 SAK10	Version			
Order No.	0457100000	SAK Series, Cross-connector, for cross-connection link, Number of			
GTIN (EAN)	4008190103545	poles: 2			
Qty.	50 pc(s).				



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Custom printing

10000109
1000000
000000
000000
111111111
10000000
100030108
CONTRACTOR .
111111111
Distances and

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/6.5 MC SDR	Version
Order No.	<u>1609850000</u>	Dekafix, Terminal marker, 5 x 6.5 mm, Pitch in mm (P): 6.50
GTIN (EAN)	4008190456610	Weidmueller, To customer specification
Qty.	180 pc(s).	

SAK-Series



Warning covers with a flash symbol provide more safety for man and machine. They are used where external voltage must be indicated within the application.

Туре	AD 4 SAK10	Version
Order No.	<u>0178600000</u>	SAK Series, cover plate, yellow, 25 mm
GTIN (EAN)	4008190068288	
Qty.	50 pc(s).	



Custom printing

1	LL	E	L	Ŀ	L	L	13
E	LL	Ŀ	Ŀ	Ŀ	L	L	1
	T.T.	T.	L	Ŀ	Ŀ	1	1
E	TT	Т	L	L	Ŀ	Ŀ	1
E	TT	Т	L	L	Ŀ	L	3
E	TT	Т	Τ.	Τ.	Ŀ	L	1
E	11	Τ.	L	L	L	T]
	П	T	1	L	T	1	1
E	TT	T		L	L	L	ľ
10		T	T	T	Т	T	1



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/8 MC SDR	Version
Order No.	<u>1856750000</u>	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
GTIN (EAN)	4032248400867	Weidmueller, To customer specification
Qty.	160 pc(s).	
,	1.17	
Туре	DEK 5/8 PLUS MC SDR	Version
	1.17	Version Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
Туре	DEK 5/8 PLUS MC SDR	

SAK-Series



End plates are fitted to the open side of the last modular terminal before the end bracket. The use of an end plate ensures the function of the modular terminal and the specified rated voltage. It guarantees protection against contact with live parts and makes the final terminal finger-proof.

General ordering data			
Туре	AP SAK4-10	Version	
Order No.	<u>0117960000</u>	SAK Series, End plate, 1.5 mm, beige, Direct mounting	
GTIN (EAN)	4008190081485		
Qty.	20 pc(s).		
Туре	AP SAK4-10 I	Version	
Order No.	<u>0117910000</u>	SAK Series, End plate, 1.5 mm, Light Grey, Direct mounting	
GTIN (EAN)	4008190183707		
Qty.	20 pc(s).		

Creation date January 8, 2022 2:57:34 AM CET

Accessories

SAK 10



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Туре AP SAK4-10 DB Version Order No. 0105100000 SAK Series, End plate, 1.5 mm, dark beige, Direct mounting GTIN (EAN) 4008190394875 Qty. 20 pc(s). Туре AP SAK4-10 BL Version Order No. 0117980000 SAK Series, End plate, 1.5 mm, blue, Direct mounting GTIN (EAN) 4008190171087 Qty. 20 pc(s). Туре AP SAK4-10 RT Version Order No. 0117900000 SAK Series, End plate, 1.5 mm, red, Direct mounting GTIN (EAN) 4008190125059 Qty. 20 pc(s).

TS 32



Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

General	ordering data	
Туре	WEW 32/1	Version
Order No.	<u>1067600000</u>	W-Series, End bracket
GTIN (EAN)	4008190099657	
Qty.	50 pc(s).	
Туре	EWK 2	Version
Order No.	<u>0199360000</u>	Accessories, End bracket
GTIN (EAN)	4008190023546	
Qty.	50 pc(s).	
Туре	EWK 1	Version
Order No.	<u>0206160000</u>	Accessories, End bracket
GTIN (EAN)	4008190080020	
Qty.	50 pc(s).	

Accessories

DEK 5/8





Weidmüller Interface GmbH & Co. KG Klingenbergstraße 26

D-32758 Detmold Germany

www.weidmueller.com

WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wearresistant labelling. A print resolution of 300 dpi also produces a very legible script. **Your benefits with MultiMark**

• Firm hold and durable printing

- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

	•	
Туре	DEK 5/8 MM WS	Version
Order No.	<u>2007130000</u>	Dekafix, Terminal marker, 5 x 8 mm, Weidmueller, white
GTIN (EAN)	4050118392012	
Qty.	500 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Custom printing

Г		
ŀ		
r		
h	0000009	
r		
Г	00000000	
Г	00000000	
Г	100000000	
Г		
r		

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/5 MC SDR	Version
Order No.	<u>1609810000</u>	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190456597	Weidmueller, To customer specification
Qty.	200 pc(s).	

SchT group marker carrier



The SchT 5 S group tag carriers are clipped directly onto the TS 32 mounting rail (G-rail) or the TS 35 mounting rail (top-hat rail). It is therefore possible to label the terminal strip irrespective of the terminal and the type of terminal. SchT 5 and SchT 5 S are fitted with ESO 5, STR 5 protective strips.

The SchT 7 is a hinged group tag carrier for inlay tags which enables easy access to the clamping screw. The SchT 7 is fitted with ESO 7, STR 7 protective strips or DEK 5.

Inlay tags and protective strips can be found under "Accessories".

General ordering data

 Type
 SCHT 7
 Version

 Order No.
 0517960000
 SCHT, Terminal marker, 39.3 x 8 mm, Pitch in mm (P): 7.00

 GTIN (EAN)
 4008190001742
 Weidmueller, white

 Oty.
 20 pc(s).
 SCHT

Accessories

SAK 10



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Test plugs Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily. Beneral ordering data Type PS 4 FSTB 4 Version Type PS 4 FSTB 4

TYP	be	PS 4 F.SIB 4	version
Ord	der No.	<u>0299600000</u>	Accessories, Test plug
GT	IN (EAN)	4008190074043	
Qty	<i>ı</i> .	20 pc(s).	

Blank

r	Ľ	I			1	1	1	1	P
ľ		T				1	T.		
						1	T.		
ľ		T			T	1	T		
l					T		T		
ľ									1
Ľ									
Í.									
f									

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	DEK 5/6.5 MC NE WS	Version
Order No.	<u>1609840000</u>	Dekafix, Terminal marker, 5 x 6.5 mm, Pitch in mm (P): 6.50
GTIN (EAN)	4008190203429	Weidmueller, white
Qty.	900 pc(s).	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DIN Rail Terminal Blocks category:

Click to view products by Weidmuller manufacturer:

Other Similar products are found below :

00110420202 8WA1011-1BH23 8WA1011-1EF20 91.010 9102100000 91.040 9123140000 9123140001 RBO 5-T-B-HEX 1333564 DP25-GY-ND 1431306 1433306 HSL-TB64-DIN 90.070 91.020 912314 260-301_NR 2757571 280-331 280-560 280-564 281-611/281-542 281-673/281-411 281-994 283-317 283-607 2909798 264-724 264-726 280-530 280-555 280-619 281-610 281-622/281-417 284-317 284-601 2907033 3048496 5542152 35956 USK 10 102510 1025100000 5520682 5607102 EMH 25-ZE30 591620-2 UM 45-SEFE M.NUT BK 1-591651-1