

Weidmüller Interface GmbH & Co. KG

ZB 16 ZKSC

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Product image







Uninsulated bus bar tap-off terminals offer a space-saving option for connecting conductors on a bus bar.

General ordering data

Accessories, Clamping yoke for busbar, Rated cross-section: Clamping yoke, Feed-through (bushing)
0316600000
ZB 16 ZKSC
4008190145989
50 pc(s).



ZB 16 ZKSC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

-			
1)ım	encione	and	weights

Depth	24 mm	Depth (inches)	0.945 inch
Height	16 mm	Height (inches)	0.63 inch
Width	10 mm	Width (inches)	0.394 inch
Net weight	7.52 a		

Material data

Material	Steel	Colour	silver

Rating data IECEx/ATEX

Certificate No. (ATEX)	DEMKO03ATEX136028U	Certificate No. (IECEX)	IECEXULD13.0005U
Wire cross section max. (ATEX)	16 mm²	Wire cross section max. (IECEX)	16 mm²
Safety notice	Installation instructions: The potential equalisation (PE) rail modules are		

suitable for use in housings in atmospheres with flammable gases and dust. For use in areas with flammable gases, these housings must meet the requirements of EN 60079-0 and EN 60079-7. For use in areas with flammable dust, these housings must meet the requirements of EN 60079-0 and EN 60079-31. When combined with other terminal block ranges and sizes, and when other accessories are used, you must comply with the clearance and creepage distances given. Regarding accessory use, the manufacturer's instructions must be followed. List of restrictions: The PE rail modules are considered one component, with Ex marking when used with the busbar holders of type SH and WEW. When used independently, the

above named components are not covered by this

certificate.

System specifications

Version for busbar 10 x 3 mm

Additional technical data

Installation advice	Feed-through (bushing)	Type of mounting	when screwed in



ZB 16 ZKSC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

CSA rating data

Certificate No. (CSA)	12400-237	Wire cross section max. (CSA)	6 AWG
Wire cross section min. (CSA)	12 AWG		

Conductors for clamping (rated connection)

Clamping range, max.	25 mm ²	Clamping range, min.	2.5 mm ²
Clamping screw		Connection cross-section, stran	ded,
	M 4	max.	25 mm ²
Connection cross-section, strand	ded, min. 16 mm²	Stripping length	16 mm
Tightening torque, min.	2.6 Nm	Type of connection	Clamping yoke
Wire connection cross section, finely		Wire connection cross section,	finely
stranded, max.	16 mm ²	stranded, min.	2.5 mm ²
Wire connection cross-section, s	solid	Wire connection cross-section,	solid
core, max.	16 mm²	core, min.	2.5 mm ²

Dimensions

TS 35 offset	39 mm

General

Installation advice	Feed-through (bushing)
installation advice	reed-through (bushing)

UL rating data

Certificate No. (UR) E60693	Conductor size Factory wiring max. (UR) 4 AWG
Conductor size Factory wiring min. (UR) 12 AWG	Conductor size Field wiring max. (UR) 4 AWG
Conductor size Field wiring min. (UR) 12 AWG	

Classifications

ETIM 6.0	EC002848	ETIM 7.0	EC002848
ETIM 8.0	EC002848	ECLASS 9.0	27-14-11-92
ECLASS 9.1	27-14-11-92	ECLASS 10.0	27-14-11-92
ECLASS 11.0	27-14-11-46		

Approvals

Approvals



ROHS	Conform

Downloads

Approval/Certificate/Document of	Attestation of Conformity
Conformity	ATEX Certificate
	IECEx Certificate
Engineering Data	CAD data – 41549 ZB 16 ZKSC DXF.dxf
	CAD data – STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	<u>StorageConditionsTerminalBlocks</u>
Catalogues	Catalogues in PDF-format
Brochures	

Creation date January 8, 2022 5:48:12 PM CET

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Mounting Fixings category:

Click to view products by Weidmuller manufacturer:

Other Similar products are found below:

5912235-2 007541 627 M3783-7001 71-074914-006 75-69211-3P 75-69214-6P 75-69220-27S 75-69224-5S 7717-8DAP 85047GULPT

85048GBESR FPK-02-R10 PMS27488-001-01 1-18023-0 H-118-2 DB1 1302030464 DC37-22-21PX 1302010957 1302263564

1302340393 1404-0016-78 14540 1561-60 1566 1566 BR16A NT20SATT01 22594-8 KBB-141 89078GBEPR 915060 SF4011-60101

97-CS-50 1671 1855-54 T-2085-SP 20800240002 21899-4 2193 2518 25745-1 H-118-1 354467 37184 4658 4665 4731 BRACKET-RA-30