

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com









The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

Version	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged condition), Bulkhead housing, End- locking clamp, lower side, Standard
Order No.	<u>1213900000</u>
Туре	HDC 24B ALU
GTIN (EAN)	4008190176303
Qty.	1 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions and weights

Height	29.3 mm	Height (inches)	1.154 inch
Width	74.4 mm	Width (inches)	2.929 inch
Mounting dimension - height	32 mm	Mounting dimension - width	130 mm
Net weight	177 g		

Temperatures

Limit temperature -40 °C ... 125 °C

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1, Potassium perfluc	probutane sulfonate 29420-49-3	
Chemical resistance	Substance	Acetone	
	Chemical resistance	Conditionally resistant	
	Substance	Drilling oil	
	Chemical resistance	Resistant	
	Substance	Diesel	
	Chemical resistance	Resistant	
	Substance	Ethyl alcohol	
	Chemical resistance	Resistant	
	Substance	Transmission oil	
	Chemical resistance	Resistant	
	Substance	Hydraulic oil	
	Chemical resistance	Resistant	
	Substance	Coolant	
	Chemical resistance	Resistant	
	Substance	Petroleum benzine	
	Chemical resistance	Resistant	
	Substance	Sweat	
	Chemical resistance	Resistant	
	Substance	Premium gasoline	
	Chemical resistance	Conditionally resistant	
	Substance	Water	
	Chemical resistance	Resistant	
	Substance	UV	
	Chemical resistance	Unstable	
	Substance	Ozone	
	Chemical resistance	Unstable	

Dimensions

Height of base B1	5.3 mm	Height of housing B	29.3 mm
Hole pitch length A2	130 mm	Total length housing	120 mm
Width base C1	47 mm	Width housing C	43 mm

General data

EMC housings	No	Housing main material	diecast aluminium
Material of locking element		Protection degree	IP65 (in plugged
-	Stainless steel, rust-proof	_	condition)
Surface finish	Powder coating		



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Version

BG	8	Clamp version	End-locking clamp
Colour (RAL)	RAL 7035	Cover	without cover
Design	Standard	Design of housing	Bulkhead housing
Design of locking system	End-locking clamp, lower side	Sealing	NBR
Size	8	Suitable for ModuPlug [®]	Yes
Top part/bottom part/lid	lower part	Type	Bulkhead (feed-through)

Classifications

ETIM 6.0	EC000437	ETIM 7.0	EC000437
ETIM 8.0	EC000437	ECLASS 9.0	27-44-02-02
ECLASS 9.1	27-44-02-02	ECLASS 10.0	27-44-02-02
ECLASS 11.0	27-44-02-02		

Important note

Product information When mounting the housings, make sure that the flat gasket is correctly seated.	

Approvals

Approvals CESSUS

ROHS	Conform
UL File Number Search	E92202

Downloads

Approval/Certificate/Document of	
Conformity	Manufacturer's declaration
Engineering Data	CAD data – STEP
Engineering Data	EPLAN, WSCAD
Technical Documentation	1213900000 HDC 24B ALU STP Blatt 1.pdf
Catalogues	Catalogues in PDF-format
Brochures	FL FIELDWIRING EN
	<u>FL FIELDWIRING EN</u>




Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Drawings





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

XXL plug housing, cable entry sideways



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 64D TSLU 1M50G	Version
Order No.	<u>1111150000</u>	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248100118	condition), Cable entry from side, Plug housing, End-locking clamp,
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: M 50

XXL plug housing, cable entry on top



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

Туре	HDC 64D TOLU 1M50G	Version
Order No.	<u>1111170000</u>	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248100125	condition), Cable entry from top, Plug housing, End-locking clamp,
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: M 50



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Hood, Cable Entry sideways



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

Туре	HDC 64D TSLU 1M32G	Version
Order No.	1786810000	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248204052	condition), Cable entry from side, Plug housing, End-locking clamp,
Qty.	1 pc(s).	lower side, high, Size of cable entries: M 32
Type	HDC 24B TSLU 1M25G	Version
Order No.	1787800000	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248205240	condition), Cable entry from side, Plug housing, End-locking clamp,
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: M 25
Type	HDC 64D TSLU 1M40G	Version
Order No.	1804610000	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged
	4032248267538	
GTIN (EAN)		condition), Cable entry from side, Plug housing, End-locking clamp, lower side, high, Size of cable entries: M 40
Qty.	1 pc(s).	
Туре	HDC 64D TSLU 1PG29G	Version
Order No.	<u>1662490000</u>	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190419011	condition), Cable entry from side, Plug housing, End-locking clamp,
Qty.	1 pc(s).	lower side, high, Size of cable entries: PG 29
Туре	HDC 24B TSLU 1PG21G	Version
Order No.	1662390000	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190418915	condition), Cable entry from side, Plug housing, End-locking clamp,
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: PG 21
Туре	HDC 64D TSLU 1PG21G	Version
Order No.	<u>1662470000</u>	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190418991	condition), Cable entry from side, Plug housing, End-locking clamp,
Qty.	1 pc(s).	lower side, high, Size of cable entries: PG 21
Туре	HDC 24B TSLU 1PG29G	Version
Order No.	<u>1662410000</u>	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190418939	condition), Cable entry from side, Plug housing, End-locking clamp,
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: PG 29
Туре	HDC 24B TSLU 1M32G	Version
Order No.	<u>1787790000</u>	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248205233	condition), Cable entry from side, Plug housing, End-locking clamp,
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: M 32



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Hood, Cable Entry at top



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

	Contract of the contract of th					
Туре	HDC 24B TOLU 1M25G	Version				
Order No.	<u>1787860000</u>	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged				
GTIN (EAN)	4032248205301	condition), Cable entry from top, Plug housing, End-locking clamp,				
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: M 25				
Туре	HDC 64D TOLU 1M32G	Version				
Order No.	<u>1786860000</u>	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged				
GTIN (EAN)	4032248204106	condition), Cable entry from top, Plug housing, End-locking clamp,				
Qty.	1 pc(s).	lower side, high, Size of cable entries: M 32				
Туре	HDC 64D TOLU 1PG29G	Version				
Order No.	<u>1662630000</u>	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged				
GTIN (EAN)	4008190419158	condition), Cable entry from top, Plug housing, End-locking clamp,				
Qty.	1 pc(s).	lower side, high, Size of cable entries: PG 29				
Туре	HDC 24B TOLU 1PG29G	Version				
Order No.	<u>1662550000</u>	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged				
GTIN (EAN)	4008190419073	condition), Cable entry from top, Plug housing, End-locking clamp,				
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: PG 29				
Туре	HDC 64D TOLU 1M25G	Version				
Order No.	<u>1786870000</u>	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged				
GTIN (EAN)	4032248204113	condition), Cable entry from top, Plug housing, End-locking clamp,				
Qty.	1 pc(s).	lower side, high, Size of cable entries: M 25				
Туре	HDC 64D TOLU 1PG21G	Version				
Order No.	<u>1662610000</u>	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged				
GTIN (EAN)	4008190419134	condition), Cable entry from top, Plug housing, End-locking clamp,				
Qty.	1 pc(s).	lower side, high, Size of cable entries: PG 21				
Туре	HDC 24B TOLU 1PG21G	Version				
Order No.	1662540000	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged				
GTIN (EAN)	4008190419066	condition), Cable entry from top, Plug housing, End-locking clamp,				
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: PG 21				
Туре	HDC 64D TOLU 1M40G	Version				
Order No.	<u>1983470000</u>	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged				
GTIN (EAN)	4032248687916	condition), Cable entry from top, Plug housing, End-locking clamp,				
Qty.	1 pc(s).	lower side, high, Size of cable entries: M 40				



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Туре	HDC 24B TOLU 1M32G	Version
Order No.	<u>1787850000</u>	HDC enclosures, Size: 8, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248205295	condition), Cable entry from top, Plug housing, End-locking clamp,
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: M 32

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heavy Duty Power Connectors category:

Click to view products by Weidmuller manufacturer:

Other Similar products are found below:

647757-1 6643411-1 6646058-2 6646137-1 6646138-1 6646479-1 6646608-1 6646786-1 6646940-1 6651091-1 6651525-1 6651529-1 6651788-1 696475-1 702-32-01109 703-25-02205 73000005059 73000005642 73080255059 73080965046 765-15-0080A 765-16-0080B 765-18-0080D 829992-1 902-77-02113 PS00/A0620/6300 PS25/A0420/63 129-1J 1409400 AN0024023 E6374G1 e6389g2 157-43GW8 MS3117-14AC 1643543-1 1650540-1 1651811-2 1766260-1 1766282-1 1766966-1 1791340000 NLDFT-3-BL-L-S120-M40A NLDFT-N-W-L-C240-M40B NLS-2-R-C240-M40B NLS-N-W-C240-M40B NPS-3-BL-T6 1986615-1 2-1589900-8 2199314-1 KA8102