

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com









The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Version	HDC enclosures, Size: 1, Protection degree: IP65
	(in plugged condition), Bulkhead housing, Side-
	locking clamp on lower side, Standard
Order No.	<u>1497700000</u>
Туре	HDC 04A AWLU
GTIN (EAN)	4008190074937
Qty.	1 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	25.7 mm	Depth (inches)	1.012 inch
Height	52.8 mm	Height (inches)	2.079 inch
Width	36.5 mm	Width (inches)	1.437 inch
Mounting dimension - width	30 mm	Net weight	38 g

Temperatures

Limit temperature -40 °C ... 125 °C

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1		
Chemical resistance	Substance	Acetone	
	Chemical resistance	Conditionally resistant	
	Substance	Drilling oil	
	Chemical resistance	Resistant	
	Substance	Diesel	
	Chemical resistance	Resistant	
	Substance	Ethyl alcohol	
	Chemical resistance	Resistant	
	Substance	Transmission oil	
	Chemical resistance	Resistant	
	Substance	Hydraulic oil	
	Chemical resistance	Resistant	
	Substance	Coolant	
	Chemical resistance	Resistant	
	Substance	Petroleum benzine	
	Chemical resistance	Resistant	
	Substance	Sweat	
	Chemical resistance	Resistant	
	Substance	Premium gasoline	
	Chemical resistance	Conditionally resistant	
	Substance	Water	
	Chemical resistance	Resistant	
	Substance	UV	
	Chemical resistance	Unstable	
	Substance	Ozone	
	Chemical resistance	Unstable	

Dimensions

Cable entry	angled	Height of base B1	3 mm	
Height of housing B	26.7 mm	Hole pitch length A2	30 mm	
Total length housing	41.5 mm	Width base C1	42 mm	
Width housing C	25.2 mm			

General data

EMC housings	No	Housing main material	diecast aluminium
Material of locking element		Protection degree	IP65 (in plugged
	Stainless steel, rust-proof		condition)
Surface finish	Powder coating	Tightening torque	0.5 Nm



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Version

BG	1	Cable entry	angled
Clamp version	Side-locking clamp	Colour (RAL)	RAL 7035
Design	Standard	Design of housing	Bulkhead housing
Design of locking system	Side-locking clamp on lower side	Sealing	NBR
Size	1	Suitable for ModuPlug [®]	No
Tightening torque	0.5 Nm	Top part/bottom part/lid	lower part
Type	Bulkhead (feed-through)		

Classifications

ETIM 6.0	EC000437	ETIM 7.0	EC000437
ETIM 8.0	EC000437	ECLASS 9.0	27-44-02-02
ECLASS 9.1	27-44-02-02	ECLASS 10.0	27-44-02-02
ECLASS 11.0	27-44-02-02		

Important note

Product information	When mounting the housings, make sure that the flat gasket is correctly seated.

Approvals

Approvals



ROHS Conform

Downloads

Approval/Certificate/Document of	
Conformity	Manufacturer's declaration
Engineering Data	CAD data – STEP
Engineering Data	EPLAN, WSCAD
Technical Documentation	1497700000_HDC_04A_AWLU_STP_Blatt1.pdf
Catalogues	Catalogues in PDF-format
Brochures	<u>FL FIELDWIRING EN</u>
	<u>FL FIELDWIRING EN</u>




Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Drawings





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Cover



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 04A DODL 2BO	Version
Order No.	<u>1665740000</u>	HDC enclosures, Size: 1, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190422769	condition), Cover for lower part of housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, Standard
Туре	HDC 04A DMDL 2BO	Version
Type Order No.	HDC 04A DMDL 2BO 1665750000	Version HDC enclosures, Size: 1, Protection degree: IP65 (in plugged

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heavy Duty Power Connectors category:

Click to view products by Weidmuller manufacturer:

Other Similar products are found below:

647757-1 6643411-1 6646058-2 6646137-1 6646138-1 6646479-1 6646608-1 6646786-1 6646940-1 6651091-1 6651525-1 6651529-1 6651788-1 696475-1 702-32-01109 703-25-02205 73000005059 73000005642 73080255059 73080965046 765-15-0080A 765-16-0080B 765-18-0080D 829992-1 902-77-02113 PS00/A0620/6300 PS25/A0420/63 129-1J 1409400 AN0024023 E6374G1 e6389g2 157-43GW8 MS3117-14AC 1643543-1 1650540-1 1651811-2 1766260-1 1766282-1 1766966-1 1791340000 NLDFT-3-BL-L-S120-M40A NLDFT-N-W-L-C240-M40B NLS-2-R-C240-M40B NLS-N-W-C240-M40B NPS-3-BL-T6 1986615-1 2-1589900-8 2199314-1 KA8102