

Weidmüller Interface GmbH & Co. KG

ZPE 2.5/4AN

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Product image







Spring connection with tension clamp Technology

Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

Version	PE terminal, Tension-clamp connection, 2.5 mm², 300 A (2.5 mm²), Green/yellow
Order No.	<u>1608660000</u>
Туре	ZPE 2.5/4AN
GTIN (EAN)	4008190076290
Qty.	50 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	38.5 mm	Depth (inches)	1.516 inch
Depth including DIN rail	39.5 mm	Height	79.5 mm
Height (inches)	3.13 inch	Width	5.1 mm
Width (inches)	0.201 inch	Net weight	15.2 g
Temperatures			
Storage temperature		Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex-
	-25 °C55 °C		Certificate of Conformity
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	120 °C
Material data			
Material	Wemid	Colour	Green/yellow
UL 94 flammability rating	V-0	Colour	Green/yellow
Rating data IECEx/ATEX			
Certificate No. (ATEX)	DEMKO15ATEX1467U	Certificate No. (IECEX)	IECEXULD15.0008U
Wire cross section max. (ATEX)	4 mm²	Wire cross section max. (IECEX)	4 mm²
Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex-	Marking EN 60079-7	Ex eb II C Gb
	Certificate of Conformity		

Version	Tension-clamp connection, With PE connection, One	End cover plate required	
	end without connector		Yes
Number of levels	1	Number of clamping points per level	4
Levels cross-connected internally	No	PE connection	Yes
Rail	TS 35	PEN function	No

Additional technical data

Explosion-tested version Yes		Installation advice	Direct mounting
Number of similar terminals	1	Open sides	right
Type of mounting	Snap-on		

CSA rating data

Certificate No. (CSA)	200039-1152892	Wire cross section max. (CSA)	12 AWG	
Wire cross section min. (CSA)	26 AWG			



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Conductors for clamping (rated connection)

Blade size	0.6 x 3.5 mm	Clamping range, max.	4 mm ²
Clamping range, min.	0.05 mm ²	Connection direction	top
Gauge to IEC 60947-1	A3	Number of connections	4
Stripping length	10 mm	Type of connection	Tension-clamp connection
Wire connection cross section AWG, max.	AWG 12	Wire connection cross section AWG, min.	AWG 30
Wire connection cross section, finely stranded, max.	4 mm²	Wire connection cross section, finely stranded, min.	0.5 mm ²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	2.5 mm ²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	0.5 mm ²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	2.5 mm ²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min.	0.5 mm ²
Wire connection cross-section, solid core, max.	4 mm²	Wire connection cross-section, solid core, min.	0.5 mm²
General			
Installation advice	Direct mounting	Rail	TS 35
Standards	IEC 60947-7-2	Wire connection cross section AWG, max.	AWG 12
Wire connection cross section AWG, min.	AWG 30		
PE rating data			
Rated short-time current	300 A (2.5 mm²)	PEN function	No
Rating data			
Rated cross-section	2.5 mm ²	Rated voltage to adjoining terminal	800 V
Standards		Volume resistance according to IEC	1.00
	IEC 60947-7-2	60947-7-x	1.33 mΩ
Rated impulse withstand voltage to adjacent terminal	8 kV	Power loss in accordance with IEC 60947-7-x	0.77 W
		Power loss in accordance with IEC	
adjacent terminal	8 kV	Power loss in accordance with IEC	
adjacent terminal Pollution severity UL rating data	8 kV	Power loss in accordance with IEC 60947-7-x	0.77 W
adjacent terminal Pollution severity UL rating data Certificate No. (UR)	8 kV 3 E60693	Power loss in accordance with IEC 60947-7-x Conductor size Factory wiring max. (UR)	0.77 W
adjacent terminal Pollution severity UL rating data	8 kV 3 E60693	Power loss in accordance with IEC 60947-7-x	0.77 W
adjacent terminal Pollution severity UL rating data Certificate No. (UR) Conductor size Factory wiring min. (UR)	8 kV 3 E60693 30 AWG	Power loss in accordance with IEC 60947-7-x Conductor size Factory wiring max. (UR)	0.77 W
adjacent terminal Pollution severity UL rating data Certificate No. (UR) Conductor size Factory wiring min. (UR) Conductor size Field wiring min. (UR) Classifications	8 kV 3 E60693 30 AWG 30 AWG	Power loss in accordance with IEC 60947-7-x Conductor size Factory wiring max. (UR) Conductor size Field wiring max. (UR)	0.77 W 12 AWG 12 AWG
adjacent terminal Pollution severity UL rating data Certificate No. (UR) Conductor size Factory wiring min. (UR) Conductor size Field wiring min. (UR) Classifications ETIM 6.0	8 kV 3 E60693 30 AWG 30 AWG	Power loss in accordance with IEC 60947-7-x Conductor size Factory wiring max. (UR) Conductor size Field wiring max. (UR)	0.77 W 12 AWG 12 AWG EC000901
adjacent terminal Pollution severity UL rating data Certificate No. (UR) Conductor size Factory wiring min. (UR) Conductor size Field wiring min. (UR) Classifications	8 kV 3 E60693 30 AWG 30 AWG	Power loss in accordance with IEC 60947-7-x Conductor size Factory wiring max. (UR) Conductor size Field wiring max. (UR)	0.77 W 12 AWG 12 AWG



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS	Conform
UL File Number Search	E60693

Downloads

20111110000	
Approval/Certificate/Document of	Attestation of Conformity
Conformity	IECEx Certificate
•	CB Test Certificate
	CB Certificate
	EAC certificate
	DNVGL certificate
	INMETRO certificate
	Lloyds Register Certificate
	MARITREG Certificate
	EAC EX Certificate
	CCC Ex Certificate
	ATEX Certificate
	Declaration of Conformity OF Declaration of Conformity and Confor
	CE Declaration of Conformity all terminals
Engineering Data	CAD data – STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
Product Change Notification	Product Change Notification ZPE Q1/2022 DE
	Product Change Notification Q1/2022 EN
User Documentation	<u>StorageConditionsTerminalBlocks</u>
	NTI ZDU/ZPE 2.5/4AN
	BPZL Z-Series
Catalogues	Catalogues in PDF-format
Brochures	




Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Drawings





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

2.5 mm²

2.5

mm²

End plates are fitted to the open side of the last modular terminal before the end bracket. The use of an end plate ensures the function of the modular terminal and the specified rated voltage. It guarantees protection against contact with live parts and makes the final terminal finger-proof.

Gonorai	ordorning data	
Туре	ZAP/TW 3 GR	Version
Order No.	1683870000	Z-series, End plate, Partition plate
GTIN (EAN)	4008190477592	
Qty.	50 pc(s).	
Туре	ZAP/TW 3 WS	Version
Order No.	1683880000	Z-series, End plate, Partition plate
GTIN (EAN)	4008190477608	
Qty.	50 pc(s).	
Туре	ZAP/TW 3 BL	Version
Order No.	<u>1608810000</u>	Z-series, End plate, Partition plate
GTIN (EAN)	4008190190934	
Qty.	50 pc(s).	
Туре	ZAP/TW 3 SW	Version
Order No.	1683890000	Z-series, End plate, Partition plate
GTIN (EAN)	4008190477615	
Qty.	50 pc(s).	
Туре	ZAP/TW 3	Version
Order No.	1608800000	Z-series, Accessories, End plate, Partition plate
GTIN (EAN)	4008190190927	
Qty.	50 pc(s).	
Туре	ZAP/TW 3 GN	Version
Order No.	1683840000	Z-series, End plate, Partition plate
GTIN (EAN)	4008190477561	
Qty.	50 pc(s).	
Туре	ZAP/TW 3 OR	Version
Order No.	1608820000	Z-series, End plate, Partition plate
GTIN (EAN)	4008190190941	
Qty.	50 pc(s).	
Туре	ZAP/TW 3 RT	Version
Order No.	1683820000	Z-series, End plate, Partition plate
GTIN (EAN)	4008190477547	
Qty.	50 pc(s).	




Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Blank



ZS markers - in proven MultiCard-format - have been developed specifically for the Z-series. They have a large printing area. The hinged mechanism even allows access to cross-connectors without dismantling. Quick installation is guaranteed by the fact that the single tags are clipped on in strips. The single tags are easy to separate.

- Hinged marker area
- · Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	ZS 12/6 MC NE WS	Version
Order No.	<u>1610020000</u>	ZS, Terminal marker, 12 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,
GTIN (EAN)	4008190444600	Allen-Bradley, white
Qty.	400 pc(s).	

ZGB pivotable group tag holder



The ZGB 15 is a hinged group tag carrier. The tag carrier can hold the dekafix 5, WS 12/5 terminal markers or the inlay tag ESO 15.

The ZGB 30 is a hinged group tag carrier. The tag carrier can hold the dekafix 5, WS 12/5 terminal markers or the inlay tag ESO 7.

Inlay tags and protective strips can be found under "Accessories".

Туре	ZGB 30	Version
Order No.	<u>1611930000</u>	Terminal markers, Terminal marker, 32 x 7 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190002251	Weidmueller, white
Qty.	20 pc(s).	
Туре	ZGB 15	Version
Order No.	<u>1636530000</u>	Terminal markers, Terminal marker, 15 x 7 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190297053	Weidmueller, white
Qty.	20 pc(s).	
Туре	ZGB 30/3.5	Version
Order No.	<u>1778290000</u>	Terminal markers, Terminal marker, 32 x 7 mm, Pitch in mm (P): 3.50
GTIN (EAN)	4032248161065	white
Qty.	20 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Test plugs



Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

General ordering data

Type PS 2.3 RT
Order No. 0180400000
GTIN (EAN) 4008190060121
Oty. 20 pc(s).

Version

Accessories, Test plug

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

1,000 pc(s).

Qty.

 Type
 DEK 5/5 MC NE WS
 Version

 Order No.
 1609801044
 Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00

 GTIN (EAN)
 4008190397111
 Weidmueller, white



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Z-Series

Z Series The use of reducing sleeves simplifies the connection of conductors with smaller cross-sections. Conductors can be reliably inserted into the clamping point without the strands fraying. The use of a reducing sleeve centres the conductor in the entry point.

General ordering data

Туре	ZRH 2.5/1 WS	Version
Order No.	<u>1614300000</u>	Z-series, Reducing sleeve
GTIN (EAN)	4008190206789	
Qty.	1,000 pc(s).	
Туре	ZRH 2.5/2 GR/V0	Version
Order No.	<u>1614290000</u>	Z-series, Reducing sleeve
GTIN (EAN)	4008190072476	
Qty.	1,000 pc(s).	
Туре	ZRH 2.5/3	Version
Order No.	<u>1614280000</u>	Z-series, Reducing sleeve
GTIN (EAN)	4008190206796	
Qty.	1,000 pc(s).	

Z-Series



Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

Туре	ZTA 1/ZA	Version
Order No.	1609050000	Accessories, Test adapter, 9 A
GTIN (EAN)	4008190206543	
Qty.	25 pc(s).	
Туре	ZTA 1	Version
Type Order No.	ZTA 1 1609040000	Version Accessories, Test adapter, 9 A



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Blank



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with PrintJet CONNECT oder/or Plotter is possible.

- Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	WS 10/5 M MC NE WS	Version
Order No.	<u>1792000000</u>	WS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4032248223862	Allen-Bradley, white
Qty.	720 pc(s).	
Туре	WS 10/5 MC NE WS	Version
Type Order No.	WS 10/5 MC NE WS 1635000000	Version WS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
	· ·	

SAK-Series



Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

Туре	EW 35	Version
Order No.	0383560000	Accessories, End bracket
GTIN (EAN)	4008190181314	
Qty.	50 pc(s).	
Туре	EW 35 GR 7032	Version
Type Order No.	EW 35 GR 7032 0383530000	Version Accessories, End bracket



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Type EW 35/SCHA/M3 Order No. 0258660000 GTIN (EAN)


4008190033477

20 pc(s).

Version

Accessories, End bracket

Blank



ZS markers - in proven MultiCard-format - have been developed specifically for the Z-series. They have a large printing area. The hinged mechanism even allows access to cross-connectors without dismantling. Quick installation is guaranteed by the fact that the single tags are clipped on in strips. The single tags are easy to separate.

- Hinged marker area
- · Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

ZS 10/5 MC NE WS Туре Order No. 1610000000

4008190263171

480 pc(s).

Version

ZS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,

Allen-Bradley, white

Z-Series

GTIN (EAN)

Qty.



Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

General ordering data

7FW 35/2 Type Version Order No. 8630740000 Z-series, End bracket GTIN (EAN) 4032248348916 Qty. 20 pc(s). Туре ZEW 35 Version

Order No. 9540000000 GTIN (EAN) 4008190956264

20 pc(s). Qty.

Z-series, End bracket



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Slotted screwdriver



VDE insulated screwdriver sets, for working on live parts up to 1000 V AC and 1500 V DC, DIN EN 60900. IEC 900. Each piece is "GS" safety tested. Blade made from fully hardened, high-alloy chromium-vanadium-molybdenum steel, gun-metal finish.

General ordering data

Type SDIS SLIM 0.6X3.5X100 Order No. 2749610000

GTIN (EAN) 4050118896350


Qty. 1 pc(s).

Version

Mounting tool, Blade width (B): 3.5 mm, Blade length: 100 mm, Blade

thickness (A): 0.6 mm

Blank



ZS markers - in proven MultiCard-format - have been developed specifically for the Z-series. They have a large printing area. The hinged mechanism even allows access to cross-connectors without dismantling. Quick installation is guaranteed by the fact that the single tags are clipped on in strips. The single tags are easy to separate.

- Hinged marker area
- · Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type ZS 15/5 MC NE WS

Order No. 1646630000

GTIN (EAN) 4008190401214

Qty. 480 pc(s).

Version

ZS, Terminal marker, 15 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,

Allen-Bradley, white



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

W-Series



Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

General ordering data

Туре	WEW 35/2	Version
Order No.	<u>1061200000</u>	W-Series, End bracket
GTIN (EAN)	4008190030230	
Qty.	50 pc(s).	
Туре	WEW 35/1	Version
Type Order No.	WEW 35/1 1059000000	Version W-Series, End bracket
	,	
Order No.	1059000000	

STR transparent strips



Туре	STR 7 F.SCHT 7	Version
Order No.	<u>0515300000</u>	Terminal markers, Protective cap, 27 x 6.3 mm, Transparent
GTIN (EAN)	4008190182175	
Qty.	20 pc(s).	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Terminal Block Tools & Accessories category:

Click to view products by Weidmuller manufacturer:

Other Similar products are found below:

00171430102 00171420102 600HL 600RJ-07 600RJ-11 600RJ-14 600RJS-10 600RJS-12 600RJS-15 600RJS-21 601RJ-09 602SP 602Z 604J CSTSPC1-2 7B941-7 88943-2100 QC102 1437403-6 1437403-9 1437403-8 1453128-1 147832-1 EC0037-000 MT2/H-- MT6/H-N MT6/V-GRND BC2-12 BCC-1-8/10 EP2.5/4UN/BG 1707755 1735590 1755480 1789281 1840227 1840230 2-1437402-1 JA2-03 JB1-03/J JB2-04 JB2-05 JB2-07 JB2-09/J PARALLELJUMPERLINK JS601 2204082 2302463 2305949 8PCV-BUSHING 8TK2-24