

ZQV 1.5N/R3.5/4 GE**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image

Screwable cross-connections are easy to mount and de mount. Thanks to the big contact surface, even high currents can be transmitted with maximum contact reliability.

General ordering data

Version	Accessories, Cross-connector, 17.5 A
Order No.	1754230000
Type	ZQV 1.5N/R3.5/4 GE
GTIN (EAN)	4032248103874
Qty.	20 pc(s).

Creation date September 16, 2022 10:48:57 AM CEST

Catalogue status 09.09.2022 / We reserve the right to make technical changes.

ZQV 1.5N/R3.5/4 GE**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	12.15 mm	Depth (inches)	0.478 inch
Height	13.1 mm	Height (inches)	0.516 inch
Width	2.4 mm	Width (inches)	0.094 inch
Net weight	1.19 g		

Temperatures

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-50
Continuous operating temp., max.	120		

Material data

Material	Wemid	Colour	yellow
UL 94 flammability rating	V-0		

System specifications

Version	For the terminals
---------	-------------------

Additional technical data

Explosion-tested version	Yes	Installation advice	Direct mounting
Type of fixing	Plugged		

Cross-connector

Number of cross-connected terminals	4	Rated current, multi-pole	17.5 A
Type	Cross-connector		

Dimensions

Pitch in mm (P)	3.5 mm
-----------------	--------

General

Installation advice	Direct mounting	Number of poles	4
---------------------	-----------------	-----------------	---

Rating data

Rated current	17.5 A
---------------	--------

Classifications

ETIM 6.0	EC000489	ETIM 7.0	EC000489
ETIM 8.0	EC000489	ECLASS 9.0	27-14-11-40
ECLASS 9.1	27-14-11-40	ECLASS 10.0	27-14-11-40
ECLASS 11.0	27-14-11-40	ECLASS 12.0	27-14-11-40

Important note

Product information	Due to stability and temperature reasons It is only possible to break out 60% of contact elements The usage of cross connectors reduces the rated voltage to 400VThe voltage reduced to 25V if cut cross connection with blank cut edges are used
---------------------	---

Data sheet

ZQV 1.5N/R3.5/4 GE

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity	EAC certificate
Engineering Data	CAD data – STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	StorageConditionsTerminalBlocks BPZL ZQV 2.5
Catalogues	Catalogues in PDF-format

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Terminal Blocks - Unspecified](#) category:

Click to view products by [Weidmuller](#) manufacturer:

Other Similar products are found below :

[262-103](#) [5606874](#) [2108470000](#) [BM5219](#) [1SNL312510R0000](#) [1SNL316010R0000](#) [5310100000024](#) [5310100000014](#) [LZW-B4.2 A12-4160](#)
[LZW-B4.6 A12-4660](#) [FCR7900](#) [FCR79001](#) [88486403](#) [ESKW 1/5 ST E3](#) [88486708](#) [ESKW 1/5 KU](#) [88838208](#) [ESKW 1/2 KU](#) [88838304](#)
[ESKW 1/2 ST](#) [PDBFS377](#) [260-112](#) [264-364](#) [1527880000](#) [1528230000](#) [LZW-B4.3 A12-4260](#) [294-4013](#) [HDFK 25 0707743](#) [E.4203](#) [TSCB4-](#)
[02P-15-01AH](#) [862-505](#) [TSCB4-01P-15-01AH](#) [TSCB4-03P-15-01AH](#) [5310100000002](#) [5310100000005](#) [5310100000007](#) [5310100000012](#)
[5310100000026](#) [5310200000004](#) [5310200000016](#) [1754220000](#) [294-4002](#) [E.4204](#) [SLK3/2/D1-D2](#) [88167524](#) [262-142](#) [264-112](#) [294-4003](#)
[FCR7901](#) [FCR79011](#) [PDBFS220](#) [PDBFS330](#) [BM22](#) [BM23](#) [BM2300](#)