

**ZQV 1.5N/R3.5/5 GE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image**

Screwable cross-connections are easy to mount and de mount. Thanks to the big contact surface, even high currents can be transmitted with maximum contact reliability.

**General ordering data**

Version	Accessories, Cross-connector, 17.5 A
Order No.	<a href="#">1754240000</a>
Type	ZQV 1.5N/R3.5/5 GE
GTIN (EAN)	4032248109647
Qty.	20 pc(s).

Creation date September 16, 2022 10:22:45 AM CEST

Catalogue status 09.09.2022 / We reserve the right to make technical changes.

## ZQV 1.5N/R3.5/5 GE

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

### Dimensions and weights

Depth	12.15 mm	Depth (inches)	0.478 inch
Height	16.6 mm	Height (inches)	0.654 inch
Width	2.4 mm	Width (inches)	0.094 inch
Net weight	1.27 g		

### Temperatures

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-50
Continuous operating temp., max.	120		

### Material data

Material	Wemid	Colour	yellow
UL 94 flammability rating	V-0		

### System specifications

Version	For the terminals
---------	-------------------

### Additional technical data

Explosion-tested version	Yes	Installation advice	Direct mounting
Type of fixing	Plugged		

### Cross-connector

Number of cross-connected terminals	5	Rated current, multi-pole	17.5 A
Type	Cross-connector		

### Dimensions

Pitch in mm (P)	3.5 mm
-----------------	--------

### General

Installation advice	Direct mounting	Number of poles	5
---------------------	-----------------	-----------------	---

### Rating data

Rated current	17.5 A
---------------	--------

### Classifications

ETIM 6.0	EC000489	ETIM 7.0	EC000489
ETIM 8.0	EC000489	ECLASS 9.0	27-14-11-40
ECLASS 9.1	27-14-11-40	ECLASS 10.0	27-14-11-40
ECLASS 11.0	27-14-11-40	ECLASS 12.0	27-14-11-40

### Important note

Product information	Due to stability and temperature reasons It is only possible to break out 60% of contact elements The usage of cross connectors reduces the rated voltage to 400VThe voltage reduced to 25V if cut cross connection with blank cut edges are used
---------------------	---

## ZQV 1.5N/R3.5/5 GE

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

# Technical data

## Approvals

Approvals



ROHS

Conform

## Downloads

Approval/Certificate/Document of  
Conformity

[EAC certificate](#)

Engineering Data

[CAD data – STEP](#)

Engineering Data

[EPLAN, WSCAD, Zuken E3.S](#)

User Documentation

[StorageConditionsTerminalBlocks](#)  
[BPZL ZQV 2.5](#)

Catalogues

[Catalogues in PDF-format](#)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Terminal Blocks - Unspecified](#) category:*

*Click to view products by [Weidmuller](#) manufacturer:*

Other Similar products are found below :

[262-103](#) [5606874](#) [BM5219](#) [1SNL312510R0000](#) [1SNL316010R0000](#) [5310100000024](#) [5310100000014](#) [LZW-B4.2](#) [A12-4160](#) [LZW-B4.6](#)  
[A12-4660](#) [FCR7900](#) [FCR79001](#) [88486403](#) [ESKW 1/5 ST E3](#) [88486708](#) [ESKW 1/5 KU](#) [88838208](#) [ESKW 1/2 KU](#) [88838304](#) [ESKW 1/2 ST](#)  
[PDBFS377](#) [260-112](#) [264-364](#) [1527880000](#) [1528230000](#) [LZW-B4.3](#) [A12-4260](#) [294-4013](#) [HDFK 25 0707743](#) [HDFK 4 0707086](#) [E.4203](#)  
[TSCB4-02P-15-01AH](#) [862-505](#) [TSCB4-01P-15-01AH](#) [TSCB4-03P-15-01AH](#) [5310100000002](#) [5310100000005](#) [5310100000012](#)  
[5310100000026](#) [5310200000004](#) [5310200000016](#) [1754220000](#) [294-4002](#) [SLK3/2/D1-D2 88167524](#) [262-142](#) [264-112](#) [294-4003](#) [FCR7901](#)  
[FCR79011](#) [PDBFS220](#) [PDBFS330](#) [BM22](#) [BM23](#) [BM2300](#) [BM2301](#) [BM2302](#)