

**ZQV 1.5/5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image**

The plug-in cross-connections feature easy handling and quick installation. This saves a great deal of time during installation in comparison with screwed solutions.

**General ordering data**

Version	Accessories, Cross-connector, 17.5 A
Order No.	<a href="#">1776 150000</a>
Type	ZQV 1.5/5
GTIN (EAN)	4032248236336
Qty.	20 pc(s).

**ZQV 1.5/5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Depth	24.8 mm	Depth (inches)	0.976 inch
Height	16.5 mm	Height (inches)	0.65 inch
Width	2.8 mm	Width (inches)	0.11 inch
Net weight	2.284 g		

**Temperatures**

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-60
Continuous operating temp., max.	130		

**Material data**

Material	Wemid	Colour	yellow
UL 94 flammability rating	V-0		

**System specifications**

Version	For the terminals
---------	-------------------

**Additional technical data**

Explosion-tested version	Yes	Installation advice	Direct mounting
Type of fixing	Plugged		

**Cross-connector**

Number of cross-connected terminals	5	Rated current, 2-pole	17.5 A
Rated current, multi-pole	17.5 A	Type	Cross-connector

**Dimensions**

Pitch in mm (P)	3.5 mm
-----------------	--------

**General**

Installation advice	Direct mounting	Number of poles	5
---------------------	-----------------	-----------------	---

**Rating data**

Rated current	17.5 A
---------------	--------

**Classifications**

ETIM 6.0	EC000489	ETIM 7.0	EC000489
ETIM 8.0	EC000489	ECLASS 9.0	27-14-11-40
ECLASS 9.1	27-14-11-40	ECLASS 10.0	27-14-11-40
ECLASS 11.0	27-14-11-40	ECLASS 12.0	27-14-11-40

**Important note**

Product information	Due to stability and temperature reasons It is only possible to break out 60% of contact elements The usage of cross connectors reduces the rated voltage to 400VThe voltage reduced to 25V if cut cross connection with blank cut edges are used
---------------------	---

## ZQV 1.5/5

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Approvals

Approvals



ROHS

Conform

### Downloads

Approval/Certificate/Document of  
Conformity

[EAC certificate](#)

Engineering Data

[CAD data – STEP](#)

Engineering Data

[EPLAN, WSCAD, Zuken E3.S](#)

User Documentation

[Operating instructions\\_ZDU1.5-ZDU35\\_ZQV.pdf](#)  
[StorageConditionsTerminalBlocks](#)  
[BPZL ZQV 2.5](#)

Catalogues

[Catalogues in PDF-format](#)

Brochures

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Terminal Blocks - Unspecified](#) category:*

*Click to view products by [Weidmuller](#) manufacturer:*

Other Similar products are found below :

[262-103](#) [5606874](#) [2108470000](#) [BM5219](#) [1SNL312510R0000](#) [1SNL316010R0000](#) [5310100000024](#) [5310100000014](#) [LZW-B4.2 A12-4160](#)  
[LZW-B4.6 A12-4660](#) [FCR7900](#) [FCR79001](#) [88486403](#) [ESKW 1/5 ST E3](#) [88486708](#) [ESKW 1/5 KU](#) [88838208](#) [ESKW 1/2 KU](#) [88838304](#)  
[ESKW 1/2 ST](#) [PDBFS377](#) [260-112](#) [264-364](#) [1527880000](#) [1528230000](#) [LZW-B4.3 A12-4260](#) [294-4013](#) [HDFK 25 0707743](#) [E.4203](#) [TSCB4-](#)  
[02P-15-01AH](#) [862-505](#) [TSCB4-01P-15-01AH](#) [TSCB4-03P-15-01AH](#) [5310100000002](#) [5310100000005](#) [5310100000007](#) [5310100000012](#)  
[5310100000026](#) [5310200000004](#) [5310200000016](#) [1754220000](#) [294-4002](#) [E.4204](#) [SLK3/2/D1-D2](#) [88167524](#) [262-142](#) [264-112](#) [294-4003](#)  
[FCR7901](#) [FCR79011](#) [PDBFS220](#) [PDBFS330](#) [BM22](#) [BM23](#) [BM2300](#)