

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Product image







Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

Туре	A4C 4
Order No.	<u>2051500000</u>
Version	Feed-through terminal, PUSH IN, $4\ mm^2$, $800\ V$, $32\ A$, dark beige
GTIN (EAN)	4050118411621
Qty.	50 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Dimensions and weights

Width	6.1 mm	Width (inches)	0.24 inch
Height	87.5 mm	Height (inches)	3.445 inch
Depth	39.5 mm	Depth (inches)	1.555 inch
Depth including DIN rail	40.5 mm	Net weight	15.06 g

Temperatures

Storage temperature, max.	40 °C	Storage temperature, min.	10 °C
Storage temperature	10 °C40 °C	Continuous operating temp., min.	-60 °C
Continuous operating temp max	130 °C		

Material data

Material	Wemid	Colour	dark beige
Colour of operational elements	orange	UL 94 flammability rating	V-0

Rating data IECEx/ATEX

Certificate No. (ATEX)	TUEV16ATEX7909U	Certificate No. (IECEX)	IECEXTUR16.0036U
Max. voltage (ATEX)	550 V	Current (ATEX)	30 A
Wire cross section max. (ATEX)	4 mm ²	Max. voltage (IECEX)	550 V
Current (IECEX)	30 A	Wire cross section max. (IECEX)	4 mm ²
Marking EN 60079-7	Ex eb II C Gb	Ex 2014/34/EU label	II 2 G D

System specifications

End cover plate required	Yes	Number of potentials	1
Number of levels	1	Number of clamping points per level	4
Number of potentials per tier	1	PE connection	No
Rail	TS 35	N-function	No
PE function	No	PEN function	No

Additional technical data

Installation advice	Rail	Open sides	right
Snap-on	No	Type of fixing	Snap-on
Type of mounting	TS 35	With snap-in pegs	No

CSA rating data

Certificate No. (CSA)	200039-70089609	Current size B (CSA)	30 A
Current size C (CSA)	30 A	Current size D (CSA)	5 A
Voltage size B (CSA)	600 V	Voltage size C (CSA)	600 V
Voltage size D (CSA)	600 V	Wire cross section max. (CSA)	10 AWG
Wire cross section min. (CSA)	26 AWG		



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Conductors for clamping (rated connection)

Blade size	0.6 x 3.5 mm	Clamping range, max.	4 mm ²
Clamping range, min.		Connection cross-section, stranded,	
	0.5 mm ²	max.	4 mm ²
Connection cross-section, stranded, m	in. 0.5 mm²	Connection direction	top
Gauge to IEC 60947-1	A4	Number of connections	4
Stripping length	12 mm	Twin wire-end ferrules, max.	1.5 mm ²
Twin wire-end ferrules, min.	0.5 mm ²	Type of connection	PUSH IN
Wire connection cross section AWG,		Wire connection cross section AWG,	
max.	AWG 12	min.	AWG 26
Wire connection cross section, finely stranded, max.	4 mm²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	4 mm²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	0.5 mm²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	4 mm²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min.	0.5 mm²	Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire connection cross-section, solid		Wire connection cross-section, solid	
core, max.	4 mm ²	core, min.	0.5 mm ²
Rated current Standards	32 A	Current at maximum wires Volume resistance according to IEC	32 A
Standards		Volume resistance according to IEC	
	IEC 60947-7-1	60947-7-x	1 mΩ
Power loss in accordance with IEC 60947-7-x	1.02 W	Rated impulse withstand voltage	8 kV
Pollution severity	3	Surge voltage category	III
UL rating data			
Certificate No. (cURus)	E60693	Conductor size Factory wiring max. (cURus)	10 AWG
Conductor size Factory wiring min. (cURus)	28 AWG	Conductor size Field wiring max. (cURu	ıs) 10 AWG
Conductor size Field wiring min. (cURu	is) 28 AWG	Current size B (cURus)	30 A
Current size C (cURus)	30 A	Current size D (cURus)	5 A
Voltage size B (cURus)	600 V	Voltage size C (cURus)	600 V
Voltage size D (cURus)	600 V		
Voltage size D (cURus) Classifications	600 V		
Classifications		ETIM 7.0	5000007
Classifications ETIM 6.0	EC000897	ETIM 7.0	EC000897
Classifications		ETIM 7.0 eClass 9.1	EC000897 27-14-11-20



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Approvals

Approvals



ATEX

ROHS	Conform
Downloads	
Approval/Certificate/Document of	Attestation of Conformity
Conformity	ATEX Certificate
	IECEx Certificate
	CB Test Certificate
	<u>CB Certificate</u>
	DE_PT0101_20160614_065_ISSUE01.pdf
Brochure/Catalogue	<u>CAT 1 TERM 16/17 EN</u>
Engineering Data	EPLAN, WSCAD, Zuken E3.S
Engineering Data	<u>STEP</u>
Tender specification	Klippon® Connect 2051500000 DE
	Klippon® Connect 2051500000 EN
User Documentation	NTI_A4C 4.pdf
	<u>StorageConditionsTerminalBlocks</u>
	Aderendhülsen für die Klippon® Connect A-Reihe
	Wire end ferrules for Klippon® Connect A-series
Safety note	
Safety notice	Safety Information




Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Drawings





Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Test adapter



Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

General ordering data

Туре	ATPG 4 MI-R
Order No.	<u>1991860000</u>
GTIN (EAN)	4050118376661
Qty.	50 pc(s).
Туре	ATPG 1.5-10 L
Type Order No.	ATPG 1.5-10 L 1991890000
•	

DEK 5/6



WS/ DEK

MultiMark DEK/WS connector markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- · Firm hold and durable printing
- · Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

Туре	DEK 5/6 MM WS	Version
Order No.	2007120000	Dekafix, Terminal marker, 5 x 6 mm, Weidmueller, white
GTIN (EAN)	4050118392104	
Qty.	600 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Covers



Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

General ordering data

Туре AAM 4 YE FLASH Order No. 2635560000 GTIN (EAN) 4050118674507 Qty. 40 pc(s).

Terminal marker, 10 x 6.1 mm, yellow

Custom printing



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Zseries. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or MC-Mobilo is possible.

- Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	WS 10/6 MC SDR	Version
Order No.	1828460000	WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,
GTIN (EAN)	4032248367399	Allen-Bradley, To customer specification
Qty.	120 pc(s).	
Туре	WS 10/6 MC M SDR	Version
Order No.	1818410000	WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,
GTIN (EAN)	4032248310883	Allen-Bradley, To customer specification
Qty.	120 pc(s).	
Туре	WS 10/6 M PLUS MC SDR	Version
Order No.	2007780000	WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,
GTIN (EAN)	4050118393187	Allen-Bradley, To customer specification
Qty.	120 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Type WS 10/6 PLUS MC SDR
Order No. 1046330000
GTIN (EAN) 4032248782031
Oty. 120 pc(s).

Version

WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,

Allen-Bradley, To customer specification

ZQV 4N



Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

Туре	ZQV 4N/9 BL
Order No.	<u>1528220000</u>
GTIN (EAN)	4050118333107
Qty.	20 pc(s).
Туре	ZOV 4N/10 BL
Order No.	<u>1528230000</u>
GTIN (EAN)	4050118333138
Qty.	20 pc(s).
Туре	ZOV 4N/50 BL
Order No.	<u>1528240000</u>
GTIN (EAN)	4050118333121
Qty.	5 pc(s).
Туре	ZQV 4N/8 BL
Order No.	<u>1528190000</u>
GTIN (EAN)	4050118332858
Qty.	20 pc(s).
Туре	ZQV 4N/3
Order No.	<u>1527940000</u>
GTIN (EAN)	4050118332865
Qty.	60 pc(s).
Туре	ZQV 4N/6 BL
Order No.	<u>1528170000</u>
GTIN (EAN)	4050118332926
Qty.	20 pc(s).
Туре	ZOV 4N/10
Order No.	<u>1528090000</u>
GTIN (EAN)	4050118332896
Qty.	20 pc(s).
Туре	ZOV 4N/5
Order No.	<u>1527980000</u>
GTIN (EAN)	4050118332759
Qty.	60 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Туре	ZQV 4N/7 BL
Order No.	<u>1528180000</u>
GTIN (EAN)	4050118333114
Qty.	20 pc(s).
Туре	ZOV 4N/7
Order No.	<u>1528020000</u>
GTIN (EAN)	4050118332780
Qty.	20 pc(s).
Туре	ZQV 4N/8
Order No.	<u>1528030000</u>
GTIN (EAN)	4050118332841
Qty.	20 pc(s).
Туре	ZQV 4N/4
Order No.	
GTIN (EAN)	4050118332889
Qty.	60 pc(s).
Туре	ZQV 4N/6
Order No.	1527990000
GTIN (EAN)	4050118332919
Qty.	20 pc(s).
Type	ZQV 4N/50 1528130000
Order No.	
GTIN (EAN)	4050118332902
Qty.	5 pc(s).
Туре	ZOV 4N/4 BL
Order No.	<u>1528120000</u>
GTIN (EAN)	4050118332872
Qty.	60 pc(s).
Туре	ZOV 4N/9
Order No.	<u>1528070000</u>
GTIN (EAN)	4050118332797
Qty.	20 pc(s).
Туре	ZQV 4N/2
Order No.	<u>1527930000</u>
GTIN (EAN)	4050118332766
Qty.	60 pc(s).
Туре	ZOV 4N/2 BL
Order No.	<u>1528040000</u>
GTIN (EAN)	4050118332773
Qty.	60 pc(s).
Туре	ZQV 4N/5 BL
Order No.	<u>1528140000</u>
GTIN (EAN)	4050118333015
Qty.	60 pc(s).
Туре	ZQV 4N/3 BL
Order No.	<u>1528080000</u>
GTIN (EAN)	4050118333008
Qty.	60 pc(s).
1.	• • • •



Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Plus



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type DEK 5/6 PLUS MC NE WS Version
Order No. 1011320000 Dekafix

1011320000 Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

GTIN (EAN) 4032248717644 Weidmueller, white

Qty. 1,000 pc(s).

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

1,000 pc(s).

Type DEK 5/6 MC NE GN Version

Order No. 1238310000 Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

GTIN (EAN) 4050118271812 Weidmueller, green

Creation date January 7, 2020 2:57:27 PM CET



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Туре	DEK 5/6 MC NE GE	Version
Order No.	1238280000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4050118038750	
` '		Weidmueller, yellow
Qty.	1,000 pc(s).	
Туре	DEK 5/6 MC NE OR	Version
Order No.	<u>1912090000</u>	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4032248540525	Weidmueller, orange
Qty.	1,000 pc(s).	
Туре	DEK 5/6 MC NE BR	Version
Order No.	1454900000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4050118323313	Weidmueller, brown
Qty.	1,000 pc(s).	
Туре	DEK 5/6 MC NE GR	Version
Order No.	1238330000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4050118323306	Weidmueller, grey
Qty.	1,000 pc(s).	
Туре	DEK 5/6 MC NE WS	Version
Order No.	1609820000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4008190203436	Weidmueller, white
Qty.	1,000 pc(s).	
Туре	DEK 5/6 MC NE BL	Version
Order No.	1238290000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4050118267327	Weidmueller, blue
Qty.	1,000 pc(s).	

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	DEK 5/6 MC SDR	Version
Order No.	<u>1609830000</u>	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4008190456603	Weidmueller, To customer specification
Qty.	200 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Type DEK 5/6 PLUS MC SDR
Order No. 1038650000
GTIN (EAN) 4032248767908
Oty. 200 pc(s).

Version

Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

Weidmueller, To customer specification

End plates



Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

Туре	AEP 4C 4 OR	Version
Order No.	2051920000	A-series, End plate
GTIN (EAN)	4050118412000	
Qty.	20 pc(s).	
Туре	AEP 4C 4 BL	Version
Order No.	2051910000	A-series, End plate
GTIN (EAN)	4050118411904	
Qty.	20 pc(s).	
Туре	AEP 4C 4	Version
Order No.	2051900000	A-series, End plate
GTIN (EAN)	4050118412017	
Qty.	20 pc(s).	



Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

WS 8/6



WS/ DEK

MultiMark DEK/WS connector markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- · Firm hold and durable printing
- · Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- · Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

General ordering data

Type WS 8/6 MM WS
Order No. 2007160000
GTIN (EAN) 4050118391879
Qty. 600 pc(s).

Version

WS, Terminal marker, 8 x 6 mm, Weidmueller, white

Digital multimeters



Multimeters are capable of measuring a number of variables. Each instrument can measure voltage and resistance, as well as performing continuity and diode testing as standard.

In addition, the individual multimeters also feature extra measuring options such as current, frequency, capacitance and temperature. Digital multimeters have the advantage of a clear display which can be read easily and directly. With these instruments, mistakes arising from faulty conversion of the measuring ranges or misreading the display are a thing of the past.

General ordering data

Type ZUB MULTIMETER
Order No. 9205270000
GTIN (EAN) 4032248723522
Qty. 1 pc(s).

Version Multimeter



Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Custom printing



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or MC-Mobilo is possible.

- · Can be fitted in strips or individually
- · Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type WS 8/6 PLUS MC SDR
Order No. 1038820000
GTIN (EAN) 4032248768073
Oty. 120 pc(s).

Version

WS, Terminal marker, 8 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,

To customer specification

Blank



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or

Can be fitted in strips or individually

MC-Mobilo is possible.

• Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type WS 8/6 PLUS MC NE WS
Order No. 1951880000
GTIN (EAN) 4032248632114
Oty. 600 pc(s).

Version

WS, Terminal marker, 8 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,

white



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Partition plates



Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

General ordering data

Туре Version Order No. 2489090000 A-series, Seperation plate GTIN (EAN) 4050118499308 Qty. 50 pc(s).

End brackets



Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

Туре	AEB 35 SCL/1 VO GY	Version
Order No.	2661290000	A-series, End bracket
		Asselles, Life bracket
GTIN (EAN)	4050118702170	
Qty.	20 pc(s).	
Туре	AEB 35 SCL/1 VO BK	Version
Order No.	<u>2661300000</u>	A-series, End bracket
GTIN (EAN)	4050118702187	
Qty.	20 pc(s).	
Туре	AEB 35 SC/1 BK	Version
Order No.	2475310000	A-series, End bracket
GTIN (EAN)	4050118487114	
Qty.	50 pc(s).	
Туре	AEB 35 SCL/1 V0	Version
Order No.	<u>2661280000</u>	A-series, End bracket
GTIN (EAN)	4050118702163	
Qty.	20 pc(s).	
Туре	AEB 35 SC/1	Version
Order No.	<u>1991920000</u>	A-series, End bracket
GTIN (EAN)	4050118376722	
Qty.	50 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Blank



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or MC-Mobilo is possible.

- Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	WS 10/6 MC M NE RT	Version
Order No.	<u>1917440000</u>	WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,
GTIN (EAN)	4032248551644	Allen-Bradley, red
Qty.	600 pc(s).	
Туре	WS 10/6 MC M NE GE	Version
Order No.	<u>1917430000</u>	WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,
GTIN (EAN)	4032248551637	Allen-Bradley, yellow
Qty.	600 pc(s).	
Туре	WS 10/6 M MC NE WS	Version
Order No.	<u>1818400000</u>	WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,
GTIN (EAN)	4032248310876	Allen-Bradley, white
Qty.	600 pc(s).	
Туре	WS 10/6 MC NE WS	Version
Order No.	1828450000	WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,
GTIN (EAN)	4032248350513	Allen-Bradley, white
Qty.	600 pc(s).	
Туре	WS 10/6 PLUS MC NE WS	Version
Order No.	1046390000	WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,
GTIN (EAN)	4032248782109	Allen-Bradley, white
Qty.	600 pc(s).	
Туре	WS 10/6 M PLUS MC NE WS	Version
Order No.	2003780000	WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,
GTIN (EAN)	4050118424461	Allen-Bradley, white
Qty.	600 pc(s).	
Туре	WS 10/6 MC M NE BL	Version
Order No.	1069080000	WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,
GTIN (EAN)	4032248824618	Allen-Bradley, blue
Qty.	600 pc(s).	
Туре	WS 10/6 MC M NE GN	Version
Order No.	<u>1917420000</u>	WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,
GTIN (EAN)	4032248551620	Allen-Bradley, green
Qty.	600 pc(s).	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DIN Rail Terminal Blocks category:

Click to view products by Weidmuller manufacturer:

Other Similar products are found below:

1045932 00110420202 00110430402 5724.2/L 592808-3 CTS25U/BL CTS2.5U-N/Y 90.080 91.010 91.040 DP25-GY-ND 15288 90.070 90.202 90.905 91.001 91.020 91.201 91.340 2713793 280-331 283-317 283-607 2909044 2909798 29-2052 SRT2-OD08CL-1 CDL4U(E)MOV 2757801 2794660 284-317 2890975 2907033 3048496 CTS2.5U-N/O 5542152 5602077 0709880 5520682 5607102 EPUSC SRT2-OD16P 2901288 591620-2 1-591651-1 NRA37-1/2 592814-1 592814-3 SRT2-ID16P NRA37-12