

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Product image







Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

| Туре | A4C 4 PE |
|------------|---|
| Order No. | <u>2051560000</u> |
| Version | PE terminal, PUSH IN, 4 mm ² , white |
| GTIN (EAN) | 4050118411751 |
| Qty. | 50 pc(s). |
| | |



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

| Dimensions and weights | | | | |
|------------------------|---------|-----------------|------------|--|
| | | | | |
| Width | 6.1 mm | Width (inches) | 0.24 inch | |
| Height | 87.5 mm | Height (inches) | 3.445 inch | |

Depth 39.5 mm Depth (inches) 1.555 inch Depth including DIN rail 40.5 mm Net weight 17.961 g

Temperatures

| Storage temperature, max. | 40 °C | Storage temperature, min. | 10 °C | |
|----------------------------------|------------|----------------------------------|--------|--|
| Storage temperature | 10 °C40 °C | Continuous operating temp., min. | -60 °C | |
| Continuous operating temp., max. | 130 °C | | | |

Material data

| Material | Wemid | Colour | white |
|--------------------------------|--------|---------------------------|-------|
| Colour of operational elements | orange | UL 94 flammability rating | V-0 |

Rating data IECEx/ATEX

| Certificate No. (ATEX) | TUEV16ATEX7909U | Certificate No. (IECEX) | IECEXTUR16.0036U |
|--------------------------------|-------------------|---------------------------------|-------------------|
| Wire cross section max. (ATEX) | 4 mm ² | Wire cross section max. (IECEX) | 4 mm ² |
| Marking EN 60079-7 | Ex eb II C Gb | Ex 2014/34/EU label | II 2 G D |

System specifications

| End cover plate required | Yes | Number of potentials | 1 |
|-------------------------------|-------|-------------------------------------|-----|
| Number of levels | 1 | Number of clamping points per level | 4 |
| Number of potentials per tier | 1 | PE connection | Yes |
| Rail | TS 35 | N-function | No |
| PE function | Yes | PEN function | No |

Additional technical data

| Installation advice | Rail | Open sides | right |
|---------------------|-------|-------------------|---------|
| Snap-on | No | Type of fixing | Snap-on |
| Type of mounting | TS 35 | With snap-in pegs | No |

CSA rating data

| Certificate No. (CSA) | 200039-70089609 | Voltage size B (CSA) | 600 V |
|-------------------------------|-----------------|-------------------------------|--------|
| Voltage size C (CSA) | 600 V | Voltage size D (CSA) | 600 V |
| Wire cross section max. (CSA) | 10 AWG | Wire cross section min. (CSA) | 26 AWG |



Technical data

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083

www.weidmueller.com

Conductors for clamping (rated connection)

| Blade size | 0.6 x 3.5 mm | Clamping range, max. | 4 mm ² |
|--|--|---|--|
| Clamping range, min. | | Connection cross-section, stranded, | |
| | 0.5 mm ² | max. | 4 mm ² |
| Connection cross-section, stranded, mi | n. 0.5 mm² | Connection direction | top |
| Gauge to IEC 60947-1 | A4 | Number of connections | 4 |
| Stripping length | 12 mm | Twin wire-end ferrules, max. | 1.5 mm ² |
| Twin wire-end ferrules, min. | 0.5 mm ² | Type of connection | PUSH IN |
| Wire connection cross section AWG, | | Wire connection cross section AWG, | |
| max. | AWG 12 | min. | AWG 26 |
| Wire connection cross section, finely stranded, max. | 4 mm² | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. | 4 mm² |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. | 0.5 mm² | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 4 mm² |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN | 0.3 11111 | Wire connection cross-section, finely stranded, min. | 4 11111 |
| 46228/4, min. | 0.5 mm ² | <u> </u> | 0.5 mm ² |
| Wire connection cross-section, solid | | Wire connection cross-section, solid | |
| core, max. | 4 mm ² | core, min. | 0.5 mm ² |
| Rated short-time current | 480 A (4 mm²) | PEN function | No |
| Rating data | | | |
| namy uata | | | |
| Rated cross-section | 4 mm² | Rated voltage to adjoining terminal | 800 V |
| | 4 mm ² IEC 60947-7-2 | Rated voltage to adjoining terminal Volume resistance according to IEC 60947-7-x | 800 V 1 mΩ |
| Rated cross-section Standards | | Volume resistance according to IEC | |
| Rated cross-section Standards Power loss in accordance with IEC | | Volume resistance according to IEC 60947-7-x | |
| Rated cross-section Standards Power loss in accordance with IEC 60947-7-x | IEC 60947-7-2 | Volume resistance according to IEC 60947-7-x | 1 mΩ |
| Rated cross-section Standards Power loss in accordance with IEC 60947-7-x Pollution severity | IEC 60947-7-2 1.02 W | Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage | 1 mΩ 8 kV |
| Rated cross-section Standards Power loss in accordance with IEC 60947-7-x Pollution severity | IEC 60947-7-2 1.02 W | Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage | 1 mΩ 8 kV |
| Rated cross-section Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data Certificate No. (cURus) | IEC 60947-7-2 1.02 W | Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage Surge voltage category Conductor size Factory wiring max. (cURus) | 1 mΩ 8 kV III |
| Rated cross-section Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data Certificate No. (cURus) Conductor size Factory wiring min. | IEC 60947-7-2 1.02 W 3 | Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage Surge voltage category Conductor size Factory wiring max. | 1 mΩ 8 kV III 10 AWG |
| Rated cross-section Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data Certificate No. (cURus) Conductor size Factory wiring min. cURus) | IEC 60947-7-2 1.02 W 3 E60693 28 AWG | Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage Surge voltage category Conductor size Factory wiring max. (cURus) Conductor size Field wiring max. (cURu | 1 mΩ 8 kV III 10 AWG Is) 10 AWG |
| Rated cross-section Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data Certificate No. (cURus) Conductor size Factory wiring min. cURus) Conductor size Field wiring min. (cURu | IEC 60947-7-2 1.02 W 3 E60693 28 AWG s) 28 AWG | Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage Surge voltage category Conductor size Factory wiring max. (cURus) Conductor size Field wiring max. (cURu | 1 mΩ 8 kV III 10 AWG us) 10 AWG 600 V |
| Rated cross-section Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data Certificate No. (cURus) Conductor size Factory wiring min. (cURus) Conductor size Field wiring min. (cURu | IEC 60947-7-2 1.02 W 3 E60693 28 AWG | Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage Surge voltage category Conductor size Factory wiring max. (cURus) Conductor size Field wiring max. (cURu | 1 mΩ 8 kV III 10 AWG Is) 10 AWG |
| Rated cross-section Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data | IEC 60947-7-2 1.02 W 3 E60693 28 AWG s) 28 AWG | Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage Surge voltage category Conductor size Factory wiring max. (cURus) Conductor size Field wiring max. (cURu | 1 mΩ 8 kV III 10 AWG us) 10 AWG 600 V |
| Rated cross-section Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data Certificate No. (cURus) Conductor size Factory wiring min. (cURus) Conductor size Field wiring min. (cURus) Voltage size C (cURus) Classifications | IEC 60947-7-2 1.02 W 3 E60693 28 AWG s) 28 AWG 600 V | Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage Surge voltage category Conductor size Factory wiring max. (cURus) Conductor size Field wiring max. (cURus) Voltage size B (cURus) Voltage size D (cURus) | 1 mΩ 8 kV III 10 AWG Is) 10 AWG 600 V 600 V |
| Rated cross-section Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data Certificate No. (cURus) Conductor size Factory wiring min. (cURus) Conductor size Field wiring min. (cURu | IEC 60947-7-2 1.02 W 3 E60693 28 AWG s) 28 AWG | Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage Surge voltage category Conductor size Factory wiring max. (cURus) Conductor size Field wiring max. (cURu | 1 mΩ 8 kV III 10 AWG us) 10 AWG 600 V |



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Approvals

Approvals



ATEX

| ROHS | Conform |
|----------------------------------|---|
| Downloads | |
| | |
| Approval/Certificate/Document of | Attestation of Conformity |
| Conformity | ATEX Certificate |
| | IECEx Certificate |
| | CB Test Certificate |
| | CB Certificate |
| | DE_PT0102_20160614_071_ISSUE01.pdf |
| Brochure/Catalogue | <u>CAT 1 TERM 16/17 EN</u> |
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |
| Engineering Data | STEP |
| Tender specification | Klippon® Connect 2051560000 DE |
| | <u>Klippon® Connect 2051560000 EN</u> |
| User Documentation | NTI_A4C 4.pdf |
| | <u>StorageConditionsTerminalBlocks</u> |
| | Aderendhülsen für die Klippon® Connect A-Reihe |
| | Wire end ferrules for Klippon® Connect A-series |
| Safety note | |
| | |
| Safety notice | Safety Information |




Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Drawings





Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Test adapter



Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

General ordering data

| Туре | ATPG 4 MI-R |
|-------------------|-----------------------------|
| Order No. | <u>1991860000</u> |
| GTIN (EAN) | 4050118376661 |
| Qty. | 50 pc(s). |
| | |
| Туре | ATPG 1.5-10 L |
| Type Order No. | ATPG 1.5-10 L 1991890000 |
| | 6 2 |

DEK 5/6



WS/ DEK

MultiMark DEK/WS connector markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- · Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

| Туре | DEK 5/6 MM WS | Version |
|------------|-------------------|--|
| Order No. | <u>2007120000</u> | Dekafix, Terminal marker, 5 x 6 mm, Weidmueller, white |
| GTIN (EAN) | 4050118392104 | |
| Qty. | 600 pc(s). | |



Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Covers



Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

General ordering data

Type AAM 4 YE FLASH
Order No. 2635560000
GTIN (EAN) 4050118674507
Qty. 40 pc(s).

Version

Terminal marker, 10 x 6.1 mm, yellow

Custom printing



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or MC-Mobilo is possible.

- Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

| Туре | WS 10/6 MC SDR | Version |
|------------|-----------------------|--|
| Order No. | 1828460000 | WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, |
| GTIN (EAN) | 4032248367399 | Allen-Bradley, To customer specification |
| Qty. | 120 pc(s). | |
| Туре | WS 10/6 MC M SDR | Version |
| Order No. | 1818410000 | WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, |
| GTIN (EAN) | 4032248310883 | Allen-Bradley, To customer specification |
| Qty. | 120 pc(s). | |
| Туре | WS 10/6 M PLUS MC SDR | Version |
| Order No. | 2007780000 | WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, |
| GTIN (EAN) | 4050118393187 | Allen-Bradley, To customer specification |
| Qty. | 120 pc(s). | |



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Type WS 10/6 PLUS MC SDR
Order No. 1046330000
GTIN (EAN) 4032248782031
Oty. 120 pc(s).

Version

WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,

Allen-Bradley, To customer specification

ZQV 4N



Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

| Order No. 1528220000 GTIN (EAN) 405011833107 Oty. 20 pc(s). Type ZOV 4N/10 BL Order No. 1528230000 GTIN (EAN) 405011833138 Oty. 20 pc(s). Type ZOW 4N/50 BL Order No. 1528240000 GTIN (EAN) 4050118333121 Qty. 5 pc(s). Type 20V 4N/8 BL Order No. 152819000 GTIN (EAN) 4050118332858 Qty. 20 pc(s). Type ZOV 4N/3 Order No. 1527940000 GTIN (EAN) 4050118332865 Qty. 60 pc(s). Type 20V 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 Qty. 20 pc(s). Type 20V 4N/10 Order No. 152890000 GTIN (EAN) 4050118332896 Qty. 20 pc(s). Type 20V 4N/5 Orde | Туре | ZOV 4N/9 BL |
|---|------------|-------------------|
| Qty. 20 pc(s). Type ZOV AN/10 BL Order No. 1528230000 GTIN (EAN) 4050118333138 Qty. 20 pc(s). Type ZOV AN/50 BL Order No. 1528240000 GTIN (EAN) 4050118333121 Qty. 5 pc(s). Type ZOV AN/8 BL Order No. 1528190000 GTIN (EAN) 4050118332858 Qty. 20 pc(s). Type ZOV AN/3 Order No. 1527940000 GTIN (EAN) 4050118332865 Qty. 60 pc(s). Type ZOV AN/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 Qty. 20 pc(s). Type ZOV AN/10 Order No. 152809000 GTIN (EAN) 4050118332759 | Order No. | <u>1528220000</u> |
| Type | GTIN (EAN) | 4050118333107 |
| Order No. 1528230000 GTIN (EAN) 4050118333138 Oty. 20 pc(s). Type ZOV 4M/50 BL Order No. 1528240000 GTIN (EAN) 4050118333121 Oty. 5 pc(s). Type ZOV 4M/5 BL Order No. 152819000 GTIN (EAN) 4050118333258 Oty. 20 pc(s). Type ZOV 4M/3 Order No. 1527940000 GTIN (EAN) 4050118332865 Oty. 60 pc(s). Type ZOV 4M/3 Order No. 152819000 GTIN (EAN) 4050118332865 Oty. 60 pc(s). Type ZOV 4M/10 Order No. 1528170000 GTIN (EAN) 4050118332926 Oty. 20 pc(s). Type ZOV 4M/10 Order No. 1528190000 GTIN (EAN) 4050118332926 Oty. 20 pc(s). Type ZOV 4M/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Oty. 20 pc(s). Type ZOV 4M/5 Order No. 1528090000 GTIN (EAN) 4050118332896 Oty. 20 pc(s). Type ZOV 4M/5 Order No. 1528090000 GTIN (EAN) 4050118332896 Oty. 20 pc(s). Type ZOV 4M/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | Qty. | 20 pc(s). |
| GTIN (EAN) 4050118333138 City. 20 pc(s). Type ZOV 4N/50 BL Order No. 1528190000 GTIN (EAN) 4050118333121 City. 5 pc(s). Type ZOV 4N/8 BL Order No. 1528190000 GTIN (EAN) 4050118332858 City. 20 pc(s). Type ZOV 4N/3 Order No. 15281940000 GTIN (EAN) 4050118332865 City. 60 pc(s). Type ZOV 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 City. 20 pc(s). Type ZOV 4N/6 BL Order No. 1528170000 GTIN (EAN) 40501183329366 City. 20 pc(s). Type ZOV 4N/6 BL Order No. 1528170000 GTIN (EAN) 40501183329366 City. 20 pc(s). Type ZOV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 City. 20 pc(s). Type ZOV 4N/5 Order No. 1528090000 GTIN (EAN) 4050118332896 City. 20 pc(s). Type ZOV 4N/5 Order No. 1527880000 GTIN (EAN) 4050118332896 City. 20 pc(s). | Туре | ZOV 4N/10 BL |
| Otry 20 pc(s). Type ZQV 4N/50 BL Order No. 1528240000 GTIN (EAN) 4050118333121 Cty. 5 pc(s). Type ZOV 4N/8 BL Order No. 1528190000 GTIN (EAN) 4050118332858 Oty. 20 pc(s). Type ZOV 4N/3 Order No. 1527940000 GTIN (EAN) 4050118332865 Oty. 60 pc(s). Type ZOV 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 Oty. 20 pc(s). Type ZOV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Oty. 20 pc(s). Type ZOV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | Order No. | <u>1528230000</u> |
| Type 20V 4N/50 BL Order No. 1528240000 GTIN (EAN) 4050118333121 Qty. 5 pc(s). Type ZOV 4N/8 BL Order No. 1528190000 GTIN (EAN) 4050118332858 Qty. 20 pc(s). Type ZOV 4M/3 Order No. 1527940000 GTIN (EAN) 4050118332865 Qty. 60 pc(s). Type ZOV 4N/8 BL Order No. 15278170000 GTIN (EAN) 4050118332865 Qty. 60 pc(s). Type ZOV 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 Qty. 20 pc(s). Type ZOV 4N/10 Order No. 1528030000 GTIN (EAN) 4050118332896 Qty. 20 pc(s). Type ZOV 4N/10 Order No. 1528030000 GTIN (EAN) 4050118332896 Qty. 20 pc(s). Type ZOV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332599 Order No. 1527980000 GTIN (EAN) 4050118332599 | GTIN (EAN) | 4050118333138 |
| Order No. 1528240000 GTIN (EAN) 4050118333121 Cty. 5 pc(s). Type ZQV 4N/8 BL Order No. 1528190000 GTIN (EAN) 4050118332858 Qty. 20 pc(s). Type ZQV 4N/3 Order No. 1527940000 GTIN (EAN) 4050118332865 Qty. 60 pc(s). Type ZQV 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 Qty. 20 pc(s). Type ZQV 4N/10 Order No. 152899000 GTIN (EAN) 4050118332896 Qty. 20 pc(s). Type ZQV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | Qty. | 20 pc(s). |
| GTIN (EAN) 4050118333121 Cty. 5 pc(s). Type ZQV 4N/8 BL Order No. 1528190000 GTIN (EAN) 4050118332858 Cty. 20 pc(s). Type ZQV 4M/3 Order No. 1527940000 GTIN (EAN) 4050118332865 Oty. 60 pc(s). Type ZQV 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 Oty. 20 pc(s). Type ZQV 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 Oty. 20 pc(s). Type ZQV 4N/10 Order No. 1528290000 GTIN (EAN) 4050118332896 Cty. 20 pc(s). Type ZQV 4N/10 Order No. 1528390000 GTIN (EAN) 4050118332896 Cty. 20 pc(s). | Туре | ZQV 4N/50 BL |
| Oty. 5 pc(s). Type ZOV 4N/8 BL Order No. 1528190000 GTIN (EAN) 4050118332858 Qty. 20 pc(s). Type ZOV 4N/3 Order No. 1527940000 GTIN (EAN) 4050118332865 Qty. 60 pc(s). Type ZOV 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 Qty. 20 pc(s). Type ZOV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Qty. 20 pc(s). Type ZOV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | Order No. | <u>1528240000</u> |
| Type ZOV 4N/8 BL Order No. 1528190000 GTIN (EAN) 4050118332858 Oty. 20 pc(s). Type ZOV 4N/3 Order No. 1527940000 GTIN (EAN) 4050118332865 Oty. 60 pc(s). Type ZOV 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 Oty. 20 pc(s). Type ZOV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Oty. 20 pc(s). Type ZOV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Oty. 20 pc(s). Type ZOV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Oty. 20 pc(s). Type ZOV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | GTIN (EAN) | 4050118333121 |
| Order No. 1528190000 GTIN (EAN) 4050118332858 Oty. 20 pc(s). Type ZOV 4N/3 Order No. 1527940000 GTIN (EAN) 4050118332865 Oty. 60 pc(s). Type ZOV 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 Oty. 20 pc(s). Type ZOV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Oty. 20 pc(s). Type ZOV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Oty. 20 pc(s). Type ZOV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | Qty. | 5 pc(s). |
| GTIN (EAN) 4050118332858 City. 20 pc(s). Type ZQV 4N/3 Order No. 1527940000 GTIN (EAN) 4050118332865 City. 60 pc(s). Type ZQV 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 City. 20 pc(s). Type ZQV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 City. 20 pc(s). Type ZQV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332896 City. 20 pc(s). | Туре | ZOV 4N/8 BL |
| Qty. 20 pc(s). Type ZQV 4N/3 Order No. 1527940000 GTIN (EAN) 4050118332865 Qty. 60 pc(s). Type ZQV 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 Qty. 20 pc(s). Type ZQV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Qty. 20 pc(s). Type ZQV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | Order No. | <u>1528190000</u> |
| Type ZQV 4N/3 Order No. 1527940000 GTIN (EAN) 4050118332865 Oty. 60 pc(s). Type ZQV 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 Oty. 20 pc(s). Type ZQV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Oty. 20 pc(s). Type ZQV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Oty. 20 pc(s). Type ZOV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | GTIN (EAN) | 4050118332858 |
| Order No. 1527940000 GTIN (EAN) 4050118332865 Oty. 60 pc(s). Type ZOV 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 Oty. 20 pc(s). Type ZOV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Oty. 20 pc(s). Type ZOV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | Qty. | 20 pc(s). |
| GTIN (EAN) 4050118332865 Qty. 60 pc(s). Type ZQV 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 Qty. 20 pc(s). Type ZQV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Qty. 20 pc(s). Type ZQV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | Туре | ZOV 4N/3 |
| Qty. 60 pc(s). Type ZQV 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 Qty. 20 pc(s). Type ZQV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Qty. 20 pc(s). Type ZQV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | Order No. | <u>1527940000</u> |
| Type ZQV 4N/6 BL Order No. 1528170000 GTIN (EAN) 4050118332926 Oty. 20 pc(s). Type ZQV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Oty. 20 pc(s). Type ZOV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | GTIN (EAN) | 4050118332865 |
| Order No. 1528170000 GTIN (EAN) 4050118332926 Qty. 20 pc(s). Type ZQV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Qty. 20 pc(s). Type ZQV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | Qty. | 60 pc(s). |
| GTIN (EAN) 4050118332926 Qty. 20 pc(s). Type ZQV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Qty. 20 pc(s). Type ZQV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | Туре | ZOV 4N/6 BL |
| Qty. 20 pc(s). Type ZQV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Qty. 20 pc(s). Type ZQV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | Order No. | <u>1528170000</u> |
| Type ZQV 4N/10 Order No. 1528090000 GTIN (EAN) 4050118332896 Qty. 20 pc(s). Type ZQV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | GTIN (EAN) | 4050118332926 |
| Order No. 1528090000 GTIN (EAN) 4050118332896 Oty. 20 pc(s). Type ZOV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | Qty. | 20 pc(s). |
| GTIN (EAN) 4050118332896 Qty. 20 pc(s). Type ZQV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | Туре | ZQV 4N/10 |
| Qty. 20 pc(s). Type ZQV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | Order No. | <u>1528090000</u> |
| Type ZQV 4N/5 Order No. 1527980000 GTIN (EAN) 4050118332759 | GTIN (EAN) | 4050118332896 |
| Order No. 1527980000 GTIN (EAN) 4050118332759 | Qty. | 20 pc(s). |
| GTIN (EAN) 4050118332759 | Туре | ZQV 4N/5 |
| | Order No. | <u>1527980000</u> |
| Oty. 60 pc(s). | GTIN (EAN) | 4050118332759 |
| | Qty. | 60 pc(s). |



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

| Туре | ZQV 4N/7 BL |
|------------|-------------------|
| Order No. | 1528180000 |
| GTIN (EAN) | 4050118333114 |
| Qty. | 20 pc(s). |
| Туре | ZQV 4N/7 |
| Order No. | 1528020000 |
| GTIN (EAN) | 4050118332780 |
| | |
| Qty. | 20 pc(s). |
| Туре | ZOV 4N/8 |
| Order No. | <u>1528030000</u> |
| GTIN (EAN) | 4050118332841 |
| Qty. | 20 pc(s). |
| Туре | ZOV 4N/4 |
| Order No. | <u>1527970000</u> |
| GTIN (EAN) | 4050118332889 |
| Qty. | 60 pc(s). |
| Туре | ZQV 4N/6 |
| Order No. | <u>1527990000</u> |
| GTIN (EAN) | 4050118332919 |
| Qty. | 20 pc(s). |
| Туре | ZQV 4N/50 |
| Order No. | <u>1528130000</u> |
| GTIN (EAN) | 4050118332902 |
| Qty. | 5 pc(s). |
| Туре | ZOV 4N/4 BL |
| Order No. | <u>1528120000</u> |
| GTIN (EAN) | 4050118332872 |
| Qty. | 60 pc(s). |
| Туре | ZQV 4N/9 |
| Order No. | <u>1528070000</u> |
| GTIN (EAN) | 4050118332797 |
| Qty. | 20 pc(s). |
| Туре | ZQV 4N/2 |
| Order No. | 1527930000 |
| GTIN (EAN) | 4050118332766 |
| Qty. | 60 pc(s). |
| Туре | ZQV 4N/2 BL |
| Order No. | 1528040000 |
| GTIN (EAN) | 4050118332773 |
| Qty. | 60 pc(s). |
| Туре | ZQV 4N/5 BL |
| Order No. | 1528140000 |
| GTIN (EAN) | 4050118333015 |
| | |
| Oty. | 60 pc(s). |
| Туре | ZQV 4N/3 BL |
| Order No. | <u>1528080000</u> |
| GTIN (EAN) | 4050118333008 |
| Qty. | 60 pc(s). |
| αty. | oo pola). |



Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Plus



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

DEK 5/6 PLUS MC NE WS

Order No. 1011320000 GTIN (EAN)

4032248717644

1,000 pc(s).

Version

Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

Weidmueller, white

Blank

Qty.



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

DEK 5/6 MC NE GN Туре Order No. 1238310000

GTIN (EAN) 4050118271812

1,000 pc(s).

Version

Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

Weidmueller, green



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

| Туре | DEK 5/6 MC NE GE | Version |
|------------|-------------------|---|
| Order No. | 1238280000 | Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 |
| GTIN (EAN) | 4050118038750 | Weidmueller, yellow |
| Qty. | 1,000 pc(s). | |
| Туре | DEK 5/6 MC NE OR | Version |
| Order No. | <u>1912090000</u> | Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 |
| GTIN (EAN) | 4032248540525 | Weidmueller, orange |
| Qty. | 1,000 pc(s). | |
| Туре | DEK 5/6 MC NE BR | Version |
| Order No. | 1454900000 | Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 |
| GTIN (EAN) | 4050118323313 | Weidmueller, brown |
| Qty. | 1,000 pc(s). | |
| Туре | DEK 5/6 MC NE GR | Version |
| Order No. | 1238330000 | Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 |
| GTIN (EAN) | 4050118323306 | Weidmueller, grey |
| Qty. | 1,000 pc(s). | |
| Туре | DEK 5/6 MC NE WS | Version |
| Order No. | 1609820000 | Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 |
| GTIN (EAN) | 4008190203436 | Weidmueller, white |
| Qty. | 1,000 pc(s). | |
| Туре | DEK 5/6 MC NE BL | Version |
| Order No. | 1238290000 | Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 |
| GTIN (EAN) | 4050118267327 | Weidmueller, blue |
| Qty. | 1,000 pc(s). | |

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

| Туре | DEK 5/6 MC SDR | Version |
|------------|----------------|---|
| Order No. | 1609830000 | Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 |
| GTIN (EAN) | 4008190456603 | Weidmueller, To customer specification |
| Qty. | 200 pc(s). | |



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

 Type
 DEK 5/6 PLUS MC SDR

 Order No.
 1038650000

 GTIN (EAN)
 4032248767908

 Qty.
 200 pc(s).

Version

Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

Weidmueller, To customer specification

End plates



Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

| Туре | AEP 4C 4 OR | Version |
|------------|---------------|---------------------|
| Order No. | 2051920000 | A-series, End plate |
| GTIN (EAN) | 4050118412000 | |
| Qty. | 20 pc(s). | |
| Туре | AEP 4C 4 BL | Version |
| Order No. | 2051910000 | A-series, End plate |
| GTIN (EAN) | 4050118411904 | |
| Qty. | 20 pc(s). | |
| Туре | AEP 4C 4 | Version |
| Order No. | 2051900000 | A-series, End plate |
| GTIN (EAN) | 4050118412017 | |
| Qty. | 20 pc(s). | |



Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

WS 8/6



WS/ DEK

MultiMark DEK/WS connector markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- · Firm hold and durable printing
- · Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- · Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

General ordering data

Type WS 8/6 MM WS
Order No. 2007160000
GTIN (EAN) 4050118391879
Qty. 600 pc(s).

Version

WS, Terminal marker, 8 x 6 mm, Weidmueller, white

Digital multimeters



Multimeters are capable of measuring a number of variables. Each instrument can measure voltage and resistance, as well as performing continuity and diode testing as standard.

In addition, the individual multimeters also feature extra measuring options such as current, frequency, capacitance and temperature. Digital multimeters have the advantage of a clear display which can be read easily and directly. With these instruments, mistakes arising from faulty conversion of the measuring ranges or misreading the display are a thing of the past.

General ordering data

Type ZUB MULTIMETER
Order No. 9205270000
GTIN (EAN) 4032248723522
Qty. 1 pc(s).

Version Multimeter



Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Custom printing



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or MC-Mobilo is possible.

- · Can be fitted in strips or individually
- · Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type WS 8/6 PLUS MC SDR
Order No. 1038820000
GTIN (EAN) 4032248768073
Oty. 120 pc(s).

Version

WS, Terminal marker, 8 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,

To customer specification

Blank



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or

- MC-Mobilo is possible.Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

 Type
 WS 8/6 PLUS MC NE WS
 Version

 Order No.
 1951880000
 WS, Terminal marker, 8 x 6 mm, Pitch in mm (P): 6.00 Weidmueller,

 GTIN (EAN)
 4032248632114
 white

 Qty.
 600 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Partition plates



Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

General ordering data

Type APP 2 Version
Order No. 2489090000 A-series, Seperation plate
GTIN (EAN) 4050118499308
Otty. 50 pc(s).

End brackets



Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

| Туре | AEB 35 SCL/1 VO GY | Version |
|------------|--------------------|-----------------------|
| Order No. | <u>2661290000</u> | A-series, End bracket |
| GTIN (EAN) | 4050118702170 | |
| Qty. | 20 pc(s). | |
| Туре | AEB 35 SCL/1 VO BK | Version |
| Order No. | <u>2661300000</u> | A-series, End bracket |
| GTIN (EAN) | 4050118702187 | |
| Qty. | 20 pc(s). | |
| Туре | AEB 35 SC/1 BK | Version |
| Order No. | <u>2475310000</u> | A-series, End bracket |
| GTIN (EAN) | 4050118487114 | |
| Qty. | 50 pc(s). | |
| Туре | AEB 35 SCL/1 V0 | Version |
| Order No. | <u>2661280000</u> | A-series, End bracket |
| GTIN (EAN) | 4050118702163 | |
| Qty. | 20 pc(s). | |
| Туре | AEB 35 SC/1 | Version |
| Order No. | 1991920000 | A-series, End bracket |
| GTIN (EAN) | 4050118376722 | |
| Qty. | 50 pc(s). | |
| | | |



Weidmüller Interface GmbH & Co. KG


Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Blank



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or MC-Mobilo is possible.

- · Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

| Туре | WS 10/6 MC M NE RT | Version |
|------------|-------------------------|--|
| Order No. | <u>1917440000</u> | WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, |
| GTIN (EAN) | 4032248551644 | Allen-Bradley, red |
| Qty. | 600 pc(s). | |
| Туре | WS 10/6 MC M NE GE | Version |
| Order No. | <u>1917430000</u> | WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, |
| GTIN (EAN) | 4032248551637 | Allen-Bradley, yellow |
| Qty. | 600 pc(s). | |
| Туре | WS 10/6 M MC NE WS | Version |
| Order No. | <u>1818400000</u> | WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, |
| GTIN (EAN) | 4032248310876 | Allen-Bradley, white |
| Qty. | 600 pc(s). | |
| Туре | WS 10/6 MC NE WS | Version |
| Order No. | 1828450000 | WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, |
| GTIN (EAN) | 4032248350513 | Allen-Bradley, white |
| Qty. | 600 pc(s). | |
| Туре | WS 10/6 PLUS MC NE WS | Version |
| Order No. | 1046390000 | WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, |
| GTIN (EAN) | 4032248782109 | Allen-Bradley, white |
| Qty. | 600 pc(s). | |
| Туре | WS 10/6 M PLUS MC NE WS | Version |
| Order No. | 2003780000 | WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, |
| GTIN (EAN) | 4050118424461 | Allen-Bradley, white |
| Qty. | 600 pc(s). | |
| Туре | WS 10/6 MC M NE BL | Version |
| Order No. | 1069080000 | WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, |
| GTIN (EAN) | 4032248824618 | Allen-Bradley, blue |
| Qty. | 600 pc(s). | |
| Туре | WS 10/6 MC M NE GN | Version |
| Order No. | <u>1917420000</u> | WS, Terminal marker, 10 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, |
| GTIN (EAN) | 4032248551620 | Allen-Bradley, green |
| Qty. | 600 pc(s). | |
| | | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DIN Rail Terminal Blocks category:

Click to view products by Weidmuller manufacturer:

Other Similar products are found below:

00110201060 00110410002 00110420002 00110420004 00110420202 00110420302 00110430002 00110430402 00110440002 00175111500 0117960000 AP SAK4-10 0117980000 AP SAK4-10 BL 0203069 0205067 0210421 0260015 0261014 0261027 0270018 0271017 0279560000 AP SAK2.5 0279580000 AP SAK2.5 BL 0302216 0303370 0303396 0304298 0305080 0305226 0305297 0305352 0308210 0309086 0309109 0309112 0309549 0310321 0310389 0311087 0311126 0311142 0311171 031-12 0311359 0311540 0311728 0311760 031-238 0313085 0321019 0328920000 SAKS 3/35 G/5X30 500V