

## **CABTITE SE 9-10 SML BK**

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

#### Similar to illustration







Whether a large or small cable diameter – Cabtite always offers the right seal insert.

The conical shape of the sealing elements allows the previously positioned snap-in grid inlays to be pushed in easily from the inside to the outsid. It reliably seals intermediate spaces and provides strain relief in accordance with DIN EN 62444. The seal inserts combined with the frames achieve an IP 66 degree of protection. As a result of its slotted design with wave cut, it is especially suitable for pre-assembled cables.

- The black seal inserts are designed for a particularly high operating temperature and offer fire safety class UL 94 HB
- The grey sealing elements comply with fire safety class UL 94 VO and are therefore suitable for the demands of the railway industry
- By using multiple inserts, two or more cables, as well as special cables, can be passed through a sealing element

#### General ordering data

Deep black, Height: 20.3 mm, Width: 20.3 mm, Depth: 17.7 mm, -40 °C120 °C, IP66  Order No.  2584080000  Type  CABTITE SE 9-10 SML BK  GTIN (EAN)  4050118616309		
Order No.         2584080000           Type         CABTITE SE 9-10 SML BK           GTIN (EAN)         4050118616309	Version	Sealing element, Cabtite (cable entry system), TPE, Deep black, Height: 20.3 mm, Width: 20.3 mm,
Type CABTITE SE 9-10 SML BK GTIN (EAN) 4050118616309		Depth: 17.7 mm, -40 °C120 °C, IP66
GTIN (EAN) 4050118616309	Order No.	<u>2584080000</u>
	Туре	CABTITE SE 9-10 SML BK
Otv. 10 pc(s).	GTIN (EAN)	4050118616309
	Qty.	10 pc(s).



## **CABTITE SE 9-10 SML BK**

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

## **Dimensions and weights**

Depth	17.7 mm	Depth (inches)	0.697 inch
Height	20.3 mm	Height (inches)	0.799 inch
Width	20.3 mm	Width (inches)	0.799 inch
Net weight	5.3 a		

## **Temperatures**

Operating temperature -40 °C...120 °C

#### **General information**

Halogen	No	Material	TPE
Outer cable diameter, max.	10 mm	Outer cable diameter, min.	9 mm
Protection degree	IP66	Sealing element	1 small sealing element
Silicone	No	UL 94 flammability rating	НВ

## Classifications

ETIM 6.0	EC000879	ETIM 7.0	EC000879
ETIM 8.0	EC000879	ECLASS 9.0	27-14-44-21
ECLASS 9.1	27-14-44-21	ECLASS 10.0	27-14-44-21
ECLASS 11.0	27-14-44-21		

#### **Approvals**

Approvals



ROHS	Conform	
UL File Number Search	E223801	

#### **Downloads**

Engineering Data	CAD data – STEP
Engineering Data	<u>EPLAN</u>
User Documentation	Cabtite Installation Instructions
Catalogues	Catalogues in PDF-format

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Grommets & Bushings category:

Click to view products by Weidmuller manufacturer:

Other Similar products are found below:

M10-036565-101 M10-036565-143 M10-036565-183 205339-4 M10-036565-122 M10-036565-163 3-1991136-0 561-FGUP0850B 561MP13716 561-FGUP0400N 1398081-1 1301800320 M10-036565-232 2298 4014B 2407 2141-P HTL-40-10-TPE 2417-P 2917-P 3108-P
2871-P 1342664 60466 50687 12468 51409 12462 15517 60752 60218 12463 BDE 21 BDE 29 HSS-M12-TPE RAL9005 HSS-M16TPE RAL9005 HSS-M25-TPE RAL9005 HSS-M20-TPE RAL9005 HTT-21 RAL7035 HTT-21-V0 BDE 11 BDE 13 BDE 13 BDE 16
SRF42 100187 100188 100216 100223 100236