

CABTITE SE 4-5 SML BK

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Similar to illustration







Whether a large or small cable diameter – Cabtite always offers the right seal insert.

The conical shape of the sealing elements allows the previously positioned snap-in grid inlays to be pushed in easily from the inside to the outsid. It reliably seals intermediate spaces and provides strain relief in accordance with DIN EN 62444. The seal inserts combined with the frames achieve an IP 66 degree of protection. As a result of its slotted design with wave cut, it is especially suitable for pre-assembled cables.

- The black seal inserts are designed for a particularly high operating temperature and offer fire safety class UL 94 HB
- The grey sealing elements comply with fire safety class UL 94 VO and are therefore suitable for the demands of the railway industry
- By using multiple inserts, two or more cables, as well as special cables, can be passed through a sealing element

General ordering data

| Version | Sealing element, Cabtite (cable entry system), TPE, |
|------------|---|
| | Deep black, Height: 20.3 mm, Width: 20.3 mm, |
| | Depth: 17.7 mm, -40 °C120 °C, IP66 |
| Order No. | <u>2584680000</u> |
| Туре | CABTITE SE 4-5 SML BK |
| GTIN (EAN) | 4050118616194 |
| Qty. | 10 pc(s). |
| | |



CABTITE SE 4-5 SML BK

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions and weights

| Depth | 17.7 mm | Depth (inches) | 0.697 inch |
|------------|---------|-----------------|------------|
| Height | 20.3 mm | Height (inches) | 0.799 inch |
| Width | 20.3 mm | Width (inches) | 0.799 inch |
| Net weight | 6.2 g | | |

Temperatures

Operating temperature -40 °C...120 °C

General information

| Halogen | No | Material | TPE |
|----------------------------|------|----------------------------|-------------------------|
| Outer cable diameter, max. | 5 mm | Outer cable diameter, min. | 4 mm |
| Protection degree | IP66 | Sealing element | 1 small sealing element |
| Silicone | No | UL 94 flammability rating | НВ |

Classifications

| ETIM 6.0 | EC000879 | ETIM 7.0 | EC000879 |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC000879 | ECLASS 9.0 | 27-14-44-21 |
| ECLASS 9.1 | 27-14-44-21 | ECLASS 10.0 | 27-14-44-21 |
| ECLASS 11.0 | 27-14-44-21 | | |

Approvals

Approvals



| ROHS | Conform |
|-----------------------|---------|
| UL File Number Search | E223801 |

Downloads

| Engineering Data | CAD data – STEP |
|--------------------|-----------------------------------|
| Engineering Data | <u>EPLAN</u> |
| User Documentation | Cabtite Installation Instructions |
| Catalogues | Catalogues in PDF-format |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Grommets & Bushings category:

Click to view products by Weidmuller manufacturer:

Other Similar products are found below:

M10-036565-101 M10-036565-143 M10-036565-183 205339-4 M10-036565-122 M10-036565-163 3-1991136-0 561-FGUP0850B 561-MP13716 561-FGUP0400N 1398081-1 1301800320 M10-036565-232 2298 4014B 2407 2141-P HTL-40-10-TPE 2417-P 2917-P 3108-P 2871-P 1342664 100187 100188 100216 100223 100236 52001970 52001980 52002010 52002050 1301800412 FEM 27-35 100175 100176 100178 100182 100196 100238 100244 100744 100084 100174 100177 100179 100180 100181 100186 100721