

## PAC-UNIV-HE40-F-1M

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)



Similar to illustration

### General ordering data

|            |  |
|------------|--|
| Version    | Pre-assembled cable, PAC, Cable LiYY, 0.25 mm <sup>2</sup> |
| Order No.  | <a href="#">7789756010</a>                                 |
| Type       | PAC-UNIV-HE40-F-1M   |
| GTIN (EAN) | 4032248996650  |
| Qty.       | 1 pc(s).   |

Creation date January 30, 2022 6:25:52 AM CET

Catalogue status 14.01.2022 / We reserve the right to make technical changes.

## PAC-UNIV-HE40-F-1M

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

## Technical data

### Dimensions and weights

Net weight 237 g

### Temperatures

Storage temperature -10...60 °C      Operating temperature -10...50 °C

### Environmental Product Compliance

REACH SVHC Lead 7439-92-1

### General Data

|                    |  |                       |                           |
|--------------------|--|-----------------------|---------------------------|
| Cable              | Cable LiYY                               | Cable length          | 1 m                       |
| Connector PLC side | H0.25/10 (FERRULES 0.25mm <sup>2</sup> ) | Interface connector   | FLAT CABLE PLANO HE10 40P |
| Material           | PVC                                      | Number of poles, min. | 40-pole                   |
| Outer diameter     | 11.7 ± 1 mm                              | Suitable for          | Digital signals           |
| Wire cross-section | 0.25 mm <sup>2</sup>                     |                       |                           |

### Electrical Data

|   |           |                       |                     |
|---|-----------|-----------------------|---------------------|
| Capacity wire / shield                      | 300 pF/m  | Capacity wire / wires | 300 pF/m            |
| High voltage test                           | 1 KV/1s   | Operating voltage     | ≤ 60 V DC ≤ 25 V AC |
| Permissible current strength per path, max. | 1 A       | Rated voltage         | ≤ 60 Vdc ≤ 25 Vac   |
| Resistance                                  | ≤ 80 mΩ/m | Total current, max.   | 3 A                 |

### Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000237    | ETIM 7.0    | EC000237    |
| ETIM 8.0    | EC000237    | ECLASS 9.0  | 27-24-22-20 |
| ECLASS 9.1  | 27-24-22-20 | ECLASS 10.0 | 27-24-22-20 |
| ECLASS 11.0 | 27-24-22-20 |             |             |

### Approvals

Approvals



### Downloads

|                    |  |
|--------------------|--|
| User Documentation | <a href="#">Colours chart</a>            |
| Catalogues         | <a href="#">Catalogues in PDF-format</a> |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Specialised Cables category](#):*

*Click to view products by [Weidmuller manufacturer](#):*

Other Similar products are found below :

[603PT6](#) [603SS6L](#) [604PT6](#) [604SS6](#) [706000D02F200](#) [910640](#) [1200740077](#) [1200740114](#) [AC172](#) [ACL-SSI-4](#) [R88ACAKA0015SRE](#)  
[R88ACAWL005SDE](#) [R88ACRGD0R3C](#) [1300150047](#) [1300660036](#) [1302262116](#) [1300150149](#) [1300220020](#) [1300220104](#) [1300220119](#)  
[1301240492](#) [1301810221](#) [1365323-1](#) [1613055](#) [176P12](#) [1971465-2](#) [20240400003](#) [20240400013](#) [2085828-1](#) [20886510030](#) [2-22733-8](#) [22733-](#)  
[8](#) [CB-5PSBC-RS](#) [CB-704EC-RS](#) [CB-BATACC-RS](#) [CB-JST3PSW-RS](#) [CB-M12COM-R10](#) [25AC84](#) [25AK84X](#) [25AU25](#) [25FN82](#) [3011-03](#)  
[AC118](#) [ACL-HHS-1M\(CAT5E\)](#) [SSL009PC2DC012N](#) [FC2A-KC6C](#) [2085828-2](#) [20886510150](#) [CCS-FCB-5](#) [CCSFCBF2](#)