



General ordering data

Order No.	9927480024
Part designation	CP SNT 55W 24-28V 2.3A
Version	Switched-mode power supplies, 85...265 V AC, 120...300 V DC , single-phase, 24...28 V DC
EAN	4032248217595
Qty.	1 pc(s).

Input

Connection system	Screw connection
Input current	1.1 A @ 115 V AC; 0.55 A @ 230 V AC
Input current at 115 Vac	1.10 A RMS +/- 20%
Input current at 125 Vdc	590 mA +/- 20%
Input current at 230 Vac	0.55 A RMS +/- 20%
Input current at 250 Vdc	315 mA +/- 20%
Input frequency	50/ 60 Hz
Input fuse	2 A time-lag fuse (internal)
Input voltage	85...265 V AC, 120...300 V DC
Max. connection range	AWG26-12 (0.1-4.0 mm ²)
Surge protection	Varistor
Turn-on current limit	Thermistor

output

Connection system	Screw connection
Control at 10...100% load	1 %
Control at input voltage	0.8 %
Mains failure bridge-over time for 115 V AC	30 ms
Mains failure bridge-over time for 230 V AC	180 ms
Max. capacitance at output	10000 µF
Max. connection range	AWG26-12 (0.1-4.0 mm ²)
Max. output power	55 V
Max. residual ripple	< 50 mV
Output current	2.3 A
Output voltage	24...28 V DC
Overload protection	/ thermal cut-out

output

Parallel connection option No

General data

DIN Rail compatibility TS 35
 Degree of efficiency at max. load 78 %
 EMC standards IEC 61000-6 /-2, -3
 Housings metal
 Low Voltage Directive 73/ 23/ EWG
 Power factor correction No
 Standards EN 50178, EN 60950, IEC950
 Status indication Green LED
 Switching frequency 100 kHz
 Weight 478 g
 Ambient temperature (operational) -20 °C...+40 °C
 Storage temperature -40 °C...+85 °C

Insulation coordination

Galvanic isolation, I/O rail 3 kV
 Galvanic isolation, input-earth 1.5 kV
 Galvanic isolation, input-output 3 kV
 Galvanic isolation, output-earth 0.5 kV
 Humidity at operating temperature 20 - 85% RH without condensation
 Humidity at storage temperature 20 - 90% RH
 Protection class IP 20

Dimensions

Clamping range, max. 4 mm²
 Clamping range, min. 0.1 mm²
 Clamping range, nom. 4 mm²
 Length 131 mm
 Height 98 mm
 Width 57 mm

Approvals

Approvals institutes



Classifications

ETIM 2.0 EC001039
 ETIM 3.0 EC001039
 eClass 4.1 27-24-04-10
 eClass 5.0 27-24-22-13
 eClass 5.1 27-24-22-13

Similar products

Order No.	Part designation	Version
9925340024	CP SNT 160W 24-28V 6.5A	Switched-mode power supplies, Min. 85/138 V AC, max. 195/250 V AC, typ. 115...230 V AC , single-phase, 24...28 V DC
9916250024	CP SNT 300W 24V 12.5A	Switched-mode power supplies, 86...265 V AC, 100...200 V DC; type 115...230 V AC , single-phase, 22...28 V DC adjustable
9927480005	CP SNT 55W 5V 3A	Switched-mode power supplies, 85...265 V AC, 120...300 V DC , single-phase, 5 V DC
9925340012	CP SNT 160W 12-15V 8A	Switched-mode power supplies, Min. 85/138 V AC, max. 195/250 V AC, typ. 115...230 V AC , single-phase, 12...15 V DC
9927480012	CP SNT 55W 12-15V 3A	Switched-mode power supplies, 85...265 V AC, 120...300 V DC , single-phase, 12...15 V DC
9925340005	CP SNT 160W 5V 8A	Switched-mode power supplies, Min. 85/138 V AC, max. 195/250 V AC, typ. 115...230 V AC , single-phase, 5 V DC
9927480048	CP SNT 55W 48V 1.04A	Switched-mode power supplies, 85...265 V AC, 120...300 V DC , single-phase, 48 V DC
9925340048	CP SNT 160W 48V 3.5A	Switched-mode power supplies, Min. 85/138 V AC, max. 195/250 V AC, typ. 115...230 V AC , single-phase, 48 V DC

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [weidmuller](#) manufacturer:

Other Similar products are found below :

[8924550000](#) [56956](#) [0133660000](#) [6720000227](#) [6720005111](#) [68676](#) [69718](#) [EXO24CH](#) [7940000218](#) [8005181001](#) [8008180000](#) [8432240000](#)
[8463580000](#) [8545830000](#) [8689870000](#) [8705640000](#) [8869870000](#) [9001080000](#) [9003720000](#) [9004250000](#) [9004780000](#) [9013260000](#)
[9014100000](#) [9019040000](#) [9026010000](#) [9028630000](#) [903708](#) [9037350000](#) [9046290000](#) [9129643500](#) [913155](#) [9159530000](#) [919656](#) [919764](#)
[9202230000](#) [9202850000](#) [9204260000](#) [9456750000](#) [9457913000](#) [980811](#) [980826](#) [9912800003](#) [9916080000](#) [9916280012](#) [9918380000](#)
[9919371205](#) [9919371224](#) [9925710000](#) [9926252005](#) [9927480024](#)