



General ordering data

Order No.	9927480024
Part designation	CP SNT 55W 24-28V 2.3A
Version	Switched-mode power supplies, 85...265 V AC, 120...300 V DC , single-phase, 24...28 V DC
EAN	4032248217595
Qty.	1 pc(s).

Input

Connection system	Screw connection
Input current	1.1 A @ 115 V AC; 0.55 A @ 230 V AC
Input current at 115 Vac	1.10 A RMS +/- 20%
Input current at 125 Vdc	590 mA +/- 20%
Input current at 230 Vac	0.55 A RMS +/- 20%
Input current at 250 Vdc	315 mA +/- 20%
Input frequency	50/ 60 Hz
Input fuse	2 A time-lag fuse (internal)
Input voltage	85...265 V AC, 120...300 V DC
Max. connection range	AWG26-12 (0.1-4.0 mm ²)
Surge protection	Varistor
Turn-on current limit	Thermistor

output

Connection system	Screw connection
Control at 10...100% load	1 %
Control at input voltage	0.8 %
Mains failure bridge-over time for 115 V AC	30 ms
Mains failure bridge-over time for 230 V AC	180 ms
Max. capacitance at output	10000 µF
Max. connection range	AWG26-12 (0.1-4.0 mm ²)
Max. output power	55 V
Max. residual ripple	< 50 mV
Output current	2.3 A
Output voltage	24...28 V DC
Overload protection	/ thermal cut-out

output

Parallel connection option No

General data

DIN Rail compatibility TS 35
 Degree of efficiency at max. load 78 %
 EMC standards IEC 61000-6 /-2, -3
 Housings metal
 Low Voltage Directive 73/ 23/ EWG
 Power factor correction No
 Standards EN 50178, EN 60950, IEC950
 Status indication Green LED
 Switching frequency 100 kHz
 Weight 478 g
 Ambient temperature (operational) -20 °C...+40 °C
 Storage temperature -40 °C...+85 °C

Insulation coordination

Galvanic isolation, I/O rail 3 kV
 Galvanic isolation, input-earth 1.5 kV
 Galvanic isolation, input-output 3 kV
 Galvanic isolation, output-earth 0.5 kV
 Humidity at operating temperature 20 - 85% RH without condensation
 Humidity at storage temperature 20 - 90% RH
 Protection class IP 20

Dimensions

Clamping range, max. 4 mm²
 Clamping range, min. 0.1 mm²
 Clamping range, nom. 4 mm²
 Length 131 mm
 Height 98 mm
 Width 57 mm

Approvals

Approvals institutes



Classifications

ETIM 2.0 EC001039
 ETIM 3.0 EC001039
 eClass 4.1 27-24-04-10
 eClass 5.0 27-24-22-13
 eClass 5.1 27-24-22-13

Similar products

Order No.	Part designation	Version
9925340024	CP SNT 160W 24-28V 6.5A	Switched-mode power supplies, Min. 85/138 V AC, max. 195/250 V AC, typ. 115...230 V AC , single-phase, 24...28 V DC
9916250024	CP SNT 300W 24V 12.5A	Switched-mode power supplies, 86...265 V AC, 100...200 V DC; type 115...230 V AC , single-phase, 22...28 V DC adjustable
9927480005	CP SNT 55W 5V 3A	Switched-mode power supplies, 85...265 V AC, 120...300 V DC , single-phase, 5 V DC
9925340012	CP SNT 160W 12-15V 8A	Switched-mode power supplies, Min. 85/138 V AC, max. 195/250 V AC, typ. 115...230 V AC , single-phase, 12...15 V DC
9927480012	CP SNT 55W 12-15V 3A	Switched-mode power supplies, 85...265 V AC, 120...300 V DC , single-phase, 12...15 V DC
9925340005	CP SNT 160W 5V 8A	Switched-mode power supplies, Min. 85/138 V AC, max. 195/250 V AC, typ. 115...230 V AC , single-phase, 5 V DC
9927480048	CP SNT 55W 48V 1.04A	Switched-mode power supplies, 85...265 V AC, 120...300 V DC , single-phase, 48 V DC
9925340048	CP SNT 160W 48V 3.5A	Switched-mode power supplies, Min. 85/138 V AC, max. 195/250 V AC, typ. 115...230 V AC , single-phase, 48 V DC

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Modular Power Supplies](#) category:

Click to view products by [Weidmuller](#) manufacturer:

Other Similar products are found below :

[73-147-000](#) [73-270-000](#) [73-316-4020](#) [73-317-0005](#) [73-495-0333](#) [73-961-4086-G2](#) [GLD150-48-103-G](#) [PS3E-B12F](#) [PS3E-E12F](#) [AS300-MLF](#)
[OVS-12E](#) [OVS-12F](#) [OVS-12J](#) [OVS-15F](#) [OVS-15J](#) [IVS13Q2Q1F4LL030ANJCUNR32](#) [LB115S48KH](#) [FP2-PSA1](#) [PS3E-F12F](#) [IMP4-3O1-](#)
[2J1-05-B-662](#) [UPS40-3003](#) [LB240S48KH](#) [LMM409 CHASSIS](#) [LPM615-CHAS](#) [ADNB008-48-1PM-C](#) [ADNB017-24-1PM-C](#) [ADNB040-24-](#)
[1PM-C](#) [VAS003ZG](#) [ADNB050-12-1PM-C](#) [ADNB040-15-1PM-C](#) [ADNB034-12-1PM-C](#) [73-166-000](#) [73-271-000](#) [73-961-4085-G2](#) [73-962-](#)
[0001](#) [OVS-15G](#) [1-155777G](#) [OVS-24F](#) [OVS-5F](#) [73-551-5086](#) [73-554-4047](#) [73-670-0001I](#) [73-713-001](#) [73-769-003](#) [73-546-001](#) [73-954-](#)
[0001C-G2](#) [73-951-0001S-G2](#) [73-560-434](#) [73-180-0001I](#) [73-554-4045](#)