

CP SNT 24W 5V 2A

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-2083
 www.weidmueller.com



One-phase switched-mode power unit in installation housing in performance classes 24 and 48 W. .
 The INSTA power units can be universally deployed because of their wide input range from 85 V AC to 265 V AC.
 They are available with output voltages from 5 V to 48 V.

General ordering data

Order No.	9928890005
Part designation	CP SNT 24W 5V 2A
Version	Power supply, switch-mode power supply unit, 5 V
GTIN (EAN)	4032248217526
Qty.	1 pc(s).

CP SNT 24W 5V 2A

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-2083
 www.weidmueller.com

Technical data

Dimensions (1)

Length	62.5 mm	Width	52 mm
Height	90.5 mm		

temperature

Ambient temperature (operational)	Storage temperature	-40 °C...+85 °C
-----------------------------------	---------------------	-----------------

Input

Conductor connection system	Screw connection	DC input voltage range	120...300 V DC
Input current	460 mA @ 115 V AC; 250 mA @ 230 V AC	Input current at 115 Vac	460 mA RMS ± 20%
Input current at 125 Vdc	235 mA ± 20%	Input current at 250 Vdc	120 mA ± 20%
Input frequency	50/ 60 Hz	Input fuse	2 A time-lag fuse (internal)
Input voltage (voltage mode input)	85...265 V AC, 120...300 V DC	Input voltage range AC	85...265 V AC
Surge protection	Varistor	making current limit	Thermistor

output

Conductor connection system	Screw connection	Control at 10...100% load	0.5 %
Control at input voltage	0.2 %	Mains failure bridge-over time	35 ms @ 115 V AC / 160 ms @ 230 V AC
Mains failure bridge-over time for 115 V AC	35 ms	Mains failure bridge-over time for 230 V AC	160 ms
Max. capacitance at output	8000 µF	Max. residual ripple	< 2 %
Output current	2 A	Output power, max.	10 W
Output voltage	5 V	Output voltage type	DC
Overload protection	Surge current / thermal cut-out	Surge protection	Varistor

General data

Ambient temperature (operational)	DIN Rail compatibility	TS 35
Degree of efficiency at max. load	EMC standards	EN 61000-6 /-2, -3
Mounting position, installation notice	Standards	EN 50178 EN 60950 IEC950
Ambient temperature (operational)		

Insulation coordination

electrical isolation, I/O rail	4 kV	electrical isolation, input-earth	1.5 kV
electrical isolation, input-output	3 kV	electrical isolation, output-earth	0.5 kV

Connection data

Clamping range, nom.	4 mm ²	Clamping range, min.	0.08 mm ²
Clamping range, max.	4 mm ²		

Approvals

Approvals institutes	CSA; GOSTME25; CE
----------------------	-------------------

Classifications

eClass 6.0	27-04-90-04
------------	-------------

CP SNT 24W 5V 2A**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-2083

www.weidmueller.com**Technical data****Notes**

Note, technical data

Derating loss: 33% @ 60°C The internal varistor found in a switch-mode power supply does not replace the need for surge protection within a system.


Datasheet

CP SNT 24W 5V 2A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com

Drawings

Electric symbol



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Modular Power Supplies](#) category:

Click to view products by [Weidmuller](#) manufacturer:

Other Similar products are found below :

[73-147-000](#) [73-270-000](#) [73-316-4020](#) [73-317-0005](#) [73-495-0333](#) [73-961-4086-G2](#) [GLD150-48-103-G](#) [PS3E-B12F](#) [PS3E-E12F](#) [AS300-MLF](#)
[OVS-12E](#) [OVS-12F](#) [OVS-12J](#) [OVS-15F](#) [OVS-15J](#) [IVS13Q2Q1F4LL030ANJCUNR32](#) [LB115S48KH](#) [FP2-PSA1](#) [PS3E-F12F](#) [IMP4-3O1-](#)
[2J1-05-B-662](#) [UPS40-3003](#) [LB240S48KH](#) [LMM409](#) [CHASSIS](#) [ADNB008-48-1PM-C](#) [ADNB017-24-1PM-C](#) [ADNB040-24-1PM-C](#)
[VAS003ZG](#) [ADNB050-12-1PM-C](#) [ADNB040-15-1PM-C](#) [ADNB034-12-1PM-C](#) [73-166-000](#) [73-271-000](#) [73-961-4085-G2](#) [73-962-0001](#)
[OVS-15G](#) [1-155777G](#) [OVS-24F](#) [OVS-5F](#) [73-551-5086](#) [73-554-4047](#) [73-670-0001I](#) [73-713-001](#) [73-769-003](#) [73-954-0001C-G2](#) [73-951-](#)
[0001S-G2](#) [73-560-434](#) [73-180-0001I](#) [73-554-4045](#) [73-956-0001S-G2](#) [73-963-0048-G2](#)