Enclosure systems and accessories
Klippon® Protect
Let's connect.

Version 2020

Weidmüller

Our Orange Selection
Quick and easy planning

To enable you to react quickly and easily to the requirements of your industrial environment, we have defined a core portfolio of more than 1,500 articles for you – our Orange Selection. The Orange Selection articles are tailored to one another and cover your standard requirements comprehensively.

All Orange Selection articles are "stock items": If you order by 3 p.m., your order will already be on the way the next working day! For even more efficient planning and production processes, we have marked all articles in our online product catalogue **catalog.weidmueller.com** as "always available" and stored the digital product data for the entire range.

By the way: the Orange Selection is of course also available in the Weidmüller Configurator **www.weidmueller.com/configurator**. Our powerful engineering software guides you intelligently and reliably through your selection and configuration process.

Further information and links to our services can be found at:
www.weidmueller.com/orange-selection

Dear Customers,

The PDF versions of our catalogues offer practical additional functions, helping you to find your way around our product range and simplifying the ordering process.

In addition to the catalogue, the PDF also contains:
- Internal page links
- Links to the online catalogue

Try it out for yourself. Click the order number to obtain more detailed information and close-up images via you web browser. The links in the PDF file also enable you to go directly to the next desired catalogue page.

Further Weidmüller product catalogues can be accessed by clicking the following:

Enclosure systems and accessories
Catalogue 5

Enclosure systems and accessories

Introduction

Klippon® Protect

Enclosures

Cable entries

Cable entry system

Tools

Appendix

Service and support

Technical appendix

Index Search according to type or order number

Enclosures systems and accessories

Introduction
Page A.2

Klippon® Protect
Page B.2

Klippon® TB
Page C.10

Klippon® EBi
Page C.48

Klippon® STB
Page C.64

Klippon® K
Page C.92

Klippon® POK
Page C.128

TBF Range
Page C.168

MPC Range
Page C.176

FPC Range
Page C.184

Standard cable glands - Plastic
Page D.6

Standard cable glands - Brass
Page D.8

Cable glands for HDC RockStar®
Page D.10

EMC cable glands
Page D.11

Cable glands - stainless steel
Page D.13

Klippon® Cable glands
Page D.27

Accessories - Lock nuts
Page D.40

Accessories - IP washer
Page D.45

Accessories - Shrouds
Page D.50

Blanking plugs
Page D.53

Compensating elements
Page D.59

Cable entry system
Page E.2

Tools
Page F.2

Introduction

Introduction	Introduction	A.2
	Klippon®	A.4
	Klippon® Services	A.6

Digitalisation presents you with many new challenges
We will support you to master them

The social and economic changes being caused by digitalisation are also pushing industrial production towards new, data-based services that need to be integrated into the value creation chains in a profitable manner.

Our objective is to support you with the implementation of these new structures and processes right from the start, and to successfully accompany you on new paths in the Industry 4.0 era.

Thanks to the entire range of Weidmüller products, the use of our local production and assembly facilities, and our global sales network, we can lay the very best foundations for a successful partnership with you, our customer.

Whether decentralisation, modularisation, data consistency and transparency or the implementation of completely individual applications in the IoT environment: the factory of the future needs to be able to take on a wide variety of challenges.

With our Klippon® products and services, we have created innovative and future-oriented solutions while setting new standards for applications within a wide range of industries.

More information about our Klippon® products and services at www.weidmueller.com/KlipponProtect

Dive into the Klippon® world and discover our innovative products and services.

It's Klippon®
Bringing excellence together

For more than 50 years, Klippon® has been synonymous with innovation, competence, and quality of products and services in the automation technology. Klippon® Services is the most recent extension to the well known, proven Klippon® Connect and Klippon® Protect products. Klippon® Services provides innovative software and assembly services. With Klippon® we are your reliable partner throughout the complete value creation process. Create your competitve advantage with Klippon®.

Your special advantages:
The flexible Klippon® Protect enclosure system is the perfect addition to our Klippon® Connect range of terminal blocks. You can rely on our mounted enclosures to offer a custom fit to your requirements and provide excellent protection. Klippon® Services completes our products range with optimal support for your processes.

Klippon® Services combines consultancy, planning, application expertise and industry know-how. You benefit from our one-stop production services. Thereby you will reduce costs, increase efficiency, and simplify quality management. We guarantee quick, quality-focused production and order-based availability. We deliver even individually assembled products anywhere within a short time.

Klippon® Connect offers a wide range of tailored application products, universal terminals and in-process services. A complete range of standard solutions and application-specific products, including all conventional connection technologies and functions for your individual application.

With Klippon® Protect, you can choose from a wide range of universal and application-specific enclosures. These products cover all relevant approvals required for use in industrial and explosive risk zones. They are flexible enough for optimal adaptation to your requirements.

Klippon® Services – expertise for your requirements

Our service connects worldwide

Planning, engineering, and production processes have to be completed with ever greater speed, precision, and efficiency. Such an increase in efficiency needs innovative tools and processes that optimally support the entire process of product creation and assembly.

With Klippon® Services, we offer a comprehensive, digitalised support for planning and developing, offering and ordering, and assembly and delivery of your distinct product.

By bringing together the entire value chain – backed by efficient software tools, extraordinary expertise, and a technologically leading production – we are answering your requirements concerning a future-orientated, ready-to-install assembly.

Your special advantages:
One-stop configuring, ordering, and delivery of the assembled product: With Klippon® Services you benefit from greater flexibility in your project business. Our services span from reliable planning and professional engineering to manufacturing in perfect quality.

An order will dispatch after just four days from Germany when a certain service level is selected. Order quantities start at one.

Configuration and ordering are simple with the Weidmüller Configurator
www.weidmueller.de/wmc

Fast Delivery Service
Obtain offers 24/7 and within minutes, including directly orderable article numbers. The Weidmüller Configurator (WMC) for planning and configuration is key for consistent processes.

Engineer to Order
We offer highly qualified engineering service for standard or modified products.

Customised Solutions
Our extensive customer consulting, powerful project management, and flexible production enable individual, customised solutions.

Efficient digital engineering

Weidmüller Configurator (WMC) integrates CAE access and direct offer

The choice is yours

Within Klippon® Services the WMC supports you step-by-step as you select and configure your assembled terminal strips and an extensive range of enclosures, including accessories and further Weidmüller products. You decide whether you want to carry out the complete configuration in WMC or whether you want to import data sets from your CAE system and simply transfer them back again after making final adjustments in the WMC. Whichever way you decide to go, you will benefit from centralised documentation that is always up to date, you will avoid transmission errors and you will no longer have to share your sensitive data with a third party. Using STEP, the universal 3D CAD exchange format, you can now also export your WMC solution directly into your CAE system, ensuring complete data consistency in all your systems.

Your special advantages:
Configuration is simple, safe, and convenient because of user-friendly operation, distinct design, and integration in your engineering workflows from planning with CAE to documentation.

Three reasons to start using the Weidmüller Configurator now:

1. Proven configuration designs in real 3D
Digital product information is based on the classification standard eCl@ss advanced. An integrated plausibility and collision control with full digital documentation ensure that your configuration is 100 % reliable.

2. Seamless CAE integration
ntegrated interfaces facilitate the simple import and export of product data between the WMC and all commonly-used engineering tools, such as Zuken E³ or EPLAN Electric P8.

3. Interfaces for automated manufacturing
The WMC provides all necessary digital information for a full automation, such as subsequent assembly, marking with M-Print® PRO, and wiring. This is the key for the fast delivery service.

Configuration and ordering are simple with the Weidmüller Configurator
www.weidmueller.com/wmc



Full engineering support
The product data can be used in engineering systems such as EPLAN Electric P8 or Zuken E³. series. 3D models are available for panel set-up.



Helpful wizard system
The intelligent wizard function documents every step in which a component is assembled and only allows permissible configurations. Mistakes are corrected automatically.



Integrated request function
The selected components can be requested directly – as individual components, pre-installed on a terminal rail, or as an assembled enclosure.

Klippon® Services – focus on your core business

"Fast Delivery Service" enables short-term delivery of assembled products

Today you are confronted with tough challenges in mechanical and plant engineering as well as in control cabinet production. On the one hand, the production of your products is becoming increasingly made to order/ custombuilt and a lot more complex. On the other hand, you have to deal with high price pressures, tight deadlines and short-term change requests. In addition, many products are requested in small quantities.

To meet these growing demands, you need ever more efficient planning and manufacturing processes - and you need to be able to rely on 100% fast and reliable delivery. With our Fast Delivery Service, we offer you both. The integrated concept simplifies your planning, accelerates your manufacturing processes and guarantees the delivery of individually assembled and ready-to-install terminal strips or enclosures within the shortest possible time. In this way, you reduce your costs, increase your flexibility and stay one step ahead of your competitors.

Klippon® Connect and Klippon® Protect
Assembled enclosures with terminal strip, add-on components and optional Ex approval.

Klippon® Protect
Individual empty enclosures with holes, threads or cut-outs according to your specifications – optionally unassembled, equipped or with add-on parts.

WMC – Digital Engineering
Our Weidmüller Configurator (WMC) gives you access to the "Fast Delivery Service". You can import directly your CAE data.



Klippon® Connect
Ready-to-install assembled terminal strips including electronic components - individually manufactured according to your specifications.

Determine your own delivery time thanks to Fast Delivery Service

We offer the choice between 3 service levels

Your assembled product

Simply configure your assembled terminal strip, your empty enclosure or your assembled enclosure with our **Weidmüller Configurator.**

Fast Delivery

The ideal solution for very demanding delivery schedules

- **5* Day Delivery europe-wide**
- Selected product range

- **10* Day Delivery europe-wide**
- Wide range of products

* Valid for orders from Germany

Fast Offer

Fast price for full bandwidth

- Individual configuration
- Direct offer

Added value

Offer provided in minutes

Available 24/7, including order numbers for direct ordering

Assembly in quantities of 1

Ready-to-install assembly that meets your individual specifications

Reliable delivery

Automated manufacturing and direct shipment from Germany

Your advantages at a glance

with our Fast Delivery Service

Reduce your costs

Your plants are becoming more and more specific and complex. Therefore, you have to stock many required components in your warehouse. With Fast Delivery, you receive complete assembled products – and can significantly minimise your purchasing and storage costs.

Increase your flexibility

More and more often you have to manufacture small quantities of plants and be prepared for shortterm changes. With Fast Delivery, you get individual terminal strips and enclosures from batch size 1 – and you receive them ready for installation. This increases your flexibility.

Meet your delivery commitments

You must complete and deliver your individual plants within tight time frames. Otherwise, your customers face high costs due to delays and production downtimes. With Fast Delivery, you can speed up all your processes and reliably meet your delivery commitments.

With Klippon® Services you benefit from optimal support

"Engineer to Order" – applications, based on your design

In a globally-orientated world, automation technology functions are becoming more complex by facing ambitious goals toward energy efficiency and smart production. We are your reliable partner for the best connections in Industrial Connectivity with our standard or customised products.

Planning
You can rely on the support of our worldwide network of industrial managers, who know the challenges you face and who can assist with your particular applications.

Engineering
After receiving your requirements, our experts analyse together with you the individual application and start the development process.



Worldwide engineering network
Within our global engineering network, we are combining our expertise with your requirements – worldwide. This expertise allows us to assist you with advice and planning support toward resolving together the everyday challenges of your applications.

Klippon® Services – plan, install, operate
Individual projects need "Customised Solutions"

Our drive is your efficiency. Therefore we accompany you in all phases of your individual project and continuously develop our Klippon® Services product range. Throughout the entire duration of the project, professional project management is at your side so that you know that your products are in good hands up to delivery and beyond. The result are tailor-made products that are precisely tailored to the specific requirements of your project.

Designing and Prototyping
Engineers create design studies and prototypes together with our experienced designers.

Consulting
Our application experts advise you on the development of your individual project solution.

Planning
A flexible, automised production process ensures high quality products, whether standard or customised.

Operation
Count on our solution-orientated after sales service combined with a complete traceability of the assembled products.

Installation
Reduce your single part orders and stock while we focus on your final product.

Assembly
We combine excellent products for your individual solution. Bringing added value for you and your customers.

Manufacturing expertise at the highest level
Precision and reliability for your products

Our engineering and manufacturing expertise influences decisions in all areas of modern connection technology. It therefore plays an integral part of every solution. A variety of customised configurations can be constructed and produced at our worldwide assembly facilities according to individual requirements. All this based on maximum process and manufacturing reliability.

Continuous data management enables automated production and makes Industry 4.0 tangible.



Automated processes – here shown for our Klippon® TB enclosure range – ensures a reliable and consistent production process.

Whether you need modified products, pre-assembled terminal rails or complete devices for individual applications: we produce the solutions developed for your application quickly and flexibly.

When quality is the key

You demand perfection – we take care of every detail

In the face of the international competition, you demand that all your equipment meets high safety, quality, and performance standards. Our products and services will support you to achieve these goals. We support you to advance new ideas that provide real value for your plant operation. After over 50 years of experience, we can determine the ideal combination of electrotechnical components which best suit your plant. We take into account your plant's specific conditions, including the local standards at its operation site. That's our definition of service.

Our laboratory assures the high quality and functionality of products.



Right from the start, we check exactly which components, materials, and systems are suitable for your application.

With our state-of-the-art processing technology, we ensure the highest quality during production and assembly.

We guarantee fast, quality-orientated production and order-ready product availability.

Klippon® Protect

Klippon® Protect	Universal program	B.2
	Application program	B.4
	Industrial applications	B.6

Klippon® Protect
Safety and protection for connection solutions

We designed the Klippon® Protect enclosure ranges to satisfy the extraordinary protection requirements for field applications. They provide outstanding high-performance features that satisfy the toughest demands within every industry and every application. The universal enclosures Klippon® Protect are made of stainless steel, aluminium, or plastic. Either one guarantees excellent protection for your assembly. With these robust enclosures, you can implement various field applications to suit your requirements. The matching system accessories enable simple integration, expansion, and customisation.

Your special advantages:
- Innovative enclosure concepts for outstanding performance even under extreme environmental conditions
- Robust and secure enclosure with optimised sealing system for the most stringent of protection requirements
- Klippon® Protect products are approved based on the most stringent international quality and safety standards

Reliable protection
The Klippon® TB has an integrated duct keeping contamination and moisture from penetrating when the enclosure is open. The outer earthing bolt is equipped with an IP67-certified seal mechanism and is protected against accidental rotation.



Temperature and sealing characteristics
All Klippon® TB and Klippon® STB enclosures are equipped with a silicone seal. It protects applications in extreme temperature conditions.



Versatile lid design
The TBF, FPC and MPC enclosures are available with either transparent or grey lids.

High IP protection
The Klippon® K aluminium enclosures are equipped with fully closed seals without adhesive points. The seal ensures an IP protection level from IP66 and up to IP68 – subject to use.

Closed moulded gaskets
The Klippon® POK polyester enclosures gaskets are made of either silicone or chloroprene. The robust and secure sealing enhances ingress protection and increases the performance of each enclosure.

Cable Glands and Cable Entry Systems: perfectly fulfiling your application needs

We offer a variety of add-on components such as cable glands for a multitude of purposes and applications in addition to our extensive Klippon® Protect range. The supplementary cable entry system Cabtite allows connecting a pre-assembled cable to an installation enclosure or cabinet.

Klippon® Protect
Proven solutions for your application

The Klippon® Protect solutions offer a wide range of standard industrial applications and explosive environments applications. The following overview of our Klippon® Protect range will give you an insight into its possibilities, including finding an individual solution.

Application range
Our Klippon® Protect application range provides solutions for monitoring and safety, measurement and control technology, and power distribution. These application solutions are based on high quality and comprehensive approvals for explosive risk zones.

Your special advantages:
- Terminal boxes, command and signalling devices as well as electronic boxes in a consistent enclosure design
- Extremely wide range of standard solutions for maximal safety, reliable functionality and low follow-up costs for maintenance, replacement and storage
- Certified to international standards for explosive risk zones and standard industrial applications such as automation, transportation and energy



Power distribution boxes and interfaces
In a complex environment, the efficient and reliable distribution of electrical energy requires optimally designed interface solutions that respond to the special features of the application. Our high-current terminal solutions offer an excellent interplay with our certified terminals with weather-resistant Klippon® Protect enclosures.

Monitoring and Safety
Through the assembly of units, we provide a myriad of monitoring and safety solutions; including proximeters for vibration measurement, temperature transmitters for monitoring of operating temperature, and eddy current sensors for non-contact distance measurement chains.



Measurement and Control systems
Tailored to your respective requirements, the Klippon® Control Station combines control devices and status displays with various electronic components. You receive a turnkey plug-and-play solution – including all required approvals.

Harmonisation – the key to market success

Klippon® Protect is individually tailored to meet the changing and extremely harsh environments of the different industries. Certified to international standards, they also meet the latest ATEX and IECEx regulations for potentially explosive atmospheres in process industries. They have certifications for use in various standard industrial applications, such as automation, railway, transportation, and energy.

Benefit from innovative automation concepts as a success factor

Klippon® products for better performance and more efficient processes

The advancing digitalisation of industrial manufacturing processes places ever higher demands on automation technology. Decentralised systems with high flexibility and easy operation are trend. System design, installation process, and plant operation are becoming more complex.

Klippon® products and services are optimally adapted to the requirements of modern automation concepts. They combine highest quality with excellent flexibility and performance – and thus become an integral part of your automation solutions. In the versatile Klippon® product portfolio you will find everything you need to optimise your production systems. The choice is yours.

Your special advantages:

- Wide range of products and services for every application
- Optimised for convenient planning, simple installation and efficient maintenance
- Highest product quality for reliable function and high durability
- Tested safety and conformity to standards
- Perfectly suited for flexible, decentralised automation concepts

Klippon® K
Klippon® K aluminium enclosures ensure a high level of system availability as well as the quick commissioning of your machines. Excellent shock, vibration, and temperature resistance combined with corrosion-resistant materials and surfaces make these enclosures particularly secure and long-lasting.

Klippon® EBi
Klippon®EBi stainless steel enclosures are suitable for both indoor and outdoor use, and can be combined with Klippon® Connect and Klippon® Protect components. They are extremely corrosion resistant and insensitive to dust and spray water. Ideally suited to the decentralised control of your system.

Cabtite
The Cabtite cable management system allows for quick cabling adjustment in the event of system modifications or during service and maintenance work. Modular components guarantee maximum flexibility while simultaneously ensuring a high level of protection.

Increase efficiency and reliability in transportation

Klippon® Protect enclosure solutions for the mobility of the future

Mobility is becoming more and more important within our society. Increasing globalisation is also bringing rapid growth in the transportation of people and goods between continents. As a result, there is demand for particularly efficient and reliable solutions in the transportation sector.

With secure connection solutions and tailor-made, individually configurable components, we are making a decisive contribution to the transport of the future. Our solutions are certified to the latest industry standards. They are produced using state-of-the-art manufacturing methods and stand for quality, durability and reliability.

Your special advantages:

- Particularly robust and long-lasting solutions
- Future-proof thanks to certification to the latest industry standards
- Resistant to an extremely wide range of external influences
- Optimally suited to the harsh environments typical of the rail and shipping industries
- Versatile use in the entire transport sector



High-current terminal solutions
Our high-current terminals are resistant to vibration, shock, and climatic conditions, making them ideal for use in engine compartments or on train bogies, for example. They can withstand large mechanical stresses and are characterised by their high electromagnetic compatibility.

Klippon® K
Our robust and resistant enclosures feature IP protection from IP66 to IP68, according to requirements. The customer-specific production in our Application Centers ensures quick assembly and a low risk of failure.

Klippon® STB
Extreme stability and corrosion resistance ensure the secure protection of devices and control components even in the harsh environments that are typical of the rail and shipping industries. Optimal sealing properties allow for use in extreme temperature ranges of between -60°C and +100°C.

Comply with international standards in the energy supply sector

Efficient and safe solutions with Klippon®

Alongside renewable energies such as wind and solar, the generation of energy from gas, coal and nuclear power will remain a key part of the world's energy mix for a long time to come. Our range of products therefore also features solutions for the specific requirements of the traditional energy sector.

With our complete solutions for all types of energy generation and supply, we can help you to guarantee the safe and reliable operation of your systems while also ensuring maximum availability. We provide you with the right Klippon® products for industrial solutions, harsh environments, explosive risk zones and safety-relevant applications – naturally with all of the market-specific certifications and approvals.

Your special advantages:

- International approvals and certifications
- Modified products for industry-specific requirements
- High resistance to weathering and corrosion
- Resistance to vibration, shock, and climatic conditions
- Compliance with explosion protection guidelines



Customer-specific solutions
Klippon® products are modified, assembled and approved in line with the respective sector. They comply with all of the required standards and guidelines on explosion protection and are resistant to vibrations, shock, and climatic conditions. For safe use in containment or non-containment areas.

Robust plastic enclosure
Klippon® plastic enclosures are extremely resistant to weather and corrosion, making them perfectly suited for use in the photovoltaic sector. International approvals and standards guarantee maximum security.

Intelligent accessories
Cable glands in protection classes IP54 to IP66, IP67 and IP69k are available as accessories. These cable glands are suitable for the most diverse applications and also cover high temperature ranges.

Safely control work processes in hazardous areas on site

Certified Klippon® Protect control and display elements

Global demand for energy sources is on the rise. This presents a range of new challenges for the process industry: from research into new energy sources through to their processing and consumption.

Klippon® products satisfy these requirements with innovative technologies and active safety concepts. They ensure secure connections between the interfaces for different areas and guarantee safe, effective, and sustainable operation within the processes. Klippon® Protect control and display elements support all areas of automation within the process industry.

Your special advantages:

- Innovative control and display elements for an extremely wide range of automation applications
- Robust enclosure solutions with comprehensive protection for the assembled components
- Convenient independent engineering with the Weidmüller Configurator
- Professional advice during the engineering process on request
- Certified products that comply with the latest local and international standards including ATEX and IECEx.

Klippon® Control Station
The robust "on-site control station" is available in customer-specific optimised versions, with different enclosure materials and assembled components. Perfect for individual project solutions with international approvals for explosive risk zones.

Klippon® TB
The robust enclosures with electro-polished surfaces are perfectly suited to harsh environments, e.g. for use as distributor enclosures in offshore, food and beverage applications. The sealing system can withstand high operating temperatures and offers IP66/67 protection against moisture and dust.

Klippon® Services
Order specific enclosure solutions with explosion protection for your application, and make the most of the professional consulting and engineering services offered by our advisors – or carry out the engineering work yourself using the Weidmüller Configurator.

Enclosures

Enclosures	Introduction	C.2
	Klippon® TB enclosure series	C.10
	Klippon® TB MH – Multi Hinge	C.12
	Klippon® TB QL – Quarter Lock	C.38
	Klippon® TB FS – Fixing Screw	C.40
	Klippon® Protect – Terminal Boxes Steel – Klippon® TB	C.42
	Klippon® EBi QL – Quarter Lock	C.48
	Klippon® STB – Sheet steel enclosures	C.64
	Klippon® Protect – Terminal Boxes Steel – Klippon® STB	C.76
	Klippon® Control Station – Steel enclosures – Klippon® STB	C.82
	Klippon® K – Aluminium enclosures	C.92
	Klippon® Protect – Terminal Boxes Aluminium – Klippon® K	C.116
	Klippon® Control Station – Aluminium enclosures – Klippon® K	C.118
	Klippon® POK – Polyester enclosures	C.128
	Klippon® Protect – Terminal Boxes Polyester – Klippon® POK	C.150
	Klippon® Control Station – Polyester enclosures – Klippon® POK	C.158
	TBF – Polyester enclosures	C.168
	MPC – Polycarbonate enclosures	C.176
	FPC – Polycarbonate enclosures	C.184

Metal enclosures

	Klippon® TB MH	Klippon® TB QL	Klippon® TB FS	Klippon® EBi QL
	Ex	Ex	Ex	
Material	Stainless steel	Stainless steel	Stainless steel	Stainless steel
Material Specification	Stainless steel 1.4404 (316L), enclosure 1.50 mm	Stainless steel 1.4404 (316L), enclosure 1.50 mm	Stainless steel 1.4404 (316L), enclosure 1.50 mm	Stainless steel 1.4301 (304), enclosure 1.50 mm, (1.25 mm)
Sea water resistance	very good	very good	very good	very good
UV resistance	very good	very good	very good	very good
Halogen free / cadmium free	x / x	x / x	x / x	x / x
Surface finish	electropolished	electropolished	electropolished	Brushed – grain size 240
Intended use	Explosive hazard areas, offshore, oil and gas industry, chemical industry, process industry	Explosive hazard areas, offshore, oil and gas industry, chemical industry, process industry	Explosive hazard areas, offshore, oil and gas industry, chemical industry, process industry	Machine construction, transport, power
Dimensions				
H x W x D (min.) in mm	229x152x133	229x152x133	229x152x133	300x200x150
H x W x D (max.) in mm	980x740x200	980x740x200	980x740x200	800x600x220
Geometry	3 standard depths	3 standard depths	3 standard depths	2 standard depths
Specific characteristics				
Gland plates	0,1,2,3,4	0,1,2,3,4	0,1,2,3,4	0,1
Type of gasket	Flat gasket	Flat gasket	Flat gasket	Flat gasket and foam seal
Seal material	Silicone	Silicone	Silicone	EPDM, polyurethane (PUR) foam
Enclosure attachment	4 or 6 mounting feet with 11 mm hole size	4 or 6 mounting feet with 11 mm hole size	4 or 6 mounting feet with 11 mm hole size	Direct mounting (9 mm mounting holes on rear wall) or via mounting feet (optionally available)
Installation mounting	4 or 6 mounting bolts with M6 threaded holes	4 or 6 mounting bolts with M6 threaded holes	4 or 6 mounting bolts with M6 threaded holes	Welded mounting bracket
Temperature range	-60 °C...+135 °C (IP66) -60 °C...+105 °C (IP67)	-60 °C...+135 °C	-60 °C...+135 °C (IP66) -60 °C...+105 °C (IP67)	-40 °C...+85 °C
Impact resistance	IK 09 (10J) in accordance with DIN EN 50102 / 7J in accordance with IEC 60079-0	IK 09 (10J) in accordance with DIN EN 50102 / 7J in accordance with IEC 60079-0	IK 09 (10J) in accordance with DIN EN 50102 / 7J in accordance with IEC 60079-0	IK 09 (10J) in accordance with IEC 62208
IP – protection class	IP66, IP67 /	IP66 /	IP66, IP67 /	IP66 /
NEMA protection class	Nema 3, Nema 4x, Nema 12	Nema 3, Nema 4x, Nema 12	Nema 3, Nema 4x, Nema 12	Nema 3, Nema 4x, Nema 5
Flammability rating				
Surface resistance (in ohms)				
Approvals				
ATEX	x	x	x	
AEx	x	x	x	
CCOE / INMETRO	In preparation / x	In preparation / x	In preparation / x	
cULus	x	x	x	x
EAC	x	x	x	
IECEx	x	x	x	
NEPSI / KOSHA	x / x	x / x	x / x	
RMR / LR / DNV GL	x / - / x	x / - / x	x / - / x	- / - / x
Configuration	Lid hinges Removable lid Gland plates Welded mounting feet Fitting for a padlock	Lid hinges Gland plates Welded mounting feet Quarter lock	Removable lid Gland plates Welded mounting feet	Lid hinges Gland plates Direct mounting, Optional mounting feet Quarter lock

	Klippon® STB		Klippon® K	
	Ex		Ex	
Material	Stainless steel	Sheet steel	Aluminium	
Material Specification	Stainless steel 1.4404 (316L) 1.50 mm	Powder-coated steel sheet 1.0330	High quality aluminium alloy (Al-Si12)	
Sea water resistance	very good	good	good	
UV resistance	very good	insufficient	very good	
Halogen free / cadmium free	x / x	x / x	x / x	
Surface finish	electropolished, Mirror-polish	powder-coated	neutral, powder-coated	
Intended use	Ex areas, packing industry, railways, shipping, process industry	Packing industry, railways, shipping, process industry	Ex-areas, process industry, transport, railways, shipping, port facilities, packaging, mechanical engineering	
Dimensions				
H x W x D (min.) in mm	120x120x80		50x45x30	
H x W x D (max.) in mm	250x400x130		230x280x111	
Geometry	5 standard depths		11 standard depths	
Specific characteristics	**Ex-version**	**Industrial version**	**Ex-version**	**Industrial version**
Gland plates	none	none	none	none
Type of gasket	Flat gasket	Flat gasket	Shaped gasket	Shaped gasket
Seal material	Silicone	Silicone	Silicone	Chloroprene, Silicone
Enclosure attachment	External holders with 8 mm holes	External holders with 8 mm holes	4 holes for M4 to M6 screws	4 holes for M4 to M6 screws
Installation mounting	20 mm C-rail welded to the enclosure	20 mm C-rail welded to the enclosure	M4 to M6 threaded holes	M4 to M6 threaded holes
Temperature range	-60 °C...+100 °C	-60 °C...+120 °C	-60 °C...+135 °C	-40 °C...+80 °C (CR); -60 °C...+135 °C (VMQ)
Impact resistance	7J in accordance with IEC 60079-0	IK 09 (10J) in accordance with DIN EN 50102	7J in accordance with IEC 60079-0	IK 09 (10J) in accordance with DIN EN 50102
IP – protection class NEMA protection class	IP66 / Nema 4, 4x	IP66	IP66, IP67 / Nema 4x	IP66, IP67, IP68 / Nema 4x
Flammability rating				
Surface resistance (in ohms)				
Approvals				
ATEX	x		x	
AEx	x			
CCOE / INMETRO	– / x			
cULus	x			x
EAC	x		x	x
IECEx	x		x	
NEPSI / KOSHA	- / x			
RMR / LR / DNV GL	x / x / x	x / x / –	x / – / x	x / – / x
Configuration				
	TAS 20 C-profile rail Welded mounting feet Earth studs in enclosure lid and base		Internal earthing screw in the enclosure base an external earth stud	internal earthing screw in the enclosure base

Plastic enclosures

	Klippon® POK		TBF	MPC	FPC
	Ex				
Material	Polyester		Polyester	Polycarbonate	Polycarbonate
Material Specification	Glass-fibre reinforced polyester in accordance with DIN 16913		Glass-fibre reinforced polyester, polycarbonate transparent cover		
Sea water resistance	very good		very good	very good	very good
UV resistance	good		good	good	good
Halogen free / cadmium free	x / x		x / x	x / x	x / x
Surface finish	Grey (industrial version), Black (Ex version)		grey	grey	grey
Intended use	Ex-areas, energy production, transportation, process industries, port facilities		Building installation, transportation, energy production, building sites, manufacturing industry, packaging industry	Building installation, transportation, energy production, building sites, manufacturing industry, packaging industry	Building installation, transportation, energy production, building sites, manufacturing industry, packaging industry
Dimensions					
H x W x D (min.) in mm	75x80x55		186x151x140	125x75x75	200x200x132
H x W x D (max.) in mm	250x600x120		603x603x175/210	250x175x150	600x400x132
Geometry	5 standard depths		3 standard depths	4 standard depths	1 standard depth
Specific characteristics	**Ex version (Black)**	**Industrial version (grey)**			
Gland plates	none	none	none	none	none
Type of gasket	Shaped seal	Shaped seal	O-ring	Foam seal	Foam seal
Seal material	Silicone	Chloroprene	Polyurethane	Polyurethane	Polyurethane
Enclosure attachment	4 holes for M4 to M6 screws	4 holes for M4 to M6 screws	4 holes or external mounting brackets (accessory)	4 holes or external mounting brackets (accessory)	4 holes or external mounting brackets (accessory)
Installation mounting	M4 to M6 threaded holes	M4 to M6 threaded holes	4 or 6 clamping screws M4	Self-tapping screws	Self-tapping screws
Temperature range	-55 °C...+100 °C	-40 °C...+100 °C	-50 °C...+130 °C (Continuous temperature max. 70 °C) (grey); -35°C ...+120°C ((Continuous temperature max. 70 °C) (transparent)	-50 °C...+100 °C (grey); -40 °C...+60 °C (transparent)	-50 °C...+100 °C (grey); -40 °C...+60 °C (transparent)
Impact resistance	7J in accordance with IEC 60079-0	IK 08 (5J) in accordance with DIN EN 50102	IK08 (5J) in accordance with IEC 62208, IK10 (20J) in accordance with IEC 62262	IK 08 (grey), IK 06 (transparent)	IK 08 (grey), IK 06 (transparent)
IP – protection class	IP66	IP66	IP66 (transparent lid) IP67 (grey lid)	IP66, IP67	IP66, IP67
Flammability rating	UL94 V0	UL94 V0	UL94 HB (grey), V2 (transparent)	V2	V2
Surface resistance (in ohms)	$<10^9$	10^{12}	10^{12}	10^{16}	10^{16}
Approvals					
ATEX	x				
AEx	x				
CCOE / INMETRO					
EAC	x	x			
cULus	x	x			
IECEx	x				
NEPSI / KOSHA	- / x				
RMR / LR / DNV GL	x / x / x	- / x / x			
Configuration					
	Fastening screws for the mounting plate		grey or transparent lid	grey or transparent lid	grey or transparent lid

Drawing design – For chapter C

The drawings contained in chapter C are constructed in the following way.

To identify the enclosure side views, these are marked with the letters A, B, C, D, E, and F. The schematic 3D representations shown underneath are of an enclosure that has been wall mounted.

F shows the view of the enclosure lid (front aspect),
E shows the interior surface of the enclosure (rear wall of the enclosure with the cover removed).
A shows the view of the enclosure from above and
B the view of the enclosure from underneath.
C shows the left and
D the right side of the enclosure.
E is the front view of the enclosure interior with the cover removed (enclosure rear wall).

You can find the dimensions of the enclosure sides for all enclosure sizes in each drawing.



A = Top
B = Bottom
C = Left
D = Right
E = Enclosure rear wall
F = Enclosure lid

Overview of dimensions

Klippon® TB MH – Multi Hinge / Klippon® TB QL – Quarter Lock / Klippon® TB FS – Fixing Screw

Page C.10

		Dimensions in mm Height x width x depth
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	229 x 152 x 133
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	260 x 260 x 150
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	260 x 260 x 200
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	306 x 306 x 150
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	306 x 306 x 200
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	350 x 260 x 150
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	350 x 260 x 200
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	400 x 300 x 150
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	400 x 300 x 200
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	458 x 382 x 150
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	458 x 382 x 200
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	480 x 480 x 150
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	480 x 480 x 200
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	550 x 350 x 150
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	550 x 350 x 200
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	620 x 450 x 150
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	620 x 450 x 200
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	762 x 508 x 150
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	762 x 508 x 200
Note		Additional enclosure sizes available on request.

Klippon® TB MH – Multi Hinge / Klippon® TB QL – Quarter Lock / Klippon® TB FS – Fixing Screw

Page C.10

		Dimensions in mm Height x width x depth
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	914 x 610 x 150
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	914 x 610 x 200
	Klippon® TB MH Klippon® TB QL Klippon® TB FS	980 x 740 x 200
Note		Additional enclosure sizes available on request.

Klippon® EBi QL – Quarter Lock

Page C.48

		Dimensions in mm Height x width x depth
	Klippon® EBi QL	300 x 200 x 150
	Klippon® EBi QL	300 x 300 x 150
	Klippon® EBi QL	300 x 300 x 220
	Klippon® EBi QL	400 x 300 x 150
	Klippon® EBi QL	400 x 300 x 220
	Klippon® EBi QL	400 x 400 x 220
	Klippon® EBi QL	500 x 400 x 220
	Klippon® EBi QL	500 x 500 x 220
	Klippon® EBi QL	600 x 400 x 220
	Klippon® EBi QL	600 x 600 x 220
	Klippon® EBi QL	800 x 600 x 220
Note		Additional enclosure sizes available on request.

Klippon® STB

Page C.64

	Dimensions in mm Height x width x depth
1.4404 (316L), mirror polished 1.4404 (316L), electropolished MS RAL 7032	120 x 120 x 80
1.4404 (316L), mirror polished 1.4404 (316L), electropolished MS RAL 7032	150 x 120 x 80
1.4404 (316L), mirror polished 1.4404 (316L), electropolished MS RAL 7032	150 x 150 x 90
1.4404 (316L), mirror polished 1.4404 (316L), electropolished MS RAL 7032	190 x 150 x 90
1.4404 (316L), mirror polished 1.4404 (316L), electropolished MS RAL 7032	190 x 190 x 100
 1.4404 (316L), mirror polished 1.4404 (316L), electropolished MS RAL 7032	250 x 250 x 120
1.4404 (316L), mirror polished 1.4404 (316L), electropolished MS RAL 7032	160 x 380 x 120
1.4404 (316L), mirror polished 1.4404 (316L), electropolished MS RAL 7032	250 x 400 x 130

Information on the net weight of the enclosures can be found in the online catalogue. MS: Mild steel

Klippon® K

Page C.92

	Dimensions in mm Height x width x depth
unpainted (S) unpainted (CR) RAL 7001 (CR) RAL 7001 (S)	45 x 50 x 30
unpainted (S) unpainted (CR) RAL 7001 (CR) RAL 7001 (S)	64 x 58 x 34
unpainted (S) unpainted (CR) RAL 7001 (CR) RAL 7001 (S)	64 x 98 x 34
unpainted Ex (S) unpainted (CR) unpainted (S) RAL 7001 Ex (S) RAL 7001 (CR) RAL 7001 (S)	70 x 70 x 45
unpainted Ex (S) unpainted (CR) unpainted (S) RAL 7001 Ex (S) RAL 7001 (CR) RAL 7001 (S)	80 x 75 x 57

Information on the net weight of the enclosures can be found in the online catalogue.

Klippon® K

Page C.92

	Dimensions in mm Height x width x depth
unpainted Ex (S) unpainted (CR) unpainted (S) RAL 7001 Ex (S) RAL 7001 (CR) RAL 7001 (S)	70 x 100 x 45
unpainted Ex (S) unpainted (CR) unpainted (S) RAL 7001 Ex (S) RAL 7001 (CR) RAL 7001 (S)	80 x 125 x 57
unpainted Ex (S) unpainted (CR) unpainted (S) RAL 7001 Ex (S) RAL 7001 (CR) RAL 7001 (S)	70 x 165 x 45
unpainted Ex (S) unpainted (CR) unpainted (S) RAL 7001 Ex (S) RAL 7001 (CR) RAL 7001 (S)	80 x 175 x 57
unpainted Ex (S) unpainted (CR) unpainted (S) RAL 7001 Ex (S) RAL 7001 (CR) RAL 7001 (S)	80 x 250 x 55
unpainted Ex (S) unpainted (CR) unpainted (S) RAL 7001 Ex (S) RAL 7001 (CR) RAL 7001 (S)	82 x 130 x 72
unpainted Ex (S) unpainted (CR) unpainted (S) RAL 7001 Ex (S) RAL 7001 (CR) RAL 7001 (S)	120 x 122 x 81
unpainted Ex (S) unpainted (CR) unpainted (S) RAL 7001 Ex (S) RAL 7001 (CR) RAL 7001 (S)	130 x 170 x 90
unpainted Ex (S) unpainted (CR) unpainted (S) RAL 7001 Ex (S) RAL 7001 (CR) RAL 7001 (S)	120 x 220 x 81
unpainted Ex (S) unpainted (CR) unpainted (S) RAL 7001 Ex (S) RAL 7001 (CR) RAL 7001 (S)	160 x 160 x 91

Information on the net weight of the enclosures can be found in the online catalogue.

Overview of dimensions

Klippon® K

Page C.92

		Dimensions in mm Height x width x depth
	unpainted Ex (S) unpainted (CR) unpainted (S) RAL 7001 Ex (S) RAL 7001 (CR) RAL 7001 (S)	**160 x 200 x 100**
	unpainted Ex (S) unpainted (CR) unpainted (S) RAL 7001 Ex (S) RAL 7001 (CR) RAL 7001 (S)	**160 x 260 x 91**
	unpainted Ex (S) unpainted (CR) unpainted (S) RAL 7001 Ex (S) RAL 7001 (CR) RAL 7001 (S)	**160 x 350 x 100**
	unpainted Ex (S) unpainted (CR) unpainted (S) RAL 7001 Ex (S) RAL 7001 (CR) RAL 7001 (S)	**230 x 280 x 111**

Information on the net weight of the enclosures can be found in the online catalogue.

Klippon® POK

Page C.128

		Dimensions in mm Height x width x depth
	RAL 7001 RAL 9011	**75 x 80 x 56**
	RAL 7001 RAL 9011	**75 x 110 x 55**
	RAL 7001 RAL 9011	**75 x 160 x 55**
	RAL 7001 RAL 9011	**75 x 190 x 55**
	RAL 7001 RAL 9011	**75 x 230 x 55**
	RAL 7001 RAL 9011	**120 x 122 x 91**
	RAL 7001 RAL 9011	**120 x 220 x 91**
	RAL 7001 RAL 9011	**160 x 160 x 91**
	RAL 7001 RAL 9011	**160 x 260 x 91**
	RAL 7001 RAL 9011	**160 x 360 x 91**

Information on the net weight of the enclosures can be found in the online catalogue.

Klippon® POK

Page C.128

		Maße [mm] Höhe x Breite xTiefe	Gewicht [g]
	RAL 7001 RAL 9011	**160 x 560 x 91**	
	RAL 7001 RAL 9011	**250 x 255 x 121**	
	RAL 7001 RAL 9011	**250 x 400 x 121**	
	RAL 7001 RAL 9011	**250 x 600 x 121**	
	RAL 7001 RAL 9011	**405 x 400 x 121**	
	RAL 7001 RAL 9011	**250 x 255 x 161**	
	RAL 7001 RAL 9011	**250 x 400 x 161**	

Information on the net weight of the enclosures can be found in the online catalogue.

TBF

Page C.168

		Dimensions in mm Height x width x depth
	grey lid (RAL7035) transparent lid	**186 x 151 x 140**
	grey lid (RAL7035) transparent lid	**302 x 186 x 175**
	grey lid (RAL7035) transparent lid	**302 x 302 x 175**
	grey lid (RAL7035) transparent lid	**372 x 302 x 175**

Information on the net weight of the enclosures can be found in the online catalogue.

TBF

Page C.168

		Dimensions in mm Height x width x depth
	grey lid (RAL7035) transparent lid	**488 x 302 x 175** **488 x 302 x 210**
	grey lid (RAL7035) transparent lid	**558 x 302 x 175** **558 x 302 x 210**
	grey lid (RAL7035) transparent lid	**603 x 302 x 175** **603 x 302 x 210**
	grey lid (RAL7035) transparent lid	**603 x 372 x 175** **603 x 372 x 210**
	grey lid (RAL7035) transparent lid	**603 x 605 x 175** **603 x 605 x 210**

Information on the net weight of the enclosures can be found in the online catalogue.

MPC

Page C.176

		Dimensions in mm Height x width x depth
	grey lid (RAL7035) transparent lid	**75 x 125 x 75**
	grey lid (RAL7035) transparent lid	**75 x 125 x 100/120**
	grey lid (RAL7035) transparent lid	**120 x 120 x 75/100/120**
	grey lid (RAL7035) transparent lid	**120 x 175 x 75/100/120/150**
	grey lid (RAL7035) transparent lid	**175 x 175 x 75 /100/120/150**
	grey lid (RAL7035) transparent lid	**175 x 250 x 100**
	grey lid (RAL7035) transparent lid	**180 x 250 x 75/150**

FPC

Page C.184

		Dimensions in mm Height x width x depth
	grey lid (RAL7035) transparent lid	**200 x 200 x 132**
	grey lid (RAL7035) transparent lid	**200 x 300 x 132**
	grey lid (RAL7035) transparent lid	**200 x 400 x 132**
	grey lid (RAL7035) transparent lid	**300 x 300 x 132**
	grey lid (RAL7035) transparent lid	**300 x 400 x 132**
	grey lid (RAL7035) transparent lid	**400 x 600 x 132**

Information on the net weight of the enclosures can be found in the online catalogue.

Klippon® TB enclosure series

Stainless steel enclosures for use within hazardous areas

The Klippon® TB enclosure series offers excellent performance characteristics and meets the stricter requirements of hazardous areas.
The enclosures are available in twelve sizes and three standard depths. They consist of 1.4404 (316L) stainless steel and meet the requirements of the IP66 and IP67 protection classes. The enclosures are tested with this equipment to the latest international standards, including EN 62208 and EN 60079.



Temperature and sealing characteristics
The enclosures come standard with a silicone seal for use under extreme temperatures.

Safe protection
An integrated dust and moisture channel prevents dirt and moisture from penetrating when the enclosure is opened. The external earthing stud is equipped with an IP66/67 certified sealing mechanism and is protected against twisting.

Versatile installation options
Mounting bolts are located within the enclosure for installing rails and mounting plates. Welded-on mounting feet provide for a fast, secure and stable wall mounting.

Approvals
The Klippon® TB range of enclosures has been awarded international approvals.

Safety and stability
The different sealing systems prevents unauthorized access to the enclosure. Welded on inner thread sockets provide a stable attachment mechanism for gland plates and protect against leaks.

Easy installation
The enclosures are delivered with up to four gland plates so that cable glands can be easily and quickly installed and attached.

Klippon® cable glands
Our complete series of IP66 and IP68 cable glands and accessories are an excellent compliment to the Klippon® TB enclosure series. Cable glands enable the connection of armoured and unarmoured cables from M20 to M75.

Industrial segments
The enclosures are designed for use in a variety of applications and for use in hazardous areas in particular. Typical applications include the process industry, the petrochemicals and power generation. All enclosures are tested and approved in compliance with the latest international standards, including ATEX and IECEx according to EN 60079.

Customer-specific solutions
Weidmüller's customer-specific-service provides comprehensive consultation, engineering and installation for modified enclosures. The enclosures can be modified during the production process according to customer demands and completed with various accessory components. There is a wide range of customer specific options available, such as enclosures with pre drilled holes and cutouts, various surfaces and materials, locking options and alternative sizes. Holders for documents and rating labels, door retainers, rain shields and many more accessories can also be installed on the enclosures per customer request.

Klippon® TB MH – Multi Hinge

Steel enclosures
for use in industrial and in potentially explosive atmospheres

The Klippon® TB enclosure range features excellent performance characteristics, even under the most difficult environmental conditions, and also comply with the stricter requirements of potentially explosive atmospheres found in the process or power generation industries. The Klippon® TB MH enclosure range offers further improvements to a product line that is already successfully leading the market.

Weidmüller manufactures and supplies the enclosures to match customer specifications – fully fitted with terminals, electronics and cable glands.

Features:

- Available in 12 sizes and 3 standard depths, with customer-specific sizes on request
- The gasket is protected against compression
- Completely removable padlock tab
- Cover lock outside the sealed zone
- Improved temperature performance
- IP66/IP67 protection
- Lid can be removed without a tool
- Welded mounting feet
- International approvals

Use our online catalogue to find additional product details, technical information and additional services:
www.weidmueller.com/KlipponTB

Overview of enclosures

Ordering data

Description	Height x width x depth in mm	0 Gland Plates	1 Gland Plate (below)	2 Gland Plates (above + below)	3 Gland plates (below + sides)	4 Gland plates (all sides)	Reference product
KTB MH 221513 S4E_*	229 x 152 x 133	1194550000	1194560000	1194570000	1194580000	1194590000	Klippon® TB10
KTB MH 262615 S4E_*	260 x 260 x 150	1194600000	1194610000	1194620000	1194630000	1194640000	Klippon® TB10A
KTB MH 262620 S4E_*	260 x 260 x 200	1194650000	1194660000	1194670000	1194680000	1194690000	Klippon® TB10A
KTB MH 303015 S4E_*	306 x 306 x 150	1194700000	1194710000	1194720000	1194730000	1194740000	Klippon® TB11
KTB MH 303020 S4E_*	306 x 306 x 200	1194750000	1194760000	1194770000	1194780000	1194790000	Klippon® TB11
KTB MH 352615 S4E_*	350 x 260 x 150	1194800000	1194810000	1194820000	1194830000	1194840000	Klippon® TB11A
KTB MH 352620 S4E_*	350 x 260 x 200	1194850000	1194860000	1194870000	1194880000	1194890000	Klippon® TB11A
KTB MH 403015 S4E_*	400 x 300 x 150	1194900000	1194910000	1194920000	1194930000	1194940000	-
KTB MH 403020 S4E_*	400 x 300 x 200	1194950000	1194960000	1194970000	1194980000	1194990000	-
KTB MH 453815 S4E_*	458 x 382 x 150	1195000000	1195010000	1195020000	1195030000	1195040000	Klippon® TB12
KTB MH 453820 S4E_*	458 x 382 x 200	1195050000	1195060000	1195070000	1195080000	1195090000	Klippon® TB12
KTB MH 484815 S4E_*	480 x 480 x 150	1195100000	1195110000	1195120000	1195130000	1195140000	Klippon® TB12A
KTB MH 484820 S4E_*	480 x 480 x 200	1195150000	1195160000	1195170000	1195180000	1195190000	Klippon® TB12A
KTB MH 553515 S4E_*	550 x 350 x 150	1195200000	1195210000	1195220000	1195230000	1195240000	Klippon® TB12B
KTB MH 553520 S4E_*	550 x 350 x 200	1195250000	1195260000	1195270000	1195280000	1195290000	Klippon® TB12B
KTB MH 624515 S4E_*	620 x 450 x 150	1195300000	1195310000	1195320000	1195330000	1195340000	Klippon® TB12D
KTB MH 624520 S4E_*	620 x 450 x 200	1195350000	1195360000	1195370000	1195380000	1195390000	Klippon® TB12D
KTB MH 765015 S4E_*	762 x 508 x 150	1195400000	1195410000	1195420000	1195430000	1195440000	Klippon® TB13
KTB MH 765020 S4E_*	762 x 508 x 200	1195450000	1195460000	1195470000	1195480000	1195490000	Klippon® TB13
KTB MH 916115 S4E_*	914 x 610 x 150	1195500000	1195510000	1195520000	1195530000	1195540000	Klippon® TB14
KTB MH 916120 S4E_*	914 x 610 x 200	1195550000	1195560000	1195570000	1195580000	1195590000	Klippon® TB14
KTB MH 987420 S4E_*	980 x 740 x 200	1195600000	1195610000	1195620000	1195630000	1195640000	-
Note		* Placeholder for the number of gland plates (0, 1, 2, 3, 4). The Klippon® TB enclosures with 2 and 4 gland plates are subject to minimum order quantities.					

Technical Overview

Technical data

Enclosure material*	Stainless steel 1.4404 (316L) 1.5 mm
Surface finish	electropolished
IP protection class	IP66 / IP67 to DIN EN 60529
NEMA protection classes	3, 4x, 12
Gland plates	1 – 4 (fixed with M6 hexagon head screws with 10 mm heads), optionally without a gland plate
Gland plate thickness	3 mm (other thickness are available on request)
Earthing inside	Enclosure base and lid: welded M6 stainless steel earth studs
Earthing outside	Continuous M10 brass earth stud (optionally with stainless-steel earth stud)
Installation mounting	4 or 9 mounting bolts with M6 threaded holes to attach the mounting plate or mounting rail
Enclosure attachment	4 or 6 welded mounting feet with 11-mm holes (2 slotted and 2 cross-shaped openings)
Lid opening	Lid can be fully removed without the use of tools, can be fitted on both sides, lid opening angle: 130°
Cover attachment	4 hinges and M6 hex-head screws (AF 10) with slot
Equipped for a padlock	Removable padlock fitting, for additional product security
Impact resistance	7 J to IEC 60079-0, IK 09 (10J) to DIN EN 50102
Gasket material	Silicone
Operating temperature range	-60 °C...+105 °C (IP66/IP67), -60 °C...+135 °C (IP66)
Torque – lid and gland plate screws	2.5 Nm
Note	* Painted enclosures are available on request.

Approvals for empty enclosures

ATEX certificate	IBExU14ATEX1028 U	EAC	RU-DE.08.B.00472
ATEX marking	II 2G Ex eb IIC Gb	cULus	E243298
	II 2D Ex tb IIIC Db	DNV GL	TAE000013S
IECEx certificate	IECEx IBE 14.0004U	Russian Maritime Register	15.40073.250
IECEx marking	Ex eb IIC Gb	CCOE	In preparation
	Ex tb IIIC Db	INMETRO	IEx 17.0020U
Nepsi Ex certificate	GYJ14.1308U	AEx	E223792
Nepsi Ex marking	Ex e IIC Gb, DIP A21	Miscellaneous	EN 45545, DIN EN 15085-2/CL2
Note	The Klippon® TB enclosure range can be pre-fitted in our customer specific production department according to your wishes.		

Approvals for control and distribution box

ATEX certificate	IBExU14ATEX1050	IECEx certificate	IECEx IBE 14.0013
ATEX marking	⟨Ex⟩ II 2G Ex eb IIC/IIB/IIA T6/T5/T4 Gb	IECEx marking	Ex eb IIC/IIB/IIA T6/T5/T4 Gb
	⟨Ex⟩ II 1G Ex ia IIC/IIB/IIA T6/T5/T4 Ga		Ex ia IIC/IIB/IIA T6/T5/T4 Ga
	⟨Ex⟩ II 2G Ex eb ia IIC/IIB/IIA T6/T5/T4 Gb		Ex eb ia IIC/IIB/IIA T6/T5/T4 Gb
	⟨Ex⟩ II 2D Ex tb IIIC T80°C/T95°C/T135°C Db		Ex tb IIIC T80°C/T95°C/T135°C Db
	⟨Ex⟩ II 1D Ex ia IIIC T80°C/T95°C/T135°C Da		Ex ia IIIC T80°C/T95°C/T135°C Da
	-60 °C ≤ Ta ≤ +40/+55/+90 °C		-60 °C...+40/+55/+90 °C
Nepsi Ex certificate	GYJ14.1309	INMETRO certificate	IEx 17.0021
Nepsi marking	Ex e IIC T4...T6 Gb	INMETRO marking	Ex eb IIC T6/T5/T4 Gb
	Ex ia IIC T4...T6 Ga		Ex ia IIC T6/T5/T4 Ga
	Ex e ia IIC T4...T6 Gb		Ex eb ia IIC T6/T5/T4 Gb
	DIP A21 T_A 85°C...T_A 135°C		Ex tb IIIC T85°C/T100°C/T135°C Db IP66/IP67
	Ex ia D20 T85 °C... T135 °C		Ex ia IIIC T85°C/T100°C/T135°C Da
EAC certificate	RUC-DE.08.B.01328	AEx certificate	E223792
EAC marking	II 2 G Ex eb IIC T6...T4	AEx marking	Class I, Zone 1, AEx e IIC Gb T6..T4
	II 2 G Ex e IIC T6...T4 Gb		Class I, Zone 2, AEx e IIC Gc T6..T4
	II 1 G Ex ia IIC T6...T4		Class I Div.2 Group A,B,C,D T6...T4
	II 1 G Ex ia IIC T6...T4 Ga		Class II Div.2 Group F,G
	II 2(1) G Ex eb ia IIC T6...T4		Zone 21, AEx tb IIIC Db
	II 2(1) G Ex e ia IIC T6...T4 Gb		
	II 2 D Ex tb IIIC T85°C...T135°C		
	II 2 D Ex tb IIIC T85°C...T135°C Db		
KOSHA certificate	16-AV4BO-0245X		
KOSHA marking	Ex eb IIC/IIB/IIA T6/T5/T4 Gb		
	Ex ia IIC/IIB/IIA T6/T5/T4 Ga		
	Ex eb ia IIC/IIB/IIA T6/T5/T4 Gb		
	Ex tb IIIC T80°C/T95°C/T135°C Db		
	Ex ia IIIC T80°C/T95°C/T135°C Da		
	60 °C...+40/+55/+90 °C		
Note	Labelling depends on the application layout. Limited to IP66 protection when used in temperatures greater than 105 °C. For details of power dissipation, please contact your Weidmüller representative. Additional approvals available on request.		

Integrate, expand, and customise: the perfect supplement to every application

The fully structured range of system accessories for the Klippon® TB enclosure range allows you to easily adapt the enclosure to meet the specific requirements of every application.

The following options are available:

1 Document holder

Document holders for storage of important documents in the enclosure.

2 Earthing studs

Earthing studs are replaceable. Available in two versions – brass and stainless steel.

3 Gland plates

Gland plates are available as spares and also in various material thicknesses.

4 Mounting plates

Mounting plates with and without a drilling pattern, for horizontal and vertical mounting of rails, or components fitted directly.

5 Mounting hardware kits

Mounting hardware kits are available for quick and easy installation of label holders, mounting plates, gland plates, document holders, and rain hoods.

6 Door stay

A door stay prevent the door from being closed unintentionally, regardless of the mounting position of the enclosure.
This item is **only** available Ex-works.

7 Locking systems

Various locking systems are available for the safe securing of the enclosure. There are padlocks for the Klippon® TB MH enclosures and a range of lock inserts for the Klippon® TB QL enclosures.

8 Type label holder

A range of label holders are available for product identification.

9 Rain hoods

The rain hood provides an ideal, additional level of protection for the enclosure. Particularly useful against heavy rainfall or extreme levels of direct sunlight.

Klippon® TB MH 221513

Depth 133 mm

Height / Width / Depth	229 / 152 / 133 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1194550000
1 gland plate - positioned at the bottom (B)	1194560000
2 gland plates - positioned at top and bottom (A & B)*	1194570000
3 gland plates - positioned at bottom, left and right (B, C & D)	1194580000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1194590000

Note *Minimum order quantity (20 pieces)

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1193930000
With hole pattern, sheet steel, galvanised	2022050000
Stainless steel 1.4301 natural	1193810000
With hole pattern, natural stainless steel 1.4301	1257650000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006720
Vertical	8000006708
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2022770000
Left and right sides (C & D), electropolished stainless steel 1.4404	2022900000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256270000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256280000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281360000
Stainless steel 1.4404, electro-polished	1314090000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000

Note *Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal		vertical	horizontal
	2.5 mm²	1x26	1x10
	4 mm²	1x21	1x8
	6 mm²	1x16	1x6
	10 mm²	1x13	1x4
	16 mm²	1x10	1x3
	35 mm²	1x7	1x2

Note
*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	6	8
M16	5	6
M20	2	3
M25	2	2
M32	1	2
M40	1	2
M50	0	0
M63	0	0
M75	0	0

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 262615

Depth 150 mm



Height / Width / Depth	260 / 260 / 150 mm

Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1194600000
1 gland plate - positioned at the bottom (B)	1194610000
2 gland plates - positioned at top and bottom (A & B)*	1194620000
3 gland plates - positioned at bottom, left and right (B, C & D)	1194630000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1194640000

Note *Minimum order quantity (20 pieces)

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1193950000
With hole pattern, sheet steel, galvanised	2022060000
Stainless steel 1.4301 natural	1193820000
With hole pattern, natural stainless steel 1.4301	1257660000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006721
Vertical	8000006709
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2022930000
Left and right sides (C & D), electropolished stainless steel 1.4404	2023090000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256290000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256310000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281370000
Stainless steel 1.4404, electro-polished	1314100000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000

Note
*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal		vertical	horizontal
	2.5 mm²	2x31	2x31
	4 mm²	1x26	1x26
	6 mm²	1x19	1x19
	10 mm²	1x15	1x15
	16 mm²	1x12	1x12
	35 mm²	1x9	1x9

Note
*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	20	15
M16	11	8
M20	9	7
M25	4	3
M32	3	2
M40	3	2
M50	2	2
M63	0	0
M75	0	0

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 262620

Depth 200 mm

Height / Width / Depth	260 / 260 / 200 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1194650000
1 gland plate - positioned at the bottom (B)	1194660000
2 gland plates - positioned at top and bottom (A & B)*	1194670000
3 gland plates - positioned at bottom, left and right (B, C & D)	1194680000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1194690000

Note *Minimum order quantity (20 pieces)

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1193950000
With hole pattern, sheet steel, galvanised	2022060000
Stainless steel 1.4301 natural	1193820000
With hole pattern, natural stainless steel 1.4301	1257660000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006721
Vertical	8000006709
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2023100000
Left and right sides (C & D), electropolished stainless steel 1.4404	2023110000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256320000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256330000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281380000
Stainless steel 1.4404, electro-polished	1314110000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000

Note
*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal		vertical	horizontal
	2.5 mm²	2x31	2x31
	4 mm²	1x26	1x26
	6 mm²	1x19	1x19
	10 mm²	1x15	1x15
	16 mm²	1x12	1x12
	35 mm²	1x9	1x9

Note
*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	33	25
M16	22	16
M20	14	11
M25	12	9
M32	6	4
M40	5	4
M50	2	2
M63	2	1
M75	1	1

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 303015

Depth 150 mm

Height / Width / Depth	306 / 306 / 150 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1194700000
1 gland plate - positioned at the bottom (B)	1194710000
2 gland plates - positioned at top and bottom (A & B)*	1194720000
3 gland plates - positioned at bottom, left and right (B, C & D)	1194730000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1194740000
Note *Minimum order quantity (20 pieces)	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1193960000
With hole pattern, sheet steel, galvanised	2022190000
Stainless steel 1.4301 natural	1193830000
With hole pattern, natural stainless steel 1.4301	1257670000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006722
Vertical	8000006710
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2023120000
Left and right sides (C & D), electropolished stainless steel 1.4404	2023130000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256340000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256350000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281390000
Stainless steel 1.4404, electro-polished	1314120000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000

Note
*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	1x41	2x40
4 mm²	1x34	2x33
6 mm²	1x25	2x25
10 mm²	1x20	1x20
16 mm²	1x17	1x16
35 mm²	1x12	1x12

Note
*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	24	20
M16	13	11
M20	11	9
M25	5	4
M32	4	3
M40	3	3
M50	3	2
M63	0	0
M75	0	0

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 303020

Depth 200 mm

Height / Width / Depth	306 / 306 / 200 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1194750000
1 gland plate - positioned at the bottom (B)	1194760000
2 gland plates - positioned at top and bottom (A & B)*	1194770000
3 gland plates - positioned at bottom, left and right (B, C & D)	1194780000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1194790000
Note *Minimum order quantity (20 pieces)	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1193960000
With hole pattern, sheet steel, galvanised	2022190000
Stainless steel 1.4301 natural	1193830000
With hole pattern, natural stainless steel 1.4301	1257670000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006722
Vertical	8000006710
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2023140000
Left and right sides (C & D), electropolished stainless steel 1.4404	2023150000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256360000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256370000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281400000
Stainless steel 1.4404, electro-polished	1314130000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000

Note
*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal		vertical	horizontal
	2.5 mm²	1x41	2x40
	4 mm²	1x34	2x33
	6 mm²	1x25	2x25
	10 mm²	1x20	1x20
	16 mm²	1x17	1x16
	35 mm²	1x12	1x12

Note
*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	40	33
M16	26	22
M20	17	14
M25	14	12
M32	8	6
M40	6	5
M50	3	2
M63	2	2
M75	2	1

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 352615

Depth 150 mm

Height / Width / Depth	350 / 260 / 150 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1194800000
1 gland plate - positioned at the bottom (B)	1194810000
2 gland plates - positioned at top and bottom (A & B)*	1194820000
3 gland plates - positioned at bottom, left and right (B, C & D)	1194830000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1194840000
Note *Minimum order quantity (20 pieces)	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1193970000
With hole pattern, sheet steel, galvanised	2022310000
Stainless steel 1.4301 natural	1193840000
With hole pattern, natural stainless steel 1.4301	1257680000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006721
Vertical	8000006711
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2023160000
Left and right sides (C & D), electropolished stainless steel 1.4404	2023210000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256380000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256390000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281410000
Stainless steel 1.4404, electro-polished	1314140000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000

Note
*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal		vertical	horizontal
	2.5 mm²	2x49	2x31
	4 mm²	1x41	2x26
	6 mm²	1x31	2x19
	10 mm²	1x25	2x15
	16 mm²	1x20	1x12
	35 mm²	1x15	1x9

Note
*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	20	23
M16	11	13
M20	9	11
M25	4	5
M32	3	4
M40	3	3
M50	2	3
M63	0	0
M75	0	0

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 352620

Depth 200 mm

Height / Width / Depth	350 / 260 / 200 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1194850000
1 gland plate - positioned at the bottom (B)	1194860000
2 gland plates - positioned at top and bottom (A & B)*	1194870000
3 gland plates - positioned at bottom, left and right (B, C & D)	1194880000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1194890000
Note *Minimum order quantity (20 pieces)	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1193970000
With hole pattern, sheet steel, galvanised	2022310000
Stainless steel 1.4301 natural	1193840000
With hole pattern, natural stainless steel 1.4301	1257680000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006721
Vertical	8000006711
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2023230000
Left and right sides (C & D), electropolished stainless steel 1.4404	2023280000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256410000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256420000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281420000
Stainless steel 1.4404, electro-polished	1314150000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000

Note
*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal		vertical	horizontal
	2.5 mm²	2x49	2x31
	4 mm²	1x41	2x26
	6 mm²	1x31	2x19
	10 mm²	1x25	2x15
	16 mm²	1x20	1x12
	35 mm²	1x15	1x9

Note
*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	33	38
M16	22	26
M20	14	17
M25	12	14
M32	6	7
M40	5	6
M50	2	3
M63	2	2
M75	1	2

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 403015

Depth 150 mm

Height / Width / Depth	400 / 300 / 150 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1194900000
1 gland plate - positioned at the bottom (B)	1194910000
2 gland plates - positioned at top and bottom (A & B)*	1194920000
3 gland plates - positioned at bottom, left and right (B, C & D)	1194930000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1194940000
Note *Minimum order quantity (10 pieces)	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1193980000
With hole pattern, sheet steel, galvanised	2022420000
Stainless steel 1.4301 natural	1193850000
With hole pattern, natural stainless steel 1.4301	1257690000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006723
Vertical	8000006712
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2023320000
Left and right sides (C & D), electropolished stainless steel 1.4404	2023330000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256430000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256440000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281430000
Stainless steel 1.4404, electro-polished	1314170000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000

Note
*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal		vertical	horizontal
	2.5 mm²	2x59	3x39
	4 mm²	2x49	3x32
	6 mm²	1x37	2x24
	10 mm²	1x30	2x19
	16 mm²	1x24	2x16
	35 mm²	1x18	1x11

Note
*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	23	29
M16	13	16
M20	11	13
M25	5	6
M32	4	5
M40	3	4
M50	3	3
M63	0	0
M75	0	0

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 403020

Depth 200 mm

Height / Width / Depth	400 / 300 / 200 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1194950000
1 gland plate - positioned at the bottom (B)	1194960000
2 gland plates - positioned at top and bottom (A & B)*	1194970000
3 gland plates - positioned at bottom, left and right (B, C & D)	1194980000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1194990000
Note *Minimum order quantity (10 pieces)	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1193980000
With hole pattern, sheet steel, galvanised	2022420000
Stainless steel 1.4301 natural	1193850000
With hole pattern, natural stainless steel 1.4301	1257690000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006723
Vertical	8000006712
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2023450000
Left and right sides (C & D), electropolished stainless steel 1.4404	2023480000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256450000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256470000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281440000
Stainless steel 1.4404, electro-polished	1314180000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000

Note
*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal		vertical	horizontal
	2.5 mm²	2x59	3x39
	4 mm²	2x49	3x32
	6 mm²	1x37	2x24
	10 mm²	1x30	2x19
	16 mm²	1x24	2x16
	35 mm²	1x18	1x11

Note
*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	38	48
M16	26	32
M20	17	20
M25	14	17
M32	7	9
M40	6	7
M50	3	3
M63	2	3
M75	2	2

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 453815

Depth 150 mm

Height / Width / Depth 458 / 382 / 150 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1195000000
1 gland plate - positioned at the bottom (B)	1195010000
2 gland plates - positioned at top and bottom (A & B)*	1195020000
3 gland plates - positioned at bottom, left and right (B, C & D)	1195030000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1195040000
Note *Minimum order quantity (10 pieces)	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1193990000
With hole pattern, sheet steel, galvanised	2022590000
Stainless steel 1.4301 natural	1193860000
With hole pattern, natural stainless steel 1.4301	1257700000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006724
Vertical	8000006713
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2023490000
Left and right sides (C & D), electropolished stainless steel 1.4404	2023500000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256480000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256490000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281450000
Stainless steel 1.4404, electro-polished	1314190000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
For DIN A5 size documents	1252750000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000

Note
*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal		vertical	horizontal
	2.5 mm²	3x71	4x54
	4 mm²	2x59	3x46
	6 mm²	2x44	3x34
	10 mm²	2x36	2x27
	16 mm²	2x29	2x22
	35 mm²	1x22	1x17

Note
*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	30	33
M16	17	19
M20	15	16
M25	6	7
M32	5	6
M40	4	5
M50	4	4
M63	0	0
M75	0	0

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 453820

Depth 200 mm

Height / Width / Depth 458 / 382 / 200 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1195050000
1 gland plate - positioned at the bottom (B)	1195060000
2 gland plates - positioned at top and bottom (A & B)*	1195070000
3 gland plates - positioned at bottom, left and right (B, C & D)	1195080000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1195090000
Note *Minimum order quantity (10 pieces)	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1193990000
With hole pattern, sheet steel, galvanised	2022590000
Stainless steel 1.4301 natural	1193860000
With hole pattern, natural stainless steel 1.4301	1257700000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006724
Vertical	8000006713
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2023510000
Left and right sides (C & D), electropolished stainless steel 1.4404	2023520000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256510000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256520000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281460000
Stainless steel 1.4404, electro-polished	1314200000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
For DIN A5 size documents	1252750000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000

Note
*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)

Assembly with terminal		vertical	horizontal
	2.5 mm²	3x71	4x54
	4 mm²	2x59	3x46
	6 mm²	2x44	3x34
	10 mm²	2x36	2x27
	16 mm²	2x29	2x22
	35 mm²	1x22	1x17

Note
*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	50	55
M16	34	38
M20	23	24
M25	18	21
M32	10	11
M40	8	9
M50	4	4
M63	3	3
M75	2	3

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 484815

Depth 150 mm

Height / Width / Depth	480 / 480 / 150 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1195100000
1 gland plate - positioned at the bottom (B)	1195110000
2 gland plates - positioned at top and bottom (A & B)*	1195120000
3 gland plates - positioned at bottom, left and right (B, C & D)	1195130000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1195140000
Note *Minimum order quantity (10 pieces)	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1194000000
With hole pattern, sheet steel, galvanised	2022610000
Stainless steel 1.4301 natural	1193870000
With hole pattern, natural stainless steel 1.4301	1257710000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Vertical	8000006714
Horizontally	8000006725
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2023530000
Left and right sides (C & D), electropolished stainless steel 1.4404	2023540000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256530000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256540000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281470000
Stainless steel 1.4404, electro-polished	1314220000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
For DIN A5 size documents	1252750000
For DIN A4 size documents	1252730000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000
Note *Packing unit (PU) = 20 pcs., sufficient for 10 fixtures **Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately	

Guide value for max. number of terminals (industry)



Assembly with terminal		vertical	horizontal
	2.5 mm²	4x75	4x74
	4 mm²	3x62	3x62
	6 mm²	3x47	3x46
	10 mm²	2x38	3x37
	16 mm²	2x31	2x31
	35 mm²	1x23	2x23

Note

*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	39	36
M16	22	20
M20	19	17
M25	8	7
M32	7	6
M40	6	5
M50	5	4
M63	0	0
M75	0	0

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 484820

Depth 200 mm

Height / Width / Depth	480 / 480 / 200 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1195150000
1 gland plate - positioned at the bottom (B)	1195160000
2 gland plates - positioned at top and bottom (A & B)*	1195170000
3 gland plates - positioned at bottom, left and right (B, C & D)	1195180000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1195190000
Note *Minimum order quantity (10 pieces)	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1194000000
With hole pattern, sheet steel, galvanised	2022610000
Stainless steel 1.4301 natural	1193870000
With hole pattern, natural stainless steel 1.4301	1257710000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006725
Vertical	8000006714
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2023580000
Left and right sides (C & D), electropolished stainless steel 1.4404	2023620000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256550000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256560000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281480000
Stainless steel 1.4404, electro-polished	1314230000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
For DIN A5 size documents	1252750000
For DIN A4 size documents	1252730000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000
Note *Packing unit (PU) = 20 pcs., sufficient for 10 fixtures **Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately	

Guide value for max. number of terminals (industry)



Assembly with terminal		vertical	horizontal
	2.5 mm²	4x75	4x74
	4 mm²	3x62	3x62
	6 mm²	3x47	3x46
	10 mm²	2x38	3x37
	16 mm²	2x31	2x31
	35 mm²	1x23	2x23

Note

*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	65	60
M16	44	40
M20	29	26
M25	24	21
M32	13	12
M40	11	10
M50	5	4
M63	4	4
M75	3	3

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 553515

Depth 150 mm

Height / Width / Depth 550 / 350 / 150 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1195200000
1 gland plate - positioned at the bottom (B)	1195210000
2 gland plates - positioned at top and bottom (A & B)*	1195220000
3 gland plates - positioned at bottom, left and right (B, C & D)	1195230000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1195240000

Note *Minimum order quantity (10 pieces)

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1194010000
With hole pattern, sheet steel, galvanised	2022650000
Stainless steel 1.4301 natural	1193880000
With hole pattern, natural stainless steel 1.4301	1257720000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006726
Vertical	8000006715
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2023660000
Left and right sides (C & D), electropolished stainless steel 1.4404	2023670000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256570000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256580000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281490000
Stainless steel 1.4404, electro-polished	1314240000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
For DIN A5 size documents	1252750000
For DIN A4 size documents	1252730000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000

Note *Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	2x89	4x48
4 mm²	2x73	4x40
6 mm²	2x55	4x30
10 mm²	2x45	3x24
16 mm²	1x37	3x20
35 mm²	1x28	2x15

Note
*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	27	42
M16	15	24
M20	13	20
M25	6	9
M32	5	7
M40	4	6
M50	3	5
M63	0	0
M75	0	0

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 553520

Depth 200 mm

Height / Width / Depth	550 / 350 / 200 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1195250000
1 gland plate - positioned at the bottom (B)	1195260000
2 gland plates - positioned at top and bottom (A & B)*	1195270000
3 gland plates - positioned at bottom, left and right (B, C & D)	1195280000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1195290000
Note *Minimum order quantity (10 pieces)	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1194010000
With hole pattern, sheet steel, galvanised	2022650000
Stainless steel 1.4301 natural	1193880000
With hole pattern, natural stainless steel 1.4301	1257720000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006726
Vertical	8000006715
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2023740000
Left and right sides (C & D), electropolished stainless steel 1.4404	2023790000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256590000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256610000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281500000
Stainless steel 1.4404, electro-polished	1314250000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
For DIN A5 size documents	1252750000
For DIN A4 size documents	1252730000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000
Note *Packing unit (PU) = 20 pcs., sufficient for 10 fixtures **Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately	

Guide value for max. number of terminals (industry)



Assembly with terminal		vertical	horizontal
	2.5 mm²	2x89	4x48
	4 mm²	2x73	4x40
	6 mm²	2x55	4x30
	10 mm²	2x45	3x24
	16 mm²	1x37	3x20
	35 mm²	1x28	2x15

Note

*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	45	70
M16	30	48
M20	20	30
M25	17	26
M32	9	14
M40	7	12
M50	3	5
M63	3	4
M75	2	3

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 624515

Depth 150 mm

Height / Width / Depth	620 / 450 / 150 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1195300000
1 gland plate - positioned at the bottom (B)	1195310000
2 gland plates - positioned at top and bottom (A & B)*	1195320000
3 gland plates - positioned at bottom, left and right (B, C & D)	1195330000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1195340000
Note *Minimum order quantity (5 pieces)	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1194020000
With hole pattern, sheet steel, galvanised	2022670000
Stainless steel 1.4301 natural	1193890000
With hole pattern, natural stainless steel 1.4301	1257740000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006727
Vertical	8000006716
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2023820000
Left and right sides (C & D), electropolished stainless steel 1.4404	2023870000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256620000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256630000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281510000
Stainless steel 1.4404, electro-polished	1314270000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
For DIN A5 size documents	1252750000
For DIN A4 size documents	1252730000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000
Note *Packing unit (PU) = 20 pcs., sufficient for 10 fixtures **Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately	

Guide value for max. number of terminals (industry)



Assembly with terminal		vertical	horizontal
	2.5 mm²	3x101	5x65
	4 mm²	3x83	5x54
	6 mm²	3x62	4x41
	10 mm²	2x49	4x33
	16 mm²	2x42	3x26
	35 mm²	1x31	2x20

Note

*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	38	48
M16	21	27
M20	18	24
M25	8	10
M32	6	9
M40	5	7
M50	4	6
M63	0	0
M75	0	0

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 624520

Depth 200 mm

Height / Width / Depth 620 / 450 / 200 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1195350000
1 gland plate - positioned at the bottom (B)	1195360000
2 gland plates - positioned at top and bottom (A & B)*	1195370000
3 gland plates - positioned at bottom, left and right (B, C & D)	1195380000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1195390000

Note *Minimum order quantity (5 pieces)

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1194020000
With hole pattern, sheet steel, galvanised	2022670000
Stainless steel 1.4301 natural	1193890000
With hole pattern, natural stainless steel 1.4301	1257740000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006727
Vertical	8000006716
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2023880000
Left and right sides (C & D), electropolished stainless steel 1.4404	2023930000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256640000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256650000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281520000
Stainless steel 1.4404, electro-polished	1314280000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
For DIN A5 size documents	1252750000
For DIN A4 size documents	1252730000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000

Note *Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)

Assembly with terminal		vertical	horizontal
	2.5 mm²	3x101	5x65
	4 mm²	3x83	5x54
	6 mm²	3x62	4x41
	10 mm²	2x49	4x33
	16 mm²	2x42	3x26
	35 mm²	1x31	2x20

Note
*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	63	80
M16	42	54
M20	27	36
M25	23	30
M32	12	17
M40	10	14
M50	4	6
M63	4	5
M75	3	4

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 765015

Depth 150 mm

Height / Width / Depth 762 / 508 / 150 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1195400000
1 gland plate - positioned at the bottom (B)	1195410000
2 gland plates - positioned at top and bottom (A & B)*	1195420000
3 gland plates - positioned at bottom, left and right (B, C & D)	1195430000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1195440000

Note *Minimum order quantity (5 pieces)

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1194030000
With hole pattern, sheet steel, galvanised	2022680000
Stainless steel 1.4301 natural	1193900000
With hole pattern, natural stainless steel 1.4301	1257750000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006728
Vertical	8000006717
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2024040000
Left and right sides (C & D), electropolished stainless steel 1.4404	2024090000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256660000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256670000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281530000
Stainless steel 1.4404, electro-polished	1314290000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
For DIN A5 size documents	1252750000
For DIN A4 size documents	1252730000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000

Note *Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	4x128	7x78
4 mm²	4x107	6x64
6 mm²	3x80	5x48
10 mm²	3x65	5x39
16 mm²	2x53	4x32
35 mm²	2x40	3x24

Note
*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	42	58
M16	24	32
M20	21	26
M25	9	12
M32	7	10
M40	6	8
M50	5	6
M63	0	0
M75	0	0

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 765020

Depth 200 mm

Height / Width / Depth 762 / 508 / 200 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1195450000
1 gland plate - positioned at the bottom (B)	1195460000
2 gland plates - positioned at top and bottom (A & B)*	1195470000
3 gland plates - positioned at bottom, left and right (B, C & D)	1195480000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1195490000
Note *Minimum order quantity (5 pieces)	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1194030000
With hole pattern, sheet steel, galvanised	2022680000
Stainless steel 1.4301 natural	1193900000
With hole pattern, natural stainless steel 1.4301	1257750000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006728
Vertical	8000006717
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2024100000
Left and right sides (C & D), electropolished stainless steel 1.4404	2024140000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256680000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256690000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281540000
Stainless steel 1.4404, electro-polished	1314300000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
For DIN A5 size documents	1252750000
For DIN A4 size documents	1252730000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000
Note *Packing unit (PU) = 20 pcs., sufficient for 10 fixtures **Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately	

Guide value for max. number of terminals (industry)

Assembly with terminal		vertical	horizontal
	2.5 mm²	4x128	7x78
	4 mm²	4x107	6x64
	6 mm²	3x80	5x48
	10 mm²	3x65	5x39
	16 mm²	2x53	4x32
	35 mm²	2x40	3x24

Note

*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	70	96
M16	48	64
M20	32	40
M25	26	34
M32	14	18
M40	12	14
M50	5	6
M63	4	6
M75	3	4

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 916115

Depth 150 mm

Height / Width / Depth	914 / 610 / 150 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1195500000
1 gland plate - positioned at the bottom (B)	1195510000
2 gland plates - positioned at top and bottom (A & B)*	1195520000
3 gland plates - positioned at bottom, left and right (B, C & D)	1195530000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1195540000
Note *Minimum order quantity (5 pieces)	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1194040000
With hole pattern, sheet steel, galvanised	2022740000
Stainless steel 1.4301 natural	1193910000
With hole pattern, natural stainless steel 1.4301	1257760000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006729
Vertical	8000006718
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2024150000
Left and right sides (C & D), electropolished stainless steel 1.4404	2024300000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256710000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256720000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281550000
Stainless steel 1.4404, electro-polished	1314320000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
For DIN A5 size documents	1252750000
For DIN A4 size documents	1252730000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000
Note *Packing unit (PU) = 20 pcs., sufficient for 10 fixtures **Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately	

Guide value for max. number of terminals (industry)



Assembly with terminal		vertical	horizontal
	2.5 mm²	5x157	8x99
	4 mm²	4x132	7x80
	6 mm²	4x100	7x62
	10 mm²	3x85	6x50
	16 mm²	3x66	5x40
	35 mm²	2x49	4x30

Note

*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	53	70
M16	29	40
M20	25	34
M25	11	14
M32	9	12
M40	8	10
M50	6	8
M63	0	0
M75	0	0

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 916120

Depth 200 mm

Height / Width / Depth	914 / 610 / 200 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1195550000
1 gland plate - positioned at the bottom (B)	1195560000
2 gland plates - positioned at top and bottom (A & B)*	1195570000
3 gland plates - positioned at bottom, left and right (B, C & D)	1195580000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1195590000
Note *Minimum order quantity (5 pieces)	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1194040000
With hole pattern, sheet steel, galvanised	2022740000
Stainless steel 1.4301 natural	1193910000
With hole pattern, natural stainless steel 1.4301	1257760000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006729
Vertical	8000006718
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2024470000
Left and right sides (C & D), electropolished stainless steel 1.4404	2024490000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256730000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256740000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281570000
Stainless steel 1.4404, electro-polished	1314330000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
For DIN A5 size documents	1252750000
For DIN A4 size documents	1252730000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000
Note *Packing unit (PU) = 20 pcs., sufficient for 10 fixtures **Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately	

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	5x157	8x99
4 mm²	4x132	7x80
6 mm²	4x100	7x62
10 mm²	3x85	6x50
16 mm²	3x66	5x40
35 mm²	2x49	4x30

Note

*For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	88	116
M16	58	80
M20	38	52
M25	33	42
M32	18	24
M40	15	20
M50	6	8
M63	5	6
M75	4	6

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB MH 987420

Depth 200 mm

980 / 740 / 200 mm



Ordering data

Stainless steel 1.4404 316L, electropolished	Order No.
0 gland plates	1195600000
1 gland plate - positioned at the bottom (B)	1195610000
2 gland plates - positioned at top and bottom (A & B)*	1195620000
3 gland plates - positioned at bottom, left and right (B, C & D)	1195630000
4 gland plates - positioned at top, bottom, left and right (A, B, C & D)*	1195640000

Note *Minimum order quantity (5 pieces)

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1194050000
With hole pattern, sheet steel, galvanised	2022760000
Stainless steel 1.4301 natural	1193920000
With hole pattern, natural stainless steel 1.4301	1257770000
Fastening screws for mounting plates	0642600000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Horizontally	8000006730
Vertical	8000006719
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Gland plates - 3 mm with M6 earth studs	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	2024560000
Left and right sides (C & D), electropolished stainless steel 1.4404	2024590000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256750000
Left and right sides (C & D), electropolished stainless steel 1.4404	1256760000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281580000
Stainless steel 1.4404, electro-polished	1314340000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
130x50 stainless steel 1.4301	1283450000
100x25 stainless steel 1.4301	1257640000
Document holders	
For DIN A6 size documents	1252780000
For DIN A5 size documents	1252750000
For DIN A4 size documents	1252730000
Set of fixings*	
For label holders, rain hoods and document holders (rivet)	1252190000
For plastic (Trafolyte), identification plate (screw)	1285200000
Earthing stud	
Stainless steel 1.4404, M10	1192690000

Note *Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	6x174	9x127
4 mm²	6x146	8x99
6 mm²	5x108	7x78
10 mm²	4x85	6x63
16 mm²	4x72	5x51
35 mm²	3x54	4x38

Note *For the enclosure versions with no, one or two gland plates, the horizontal distance of the mounting feet is reduced by 30 mm.
When mounting modular terminals please leave a distance of 10 mm to the ends of the DIN rail.
Ordering recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	96	126
M16	64	84
M20	42	54
M25	36	48
M32	20	26
M40	16	22
M50	6	10
M63	6	8
M75	4	6

Note Our IP 68 brass cable glands serve as a reference for these recommended values.

Dimensions of mounting plate



Klippon® TB QL – Quarter Lock

Steel enclosures
for use in industrial and in explosive hazard areas

The Klippon® TB enclosure range features excellent performance characteristics, even under the most difficult environmental conditions, and comply with the stricter requirements of explosive hazard areas found in the process or power generation industries. The Klippon® TB QL enclosure range offers further improvements to a product line that is already successfully leading the market.

Weidmüller manufactures and supplies the enclosures to match customer specifications – fully fitted with terminals, electronics and cable glands.

Features:

- Available in 12 sizes and 3 standard depths, with customer-specific sizes on request
- Equipped with up to 4 gland plates
- The gasket is protected against compression
- Quick-locking lid, comes with a slot as standard
- Improved temperature performance
- IP66 protection class
- Earth studs in enclosure cover and bottom section
- Welded mounting feet

Use our online catalogue to find additional product details, technical information and additional services:
www.weidmueller.com/KlipponTB

Overview of enclosures

Ordering data

Description	Height x width x depth in mm	0 Gland Plates	1 Gland Plate (below)	2 Gland Plates (above + below)	3 Gland Plates (below + sides)	4 Gland Plates (all sides)
KTB QL 221513 S4E_*	229 x 152 x 133	1199850000	1199860000	1199870000	1199880000	1199890000
KTB QL 262615 S4E_*	260 x 260 x 150	1199900000	1199910000	1199920000	1199930000	1199940000
KTB QL 262620 S4E_*	260 x 260 x 200	1199950000	1199960000	1199970000	1199980000	1199990000
KTB QL 303015 S4E_*	306 x 306 x 150	1200010000	1200020000	1200030000	1200040000	1200050000
KTB QL 303020 S4E_*	306 x 306 x 200	1200060000	1200070000	1200080000	1200090000	1200100000
KTB QL 352615 S4E_*	350 x 260 x 150	1200110000	1200120000	1200130000	1200140000	1200150000
KTB QL 352620 S4E_*	350 x 260 x 200	1200160000	1200170000	1200180000	1200190000	1200210000
KTB QL 403015 S4E_*	400 x 300 x 150	1200220000	1200230000	1200240000	1200250000	1200260000
KTB QL 403020 S4E_*	400 x 300 x 200	1200270000	1200280000	1200290000	1200310000	1200320000
KTB QL 453815 S4E_*	458 x 382 x 150	1200330000	1200340000	1200350000	1200360000	1200370000
KTB QL 453820 S4E_*	458 x 382 x 200	1200380000	1200390000	1200410000	1200420000	1200430000
KTB QL 484815 S4E_*	480 x 480 x 150	1200440000	1200450000	1200460000	1200470000	1200480000
KTB QL 484820 S4E_*	480 x 480 x 200	1200490000	1200510000	1200520000	1200530000	1200540000
KTB QL 553515 S4E_*	550 x 350 x 150	1200550000	1200560000	1200570000	1200580000	1200590000
KTB QL 553520 S4E_*	550 x 350 x 200	1200610000	1200620000	1200630000	1200640000	1200650000
KTB QL 624515 S4E_*	620 x 450 x 150	1200660000	1200670000	1200680000	1200690000	1200710000
KTB QL 624520 S4E_*	620 x 450 x 200	1200720000	1200730000	1200740000	1200750000	1200760000
KTB QL 765015 S4E_*	762 x 508 x 150	1200770000	1200780000	1200790000	1200810000	1200820000
KTB QL 765020 S4E_*	762 x 508 x 200	1200830000	1200840000	1200850000	1200860000	1200870000
KTB QL 916115 S4E_*	914 x 610 x 150	1200940000	1200890000	1200910000	1200920000	1200930000
KTB QL 916120 S4E_*	914 x 610 x 200	1200880000	1200950000	1200960000	1200970000	1200980000
KTB QL 987420 S4E_*	980 x 740 x 200	1200990000	1201010000	1201020000	1201030000	1201040000
Note		* Placeholder for the number of gland plates (0, 1, 2, 3, 4). The Klippon® TB QL enclosures are subject to a minimum order quantity.				

Technical Overview

Technical data

Enclosure material*	Stainless steel 1.4404 (316L) 1.5 mm
Surface finish	Electropolished
IP protection class	IP66 to IEC EN 60079-0
NEMA protection classes	3, 4x, 12
Gland plates	1 - 4 (fixed with M6 hexagon head screws and 10 mm heads), optionally without a gland plate
Gland plate thickness	3 mm (other thickness of up to 20 mm are available on request)
Earthing inside	Enclosure base and lid: welded M6 stainless steel earth studs
Earthing outside	Continuous M10 brass earth stud (optionally with stainless-steel earth stud)
Installation mounting	4 or 9 mounting bolts with M6 threaded holes to attach the mounting plate or mounting rails
Enclosure attachment	4 or 6 welded mounting feet with 11-mm holes (2 slotted and 2 cross-shaped openings)
Lid opening	Can be removed completely, lid opening angle 130 °
Cover attachment	Quarter-turn lock with slotted insert (other inserts available on request)
Impact resistance	7 J in accordance with IEC 60079-0, IK 09 (10J) in accordance with DIN EN 50102
Gasket material	Silicone
Operating temperature range	-60 °C...+135 °C
Torque for flange plate screws	2.5 Nm
Note	* Painted steel enclosures are available on request.

Approvals for empty enclosures

ATEX certificate	IBExU14ATEX1028 U	EAC	RU-DE.08.B.00472
ATEX marking	II 2G Ex eb IIC Gb	cULus	E243298
	II 2D Ex tb IIIC Db	DNV GL	TAE000013S
IECEx certificate	IECEx IBE 14.0004U	Russian Maritime Register	15.40075.250
IECEx marking	Ex eb IIC Gb	CCOE	In preparation
	Ex tb IIIC Db	INMETRO	IEx 17.0020U
Nepsi Ex certificate	GYJ14.1308U	AEx	E223792
Nepsi Ex marking	Ex e IIC Gb, DIP A21	Miscellaneous	EN 45545, DIN EN 15085-2/CL2
Note	The Klippon® TB enclosure range can be pre-fitted in our customer specific production department according to your wishes.		

Approvals for control and distribution box

ATEX certificate	IBExU14ATEX1050	IECEx certificate	IECEx IBE 14.0013
ATEX marking	Ⓔ II 2G Ex eb IIC/IIB/IIA T6/T5/T4 Gb	IECEx marking	Ex eb IIC/IIB/IIA T6/T5/T4 Gb
	Ⓔ II 1G Ex ia IIC/IIB/IIA T6/T5/T4 Ga		Ex ia IIC/IIB/IIA T6/T5/T4 Ga
	Ⓔ II 2G Ex eb ia IIC/IIB/IIA T6/T5/T4 Gb		Ex eb ia IIC/IIB/IIA T6/T5/T4 Gb
	Ⓔ II 2D Ex tb IIIC T80°C/T95°C/T135°C Db		Ex tb IIIC T80°C/T95°C/T135°C Db
	Ⓔ II 1D Ex ia IIIC T80°C/T95°C/T135°C Da		Ex ia IIIC T80°C/T95°C/T135°C Da
	-60 °C ≤ Ta ≤ +40/+55/+90 °C		-60 °C...+40/+55/+90 °C
Nepsi Ex certificate	GYJ14.1309	INMETRO certificate	IEx 17.0021
Nepsi marking	Ex e IIC T4...T6 Gb	INMETRO marking	Ex eb IIC T6/T5/T4 Gb
	Ex ia IIC T4...T6 Ga		Ex ia IIC T6/T5/T4 Ga
	Ex e ia IIC T4...T6 Gb		Ex eb ia IIC T6/T5/T4 Gb
	DIP A21 T_A 85°C...T_A 135°C		Ex tb IIIC 85°C/100°C/135°C Db IP66/IP67
	Ex ia D20 T85 °C... T135 °C		Ex ia IIIC 85°C/100°C/135°C Da
EAC certificate	RUC-DE.08.B.01328	AEx certificate	E223792
EAC marking	II 2 G Ex eb IIC T6...T4	AEx marking	Class I, Zone 1, AEx e IIC Gb T6..T4
	II 2 G Ex e IIC T6...T4 Gb		Class I, Zone 2, AEx e IIC Gc T6..T4
	II 1 G Ex ia IIC T6...T4		Class I Div.2 Group A,B,C,D T6...T4
	II 1 G Ex ia IIC T6...T4 Ga		Class II Div.2 Group F,G
	II 2(1) G Ex eb ia IIC T6...T4		Zone 21, AEx tb IIIC Db
	II 2(1) G Ex e ia IIC T6...T4 Gb		
	II 2 D Ex tb IIIC T85°C...T135°C		
	II 2 D Ex tb IIIC T85°C...T135°C Db		
KOSHA certificate	16-AV4BO-0245X		
KOSHA marking	Ex eb IIC/IIB/IIA T6/T5/T4 Gb		
	Ex ia IIC/IIB/IIA T6/T5/T4 Ga		
	Ex eb ia IIC/IIB/IIA T6/T5/T4 Gb		
	Ex tb IIIC T80°C/T95°C/T135°C Db		
	Ex ia IIIC T80°C/T95°C/T135°C Da		
	-60 °C...+40/+55/+90 ° C		
Note	Labelling depends on the application layout. For details of power dissipation, please contact your Weidmüller representative. Additional approvals available on request.		

Klippon® TB FS – Fixing Screw

Steel enclosures
for use in industrial and in explosive hazard areas

The Klippon® TB enclosure range features superior performance characteristics, even under the most extreme environmental conditions. The Klippon® TB FS enclosure range complements our Klippon® TB MH and Klippon® TB QL standard enclosures.

Weidmüller manufactures and supplies the enclosures to match customer specifications – fully fitted with terminals, electronics and cable glands.

Features:

- Available in 12 sizes and 3 standard depths
- Equipped with up to 4 gland plates
- The gasket is protected against compression
- Cover lock outside the sealed zone
- Improved temperature performance
- IP66/IP67 protection class
- Earth studs in enclosure cover and bottom section
- Welded mounting feet

Use our online catalogue to find additional product details, technical information and additional services:

www.weidmueller.com/KlipponTB

Overview of enclosures

Ordering data

Description	Length x width x depth in mm	0 Gland Plate	1 Gland Plate (below)	2 Gland Plates (above + below)	3 Gland Plates (below + sides)	4 Gland Plates (all sides)
KTB FS 221513 S4E_*	229 x 152 x 133	1195650000	1195660000	1195670000	1195680000	1195690000
KTB FS 262615 S4E_*	260 x 260 x 150	1195700000	1195710000	1195720000	1195730000	1195740000
KTB FS 262620 S4E_*	260 x 260 x 200	1195750000	1195760000	1195770000	1195780000	1195790000
KTB FS 303015 S4E_*	306 x 306 x 150	1195800000	1195810000	1195820000	1195830000	1195840000
KTB FS 303020 S4E_*	306 x 306 x 200	1195850000	1195860000	1195870000	1195880000	1195890000
KTB FS 352615 S4E_*	350 x 260 x 150	1195900000	1195910000	1195920000	1195930000	1195940000
KTB FS 352620 S4E_*	350 x 260 x 200	1195950000	1195960000	1195970000	1195980000	1195990000
KTB FS 403015 S4E_*	400 x 300 x 150	1196000000	1196010000	1196020000	1196030000	1196040000
KTB FS 403020 S4E_*	400 x 300 x 200	1196050000	1196060000	1196070000	1196080000	1196090000
KTB FS 453815 S4E_*	458 x 382 x 150	1196100000	1196110000	1196120000	1196130000	1196140000
KTB FS 453820 S4E_*	458 x 382 x 200	1196150000	1196160000	1196170000	1196180000	1196190000
KTB FS 484815 S4E_*	480 x 480 x 150	1196200000	1196210000	1196220000	1196230000	1196240000
KTB FS 484820 S4E_*	480 x 480 x 200	1196250000	1196260000	1196270000	1196280000	1196290000
KTB FS 553515 S4E_*	550 x 350 x 150	1196300000	1196310000	1196320000	1196330000	1196340000
KTB FS 553520 S4E_*	550 x 350 x 200	1196350000	1196360000	1196370000	1196380000	1196390000
KTB FS 624515 S4E_*	620 x 450 x 150	1196400000	1196410000	1196420000	1196430000	1196440000
KTB FS 624520 S4E_*	620 x 450 x 200	1196450000	1196460000	1196470000	1196480000	1196490000
KTB FS 765015 S4E_*	762 x 508 x 150	1196500000	1196510000	1196520000	1196530000	1196540000
KTB FS 765020 S4E_*	762 x 508 x 200	1196550000	1196560000	1196570000	1196580000	1196590000
KTB FS 916115 S4E_*	914 x 610 x 150	1196600000	1196610000	1196620000	1196630000	1196640000
KTB FS 916120 S4E_*	914 x 610 x 200	1196650000	1196660000	1196670000	1196680000	1196690000
KTB FS 987420 S4E_*	980 x 740 x 200	1196700000	1196710000	1196720000	1196730000	1196740000
Note		* Placeholder for the number of gland plates (0, 1, 2, 3, 4). The Klippon® TB FS enclosures are subject to a minimum order quantity.				

Technical Overview

Technical data

Enclosure material*	Stainless steel 1.4404 (316L) 1.5 mm
Surface	Electroplished
IP protection class	IP66 / IP67 (IP66 to IEC EN 60079-0)
NEMA Rating	3, 4x, 12
Gland plates	1 - 4 (fixed with M6 hexagon head screws with a slot and 10 mm heads), optionally without a gland plate
Gland plate thickness	3 mm (other thickness are available on request)
Earthing inside	Enclosure base part and enclosure cover: welded M6 stainless steel earth studs
Earthing outside	Continuous M10 brass earth stud (optionally with stainless-steel earth stud)
Installation mounting	4 or 9 mounting bolts with M6 threaded holes to attach the mounting plate or mounting rails
Enclosure attachment	4 or 6 welded-on mounting feet with 11-mm holes (2 slotted and 2 cross-shaped openings)
Lid opening	Fully removable lid
Lid fixing	M6 hexagon head slotted screws SW10
Impact resistance	7J in accordance with IEC 60079-0, IK 09 (10J) in accordance with DIN EN 50102
Gasket material	Silicone
Operating temperature range	–60 °C...+105 °C (IP66/IP67), –60 °C...+135 °C (IP66)
Torque - cover and flange plate screws	2.5 Nm
Note	* Lacquered enclosures available on request.

Approvals for empty enclosures

ATEX certificate	IBExU14ATEX1028 U	EAC	RU-DE.08.B.00472
ATEX marking	II 2G Ex eb IIC Gb	cULus	E256877
	II 2D Ex tb IIIC Db	DNV GL	TAE000013S
IECEx certificate	IECEx IBE 14.0004U	Russian Maritime Register	15.40074.250
IECEx marking	Ex eb IIC Gb	CCOE	In preparation
	Ex tb IIIC Db	INMETRO	IEx 17.0020U
Nepsi Ex certificate	GYJ14.1308U	AEx	E223792
Nepsi Ex marking	Ex e IIC Gb, DIP A21	Miscellaneous	EN 45545, DIN EN 15085-2/CL2
Note	The Klippon® TB enclosure range can be pre-fitted in our customer specific production department according to your wishes.		

Approvals for control and distribution box

ATEX certificate	IBExU14ATEX1050	IECEx certificate	IECEx IBE 14.0013
ATEX marking	Ⓔ II 2G Ex eb IIC/IIB/IIA T6/T5/T4 Gb	IECEx marking	Ex eb IIC/IIB/IIA T6/T5/T4 Gb
	Ⓔ II 1G Ex ia IIC/IIB/IIA T6/T5/T4 Ga		Ex ia IIC/IIB/IIA T6/T5/T4 Ga
	Ⓔ II 2G Ex eb ia IIC/IIB/IIA T6/T5/T4 Gb		Ex eb ia IIC/IIB/IIA T6/T5/T4 Gb
	Ⓔ II 2D Ex tb IIIC T80°C/T95°C/T135°C Db		Ex tb IIIC T80°C/T95°C/T135°C Db
	Ⓔ II 1D Ex ia IIIC T80°C/T95°C/T135°C Da		Ex ia IIIC T80°C/T95°C/T135°C Da
	-60 °C ≤ Ta ≤ +40/+55/+90 °C		-60 °C...+40/+55/+90 °C
Nepsi Ex certificate	GYJ14.1309	INMETRO certificate	IEx 17.0021
Nepsi marking	Ex e IIC T4...T6 Gb	INMETRO marking	Ex eb IIC T6/T5/T4 Gb
	Ex ia IIC T4...T6 Ga		Ex ia IIC T6/T5/T4 Ga
	Ex e ia IIC T4...T6 Gb		Ex eb ia IIC T6/T5/T4 Gb
	DIP A21 T_A 85°C...T_A 135°C		Ex tb IIIC 85°C/100°C/135°C Db IP66/IP67
	Ex ia D20 T85 °C... T135 °C		Ex ia IIIC 85°C/100°C/135°C Da
EAC certificate	RUC-DE.08.B.01328	AEx certificate	E223792
EAC marking	II 2 G Ex eb IIC T6...T4	AEx marking	Class I, Zone 1, AEx e IIC Gb T6..T4
	II 2 G Ex e IIC T6...T4 Gb		Class I, Zone 2, AEx e IIC Gc T6..T4
	II 1 G Ex ia IIC T6...T4		Class I Div.2 Group A,B,C,D T6...T4
	II 1 G Ex ia IIC T6...T4 Ga		Class II Div.2 Group F,G
	II 2(1) G Ex eb ia IIC T6...T4		Zone 21, AEx tb IIIC Db
	II 2(1) G Ex e ia IIC T6...T4 Gb		
	II 2 D Ex tb IIIC T85°C...T135°C		
	II 2 D Ex tb IIIC T85°C...T135°C Db		
KOSHA certificate	16-AV4BO-0245X		
KOSHA marking	Ex eb IIC/IIB/IIA T6/T5/T4 Gb		
	Ex ia IIC/IIB/IIA T6/T5/T4 Ga		
	Ex eb ia IIC/IIB/IIA T6/T5/T4 Gb		
	Ex tb IIIC T80°C/T95°C/T135°C Db		
	Ex ia IIIC T80°C/T95°C/T135°C Da		
	-60 °C...+40/+55/+90 °C		
Note	Labelling depends on the application layout. For details of power dissipation, please contact your Weidmüller representative. Additional approvals available on request.		

Klippon® Protect – Terminal Boxes – Product overview Steel enclosures

Various types of terminal boxes are available for installing signal / power supplies or distributors in explosive risk zones.
The terminal boxes are explosion-protected equipment approved for use in Ex areas in zones 0, 1, 2 and 20, 21, 22.

They are certified in accordance with the latest international standards Ex e, Ex ia and Ex tb. Customer-specific configuration means these terminal boxes are the optimum solution for all applications. Use the product overview to find the right solution for you!
Combine the enclosure, with or without threaded holes, a suitable mounting rail or pre-fitted strip terminals.

We have put together a small selection for you,
but we are happy to configure a bespoke solution for you.

Features:
- Available in a wide range of versions to meet customer requirements
- Additional international approvals alongside IECEx, ATEX and EAC also available
- Increased quality thanks to the use of established basic products in the Klippon® brand

Overview of enclosures

Terminal boxes based on the Klippon® TB range of enclosures

Description	Height x width x depth in mm	Marking	Approval	Order No.
KTB MH 221513 Exia	229 x 152 x 133	Ex ia IIC T4 Ga	IECEx, ATEX, EAC	8000028398
KTB MH 262615 Exia	260 x 260 x 150	Ex ia IIC T4 Ga	IECEx, ATEX, EAC	8000028399
KTB QL 303020 Exe	306 x 306 x 200	Ex eb IIC T6 Gb	IECEx, ATEX, EAC	8000028400
KTB QL 484820 Exe	480 x 480 x 200	Ex eb IIC T6 Gb	IECEx, ATEX, EAC	8000028401
Note				

Technical Overview

Technical data

Enclosures	
Material	Stainless steel 1.4404 (316L) 1.5 mm
Surface finish	Electropolished (Klippon® TB)
IP protection class	IP66 / IP67 to DIN EN 60529
Gasket material	Silicone
Terminal block	
Material	Wemid
Colour	beige, blue or green/yellow
Connection system	screw connection
Clampable wires (H05V/H07V)	solid, flexible and flexible with ferrule
Note	

Approvals for Klippon® TB

ATEX certificate	IBExU14ATEX1050
IECEx certificate	IECEx IBE 14.0013
EAC certificate	RUC-DE.08.B.01328
Note	Labelling depends on the application layout. For details of power dissipation, please contact your Weidmüller representative.

Klippon® TB MH 221513 Ex ia terminal box

Depth 133 mm



Height / Width / Depth	229 / 152 / 133 mm

Ordering data

	Order No.
KTB MH 221513 Exia	8000028398
Note	

Technical data

Article - short description	Klippon® Klippon TB (Terminal Box)-Enclosures, Terminal Box
Identification	Ex ia IIC T4 Ga
Certificate no. assembled enclosure (ATEX)	IBExU14ATEX1050
Certificate no. assembled enclosure (IECEx)	IECEx IBE 14.0013
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-11, IEC 60079-31, EN 60079-0, EN 60079-7, EN 60079-11, EN 60079-31, EN/IEC 60079-26
Ambient temperature	Tamb -40°C...+55°C
Type label material	Polyester coated with aluminium
Protection class	IP66
Assembly	
Modular terminal blocks	1x22
Rated cross-section	4 mm²
Rated voltage	60 V
Rated current	1.00 A
Drill holes side A	none
Drill holes side B	2 x M16, 3 x M20, 1 x BDX
Technical data, enclosure	
Material	Stainless steel 1.4404 (316L)
Surface finish	electropolished
Material thickness	1.5 mm
Material thickness of flange	3 mm
Gland plates	Bottom
Seal material	Silicone
Enclosure attachment	4 welded-on mounting feet with 11 mm hole size
Mounting dimension - height / -width	152 mm / 178 mm
Lid attachment	4 hinges and M6 hex-head slotted screws SW10
Access opening: height / Access opening: width	176 mm / 93 mm
Earth, enclosure, external	Continuous M10 earth stud in body enclosure
Earth, enclosure, internal	Welded-on M6 stainless-steel earth stud in enclosure body and lid.

Note

Accessories

Mounting plates and fastening screws	Order No.
Stainless steel 1.4301 natural	1193810000
Fastening screws for mounting plates	0642600000
Gland plate 3 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1280890000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256270000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281360000
Label holder	
70 x 70 angled stainless steel 1.4301	1279320000
Earthing stud	
Stainless steel 1.4404, M10	1192690000
Pressure compensating element with drainage function	
M20, brass	2519520000
Cable glands	
Nickel-plated brass, Ex e, M16, 3-12 mm	1460040000
Nickel-plated brass, Ex e, M20, 3-12 mm	1460050000
Blanking plugs	
Stainless steel 1.4404 (316L), Ex e, M16	1477820000
Stainless steel 1.4404 (316L), Ex e, M20	1477840000
Locknuts	
Nickel-plated brass, M16	1736990000
Nickel-plated brass, M20	1737000000
Grounding strap	
green-yellow, 6 mm² for M6 bolt	2475490000
Note	

Reference products

	Order No.
KTB MH 221513 S4E1	1194560000
WDU 4 BL	1020180000
KLIPPON BDX M20 S	2519550000

Note

Note

Klippon® TB MH 262615 Ex ia terminal box

Depth 150 mm



Height / Width / Depth	260 / 260 / 150 mm

Ordering data

	Order No.
KTB MH 262615 Exia	8000028399
Note	

Technical data

Article - short description	Klippon® Klippon TB (Terminal Box)-Enclosures, Terminal Box
Identification	Ex ia IIC T4 Ga
Certificate no. assembled enclosure (ATEX)	IBExU14ATEX1050
Certificate no. assembled enclosure (IECEx)	IECEx IBE 14.0013
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-11, IEC 60079-31, EN 60079-0, EN 60079-7, EN 60079-11, EN 60079-31, EN/IEC 60079-26
Ambient temperature	Tamb -40°C...+55°C
Type label material	Polyester coated with aluminium
Protection class	IP66
Assembly	
Modular terminal blocks	1x30
Rated cross-section	4 mm²
Rated voltage	60 V
Rated current	1.00 A
Drill holes side A	none
Drill holes side B	5 x M20, 1 x M32, 1 x BDX
Technical data, enclosure	
Material	Stainless steel 1.4404 (316L)
Surface finish	electropolished
Material thickness	1.5 mm
Material thickness of flange	3 mm
Gland plates	Bottom
Seal material	Silicone
Enclosure attachment	4 welded-on mounting feet with 11 mm hole size
Mounting dimension - height / -width	170 mm / 286 mm
Lid attachment	4 hinges and M6 hex-head slotted screws SW10
Access opening: height / Access opening: width	207 mm / 201 mm
Earth, enclosure, external	Continuous M10 earth stud in body enclosure
Earth, enclosure, internal	Welded-on M6 stainless-steel earth stud in enclosure body and lid.

Note

Accessories

Mounting plates and fastening screws	Order No.
Stainless steel 1.4301 natural	1193820000
Fastening screws for mounting plates	0642600000
Gland plate 3 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1280910000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256290000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281370000
Label holder	
100x25 stainless steel 1.4301	1257640000
130x50 stainless steel 1.4301	1283450000
70 x 70 angled stainless steel 1.4301	1279320000
Earthing stud	
Stainless steel 1.4404, M10	1192690000
Document holders	
For DIN A6 size documents	1252780000
Pressure compensating element with drainage function	
M20, brass	2519520000
Cable glands	
Nickel-plated brass, Ex e, M20, 3-12 mm	1460050000
Nickel-plated brass, Ex e, M32, 14-24 mm	1460080000
Blanking plugs	
Stainless steel 1.4404 (316L), Ex e, M20	1477840000
Stainless steel 1.4404 (316L), Ex e, M32	1477890000
Locknuts	
Nickel-plated brass, M20	1737000000
Nickel-plated brass, M32	1737020000
Grounding strap	
green-yellow, 6 mm² for M6 bolt	2475490000
Note	

Reference products

	Order No.
KTB MH 262615 S4E1	1194610000
WDU 4 BL	1020180000
KLIPPON BDX M20 S	2519550000

Note

Note

Klippon® TB QL 303020 Ex e terminal box

Depth 200 mm



Height / Width / Depth	306 / 306 / 200 mm

Ordering data

	Order No.
KTB QL 303020 EXE	8000028400
Note	

Technical data

Article - short description	Klippon® Klippon TB (Terminal Box)-Enclosures, Terminal Box
Identification	Ex eb IIC T6 Gb
Certificate no. assembled enclosure (ATEX)	IBExU14ATEX1050
Certificate no. assembled enclosure (IECEx)	IECEx IBE 14.0013
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-31, EN 60079-0, EN 60079-7, EN 60079-31
Ambient temperature	Tamb -40°C...+40°C
Type label material	Polyester coated with aluminium
Protection class	IP66
Assembly	
Modular terminal blocks	1x32, 4 x PE
Rated cross-section	4 mm²
Rated voltage	550 V
Rated current	6.00 A
Drill holes side A	none
Drill holes side B	6 x M20, 1 x M32, 1 x BDX
Technical data, enclosure	
Material	Stainless steel 1.4404 (316L)
Surface finish	electropolished
Material thickness	1.5 mm
Material thickness of flange	3 mm
Gland plates	Bottom
Seal material	Silicone
Enclosure attachment	4 welded-on mounting feet with 11 mm hole size
Mounting dimension - height / -width	203 mm / 332 mm
Lid attachment	Quarter-turn fastener with slotted insert
Access opening: height / Access opening: width	253 mm / 247 mm
Earth, enclosure, external	Continuous M10 earth stud in body enclosure
Earth, enclosure, internal	Welded-on M6 stainless-steel earth stud in enclosure body and lid.

Note

Accessories

Mounting plates and fastening screws	Order No.
Stainless steel 1.4301 natural	1193830000
Fastening screws for mounting plates	0642600000
Gland plate 3 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1280970000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256360000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281400000
Label holder	
100x25 stainless steel 1.4301	1257640000
130x50 stainless steel 1.4301	1283450000
70 x 70 angled stainless steel 1.4301	1279320000
Document holders	
For DIN A6 size documents	1252780000
Earthing stud	
Stainless steel 1.4404, M10	1192690000
Pressure compensating element with drainage function	
M20, brass	2519520000
Cable glands	
Nickel-plated brass, Ex e, M20, 3-12 mm	1460050000
Nickel-plated brass, Ex e, M32, 14-24 mm	1460080000
Blanking plugs	
Stainless steel 1.4404 (316L), Ex e, M20	1477840000
Stainless steel 1.4404 (316L), Ex e, M32	1477890000
Locknuts	
Nickel-plated brass, M20	1737000000
Nickel-plated brass, M32	1737020000
Grounding strap	
green-yellow, 6 mm² for M6 bolt	2475490000
Note	

Reference products

	Order No.
KTB QL 303020 S4E1	1200070000
WDU 4	1020100000
WPE 4	1010100000
KLIPPON BDX M20 S	2519550000

Note

Note

Klippon® TB QL 484820 Ex e terminal box

Depth 200 mm



Height / Width / Depth	480 / 480 / 200 mm

Ordering data

	Order No.
KTB QL 484820 Exe	8000028401
Note	

Technical data

Article - short description	Klippon® Klippon TB (Terminal Box)-Enclosures, Terminal Box
Identification	Ex eb IIC T6 Gb
Certificate no. assembled enclosure (ATEX)	IBExU14ATEX1050
Certificate no. assembled enclosure (IECEx)	IECEx IBE 14.0013
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-31, EN 60079-0, EN 60079-7, EN 60079-31
Ambient temperature	Tamb -40°C...+40°C
Type label material	Polyester coated with aluminium
Protection class	IP66
Assembly	
Modular terminal blocks	1x66, 1x59, 5 x PE
Rated cross-section	4 mm²
Rated voltage	550 V
Rated current	6.00 A
Drill holes side A	none
Drill holes side B	2 x M20, 2 x M25, 1 x M40
Technical data, enclosure	
Material	Stainless steel 1.4404 (316L)
Surface finish	electropolished
Material thickness	1.5 mm
Material thickness of flange	3 mm
Gland plates	Bottom
Seal material	Silicone
Enclosure attachment	4 welded-on mounting feet with 11 mm hole size
Mounting dimension - height / -width	327 mm / 506 mm
Lid attachment	Quarter-turn fastener with slotted insert
Access opening: height / Access opening: width	427 mm / 421 mm
Earth, enclosure, external	Continuous M10 earth stud in body enclosure
Earth, enclosure, internal	Welded-on M6 stainless-steel earth stud in enclosure body and lid.
Note	

Accessories

Mounting plates and fastening screws	Order No.
Stainless steel 1.4301 natural	1193870000
Fastening screws for mounting plates	0642600000
Gland plate 3 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1281130000
Gland plates and screws - 6 mm	
Top and bottom sides (A & B), electropolished stainless steel 1.4404	1256550000
Mounting screw, stainless steel 1.4404	1253230000
Rain hoods	
Stainless steel 1.4301, mirror-polished	1281480000
Label holder	
100x25 stainless steel 1.4301	1257640000
130x50 stainless steel 1.4301	1283450000
70 x 70 angled stainless steel 1.4301	1279320000
Document holders	
For DIN A6 size documents	1252780000
For DIN A4 size documents	1252730000
Earthing stud	
Stainless steel 1.4404, M10	1192690000
Pressure compensating element with drainage function	
M20, brass	2519520000
Cable glands	
Nickel-plated brass, Ex e, M20, 3-12 mm	1460050000
Nickel-plated brass, Ex e, M25, 10-18 mm	1460070000
Nickel-plated brass, Ex e, M40, 22-32 mm	1460090000
Blanking plugs	
Stainless steel 1.4404 (316L), Ex e, M20	1477840000
Stainless steel 1.4404 (316L), Ex e, M25	1477870000
Stainless steel 1.4404 (316L), Ex e, M40	1477910000
Locknuts	
Nickel-plated brass, M20	1737000000
Nickel-plated brass, M25	1737010000
Nickel-plated brass, M40	1737030000
Grounding strap	
green-yellow, 6 mm² for M6 bolt	2475490000
Note	

Reference products

	Order No.
KTB QL 484820 S4E1	1200510000
WDU 4	1020100000
WPE 4	1010100000
KLIPPON BDX M20 S	2519550000
Note	

Perfect protection for your components

Klippon® EBi stainless steel enclosures for industrial applications

Industrial environments place high demands on the enclosures. Even moderate environmental conditions require sophisticated measures for protecting the internal components from dust and moisture to ensure trouble-free operation.

Klippon® EBi stainless steel enclosures provide perfect protection for instrumentation, distribution, and control applications. All versions are dust- and water ingress-proof to IP66 or NEMA 4X and impact-resistant to IK09. They are made of durable 1.4301 stainless steel and comply with the latest international standards. The Klippon® EBi enclosures are available with or without a bottom gland plate. Lid fixing options include either a quarter lock (QL) as standard or a fixing screw (FS) version which is available on a request basis.

Your special advantages:

- Protection class IP66 / NEMA 4X
- Impact resistance according to IK09
- International conformity according to EN 62208, DNV GL and UL
- Operating temperatures from -40 °C to +85 °C
- PUR cover gasket for protection and safety
- Flexible wall assembly thanks to rear mounting holes or mounting feet (optional)
- Individual configuration supported by the Weidmüller Configurator (WMC)

Use our online catalogue to find additional product details, technical information and additional services:

www.weidmueller.com/KlipponEBi

Quarter Lock Insert
Hinged door with a quarter lock facility ensures safe and easy accessibility. If required, hinges can be placed on either side of the enclosure to support side by side placement.

Gland plate with Torx® screws
Torx® screws (M5/T20) are used for gland plate mounting to facilitate compliance with the required torque.

Flexible mounting
A dedicated mounting profile facilitates the flexible, simple and secure installation of mounting rails or mounting plates for component installation within the enclosure.

Klippon® EBi QL – Quarter Lock

Stainless steel enclosures
for use within harsh industrial environments

Even under moderate environmental conditions, there is an increasing need for complex, individual automated solutions. A harsh industrial environment places additional, heavy demands on applications and determines the design of the industrial enclosures to meet these demands. With complete protection and excellent durability, our Klippon® EBi stainless steel enclosures offer the best protection for the components inside them.

- Available in 11 sizes and 2 depths
- Impact resistance IK09 (10J) in accordance with DIN EN 50102 for industrial applications
- Dedicated internal mounting support bracket for fixing terminal rail or mounting plates with self forming screws
- Concealed hinges
- Supplied in 0 or 1 gland plate version
- Direct enclosure mounting is provided via the fixing positions placed into the rear of the enclosure
- Mounting feet in stainless steel are optionally available and can be rotated 90°
- Dust and moisture channel
- Double-bit locking system

Our assembly service can supply these enclosure preassembled with terminals, electronics and cable glands.

Use our online catalogue to find additional product details, technical information and additional services:
www.weidmueller.com/KlipponEBi

Overview of enclosures

Ordering data

Description	Height x width x depth in mm	0 Gland Plate	1 Gland Plate (below)
KEBi QL 302015 S2B_* **	300 x 200 x 150	2470690000	2470800000
KEBi QL 303015 S2B_* **	300 x 300 x 150	2470700000	2470810000
KEBi QL 303022 S2B_* **	300 x 300 x 220	2470710000	2470820000
KEBi QL 403015 S2B_*	400 x 300 x 150	2470720000	2470830000
KEBi QL 403022 S2B_*	400 x 300 x 220	2470730000	2470840000
KEBi QL 404022 S2B_*	400 x 400 x 220	2470740000	2470850000
KEBi QL 504022 S2B_*	500 x 400 x 220	2470750000	2470860000
KEBi QL 505022 S2B_*	500 x 500 x 220	2470760000	2470870000
KEBi QL 604022 S2B_*	600 x 400 x 220	2470770000	2470880000
KEBi QL 606022 S2B_*	600 x 600 x 220	2470780000	2470890000
KEBi QL 806022 S2B_*	800 x 600 x 220	2470790000	2470900000
Note	*Placeholder for the number of gland plates (0 or 1), **smaller reference size for material thickness		

Technical Overview

Features

• Available in 11 sizes and 2 standard depths
• Welded mounting bracket for securing the mounting plate or mounting rail by means of self-tapping screws
• External earth - M6 earth rivet
• Concealed hinges
• M6 earthing bolt welded in the cover and base of the enclosure
• Available with 0 or 1 gland plates
• Optimised laser welding, high quality standard
• Direct mounting of the enclosure with rear mounting holes
• Mounting feet in stainless steel are optionally available, and can be rotated by 90°
• Moisture and dust channel
• Double-bit locking system
• Permanent labelling of items
• Key included for sash lock
• Packaging optimally designed for enclosure
Note

Technical data

Material	Stainless steel 1.4301 (304) 1.5 mm (1.25 mm for smaller sizes**)
Surface	Brushed – grain size 240
IP protection class	IP 66 to DIN EN 60529
NEMA Rating	3, 4x, 5
Gland plates	Stainless steel 1.4301 (304) 2 mm, fitted with M5 Torx T20 screws
Earthing inside	Welded-on M6 stainless-steel earth stud in enclosure lid and base
Earthing outside	External earth position – suitable for M6 threaded screw
Installation mounting	Welded mounting bracket for flexible mounting of the mounting plate, rails or TAS 20 rails. They contain 4.51 mm drill holes for accommodating the mounting plate or TS/TAS by means of self-tapping screws (1274150000)
Enclosure attachment	Direct mounting (9 mm mounting holes on rear wall) or via mounting feet (optionally available), adjustable by 90°
Lid opening	125°
Lid fixing	Quarter lock with double bit
Impact resistance	IK09 (10J) to DIN EN 50102
Gasket material	Polyurethane (PUR) foam (cover), EPDM flat gasket (gland plate)
Operating temperature range	-40 °C ... +85 °C
Tightening torque of gland plates screws*	2.5 Nm
Note	*SD TH20 screwdriver (9009160000) optionally available

Approvals for empty enclosures

Empty enclosure standard	DIN EN 62208
DNV GL	TAE00002RN
cULus	E 243298
Note	For details of power dissipation, please contact your Weidmüller representative.

Klippon® EBi QL 302015

Depth 150 mm

Height / Width / Depth	300 / 200 / 150 mm



Ordering data

Stainless steel 1.4301 (304), brushed	Order No.
0 gland plates	2470690000
1 gland plate - positioned at the bottom (B)	2470800000
Note	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1309690000
Stainless steel 1.4301 natural	1309700000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Vertical	8000037556
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Mild steel nickel plated Spacer M6 x 8, set of 2	
15 mm length	3896100000
20 mm length	3896200000
30 mm length	3896300000
Mounting feet, set containing 4 pieces each	
Stainless steel 1.4301 natural	1289180000
Lock inserts	
Slot	1191600000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Double-bit key	
	2473930000

Note
*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	1x36	3x17
4 mm²	1x30	3x14
6 mm²	1x23	3x11
10 mm²	1x18	3x9
16 mm²	1x15	3x7
35 mm²	1x11	3x5

Note
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.Order recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	21	33
M16	15	27
M20	8	14
M25	6	12
M32	3	5
M40	2	4
M50	2	3
M63	1	2
M75		

Note Our IP 68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® EBi QL 303015

Depth 150 mm

Height / Width / Depth	300 / 300 / 150 mm



Ordering data

Stainless steel 1.4301 (304), brushed	Order No.
0 gland plates	2470700000
1 gland plate - positioned at the bottom (B)	2470810000
Note	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1310410000
Stainless steel 1.4301 natural	1310320000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Vertical	8000037556
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Mild steel nickel plated Spacer M6 x 8, set of 2	
15 mm length	3896100000
20 mm length	3896200000
30 mm length	3896300000
Mounting feet, set containing 4 pieces each	
Stainless steel 1.4301 natural	1289180000
Lock inserts	
Slot	1191600000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Double-bit key	
	2473930000

Note

*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	3x36	3x36
4 mm²	3x30	3x30
6 mm²	3x23	3x23
10 mm²	3x18	3x18
16 mm²	3x15	3x15
35 mm²	3x11	3x11

Note

The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.Order recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	33	33
M16	27	27
M20	14	14
M25	12	12
M32	5	5
M40	4	4
M50	3	3
M63	2	2
M75		

Note

Our IP 68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® EBi QL 303022

Depth 220 mm

Height / Width / Depth	300 / 300 / 220 mm



Ordering data

Stainless steel 1.4301 (304), brushed	Order No.
0 gland plates	2470710000
1 gland plate - positioned at the bottom (B)	2470820000
Note	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1310410000
Stainless steel 1.4301 natural	1310320000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Vertical	8000037556
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Mild steel nickel plated Spacer M6 x 8, set of 2	
15 mm length	3896100000
20 mm length	3896200000
30 mm length	3896300000
Mounting feet, set containing 4 pieces each	
Stainless steel 1.4301 natural	1289180000
Lock inserts	
Slot	1191600000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Double-bit key	
	2473930000

Note

*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	3x36	3x36
4 mm²	3x30	3x30
6 mm²	3x23	3x23
10 mm²	3x18	3x18
16 mm²	3x15	3x15
35 mm²	3x11	3x11

Note

The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.Order recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	76	76
M16	45	45
M20	28	28
M25	18	18
M32	15	15
M40	8	8
M50	6	6
M63	2	2
M75	2	2

Note Our IP 68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® EBi QL 403015

Depth 150 mm



Height / Width / Depth	400 / 300 / 150 mm

Ordering data

Stainless steel 1.4301 (304), brushed	Order No.
0 gland plates	2470720000
1 gland plate - positioned at the bottom (B)	2470830000
Note	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1310420000
Stainless steel 1.4301 natural	1310330000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Vertical	8000037555
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Mild steel nickel plated Spacer M6 x 8, set of 2	
15 mm length	3896100000
20 mm length	3896200000
30 mm length	3896300000
Mounting feet, set containing 4 pieces each	
Stainless steel 1.4301 natural	1289180000
Lock inserts	
Slot	1191600000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Double-bit key	
	2473930000

Note
*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	3x56	4x36
4 mm²	3x47	4x30
6 mm²	3x35	4x23
10 mm²	3x28	4x18
16 mm²	3x23	4x15
35 mm²	3x18	4x11

Note
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.Order recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	33	48
M16	27	39
M20	14	20
M25	12	16
M32	5	7
M40	4	5
M50	3	4
M63	2	3
M75		

Note Our IP 68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® EBi QL 403022

Depth 220 mm

Height / Width / Depth	400 / 300 / 220 mm



Ordering data

Stainless steel 1.4301 (304), brushed	Order No.
0 gland plates	2470730000
1 gland plate - positioned at the bottom (B)	2470840000
Note	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1310420000
Stainless steel 1.4301 natural	1310330000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Vertical	8000037555
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Mild steel nickel plated Spacer M6 x 8, set of 2	
15 mm length	3896100000
20 mm length	3896200000
30 mm length	3896300000
Mounting feet, set containing 4 pieces each	
Stainless steel 1.4301 natural	1289180000
Lock inserts	
Slot	1191600000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Double-bit key	
	2473930000

Note
*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	3x56	4x36
4 mm²	3x47	4x30
6 mm²	3x35	4x23
10 mm²	3x28	4x18
16 mm²	3x23	4x15
35 mm²	3x18	4x11

Note
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.Order recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	76	112
M16	45	65
M20	28	40
M25	18	24
M32	15	21
M40	8	10
M50	6	8
M63	2	3
M75	2	2

Note Our IP 68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® EBi QL 404022

Depth 220 mm

Height / Width / Depth	400 / 400 / 220 mm



Ordering data

Stainless steel 1.4301 (304), brushed	Order No.
0 gland plates	2470740000
1 gland plate - positioned at the bottom (B)	2470850000
Note	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1310430000
Stainless steel 1.4301 natural	1310340000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Vertical	8000037555
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Mild steel nickel plated Spacer M6 x 8, set of 2	
15 mm length	3896100000
20 mm length	3896200000
30 mm length	3896300000
Mounting feet, set containing 4 pieces each	
Stainless steel 1.4301 natural	1289180000
Lock inserts	
Slot	1191600000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Double-bit key	
	2473930000

Note

*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	4x56	4x56
4 mm²	4x47	4x47
6 mm²	4x35	4x35
10 mm²	4x28	4x28
16 mm²	4x23	4x23
35 mm²	4x18	4x18

Note

The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.Order recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	112	112
M16	65	65
M20	40	40
M25	24	24
M32	21	21
M40	10	10
M50	8	8
M63	3	3
M75	2	2

Note Our IP 68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® EBi QL 504022

Depth 220 mm

Height / Width / Depth	500 / 400 / 220 mm



Ordering data

Stainless steel 1.4301 (304), brushed	Order No.
0 gland plates	2470750000
1 gland plate - positioned at the bottom (B)	2470860000
Note	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1310440000
Stainless steel 1.4301 natural	1310350000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Vertical	8000037554
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Mild steel nickel plated Spacer M6 x 8, set of 2	
15 mm length	3896100000
20 mm length	3896200000
30 mm length	3896300000
Mounting feet, set containing 4 pieces each	
Stainless steel 1.4301 natural	1289180000
Lock inserts	
Slot	1191600000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Double-bit key	
	2473930000

Note

*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	4x75	6x56
4 mm²	4x63	6x47
6 mm²	4x47	6x35
10 mm²	4x38	6x28
16 mm²	4x32	6x23
35 mm²	4x24	6x18

Note

The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.Order recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	112	140
M16	65	85
M20	40	52
M25	24	33
M32	21	27
M40	10	14
M50	8	10
M63	3	4
M75	2	3

Note Our IP 68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® EBi QL 505022

Depth 220 mm

Height / Width / Depth	500 / 500 / 220 mm



Ordering data

Stainless steel 1.4301 (304), brushed	Order No.
0 gland plates	2470760000
1 gland plate - positioned at the bottom (B)	2470870000
Note	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1310450000
Stainless steel 1.4301 natural	1310360000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Vertical	8000037554
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Mild steel nickel plated Spacer M6 x 8, set of 2	
15 mm length	3896100000
20 mm length	3896200000
30 mm length	3896300000
Mounting feet, set containing 4 pieces each	
Stainless steel 1.4301 natural	1289180000
Lock inserts	
Slot	1191600000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Double-bit key	
	2473930000

Note
*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	6x75	6x75
4 mm²	6x63	6x63
6 mm²	6x47	6x47
10 mm²	6x38	6x38
16 mm²	6x32	6x32
35 mm²	6x24	6x24

Note
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.Order recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	140	140
M16	85	85
M20	52	52
M25	33	33
M32	27	27
M40	14	14
M50	10	10
M63	4	4
M75	3	3

Note Our IP 68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® EBi QL 604022

Depth 220 mm

Height / Width / Depth	600 / 400 / 220 mm



Ordering data

Stainless steel 1.4301 (304), brushed	Order No.
0 gland plates	2470770000
1 gland plate - positioned at the bottom (B)	2470880000
Note	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1310460000
Stainless steel 1.4301 natural	1310370000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Vertical	8000037553
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Mild steel nickel plated Spacer M6 x 8, set of 2	
15 mm length	3896100000
20 mm length	3896200000
30 mm length	3896300000
Mounting feet, set containing 4 pieces each	
Stainless steel 1.4301 natural	1289180000
Lock inserts	
Slot	1191600000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Double-bit key	
	2473930000

Note
*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	4x94	8x56
4 mm²	4x79	8x47
6 mm²	4x60	8x35
10 mm²	4x48	8x28
16 mm²	4x40	8x23
35 mm²	4x30	8x18

Note
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.Order recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	112	176
M16	65	96
M20	40	64
M25	24	39
M32	21	33
M40	10	16
M50	8	14
M63	3	5
M75	2	4

Note Our IP 68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® EBi QL 606022

Depth 220 mm

Height / Width / Depth 600 / 600 / 220 mm



Ordering data

Stainless steel 1.4301 (304), brushed	Order No.
0 gland plates	2470780000
1 gland plate - positioned at the bottom (B)	2470890000
Note	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1310470000
Stainless steel 1.4301 natural	1310380000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Vertical	8000037553
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Mild steel nickel plated Spacer M6 x 8, set of 2	
15 mm length	3896100000
20 mm length	3896200000
30 mm length	3896300000
Mounting feet, set containing 4 pieces each	
Stainless steel 1.4301 natural	1289180000
Lock inserts	
Slot	1191600000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Double-bit key	
	2473930000

Note

*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	8x94	8x94
4 mm²	8x79	8x79
6 mm²	8x60	8x60
10 mm²	8x48	8x48
16 mm²	8x40	8x40
35 mm²	8x30	8x30

Note

The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.Order recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	165	176
M16	96	96
M20	64	64
M25	39	39
M32	33	33
M40	16	16
M50	14	14
M63	5	5
M75	4	4

Note Our IP 68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® EBi QL 806022

Depth 220 mm

800 / 600 / 220 mm



Ordering data

Stainless steel 1.4301 (304), brushed	Order No.
0 gland plates	2470790000
1 gland plate - positioned at the bottom (B)	2470900000
Note	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	1310480000
Stainless steel 1.4301 natural	1310390000
Fastening screws for terminal rails*	1274150000
Mounting rails, TS35x7.5**	
Vertical	8000037552
Stainless steel spacer M6 x 8, Set of 4	
10 mm length	0935110000
15 mm length	0935120000
20 mm length	0935130000
30 mm length	0935140000
Mild steel nickel plated Spacer M6 x 8, set of 2	
15 mm length	3896100000
20 mm length	3896200000
30 mm length	3896300000
Mounting feet, set containing 4 pieces each	
Stainless steel 1.4301 natural	1289180000
Lock inserts	
Slot	1191600000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Double-bit key	
	2473930000

Note
*Packing unit (PU) = 20 pcs., sufficient for 10 fixtures
**Packing unit (PU) = 20 pcs., fixing screws 1274150000 available separately

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	8x133	11x94
4 mm²	8x111	11x79
6 mm²	8x84	11x60
10 mm²	8x67	11x48
16 mm²	8x56	11x40
35 mm²	8x42	11x30

Note
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.Order recommendations:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	165	222
M16	96	140
M20	64	88
M25	39	54
M32	33	45
M40	16	22
M50	14	18
M63	5	7
M75	4	5

Note Our IP 68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® STB stainless and sheet steel enclosures

Protection for industrial standard applications and potentially explosive atmospheres

The Klippon® STB range manufactured from either sheet or stainless steel is the perfectly designed Small Terminal Box. It provides the ideal connection point for either industrial or harsh environment applications.

The name Klippon® has long been synonymous for competence and quality in the supply of enclosures and customer solutions. This philosophy continues with our Klippon® STB range of enclosures.

Flexible, internal mounting options
Terminal rails can be installed on the industry standard mounting rails using the provided fixing set with welded C-profile (TAS 20). A maximum possible internal working area is provided while ensuring a stable and flexible area for the rail assembly.



Internal / external earthing screw
The enclosures are supplied with a pre-welded internal and external M6 stainless steel earth stud.

Approvals
Klippon® STB enclosures have the latest international approvals.

Enhanced sealing performance
The new silicon seal has impressive thermal properties and can withstand temperatures from -60 °C to +120 °C. Compression protection ensures the complete functionality of the seal.

Industries
Klippon® STB enclosures can be used in a variety of applications. For example, they are ideal for use in standard applications such as machine construction or transportation. They can also be used in explosive risk zones in the process and petrochemical industry.



Mounting lugs
Mounting lugs are pre-fitted as standard. They are vibration and shock resistant and designed to be secure in operation.

Customised solutions
Weidmüller delivers enclosures in the Klippon® STB series connection ready. With Klippon Services, Weidmüller offers extensive consultation, engineering and installation services for modified enclosures. Depending on the customer- and industry-specific application, the enclosures can be modified and, subject to international specifications and regulations, sent worldwide together with a wide range of accessories.

Klippon® STB – Small Terminal Box

Steel enclosures

Ideally suited for the energy and process industry and transportation, the Klippon® STB range is the perfect complement to our existing Klippon® enclosure product line. Enclosures of this range comply with international standards.

Some of the many advantages of these cases are:
- Available in stainless steel or in steel sheet
- Higher temperature resistant seals than the standard
- Flexible options when mounting the internal rail
- The gasket is protected against compression; this ensures that a permanent and secure seal is maintained.
- Earth studs in the lid and in the enclosure base
- Lasered welding seams offer improved quality
- Delivered with welded mounting feet to ensure an sturdy enclosure installation

Weidmüller can manufacture and supply this enclosure to match customer specifications and fitted with all necessary terminals and cable glands.

Use our online catalogue to find additional product details, technical information and additional services:
www.weidmueller.com/KlipponSTB

Overview of enclosures

Ordering data

Description	Height x width x depth in mm	Mirror-polish	Electropolished	Powder-coated (RAL7032)
Klippon® STB 1	120 x 120 x 80	1002690000	1058810000	1024970000
Klippon® STB 1.1	150 x 120 x 80	1002750000	1058820000	1024980000
Klippon® STB 2	150 x 150 x 90	1002740000	1058830000	1024990000
Klippon® STB 2.1	190 x 150 x 90	1002730000	1058840000	1025010000
Klippon® STB 3	190 x 190 x 100	1002720000	1058850000	1025020000
Klippon® STB 4	250 x 250 x 120	1002710000	1058860000	1025030000
Klippon® STB 5	160 x 380 x 120	1002700000	1058880000	1025040000
Klippon® STB 6	250 x 400 x 130	1002760000	1058870000	1025050000
Note				

Technical Overview

Features

• Mirror-polished or electropolished stainless steel 1.4404 (316L) or powder coated steel sheet 1.0330
• Fitted with a welded, internal C-profile rail (TAS 20) and mounting feet
• Laser cut weld seams
• Approved according to the latest international standards
Note We deliver enclosures through our assembly service which are ready to be connected and suitable for every application

Technical data

	Stainless steel	Sheet steel
Enclosure material	Stainless steel 1.4404 (316L) in1.50 mm	Steel sheet 1.0330 in1.50 mm
Surface finish	Mirror-polished, electropolished	Powder-coated RAL 7032
IP protection class	IP 66	IP 66
NEMA Rating	4, 4x	
Earthing	Enclosure base part: internal / external M6 stainless steel Lid: M6 x 10 stainless steel	Enclosure base part: internal / external M6 stainless steel Lid: M6 x 10 stainless steel
Installation mounting	Welded C-profile rail	Welded C-profile rail
Enclosure attachment	2 external mounting feet with 8 mm holes	2 external mounting feet with 8 mm holes
Lid opening	Completely removable lid with 4 x M5 screws	Completely removable lid with 4 x M5 screws
Impact resistance	7J in accordance with IEC 60079-0	10J industrial version in accordance with DIN EN 50102
Gasket material	Silicone -60 °C...+100 °C *	Silicone -60 °C...+120 °C
Lid screws, torque	2.5 Nm	2.5 Nm
Note	* +120 °C only for industrial applications	

Approvals for empty enclosures

	Stainless steel	Sheet steel
ATEX certificate	IBExU07ATEX1147 U	
ATEX marking	⟨Ex⟩ II 2G Ex eb IIC Gb , ⟨Ex⟩ II 1G Ex ia IIC Ga, ⟨Ex⟩ II 2D Ex tb IIIC Db	
IECEx certificate	IECEx IBE 09.0018U	
IECEx marking	Ex eb IIC Gb, Ex ia IIC Ga, Ex tb IIIC Db	
AEx	E223792	
cULus	E197061 and E256877	
Lloyds Register	08/20032	08/20032
DNV GL	59 358 - 08 HH	
Russian Maritime Register	15.40041.250	15.40041.250
INMETRO	IEx 13.0002U	
EAC	RUC-DE.BE02.B.00173	
Note	This enclosure range is component certified. If other electrical components are inserted into the case, additional certification is required.	

Approvals for control and distribution box

	Stainless steel		
ATEX certificate	IBExU07ATEX1148	INMETRO certificte	IEx 13.0003
ATEX marking	⟨Ex⟩ II 2G Ex eb IIC T6/T5/T4 Gb ⟨Ex⟩ II 2(1)G Ex eb ia [Ga] IIC T6/T5/T4 Gb ⟨Ex⟩ II 1G Ex ia IIC T6/T5/T4 Ga ⟨Ex⟩ II 2D Ex tb IIIC T80°C/T95°C/T100°C Db -60°C ≤ Ta ≤ +40/+55/+60 °C	INMETRO marking	Ex eb IIC T6/T5/T4 Gb Ex e [ia Ga] IIC T6/T5/T4 Gb Ex ia IIC T6/T5/T4 Ga Ex tb IIIC T80°C/95°C/120°C Db IP66
IECEx certificate	IECEx IBE 09.0019	EAC certificte	RUC-DE.08.B.01328
IECEx marking	Ex eb IIC T6/T5/T4 Gb Ex eb ia [Ga] IIC T6/T5/T4 Gb Ex ia IIC T6/T5/T4 Ga Ex tb IIIC T80°C/T95°C/T100°C Db -60°C ≤ Ta ≤ +40/+55/+60 °C	EAC marking	II 2 G Ex e IIC T6...T4 Gb, II 2(1) G Ex e [ia Ga] IIC T6...T4 Gb, II 1 G Ex ia IIC T6...T4 Ga, II 2 D Ex tb IIIC T80°C...T130°C Db
KOSHA certificate	16-AV4B0-247X	AEx certificate	E223792
KOSHA marking	Ex eb IIC T6/T5/T4 Gb Ex eb ia [Ga] IIC T6/T5/T4 Gb Ex ia IIC T6/T5/T4 Ga Ex tb IIIC T80°C/T95°C/T100°C Db -60°C ≤ Ta ≤ +40/+55/+60 °C	AEx marking	Class I, Zone 1, AEx e IIC Gb T6..T4 Class I, Zone 2, AEx e IIC Gc T6..T4 Class I Div.2 Group A,B,C,D T6...T4 Class II Div.2 Group F,G Zone 21, AEx tb IIIC Db
Note	If you have specific requirements for equipment operating in explosive hazard areas, please contact us at Weidmüller to receive a full copy of the certification. For details of power dissipation, please contact your Weidmüller representative.		

Klippon® STB 1

Depth 80 mm



Height / Width / Depth	120 / 120 / 80 mm

Ordering data

Stainless steel 1.4404 (316L)	Order No.
mirror-polished	1002690000
electro-polished	1058810000
Sheet steel, powder-coated (RAL 7032)	
powder-coated	1024970000

Note The colours of painted enclosures may vary under certain circumstances.

Accessories

Mounting rails, TS35x7.5	Order No.
Vertical	8683740000
Sliding fixing nut with screw	
M5	0433500000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Pressure compensating element with drainage function	
M20, stainless steel 1.4404 (316L)	2519550000

Note The enclosure is supplied with a set of sliding fixing nuts, washer, screws M5, to fix the mounting rail TS 35 or TS 32 into the C-Profile.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	1x17	
4 mm²	1x14	
6 mm²	1x11	
10 mm²	1x8	
16 mm²	1x7	

Note
The mounting rails are designed to be installed directly.
Assembly with terminals provides for 10 mm clearance to the ends of the mounting rail.
Recommended order:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	10	8
M16	6	4
M20	6	4
M25	3	2
M32	2	1
M40	2	1
M50		
M63		

Note

Klippon® STB 1.1

Depth 80 mm



Height / Width / Depth	150 / 120 / 80 mm

Ordering data

Stainless steel 1.4404 (316L)	Order No.
mirror-polished	1002750000
electro-polished	1058820000
Sheet steel, powder-coated (RAL 7032)	
powder-coated	1024980000

Note The colours of painted enclosures may vary under certain circumstances.

Accessories

Mounting rails, TS35x7.5	Order No.
Vertical	8683740000
Sliding fixing nut with screw	
M5	0433500000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Pressure compensating element with drainage function	
M20, stainless steel 1.4404 (316L)	2519550000

Note The enclosure is supplied with a set of sliding fixing nuts, washer, screws M5, to fix the mounting rail TS 35 or TS 32 into the C-Profile.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	1x23	
4 mm²	1x19	
6 mm²	1x14	
10 mm²	1x11	
16 mm²	1x9	

Note
The mounting rails are designed to be installed directly.
Assembly with terminals provides for 10 mm clearance to the ends of the mounting rail.
Recommended order:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	10	10
M16	6	6
M20	6	6
M25	3	2
M32	2	2
M40	2	1
M50		
M63		

Note

Klippon® STB 2

Depth 90 mm



Height / Width / Depth	150 / 150 / 90 mm

Ordering data

Stainless steel 1.4404 (316L)	Order No.
mirror-polished	1002740000
electro-polished	1058830000
Sheet steel, powder-coated (RAL 7032)	
powder-coated	1024990000

Note The colours of painted enclosures may vary under certain circumstances.

Accessories

Mounting rails, TS35x7.5	Order No.
Vertical	8683740000
Sliding fixing nut with screw	
M5	0433500000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Pressure compensating element with drainage function	
M20, stainless steel 1.4404 (316L)	2519550000

Note The enclosure is supplied with a set of sliding fixing nuts, washer, screws M5, to fix the mounting rail TS 35 or TS 32 into the C-Profile.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	1x23	
4 mm²	1x19	
6 mm²	1x14	
10 mm²	1x11	
16 mm²	1x9	

Note
The mounting rails are designed to be installed directly.
Assembly with terminals provides for 10 mm clearance to the ends of the mounting rail.
Recommended order:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	15	15
M16	10	8
M20	8	6
M25	3	2
M32	3	2
M40	2	2
M50	1	1
M63		

Note

Klippon® STB 2.1

Depth 90 mm



Height / Width / Depth	190 / 150 / 90 mm

Ordering data

Stainless steel 1.4404 (316L)	Order No.
mirror-polished	1002730000
electro-polished	1058840000
Sheet steel, powder-coated (RAL 7032)	
powder-coated	1025010000

Note The colours of painted enclosures may vary under certain circumstances.

Accessories

Mounting rails, TS35x7.5	Order No.
Vertical	1567660000
Sliding fixing nut with screw	
M5	0433500000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Pressure compensating element with drainage function	
M20, stainless steel 1.4404 (316L)	2519550000

Note The enclosure is supplied with a set of sliding fixing nuts, washer, screws M5, to fix the mounting rail TS 35 or TS 32 into the C-Profile.

Guide value for max. number of terminals (industry)

Assembly with terminal		vertical	horizontal
	2.5 mm²	1x30	
	4 mm²	1x25	
	6 mm²	1x20	
	10 mm²	1x15	
	16 mm²	1x13	



Note
The mounting rails are designed to be installed directly.
Assembly with terminals provides for 10 mm clearance to the ends of the mounting rail.
Recommended order:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries		A / B	C / D
	M12	15	18
	M16	10	10
	M20	8	10
	M25	3	3
	M32	3	3
	M40	2	2
	M50	1	1
	M63		

Note

Klippon® STB 3

Depth 100 mm



Height / Width / Depth	190 / 190 / 100 mm

Ordering data

Stainless steel 1.4404 (316L)	Order No.
mirror-polished	1002720000
electro-polished	1058850000
Sheet steel, powder-coated (RAL 7032)	
powder-coated	1025020000

Note The colours of painted enclosures may vary under certain circumstances.

Accessories

Mounting rails, TS35x7.5	Order No.
Vertical	1567660000
Sliding fixing nut with screw	
M5	0433500000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Pressure compensating element with drainage function	
M20, stainless steel 1.4404 (316L)	2519550000

Note The enclosure is supplied with a set of sliding fixing nuts, washer, screws M5, to fix the mounting rail TS 35 or TS 32 into the C-Profile.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	1x30	
4 mm²	1x25	
6 mm²	1x20	
10 mm²	1x15	
16 mm²	1x13	

Note
The mounting rails are designed to be installed directly.
Assembly with terminals provides for 10 mm clearance to the ends of the mounting rail.
Recommended order:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	21	21
M16	15	15
M20	10	8
M25	8	6
M32	3	3
M40	3	2
M50	2	1
M63	1	

Note

Klippon® STB 4

Depth 120 mm



Height / Width / Depth	250 / 250 / 120 mm

Ordering data

Stainless steel 1.4404 (316L)	Order No.
mirror-polished	1002710000
electro-polished	1058860000
Sheet steel, powder-coated (RAL 7032)	
powder-coated	1025030000

Note The colours of painted enclosures may vary under certain circumstances.

Accessories

Mounting rails, TS35x7.5	Order No.
Horizontally	8563410000
Vertical	8803610000
Sliding fixing nut with screw	
M5	0433500000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Pressure compensating element with drainage function	
M20, stainless steel 1.4404 (316L)	2519550000

Note The enclosure is supplied with a set of sliding fixing nuts, washer, screws M5, to fix the mounting rail TS 35 or TS 32 into the C-Profile.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	2x42	2x42
4 mm²	2x35	2x35
6 mm²	2x27	2x27
10 mm²	2x22	2x22
16 mm²	2x18	2x18

Note
The mounting rails are designed to be installed directly.
Assembly with terminals provides for 10 mm clearance to the ends of the mounting rail.
Recommended order:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	24	24
M16	21	21
M20	12	12
M25	10	10
M32	8	8
M40	3	3
M50	3	2
M63	2	1

Note

Klippon® STB 5

Depth 120 mm



Height / Width / Depth	160 / 380 / 120 mm

Ordering data

Stainless steel 1.4404 (316L)	Order No.
mirror-polished	1002700000
electro-polished	1058880000
Sheet steel, powder-coated (RAL 7032)	
powder-coated	1025040000

Note The colours of painted enclosures may vary under certain circumstances.

Accessories

Mounting rails, TS35x7.5	Order No.
Horizontally	8563410000
Vertical	8803610000
Sliding fixing nut with screw	
M5	0433500000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Pressure compensating element with drainage function	
M20, stainless steel 1.4404 (316L)	2519550000

Note The enclosure is supplied with a set of sliding fixing nuts, washer, screws M5, to fix the mounting rail TS 35 or TS 32 into the C-Profile.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	3x25	1x68
4 mm²	3x21	1x57
6 mm²	3x16	1x44
10 mm²	3x12	1x35
16 mm²	3x10	1x29

Note
The mounting rails are designed to be installed directly.
Assembly with terminals provides for 10 mm clearance to the ends of the mounting rail.
Recommended order:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	64	20
M16	33	12
M20	30	12
M25	16	6
M32	10	4
M40	6	2
M50	4	1
M63	2	1

Note

Klippon® STB 6

Depth 130 mm



Height / Width / Depth	250 / 400 / 130 mm

Ordering data

Stainless steel 1.4404 (316L)	Order No.
mirror-polished	1002760000
electro-polished	1058870000
Sheet steel, powder-coated (RAL 7032)	
powder-coated	1025050000

Note The colours of painted enclosures may vary under certain circumstances.

Accessories

Mounting rails, TS35x7.5	Order No.
Vertical	8803610000
Horizontally	8563410000
Sliding fixing nut with screw	
M5	0433500000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Pressure compensating element with drainage function	
M20, stainless steel 1.4404 (316L)	2519550000

Note The enclosure is supplied with a set of sliding fixing nuts, washer, screws M5, to fix the mounting rail TS 35 or TS 32 into the C-Profile.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	3x42	2x72
4 mm²	3x35	2x60
6 mm²	3x27	2x46
10 mm²	3x22	2x37
16 mm²	3x18	2x30

Note
The mounting rails are designed to be installed directly.
Assembly with terminals provides for 10 mm clearance to the ends of the mounting rail.
Recommended order:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for terminal blocks, please refer to online catalogue

Guide value for max. number of cable entries

Cable entries	A / B	C / D
M12	64	36
M16	33	21
M20	30	18
M25	16	10
M32	10	8
M40	6	3
M50	4	2
M63	2	2

Note

Klippon® Protect – Terminal Boxes – Product overview Steel enclosures

Various types of terminal boxes are available for installing signal / power supplies or distributors in explosive risk zones.
The terminal boxes are explosion-protected equipment approved for use in Ex areas in zones 0, 1, 2 and 20, 21, 22.

They are certified in accordance with the latest international standards Ex e, Ex ia and Ex tb. Customer-specific configuration means these terminal boxes are the optimum solution for all applications. Use the product overview to find the right solution for you!
Combine the enclosure, with or without threaded holes, a suitable mounting rail or pre-fitted strip terminals.

We have put together a small selection for you,
but we are happy to configure a bespoke solution for you.

Features:

- Available in a wide range of versions to meet customer requirements
- Additional international approvals alongside IECEx, ATEX and EAC also available
- Increased quality thanks to the use of established basic products in the Klippon® brand

Overview of enclosures

Terminal boxes based on the Klippon® STB range of enclosures

Description	Height x width x depth in mm	Marking	Approval	Order No.
STB 1 Exia	120 x 120 x 80	Ex ia IIC T4 Ga	IECEx, ATEX, EAC	8000028394
STB 2 Exe	150 x 150 x 90	Ex eb IIC T6 Gb	IECEx, ATEX, EAC	8000028395
STB 3 Exe	190 x 190 x 100	Ex eb IIC T6 Gb	IECEx, ATEX, EAC	8000028396
STB 4 Exe	250 x 250 x 120	Ex eb IIC T6 Gb	IECEx, ATEX, EAC	8000028397
Note				

Technical Overview

Technical data

Enclosures	
Material	Stainless steel 1.4404 (316L) 1.5 mm
Surface finish	Mirror-polished (Klippon® STB)
IP protection class	IP66 to DIN EN 60529
Gasket material	Silicone
Terminal block	
Material	Wemid
Colour	beige, blue or green/yellow
Connection system	screw connection
Clampable wires (H05V/H07V)	solid, flexible and flexible with ferrule
Note	

Approvals for Klippon® STB

ATEX certificate	IBExU07ATEX1148
IECEx certificate	IECEx IBE 09.0019
EAC certificate	RUC-DE.08.B.01328
Note	Labelling depends on the application layout. For details of power dissipation, please contact your Weidmüller representative.

Klippon® STB 1 Ex ia terminal box

Depth 80 mm





Height / Width / Depth	120 / 120 / 80 mm

Ordering data

	Order No.
STB 1 EXIA	8000028394

Note

Technical data

Article - short description	Klippon® Klippon STB (Small Terminal Box)-Enclosures, Terminal Box
Identification	Ex ia IIC T4 Ga
Certificate no. assembled enclosure (ATEX)	IBExU 07ATEX1148
Certificate no. assembled enclosure (IECEx)	IECEx IBE09.0019
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-11, IEC 60079-31, EN 60079-0, EN 60079-7, EN 60079-11, EN 60079-31
Ambient temperature	Tamb -40°C...+55°C
Type label material	Polyester coated with aluminium
Protection class	IP66
Assembly	
Modular terminal blocks	1x11
Rated cross-section	4 mm²
Rated voltage	60 V
Rated current	1.00 A
Drill holes side A	4 x M16
Drill holes side B	4 x M16, 1 x BDX
Technical data, enclosure	
Material	Stainless steel 1.4404 (316L)
Surface finish	Mirror polished
Material thickness	1.5 mm
Seal material	Silicone
Enclosure attachment	Welded-on mounting foot with 8-mm holes
Mounting dimension - height / -width	60 mm / 145 mm
Lid attachment	M5 hex-head slotted screws SW10
Access opening: width / Access opening: height	100 mm / 99.4 mm
Earth, enclosure, external	Welded-on M6 x 16 stainless-steel bolts
Earth, enclosure, internal	Welded-on M6 x 16 stainless-steel bolts

Accessories

Pressure compensating element with drainage function	Order No.
M20, brass	2519520000
Cable glands	
Nickel-plated brass, Ex e, M16, 3-12 mm	1460040000
Blanking plugs	
Stainless steel 1.4404 (316L), Ex e, M16	1477820000
Locknuts	
Nickel-plated brass, M16	1736990000
Grounding strap	
green-yellow, 6 mm² for M6 bolt	2475490000

Note

Reference products

	Order No.
KLIPPON STB 1 SS	1002690000
WDU 4 BL	1020180000
KLIPPON BDX M20 S	2519550000

Note

Note

Klippon® STB 2 Ex e terminal box

Depth 90 mm



Height / Width / Depth	150 / 150 / 90 mm

Ordering data

	Order No.
STB 2 Exe	8000028395
Note	

Technical data

Article - short description	Klippon® Klippon STB (Small Terminal Box)-Enclosures, Terminal Box
Identification	Ex eb IIC T6 Gb
Certificate no. assembled enclosure (ATEX)	IBExU 07ATEX1148
Certificate no. assembled enclosure (IECEx)	IECEx IBE09.0019
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-11, IEC 60079-31, EN 60079-0, EN 60079-7, EN 60079-11, EN 60079-31
Ambient temperature	Tamb -40°C...+40°C
Type label material	Polyester coated with aluminium
Protection class	IP66
Assembly	
Modular terminal blocks	1x14
Rated cross-section	4 mm²
Rated voltage	550 V
Rated current	6.00 A
Drill holes side A	4 x M20
Drill holes side B	4 x M20, 1 x BDX
Technical data, enclosure	
Material	Stainless steel 1.4404 (316L)
Surface finish	Mirror polished
Material thickness	1.5 mm
Seal material	Silicone
Enclosure attachment	Welded-on mounting foot with 8-mm holes
Mounting dimension - height / -width	75 mm / 175 mm
Lid attachment	M5 hex-head slotted screws SW10
Access opening: width / Access opening: height	130 mm / 130 mm
Earth, enclosure, external	Welded-on M6 x 16 stainless-steel bolts
Earth, enclosure, internal	Welded-on M6 x 16 stainless-steel bolts

Accessories

Pressure compensating element with drainage function	Order No.
M20, brass	2519520000
Cable glands	
Nickel-plated brass, Ex e, M20, 3-12 mm	1460050000
Blanking plugs	
Stainless steel 1.4404 (316L), Ex e, M20	1477840000
Locknuts	
Plastic, M20	1736930000
Nickel-plated brass, M20	1737000000
Grounding strap	
green-yellow, 6 mm² for M6 bolt	2475490000
Note	

Reference products

	Order No.
KLIPPON STB 2 SS	1002740000
WDU 4	1020100000
KLIPPON BDX M20 S	2519550000

Note

Note

Klippon® STB 3 Ex e terminal box

Depth 100 mm



Height / Width / Depth	190 / 190 / 100 mm

Ordering data

	Order No.
STB 3 Exe	8000028396
Note	

Technical data

Article - short description	Klippon® Klippon STB (Small Terminal Box)-Enclosures, Terminal Box
Identification	Ex eb IIC T6 Gb
Certificate no. assembled enclosure (ATEX)	IBExU 07ATEX1148
Certificate no. assembled enclosure (IECEx)	IECEx IBE09.0019
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-11, IEC 60079-31, EN 60079-0, EN 60079-7, EN 60079-11, EN 60079-31
Ambient temperature	Tamb -40°C...+40°C
Type label material	Polyester coated with aluminium
Protection class	IP66
Assembly	
Modular terminal blocks	1x18, 2 x PE
Rated cross-section	4 mm²
Rated voltage	550 V
Rated current	6.00 A
Drill holes side A	4 x M20
Drill holes side B	4 x M20, 1 x BDX
Technical data, enclosure	
Material	Stainless steel 1.4404 (316L)
Surface finish	Mirror polished
Material thickness	1.5 mm
Seal material	Silicone
Enclosure attachment	Welded-on mounting foot with 8-mm holes
Mounting dimension - height / -width	95 mm / 215 mm
Lid attachment	M5 hex-head slotted screws SW10
Access opening: width / Access opening: height	170 mm / 170 mm
Earth, enclosure, external	Welded-on M6 x 16 stainless-steel bolts
Earth, enclosure, internal	Welded-on M6 x 16 stainless-steel bolts

Accessories

Pressure compensating element with drainage function	Order No.
M20, brass	2519520000
Cable glands	
Nickel-plated brass, Ex e, M20, 3-12 mm	1460050000
Blanking plugs	
Stainless steel 1.4404 (316L), Ex e, M20	1477840000
Locknuts	
Plastic, M20	1736930000
Nickel-plated brass, M20	1737000000
Grounding strap	
green-yellow, 6 mm² for M6 bolt	2475490000
Note	

Reference products

	Order No.
KLIPPON STB 3 SS	1002720000
WDU 4	1020100000
WPE 4	1010100000
KLIPPON BDX M20 S	2519550000

Note

Note

Klippon® STB 4 Ex e terminal box

Depth 120 mm



250 / 250 / 120 mm

Ordering data

	Order No.
STB 4 Exe	8000028397
Note	

Technical data

Article - short description	Klippon® Klippon STB (Small Terminal Box)-Enclosures, Terminal Box
Identification	Ex eb IIC T6 Gb
Certificate no. assembled enclosure (ATEX)	IBExU 07ATEX1148
Certificate no. assembled enclosure (IECEx)	IECEx IBE09.0019
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-11, IEC 60079-31, EN 60079-0, EN 60079-7, EN 60079-11, EN 60079-31
Ambient temperature	Tamb -40°C...+40°C
Type label material	Polyester coated with aluminium
Protection class	IP66
Assembly	
Modular terminal blocks	1x26, 2 x PE
Rated cross-section	4 mm²
Rated voltage	550 V
Rated current	6.00 A
Drill holes side A	6 x M25
Drill holes side B	6 x M25, 1 x BDX
Technical data, enclosure	
Material	Stainless steel 1.4404 (316L)
Surface finish	Mirror polished
Material thickness	1.5 mm
Seal material	Silicone
Enclosure attachment	Welded-on mounting foot with 8-mm holes
Mounting dimension - height / -width	125 mm / 275 mm
Lid attachment	M5 hex-head slotted screws SW10
Access opening: width / Access opening: height	230 mm / 230 mm
Earth, enclosure, external	Welded-on M6 x 16 stainless-steel bolts
Earth, enclosure, internal	Welded-on M6 x 16 stainless-steel bolts

Accessories

Pressure compensating element with drainage function	Order No.
M20, brass	2519520000
Cable glands	
Nickel-plated brass, Ex e, M25, 10-18 mm	1460070000
Blanking plugs	
Stainless steel 1.4404 (316L), Ex e, M25	1477870000
Locknuts	
Plastic, M25	1736940000
Nickel-plated brass, M25	1737010000
Grounding strap	
green-yellow, 6 mm² for M6 bolt	2475490000
Note	

Reference products

	Order No.
KLIPPON STB 4 SS	1002710000
WDU 4	1020100000
WPE 4	1010100000
KLIPPON BDX M20 S	2519550000

Note

Note

Safely control work processes in hazardous areas on site

With certified enclosure solutions with control and display elements

Harsh industrial environments and hazardous areas, such as in the oil and gas industry, place extreme demands on the safety, the robustness and quality of products and devices.

We meet these challenges with the Klippon® Control Station, the addition to our range of customised enclosure solutions. More than 50 years of expertise have made us market leader in this area with global competence centres. The basis of our enclosure solutions is provided by the usual Weidmüller quality and comprehensive approvals for explosion hazard areas. Based on this, our sturdy "on-site control station" is available in two standard sizes and with up to four control and display elements and provides a flexible solution to meet your specific needs.

Order your distributor enclosure as well as control and signaling units from a single source and from one enclosure design – for reliable security and reduced storage costs for maintenance and repair operations.

Your special advantages:
Ideal for urgent service calls
We have prepared moduls of the proven Klippon® enclosure series STB available for you for further processing. This means we manufacture a control solution suitable for your application at short notice.

Predestined for emergency shutdown applications: Klippon® Control Stations score when it comes to the safe shutdown of plant sections, such as in the process industry

Project solutions from a single source
Obtain command/signaling units and distribution and control boxes as a complete solution – tailored to the individual requirements of your projects in hazardous areas.

Customised assembly
In addition to standard types from stock, you can obtain enclosure solutions from us that are completely assembled and equipped according to customer requirements.

A variety of sizes and materials
Enclosures in stainless steel, aluminium or polyester are available for different environmental conditions. Depending on the size of the enclosure, it provides space for the integration of up to four control and display elements.

International certificates
The Klippon® Control Station is tested and certified among others according to ATEX and IECEx.

Durability for maximum requirements

Klippon® Protect sets the highest standards with stainless steel enclosures

The enclosure ranges Klippon® TB and Klippon® STB are offered in stainless steel and boost market leading performance characteristics, which even allow them to meet the demanding requirements for use with the harshest environments. The enclosures are certified and comply with the latest international standards – including ATEX and IECEx.

Additional features:

- Standard silicone seals for use in extreme temperature environments
- High Ingress Performace - IP66
- Welded-on mounting feet for wall mounting

Technical data	Stainless steel
Material	Stainless steel 1.4404 (316L) 1.50 mm
Surface finish	Mirror-polished
Colour	Natural
IP protection class	IP 54; IP 66
Ambient temperature	-55 °C to 55 °C
Seal material of enclosure	Silicone
Seal material of command and signalling units	EPDM
Flammability rating	-
Impact resistance IK	7 joules in acc. with IEC60079-0 4 joules in acc. with IEC60079-0 with integrated illuminated pushbutton or light module
Cable gland material	Nickel-plated brass
Cable gland clamping area min. – max. in mm	
M20	3–12 mm
M25	10–18 mm
Max. rated cross-section	2.5 mm²
Max. operating voltage	400 V
with integrated illuminated pushbutton or light module	250 V
Maximum operating current at 40 °C ambient temperature	
1.5 mm² – T6	10 A
1.5 mm² – T5	16 A
2.5 mm² – T6	16 A
Maximum operating current at 55 °C ambient temperature	
1.5 mm² – T4	16 A
1.5 mm² – T5	10 A
2.5 mm² – T5	16 A
Temperature class	T4, T5, T6
Type of mounting	Wall mounting
Earthing inside	M6x10 earthing studs integrated in the cover, stainless steel
Lid attachment	Hexagonal slothead screws SW10
Lid screw torque	2.5 Nm
Earthing torque	7.5 Nm
Earthing outside	M6 earthing studs, stainless steel
Approvals	IECEXITA14.0013X TUEV14ATEX7606X MARITREG 15.40082.250
Marking	2G Ex e d IIC T* Gb 2G Ex ib d [ia] IIC T* Gb 2D Ex tb IIIC T80/100 °C Db
Mounting feet	2 welded-on mounting feet with 8 mm holes

	Number of built-in components			Emergency stop pushbutton	Key switch	Pushbutton		Illuminated push button		Light module		Dimensions with built-in components HxWxD in mm	Designation	Cable gland	Order number
	●	● ●	● ● ●	red	I – 0 – II	red	green	red	green	red	green				
Stainless steel	●			1								150x120x119	KLIPPON CS STB 1-1	VG M20	**1537200000**
	●						1					150x120x95	KLIPPON CS STB 1-1	VG M20	**1537210000**
	●				1							150x120x109	KLIPPON CS STB 1-1	VG M20	**1537220000**
	●								1			150x120x96	KLIPPON CS STB 1-1	VG M20	**1537230000**
	●			1								153x120x119	KLIPPON CS STB 1-2	VG M25	**1537240000**
	●						1					153x120x95	KLIPPON CS STB 1-2	VG M25	**1537250000**
	●				1							153x120x109	KLIPPON CS STB 1-2	VG M25	**1537280000**
	●								1			153x120x96	KLIPPON CS STB 1-2	VG M25	**1537290000**
		●				1	1					223x150x95	KLIPPON CS STB 2.1-2	VG M25	**1537300000**
		●					1				1	223x150x103	KLIPPON CS STB 2.1-2	VG M25	**1537310000**
		●		1						1		223x150x119	KLIPPON CS STB 2.1-2	VG M25	**1537320000**
			●			1	2					223x150x95	KLIPPON CS STB 2.1-6	VG M25	**1537330000**
			●			1	1		1			223x150x103	KLIPPON CS STB 2.1-7	VG M25	**1537340000**
			●	1		1	1					220x150x119	KLIPPON CS STB 2.1-7	VG M20	**1537370000**

	Klippon® CS STB 1-1	Klippon® CS STB 1-1

Technical data

Enclosure		
Dimensions with installation (HxBxD)	150 / 120 / 119 mm	150 / 120 / 95 mm
Material	Stainless steel 1.4404 (316L)	Stainless steel 1.4404 (316L)
General characteristics		
Surface finish / Colour	Mirror polished / Natural	Mirror polished / Natural
Protection class	IP54, IP66	IP54, IP66
Ambient temperature	-55 °C...+55 °C	-55 °C...+55 °C
Impact resistance	7 joules in acc. with IEC 60079-0	7 joules in acc. with IEC 60079-0
Enclosure seal material	Silicone (VMQ)	Silicone (VMQ)
Seal material of operating and display elements	EPDM	EPDM
Type of mounting	Wall mounting	Wall mounting
Internal earth	M6 x 10 earthing studs integrated in the lid, stainless steel	M6 x 10 earthing studs integrated in the lid, stainless steel
External earth	M6 earthing studs, stainless steel	M6 earthing studs, stainless steel
Lid attachment	M5 hexagonal screw with slot and 10mm distance across flats	M5 hexagonal screw with slot and 10mm distance across flats
Torque for lid screws	2.5 Nm	2.5 Nm
Earth stud torque	7.5 Nm	7.5 Nm
Electrical properties*		
Wire connection cross section, finely stranded, max.	2.5 mm²	2.5 mm²
Operating voltage, max.	400 V	400 V
Temperature class	T4, T5, T6	T4, T5, T6
Enclosure assembly		
1 Position in enclosure	EMERGENCY-STOP pushbutton with yellow, contrasting label	Pushbutton - green
2 Position in enclosure		
3 Position in enclosure		
4 Position in enclosure		
Contact design	2 NC contact, positive opening contacts	1 NC contact, 1 NO contacts
Actuators	EMERGENCY STOP pushbutton	Pushbutton
Actuator colour	red	green
Illumination module colour		
Illuminated button actuator colour		
Cable entries		
Drill holes side B	1 x M20	1 x M20
Cable gland	1460050000 - VG M20 EXE MS	1460050000 - VG M20 EXE MS
Clamping range min. / max.	3 mm / 12 mm	3 mm / 12 mm
Approval and Marking		
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-31	IEC 60079-0, IEC 60079-7, IEC 60079-31
Certificate No. (IECEX)	IECEXITA14.0013X	IECEXITA14.0013X
Certificate No. (ATEX)	TUEV14ATEX7606X	TUEV14ATEX7606X
Certificate No. (EAC)	RUC-DE.TB08.B.01838	RUC-DE.BE02.B.00173
Certificate No. (MARITREG)	15.40082.250	15.40082.250
Marking	II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db	II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
Note		

Ordering data

Type	Qty.	Order No.
KLIPPON CS STB 1-1	1	1537200000

Type	Qty.	Order No.
KLIPPON CS STB 1-1	1	1537210000

Note		
	*Other temperature classes and connection values on request, or see "Notice to Installer".	*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS STB 1-1

150 / 120 / 109 mm
Stainless steel 1.4404 (316L)
Mirror polished / Natural
IP54, IP66
-55 °C...+55 °C
7 joules in acc. with IEC 60079-0
Silicone (VMQ)
EPDM
Wall mounting
M6 x 10 earthing studs integrated in the lid, stainless steel
M6 earthing studs, stainless steel
M5 hexagonal screw with slot and 10mm distance across flats
2.5 Nm
7.5 Nm
2.5 mm²
400 V
T4, T5, T6
Key-operated switch
1 NC contact, 1 NO contacts
Key-operated switch, 3 switching positions, I - 0 - II, (I + II), latching, Key retractable
1 x M20
1460050000 - VG M20 EXE MS
3 mm / 12 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.BE02.B.00173
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db

Type	Qty.	Order No.
KLIPPON CS STB 1-1	1	1537220000

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS STB 1-1

150 / 120 / 96 mm
Stainless steel 1.4404 (316L)
Mirror polished / Natural
IP54, IP66
-55 °C...+55 °C
4 joules in acc. with IEC 60079-0
Silicone (VMQ)
EPDM
Wall mounting
M6 x 10 earthing studs integrated in the lid, stainless steel
M6 earthing studs, stainless steel
M5 hexagonal screw with slot and 10mm distance across flats
2.5 Nm
7.5 Nm
2.5 mm²
250 V
T4, T5, T6
Illuminated pushbutton - green
2 NO contacts
Pushbutton
green
green
1 x M20
1460050000 - VG M20 EXE MS
3 mm / 12 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.BE02.B.00173
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db

Type	Qty.	Order No.
KLIPPON CS STB 1-1	1	1537230000

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS STB 1-2

153 / 120 / 119 mm
Stainless steel 1.4404 (316L)
Mirror polished / Natural
IP54, IP66
-55 °C...+55 °C
7 joules in acc. with IEC 60079-0
Silicone (VMQ)
EPDM
Wall mounting
M6 x 10 earthing studs integrated in the lid, stainless steel
M6 earthing studs, stainless steel
M5 hexagonal screw with slot and 10mm distance across flats
2.5 Nm
7.5 Nm
2.5 mm²
400 V
T4, T5, T6
EMERGENCY-STOP pushbutton with yellow, contrasting label
2 NC contact, positive opening contacts
EMERGENCY STOP pushbutton
red
1 x M25
1460070000 - VG M25 EXE MS
10 mm / 18 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.TB08.B.01838
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db

Type	Qty.	Order No.
KLIPPON CS STB 1-2	1	1537240000

*Other temperature classes and connection values on request, or see "Notice to Installer".

Technical data

	Klippon® CS STB 1-2	Klippon® CS STB 1-2
Enclosure		
Dimensions with installation (HxBxD)	153 / 120 / 95 mm	153 / 120 / 109 mm
Material	Stainless steel 1.4404 (316L)	Stainless steel 1.4404 (316L)
General characteristics		
Surface finish / Colour	Mirror polished / Natural	Mirror polished / Natural
Protection class	IP54, IP66	IP54, IP66
Ambient temperature	-55 °C...+55 °C	-55 °C...+55 °C
Impact resistance	7 joules in acc. with IEC 60079-0	7 joules in acc. with IEC 60079-0
Enclosure seal material	Silicone (VMQ)	Silicone (VMQ)
Seal material of operating and display elements	EPDM	EPDM
Type of mounting	Wall mounting	Wall mounting
Internal earth	M6 x 10 earthing studs integrated in the lid, stainless steel	M6 x 10 earthing studs integrated in the lid, stainless steel
External earth	M6 earthing studs, stainless steel	M6 earthing studs, stainless steel
Lid attachment	M5 hexagonal screw with slot and 10mm distance across flats	M5 hexagonal screw with slot and 10mm distance across flats
Torque for lid screws	2.5 Nm	2.5 Nm
Earth stud torque	7.5 Nm	7.5 Nm
Electrical properties*		
Wire connection cross section, finely stranded, max.	2.5 mm²	2.5 mm²
Operating voltage, max.	400 V	400 V
Temperature class	T4, T5, T6	T4, T5, T6
Enclosure assembly		
1 Position in enclosure	Pushbutton - green	Key-operated switch
2 Position in enclosure		
3 Position in enclosure		
4 Position in enclosure		
Contact design	1 NC contact, 1 NO contacts	1 NC contact, 1 NO contacts
Actuators	Pushbutton	Key-operated switch, 3 switching positions, I - 0 - II, (I + II), latching, Key retractable
Actuator colour	green	
Illumination module colour		
Illuminated button actuator colour		
Cable entries		
Drill holes side B	1 x M25	1 x M25
Cable gland	1460070000 - VG M25 EXE MS	1460070000 - VG M25 EXE MS
Clamping range min. / max.	10 mm / 18 mm	10 mm / 18 mm
Approval and Marking		
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-31	IEC 60079-0, IEC 60079-7, IEC 60079-31
Certificate No. (IECEX)	IECEXITA14.0013X	IECEXITA14.0013X
Certificate No. (ATEX)	TUEV14ATEX7606X	TUEV14ATEX7606X
Certificate No. (EAC)	RUC-DE.BE02.B.00173	RUC-DE.TB08.B.01838
Certificate No. (MARITREG)	15.40082.250	15.40082.250
Marking	II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db	II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db

Note

Ordering data

Type	Qty.	Order No.
KLIPPON CS STB 1-2	1	1537250000

Type	Qty.	Order No.
KLIPPON CS STB 1-2	1	1537280000

Note

*Other temperature classes and connection values on request, or see "Notice to Installer".

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS STB 1-2

153 / 120 / 96 mm
Stainless steel 1.4404 (316L)
Mirror polished / Natural
IP54, IP66
-55 °C...+55 °C
4 joules in acc. with IEC 60079-0
Silicone (VMQ)
EPDM
Wall mounting
M6 x 10 earthing studs integrated in the lid, stainless steel
M6 earthing studs, stainless steel
M5 hexagonal screw with slot and 10mm distance across flats
2.5 Nm
7.5 Nm
2.5 mm²
250 V
T4, T5, T6
Illuminated pushbutton - green
2 NO contacts
Pushbutton
green
green
1 x M25
1460070000 - VG M25 EXE MS
3 mm / 12 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.BE02.B.00173
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db

Type	Qty.	Order No.
KLIPPON CS STB 1-2	1	1537290000

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS STB 2.1-2

223 / 150 / 95 mm
Stainless steel 1.4404 (316L)
Mirror polished / Natural
IP54, IP66
-55 °C...+55 °C
7 joules in acc. with IEC 60079-0
Silicone (VMQ)
EPDM
Wall mounting
M6 x 10 earthing studs integrated in the lid, stainless steel
M6 earthing studs, stainless steel
M5 hexagonal screw with slot and 10mm distance across flats
2.5 Nm
7.5 Nm
2.5 mm²
400 V
T4, T5, T6
Pushbutton - red
Pushbutton - green
2 NC contact, 2 NO contacts
Pushbutton
red, green
green
1 x M25
1460070000 - VG M25 EXE MS
10 mm / 18 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.BE02.B.00173
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db

Type	Qty.	Order No.
KLIPPON CS STB 2.1-2	1	1537300000

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS STB 2.1-2

223 / 150 / 103 mm
Stainless steel 1.4404 (316L)
Mirror polished / Natural
IP54, IP66
-55 °C...+55 °C
4 joules in acc. with IEC 60079-0
Silicone (VMQ)
EPDM
Wall mounting
M6 x 10 earthing studs integrated in the lid, stainless steel
M6 earthing studs, stainless steel
M5 hexagonal screw with slot and 10mm distance across flats
2.5 Nm
7.5 Nm
2.5 mm²
250 V
T4, T5, T6
Light module - green
Pushbutton - green
1 NC contact, 1 NO contacts
Pushbutton
green
green
1 x M25
1460070000 - VG M25 EXE MS
10 mm / 18 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.BE02.B.00173
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db

Type	Qty.	Order No.
KLIPPON CS STB 2.1-2	1	1537310000

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS STB 2.1-2

Klippon® CS STB 2.1-6

Technical data

Enclosure		
Dimensions with installation (HxBxD)	223 / 150 / 119 mm	223 / 150 / 95 mm
Material	Stainless steel 1.4404 (316L)	Stainless steel 1.4404 (316L)
General characteristics		
Surface finish / Colour	Mirror polished / Natural	Mirror polished / Natural
Protection class	IP54, IP66	IP54, IP66
Ambient temperature	-55 °C...+55 °C	-55 °C...+55 °C
Impact resistance	4 joules in acc. with IEC 60079-0	7 joules in acc. with IEC 60079-0
Enclosure seal material	Silicone (VMQ)	Silicone (VMQ)
Seal material of operating and display elements	EPDM	EPDM
Type of mounting	Wall mounting	Wall mounting
Internal earth	M6 x 10 earthing studs integrated in the lid, stainless steel	M6 x 10 earthing studs integrated in the lid, stainless steel
External earth	M6 earthing studs, stainless steel	M6 earthing studs, stainless steel
Lid attachment	M5 hexagonal screw with slot and 10mm distance across flats	M5 hexagonal screw with slot and 10mm distance across flats
Torque for lid screws	2.5 Nm	2.5 Nm
Earth stud torque	7.5 Nm	7.5 Nm
Electrical properties*		
Wire connection cross section, finely stranded, max.	2.5 mm²	2.5 mm²
Operating voltage, max.	250 V	400 V
Temperature class	T4, T5, T6	T4, T5, T6
Enclosure assembly		
1 Position in enclosure	Light module - red	Pushbutton - green
2 Position in enclosure	EMERGENCY-STOP pushbutton with yellow, contrasting label	Pushbutton - red
3 Position in enclosure		Pushbutton - green
4 Position in enclosure		
Contact design	2 NC contact, positive opening contacts	3 NC contact, 3 NO contacts
Actuators	EMERGENCY STOP pushbutton	Pushbutton
Actuator colour	red	green, red
Illumination module colour		
Illuminated button actuator colour		
Cable entries		
Drill holes side B	1 x M25	1 x M25
Cable gland	1460070000 - VG M25 EXE MS	1460070000 - VG M25 EXE MS
Clamping range min. / max.	10 mm / 18 mm	10 mm / 18 mm
Approval and Marking		
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-31	IEC 60079-0, IEC 60079-7, IEC 60079-31
Certificate No. (IECEX)	IECEXITA14.0013X	IECEXITA14.0013X
Certificate No. (ATEX)	TUEV14ATEX7606X	TUEV14ATEX7606X
Certificate No. (EAC)	RUC-DE.08.B.00472	RUC-DE.BE02.B.00173
Certificate No. (MARITREG)	15.40082.250	15.40082.250
Marking	II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db	II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db

Note

Ordering data

Type	Qty.	Order No.
KLIPPON CS STB 2.1-2	1	**1537320000**

Type	Qty.	Order No.
KLIPPON CS STB 2.1-6	1	**1537330000**

Note

*Other temperature classes and connection values on request, or see "Notice to Installer".

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS STB 2.1-7

223 / 150 / 103 mm
Stainless steel 1.4404 (316L)
Mirror polished / Natural
IP54, IP66
-55 °C...+55 °C
4 joules in acc. with IEC 60079-0
Silicone (VMQ)
EPDM
Wall mounting
M6 x 10 earthing studs integrated in the lid, stainless steel
M6 earthing studs, stainless steel
M5 hexagonal screw with slot and 10mm distance across flats
2.5 Nm
7.5 Nm
2.5 mm²
250 V
T4, T5, T6
Pushbutton - red
Light module - green
Pushbutton - green
2 NC contact, 2 NO contacts
Pushbutton
red, green
green
1 x M25
1460070000 - VG M25 EXE MS
10 mm / 18 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.BE02.B.00173
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db

Type	Qty.	Order No.
KLIPPON CS STB 2.1-7	1	1537340000

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS STB 2.1-7

220 / 150 / 119 mm
Stainless steel 1.4404 (316L)
Mirror polished / Natural
IP54, IP66
-55 °C...+55 °C
7 joules in acc. with IEC 60079-0
Silicone (VMQ)
EPDM
Wall mounting
M6 x 10 earthing studs integrated in the lid, stainless steel
M6 earthing studs, stainless steel
M5 hexagonal screw with slot and 10mm distance across flats
2.5 Nm
7.5 Nm
2.5 mm²
400 V
T4, T5, T6
Pushbutton - green
Pushbutton - red
EMERGENCY-STOP pushbutton with yellow, contrasting label
2 NO contacts, 2 NC contact, positive opening contacts
Pushbutton, EMERGENCY STOP pushbutton
green, red
2 x M20
1460050000 - VG M20 EXE MS
3 mm / 12 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.BE02.B.00173
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db

Type	Qty.	Order No.
KLIPPON CS STB 2.1-7	1	1537370000

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® K – aluminium enclosure
Robust enclosure for industrial applications

The aluminium Klippon® K enclosures are suitable for use in an extremely wide range of different areas. Various components can be installed inside the enclosures, and will benefit in particular from the high temperature resistance, the excellent IP protection and the good impact resistance.



Standardised closure system
The cover is attached using captive Torx slotted screws. The highly functional screw connection with coated stainless steel screws allows for use even in corrosive atmospheres. Working with the enclosures requires just one single tool, as only Torx slotted screws are used.

Earth studs
M6 brass earth studs and M10 stainless steel earth studs are available as accessories. Klippon® K Ex enclosures are fitted with an M4 earth stud as standard, and are available on request.

High IP protection
There are no glued areas on the moulded seal of the enclosure, which helps ensure optimal leak-tightness. The seal guarantees an IP protection of IP66 to IP68 (depending on the use).

Mounting options
The matching terminal rails or mounting plates are available as accessories and can be used to install a wide range of different components inside the enclosure.



Versatile attachment options
The enclosure can be attached directly using the designated attachment holes. Alternatively, it can be attached from the outside using the assembly feet that are available as accessories.

Ex applications
Klippon® K enclosures with explosion protection for use in explosive risk zones are optionally available.

Customer-specific assembly
Enjoy more flexibility in your project business with Klippon® Services. We combine reliable planning, professional engineering and production in the perfect quality to create your customised product.

Klippon® K – Aluminium enclosures

Klippon® K-Series aluminium enclosures can be used in a variety of applications, e.g. for the assembly of modular terminal blocks, switches, power supplies, operational and display elements or electronic modules.

The extensive Klippon® K enclosure range has the following advantages:
- More flexibility – 19 different sizes
- Available in two surface finishes – powder-coated and natural
- Mounting holes not within the sealed area
- Fastening thread to attach mounting rails and plates
- Closed moulded gasket (no glue seam)

Weidmüller manufactures and supplies the enclosures to match customer specifications – fully fitted with terminals, electronics and cable glands.

Use our online catalogue to find additional product details, technical information and additional services:
www.weidmueller.com/KlipponK

Overview of enclosures

Ordering data

Description	Height x width x depth in mm	Powder-coated (RAL 7001)*			Unpainted		
		Standard		Ex enclosure**	Standard		Ex enclosure**
		CR moulded seal	Silicone moulded seal**	Silicone moulded seal	CR moulded seal	Silicone moulded seal**	Silicone moulded seal
Klippon® K 0	45 x 50 x 30	9529090000	1937920000		0573200000	1939760000	
Klippon® K 01	64 x 58 x 34	9529100000	1937850000		1565240000	1939540000	
Klippon® K 02	64 x 98 x 34	9529110000	1937840000		1565250000	1939550000	
Klippon® K 1	70 x 70 x 45	9529120000	1937630000	1329630000	0342000000	1939560000	9526840000
Klippon® K 11	80 x 75 x 57	9529130000	1937910000	1329640000	0573300000	1939570000	9526850000
Klippon® K 2	70 x 100 x 45	9529140000	1937930000	1329650000	0342100000	1939580000	9526860000
Klippon® K 21	80 x 125 x 57	9529150000	1937830000	1328120000	0573400000	1939590000	9526870000
Klippon® K 3	70 x 165 x 45	9529160000	1937900000	1329670000	0342200000	1939600000	9526880000
Klippon® K 31	80 x 175 x 57	9529170000	1937820000	1329680000	0573500000	1939610000	9526890000
Klippon® K 32	80 x 250 x 55	9529180000	1937810000	1329690000	1565260000	1939620000	9526900000
Klippon® K 4	82 x 130 x 72	9529190000	1937890000	1329700000	0342300000	1939630000	9526910000
Klippon® K 41	120 x 122 x 81	9529200000	1937800000	1329710000	1565270000	1939640000	9526920000
Klippon® K 5	130 x 170 x 90	9529210000	1937860000	1329720000	0342400000	1939650000	9526930000
Klippon® K 51	120 x 220 x 81	9529220000	1937750000	1328130000	1565280000	1939660000	9526940000
Klippon® K 52	160 x 160 x 91	9529230000	1937740000	1329730000	1565290000	1939670000	9526950000
Klippon® K 6	160 x 200 x 100	9529240000	1937870000	1329740000	0342500000	1939690000	9526960000
Klippon® K 61	160 x 260 x 91	9529250000	1937730000	1328140000	0573600000	1939700000	9526970000
Klippon® K 7	160 x 350 x 100	9529260000	1937880000	1329750000	0342600000	1939710000	9526980000
Klippon® K 71	230 x 280 x 111	9529270000	1937720000	1329770000	0573700000	1939730000	9526990000
Note	*Colour variations may occur under certain circumstances, **Delivery time on request, Ex enclosures available on request						

Technical Overview

Features

• Two surfaces: natural and powder-coated
• High IP protection up to IP68
• Moulded silicone gasket for applications with high temperatures
• A uniform Torx®-slotted screw head is used for over 19 different enclosure sizes.
• Alloy is resistant to salt water
• Approved according to the latest international standards
Note We deliver enclosures through our assembly service which are ready to be connected and suitable for every application

Technical data

	Ex	Standard
Enclosure material	High quality aluminium alloy (Al-Si12)	High quality aluminium alloy (Al-Si12)
Surface, untreated	Smooth	Smooth
Surface, painted	Silver grey, textured, similar to RAL 7001	Silver grey, textured, similar to RAL 7001
Painting	50-90 µm paint thickness	50-90 µm paint thickness
IP protection class	IP66, IP67 to DIN EN 60529	IP66, IP67 and IP68* to DIN EN 60529
NEMA		4, 4x
Earthing outside	Earthing studs, M4	
Installation mounting	Flexible DIN rail mounting	Flexible DIN rail mounting
Enclosure mounting	Direct mounting with optional mounting brackets (from a size of 120 x 122 x 81 Klippon® K 41)	Direct mounting with optional mounting brackets (from a size of 120 x 122 x 81 Klippon® K 41)
Lid fixing	Captive stainless steel Torx® 20 or slotted screws.	Captive stainless steel Torx® 20 or slotted screws.
Impact resistance	7J to IEC 60079-0	IK 09 (10J) to DIN EN 50102
Gasket material	Silicone (VMQ)	Chloroprene / Silicone (VMQ)
Temperature range	-60 °C...+135 °C	-40 °C...+80 °C with chloroprene gasket / -60 °C...+135 °C with silicone gasket
Lid screws, torque**	2.5 Nm	2.5 Nm
Note	* (t=72h; h=1m) ** To secure the lid we recommend the use of our Torx® TH20 screwdriver (9009160000) Depending on the screw head size, our slotted screwdriver may also be used as an alternative, Ex enclosures available on request	

Approvals for empty enclosures

	Ex	Standard
ATEX certificate	IBExU12ATEX1144 U	
ATEX marking	II 2G Ex e IIC Gb or II 2G Ex eb IIC II 2D Ex t IIIC Db or II 2D Ex tb IIIC	
IECEx certificate	IECEx IBE 13.0001U	
IECEx marking	Ex e IIC Gb or Ex eb IIC Ex tb IIIC Db or Ex tb IIIC	
EAC	E197061 (Ord.Loc.)	
cULus		E197061
Russian Maritime Register	19.00108.272	19.00108.272
DNV GL	TAE00002SM	TAE00002SM
Installation	The Klippon® K enclosure range can be pre-fitted in our customer specific production department according to your wishes.	
Note	This enclosure range is component certified. If other electrical components are inserted into the case, additional certification is required.	

Approvals for control and distribution box

	Ex		
ATEX certificate	IBExU12ATEX1145 X	EAC certificate	RUC-DE.08.B.01328
ATEX marking	II 2G Ex e IIC T6...T4 Gb or II 2G Ex eb IIC T6...T4 II 2G Ex ia IIC T6...T4 Gb or II 2 Ex ia IIC T6...T4 II 2(1)G Ex e ia IIC T6...T4 Gb or II 2(1)G Ex eb ia IIC T6...T4 II 2D Ex t IIIC T85°C...135°C Db or II 2 D Ex tb IIIC T85°C...135°C	EAC marking	II 2 G Ex eb IIC T6... T4 II 2 G Ex e IIC T6... T4 Gb II 2 G Ex ia IIC T6... T4 II 2 G Ex ia IIC T6... T4 Gb II 2(1) G Ex eb ia IIC T6... T4 II 2(1) G Ex e ia IIC T6... T4 Gb II 2 D Ex tb IIIC T85°C...T135°C II 2 D Ex tb IIIC T85°C...T135°C Db
IECEx certificate	IECEx IBE 13.0002X		
IECEx marking	Ex e IIC T6...T4 Gb or Ex eb IIC T6...T4 Ex ia IIC T6...T4 Gb Ex e ia IIC T6...T4 Gb Ex tb IIIC T85°C...135°C Db or Ex tb IIIC T85°C...135°C		
Note	If you have specific requirements for equipment operating in explosive hazard areas, please contact us at Weidmüller to receive a full copy of the certification. For details of power dissipation, please contact your Weidmüller representative.		

Klippon® K 0

Depth 30 mm



Height / Width / Depth	45 / 50 / 30 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	**9529090000**
Standard (silicone seal)*	**1937920000**
unpainted	
Standard (CR seal)	**0573200000**
Standard (silicone seal)*	**1939760000**

Note The colours of painted enclosures may vary under certain circumstances. *Delivery time on request

Accessories

Torx®screw driver	Order No.
not insulated, Torx® TH20	**9009160000**
Pressure compensation elements	
Polyamide 6, M12	**1868570000**
Stainless steel 1.4305, M12	**1868550000**

Note Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	1x1*	1x1*
4 mm²	1x1*	1x1*
6 mm²		
10 mm²		
16 mm²		

Note *Please refer to the Terminal Block catalogue or the SAK Series for more information about assembling the enclosures with terminal blocks. There are no prescribed possible attachment points in the enclosure.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	1	1
M16	1	1
M20		
M25		
M32		
M40		
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Klippon® K 01

Depth 34 mm



Height / Width / Depth	64 / 58 / 34 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	**9529100000**
Standard (silicone seal)*	**1937850000**
unpainted	
Standard (CR seal)	**1565240000**
Standard (silicone seal)*	**1939540000**

Note The colours of painted enclosures may vary under certain circumstances. *Delivery time on request

Accessories

Torx®screw driver	Order No.
not insulated, Torx® TH20	**9009160000**
Pressure compensation elements	
Polyamide 6, M12	**1868570000**
Stainless steel 1.4305, M12	**1868550000**

Note Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	1x1*	1x1*
4 mm²	1x1*	1x1*
6 mm²		
10 mm²		
16 mm²		

Note *Please refer to the Terminal Block catalogue or the SAK Series for more information about assembling the enclosures with terminal blocks. There are no prescribed possible attachment points in the enclosure.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	1	1
M16	1	1
M20		
M25		
M32		
M40		
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Klippon® K 02

Depth 34 mm



Height / Width / Depth	64 / 98 / 34 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	**9529110000**
Standard (silicone seal)*	**1937840000**
unpainted	
Standard (CR seal)	**1565250000**
Standard (silicone seal)*	**1939550000**

Note The colours of painted enclosures may vary under certain circumstances. *Delivery time on request

Accessories

Torx®screw driver	Order No.
not insulated, Torx® TH20	**9009160000**
Pressure compensation elements	
Polyamide 6, M12	**1868570000**
Stainless steel 1.4305, M12	**1868550000**

Note Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	1x1*	1x1*
4 mm²	1x1*	1x1*
6 mm²		
10 mm²		
16 mm²		

Note *Please refer to the Terminal Block catalogue or the SAK Series for more information about assembling the enclosures with terminal blocks. There are no prescribed possible attachment points in the enclosure.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	3	1
M16	3	1
M20	2	
M25		
M32		
M40		
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Klippon® K 1

Depth 45 mm



XX* for 9526840000 and1329630000

Height / Width / Depth	70 / 70 / 45 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	**9529120000**
Standard (silicone seal)*	**1937630000**
unpainted	
Standard (CR seal)	**0342000000**
Standard (silicone seal)*	**1939560000**

Note The colours of painted enclosures may vary under certain circumstances. Ex-enclosures are available on request. *Delivery time on request

Accessories

Terminal rail, Set	Order No.
15 mm width	**1909980000**
Mounting plate	
Steel sheet, zinc plated	**1905280000**
Torx®screw driver	
not insulated, Torx® TH20	**9009160000**
Earthing stud	
Brass, M6	**1277250000**
Stainless steel 1.4404, M6	**1283430000**
Pressure compensation elements	
Polyamide 6, M12	**1868570000**
Stainless steel 1.4305, M12	**1868550000**

Note The accessory sets contain the necessary mounting materials. Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	1x1*	1x5
4 mm²	1x1*	1x1*
6 mm²		
10 mm²		
16 mm²		

Note *Please refer to the Terminal Block Catalogue or the SAK Series for more information about populating the enclosures with terminal blocks. For vertical installations, we recommend using not more than one BK 4 or BK 4 CRN (0625120000). For horizontal installations with 2.5mm² 1x5 AKZ terminal blocks (only possible on a TS 15) for 4mm², use not more than one BK 4. There are no pre-defined mounting points set within this enclosure for installing internal equipment in a vertical position.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	2	1
M16	2	1
M20	1	
M25		
M32		
M40		
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® K 11

Depth 57 mm



Height / Width / Depth	80 / 75 / 57 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	**9529130000**
Standard (silicone seal)*	**1937910000**
unpainted	
Standard (CR seal)	**0573300000**
Standard (silicone seal)*	**1939570000**

Note The colours of painted enclosures may vary under certain circumstances. Ex-enclosures are available on request. *Delivery time on request

Accessories

Terminal rail, Set	Order No.
15 mm width	**1909990000**
Mounting plate	
Steel sheet, zinc plated	**3073000000**
Hinge, diecast zinc, Set	
	1580360000
Torx®screw driver	
not insulated, Torx® TH20	**9009160000**
Earthing stud	
Brass, M6	**1277250000**
Stainless steel 1.4404, M6	**1283430000**
Pressure compensation elements	
Polyamide 6, M12	**1868570000**
Stainless steel 1.4305, M12	**1868550000**

Note The accessory sets contain the necessary mounting materials. Necessary on use of 1 hinge per longitudinal side. Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	1x1*	1x5
4 mm²	1x1*	1x4
6 mm²		
10 mm²		
16 mm²		

Note *Please refer to the Terminal Block Catalogue or the SAK Series for more information about populating the enclosures with terminal blocks. We recommend at most one BK 6 or BK 6 CRN (0625220000) in vertical installations. There are no pre-defined mounting points set within this enclosure for installing internal equipment in a vertical position.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	2	2
M16	2	2
M20	1	1
M25	1	
M32		
M40		
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® K 2

Depth 45 mm



XX* for 9526860000 and 1329650000

Height / Width / Depth	70 / 100 / 45 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	9529140000
Standard (silicone seal)*	1937930000
unpainted	
Standard (CR seal)	0342100000
Standard (silicone seal)*	1939580000

Note The colours of painted enclosures may vary under certain circumstances. Ex-enclosures are available on request. *Delivery time on request

Accessories

Terminal rail, Set	Order No.
15 mm width	1910010000
Mounting plate	
Steel sheet, zinc plated	1905270000
Torx®screw driver	
not insulated, Torx® TH20	9009160000
Earthing stud	
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000

Note The accessory sets contain the necessary mounting materials. Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x10
4 mm²	*	
6 mm²		
10 mm²		
16 mm²		

Note *Please refer to the Terminal Block Catalogue or the SAK Series for more information about populating the enclosures with terminal blocks. We recommend at most one BK 6 or BK 6 CRN (0625220000) for vertical installations. There are no pre-defined mounting points set within this enclosure for installing internal equipment in a vertical position.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	3	1
M16	3	1
M20	2	
M25		
M32		
M40		
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® K 21

Depth 57 mm



Height / Width / Depth	80 / 125 / 57 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	**9529150000**
Standard (silicone seal)*	**1937830000**
unpainted	
Standard (CR seal)	**0573400000**
Standard (silicone seal)*	**1939590000**

Note The colours of painted enclosures may vary under certain circumstances. Ex-enclosures are available on request. *Delivery time on request

Accessories

Terminal rail, Set	Order No.
15 mm width	**1910020000**
Mounting plate	
Steel sheet, zinc plated	**3073020000**
Hinge, diecast zinc, Set	
	1580360000
Torx®screw driver	
not insulated, Torx® TH20	**9009160000**
Earthing stud	
Brass, M6	**1277250000**
Stainless steel 1.4404, M6	**1283430000**
Pressure compensation elements	
Stainless steel 1.4305, M12	**1868550000**
Polyamide 6, M12	**1868570000**

Note The accessory sets contain the necessary mounting materials. Necessary on use of 1 hinge per longitudinal side. Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x15
4 mm²	*	1x12
6 mm²		
10 mm²		
16 mm²		

Note *Please refer to the Terminal Block Catalogue or the SAK Series for more information about populating the enclosures with terminal blocks. We recommend BK 6 or BK 6 CRN (0625220000) for vertical installations. There are no pre-defined mounting points set within this enclosure for installing internal equipment in a vertical position.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	6	2
M16	4	2
M20	3	1
M25	2	
M32		
M40		
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® K 3

Depth 45 mm



XX* for 9526880000 and 1329670000

Height / Width / Depth	70 / 165 / 45 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	**9529160000**
Standard (silicone seal)*	**1937900000**
unpainted	
Standard (CR seal)	**0342200000**
Standard (silicone seal)*	**1939600000**

Note The colours of painted enclosures may vary under certain circumstances. Ex-enclosures are available on request. *Delivery time on request

Accessories

Terminal rail, Set	Order No.
15 mm width	**1910030000**
Mounting plate	
Steel sheet, zinc plated	**1898210000**
Torx®screw driver	
not insulated, Torx® TH20	**9009160000**
Earthing stud	
Brass, M6	**1277250000**
Stainless steel 1.4404, M6	**1283430000**
Pressure compensation elements	
Stainless steel 1.4305, M12	**1868550000**
Polyamide 6, M12	**1868570000**

Note The accessory sets contain the necessary mounting materials. Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x22
4 mm²	*	
6 mm²		
10 mm²		
16 mm²		

Note *Please refer to the Terminal Block Catalogue or the SAK Series for more information about populating the enclosures with terminal blocks. We recommend BK 6 or BK 6 CRN (0625220000) for vertical installations. There are no pre-defined mounting points set within this enclosure for installing internal equipment in a vertical position.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	6	1
M16	5	1
M20	4	
M25		
M32		
M40		
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® K 31

Depth 57 mm



Height / Width / Depth	80 / 175 / 57 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	9529170000
Standard (silicone seal)*	1937820000
unpainted	
Standard (CR seal)	0573500000
Standard (silicone seal)*	1939610000

Note The colours of painted enclosures may vary under certain circumstances. Ex-enclosures are available on request. *Delivery time on request

Accessories

Terminal rail, Set	Order No.
15 mm width	1910040000
Mounting plate	
Steel sheet, zinc plated	3073040000
Hinge, diecast zinc, Set	
	1580360000
Torx®screw driver	
not insulated, Torx® TH20	9009160000
Earthing stud	
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Stainless steel 1.4305, M12	1868550000
Polyamide 6, M12	1868570000

Note The accessory sets contain the necessary mounting materials. Necessary on use of 1 hinge per longitudinal side. Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)

Assembly with terminal		vertical	horizontal
	2.5 mm²	*	1x23
	4 mm²	*	1x19
	6 mm²		
	10 mm²		
	16 mm²		

Note *Please refer to the Terminal Block Catalogue or the SAK Series for more information about populating the enclosures with terminal blocks. We recommend BK 6 or BK 6 CRN (0625220000) for vertical installations. There are no pre-defined mounting points set within this enclosure for installing internal equipment in a vertical position.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	9	2
M16	6	2
M20	4	1
M25	3	
M32		
M40		
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® K 32

Depth 55 mm



Height / Width / Depth	80 / 250 / 55 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	**9529180000**
Standard (silicone seal)*	**1937810000**
unpainted	
Standard (CR seal)	**1565260000**
Standard (silicone seal)*	**1939620000**

Note The colours of painted enclosures may vary under certain circumstances. Ex-enclosures are available on request. *Delivery time on request

Accessories

Mounting plate	Order No.
Steel sheet, zinc plated	**3073050000**
Torx®screw driver	
not insulated, Torx® TH20	**9009160000**
Earthing stud	
Brass, M6	**1277250000**
Stainless steel 1.4404, M6	**1283430000**
Pressure compensation elements	
Stainless steel 1.4305, M12	**1868550000**
Polyamide 6, M12	**1868570000**

Note The accessory sets contain the necessary mounting materials. Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x38
4 mm²	*	1x32
6 mm²		
10 mm²		
16 mm²		

Note *Please refer to the Terminal Block Catalogue or the SAK Series for more information about populating the enclosures with terminal blocks. We recommend BK 6 or BK 6 CRN (0625220000) for vertical installations. There are no pre-defined mounting points set within this enclosure for installing internal equipment in a vertical position.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	15	2
M16	9	2
M20	7	1
M25	6	
M32		
M40		
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® K 4

Depth 72 mm



Height / Width / Depth	82 / 130 / 72 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	9529190000
Standard (silicone seal)*	1937890000
unpainted	
Standard (CR seal)	0342300000
Standard (silicone seal)*	1939630000

Note The colours of painted enclosures may vary under certain circumstances. Ex-enclosures are available on request. *Delivery time on request

Accessories

Terminal rail, Set	Order No.
35 mm width	1910060000
Mounting plate	
Steel sheet, zinc plated	3073060000
Hinge, diecast zinc, Set	
	1580360000
Torx®screw driver	
not insulated, Torx® TH20	9009160000
Earthing stud	
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Pressure compensation elements	
Stainless steel 1.4305, M12	1868550000
Polyamide 6, M12	1868570000

Note Sets also contain the mounting material, if necessary. 1 hinge per longitudinal side. Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	1x5	*
4 mm²	1x4	*
6 mm²	1x3	
10 mm²	1x2	
16 mm²		

Note
The mounting rails are designed to be installed directly.
Assembly with terminals provides for 10 mm clearance to the ends of the mounting rail.
Ordering recommendations:
TS 35 mounting rail (screw-type terminals) WDU 2.5 1020000000 / (tension clamp terminals) ZDU 2.5 1608510000
*For fitting the enclosures with terminal blocks, please refer to the Terminal block catalogue or the SAK series. We recommend BK 6 or BK 6 CRN (0625220000) for horizontal installations. There are no pre-defined mounting points set within this enclosure for installing internal equipment in a horizontal position.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	5	2
M16	3	2
M20	2	1
M25	2	1
M32		1
M40		
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® K 41

Depth 81 mm



Height / Width / Depth	120 / 122 / 81 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	9529200000
Standard (silicone seal)*	1937800000
unpainted	
Standard (CR seal)	1565270000
Standard (silicone seal)*	1939640000

Note The colours of painted enclosures may vary under certain circumstances. Ex-enclosures are available on request. *Delivery time on request

Accessories

Terminal rail, Set	Order No.
35 mm width	1910070000
Mounting plate	
Steel sheet, zinc plated	3073070000
Hinge, diecast zinc, Set	
	1580360000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9527590000
Torx®screw driver	
not insulated, Torx® TH20	9009160000
Earthing stud	
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Pressure compensation elements	
Stainless steel 1.4305, M12	1868550000
Polyamide 6, M12	1868570000

Note The accessory sets contain the necessary mounting materials. Necessary on use of 1 hinge per longitudinal side. Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x13
4 mm²	*	1x11
6 mm²		1x8
10 mm²		1x6
16 mm²		

Note *Please refer to the Terminal Block Catalogue or the SAK Series for more information about populating the enclosures with terminal blocks. We recommend BK 6 or BK 6 CRN (0625220000) for vertical installations. There are no specified mounting options available for mounting the enclosure in a vertical position. There are no pre-defined mounting points set within this enclosure for installing internal equipment in a vertical position.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	6	4
M16	6	4
M20	3	2
M25	2	1
M32	1	1
M40		
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® K 5

Depth 90 mm



Height / Width / Depth	130 / 170 / 90 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	**9529210000**
Standard (silicone seal)*	**1937860000**
unpainted	
Standard (CR seal)	**0342400000**
Standard (silicone seal)*	**1939650000**

Note The colours of painted enclosures may vary under certain circumstances. Ex-enclosures are available on request. *Delivery time on request

Accessories

Terminal rail, Set	Order No.
35 mm width	**1910080000**
Mounting plate	
Steel sheet, zinc plated	**3073080000**
Hinge, diecast zinc, Set	
	1580360000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	**9529080000**
Torx®screw driver	
not insulated, Torx® TH20	**9009160000**
Earthing stud	
Brass, M6	**1277250000**
Stainless steel 1.4404, M6	**1283430000**
Brass, M10	**1277220000**
Stainless steel 1.4404, M10	**1283440000**
Pressure compensation elements	
Stainless steel 1.4305, M12	**1868550000**
Polyamide 6, M12	**1868570000**

Note The accessory sets contain the necessary mounting materials. Necessary on use of 1 hinge per longitudinal side. Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x20
4 mm²	*	1x17
6 mm²		1x12
10 mm²		1x10
16 mm²		1x8

Note
The mounting rails are designed to be installed directly.
Assembly with terminals provides for 10 mm clearance to the ends of the mounting rail.
Order recommendations:
TS 35 mounting rail with WDU clamping yoke technology, ZDU spring-cage terminal block or A2C PUSH IN technology
Ordering information for the terminal blocks, please refer to the online catalogue.
*For fitting the enclosures with terminal blocks, please refer to the Terminal block catalogue or the SAK series. We recommend BK 6 or BK 6 CRN (0625220000) for vertical installations. There are no specified mounting options available for mounting the enclosure in a vertical position. There are no pre-defined mounting points set within this enclosure for installing internal equipment in a vertical position.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	11	4
M16	8	2
M20	4	1
M25	3	1
M32	2	1
M40		
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® K 51

Depth 81 mm



Height / Width / Depth	120 / 220 / 81 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	9529220000
Standard (silicone seal)*	1937750000
unpainted	
Standard (CR seal)	1565280000
Standard (silicone seal)*	1939660000

Note The colours of painted enclosures may vary under certain circumstances. Ex-enclosures are available on request. *Delivery time on request

Accessories

Terminal rail, Set	Order No.
35 mm width	1910090000
Mounting plate	
Steel sheet, zinc plated	3073090000
Hinge, diecast zinc, Set	
	1580360000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9527590000
Torx®screw driver	
not insulated, Torx® TH20	9009160000
Earthing stud	
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Pressure compensation elements	
Stainless steel 1.4305, M12	1868550000
Polyamide 6, M12	1868570000

Note The accessory sets contain the necessary mounting materials. Necessary on use of 2 hinges per longitudinal side. Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x31
4 mm²	*	1x26
6 mm²		1x19
10 mm²		1x16
16 mm²		

Note
The mounting rails are designed to be installed directly.
Assembly with terminals provides for 10 mm clearance to the ends of the mounting rail.
Order recommendations:
TS 35 mounting rail with WDU clamping yoke technology, ZDU spring-cage terminal block or A2C PUSH IN technology
Ordering information for the terminal blocks, please refer to the online catalogue.
*For fitting the enclosures with terminal blocks, please refer to the Terminal block catalogue or the SAK series. We recommend BK 6 or BK 6 CRN (0625220000) for vertical installations. There are no specified mounting options available for mounting the enclosure in a vertical position. There are no pre-defined mounting points set within this enclosure for installing internal equipment in a vertical position.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	23	6
M16	14	3
M20	8	2
M25	5	1
M32	3	1
M40	3	
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® K 52

Depth 91 mm



Height / Width / Depth	160 / 160 / 91 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	9529230000
Standard (silicone seal)*	1937740000
unpainted	
Standard (CR seal)	1565290000
Standard (silicone seal)*	1939670000

Note The colours of painted enclosures may vary under certain circumstances. Ex-enclosures are available on request. *Delivery time on request

Accessories

Terminal rail, Set	Order No.
35 mm width	1910100000
Mounting plate	
Steel sheet, zinc plated	3073100000
Hinge, diecast zinc, Set	
	1580360000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9527590000
Torx®screw driver	
not insulated, Torx® TH20	9009160000
Earthing stud	
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Pressure compensation elements	
Stainless steel 1.4305, M12	1868550000
Polyamide 6, M12	1868570000

Note The accessory sets contain the necessary mounting materials. Necessary on use of 1 hinge per longitudinal side. Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x16
4 mm²	*	1x13
6 mm²		1x10
10 mm²		1x8
16 mm²		1x6

Note
The mounting rails are designed to be installed directly.
Assembly with terminals provides for 10 mm clearance to the ends of the mounting rail.
Order recommendations:
TS 35 mounting rail with WDU clamping yoke technology, ZDU spring-cage terminal block or A2C PUSH IN technology
Ordering information for the terminal blocks, please refer to the online catalogue.
*For fitting the enclosures with terminal blocks, please refer to the Terminal block catalogue or the SAK series. We recommend BK 6 or BK 6 CRN (0625220000) for vertical installations. There are no specified mounting options available for mounting the enclosure in a vertical position. There are no pre-defined mounting points set within this enclosure for installing internal equipment in a vertical position.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	14	8
M16	8	5
M20	5	3
M25	3	2
M32	2	1
M40	1	
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® K 6

Depth 100 mm



Height / Width / Depth	160 / 200 / 100 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	9529240000
Standard (silicone seal)*	1937870000
unpainted	
Standard (CR seal)	0342500000
Standard (silicone seal)*	1939690000

Note The colours of painted enclosures may vary under certain circumstances. Ex-enclosures are available on request. *Delivery time on request

Accessories

Terminal rail, Set	Order No.
35 mm width	1910110000
Mounting plate	
Steel sheet, zinc plated	3073110000
Hinge, diecast zinc, Set	
	1580360000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9529080000
Torx®screw driver	
not insulated, Torx® TH20	9009160000
Earthing stud	
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Pressure compensation elements	
Stainless steel 1.4305, M12	1868550000
Polyamide 6, M12	1868570000

Note The accessory sets contain the necessary mounting materials. Necessary on use of 2 hinges per longitudinal side. Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x25
4 mm²	*	1x21
6 mm²		1x16
10 mm²		1x12
16 mm²		1x10

Note
The mounting rails are designed to be installed directly.
Assembly with terminals provides for 10 mm clearance to the ends of the mounting rail.
Order recommendations:
TS 35 mounting rail with WDU clamping yoke technology, ZDU spring-cage terminal block or A2C PUSH IN technology
Ordering information for the terminal blocks, please refer to the online catalogue.
*For fitting the enclosures with terminal blocks, please refer to the Terminal block catalogue or the SAK series. We recommend BK 6 or BK 6 CRN (0625220000) for vertical installations. There are no specified mounting options available for mounting the enclosure in a vertical position. There are no pre-defined mounting points set within this enclosure for installing internal equipment in a vertical position.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	17	6
M16	12	6
M20	7	3
M25	4	2
M32	3	2
M40	2	1
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® K 61

Depth 91 mm



Height / Width / Depth	160 / 260 / 91 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	9529250000
Standard (silicone seal)*	1937730000
unpainted	
Standard (CR seal)	0573600000
Standard (silicone seal)*	1939700000

Note The colours of painted enclosures may vary under certain circumstances. Ex-enclosures are available on request. *Delivery time on request

Accessories

Terminal rail, Set	Order No.
35 mm width	1910120000
Mounting plate	
Steel sheet, zinc plated	3073120000
Hinge, diecast zinc, Set	
	1580360000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9527590000
Torx®screw driver	
not insulated, Torx® TH20	9009160000
Earthing stud	
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Pressure compensation elements	
Stainless steel 1.4305, M12	1868550000
Polyamide 6, M12	1868570000

Note The accessory sets contain the necessary mounting materials. Necessary on use of 2 hinges per longitudinal side. Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal		vertical	horizontal
	2.5 mm²	*	1x39
	4 mm²	*	1x33
	6 mm²		1x24
	10 mm²		1x20
	16 mm²		1x16

Note
The mounting rails are designed to be installed directly.
Assembly with terminals provides for 10 mm clearance to the ends of the mounting rail.
Order recommendations:
TS 35 mounting rail with WDU clamping yoke technology, ZDU spring-cage terminal block or A2C PUSH IN technology
Ordering information for the terminal blocks, please refer to the online catalogue.
*For fitting the enclosures with terminal blocks, please refer to the Terminal block catalogue or the SAK series. We recommend BK 6 or BK 6 CRN (0625220000) for vertical installations. There are no specified mounting options available for mounting the enclosure in a vertical position. There are no pre-defined mounting points set within this enclosure for installing internal equipment in a vertical position.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	27	8
M16	23	6
M20	13	3
M25	8	2
M32	4	1
M40	3	1
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® K 7

Depth 100 mm



Height / Width / Depth	160 / 350 / 100 mm

Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	9529260000
Standard (silicone seal)*	1937880000
unpainted	
Standard (CR seal)	0342600000
Standard (silicone seal)*	1939710000

Note The colours of painted enclosures may vary under certain circumstances. Ex-enclosures are available on request. *Delivery time on request

Accessories

Terminal rail, Set	Order No.
35 mm width	1910130000
Mounting plate	
Steel sheet, zinc plated	3073130000
Hinge, diecast zinc, Set	
	1580360000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9529080000
Torx®screw driver	
not insulated, Torx® TH20	9009160000
Earthing stud	
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Pressure compensation elements	
Stainless steel 1.4305, M12	1868550000
Polyamide 6, M12	1868570000

Note The accessory sets contain the necessary mounting materials. Necessary on use of 2 hinges per longitudinal side. Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal		vertical	horizontal
	2.5 mm²	*	1x55
	4 mm²	*	1x46
	6 mm²		1x34
	10 mm²		1x28
	16 mm²		1x23

Note
The mounting rails are designed to be installed directly.
Assembly with terminals provides for 10 mm clearance to the ends of the mounting rail.
Order recommendations:
TS 35 mounting rail with WDU clamping yoke technology, ZDU spring-cage terminal block or A2C PUSH IN technology
Ordering information for the terminal blocks, please refer to the online catalogue.
*For fitting the enclosures with terminal blocks, please refer to the Terminal block catalogue or the SAK series. We recommend BK 6 or BK 6 CRN (0625220000) for vertical installations. There are no specified mounting options available for mounting the enclosure in a vertical position. There are no pre-defined mounting points set within this enclosure for installing internal equipment in a vertical position.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	42	8
M16	26	6
M20	17	3
M25	10	2
M32	6	2
M40	5	1
M50		
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® K 71

Depth 111 mm

230 / 280 / 111 mm



Ordering data

powder-coated (RAL 7001)	Order No.
Standard (CR seal)	9529270000
Standard (silicone seal)*	1937720000
unpainted	
Standard (CR seal)	0573700000
Standard (silicone seal)*	1939730000

Note The colours of painted enclosures may vary under certain circumstances. Ex-enclosures are available on request. *Delivery time on request

Accessories

Terminal rail, Set	Order No.
35 mm width	1910140000
Mounting plate	
Steel sheet, zinc plated	3073140000
Hinge, diecast zinc, Set	
	1580360000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9527590000
Torx®screw driver	
not insulated, Torx® TH20	9009160000
Earthing stud	
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Pressure compensation elements	
Stainless steel 1.4305, M12	1868550000
Polyamide 6, M12	1868570000

Note The accessory sets contain the necessary mounting materials. Necessary on use of 2 hinges per longitudinal side. Helicoil for outdoor applications, available ex-works.

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	2x43
4 mm²	*	2x36
6 mm²		2x26
10 mm²		2x21
16 mm²		2x17

Note
The mounting rails are designed to be installed directly.
Assembly with terminals provides for 10 mm clearance to the ends of the mounting rail.
Order recommendations:
TS 35 mounting rail with WDU clamping yoke technology, ZDU spring-cage terminal block or A2C PUSH IN technology
Ordering information for the terminal blocks, please refer to the online catalogue.
*For fitting the enclosures with terminal blocks, please refer to the Terminal block catalogue or the SAK series. We recommend BK 6 or BK 6 CRN (0625220000) for vertical installations. There are no specified mounting options available for mounting the enclosure in a vertical position. There are no pre-defined mounting points set within this enclosure for installing internal equipment in a vertical position.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	42	28
M16	30	18
M20	21	10
M25	12	8
M32	10	3
M40	4	2
M50	3	2
M63		

Note Our IP68 brass cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® Protect – Terminal Boxes – Product overview: Aluminium enclosure

Use the product overview to find the right solution for you! Combine your own industrial version consisting of an enclosure, with or without threaded holes, a suitable mounting rail or pre-fitted terminal strips. The compatible components are always shown in a row.

Klippon Protect enclosures with explosion protection for use in explosive risk zones are available on request.

Aluminium enclosure, uncoated

Empty enclosure without threaded holes



Mounting rail (TS)
Mounting plate (MOPL)

Dimensions of the enclosure height x width x depth in mm	Enclosure type	Order No.	Qty.	Type	Length in mm	Rail mounting slot dimensions in mm	Order No.	Qty.
Aluminium, uncoated								
64 x 58 x 34	Klippon® K01	**1565240000**	10	-	-	-	–	-
70 x 70 x 45	Klippon® K1	**0342000000**	10	TS15	60	4.5 x 20	**1909980000**	1
80 x 75 x 57	Klippon® K11	**0573300000**	10	TS15	64	4.5 x 20	**1909990000**	1
70 x 100 x 45	Klippon® K2	**0342100000**	10	TS15	90	4.5 x 20	**1910010000**	1
80 x 125 x 57	Klippon® K21	**0573400000**	5	TS15	114	4.5 x 20	**1910020000**	1
70 x 165 x 45	Klippon® K3	**0342200000**	5	TS15	155	4.5 x 20	**1910030000**	1
				MOPL	154	4.2 x 14	**8000004497**	1
80 x 175 x 57	Klippon® K31	**0573500000**	5	TS15	164	4.5 x 20	**1910040000**	1
82 x 130 x 72	Klippon® K4	**0342300000**	1	TS35	64	5.5 x 20	**1910060000**	1
120 x 122 x 81	Klippon® K41	**1565270000**	1	TS35	105	6.3 x 20	**1910070000**	1
130 x 170 x 90	Klippon® K5	**0342400000**	1	TS35	148	5.5 x 20	**1910080000**	1
160 x 160 x 91	Klippon® K52	**1565290000**	1	TS35	140	6.3 x 20	**1910100000**	1
		protection class IP 66		suitable for the enclosures of the respective line				

[1] Multi-pole terminal strip (terminal block BK 4, BK 6 or BK 12), mounted on mounting plate
[2] Space for further threaded holes up to M40



Empty enclosure with threaded holes



Terminal strip

Ex protected Terminal Boxes

Threaded hole Side A	Threaded hole Side B	Order No.	Qty.	Connection technology	Cross-section mm²	Number of DU*	Number of PE*	Order No.	Qty.	Order No.
1x M16	1x M16	**8000004184**	1	Screw connection	4	4	0	**7906080000**	100	–
1x M16	2x M16	**8000004147**	1	Screw connection	4	4	0	**8000004129**[1)]	1	**8000004202**
1x M20	1x M20	**8000004148**	1							**8000004203**
2x M16	2x M16	**8000004149**	1							**8000004207**
2x M20	2x M20	**8000004150**	1	Tension clamp connection	2.5	5	1	**8000004130**	1	**8000004208**
2x M16	2x M16			Tension clamp connection	2.5	5	1			**8000004204**
2x M20	2x M20			Screw connection	4	5	2			**8000004209**
2x M20	2x M20	**8000004151**	1	Screw connection	4	6	0	**8000004132**[1)]	1	**8000004210**
3x M16	3x M16	**8000004152**	1	Screw connection	4	13	2	**8000004134**	1	**8000004212**
3x M16	3x M16			Tension clamp connection	2.5	14	2	**8000004133**	1	**8000004211**
4x M20	4x M20	**8000004153**	1	Screw connection	4	12	0	**8000004135**[1)]	1	**8000004213**
4x M20	4x M20	**8000004154**	1	Screw connection	4	21	2	**8000004137**	1	
4x M20	4x M20			Tension clamp connection	2.5	24	2	**8000004136**	1	**8000004214**
2x M20	2x M20	**8000004155**	1	Screw connection	4	5	2	**8000004138**	1	
2x M20	2x M20			Tension clamp connection	4	4	1	**8000004139**	1	
2x M25	2x M25	**8000003446**	1	Screw connection	4	12	2	**8000003444**	1	**8000003589**
3x M20	3x M20	**8000003447**	1							
2x M25	2x M25									
3x M20	3x M20									**8000003591**
4x M20	4x M20	**8000004158**	1	Screw connection	4	17	2	**8000004140**	1	**8000004218**
4x M20	4x M20			Tension clamp connection	4	15	2		1	**8000004219**
4x M20	4x M20		1	Screw connection	4	16	2	**8000004142**	1	**8000004220**
4x M20	4x M20			Tension clamp connection	2.5	19	2	**8000004143**	1	**8000004221**

suitable for the enclosure of the respective line
*DU = feed-through terminals, PE = PE terminals

Ex-enclosure with threaded holes and terminal strip according to the respective line

Safely control work processes in harsh environments on site

With certified enclosure solutions with control and display elements

Harsh industrial environments, such as those in the water treatment industry, place extreme demands on the safety, robustness and quality of products and devices.

We meet these challenges with the Klippon® Control Station, the addition to our range of customised enclosure solutions. More than 50 years of expertise have made us market leader in this area with global competence centres. The basis of our enclosure solutions is provided by the usual Weidmüller quality and comprehensive approvals for explosion hazard areas. Based on this, our sturdy "on-site control station" is available in two standard sizes and with up to four control and display elements and provides a flexible solution to meet your specific needs.

Order your distributor enclosure as well as control and signaling units from a single source and from one enclosure design – for reliable security and reduced storage costs for maintenance and repair operations.

Your special advantages:
Ideal for urgent service calls
We have prepared modules of the proven Klippon® enclosure series K available for you for further processing. This means we manufacture a control solution suitable for your application at short notice.

Predestined for emergency shutdown applications: Klippon® Control Stations score when it comes to the safe shutdown of plant sections, such as in the process industry

Project solutions from a single source
Obtain command/signaling units and distribution and control boxes as a complete solution – tailored to the individual requirements of your projects in hazardous areas.

Customised assembly
In addition to standard types from stock, you can obtain enclosure solutions from us that are completely assembled and equipped according to customer requirements.



A variety of sizes and materials
Enclosures in stainless steel, aluminium or polyester are available for different environmental conditions. Depending on the size of the enclosure, it provides space for the integration of up to four control and display elements.

International certificates
The Klippon® Control Station is tested and certified among others according to ATEX and IECEx.

Reliable stability for all applications

Klippon® Protect – convincing with impact-resistant aluminium enclosures

Aluminium enclosures (Klippon® K) can be used with a wide range of applications and are ideally suited for the assembly of terminal blocks, switches, power supplies, operating and display elements or electronic modules. Available in aluminium alloy and powder coated RAL 7001. The mounting holes are located outside the sealing area, while a corresponding thread enables mounting rails and mounting plates to be affixed.

Additional features:

- Standardised enclosure with integrated threaded holes
- Cover attachment with corrosion-resistant Torx slothead screws
- Fastening by means of mounting feet or internal mounting holes
- Splice-free seals for optimum ingress protection up to IP 66

Technical data	Aluminium
Material	Aluminium alloy (AL-Si12)
Surface finish	Powder-coated
Colour	RAL 7001
IP protection class	IP 54; IP 66
Ambient temperature	-55 °C to 55 °C
Seal material of enclosure	Silicone (VMQ)
Seal material of command and signalling units	EPDM
Flammability rating	-
Impact resistance IK	7 joules in acc. with IEC60079-0 4 joules in acc. with IEC60079-0 with integrated illuminated pushbutton or light module
Cable gland material	Nickel-plated brass
Cable gland clamping area min. – max. in mm	
M20	3–12 mm
M25	10–18 mm
Max. rated cross-section	2.5 mm²
Max. operating voltage	400 V
with integrated illuminated pushbutton or light module	250 V
Maximum operating current at 40 °C ambient temperature	
1.5 mm² – T6	10 A
1.5 mm² – T5	16 A
2.5 mm² – T6	16 A
Maximum operating current at 55 °C ambient temperature	
1.5 mm² – T4	16 A
1.5 mm² – T5	10 A
2.5 mm² – T5	16 A
Temperature class	T4, T5, T6
Type of mounting	Wall mounting
Earthing inside	Earth terminal
Lid attachment	Torx® 20 slothead screws
Lid screw torque	2.5 Nm
Earthing torque	2.5 Nm
Earthing outside	M4 earthing studs, stainless steel
Approvals	IECEXITA14.0013X TUEV14ATEX7606X MARITREG 15.40082.250
Marking	2G Ex e d IIC T* Gb 2G Ex ib d [ia] IIC T* Gb 2D Ex tb IIIC T80/100 °C Db
Mounting feet	9527590000

	Number of built-in components				Emergency stop pushbutton	Key switch	Pushbutton		Illuminated pushbutton		Light module		Dimensions with built-in components HxWxD in mm	Designation	Cable gland	Order number	
	●	●●	●●●	●●●●	red	I – 0 – II	red	green	red	green	red	green					
Aluminium	●				1								149x120x119	KLIPPON CS K41-1	VG M20	1537470000	
	●						1						149x120x94	KLIPPON CS K41-1	VG M20	1537480000	
	●					1							149x120x108	KLIPPON CS K41-1	VG M20	1537490000	
	●									1			149x120x96	KLIPPON CS K41-1	VG M20	1537500000	
		●					1	1					152x120x119	KLIPPON CS K41-4	VG M25	1537510000	
		●						1				1	152x120x103	KLIPPON CS K41-4	VG M25	1537520000	
		●			1						1		152x120x119	KLIPPON CS K41-4	VG M25	1537530000	
			●				1	1			1		250x120x103	KLIPPON CS K51-2	VG M25	1537540000	
			●				1	2					250x120x94	KLIPPON CS K51-2	VG M25	1537550000	
			●		1		1	1					250x120x119	KLIPPON CS K51-2	VG M25	1537570000	
				●			1	1			1	1	250x120x103	KLIPPON CS K51-4	VG M25	1537580000	

Technical data

	Klippon® CS K41-1	Klippon® CS K41-1
Enclosure		
Dimensions with installation (HxBxD)	149 / 120 / 119 mm	149 / 120 / 94 mm
Material	Aluminium AlSi12	Aluminium AlSi12
General characteristics		
Surface finish / Colour	Powder-coated / Silver grey	Powder-coated / Silver grey
Protection class	IP54, IP66	IP54, IP66
Ambient temperature	-55 °C...+55 °C	-55 °C...+55 °C
Impact resistance	7 joules in acc. with IEC 60079-0	7 joules in acc. with IEC 60079-0
Enclosure seal material	Silicone (VMQ)	Silicone (VMQ)
Seal material of operating and display elements	EPDM	EPDM
Type of mounting	Wall mounting	Wall mounting
Internal earth	Earth terminal	Earth terminal
External earth	M4 earthing studs, stainless steel	M4 earthing studs, stainless steel
Lid attachment	Torx®-20 slothead screws	Torx®-20 slothead screws
Torque for lid screws	2.5 Nm	2.5 Nm
Earth stud torque	2.5 Nm	2.5 Nm
Electrical properties*		
Wire connection cross section, finely stranded, max.	2.5 mm²	2.5 mm²
Operating voltage, max.	400 V	400 V
Temperature class	T4, T5, T6	T4, T5, T6
Enclosure assembly		
1 Position in enclosure	EMERGENCY-STOP pushbutton with yellow, contrasting label	Pushbutton - green
2 Position in enclosure		
3 Position in enclosure		
4 Position in enclosure		
Contact design	2 NC contact, positive opening contacts	1 NC contact, 1 NO contacts
Actuators	EMERGENCY STOP pushbutton	Pushbutton
Actuator colour	red	green
Illumination module colour		
Illuminated button actuator colour		
Cable entries		
Drill holes side B	1 x M20	1 x M20
Cable gland	1460050000 - VG M20 EXE MS	1460050000 - VG M20 EXE MS
Clamping range min. / max.	3 mm / 12 mm	3 mm / 12 mm
Approval and Marking		
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-31	IEC 60079-0, IEC 60079-7, IEC 60079-31
Certificate No. (IECEX)	IECEXITA14.0013X	IECEXITA14.0013X
Certificate No. (ATEX)	TUEV14ATEX7606X	TUEV14ATEX7606X
Certificate No. (EAC)	RUC-DE.BE02.B.00173	RUC-DE.TB08.B.01838
Certificate No. (MARITREG)	15.40082.250	15.40082.250
Marking	II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db	II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
Accessories		
Mounting feet	9527590000 - KLIPPON K MF KIT 25	9527590000 - KLIPPON K MF KIT 25
Note		

Ordering data

Type	Qty.	Order No.
KLIPPON CS K41-1	1	1537470000

Type	Qty.	Order No.
KLIPPON CS K41-1	1	1537480000

Note	
	*Other temperature classes and connection values on request, or see "Notice to Installer".

Note	
	*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS K41-1

149 / 120 / 108 mm
Aluminium AlSi12
Powder-coated / Silver grey
IP54, IP66
-55 °C...+55 °C
7 joules in acc. with IEC 60079-0
Silicone (VMQ)
EPDM
Wall mounting
Earth terminal
M4 earthing studs, stainless steel
Torx®-20 slothead screws
2.5 Nm
2.5 Nm
2.5 mm²
400 V
T4, T5, T6
Key-operated switch
1 NC contact, 1 NO contacts
Key-operated switch, 3 switching positions, I - 0 - II, (I + II), latching, Key retractable
1 x M20
1460050000 - VG M20 EXE MS
3 mm / 12 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.BE02.B.00173
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
9527590000 - KLIPPON K MF KIT 25

Type	Qty.	Order No.
KLIPPON CS K41-1	1	**1537490000**

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS K41-1

149 / 120 / 96 mm
Aluminium AlSi12
Powder-coated / Silver grey
IP54, IP66
-55 °C...+55 °C
4 joules in acc. with IEC 60079-0
Silicone (VMQ)
EPDM
Wall mounting
Earth terminal
M4 earthing studs, stainless steel
Torx®-20 slothead screws
2.5 Nm
2.5 Nm
2.5 mm²
250 V
T4, T5, T6
Illuminated pushbutton - green
2 NO contacts
Pushbutton
green
green
1 x M20
1460050000 - VG M20 EXE MS
3 mm / 12 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.BE02.B.00173
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
9527590000 - KLIPPON K MF KIT 25

Type	Qty.	Order No.
KLIPPON CS K41-1	1	**1537500000**

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS K41-4

152 / 120 / 119 mm
Aluminium AlSi12
Powder-coated / Silver grey
IP54, IP66
-55 °C...+55 °C
7 joules in acc. with IEC 60079-0
Silicone (VMQ)
EPDM
Wall mounting
Earth terminal
M4 earthing studs, stainless steel
Torx®-20 slothead screws
2.5 Nm
2.5 Nm
2.5 mm²
400 V
T4, T5, T6
Pushbutton - red
Pushbutton - green
2 NC contact, 2 NO contacts
Pushbutton
red, green
1 x M25
1460070000 - VG M25 EXE MS
10 mm / 18 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.BE02.B.00173
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
9527590000 - KLIPPON K MF KIT 25

Type	Qty.	Order No.
KLIPPON CS K41-4	1	**1537510000**

*Other temperature classes and connection values on request, or see "Notice to Installer".

Technical data

	Klippon® CS K41-4	Klippon® CS K41-4
Enclosure		
Dimensions with installation (HxBxD)	152 / 120 / 103 mm	152 / 120 / 119 mm
Material	Aluminium AlSi12	Aluminium AlSi12
General characteristics		
Surface finish / Colour	Powder-coated / Silver grey	Powder-coated / Silver grey
Protection class	IP54, IP66	IP54, IP66
Ambient temperature	-55 °C...+55 °C	-55 °C...+55 °C
Impact resistance	4 joules in acc. with IEC 60079-0	4 joules in acc. with IEC 60079-0
Enclosure seal material	Silicone (VMQ)	Silicone (VMQ)
Seal material of operating and display elements	EPDM	EPDM
Type of mounting	Wall mounting	Wall mounting
Internal earth	Earth terminal	Earth terminal
External earth	M4 earthing studs, stainless steel	M4 earthing studs, stainless steel
Lid attachment	Torx®-20 slothead screws	Torx®-20 slothead screws
Torque for lid screws	2.5 Nm	2.5 Nm
Earth stud torque	2.5 Nm	2.5 Nm
Electrical properties*		
Wire connection cross section, finely stranded, max.	2.5 mm²	2.5 mm²
Operating voltage, max.	250 V	250 V
Temperature class	T4, T5, T6	T4, T5, T6
Enclosure assembly		
1 Position in enclosure	Light module - green	Light module - red
2 Position in enclosure	Pushbutton - green	EMERGENCY-STOP pushbutton with yellow, contrasting label
3 Position in enclosure		
4 Position in enclosure		
Contact design	1 NC contact, 1 NO contacts	2 NC contact, positive opening contacts
Actuators	Pushbutton	EMERGENCY STOP pushbutton
Actuator colour	green	red
Illumination module colour	green	
Illuminated button actuator colour		
Cable entries		
Drill holes side B	1 x M25	1 x M25
Cable gland	1460070000 - VG M25 EXE MS	1460070000 - VG M25 EXE MS
Clamping range min. / max.	10 mm / 18 mm	10 mm / 18 mm
Approval and Marking		
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-31	IEC 60079-0, IEC 60079-7, IEC 60079-31
Certificate No. (IECEX)	IECEXITA14.0013X	IECEXITA14.0013X
Certificate No. (ATEX)	TUEV14ATEX7606X	TUEV14ATEX7606X
Certificate No. (EAC)	RUC-DE.BE02.B.00173	RUC-DE.BE02.B.00173
Certificate No. (MARITREG)	15.40082.250	15.40082.250
Marking	II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db	II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
Accessories		
Mounting feet	9527590000 - KLIPPON K MF KIT 25	9527590000 - KLIPPON K MF KIT 25
Note		

Ordering data

Type	Qty.	Order No.
KLIPPON CS K41-4	1	1537520000

Type	Qty.	Order No.
KLIPPON CS K41-4	1	1537530000

Note		
	*Other temperature classes and connection values on request, or see "Notice to Installer".	*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS K51-2

250 / 120 / 103 mm
Aluminium AlSi12
Powder-coated / Silver grey
IP54, IP66
-55 °C...+55 °C
4 joules in acc. with IEC 60079-0
Silicone (VMQ)
EPDM
Wall mounting
Earth terminal
M4 earthing studs, stainless steel
Torx®-20 slothead screws
2.5 Nm
2.5 Nm
2.5 mm²
250 V
T4, T5, T6
Pushbutton - red
Light module - green
Pushbutton - green
2 NC contact, 2 NO contacts
Pushbutton
red, green
green
1 x M25
1460070000 - VG M25 EXE MS
10 mm / 18 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.BE02.B.00173
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
9527590000 - KLIPPON K MF KIT 25

Type	Qty.	Order No.
KLIPPON CS K51-2	1	**1537540000**

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS K51-2

250 / 120 / 94 mm
Aluminium AlSi12
Powder-coated / Silver grey
IP54, IP66
-55 °C...+55 °C
7 joules in acc. with IEC 60079-0
Silicone (VMQ)
EPDM
Wall mounting
Earth terminal
M4 earthing studs, stainless steel
Torx®-20 slothead screws
2.5 Nm
2.5 Nm
2.5 mm²
400 V
T4, T5, T6
Pushbutton - green
Pushbutton - red
Pushbutton - green
3 NC contact, 3 NO contacts
Pushbutton
green, red
1 x M25
1460070000 - VG M25 EXE MS
10 mm / 18 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.BE02.B.00173
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
9527590000 - KLIPPON K MF KIT 25

Type	Qty.	Order No.
KLIPPON CS K51-2	1	**1537550000**

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS K51-2

250 / 120 / 119 mm
Aluminium AlSi12
Powder-coated / Silver grey
IP54, IP66
-55 °C...+55 °C
7 joules in acc. with IEC 60079-0
Silicone (VMQ)
EPDM
Wall mounting
Earth terminal
M4 earthing studs, stainless steel
Torx®-20 slothead screws
2.5 Nm
2.5 Nm
2.5 mm²
400 V
T4, T5, T6
Pushbutton - green
Pushbutton - red
EMERGENCY-STOP pushbutton with yellow, contrasting label
2 NO contacts, 2 NC contact, positive opening contacts
Pushbutton, EMERGENCY STOP pushbutton
green, red
1 x M25
1460070000 - VG M25 EXE MS
10 mm / 18 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.TB08.B.01838
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
9527590000 - KLIPPON K MF KIT 25

Type	Qty.	Order No.
KLIPPON CS K51-2	1	**1537570000**

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS K51-4

Technical data

Enclosure	
Dimensions with installation (HxBxD)	250 / 120 / 103 mm
Material	Aluminium AlSi12
General characteristics	
Surface finish / Colour	Powder-coated / Silver grey
Protection class	IP54, IP66
Ambient temperature	-55 °C...+55 °C
Impact resistance	4 joules in acc. with IEC 60079-0
Enclosure seal material	Silicone (VMQ)
Seal material of operating and display elements	EPDM
Type of mounting	Wall mounting
Internal earth	Earth terminal
External earth	M4 earthing studs, stainless steel
Lid attachment	Torx®-20 slothead screws
Torque for lid screws	2.5 Nm
Earth stud torque	2.5 Nm
Electrical properties*	
Wire connection cross section, finely stranded, max.	2.5 mm²
Operating voltage, max.	250 V
Temperature class	T4, T5, T6
Enclosure assembly	
1 Position in enclosure	Light module - red
2 Position in enclosure	Pushbutton - red
3 Position in enclosure	Light module - green
4 Position in enclosure	Pushbutton - green
Contact design	2 NC contact, 2 NO contacts
Actuators	Pushbutton
Actuator colour	green, red
Illumination module colour	red, green
Illuminated button actuator colour	
Cable entries	
Drill holes side B	1 x M25
Cable gland	1460070000 - VG M25 EXE MS
Clamping range min. / max.	10 mm / 18 mm
Approval and Marking	
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-31
Certificate No. (IECEX)	IECEXITA14.0013X
Certificate No. (ATEX)	TUEV14ATEX7606X
Certificate No. (EAC)	RUC-DE.BE02.B.00173
Certificate No. (MARITREG)	15.40082.250
Marking	II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
Accessories	
Mounting feet	9527590000 - KLIPPON K MF KIT 25

Note	

Ordering data

Type	Qty.	Order No.
KLIPPON CS K51-4	1	**1537580000**

Note	*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® POK – Polyester Enclosures

Universal terminal boxes for standard industrial applications and for potentially explosive atmospheres in Zones 1 and 2, 21 and 22

The Klippon® POK enclosure range is made from a high-quality glass fibre reinforced polyester and is ideal for applications and environments where corrosion resistance, impact resistance and a high IP protection class is a requirement.

Key Features:

- Manufactured from glass fibre reinforced polyester
- Available in 17 sizes
- Two standard finishes (colours)
  Grey, similar to RAL 7001 (industrial use)
  Black, similar to RAL 9011 (harsh environments, Ex)
- Captive lid fixing screws are stainless steel
- Fixing holes are located outside of the lid sealing area to ensure high ingress protection of IP66
- Threaded holes for internal component mounting
- Silicone sealing for extreme temperature environments
- Impact resistance up to 7 Joules
- Approved to the latest international standards, including EN 62208 and IEC EN 60079



Cross-head screws
The enclosure lid is secured with stainless steel captive cross-head screws. Handling the enclosure is made simple. A single tool is the only requirement for quick and easy installation.

Mounting plates
Internal mounting plates for the installation of terminal rails, terminal blocks or other equipment are available.



Brass Earth Continuity Plate
An angled design made to complement the Klippon® POK enclosures installed in potentially explosive atmospheres. The brass earth continuity plate is available as an optional accessory.





Earth kit
The Klippon® POK Ex enclosures are designed for applications installed in potentially explosive atmospheres. An M6 or M10 internal/external earth kit is available as an optional accessory.

Other Colour
Grey, similar to RAL7001
Black, simillar to RAL 9011
Other colours are available on request (subject to a minimum order quantity).

Enclosure wall fixing (direct or via mounting lugs)
The fixing positions of each enclosure are located outside of the sealing area. The enclosure can be fastened directly via fixing holes found on the rear side of the enclosure or alternatively, it is possible to secure the enclosure from the outside by means of mounting lugs that are separately available.

Closed moulded sealing
Robust and secure sealing increases the performance of each enclosure with enhanced ingress protection.

The Klippon® POK enclosures are supplied as standard with a removable and replaceable moulded gasket.
Available in either silicone or chloroprene material and depending upon the enclosure type they are adapted to the contour of each enclosure to ensure ingress performance is maintained.

Klippon® POK – Polyester enclosures

The Klippon® POK range of polyester enclosures are designed to protect and integrate with general purpose electrical and electronic equipment as well as control components in harsh environments or potentially explosive atmospheres.

Designed to meet the rigourous demands of industrial automation or process control and energy industries and with signal and component protection in mind, the Klippon POK enclosure range is designed to meet the customers' application needs.

Our customer specific assembly service can provide a fully customised enclosure solution, designed to meet the customer requirements.

Features:

- For use in potentially explosive atmospheres and industrial applications
- Extremely robust with a high impact resistance
- Approved to the latest international standards
- M4 or M6 mounting elements integrated into enclosure body for installation of mounting plates, mounting rails, printed circuit boards etc.

Note: The enclosure range Klippon® POK can be assembled with terminals or other approved equipment by our locally available Application-Specific Solutions service. Please ask us for more details.

Use our online catalogue to find additional product details, technical information and additional services:
www.weidmueller.com/KlipponPOK

Overview of enclosures

Ordering data

Description	Hight x width x depth in mm	Standard (grey finish)	Ex Enclosures (black finish)	Reference product
Klippon® POK 080806	75 x 80 x 55	1305810000	1306000000	Klippon® POK 1
Klippon® POK 081106	75 x 110 x 56	1305820000	1306010000	Klippon® POK 2
Klippon® POK 081606	75 x 160 x 56	1305830000	1306020000	Klippon® POK 3
Klippon® POK 081906	75 x 190 x 55	1305840000	1306030000	Klippon® POK 31
Klippon® POK 082306	75 x 230 x 56	1305850000	1306040000	Klippon® POK 32
Klippon® POK 121209	120 x 122 x 90	1305870000	1306050000	Klippon® POK 4
Klippon® POK 122209	120 x 220 x 90	1305880000	1306070000	Klippon® POK 5
Klippon® POK 161609	160 x 160 x 90	1305890000	1306080000	Klippon® POK 51
Klippon® POK 162609	160 x 260 x 90	1305900000	1306090000	Klippon® POK 6
Klippon® POK 163609	160 x 360 x 90	1305910000	1306100000	Klippon® POK 7
Klippon® POK 165609	160 x 560 x 90	1305920000	1306110000	Klippon® POK 71
Klippon® POK 252512	250 x 255 x 120	1305930000	1306120000	Klippon® POK 8
Klippon® POK 252516	250 x 255 x 160.5	1305980000	1306170000	Klippon® POK 9
Klippon® POK 254012	250 x 400 x 120	1305940000	1306130000	Klippon® POK 91
Klippon® POK 254016	250 x 400 x 160.5	1305990000	1306180000	Klippon® POK 10
Klippon® POK 256012	250 x 600 x 120	1305950000	1306140000	Klippon® POK 11
Klippon® POK 404012	405 x 400 x 120	1305970000	1306150000	Klippon® POK 12
Hinweis				

Technical Overview

Technical data

	Ex	Standard
Enclosure material	Glass fibre-reinforced polyester to DIN 16913 with added graphite	Glass fibre-reinforced polyester to DIN 16913
Surface	Black, similar to RAL 9011	Grey, similar to RAL7001
IP Rating	IP 66 to DIN EN 60529	IP 66 to DIN EN 60529
NEMA Rating	4, 4x	4, 4x
Equipment mounting	M4 to M6 threaded bushes	M4 to M6 threaded bushes
Enclosure mounting	4 holes for M4 to M6 screw	4 holes for M4 to M6 screw
Lid fixing	M4/M6 slothead / crosshead screws from stainless steel	M4/M6 slothead / crosshead screws from stainless steel
Impact Resistance	7J to IEC 60029-0	IK08 (5J) to DIN EN 50102
Gasket material	Silicone (VMQ)	Chloroprene
Temperature range	-55 °C...+100 °C	-40 °C...+100 °C
Torque screws of lid M4	2.0 – 2.5 Nm	2.0 – 2.5 Nm
Torque screws of lid M6	2.5 – 3.0 Nm	2.5 – 3.0 Nm
Surface resistance (in ohms)	< 10^9 Ohm	10^{12} Ohm
Flammability	UL 94 V0, self extinguishing	UL 94 V0, self extinguishing
Toxicity	Halogen and cadmium-free	Halogen and cadmium-free
Note		

Approvals for empty enclosures

	Ex	Standard
ATEX certificate	IBExU13ATEX1003 U	
ATEX marking	⟨Ex⟩ II 2G Ex e IIC Gb or ⟨Ex⟩ II 2G Ex eb IIC ⟨Ex⟩ II 2D Ex tb IIIC Db or ⟨Ex⟩ II 2D Ex tb IIIC	
IECEx certificate	IECEx IBE 13.0003U	
IECEx marking	Ex e IIC Gb or Ex eb IIC Ex tb IIIC Db or Ex tb IIIC	
EAC	RUC-DE.08.B.00472	RUC-DE.08.B.00472
cULus	E 256877	E 256877
Lloyd's Register	14/20001	14/20001
Russian Maritime Register	19.00109.272	
DNV GL	TAE00002R2	TAE00002R2
AEx	E223792	
Note		

Approvals terminal enclosures

ATEX certificate	IBExU13ATEX1004 X		
ATEX marking	⟨Ex⟩ II 2G Ex e IIC T6...T5 Gb or ⟨Ex⟩ II 2G Ex eb IIC T6...T5 ⟨Ex⟩ II 1G Ex ia IIC T6...T5 Ga or ⟨Ex⟩ II 1G Ex ia IIC T6...T5 ⟨Ex⟩ II 2(1)G Ex e ia IIC T6...T5 Gb or ⟨Ex⟩ II 2(1)G Ex eb ia IIC T6...T5 ⟨Ex⟩ II 2D Ex tb IIIC T 85 °C...100 °C Db or ⟨Ex⟩ II 2D Ex tb IIIC T 85 °C...100 °C		
IECEx certificate	IECEx IBE 13.0004X		
IECEx marking	Ex e IIC T6...T5 Gb or Ex eb IIC T6...T5 Ex ia IIC T6...T5 Ga or Ex ia IIC T6...T5 Ex e ia IIC T6...T5 Gb or Ex eb ia IIC T6...T5 Ex tb IIIC T 85 °C...100 °C Db or Ex tb IIIC T 85 °C...100 °C		
EAC certificate	RUC-DE.08.B.01328	AEx certificate	E223792
EAC marking	II 2 G Ex eb IIC T6/T5 II 2 G Ex e IIC T6/T5 Gb II 1 G Ex ia IIC T6/T5 II 1 G Ex ia IIC T6/T5 Ga II 2(1) G Ex eb ia IIC T6/T5 II 2(1) G Ex e ia IIC T6/T5 Gb II 2 D Ex tb IIIC T 85 °C...100 °C II 2 D Ex tb IIIC T 85 °C...100 °C Db	AEx marking	Class I, Zone 1, AEx e IIC Gb T6..T4 Class I, Zone 2, AEx e IIC Gc T6..T4 Class I Div.2 Group A,B,C,D T6...T4 Class II Div.2 Group F,G Zone 21, AEx tb IIIC Db
KOSHA certificate	16-AV4B0-246X		
KOSHA marking	Ex e IIC T6...T5 Gb or Ex eb IIC T6...T5 Ex ia IIC T6...T5 Ga or Ex ia IIC T6...T5 Ex e ia IIC T6...T5 Gb or Ex eb ia IIC T6...T5 Ex tb IIIC T 85 °C...100 °C Db or Ex tb IIIC T 85 °C...100 °C		
Note	If you have specific requirements for installations within potentially explosive atmospheres, please contact Weidmüller for a copy of the approval certificates. For details of power dissipation, please contact your Weidmüller representative.		

Klippon® POK 080806

Depth 55 mm



Height / Width / Depth	75 / 80 / 55 mm

Ordering data

RAL 7001	Order No.
Standard	1305810000
RAL 9011	
Ex enclosure	1306000000

Note The overview page lists the ambient temperatures.

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	9510570000
Steel sheet, galvanized for applications with earthing plate	1534280000
Fastening screws for mounting plates	0642600000
Mounting rails, TS15x5	
Horizontally	8000003889
Brass Earth Continuity Plate	
Brass	1390910000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510900000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	1x1*	1x5
4 mm²	1x1*	1x4
6 mm²		
10 mm²		
16 mm²		

Note * Please refer to the Terminal Block catalogue or the SAK Series for more information about assembling the enclosures with terminal blocks. We recommend a maximum of one BK 6, e.g. BK 6 CRN (0625220000), for vertical installation. There are no specified mounting options available for mounting the enclosure in a vertical position.
Order recommendations:
TS 35 mounting rail with WDU clamping yoke technology, ZDU spring-cage terminal block or A2C PUSH IN technology
TS 32 mounting rail with clamping yoke technology SAK
TS 15 mounting rail with clamping yoke technology AKZ
Ordering information for the terminal blocks, please refer to the online catalogue.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	4	1
M16	2	1
M20	1	1
M25	1	
M32		
M40		
M50		
M63		

Note ** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® POK 081106

Depth 56 mm



Height / Width / Depth	75 / 110 / 56 mm

Ordering data

RAL 7001	Order No.
Standard	1305820000
RAL 9011	
Ex enclosure	1306010000

Note The overview page lists the ambient temperatures.

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	9510580000
Steel sheet, galvanized for applications with earthing plate	1534290000
Fastening screws for mounting plates	0642600000
Mounting rails, TS15x5	
Horizontally	8000003890
Brass Earth Continuity Plate	
Brass	1390920000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510900000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	1x1*	1x10
4 mm²	1x1*	1x9
6 mm²		
10 mm²		
16 mm²		

Note * Please refer to the Terminal Block catalogue or the SAK Series for more information about assembling the enclosures with terminal blocks. We recommend a maximum of one BK 6, e.g. BK 6 CRN (0625220000), for vertical installation. There are no specified mounting options available for mounting the enclosure in a vertical position.
Order recommendations:
TS 35 mounting rail with WDU clamping yoke technology, ZDU spring-cage terminal block or A2C PUSH IN technology
TS 32 mounting rail with clamping yoke technology SAK
TS 15 mounting rail with clamping yoke technology AKZ
Ordering information for the terminal blocks, please refer to the online catalogue.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	7	1
M16	3	1
M20	2	1
M25	2	
M32		
M40		
M50		
M63		

Note ** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® POK 081606

Depth 56 mm



Height / Width / Depth	75 / 160 / 56 mm

Ordering data

RAL 7001	Order No.
Standard	1305830000
RAL 9011	
Ex enclosure	1306020000

Note The overview page lists the ambient temperatures.

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	9510680000
Steel sheet, galvanized for applications with earthing plate	1534310000
Fastening screws for mounting plates	0642600000
Mounting rails, TS15x5	
Horizontally	8000003891
Brass Earth Continuity Plate	
Brass	1390930000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510900000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x20
4 mm²	*	1x17
6 mm²		
10 mm²		
16 mm²		

Note * Please refer to the Terminal Block catalogue or the SAK Series for more information about assembling the enclosures with terminal blocks. We recommend a maximum of one BK 6, e.g. BK 6 CRN (0625220000), for vertical installation. There are no specified mounting options available for mounting the enclosure in a vertical position.
Order recommendations:
TS 35 mounting rail with WDU clamping yoke technology, ZDU spring-cage terminal block or A2C PUSH IN technology
TS 32 mounting rail with clamping yoke technology SAK
TS 15 mounting rail with clamping yoke technology AKZ
Ordering information for the terminal blocks, please refer to the online catalogue.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	11	1
M16	5	1
M20	4	1
M25	3	
M32		
M40		
M50		
M63		

Note ** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® POK 081906

Depth 55 mm



Height / Width / Depth	75 / 190 / 55 mm

Ordering data

RAL 7001	Order No.
Standard	1305840000
RAL 9011	
Ex enclosure	1306030000

Note The overview page lists the ambient temperatures.

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	9510690000
Steel sheet, galvanized for applications with earthing plate	1534320000
Fastening screws for mounting plates	0642600000
Mounting rails, TS15x5	
Horizontally	8000003892
Brass Earth Continuity Plate	
Brass	1390940000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510900000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x26
4 mm²	*	1x22
6 mm²		
10 mm²		
16 mm²		

Note

* Please refer to the Terminal Block catalogue or the SAK Series for more information about assembling the enclosures with terminal blocks. We recommend a maximum of one BK 6, e.g. BK 6 CRN (0625220000), for vertical installation. There are no specified mounting options available for mounting the enclosure in a vertical position.
Order recommendations:
TS 35 mounting rail with WDU clamping yoke technology, ZDU spring-cage terminal block or A2C PUSH IN technology
TS 32 mounting rail with clamping yoke technology SAK
TS 15 mounting rail with clamping yoke technology AKZ
Ordering information for the terminal blocks, please refer to the online catalogue.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	14	1
M16	6	1
M20	5	1
M25	4	
M32		
M40		
M50		
M63		

Note

** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® POK 082306

Depth 56 mm



Height / Width / Depth	75 / 230 / 56 mm

Ordering data

RAL 7001	Order No.
Standard	1305850000
RAL 9011	
Ex enclosure	1306040000

Note The overview page lists the ambient temperatures.

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, galvanized for applications with earthing plate	1534330000
Fastening screws for mounting plates	0642600000
Mounting rails, TS15x5	
Horizontally	8000032382
Brass Earth Continuity Plate	
Brass	1390950000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510900000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x33
4 mm²	*	1x28
6 mm²		
10 mm²		
16 mm²		

Note * Please refer to the Terminal Block catalogue or the SAK Series for more information about assembling the enclosures with terminal blocks. We recommend a maximum of one BK 6, e.g. BK 6 CRN (0625220000), for vertical installation. There are no specified mounting options available for mounting the enclosure in a vertical position.
Order recommendations:
TS 35 mounting rail with WDU clamping yoke technology, ZDU spring-cage terminal block or A2C PUSH IN technology
TS 32 mounting rail with clamping yoke technology SAK
TS 15 mounting rail with clamping yoke technology AKZ
Ordering information for the terminal blocks, please refer to the online catalogue.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	16	1
M16	6	1
M20	6	1
M25	4	
M32		
M40		
M50		
M63		

Note ** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® POK 121209

Depth 90 mm



Height / Width / Depth	120 / 122 / 90 mm

Ordering data

RAL 7001	Order No.
Standard	1305870000
RAL 9011	
Ex enclosure	1306050000

Note The overview page lists the ambient temperatures.

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	9510590000
Steel sheet, galvanized for applications with earthing plate	1534340000
Fastening screws for mounting plates	0642600000
Mounting rails, TS15x5	
Horizontally	8000003890
Brass Earth Continuity Plate	
Brass	1390970000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510910000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x12
4 mm²	*	1x10
6 mm²		1x7
10 mm²		1x6
16 mm²		1x5

Note
The assembly with terminal rails is designed for direct mounting.
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.
Recommendations for ordering:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal block ZDU or PUSH IN technology A2C
TS 32 Mounting rail with clamping yoke technology SAK
TS 15 Mounting rail with clamping yoke technology AKZ
Order information for rail-mounted terminal blocks, please refer to the online catalogue
*There are no specified mounting options available for vertical mounting in the enclosure.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	12	8
M16	6	4
M20	4	3
M25	2	1
M32	1	1
M40		
M50		
M63		

Note ** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® POK 122209

Depth 90 mm



Height / Width / Depth	120 / 220 / 90 mm

Ordering data

RAL 7001	Order No.
Standard	1305880000
RAL 9011	
Ex enclosure	1306070000

Note The overview page lists the ambient temperatures.

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	9510600000
Steel sheet, galvanized for applications with earthing plate	1534350000
Fastening screws for mounting plates	0642600000
Mounting rails, TS35x7.5	
Horizontally	8000037568
Brass Earth Continuity Plate	
Brass	1390980000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510910000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x31
4 mm²	*	1x26
6 mm²		1x19
10 mm²		1x15
16 mm²		1x13

Note
The assembly with terminal rails is designed for direct mounting.
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.
Recommendations for ordering:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
Order information for rail-mounted terminal blocks, please refer to the online catalogue
*There are no specified mounting options available for vertical mounting in the enclosure.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	24	8
M16	14	4
M20	12	3
M25	5	1
M32	4	1
M40	3	
M50		
M63		

Note ** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® POK 161609

Depth 90 mm



Height / Width / Depth	160 / 160 / 90 mm

Ordering data

RAL 7001	Order No.
Standard	1305890000
RAL 9011	
Ex enclosure	1306080000

Note The overview page lists the ambient temperatures.

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	9510610000
Steel sheet, galvanized for applications with earthing plate	1534360000
Fastening screws for mounting plates	0642600000
Mounting rails, TS35x7.5	
Horizontally	8000003908
Brass Earth Continuity Plate	
Brass	1390990000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510910000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x17
4 mm²	*	1x14
6 mm²		1x11
10 mm²		1x9
16 mm²		1x7

Note
The assembly with terminal rails is designed for direct mounting.
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.
Recommendations for ordering:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
Order information for rail-mounted terminal blocks, please refer to the online catalogue
*There are no specified mounting options available for vertical mounting in the enclosure.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	15	11
M16	12	6
M20	6	4
M25	3	2
M32	2	2
M40	2	1
M50		
M63		

Note ** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® POK 162609

Depth 90 mm



Height / Width / Depth	160 / 260 / 90 mm

Ordering data

RAL 7001	Order No.
Standard	1305900000
RAL 9011	
Ex enclosure	1306090000
Note The overview page lists the ambient temperatures.	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	9510620000
Steel sheet, galvanized for applications with earthing plate	1534370000
Fastening screws for mounting plates	0642600000
Mounting rails, TS35x7.5	
Horizontally	8000003909
Brass Earth Continuity Plate	
Brass	1391000000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510910000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x36
4 mm²	*	1x30
6 mm²		1x23
10 mm²		1x16
16 mm²		1x16

Note

The assembly with terminal rails is designed for direct mounting.
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.
Recommendations for ordering:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
Order information for rail-mounted terminal blocks, please refer to the online catalogue
*There are no specified mounting options available for vertical mounting in the enclosure.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	30	11
M16	24	6
M20	14	4
M25	5	2
M32	4	2
M40	3	1
M50		
M63		

Note ** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Note

Klippon® POK 163609

Depth 90 mm



Height / Width / Depth	160 / 360 / 90 mm

Ordering data

RAL 7001	Order No.
Standard	1305910000
RAL 9011	
Ex enclosure	1306100000

Note The overview page lists the ambient temperatures.

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	9510630000
Steel sheet, galvanized for applications with earthing plate	1534380000
Fastening screws for mounting plates	0642600000
Mounting rails, TS35x7.5	
Horizontally	8000003910
Brass Earth Continuity Plate	
Brass	1391010000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510910000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x56
4 mm²	*	1x47
6 mm²		1x36
10 mm²		1x29
16 mm²		1x24

Note
The assembly with terminal rails is designed for direct mounting.
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.
Recommendations for ordering:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
Order information for rail-mounted terminal blocks, please refer to the online catalogue
*There are no specified mounting options available for vertical mounting in the enclosure.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	45	11
M16	36	6
M20	20	4
M25	8	2
M32	6	2
M40	5	1
M50		
M63		

Note ** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® POK 165609

Depth 90 mm



Height / Width / Depth	160 / 560 / 90 mm

Ordering data

RAL 7001	Order No.
Standard	1305920000
RAL 9011	
Ex enclosure	1306110000

Note The overview page lists the ambient temperatures.

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	9510710000
Steel sheet, galvanized for applications with earthing plate	1534390000
Fastening screws for mounting plates	0642600000
Mounting rails, TS35x7.5	
Horizontally	8000003911
Brass Earth Continuity Plate	
Brass	1391020000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510910000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	1x94
4 mm²	*	1x79
6 mm²		1x60
10 mm²		1x49
16 mm²		1x41

Note
The assembly with terminal rails is designed for direct mounting.
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.
Recommendations for ordering:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
Order information for rail-mounted terminal blocks, please refer to the online catalogue
*There are no specified mounting options available for vertical mounting in the enclosure.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	66	11
M16	58	6
M20	32	4
M25	12	2
M32	10	2
M40	8	1
M50		
M63		

Note ** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® POK 252512

Depth 120 mm



Height / Width / Depth	250 / 255 / 120 mm

Ordering data

RAL 7001	Order No.
Standard	1305930000
RAL 9011	
Ex enclosure	1306120000

Note The overview page lists the ambient temperatures.

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	9510640000
Steel sheet, galvanized for applications with earthing plate	1534410000
Fastening screws for mounting plates	0642600000
Mounting rails, TS35x7.5	
Horizontally	8000003912
Brass Earth Continuity Plate	
Brass	1391030000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510910000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	2x38
4 mm²	*	2x31
6 mm²		2x23
10 mm²		2x19
16 mm²		2x15

Note
The assembly with terminal rails is designed for direct mounting.
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.
Recommendations for ordering:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
Order information for rail-mounted terminal blocks, please refer to the online catalogue
*There are no specified mounting options available for vertical mounting in the enclosure.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	36	32
M16	32	21
M20	10	15
M25	10	8
M32	8	3
M40	3	3
M50	2	2
M63		

Note ** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® POK 252516

Depth 160.5 mm



Height / Width / Depth	250 / 255 / 160.5 mm

Ordering data

RAL 7001	Order No.
Standard	1305980000
RAL 9011	
Ex enclosure	1306170000

Note The overview page lists the ambient temperatures.

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	9510640000
Steel sheet, galvanized for applications with earthing plate	1534410000
Fastening screws for mounting plates	0642600000
Mounting rails, TS35x7.5	
Horizontally	8000003912
Brass Earth Continuity Plate	
Brass	1391030000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510910000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	2x38
4 mm²	*	2x31
6 mm²		2x23
10 mm²		2x19
16 mm²		2x15

Note
The assembly with terminal rails is designed for direct mounting.
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.
Recommendations for ordering:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
Order information for rail-mounted terminal blocks, please refer to the online catalogue
*There are no specified mounting options available for vertical mounting in the enclosure.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	36	32
M16	32	21
M20	18	15
M25	10	8
M32	8	3
M40	3	3
M50	2	2
M63		

Note ** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® POK 254012

Depth 120 mm



Height / Width / Depth	250 / 400 / 120 mm

Ordering data

RAL 7001	Order No.
Standard	1305940000
RAL 9011	
Ex enclosure	1306130000

Note The overview page lists the ambient temperatures.

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	9510650000
Steel sheet, galvanized for applications with earthing plate	1534420000
Fastening screws for mounting plates	0642600000
Mounting rails, TS35x7.5	
Horizontally	8000003913
Brass Earth Continuity Plate	
Brass	1391040000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510910000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	2x67
4 mm²	*	2x55
6 mm²		2x41
10 mm²		2x33
16 mm²		2x27

Note
The assembly with terminal rails is designed for direct mounting.
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.
Recommendations for ordering:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
Order information for rail-mounted terminal blocks, please refer to the online catalogue
*There are no specified mounting options available for vertical mounting in the enclosure.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	62	32
M16	54	21
M20	33	15
M25	18	8
M32	14	3
M40	6	3
M50	4	2
M63		

Note ** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® POK 254016

Depth 160.5 mm



Height / Width / Depth	250 / 400 / 160.5 mm

Ordering data

RAL 7001	Order No.
Standard	1305990000
RAL 9011	
Ex enclosure	1306180000
Note The overview page lists the ambient temperatures.	

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	9510650000
Steel sheet, galvanized for applications with earthing plate	1534420000
Fastening screws for mounting plates	0642600000
Mounting rails, TS35x7.5	
Horizontally	8000003913
Brass Earth Continuity Plate	
Brass	1391040000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510910000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	2x67
4 mm²	*	2x55
6 mm²		2x41
10 mm²		2x33
16 mm²		2x27

Note

The assembly with terminal rails is designed for direct mounting.
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.
Recommendations for ordering:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
Order information for rail-mounted terminal blocks, please refer to the online catalogue
*There are no specified mounting options available for vertical mounting in the enclosure.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	62	32
M16	54	21
M20	33	15
M25	18	8
M32	14	3
M40	6	3
M50	4	2
M63		

Note ** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® POK 256012

Depth 120 mm



Height / Width / Depth	250 / 600 / 120 mm

Ordering data

RAL 7001	Order No.
Standard	1305950000
RAL 9011	
Ex enclosure	1306140000

Note The overview page lists the ambient temperatures.

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	9510660000
Steel sheet, galvanized for applications with earthing plate	1534430000
Fastening screws for mounting plates	0642600000
Mounting rails, TS35x7.5	
Horizontally	8000003914
Brass Earth Continuity Plate	
Brass	1391050000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510910000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	2x107
4 mm²	*	2x89
6 mm²		2x66
10 mm²		2x53
16 mm²		2x44

Note
The assembly with terminal rails is designed for direct mounting.
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
Order information for rail-mounted terminal blocks, please refer to the online catalogue
*There are no specified mounting options available for vertical mounting in the enclosure.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	96	32
M16	80	21
M20	24	15
M25	20	8
M32	20	3
M40	8	3
M50	6	2
M63		

Note ** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Klippon® POK 404012

Depth 120 mm

405 / 400 / 120 mm



Ordering data

RAL 7001	Order No.
Standard	1305970000
RAL 9011	
Ex enclosure	1306150000

Note The overview page lists the ambient temperatures.

Accessories

Mounting plates and fastening screws	Order No.
Steel sheet, zinc plated	9510670000
Steel sheet, galvanized for applications with earthing plate	1534440000
Fastening screws for mounting plates	0642600000
Mounting rails, TS35x7.5	
Horizontally	8000003913
Brass Earth Continuity Plate	
Brass	1391070000
External mounting feet, set of 4	
Stainless steel 1.4301 natural	9510910000
Earthing stud	
Brass, M10	1277220000
Stainless steel 1.4404, M10	1283440000
Brass, M6	1277250000
Stainless steel 1.4404, M6	1283430000
Pressure compensation elements	
Polyamide 6, M12	1868570000
Stainless steel 1.4305, M12	1868550000
Stainless steel 1.4404, M20 for Ex applications	2519570000

Note

Guide value for max. number of terminals (industry)



Assembly with terminal	vertical	horizontal
2.5 mm²	*	3x67
4 mm²	*	3x55
6 mm²		3x41
10 mm²		3x33
16 mm²		3x27

Note
The assembly with terminal rails is designed for direct mounting.
The assembly with modular terminals gives consideration to a distance of 10 mm from the end of each mounting rail.
Recommendations for ordering:
TS 35 Mounting rail with clamping yoke technology WDU, spring-cage terminal ZDU or PUSH IN technology A2C
Order information for rail-mounted terminal blocks, please refer to the online catalogue
*There are no specified mounting options available for vertical mounting in the enclosure.

Guide value for max. number of cable entries

Guide value for max. number of cable entries	A / B	C / D
M12	62	60
M16	54	39
M20	33	30
M25	18	18
M32	14	7
M40	6	5
M50	4	4
M63		

Note ** Our IP 68 plastic cable glands are used as the reference for these guideline values.

Dimensions of mounting plate



Note

Klippon® Protect Terminal Boxes – Product overview: Polyester enclosure

Use the product overview to find the right solution for you! Combine your own industrial version consisting of an enclosure, with or without threaded holes, a suitable mounting rail or pre-fitted terminal strips. The compatible components are always shown in a row.

Klippon® Protect offers you approved Terminal Boxes with for use in explosive areas can be found in the last column. They come with threaded holes and are already equipped with a terminal strip.

Polyester enclosure

Empty enclosure without threaded holes



Mounting rail (TS)
Mounting plate (MOPL)

Dimensions of the enclosure height x width x depth mm	Enclosure type	Order No.	Qty.	Type	Length mm	Rail mounting slot dimensions mm	Order No.	Qty.
Polyester, RAL 7001								
75 x 80 x 55	Klippon® 080806	**1305810000**	1	TS 15	68	4.5 x 20	**1928060000**	1
75 x 110 x 56	Klippon® 081106	**1305820000**	1	TS 15	98	4.5 x 20	**1928070000**	1
75 x 160 x 56	Klippon® 081606	**1305830000**	1	TS 15	147	4.5 x 20	**1928080000**	1
120 x 122 x 90	Klippon® 121209	**1305870000**	1	TS 35	105	6.3 x 20	**1910070000**	1
160 x 160 x 90	Klippon® 161609	**1305890000**	1	TS 35	140	6.3 x 20	**1910100000**	1
		protection class IP 66		suitable for the enclosure of the respective line				

[1] Multi-pole terminal blocks (block terminals BK 4, BK 6 or BK 12) can be directly fitted
[2] Space for further threaded holes up to M32

Empty enclosure
with threaded holes





Terminal strip

Ex protected
Terminal Boxes

Threaded hole Side A	Threaded hole Side B	Order No.	Qty.	Connection technology	Cross-section mm²	Number of DU*	Number of PE*	Order No.	Qty.	Order No.
2x M16	2x M16	**8000004160**	1	Screw connection	4	4	0	**8000004365**[1]	1	**8000004222**
2x M16	2x M16			Screw connection	4	6	2	**8000004144**	1	**8000004223**
2x M20	2x M20	**8000004161**	1	Screw connection	4	6	0	**8000004366**[1]	1	**8000004224**
2x M20	2x M20			Screw connection	4	10	2	**8000004145**	1	**8000004225**
4x M20	4x M20	**8000004162**	1	Screw connection	4	12	0	**8000004367**[1]	1	**8000004226**
4x M20	4x M20			Screw connection	4	18	2	**8000004146**	1	**8000004228**
3x M20	3x M20	**8000003448**	1	Screw connection	4	12	2	**8000003444**	1	**8000003593**
3x M20	3x M20								1	**8000003594**
4x M20	4x M20	**8000004164**[2]	1	Screw connection	4	16	2	**8000004142**	1	**8000004229**
4x M20	4x M20			Tension clamp connection	2.5	19	2	**8000004143**	1	**8000004230**

suitable for the enclosures of the respective line
*DU = feed-through terminals, PE = PE terminals

Ex enclosure with an external earthing connection, holes and strip terminals in each row

Klippon® POK 080806

55 mm

Height / Width / Depth	75 / 80 / 55 mm



Accessories

Cable glands	Order No.
VG M16 EXE 5-8 SI7J G4	2722080000
VG M16 EXE 6-10 SI7J G4	2722090000
Stopping plugs	
VP M16 EX SI 7J	2066720000

Empty enclosure with tapped holes

Drill holes side A	Drill holes side B	Order No.
2 x M16x1.5	2 x M16x1.5	8000004160

Note

Note

Terminal block, suitable for empty enclosure

Type	Type of connection	Conductor can be clamped	Rated cross-section	No. of DU*	No. of PE*	Order No.
BK 4/E	Screw connection	Solid / stranded	0.5...4 mm² / 1.5...4 mm²	4	0	8000004365
		Flexible / flexible with wire-end ferrule	0.5...4 mm² / 0.5...4 mm²			
AKZ 4	Screw connection	Solid / stranded	0.5...6 mm² / 1.5...4 mm²	6	2	8000004144
		Flexible / flexible with wire-end ferrule	0.5...4 mm² / 0.5...2.5 mm²			

Note Markers numbered 1-50 (horizontal text) and mounting screws are included in the delivery.
*DU = feed-through terminals, PE = PE terminals

Distribution box with ATEX II 2GD T85°C Ex e II T6

Drill holes side A	Drill holes side B	No. of DU*	No. of PE*	Order No.
2 x M16x1.5	2 x M16x1.5	6	2	8000004223
2 x M16x1.5	2 x M16x1.5	6	2	8000004222

Note Enclosures are delivered in RAL 9011.
*DU = feed-through terminals, PE = PE terminals

Terminal rail / mounting plate set

Product type	Type	Length	Order No.
Rail	TS15 68 Klippon POK1 CSS	68 mm	1928060000

Note

Klippon® POK 081106

56 mm

Height / Width / Depth	75 / 110 / 56 mm



Accessories

Cable glands		Order No.
	VG M20 EXE 7-13 SI7J G4	2722110000
	VG M20 EXE 11-14 SI7J G4	2722120000
Stopping plugs		
	VP M20 EX SI 7J	2066730000
Gauge rings		
	ADAP EX M20-M16	1737560000

Empty enclosure with tapped holes

	Drill holes side A	Drill holes side B	Order No.
	2 x M20x1.5	2 x M20x1.5	8000004161

Note

Note

Terminal block, suitable for empty enclosure

	Type	Type of connection	Conductor can be clamped	Rated cross-section	No. of DU*	No. of PE*	Order No.
	BK 6/E	Screw connection	Solid / stranded	0.5...4 mm² / 1.5...4 mm²	6	0	8000004366
			Flexible / flexible with wire-end ferrule	0.5...4 mm² / 0.5...4 mm²			
	AKZ 4	Screw connection	Solid / stranded	0.5...6 mm² / 1.5...4 mm²	10	2	8000004145
			Flexible / flexible with wire-end ferrule	0.5...4 mm² / 0.5...2.5 mm²			

Note Markers numbered 1-50 (horizontal text) and mounting screws are included in the delivery.
*DU = feed-through terminals, PE = PE terminals

Distribution box with ATEX II 2GD T85°C Ex e II T6

Drill holes side A	Drill holes side B	No. of DU*	No. of PE*	Order No.
2 x M20x1.5	2 x M20x1.5	10	2	8000004225
2 x M20x1.5	2 x M20x1.5	6	0	8000004224

Note Enclosures are delivered in RAL 9011.
*DU = feed-through terminals, PE = PE terminals

Terminal rail / mounting plate set

	Product type	Type	Length	Order No.
	Rail	TS15 98 Klippon POK2 CSS	98 mm	1928070000

Note

Klippon® POK 081606

56 mm

Height / Width / Depth	75 / 160 / 56 mm



Accessories

Cable glands	Order No.
VG M20 EXE 7-13 SI7J G4	2722110000
VG M20 EXE 11-14 SI7J G4	2722120000
Stopping plugs	
VP M20 EX SI 7J	2066730000
Gauge rings	
ADAP EX M20-M16	1737560000

Empty enclosure with tapped holes

Drill holes side A	Drill holes side B	Order No.
4 x M20x1.5	4 x M20x1.5	8000004162

Note

Note

Terminal block, suitable for empty enclosure

Type	Type of connection	Conductor can be clamped	Rated cross-section	No. of DU*	No. of PE*	Order No.
BK 12/E	Screw connection	Solid / stranded	0.5...4 mm² / 1.5...4 mm²	12	0	8000004367
		Flexible / flexible with wire-end ferrule	0.5...4 mm² / 0.5...4 mm²			
AKZ 4	Screw connection	Solid / stranded	0.5...6 mm² / 1.5...4 mm²	18	2	8000004146
		Flexible / flexible with wire-end ferrule	0.5...4 mm² / 0.5...2.5 mm²			

Note Markers numbered 1-50 (horizontal text) and mounting screws are included in the delivery.
*DU = feed-through terminals, PE = PE terminals

Distribution box with ATEX II 2GD T85°C Ex e II T6

Drill holes side A	Drill holes side B	No. of DU*	No. of PE*	Order No.
4 x M20x1.5	4 x M20x1.5	18	2	8000004228
4 x M20x1.5	4 x M20x1.5	12	0	8000004226

Note Enclosures are delivered in RAL 9011.
*DU = feed-through terminals, PE = PE terminals

Terminal rail / mounting plate set

Product type	Type	Length	Order No.
Rail	TS15 147 Klippon POK3 CSS	147 mm	1928080000

Note

Klippon® POK 121209

90 mm

Height / Width / Depth	120 / 122 / 90 mm



Accessories

Cable glands		Order No.
	VG M20 EXE 7-13 SI7J G4	2722110000
	VG M20 EXE 11-14 SI7J G4	2722120000
Stopping plugs		
	VP M20 EX SI 7J	2066730000
Gauge rings		
	ADAP EX M20-M16	1737560000

Empty enclosure with tapped holes

	Drill holes side A	Drill holes side B	Order No.
	3 x M20x1.5	3 x M20x1.5	8000003448

Note

Note

Terminal block, suitable for empty enclosure

	Type	Type of connection	Conductor can be clamped	Rated cross-section	No. of DU*	No. of PE*	Order No.
	WDU 4	Screw connection	Solid/stranded	0.5...6 mm² / 1.5...6 mm²	12	2	8000003444
			Flexible / flexible with wire-end ferrule	0.5...6 mm² / 0.5...4 mm²			

Note

Markers numbered 1-50 (horizontal text) and mounting screws are included in the delivery.
*DU = feed-through terminals, PE = PE terminals

Distribution box with ATEX II 2GD T85°C Ex e II T6

Drill holes side A	Drill holes side B	No. of DU*	No. of PE*	Order No.
3 x M20x1.5	3 x M20x1.5	12	2	8000003593
3 x M20x1.5	3 x M20x1.5	9	2	8000003594

Note

Enclosures are delivered in RAL 9011.
*DU = feed-through terminals, PE = PE terminals

Terminal rail / mounting plate set

	Product type	Type	Length	Order No.
	Rail	TS35 105 Klippon K41/POK4	105 mm	1910070000

Note

Klippon® POK 161609

90 mm

Height / Width / Depth	160 / 160 / 90 mm



Accessories

Cable glands		Order No.
	VG M20 EXE 7-13 SI7J G4	2722110000
	VG M20 EXE 11-14 SI7J G4	2722120000
Stopping plugs		
	VP M20 EX SI 7J	2066730000
Gauge rings		
	ADAP EX M20-M16	1737560000

Empty enclosure with tapped holes

	Drill holes side A	Drill holes side B	Order No.
	4 x M20x1.5	4 x M20x1.5	8000004164

Note

Note

Terminal block, suitable for empty enclosure

	Type	Type of connection	Conductor can be clamped	Rated cross-section	No. of DU*	No. of PE*	Order No.
	ZDK 2.5	Tension-clamp connection	Double-level terminal	0.5...2.5 mm² / ... 0.5...2.5 mm² / 0.5...2.5 mm²	19	2	8000004143
	WDK 4N	Screw connection	Solid/stranded Flexible / flexible with wire-end ferrule	0.5...6 mm² / 1.5...6 mm² 0.5...4 mm² / 0.5...4 mm²	16	2	8000004142

Note

Markers numbered 1-50 (horizontal text) and mounting screws are included in the delivery.
*DU = feed-through terminals, PE = PE terminals

Distribution box with ATEX II 2GD T85°C Ex e II T6

Drill holes side A	Drill holes side B	No. of DU*	No. of PE*	Order No.
4 x M20x1.5	4 x M20x1.5	16	2	8000004229
4 x M20x1.5	4 x M20x1.5	19	2	8000004230

Note

Enclosures are delivered in RAL 9011.
*DU = feed-through terminals, PE = PE terminals

Terminal rail / mounting plate set

	Product type	Type	Length	Order No.
	Rail	TS35/140 Klippon K52 POK51	140 mm	1910100000

Note

Safely control work processes in hazardous areas on site

With certified enclosure solutions with control and display elements

Harsh industrial environments and hazardous areas, such as in the oil and gas industry, place extreme demands on the safety, the robustness and quality of products and devices.

We meet these challenges with the Klippon® Control Station, the addition to our range of customised enclosure solutions. More than 50 years of expertise have made us market leader in this area with global competence centres. The basis of our enclosure solutions is provided by the usual Weidmüller quality and comprehensive approvals for explosion hazard areas. Based on this, our sturdy "on-site control station" is available in two standard sizes and with up to four control and display elements and provides a flexible solution to meet your specific needs.

Order your distributor enclosure as well as control and signaling units from a single source and from one enclosure design – for reliable security and reduced storage costs for maintenance and repair operations.

Your special advantages:
Ideal for urgent service calls
We have prepared modules of the proven Klippon® enclosures POK available for you for further processing. This means we manufacture a control solution suitable for your application at short notice.

Predestined for emergency shutdown applications: Klippon® Control Stations score when it comes to the safe shutdown of plant sections, such as in the process industry

Project solutions from a single source
Obtain command/signaling units and distribution and control boxes as a complete solution – tailored to the individual requirements of your projects in hazardous areas.

Customised assembly
In addition to standard types from stock, you can obtain enclosure solutions from us that are completely assembled and equipped according to customer requirements.

A variety of sizes and materials
Enclosures in stainless steel, aluminium or polyester are available for different environmental conditions. Depending on the size of the enclosure, it provides space for the integration of up to four control and display elements.

International certificates
The Klippon® Control Station is tested and certified among others according to ATEX and IECEx.

Robust solutions for demanding environments

Klippon® Protect provides high-quality polyester enclosures

Our enclosures made of high-quality polyester (Klippon® POK) are the ideal solutions for demanding electrical connectivity applications. They are particularly suitable for applications that demand corrosion resistance, impact resistance and a high protection class. Suitable for use within hazardous environments.

Additional features:

- Extremely robust, weather-proof and impact-resistant up to 7 joules
- Simple fastening of mounting rails
- High ingress protection IP66

Technical data	Polyester enclosures
Material	Glass-fibre reinforced polyester with graphite mixture
Surface finish	Natural, black
Colour	Similar to RAL 9011
IP protection class	IP 54; IP 66
Ambient temperature	-55 °C to 55 °C
Seal material of enclosure	Silicone (VMQ)
Seal material of command and signalling units	EPDM
Flammability rating	-
Impact resistance IK	7 joules in acc. with IEC60079-0 4 joules in acc. with IEC60079-0 with integrated illuminated pushbutton or light module
Cable gland material	Polyamide
Cable gland clamping area min. – max. in mm	
M20	Available on request
M25	6–12 mm
Max. rated cross-section	2.5 mm²
Max. operating voltage	400 V
with integrated illuminated pushbutton or lighting module	250 V
Maximum operating current at 40 °C ambient temperature	
1.5 mm² – T6	10 A
1.5 mm² – T5	16 A
2.5 mm² – T6	16 A
Maximum operating current at 55 °C ambient temperature	
1.5 mm² – T4	16 A
1.5 mm² – T5	10 A
2.5 mm² – T5	16 A
Temperature class	T4, T5, T6
Type of mounting	Wall mounting
Earthing inside	Earth terminal
Lid attachment	Crosshead screws, stainless steel
Lid screw torque	2.5–3.0 Nm
Earthing torque	-
Earthing outside	Available on request
Approvals	IECEXITA14.0013X TUEV14ATEX7606X MARITREG 15.40082.250
Marking	2G Ex e d IIC T* Gb 2G Ex ib d [ia] IIC T* Gb 2D Ex tb IIIC T80/100 °C Db
Mounting feet	9510910000

	Number of built-in components				Emergency stop pushbutton	Key switch	Pushbutton		Illuminated pushbutton		Light module		Dimensions with built-in components HxWxD in mm	Designation	Cable gland	Order number	
	●	●●	●●●	●●●●	red	I – 0 – II	red	green	red	green	red	green					
Polyester	●				1								152x120x128	KLIPPON CS POK 121209-2	VG M25	**1537070000**	
	●							1					152x120x103	KLIPPON CS POK 121209-2	VG M25	**1537080000**	
	●					1							152x120x117	KLIPPON CS POK 121209-2	VG M25	**1537090000**	
	●									1			152x120x105	KLIPPON CS POK 121209-2	VG M25	**1537100000**	
		●					1	1					152x120x103	KLIPPON CS POK 121209-4	VG M25	**1537110000**	
		●						1				1	152x120x112	KLIPPON CS POK 121209-4	VG M25	**1537120000**	
		●			1						1		152x120x128	KLIPPON CS POK 121209-4	VG M25	**1537130000**	
			●				1	1				1	250x120x112	KLIPPON CS POK 122209-2	VG M25	**1537140000**	
			●				1	2					250x120x103	KLIPPON CS POK 122209-2	VG M25	**1537150000**	
			●		1		1	1					250x120x128	KLIPPON CS POK 122209-2	VG M25	**1537170000**	
				●			1	1			1	1	250x120x112	KLIPPON CS POK 122209-4	VG M25	**1537180000**	

	Klippon® CS POK 121209-2	Klippon® CS POK 121209-2

Technical data

Enclosure		
Dimensions with installation (HxBxD)	152 / 120 / 128 mm	152 / 120 / 103 mm
Material	Glass-fibre reinforced polyester with graphite mixture	Glass-fibre reinforced polyester with graphite mixture
General characteristics		
Surface finish / Colour	untreated / graphite black	untreated / graphite black
Protection class	IP54, IP66	IP54, IP66
Ambient temperature	-55 °C...+55 °C	-55 °C...+55 °C
Impact resistance	7 joules in acc. with IEC 60079-0	7 joules in acc. with IEC 60079-0
UL 94 flammability rating	V-0	V-0
Enclosure seal material	Silicone (VMQ)	Silicone (VMQ)
Seal material of operating and display elements	EPDM	EPDM
Type of mounting	Wall mounting	Wall mounting
External earth	Available on request	Available on request
Lid attachment	Crosshead screws, stainless steel	Crosshead screws, stainless steel
Torque for lid screws	2.5 Nm	2.5 Nm
Electrical properties*		
Wire connection cross section, finely stranded, max.	2.5 mm²	2.5 mm²
Operating voltage, max.	400 V	400 V
Temperature class	T4, T5, T6	T4, T5, T6
Enclosure assembly		
1 Position in enclosure	EMERGENCY-STOP pushbutton with yellow, contrasting label	Pushbutton - green
2 Position in enclosure		
3 Position in enclosure		
4 Position in enclosure		
Contact design	2 NC contact, positive opening contacts	1 NC contact, 1 NO contacts
Actuators	EMERGENCY STOP pushbutton	Pushbutton
Actuator colour	red	green
Illumination module colour		
Illuminated button actuator colour		
Cable entries		
Drill holes side B	1 x M25	1 x M25
Cable gland	2721990000 - VG M25 EXE 12-17 CR7J G4	2721990000 - VG M25 EXE 12-17 CR7J G4
Clamping range min. / max.	12 mm / 17 mm	12 mm / 17 mm
Approval and Marking		
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-31	IEC 60079-0, IEC 60079-7, IEC 60079-31
Certificate No. (IECEX)	IECEXITA14.0013X	IECEXITA14.0013X
Certificate No. (ATEX)	TUEV14ATEX7606X	TUEV14ATEX7606X
Certificate No. (EAC)	RUC-DE.BE02.B.00173	RUC-DE.BE02.B.00173
Certificate No. (MARITREG)	15.40082.250	15.40082.250
Marking	II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db	II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
Accessories		
Mounting feet	9510910000 - MF POK BIG	9510910000 - MF POK BIG
Note		

Ordering data

Type	Qty.	Order No.
KLIPPON CS POK 121209-2	1	1537070000

Type	Qty.	Order No.
KLIPPON CS POK 121209-2	1	1537080000

Note		
	*Other temperature classes and connection values on request, or see "Notice to Installer".	*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS POK 121209-2

152 / 120 / 117 mm
Glass-fibre reinforced polyester with graphite mixture
untreated / graphite black
IP54, IP66
-55 °C...+55 °C
7 joules in acc. with IEC 60079-0
V-0
Silicone (VMQ)
EPDM
Wall mounting
Available on request
Crosshead screws, stainless steel
2.5 Nm
2.5 mm²
400 V
T4, T5, T6
Key-operated switch
1 NC contact, 1 NO contacts
Key-operated switch, 3 switching positions, I - 0 - II, (I + II), latching, Key retractable
1 x M25
2721990000 - VG M25 EXE 12-17 CR7J G4
12 mm / 17 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.TB08.B.01838
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
9510910000 - MF POK BIG

Type	Qty.	Order No.
KLIPPON CS POK 121209-2	1	**1537090000**

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS POK 121209-2

152 / 120 / 105 mm
Glass-fibre reinforced polyester with graphite mixture
untreated / graphite black
IP54, IP66
-55 °C...+55 °C
4 joules in acc. with IEC 60079-0
V-0
Silicone (VMQ)
EPDM
Wall mounting
Available on request
Crosshead screws, stainless steel
2.5 Nm
2.5 mm²
250 V
T4, T5, T6
Illuminated pushbutton - green
2 NO contacts
Pushbutton
green
green
1 x M25
2721990000 - VG M25 EXE 12-17 CR7J G4
12 mm / 17 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.BE02.B.00173
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
9510910000 - MF POK BIG

Type	Qty.	Order No.
KLIPPON CS POK 121209-2	1	**1537100000**

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS POK 121209-4

152 / 120 / 103 mm
Glass-fibre reinforced polyester with graphite mixture
untreated / graphite black
IP54, IP66
-55 °C...+55 °C
7 joules in acc. with IEC 60079-0
V-0
Silicone (VMQ)
EPDM
Wall mounting
Available on request
Crosshead screws, stainless steel
2.5 Nm
2.5 mm²
400 V
T4, T5, T6
Pushbutton - red
Pushbutton - green
2 NC contact, 2 NO contacts
Pushbutton
red, green
1 x M25
2721990000 - VG M25 EXE 12-17 CR7J G4
12 mm / 17 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.BE02.B.00173
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
9510910000 - MF POK BIG

Type	Qty.	Order No.
KLIPPON CS POK 121209-4	1	**1537110000**

*Other temperature classes and connection values on request, or see "Notice to Installer".

	Klippon® CS POK 121209-4	Klippon® CS POK 121209-4

Technical data

Enclosure		
Dimensions with installation (HxBxD)	152 / 120 / 112 mm	152 / 120 / 128 mm
Material	Glass-fibre reinforced polyester with graphite mixture	Glass-fibre reinforced polyester with graphite mixture
General characteristics		
Surface finish / Colour	untreated / graphite black	untreated / graphite black
Protection class	IP54, IP66	IP54, IP66
Ambient temperature	-55 °C...+55 °C	-55 °C...+55 °C
Impact resistance	4 joules in acc. with IEC 60079-0	4 joules in acc. with IEC 60079-0
UL 94 flammability rating	V-0	V-0
Enclosure seal material	Silicone (VMQ)	Silicone (VMQ)
Seal material of operating and display elements	EPDM	EPDM
Type of mounting	Wall mounting	Wall mounting
External earth	Available on request	Available on request
Lid attachment	Crosshead screws, stainless steel	Crosshead screws, stainless steel
Torque for lid screws	2.5 Nm	2.5 Nm
Electrical properties*		
Wire connection cross section, finely stranded, max.	2.5 mm²	2.5 mm²
Operating voltage, max.	250 V	250 V
Temperature class	T4, T5, T6	T4, T5, T6
Enclosure assembly		
1 Position in enclosure	Light module - green	Light module - red
2 Position in enclosure	Pushbutton - green	EMERGENCY-STOP pushbutton with yellow, contrasting label
3 Position in enclosure		
4 Position in enclosure		
Contact design	1 NC contact, 1 NO contacts	2 NC contact, positive opening contacts
Actuators	Pushbutton	EMERGENCY STOP pushbutton
Actuator colour	green	red
Illumination module colour	green	red
Illuminated button actuator colour		
Cable entries		
Drill holes side B	1 x M25	1 x M25
Cable gland	2721990000 - VG M25 EXE 12-17 CR7J G4	2721990000 - VG M25 EXE 12-17 CR7J G4
Clamping range min. / max.	12 mm / 17 mm	12 mm / 17 mm
Approval and Marking		
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-31	IEC 60079-0, IEC 60079-7, IEC 60079-31
Certificate No. (IECEX)	IECEXITA14.0013X	IECEXITA14.0013X
Certificate No. (ATEX)	TUEV14ATEX7606X	TUEV14ATEX7606X
Certificate No. (EAC)	RUC-DE.BE02.B.00173	RUC-DE.TB08.B.01838
Certificate No. (MARITREG)	15.40082.250	15.40082.250
Marking	II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db	II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
Accessories		
Mounting feet	9510910000 - MF POK BIG	9510910000 - MF POK BIG
Note		

Ordering data

Type	Qty.	Order No.
KLIPPON CS POK 121209-4	1	1537120000

Type	Qty.	Order No.
KLIPPON CS POK 121209-4	1	1537130000

Note		
	*Other temperature classes and connection values on request, or see "Notice to Installer".	*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS POK 122209-2

250 / 120 / 112 mm
Glass-fibre reinforced polyester with graphite mixture
untreated / graphite black
IP54, IP66
-55 °C...+55 °C
4 joules in acc. with IEC 60079-0
V-0
Silicone (VMQ)
EPDM
Wall mounting
Available on request
Crosshead screws, stainless steel
2.5 Nm
2.5 mm²
250 V
T4, T5, T6
Pushbutton - red
Light module - green
Pushbutton - green
2 NC contact, 2 NO contacts
Pushbutton
red, green
green
1 x M25
2721990000 - VG M25 EXE 12-17 CR7J G4
12 mm / 17 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.BE02.B.00173
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
9510910000 - MF POK BIG

Type	Qty.	Order No.
KLIPPON CS POK 122209-2	1	1537140000

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS POK 122209-2

250 / 120 / 103 mm
Glass-fibre reinforced polyester with graphite mixture
untreated / graphite black
IP54, IP66
-55 °C...+55 °C
7 joules in acc. with IEC 60079-0
V-0
Silicone (VMQ)
EPDM
Wall mounting
Available on request
Crosshead screws, stainless steel
2.5 Nm
2.5 mm²
400 V
T4, T5, T6
Pushbutton - green
Pushbutton - red
Pushbutton - green
3 NC contact, 3 NO contacts
Pushbutton
green, red
1 x M25
2721990000 - VG M25 EXE 12-17 CR7J G4
12 mm / 17 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.TB08.B.01838
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
9510910000 - MF POK BIG

Type	Qty.	Order No.
KLIPPON CS POK 122209-2	1	1537150000

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS POK 122209-2

250 / 120 / 128 mm
Glass-fibre reinforced polyester with graphite mixture
untreated / graphite black
IP54, IP66
-55 °C...+55 °C
7 joules in acc. with IEC 60079-0
V-0
Silicone (VMQ)
EPDM
Wall mounting
Available on request
Crosshead screws, stainless steel
2.5 Nm
2.5 mm²
400 V
T4, T5, T6
Pushbutton - green
Pushbutton - red
EMERGENCY-STOP pushbutton with yellow, contrasting label
2 NO contacts, 2 NC contact, positive opening contacts
Pushbutton, EMERGENCY STOP pushbutton
green, red
1 x M25
2721990000 - VG M25 EXE 12-17 CR7J G4
12 mm / 17 mm
IEC 60079-0, IEC 60079-7, IEC 60079-31
IECEXITA14.0013X
TUEV14ATEX7606X
RUC-DE.BE02.B.00173
15.40082.250
II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
9510910000 - MF POK BIG

Type	Qty.	Order No.
KLIPPON CS POK 122209-2	1	1537170000

*Other temperature classes and connection values on request, or see "Notice to Installer".

Klippon® CS POK 122209-4

Technical data

Enclosure	
Dimensions with installation (HxBxD)	250 / 120 / 112 mm
Material	Glass-fibre reinforced polyester with graphite mixture
General characteristics	
Surface finish / Colour	untreated / graphite black
Protection class	IP54, IP66
Ambient temperature	-55 °C...+55 °C
Impact resistance	4 joules in acc. with IEC 60079-0
UL 94 flammability rating	V-0
Enclosure seal material	Silicone (VMQ)
Seal material of operating and display elements	EPDM
Type of mounting	Wall mounting
External earth	Available on request
Lid attachment	Crosshead screws, stainless steel
Torque for lid screws	2.5 Nm
Electrical properties*	
Wire connection cross section, finely stranded, max.	2.5 mm²
Operating voltage, max.	250 V
Temperature class	T4, T5, T6
Enclosure assembly	
1 Position in enclosure	Light module - red
2 Position in enclosure	Pushbutton - red
3 Position in enclosure	Light module - green
4 Position in enclosure	Pushbutton - green
Contact design	2 NC contact, 2 NO contacts
Actuators	Pushbutton
Actuator colour	green, red
Illumination module colour	red, green
Illuminated button actuator colour	
Cable entries	
Drill holes side B	1 x M25
Cable gland	2721990000 - VG M25 EXE 12-17 CR7J G4
Clamping range min. / max.	12 mm / 17 mm
Approval and Marking	
Standards	IEC 60079-0, IEC 60079-7, IEC 60079-31
Certificate No. (IECEX)	IECEXITA14.0013X
Certificate No. (ATEX)	TUEV14ATEX7606X
Certificate No. (EAC)	RUC-DE.BE02.B.00173
Certificate No. (MARITREG)	15.40082.250
Marking	II 2 G Ex d e IIC T* Gb II 2 D Ex tb IIIC T*°C Db
Accessories	
Mounting feet	9510910000 - MF POK BIG

Note	

Ordering data

Type	Qty.	Order No.
KLIPPON CS POK 122209-4	1	**1537180000**

Note	*Other temperature classes and connection values on request, or see "Notice to Installer".

TBF – Large polyester enclosures

The enclosures in the TBF range are made from sturdy glass-fibre reinforced polyester. They offer a universal solution for protection of components such as controllers, measuring instruments, valves and other devices. Suitable applications include photovoltaics and energy distribution.

Key features of this product range include:
- Available in 9 sizes, with grey or transparent lids
- The lid has nylon screws fitted
- Mounting holes are outside the sealed area
- Thread for fitting to terminal rails and mounting plates
- High Ingress Protection (IP 66 and IP 67)

Weidmüller manufactures and supplies the enclosures to match customer specifications – fully fitted with terminals, electronics and cable glands.

Use our online catalogue to find additional product details, technical information and additional services:
www.weidmueller.com/TBF

Overview of enclosures

Ordering data

Description	Dimensions in mm	Grey lid	Transparent lid
TBF 19/15	186 x 151 x 140	0360100000	0500500000
TBF 30/19	302 x 186 x 175	0360200000	0500600000
TBF 30/30	302 x 302 x 175	0360300000	0500700000
TBF 37/30	372 x 302 x 175	0360400000	0500800000
TBF 49/30	488 x 302 x 175 / 210	9502800000	9502840000
TBF 56/30	558 x 302 x 175 / 210	9502810000	9502850000
TBF 60/30	603 x 302 x 175 / 210	0360500000	0500900000
TBF 60/37	603 x 372 x 175 / 210	9502820000	9502860000
TBF 60/60	603 x 603 x 175 / 210	9502830000	9502870000
Note			

Technical Overview

Features

• Extremely tough and impact resistant thanks to the glass-fibre reinforced polyester
• Extremely weather resistant
• High IP rating
• Approved according to the latest international standards
Note We deliver enclosures through our assembly service which are ready to be connected and suitable for every application.

Technical data

	Grey lid	Transparent lid
Enclosure material	Base and lid made of glass-fibre reinforced polyester (GRP)	Base made of glass-fibre reinforced polyester (GRP) Lid is polycarbonate (PC)
Surface finish	grey, similar to RAL 7035	
IP protection class	IP66 and IP67	IP 66
Installation mounting	4 or 6 M4 clamping screws	4 or 6 M4 clamping screws
Enclosure mounting	4 holes of 7 mm diameter or with external fastening lugs, see accessories	4 holes of 7 mm diameter or with external fastening lugs, see accessories
Lid fixing	4, 6 or 8 captive cross-headed nylon screws	4, 6 or 8 captive cross-headed nylon screws
Impact resistance	IK08 to IEC 62208 IK10 to EN/IEC 62262	IK08 to IEC 62208 IK10 to EN/IEC 62262
Gasket material	Polyurethane	Polyurethane
Temperature range	-50 °C...+130 °C (permanent temperature max. 70°C)	-35 °C...+120 °C (permanent temperature max. 70°C)
Flammability characteristics	UL 94 HB	V2
Toxicity	Free from halogens	Free from halogens
Note	For details of power dissipation, please contact your Weidmüller representative.	

	TBF 19/15	140 mm	TBF 30/19	175 mm
				
Height / Width / Depth	186 / 151 / 140 mm		302 / 186 / 175 mm	

Technical data

Assembly with terminal	vertical	horizontal	vertical	horizontal
2.5 mm²	1x11	1x18	2x22	1x44
4 mm²	1x9	1x15	2x18	1x37
6 mm²	1x7	1x7	2x14	2x14
10 mm²	1x6	1x9	2x11	1x22
16 mm²	1x4	1x6	2x8	1x16
35 mm²	1x3	1x5	2x7	1x14
Guide value for max. number of cable entries	**A / B**	**C / D**	**A / B**	**C / D**
M12	11	11	28	53
M16	6	6	14	30
M20	2	2	11	22
M25	2	2	6	10
M32	1	1	3	5
M40	1	1	3	3
M50			1	3
M63			1	2
M75				
Note				

Ordering data

	Type	Qty.	Order No.	Type	Qty.	Order No.
Enclosure with grey lid	TBF 19/15/14 7035	1	**0360100000**	TBF 30/19/18 7035	1	**0360200000**
Enclosure with transparent lid	TBF 19/15/14 TRSP	1	**0500500000**	TBF 30/19/18 TRSP	1	**0500600000**
Note						

Accessories

	Type	Qty.	Order No.	Type	Qty.	Order No.
Mounting plates and fastening screws						
Steel sheet, zinc plated	MP TBF 19/15	1	**9502720000**	MP TBF 30/19	1	**3018950000**
M4 screw	FKSC M4X6 D8/SW2	100	**1567480000**	FKSC M4X6 D8/SW2	100	**1567480000**
External mounting lug, set of 4						
Polyamide	MF TBF	1	**0360800000**	MF TBF	1	**0360800000**
Earthing stud						
Brass, M6	PEBZ M6 BR SET	1	**1277250000**	PEBZ M6 BR SET	1	**1277250000**
Stainless steel 1.4404, M6	PEBZ M6 S4 SET	1	**1283430000**	PEBZ M6 S4 SET	1	**1283430000**
Brass, M10	PEBZ M10 BR SET	1	**1277220000**	PEBZ M10 BR SET	1	**1277220000**
Stainless steel 1.4404, M10	PEBZ M10 S4 SET	1	**1283440000**	PEBZ M10 S4 SET	1	**1283440000**
Pressure compensation elements						
Polyamide 6, M12	DAE M12 PA LONG	10	**1868570000**	DAE M12 PA LONG	10	**1868570000**
Stainless steel 1.4305, M12	DAE M12 SS	10	**1868550000**	DAE M12 SS	10	**1868550000**
Note						

	TBF 30/30	175 mm	TBF 37/30	175 mm
				
Height / Width / Depth	302 / 302 / 175 mm		372 / 302 / 175 mm	

Technical data

Assembly with terminal	vertical	horizontal	vertical	horizontal
2.5 mm²	2x44	1x44	2x57	2x44
4 mm²	2x37	1x37	2x48	2x37
6 mm²	2x28	2x28	2x36	2x36
10 mm²	2x22	1x22	2x29	2x22
16 mm²	2x16	1x16	2x21	2x16
35 mm²	2x14	1x14	2x18	2x14
Guide value for max. number of cable entries	**A / B**	**C / D**	**A / B**	**C / D**
M12	44	44	44	56
M16	24	24	24	30
M20	20	20	20	27
M25	10	10	10	12
M32	4	4	4	5
M40	3	3	3	4
M50	3	3	3	4
M63	2	2	2	3
M75				
Note				

Ordering data

	Type	Qty.	Order No.	Type	Qty.	Order No.
Enclosure with grey lid	TBF 30/30/18 7035	1	**0360300000**	TBF 37/30/18 7035	1	**0360400000**
Enclosure with transparent lid	TBF 30/30/18 TRSP	1	**0500700000**	TBF 37/30/18 TRSP	1	**0500800000**
Note						

Accessories

Mounting plates and fastening screws	Type	Qty.	Order No.	Type	Qty.	Order No.
Steel sheet, zinc plated	MP TBF 30/30	1	**9502730000**	MP TBF 37/30	1	**9502740000**
M4 screw	FKSC M4X6 D8/SW2	100	**1567480000**	FKSC M4X6 D8/SW2	100	**1567480000**
External mounting lug, set of 4						
Polyamide	MF TBF	1	**0360800000**	MF TBF	1	**0360800000**
Earthing stud						
Brass, M6	PEBZ M6 BR SET	1	**1277250000**	PEBZ M6 BR SET	1	**1277250000**
Stainless steel 1.4404, M6	PEBZ M6 S4 SET	1	**1283430000**	PEBZ M6 S4 SET	1	**1283430000**
Brass, M10	PEBZ M10 BR SET	1	**1277220000**	PEBZ M10 BR SET	1	**1277220000**
Stainless steel 1.4404, M10	PEBZ M10 S4 SET	1	**1283440000**	PEBZ M10 S4 SET	1	**1283440000**
Pressure compensation elements						
Polyamide 6, M12	DAE M12 PA LONG	10	**1868570000**	DAE M12 PA LONG	10	**1868570000**
Stainless steel 1.4305, M12	DAE M12 SS	10	**1868550000**	DAE M12 SS	10	**1868550000**

Note

	TBF 49/30	175 mm	TBF 56/30	175 mm
				
Height / Width / Depth	488 / 302 / 175 mm		558 / 302 / 175 mm	

Technical data

Assembly with terminal	vertical	horizontal	vertical	horizontal
2.5 mm²	2x80	3x44	2x94	4x44
4 mm²	2x67	3x37	2x79	4x37
6 mm²	2x51	2x51	2x59	2x59
10 mm²	2x41	3x22	2x48	4x22
16 mm²	2x29	3x16	2x34	4x16
35 mm²	2x25	3x14	2x30	4x14
Guide value for max. number of cable entries	**A / B**	**C / D**	**A / B**	**C / D**
M12	44	42	44	80
M16	24	42	24	46
M20	20	36	20	40
M25	10	18	10	18
M32	4	7	4	8
M40	3	5	3	6
M50	3	5	3	4
M63	2	4	2	4
M75				
Note				

Ordering data

	Type	Qty.	Order No.	Type	Qty.	Order No.
Enclosure with grey lid	TBF 49/30/18 7035	1	**9502800000**	TBF 56/30/18 7035	1	**9502810000**
Enclosure with transparent lid	TBF 49/30/21 TRSP	1	**9502840000**	TBF 56/30/21 TRSP	1	**9502850000**
Note	Grey lid: 130 mm internal height, 175 mm total height Transparent lid: 160 mm internal height, 210 mm total height			Grey lid: 130 mm internal height, 175 mm total height Transparent lid: 160 mm internal height, 210 mm total height		

Accessories

	Type	Qty.	Order No.	Type	Qty.	Order No.
Mounting plates and fastening screws						
Steel sheet, zinc plated	MP TBF 49/30	1	**9500960000**	MP TBF 56/30	1	**9500950000**
M4 screw	FKSC M4X6 D8/SW2	100	**1567480000**	FKSC M4X6 D8/SW2	100	**1567480000**
External mounting lug, set of 4						
Polyamide	MF TBF	1	**0360800000**	MF TBF	1	**0360800000**
Earthing stud						
Brass, M6	PEBZ M6 BR SET	1	**1277250000**	PEBZ M6 BR SET	1	**1277250000**
Stainless steel 1.4404, M6	PEBZ M6 S4 SET	1	**1283430000**	PEBZ M6 S4 SET	1	**1283430000**
Brass, M10	PEBZ M10 BR SET	1	**1277220000**	PEBZ M10 BR SET	1	**1277220000**
Stainless steel 1.4404, M10	PEBZ M10 S4 SET	1	**1283440000**	PEBZ M10 S4 SET	1	**1283440000**
Pressure compensation elements						
Polyamide 6, M12	DAE M12 PA LONG	10	**1868570000**	DAE M12 PA LONG	10	**1868570000**
Stainless steel 1.4305, M12	DAE M12 SS	10	**1868550000**	DAE M12 SS	10	**1868550000**
Note						

TBF 60/30 — 175 mm



Height / Width / Depth	603 / 302 / 175 mm

Technical data

Assembly with terminal	vertical	horizontal
2.5 mm²	5x44	1x101
4 mm²	5x37	1x85
6 mm²	5x28	5x28
10 mm²	5x22	1x51
16 mm²	5x16	1x37
35 mm²	5x14	1x32
Guide value for max. number of cable entries	**A / B**	**C / D**
M12	44	88
M16	24	48
M20	20	40
M25	10	20
M32	4	8
M40	3	6
M50	3	6
M63	2	4
M75		

Note

Ordering data

	Type	Qty.	Order No.
Enclosure with grey lid	TBF 60/30/18 7035	1	**0360500000**
Enclosure with transparent lid	TBF 60/30/21 TRSP	1	**0500900000**

Note

Grey lid: 130 mm internal height, 175 mm total height
Transparent lid: 160 mm internal height, 210 mm total height

Accessories

Mounting plates and fastening screws	Type	Qty.	Order No.
Steel sheet, zinc plated	MP TBF 60/30	1	**9502750000**
M4 screw	FKSC M4X6 D8/SW2	100	**1567480000**
External mounting lug, set of 4			
Polyamide	MF TBF	1	**0360800000**
Earthing stud			
Brass, M6	PEBZ M6 BR SET	1	**1277250000**
Stainless steel 1.4404, M6	PEBZ M6 S4 SET	1	**1283430000**
Brass, M10	PEBZ M10 BR SET	1	**1277220000**
Stainless steel 1.4404, M10	PEBZ M10 S4 SET	1	**1283440000**
Pressure compensation elements			
Polyamide 6, M12	DAE M12 PA LONG	10	**1868570000**
Stainless steel 1.4305, M12	DAE M12 SS	10	**1868550000**

Note

	TBF 60/37	175 mm	TBF 60/60	175 mm
				
Height / Width / Depth	603 / 372 / 175 mm		603 / 605 / 175 mm	

Technical data

Assembly with terminal	vertical	horizontal	vertical	horizontal
2.5 mm²	5x57	2x101	5x101	4x101
4 mm²	5x48	2x85	5x85	4x85
6 mm²	5x36	5x36	5x64	5x64
10 mm²	5x29	2x51	5x51	4x51
16 mm²	5x21	2x37	5x37	4x37
35 mm²	5x18	2x32	5x32	4x32
Guide value for max. number of cable entries	**A / B**	**C / D**	**A / B**	**C / D**
M12	52	88	88	88
M16	30	48	48	48
M20	26	40	40	40
M25	12	20	20	20
M32	5	8	8	8
M40	4	6	6	6
M50	4	6	6	6
M63	3	4	4	4
M75				
Note				

Ordering data

	Type	Qty.	Order No.	Type	Qty.	Order No.
Enclosure with grey lid	TBF 60/37/18 7035	1	**9502820000**	TBF 60/60/18 7035	1	**9502830000**
Enclosure with transparent lid	TBF 60/37/21 TRSP	1	**9502860000**	TBF 60/60/21 TRSP	1	**9502870000**
Note	Grey lid: 130 mm internal height, 175 mm total height Transparent lid: 160 mm internal height, 210 mm total height			Grey lid: 130 mm internal height, 175 mm total height Transparent lid: 160 mm internal height, 210 mm total height		

Accessories

	Type	Qty.	Order No.	Type	Qty.	Order No.
Mounting plates and fastening screws						
Steel sheet, zinc plated	MP TBF 60/37	1	**9502910000**	MP TBF 60/60	1	**9502920000**
M4 screw	FKSC M4X6 D8/SW2	100	**1567480000**	FKSC M4X6 D8/SW2	100	**1567480000**
External mounting lug, set of 4						
Polyamide	MF TBF	1	**0360800000**	MF TBF	1	**0360800000**
Earthing stud						
Brass, M6	PEBZ M6 BR SET	1	**1277250000**	PEBZ M6 BR SET	1	**1277250000**
Stainless steel 1.4404, M6	PEBZ M6 S4 SET	1	**1283430000**	PEBZ M6 S4 SET	1	**1283430000**
Brass, M10	PEBZ M10 BR SET	1	**1277220000**	PEBZ M10 BR SET	1	**1277220000**
Stainless steel 1.4404, M10	PEBZ M10 S4 SET	1	**1283440000**	PEBZ M10 S4 SET	1	**1283440000**
Pressure compensation elements						
Polyamide 6, M12	DAE M12 PA LONG	10	**1868570000**	DAE M12 PA LONG	10	**1868570000**
Stainless steel 1.4305, M12	DAE M12 SS	10	**1868550000**	DAE M12 SS	10	**1868550000**
Note						

MPC – Small polycarbonate enclosures

The polycarbonate enclosures of the MPC range are ideal for enclosing electrical, electro-mechanical and pneumatic devices as well as PCBs. The enclosures are used in situations with extreme mechanical and chemical conditions.

The characteristics of the enclosures are:
- Available in 17 sizes, with grey or transparent lids
- Lid fixing screws equipped with sealing holes
- Fixing holes outside the sealed area
- Thread for fitting to terminal rails, mounting plates and PCBs

Weidmüller manufactures and supplies the enclosures to match customer specifications – fully fitted with terminals, electronics and cable glands.

Use our online catalogue to find additional product details, technical information and additional services:
www.weidmueller.com/MPC

Overview of enclosures

Ordering data

Description	Dimensions in mm	Grey lid	Transparent lid
MPC 07/12/07	75 x 125 x 75	9535170000	9535180000
MPC 07/12/10	75 x 125 x 100	9535190000	9535200000
MPC 07/12/12	75 x 125 x 120	9535210000	9535220000
MPC 12/12/07	120 x 120 x 75	9535230000	9535240000
MPC 12/12/10	120 x 120 x 100	9535250000	9535260000
MPC 12/12/12	120 x 120 x 120	9535270000	9535280000
MPC 12/17/07	120 x 175 x 75	9535290000	9535300000
MPC 12/17/10	120 x 175 x 100	9535310000	9535320000
MPC 12/17/12	120 x 175 x 120	9535330000	9535340000
MPC 12/17/15	120 x 175 x 150	9535350000	9535360000
MPC 17/17/07	175 x 175 x 75	9535370000	9535380000
MPC 17/17/10	175 x 175 x 100	9535390000	9535400000
MPC 17/17/12	175 x 175 x 120	9535410000	
MPC 17/17/15	175 x 175 x 150	9535430000	9535440000
MPC 17/25/07	175 x 250 x 75	9535450000	
MPC 17/25/10	175 x 250 x 100	9535470000	9535480000
MPC 17/25/15	175 x 250 x150	9535490000	9535500000
Note			

Technical Overview

Features

• High thermal stability thanks to the polycarbonate
• Extremely tough and impact resistant thanks to the high fibre-glass content.
• Good IP rating, due to use of polyurethane (PUR) gasket material
• Approved according to the latest international standards
Note We deliver enclosures through our assembly service which are ready to be connected and suitable for every application.

Technical data

	Grey lid	Transparent lid
Enclosure material	Base and lid made of glass-fibre reinforced polycarbonate	Base made of glass-fibre reinforced polycarbonate, ABS lid
Cover	Grey	Transparent
Surface finish	Grey, similar to RAL 7035	Grey, similar to RAL 7035
IP protection class	IP 66, IP 67	IP 66, IP 67
Installation mounting	Self-tapping screws	Self-tapping screws
Enclosure mounting	4 holes (4.5 mm diameter) or external mounting brackets (optional)	4 holes (4.5 mm diameter) or external mounting brackets (optional)
Lid fixing	4 cross-head screws (polyamide)	4 cross-head screws (polyamide)
Gasket material	Polyurethane foam	Polyurethane foam
Temperature range	-50 °C...+100 °C	-40 °C...+60 °C
Impact resistance	IK 08	IK 06
Note	For details of power dissipation, please contact your Weidmüller representative.	

	MPC 07/12/07	75 mm	MPC 07/12/12	125 mm
				
Height / Width / Depth	75 / 125 / 75 mm		75 / 125 / 125 mm	

Technical data

Assembly with terminal	vertical	horizontal	vertical	horizontal
2.5 mm²	1x13	1x13	1x13	1x13
4 mm²	1x11	1x11	1x11	1x11
6 mm²	1x8	1x8	1x8	1x8
10 mm²	1x6	1x6	1x6	1x6
16 mm²			1x5	1x1
35 mm²			1x4	1x1
Guide value for max. number of cable entries	**A / B**	**C / D**	**A / B**	**C / D**
M12	1	4	1	4
M16	1	3	1	3
M20	1	3	1	3
M25				
M32				
M40				
M50				
M63				
M75				
Note				

Ordering data

	Type	Qty.	Order No.	Type	Qty.	Order No.
Enclosure with grey lid	MPC 07/12/07 7035	1	9535170000	MPC 07/12/12 7035	1	9535210000
Enclosure with transparent lid	MPC 07/12/07 TRSP	1	9535180000	MPC 07/12/12 TRSP	1	9535220000
Note						

Accessories

	Type	Qty.	Order No.	Type	Qty.	Order No.
Mounting plates and fastening screws						
Steel sheet, zinc plated	MP MPC 07/12	10	9535540000	MP MPC 07/12	10	9535540000
M4 screw	FKSC M4X6 D8/SW2	100	1567480000	FKSC M4X6 D8/SW2	100	1567480000
Mounting rails, TS15x5						
Vertical	TS15X5 ST MPC1217 VER	20	8000037598	TS15X5 MPC1217 VER	20	8000037598
Horizontally	TS15X5 ST MPC0712 VER	20	8000037599	TS15X5 MPC0712 VER	20	8000037599
Mounting rails, TS35x7.5						
Horizontally	TS 35x105_MPC_12	20	8000037603	TS 35x105_MPC_12	20	8000037603
Vertical						
External mounting lug, set of 4						
	MF MPC	1	9535600000	MF MPC	1	9535600000
Hinge, set of 2						
	HG MPC	1	9535590000	HG MPC	1	9535590000
Earthing stud						
Brass, M6	PEBZ M6 BR SET	1	1277250000	PEBZ M6 BR SET	1	1277250000
Stainless steel 1.4404, M6	PEBZ M6 S4 SET	1	1283430000	PEBZ M6 S4 SET	1	1283430000
Brass, M10	PEBZ M10 BR SET	1	1277220000	PEBZ M10 BR SET	1	1277220000
Stainless steel 1.4404, M10	PEBZ M10 S4 SET	1	1283440000	PEBZ M10 S4 SET	1	1283440000
Pressure compensation elements						
Polyamide 6, M12	DAE M12 PA LONG	10	1868570000	DAE M12 PA LONG	10	1868570000
Stainless steel 1.4305, M12	DAE M12 SS	10	1868550000	DAE M12 SS	10	1868550000
Note						

	MPC 12/12/07	75 mm	MPC 12/17/07	75 mm
				
Height / Width / Depth	125 / 125 / 75 mm		125 / 175 / 75 mm	

Technical data

Assembly with terminal	vertical	horizontal	vertical	horizontal
2.5 mm²	1x13	1x13	1x22	1x22
4 mm²	1x11	1x11	1x19	1x19
6 mm²	1x8	1x8	1x14	1x14
10 mm²	1x6	1x6	1x11	1x11
16 mm²				
35 mm²				
Guide value for max. number of cable entries	**A / B**	**C / D**	**A / B**	**C / D**
M12	4	4	4	6
M16	3	3	3	4
M20	3		3	4
M25				
M32				
M40				
M50				
M63				
M75				
Note				

Ordering data

	Type	Qty.	Order No.	Type	Qty.	Order No.
Enclosure with grey lid	MPC 12/12/07 7035	1	9535230000	MPC 12/17/07 7035	1	9535290000
Enclosure with transparent lid	MPC 12/12/07 TRSP	1	9535240000	MPC 12/17/07 TRSP	1	9535300000
Note						

Accessories

Mounting plates and fastening screws						
Steel sheet, zinc plated	MP MPC 12/12	10	9535550000	MP MPC 12/17	1	9535560000
M4 screw	FKSC M4X6 D8/SW2	100	1567480000	FKSC M4X6 D8/SW2	100	1567480000
Mounting rails, TS15x5						
Vertical	TS15X5 ST MPC1217 VER	20	8000037598			
Horizontally						
Mounting rails, TS35x7.5						
Horizontally	TS 35x105_MPC_12	20	8000037603	TS 35x105_MPC_12	20	8000037603
Vertical	TS35 MPC 1717 VER	20	8000037605	TS35 MPC 1717 VER	20	8000037605
External mounting lug, set of 4						
	MF MPC	1	9535600000	MF MPC	1	9535600000
Hinge, set of 2						
	HG MPC	1	9535590000	HG MPC	1	9535590000
Earthing stud						
Brass, M6	PEBZ M6 BR SET	1	1277250000	PEBZ M6 BR SET	1	1277250000
Stainless steel 1.4404, M6	PEBZ M6 S4 SET	1	1283430000	PEBZ M6 S4 SET	1	1283430000
Brass, M10	PEBZ M10 BR SET	1	1277220000	PEBZ M10 BR SET	1	1277220000
Stainless steel 1.4404, M10	PEBZ M10 S4 SET	1	1283440000	PEBZ M10 S4 SET	1	1283440000
Pressure compensation elements						
Polyamide 6, M12	DAE M12 PA LONG	10	1868570000	DAE M12 PA LONG	10	1868570000
Stainless steel 1.4305, M12	DAE M12 SS	10	1868550000	DAE M12 SS	10	1868550000
Note						

	MPC 12/17/10	100 mm	MPC 12/17/12	125 mm
				
Height / Width / Depth	125 / 175 / 100 mm		125 / 175 / 125 mm	

Technical data

Assembly with terminal	vertical	horizontal	vertical	horizontal
2.5 mm²	1x22	1x22	1x13	1x22
4 mm²	1x19	1x19	1x11	1x19
6 mm²	1x14	1x14	1x8	1x8
10 mm²	1x11	1x11	1x6	1x11
16 mm²	1x9	1x5	1x5	1x5
35 mm²	1x7	1x4	1x4	1x4
Guide value for max. number of cable entries	**A / B**	**C / D**	**A / B**	**C / D**
M12	4	6	4	6
M16	3	4	3	4
M20	3	4	3	4
M25				
M32				
M40				
M50				
M63				
M75				
Note				

Ordering data

	Type	Qty.	Order No.	Type	Qty.	Order No.
Enclosure with grey lid	MPC 12/17/10 7035	1	9535310000	MPC 12/17/12 7035	1	9535330000
Enclosure with transparent lid	MPC 12/17/10 TRSP	1	9535320000	MPC 12/17/12 TRSP	1	9535340000
Note						

Accessories

	Type	Qty.	Order No.	Type	Qty.	Order No.
Mounting plates and fastening screws						
Steel sheet, zinc plated	MP MPC 12/17	1	9535560000	MP MPC 12/17	1	9535560000
M4 screw	FKSC M4X6 D8/SW2	100	1567480000	FKSC M4X6 D8/SW2	100	1567480000
Mounting rails, TS15x5						
Vertical	TS15X5 ST MPC1217 VER	20	8000037598	TS15X5 MPC1217 VER	20	8000037598
Horizontally						
Mounting rails, TS35x7.5						
Horizontally						
Vertical	TS35 MPC 1717 VER	20	8000037605	TS35 MPC 1717 VER	20	8000037605
External mounting lug, set of 4						
	MF MPC	1	9535600000	MF MPC	1	9535600000
Hinge, set of 2						
	HG MPC	1	9535590000	HG MPC	1	9535590000
Earthing stud						
Brass, M6	PEBZ M6 BR SET	1	1277250000	PEBZ M6 BR SET	1	1277250000
Stainless steel 1.4404, M6	PEBZ M6 S4 SET	1	1283430000	PEBZ M6 S4 SET	1	1283430000
Brass, M10	PEBZ M10 BR SET	1	1277220000	PEBZ M10 BR SET	1	1277220000
Stainless steel 1.4404, M10	PEBZ M10 S4 SET	1	1283440000	PEBZ M10 S4 SET	1	1283440000
Pressure compensation elements						
Polyamide 6, M12	DAE M12 PA LONG	10	1868570000	DAE M12 PA LONG	10	1868570000
Stainless steel 1.4305, M12	DAE M12 SS	10	1868550000	DAE M12 SS	10	1868550000
Note						

MPC 17/17/07 — 75 mm



Height / Width / Depth	175 / 175 / 75 mm

Technical data

Assembly with terminal	vertical	horizontal
2.5 mm²	1x22	1x22
4 mm²	1x19	1x19
6 mm²	1x14	1x14
10 mm²	1x11	1x11
16 mm²		
35 mm²		

Guide value for max. number of cable entries	A / B	C / D
M12	6	6
M16	4	4
M20	4	
M25		
M32		
M40		
M50		
M63		
M75		

Note

Ordering data

	Type	Qty.	Order No.
Enclosure with grey lid	MPC 17/17/07 7035	1	9535370000
Enclosure with transparent lid	MPC 17/17/07 TRSP	1	9535380000

Note

Accessories

	Type	Qty.	Order No.
Mounting plates and fastening screws			
Steel sheet, zinc plated	MP MPC 17/17	1	9535570000
M4 screw	FKSC M4X6 D8/SW2	100	1567480000
Mounting rails, TS15x5			
Vertical			
Horizontally			
Mounting rails, TS35x7.5			
Horizontally	TS 35x105_MPC_12	20	8000037603
Vertical	TS35 MPC 1717 VER	20	8000037605
External mounting lug, set of 4			
	MF MPC	1	9535600000
Hinge, set of 2			
	HG MPC	1	9535590000
Earthing stud			
Brass, M6	PEBZ M6 BR SET	1	1277250000
Stainless steel 1.4404, M6	PEBZ M6 S4 SET	1	1283430000
Brass, M10	PEBZ M10 BR SET	1	1277220000
Stainless steel 1.4404, M10	PEBZ M10 S4 SET	1	1283440000
Pressure compensation elements			
Polyamide 6, M12	DAE M12 PA LONG	10	1868570000
Stainless steel 1.4305, M12	DAE M12 SS	10	1868550000

Note

	MPC 17/17/15	150 mm	MPC 17/25/07	75 mm
				
Height / Width / Depth	175 / 175 / 150 mm		250 / 175 / 75 mm	

Technical data

Assembly with terminal	vertical	horizontal	vertical	horizontal
2.5 mm²	1x22	1x22		
4 mm²	1x19	1x19		
6 mm²	1x14	1x14		
10 mm²	1x11	1x11		
16 mm²	1x9	1x9		
35 mm²	1x7	1x7		
Guide value for max. number of cable entries	**A / B**	**C / D**	**A / B**	**C / D**
M12	6	6		
M16	4	4		
M20	4			
M25				
M32				
M40				
M50				
M63				
M75				
Note				

Ordering data

	Type	Qty.	Order No.	Type	Qty.	Order No.
Enclosure with grey lid	MPC 17/17/15 7035	1	**9535430000**	MPC 17/25/07 7035	1	**9535450000**
Enclosure with transparent lid	MPC 17/17/15 TRSP	4	**9535440000**			
Note						

Accessories

	Type	Qty.	Order No.	Type	Qty.	Order No.
Mounting plates and fastening screws						
Steel sheet, zinc plated	MP MPC 17/17	1	**9535570000**	MP MPC 17/25	1	**9535580000**
M4 screw	FKSC M4X6 D8/SW2	100	**1567480000**	FKSC M4X6 D8/SW2	100	**1567480000**
Mounting rails, TS15x5						
Vertical						
Horizontally						
Mounting rails, TS35x7.5						
Horizontally				TS35X7.5 MPC1725 HOR	20	**8000037601**
Vertical	TS35X7.5 ST MPC1725 VER	20	**8000037600**	TS35X7.5 MPC1725 VER	20	**8000037600**
External mounting lug, set of 4						
	MF MPC	1	**9535600000**	MF MPC	1	**9535600000**
Hinge, set of 2						
	HG MPC	1	**9535590000**	HG MPC	1	**9535590000**
Earthing stud						
Brass, M6	PEBZ M6 BR SET	1	**1277250000**	PEBZ M6 BR SET	1	**1277250000**
Stainless steel 1.4404, M6	PEBZ M6 S4 SET	1	**1283430000**	PEBZ M6 S4 SET	1	**1283430000**
Brass, M10	PEBZ M10 BR SET	1	**1277220000**	PEBZ M10 BR SET	1	**1277220000**
Stainless steel 1.4404, M10	PEBZ M10 S4 SET	1	**1283440000**	PEBZ M10 S4 SET	1	**1283440000**
Pressure compensation elements						
Polyamide 6, M12	DAE M12 PA LONG	10	**1868570000**	DAE M12 PA LONG	10	**1868570000**
Stainless steel 1.4305, M12	DAE M12 SS	10	**1868550000**	DAE M12 SS	10	**1868550000**
Note						

	MPC 17/25/10	100 mm	MPC 17/25/15	150 mm
				
Height / Width / Depth	175 / 250 / 100 mm		250 / 175 / 150 mm	

Technical data

Assembly with terminal	vertical	horizontal	vertical	horizontal
2.5 mm²	1x37	1x37		
4 mm²	1x31	1x31		
6 mm²	1x23	1x23		
10 mm²	1x19	1x19		
16 mm²	1x15	1x9		
35 mm²	1x11	1x7		
Guide value for max. number of cable entries	**A / B**	**C / D**	**A / B**	**C / D**
M12	6	9	1	9
M16	4	7	1	7
M20	4	6	1	6
M25				
M32				
M40				
M50				
M63				
M75				
Note				

Ordering data

	Type	Qty.	Order No.	Type	Qty.	Order No.
Enclosure with grey lid	MPC 17/25/10 7035	1	9535470000	MPC 17/25/15 7035	1	9535490000
Enclosure with transparent lid	MPC 17/25/10 TRSP	1	9535480000	MPC 17/25/15 TRSP	1	9535500000
Note						

Accessories

Mounting plates and fastening screws	Type	Qty.	Order No.	Type	Qty.	Order No.
Steel sheet, zinc plated	MP MPC 17/25	1	9535580000	MP MPC 17/25	1	9535580000
M4 screw	FKSC M4X6 D8/SW2	100	1567480000	FKSC M4X6 D8/SW2	100	1567480000
Mounting rails, TS15x5						
Vertical						
Horizontally						
Mounting rails, TS35x7.5						
Horizontally	TS35X7.5 ST MPC1725 HOR	20	8000037601	TS35X7.5 MPC1725 HOR	20	8000037601
Vertical	TS35X7.5 ST MPC1725 VER	20	8000037600	TS35X7.5 MPC1725 VER	20	8000037600
External mounting lug, set of 4						
	MF MPC	1	9535600000	MF MPC	1	9535600000
Hinge, set of 2						
	HG MPC	1	9535590000	HG MPC	1	9535590000
Earthing stud						
Brass, M6	PEBZ M6 BR SET	1	1277250000	PEBZ M6 BR SET	1	1277250000
Stainless steel 1.4404, M6	PEBZ M6 S4 SET	1	1283430000	PEBZ M6 S4 SET	1	1283430000
Brass, M10	PEBZ M10 BR SET	1	1277220000	PEBZ M10 BR SET	1	1277220000
Stainless steel 1.4404, M10	PEBZ M10 S4 SET	1	1283440000	PEBZ M10 S4 SET	1	1283440000
Pressure compensation elements						
Polyamide 6, M12	DAE M12 PA LONG	10	1868570000	DAE M12 PA LONG	10	1868570000
Stainless steel 1.4305, M12	DAE M12 SS	10	1868550000	DAE M12 SS	10	1868550000
Note						

FPC – Medium-sized polycarbonate enclosures

The FPC enclosure range is the next generation of the MPC range. The enclosures have the same technical characteristics and are ideal for enclosing electrical, electro-mechanical and pneumatic devices and PCBs. The enclosures are used in situations where extreme mechanical and chemical conditions exist.

The characteristics of the enclosures are:
- Available in 6 sizes, with grey or transparent lids
- Lid fixing screws equipped with sealing holes
- Fixing holes outside the sealed area
- Thread for fitting to terminal rails, mounting plates and PCBs

Weidmüller manufactures and supplies the enclosures to match customer specifications – fully fitted with terminals, electronics and cable glands.

Use our online catalogue to find additional product details, technical information and additional services:
www.weidmueller.com/FPC

Overview of enclosures

Ordering data

Description	Dimensions in mm	Grey lid	Transparent lid
FPC 20/20/13	200 x 200 x 132	**9535690000**	**9535680000**
FPC 20/30/13	200 x 300 x 132	**9535710000**	**9535700000**
FPC 20/40/13	200 x 400 x 132	**9535730000**	**9535720000**
FPC 30/30/13	300 x 300 x 132	**9535750000**	**9535740000**
FPC 30/40/13	300 x 400 x 132	**9535770000**	**9535760000**
FPC 40/60/13	400 x 600 x 132	**9535810000**	**9535820000**
Note			

Technical data

	Grey lid	Transparent lid
Enclosure material	Base and lid made of glass-fibre reinforced polycarbonate	Base made of glass-fibre reinforced polycarbonate, ABS lid
Cover	Grey	Transparent
Surface finish	Grey, similar to RAL 7035	Grey, similar to RAL 7035
IP protection class	IP 66, IP 67	IP 66, IP 67
Installation mounting	Self-tapping screws	Self-tapping screws
Enclosure mounting	4 holes (7.5 mm diameter) or external mounting brackets (optional)	4 holes (7.5 mm diameter) or external mounting brackets (optional)
Lid fixing	4 or 6 cross-head screws (polyamide)	4 or 6 cross-head screws (polyamide)
Gasket material	Polyurethane foam	Polyurethane foam
Temperature range	-50 °C...+100 °C	-40 °C...+60 °C
Impact resistance	IK 08	IK 06
Note	For details of power dissipation, please contact your Weidmüller representative.	

	FPC 20/20/13	132 mm	FPC 20/30/13	132 mm
				
Height / Width / Depth	200 / 200 / 132 mm		200 / 300 / 132 mm	

Technical data

Assembly with terminal	vertical	horizontal	vertical	horizontal
2.5 mm²	1x17	1x17	2x20	1x40
4 mm²	1x14	1x14	2x17	1x33
6 mm²	1x10	1x10	2x13	2x13
10 mm²	1x8	1x8	2x10	1x20
16 mm²	1x7	1x7	2x8	1x17
35 mm²	1x5	1x5	2x6	1x12
Guide value for max. number of cable entries	**A / B**	**C / D**	**A / B**	**C / D**
M12	20	20	38	20
M16	11	11	21	11
M20	6	6	12	6
M25	4	4	8	4
M32	2	2	3	2
M40	1	1	3	1
M50	1	1	2	1
M63	1	1	2	1
M75				
Note				

Ordering data

	Type	Qty.	Order No.	Type	Qty.	Order No.
Enclosure with grey lid	FPC 20/20/13 7035	1	9535690000	FPC 20/30/13 7035	1	9535710000
Enclosure with transparent lid	FPC 20/20/13 TRSP	1	9535680000	FPC 20/30/13 TRSP	1	9535700000
Note						

Accessories

Mounting plates and fastening screws	Type	Qty.	Order No.	Type	Qty.	Order No.
Steel sheet, zinc plated	MP FPC 20/20	1	9535920000	MP FPC 20/30	1	9535930000
M4 screw	FKSC M4X6 D8/SW2	100	1567480000	FKSC M4X6 D8/SW2	100	1567480000
Mounting rails, TS15x5						
Vertical	TS15X5 ST FPC 20 VER	20	8000037604	TS15X5 FPC 20 VER	20	8000037604
Mounting rails, TS35x7.5						
Horizontally	TS35X7.5 ST FPC 20 HOR	20	8000037557	TS35X7.5 FPC 30 HOR	20	8000037559
Vertical	TS35X7.5 ST FPC 20 VER	20	8000037558	TS35X7.5 FPC 20 VER	20	8000037558
External mounting lug, set of 4						
	MF FPC	1	9536040000	MF FPC	1	9536040000
Hinge, set of 2						
	HG FPC	1	9535990000	HG FPC	1	9535990000
Earthing stud						
Brass, M6	PEBZ M6 BR SET	1	1277250000	PEBZ M6 BR SET	1	1277250000
Stainless steel 1.4404, M6	PEBZ M6 S4 SET	1	1283430000	PEBZ M6 S4 SET	1	1283430000
Brass, M10	PEBZ M10 BR SET	1	1277220000	PEBZ M10 BR SET	1	1277220000
Stainless steel 1.4404, M10	PEBZ M10 S4 SET	1	1283440000	PEBZ M10 S4 SET	1	1283440000
Pressure compensation elements						
Polyamide 6, M12	DAE M12 PA LONG	10	1868570000	DAE M12 PA LONG	10	1868570000
Stainless steel 1.4305, M12	DAE M12 SS	10	1868550000	DAE M12 SS	10	1868550000
Note						

	FPC 20/40/13	132 mm	FPC 30/30/13	132 mm
				
Height / Width / Depth	200 / 400 / 132 mm		300 / 300 / 132 mm	

Technical data

Assembly with terminal	vertical	horizontal	vertical	horizontal
2.5 mm²	3x20	1x59	2x40	1x40
4 mm²	3x17	1x49	2x33	1x33
6 mm²	3x13	3x13	2x25	2x25
10 mm²	3x10	1x30	2x20	1x20
16 mm²	3x8	1x25	2x17	1x17
35 mm²	3x6	1x19	2x12	1x12
Guide value for max. number of cable entries	**A / B**	**C / D**	**A / B**	**C / D**
M12	56	20	38	38
M16	30	11	21	21
M20	18	6	12	12
M25	12	4	8	8
M32	5	2	3	3
M40	4	1	3	3
M50	4	1	2	2
M63	3	1	2	2
M75				
Note				

Ordering data

	Type	Qty.	Order No.	Type	Qty.	Order No.
Enclosure with grey lid	FPC 20/40/13 7035	1	**9535730000**	FPC 30/30/13 7035	1	**9535750000**
Enclosure with transparent lid	FPC 20/40/13 TRSP	1	**9535720000**	FPC 30/30/13 TRSP	1	**9535740000**
Note						

Accessories

	Type	Qty.	Order No.	Type	Qty.	Order No.
Mounting plates and fastening screws						
Steel sheet, zinc plated	MP FPC 20/40	1	**9535940000**	MP FPC 30/30	1	**9535950000**
M4 screw	FKSC M4X6 D8/SW2	100	**1567480000**	FKSC M4X6 D8/SW2	100	**1567480000**
Mounting rails, TS15x5						
Vertical	TS15X5 ST FPC 20 VER	20	**8000037604**	TS15X5 FPC 20 VER	20	**8000037604**
Mounting rails, TS35x7.5						
Horizontally	TS35X7.5 ST FPC 40 HOR	20	**8000037560**	TS35X7.5 FPC 40 HOR	20	**8000037560**
Vertical	TS35X7.5 ST FPC 20 VER	20	**8000037558**	TS35X7.5 FPC 20 VER	20	**8000037558**
External mounting lug, set of 4						
	MF FPC	1	**9536040000**	MF FPC	1	**9536040000**
Hinge, set of 2						
	HG FPC	1	**9535990000**	HG FPC	1	**9535990000**
Earthing stud						
Brass, M6	PEBZ M6 BR SET	1	**1277250000**	PEBZ M6 BR SET	1	**1277250000**
Stainless steel 1.4404, M6	PEBZ M6 S4 SET	1	**1283430000**	PEBZ M6 S4 SET	1	**1283430000**
Brass, M10	PEBZ M10 BR SET	1	**1277220000**	PEBZ M10 BR SET	1	**1277220000**
Stainless steel 1.4404, M10	PEBZ M10 S4 SET	1	**1283440000**	PEBZ M10 S4 SET	1	**1283440000**
Pressure compensation elements						
Polyamide 6, M12	DAE M12 PA LONG	10	**1868570000**	DAE M12 PA LONG	10	**1868570000**
Stainless steel 1.4305, M12	DAE M12 SS	10	**1868550000**	DAE M12 SS	10	**1868550000**
Note						

	FPC 30/40/13	132 mm	FPC 40/60/13	132 mm
				
Height / Width / Depth	300 / 400 / 132 mm		400 / 600 / 132 mm	

Technical data

Assembly with terminal	vertical	horizontal	vertical	horizontal
2.5 mm²	3x40	1x59	5x59	2x97
4 mm²	3x33	1x49	5x49	2x81
6 mm²	3x25	3x25	5x37	5x37
10 mm²	3x20	1x30	5x30	2x49
16 mm²	3x17	1x25	5x25	2x41
35 mm²	3x12	1x19	5x19	2x31
Guide value for max. number of cable entries	**A / B**	**C / D**	**A / B**	**C / D**
M12	56	38	76	56
M16	30	21	42	30
M20	18	12	24	18
M25	12	8	16	12
M32	5	3	6	5
M40	4	3	6	4
M50	4	2	4	4
M63	3	2	4	3
M75				
Note				

Ordering data

	Type	Qty.	Order No.	Type	Qty.	Order No.
Enclosure with grey lid	FPC 30/40/13 7035	1	**9535770000**	FPC 40/60/13 7035	1	**9535810000**
Enclosure with transparent lid	FPC 30/40/13 TRSP	1	**9535760000**	FPC 40/60/13 TRSP	1	**9535820000**
Note						

Accessories

	Type	Qty.	Order No.	Type	Qty.	Order No.
Mounting plates and fastening screws	MP FPC 30/40	1	**9535960000**	MP FPC 40/60	1	**9535980000**
Steel sheet, zinc plated	FKSC M4X6 D8/SW2	100	**1567480000**	FKSC M4X6 D8/SW2	100	**1567480000**
Mounting rails, TS15x5						
Vertical						
Mounting rails, TS35x7.5						
Horizontally	TS35X7.5 ST FPC 40 HOR	20	**8000037560**	TS35X7.5 FPC 60 HOR	20	**8000037563**
Vertical	TS35X7.5 ST FPC 30 VER	20	**8000037561**	TS35X7.5 FPC 40 VER	20	**8000037562**
External mounting lug, set of 4						
	MF FPC	1	**9536040000**	MF FPC	1	**9536040000**
Hinge, set of 2						
	HG FPC	1	**9535990000**	HG FPC	1	**9535990000**
Earthing stud						
Brass, M6	PEBZ M6 BR SET	1	**1277250000**	PEBZ M6 BR SET	1	**1277250000**
Stainless steel 1.4404, M6	PEBZ M6 S4 SET	1	**1283430000**	PEBZ M6 S4 SET	1	**1283430000**
Brass, M10	PEBZ M10 BR SET	1	**1277220000**	PEBZ M10 BR SET	1	**1277220000**
Stainless steel 1.4404, M10	PEBZ M10 S4 SET	1	**1283440000**	PEBZ M10 S4 SET	1	**1283440000**
Pressure compensation elements						
Polyamide 6, M12	DAE M12 PA LONG	10	**1868570000**	DAE M12 PA LONG	10	**1868570000**
Stainless steel 1.4305, M12	DAE M12 SS	10	**1868550000**	DAE M12 SS	10	**1868550000**
Note						

Cable entries

Cable entries	Introduction	D.2
	Overview	D.4
	Standard cable glands – Plastic	D.6
	Standard cable glands – Brass	D.8
	EMC cable glands	D.11
	Standard cable glands – Stainless steel	D.13
	Standard cable glands	D.15
	Klippon® Cable Glands	D.16
	Ex-cable glands – Brass	D.27
	Ex-cable glands – Plastic	D.36
	Accessories – Lock nuts	D.40
	Accessories – Flat IP washer	D.45
	Accessories – Earthing rings	D.49
	Accessories – Shrouds	D.50
	Accessories – Washers	D.52
	Blanking plugs	D.53
	Ex-Blanking plugs	D.55
	Compensating elements	D.59
	Ex-Compensating elements	D.61

Cable entries

Weidmüller offers a variety of add-on components for a multitude of purposes and applications in addition to its extensive Klippon® Protect range.

In addition to brass, plastic and stainless steel cable glands, there are also sealing plugs, pressure-equalising elements, adapters and relevant accessories – such as lock nuts, flat gaskets, flat washers and earthing rings – available.

To match the assembled enclosures, the cable glands meet the requirements of IP protection classes IP54 to IP69K and can be used as required in standard industrial applications, EMC applications or even explosive risk zones, plus they comply with the approvals required for this purpose.

The Ex-certified Klippon® cable glands also allow for the connection of cables and conductors with different reinforcements with and without lead sheathing, as well as the connection of steel wire and steel tape cables. They can withstand temperatures ranging from -60°C to +180°C.

Depending on the cable gland variants and application, the cable glands, sealing plugs, adaptors, pressure-equalising elements, and accessories are manufactured and certified according to the following standards:

- IEC/EN 62444 (Construction and design)
- IEC/EN 60529 (IP protection class testing)
- IEC/EN 60079-0 (General Ex requirements)
- IEC/EN 60079-1 (Ex d Ex standard)
- IEC/EN 60079-7 (Ex e Ex standard)
- IEC/EN 60079-11 (Ex i Ex standard)
- IEC/EN 60423 (Metric thread)
- DIN 40430 (PG and NPT threads)

The range of cable glands, sealing plugs and pressure-equalising elements is available in metric (M) and high-strength (PG) threads in sizes ranging from M12 to M75 and PG7 to PG48. When choosing cable glands and sealing plugs, please refer to the table with the sealing characteristics of the O-rings, flat gaskets and seal inserts. The O-Ring or flat gasket is always intended for sealing the connecting thread on an enclosure, for example, while the seal insert of each cable gland is intended for actually sealing and crushing the connecting cable.

You should always observe the maximum drill-hole diameter when installing a cable gland, sealing plug, adaptor, or pressure compensation element (e.g. onto the gland plate of an enclosure). These must not exceed the following specified maximum values / tolerances so that the protection degree of the whole enclosure can be guaranteed.
Please also refer to the instruction manual; deviating information is possible.

Through-hole information

M thread	Through-hole, in mm
M 12	12.2
M 16	16.2
M 20	20.2
M 25	25.2
M 32	32.2
M 40	40.2
M 50	50.2
M 63	63.2
M 75	75.2
PG thread	**Through-hole, in mm**
PG 7	12.4
PG 9	15.1
PG 11	18.5
PG 13.5	20.4
PG 16	22.5
PG 21	28.3
PG 29	37.4
PG 36	47.2
PG 42	54.2
PG 48	59.5

Overview of sealing materials for O-rings, flat gaskets as well as seal inserts

Abbreviation	Material	Trade name	Temperature range	Chemical resistance	Fire resistant	Shore	Free from halogens	UV resistance
TPE	Thermo-plastic elastomer	Santroprene	–40 °C to +130 °C	Hydrocarbons, oils, acids	UL94, HB	64	Yes	very good
CR	Chloroprene rubber	Neoprene	–40 °C to +130 °C	Mineral oils, greases, fuels	very good	40 - 90	No	very good
NBR	Nitrile rubber	Perbunan, Nitrile	–40 °C to +130 °C	Hydrocarbons, oils, acids, aliphatic solvents, greases, fuels	weak	40 - 90	No	good
EPDM	Ethylene-propylene-diene rubber	Keltan	–50 °C to +130 °C	Weather-, grease-, mineral oil-, chlorine-,and ozone resistant, hydrocarbons	weak	20 - 90		very good
FPM	Fluoro-rubber	Viton	–25 °C to +200 °C	ozone, oxygen, mineral oils, synthetic hydraulic fluids, fuels, aromatics, many organic solvents and chemicals	weak	65 - 95		good

Note: The data refer only to the sealing material, not to the entire component.

Abbreviations – technical data

A, L	Length in mm
L1	Length of thread in mm
D	Diameter in mm
S	Thickness in mm
S1,S2	Depth in mm
SW, SW1, SW2	Distance across flats in mm
KB	Clamping range in mm
KB ZE	Clamping range strain relief in mm
Thread	External thread
SUHB	Shroud / Protective cap
DR	Tightening torque in Nm
HM	Cap nut / pressure screw
Qty.	Packing unit in pieces

Product designation

VG	Cable gland
VP	Sealing plugs
KDSU	Klippon® Double Seal Universal
KDSW	Klippon® Double Seal for SWA
KDSX	Klippon® Double Seal for SWB/STA
KSG	Klippon® Standard Gland
KUB	Klippon® Universal Barrier
KSPA	Klippon® Stopping Plug Type A
KSPMH	Klippon® Stopping Plug Mushroom
KSWN	Klippon® Sealing Washer Nylon
KSWF	Klippon® Sealing Washer Red Fibre
KSP	Klippon® Shroud PVC/Silicone
SKMU	Hexagon nut
DAE	Pressure compensation element
BD	Breather drain (compensation element)
SZS	Serrated Star Washers
ZE	Strain relief
EMV	Electromagnetic compatibility
EA	Earthing ring
SKS	Spiral kink protection
GWDR	Threaded sealing ring or IP washer

Glands and accessories

The tables below provide an overview of the Weidmüller cable glands and the recommended accessories.

Standard cable glands

Material/Type		Approvals: IP class of protection without seal	Approvals: IP class of protection with seal	Ex	EMC	Armouring	Thread sealing rings: CSM GWDR PO	Thread sealing rings: CR GWDR...NP	Thread sealing rings: O-Ring	Locknuts: grey SKMU...K GR	Locknuts: black SKMU...K SW	Locknuts: brass SKMU...MS	Locknuts: MS EMC SKMU EMV...
Plastic													
	VG ... K68	IP68 / 5 bar								•			
	VG ... K68 SKS	IP68 / 5 bar								•			
Nickel-plated brass													
	VG ... MS68		IP54,IP66, IP68 / 5 bar, IP69k						included			•	
	VGM...MS68...BG		IP68						included			•	
	VG ... MS54-ZE	IP54										•	
	VG ... EMV-4		IP66, IP68 / 5 bar, IP69k		•				included				•
	VGM...EMC...SET		IP68		•				included				•
Stainless steel													
	VG...SS68		IP54,IP66, IP68 / 5 bar, IP69k						included			•	
	VGM...SS68...BG		IP68						included			•	

Cable glands HQ

Material/Type		Approvals: IP class of protection without seal	Approvals: IP class of protection with seal	Ex	EMC	Armouring	Thread sealing rings: CSM GWDR PO	Thread sealing rings: CR GWDR...NP	Thread sealing rings: O-Ring	Locknuts: grey SKMU...K GR	Locknuts: black SKMU...K SW	Locknuts: brass SKMU...MS	Locknuts: MS EMC SKMU EMV...
Nickel-plated brass, Ex													
	VG ... K68 ...	IP65											
Brass Ex													
	VG ... MS68 ...	IP65											
	VG ... EMV68 ...	IP65			•								

Cable glands Ex

Material/Type		Approvals: IP class of protection without seal	Approvals: IP class of protection with seal	Ex	EMC	Armouring	Thread sealing rings: KSWN	Thread sealing rings: CR GWDR...NP	Thread sealing rings: O-Ring	Locknuts: grey SKMU...K GR	Locknuts: black SKMU...K SW	Locknuts: brass SKMU...MS	Locknuts: MS EMC SKMU EMV...
Nickel-plated brass, Ex													
	KDSU...BN/BS O NII		IP66, IP68 / 2.5 bar	Ex e/d		•			included			•	
	KUB...BS O NI *		IP66, IP68 / 10 bar	Ex e/d		•			included			•	
	KDSW...BN/BS O/L NI	IP54	IP54, IP66, IP68 / 2.5 bar	Ex e/d		•	optional					•	
	KDSX...BS O NI	IP54	IP54, IP66, IP68 / 2.5 bar	Ex e/d		•	optional					•	
	KSG...BN/BS O NI		IP66, IP68 / 2.5 bar	Ex e/d					included			•	
Plastic Ex													
	VG...EXI...7J		IP54, IP66, IP68 / 5 bar	Ex e					included		•		
	VG...EXE...7J		IP54, IP66, IP68 / 5 bar	Ex i					included		•		
Note:	* Available on request. Ex - Stainless steel glands on request												

Adaptor

Material/Type		Approvals		Thread sealing rings			Locknuts			
		IP class of protection with seal	Ex	GWDR PO	CR GWDR...NP	O-Ring	grey SKMU...K GR	black SKMU...K SW	brass SKMU...MS	MS EMC SKMU EMV...
Plastic										
	DAE M12 PA	IP66, IP68, IP69K				included				
	DAE M12 PA long	IP66, IP68, IP69K				included		•		
Stainless steel										
	DAE M12 SS	IP66, IP68, IP69K				included			•	•
Brass Ex										
	KLIPPON BDX ... B	IP66	•			included				
Stainless steel Ex										
	KLIPPON BDX ... S	IP66	•			included				

Stopping plugs

Material/Type		Approvals			Thread sealing rings			Locknuts			
		IP class of protection without seal	IP class of protection with seal	Ex	GWDR PO	CR GWDR...NR	O-Ring	grey SKMU...K GR	black SKMU...K SW	brass SKMU...MS	MS EMC SKMU EMV...
Plastic											
	VP ... K54	IP54	IP65					•			
Nickel-plated brass											
	VP ... MS65		IP68				included			•	
Stainless steel											
	KSPMH...SSC		IP66, IP68	Ex e/d			included			•	
Plastic Ex											
	VP...Ex SW	IP54, IP66	IP66, IP68	Ex e		optional			•		
Nickel-plated brass, Ex											
	VP...Ex MS		IP54, IP64, IP68	Ex e/d			included			•	
Brass Ex											
	KSPMH...BSC		IP66, IP68	Ex e/d			included			•	

Cable glands – Plastic – IP68

Cable gland made of plastic with integrated strain relief for industrial applications where IP67 or IP68 protection is required. Tested and approved according to EN 62444 and UL514B.



Technical data

Material / Colour	Polyamide 6 / Light Grey / RAL 7035
Seal insert	CR
Temperature range	-40 °C...100 °C
Protection class	IP67, IP68 - 5 bar (30 min.)
Flammability rating	V-2
Note	Version with moulded sealing lip. Length L varies depending on the cable diameter used.

Ordering data

Type	Thread	KB	L/L1	SW	Qty.	Order No.
metric						
VG M12-1/K68	M 12	3-6.5	30.5 / 8	15	100	**1772280000**
VG M16-1/K68	M 16	4-8	34.5 / 8	19	50	**1909860000**
VG M16 - K 68	M 16	5-10	40 / 10	22	50	**1772290000**
VG M20-1/K68	M 20	6-12	39.5 / 10	24	50	**1772300000**
VG M25-1/K68	M 25	11-17	43 / 8	29	50	**1909870000**
VG M25 - K 68	M 25	13-18	47 / 10	33	25	**1772310000**
VG M32-1/K68	M 32	15-21	52 / 10	36	20	**1909880000**
VG M32 - K 68	M 32	18-25	56 / 15	42	20	**1772320000**
VG M40-1/K68	M 40	19-28	57 / 10	46	10	**1909890000**
VG M40 - K 68	M 40	22-32	69.5 / 18	53	10	**1772330000**
VG M50 - K 68	M 50	30-38	71 / 18	60	10	**1772340000**
VG M63-1/K68	M 63	34-44	71 / 18	65	10	**1772350000**
PG						
VG 7-K68	PG 7	3-6.5	30 / 8	15	100	**1568970000**
VG 9-K68	PG 9	4-8	34.5 / 8	19	50	**1568980000**
VG 11-K68	PG 11	5-10	37 / 8	22	50	**1568990000**
VG 13.5-K68	PG 13.5	6-12	39 / 10	24	50	**1569000000**
VG 16-K68	PG 16	10-14	41 / 10	27	50	**1569010000**
VG 21-K68	PG 21	13-18	48 / 11	33	25	**1569020000**
VG 29-K68	PG 29	18-25	52 / 11	42	20	**1569030000**
VG 36-K68	PG 36	22-32	64.5 / 13	53	10	**1569040000**
VG 42-K68	PG 42	30-38	66.5 / 13	60	10	**1569050000**
VG 48-K68	PG 48	34-44	67.5 / 14	65	10	**1718770000**
Note	Long-thread version on request, halogen-free without sealing ring. Installation specifications and tightening torques can be found in the installation instructions. For further information please use our online catalogue: catalog.weidmueller.com.					

Cable glands – Plastic – SKS

Cable gland made of plastic with spiral bending protection and integrated strain relief, specially suited for moving connections. It prevents cables from bending at acute angles.



Technical data

Material / Colour	Polyamide 6 / Light Grey / RAL 7035
Seal insert	CR
Temperature range	-20 °C...100 °C
Protection class	IP68 - 5 bar (30 min.)
Flammability rating	V-2
Note	Version with moulded sealing lip Length L varies depending on the cable diameter used.

Ordering data

Type	Thread	KB	L/L1	SW	Qty.	Order No.
metric						
VG M12-K68 SKS	M 12	3-6.5	63.5 / 8	15	100	**1776700000**
VG M16-K68 SKS	M 16	5-10	94.5 / 15	22	50	**1776710000**
VG M20-K68 SKS 6-12	M 20	6-12	101.5 / 11	24	50	**1778860000**
VG M20-K68 SKS 10-14	M 20	10-14	116 / 15	27	25	**1776720000**
VG M25-K68 SKS	M 25	13-18	132.5 / 15	33	25	**1776730000**
PG						
VG 7-K68 SKS	PG 7	3-6.5	63 / 8	15	50	**1720470000**
VG 9-K68 SKS	PG 9	4-8	74 / 8	19	50	**1720480000**
VG 11-K68 SKS	PG 11	5-10	87 / 8	22	100	**1720490000**
VG 13.5-K68 SKS	PG 13.5	6-12	98 / 9	24	50	**1720500000**
VG 16-K68 SKS	PG 16	10-14	112 / 10	27	25	**1720510000**
VG 21-K68 SKS	PG 21	13-18	130 / 11	33	20	**1720520000**
Note	Long-thread version on request, halogen-free without sealing ring. Installation specifications and tightening torques can be found in the installation instructions. For further information please use our online catalogue: catalog.weidmueller.com.					

Cable glands – Brass – IP68

Cable gland made of brass for industrial applications where IP68 or IP69K protection is required.



Technical data

Material	Brass, nickel-plated
O-ring / Seal insert	NBR / CR
Temperature range	-40 °C...100 °C
Clamp insert	Polyamide
Protection degree with GWDR	IP54, IP66, IP67, IP68 - 5 bar (30 min.), IP69K
Note	Length "L" varies depending on the cable diameter used; IP69K protection applies to all metric cable glands; the following thread sizes are excluded from IP69K: PG29, PG36, PG42 and PG48.

Ordering data

Type	Thread	KB	L/L1	SW1/SW2	Qty.	Order No.
metric						
VG M12 - MS 68	M 12	3-6.5	28 / 6	14 / 14	50	**1772200000**
VG M16 - MS 68	M 16	4-8	30 / 7	17 / 18	50	**1772210000**
VG M16-1/MS68	M 16	5-10	35.5 / 7	20 / 20	50	**1909910000**
VG M20 - MS 68	M 20	6-12	34.5 / 8	22 / 22	50	**1772220000**
VG M25 - MS 68	M 25	10-14	35.7 / 8	24 / 27	25	**1772230000**
VG M25-1/MS68	M 25	11-17	40.5 / 8	27 / 27	25	**1909920000**
VG M32 - MS 68	M 32	13-18	42 / 9	30 / 34	10	**1772240000**
VG M32-1/MS68	M 32	15-21	44 / 8	34 / 34	10	**1909930000**
VG M40 - MS 68	M 40	18-25	47 / 9	40 / 43	10	**1772250000**
VG M40-1/MS68	M 40	19-28	52.5 / 9	43 / 43	10	**1909940000**
VG M50 - MS 68	M 50	22-32	57 / 9	50 / 55	5	**1772260000**
VG M50-1/MS68	M 50	27-38	61 / 9	58 / 58	5	**1909950000**
VG M63 - MS 68	M 63	34-44	67 / 14	64 / 68	5	**1772270000**
PG (IP69K)						
VG 7-MS68	PG 7	3-6.5	28 / 6	14 / 14	50	**1569060000**
VG 9-MS68	PG 9	4-8	29.5 / 6	17 / 17	50	**1569070000**
VG 11-MS68	PG 11	5-10	32 / 6	20 / 20	50	**1569080000**
VG 13,5-MS68	PG 13.5	6-12	31 / 6.5	22 / 22	50	**1569090000**
VG 16-MS68	PG 16	10-14	34.5 / 6.5	24 / 24	25	**1569100000**
VG 21-MS68	PG 21	13-18	39.7 / 7.2	30 / 30	25	**1569110000**
PG (IP68)						
VG 29-MS68	PG 29	18-25	46.5 / 8	40 / 40	10	**1569120000**
VG 36-MS68	PG 36	22-32	57 / 9	50 / 50	5	**1569130000**
VG 42-MS68	PG 42	30-38	60.5 / 12	58 / 58	5	**1569140000**
VG 48-MS68	PG 48	34-44	69 / 14	64 / 64	5	**1718790000**

Note

Long-thread version on request
VDE for metric version
Installation specifications and tightening torques can be found in the installation instructions.
For further information please use our online catalogue: catalog.weidmueller.com.

Cable glands – Brass – IP68

EN 45545

Cable gland made of brass with spherical sealing insert which squeezes the cable gently over a large area. This cable gland is suitable for railway applications; its sealing material conforms to the requirements of EN 45545.



Technical data

Material	Brass, nickel-plated
O-Ring / Seal insert	NBR / T80s
Temperature range	-40 °C ... 130 °C
Protection class	IP68 - 15 bar
Note	

Ordering data

Type	Thread	KB	L/L1	SW	Qty.	Order No.
VGM25-MS68 11-20 BG	M 25	11-20	36.5 / 7.5	30	50	**1193600000**
VGM32-MS68 15-25 BG	M 32	15-25	40 / 8	36	25	**1193610000**
VGM40-MS68 20-32 BG	M 40	20-32	43 / 8	45	10	**1193620000**
VGM40/1-MS68 20-32 BG	M 40	20-32	82 / 8	45	10	**1205890000**

Note

When using mounting covers with 3 X M 40 cable input threads, the elongated version must be used for the cable gland in the middle.
Installation specifications and tightening torques can be found in the installation instructions.
For further information please use our online catalogue: catalog.weidmueller.com

Clamping screws – Brass – IP65

The special cable glands (clamping screws) are designed for use in HDC RockStar® base enclosures. The seal insert used contains several removable or separable inlets.



Technical data

Clamping screw material	Brass, nickel-plated
Sealing ring material	SBR/NBR
Pressure ring material	Polyamide
Temperature range	-20 °C...60 °C
Protection class	IP65
Note	

Ordering data

Type	Thread	Inserts in mm	SW	Qty.	Order No.
metric					
VG H M20 MS	M 20	4 / 7 / 10 / 13	20	50	**1921720000**
VG H M25 MS	M 25	8.5 / 11.5 / 14.5 / 18	25	25	**1921740000**
VG H M32 MS	M 32	16 / 19 / 22 / 25	32	20	**1921760000**
VG H M40 MS	M 40	23 / 26 / 29 / 32	40	10	**1921770000**
PG					
KV 11-M	PG 11	7.5 / 10 / 12.5	10	10	**1656390000**
KV 13-M	PG 13	7.5 / 10 / 12.5	10	10	**1656400000**
KV 16-M	PG 16	7.5 / 10 / 12.5 / 15	10	10	**1656410000**
KV 21-M	PG 21	10 / 13 / 16 / 19	10	10	**1656420000**
KV 29-M	PG 29	18 / 21 / 24 / 27	10	10	**1656430000**
Note					

Cable glands – Brass – EMC–4

Cable gland made of brass with EMC contact system for the particularly time-saving installation of shielded cables. It is characterised by the following features: very low installation effort, vibration-resistant and patented active contact system.



Technical data

Material	Brass, nickel-plated
O-Ring / Seal insert	NBR / CR
Temperature range	-40 °C...100 °C
Protection class	IP66, IP68 - 5 bar (30 min.), IP69K
Clamp insert	Polyamide
Note	

Ordering data

Type	Thread	KB	Shield Ø	L/L1	SW	Qty.	Order No.
VG M12 EMV-4 MS 3-6.5	M 12	3-6.5	2.00-5.00	34 / 6	14	50	**2435070000**
VG M16 EMV-4 MS 5-10	M 16	5-10	3.50-8.00	39 / 6	20	50	**2435140000**
VG M20 EMV-4 MS 6-12	M 20	6-12	4.50-10.00	38 / 6	22	50	**2435150000**
VG M20 EMV-4 MS 8-14	M 20	7.5-14	5.50-11.50	48 / 8	24	50	**2435160000**
VG M25 EMV-4 MS 10-18	M 25	10-18	7.00-14.00	51 / 8	30	25	**2435170000**
VG M32 EMV-4 MS 16-25	M 32	16-25	12.00-20.00	62 / 9	40	10	**2435180000**
VG M40 EMV-4 MS 22-32	M 40	22-32	18.00-27.00	69.5 / 9	50	5	**2435190000**
VG M50 EMV-4 MS 30-38	M 50	30-38	26.00-34.00	62 / 9	58	5	**2435200000**
VG M63 EMV-4 MS 34-44	M 63	34-44	30.00-40.00	73 / 14	68	5	**2435210000**

Note

Installation specifications and tightening torques can be found in the installation instructions.
For further information please use our online catalogue: catalog.weidmueller.com.

Cable glands – Brass – EMC SET

EN 45545

Cable gland made of brass for internal shield connection or potential equalisation; easy-to-use, permanent, secure shield connection. This cable gland is suitable for railway applications; its sealing material meets the requirements of EN 45545.



Technical data

Material	Brass, nickel-plated
O-Ring / Seal insert	NBR / T80s
Temperature range	-40 °C ... 130 °C
Protection class	IP68 - 15 bar
Note	

Ordering data

Type	Thread	KB	L/L1	SW	Qty.	Order No.
VGM25-MS68 EMC 11-20SET	M 25	11-20	63.5 / 34	30	1	**1463720000**
VGM32-MS68 EMC 15-25SET	M 32	15-25	66.5 / 34	36	1	**1463730000**

Note

Installation specifications and tightening torques can be found in the installation instructions.
For further information please use our online catalogue: catalog.weidmueller.com.

Cable glands – Stainless steel – IP68

Cable gland made of stainless steel for standard industrial applications that require a high degree of protection (IP68 or IP69K). These cable glands – with their resistance to impact and sea water – are also suitable for use in applications under extreme environmental conditions.



Technical data

Material	Stainless steel 1.4305 (303)
O-Ring / Seal insert	NBR / CR
Temperature range	-40 °C...100 °C
Protection class	IP54, IP66, IP67, IP68 - 5 bar (30 min.), IP69K
Note	

Ordering data

Type	Thread	KB	L/L1	SW1/SW2	Qty.	Order No.
metric						
VGM12-SS 68 KB 3-6.5	M 12	3-6.5	28 / 6	14 / 14	50	**1009840000**
VGM16-SS 68 KB 4-8	M 16	4-8	30 / 7	17 / 19	50	**1009850000**
VGM20-SS 68 KB 6-12	M 20	6-12	32 / 8	22 / 22	50	**1009860000**
VGM25-SS 68 KB 10-14	M 25	10-14	35.5 / 8	24 / 27	25	**1009870000**
VGM32-SS 68 KB 13-18	M 32	13-18	41.5 / 9	30 / 36	20	**1009880000**
VGM40-SS 68 KB 18-25	M 40	18-25	49.6 / 9	41 / 46	20	**1009890000**
VGM50-SS 68 KB 22-32	M 50	22-32	55 / 9	50 / 55	5	**1009900000**
VGM63-SS 68 KB 34-44	M 63	34-44	67 / 14	65 / 70	5	**1009910000**
PG						
VG 7-SS 68 KB 3-6.5	PG 7	3-6.5	28 / 6	14 / 14	50	**1009740000**
VG 9-SS 68 KB 4-8	PG 9	4-8	29 / 6	17 / 17	50	**1009750000**
VG 11-SS 68 KB 5-10	PG 11	5-10	31.5 / 6	22 / 22	50	**1009760000**
VG 16-SS 68 KB 10-14	PG 16	10-14	34 / 6.5	24 / 24	25	**1009780000**
VG 21-SS 68 KB 13-18	PG 21	13-18	39.7 / 7.2	30 / 30	25	**1009790000**
VG 29-SS 68 KB 18-25	PG 29	18-25	46.5 / 8	41 / 41	20	**1009800000**
VG 36-SS 68 KB 22-32	PG 36	22-32	55 / 9	50 / 50	15	**1009810000**

Note

1.4404 (316L) on request.
Installation specifications and tightening torques can be found in the installation instructions.
For further information please use our online catalogue: catalog.weidmueller.com.

Cable gland – Stainless steel – IP68

EN 45545

Cable gland with spherical seal insert that squeezes the cable gently over a large area. This cable gland is suitable for railway applications; its sealing material meets the requirements of EN 45545.



Technical data

Material	Stainless steel 1.4305 (303)
O-Ring / Seal insert	Silicone / T80s
Temperature range	-40 °C ... 130 °C
Protection class	IP68 - 15 bar
Note	

Ordering data

Type	Thread	KB	L/L1	SW	Qty.	Order No.
VGM25-SS68 11-20 BG	M 25	11-20	36.5 / 7.5	30	50	**1193570000**
VGM32-SS68 15-25 BG	M 32	15-25	40 / 8	36	25	**1193580000**
VGM40-SS68 20-32 BG	M 40	20-32	43 / 8	45	10	**1193590000**
VGM40/1-SS68 20-32 BG	M 40	20-32	82 / 8	45	10	**1205920000**

Note

When using mounting covers with 3 X M 40 cable input threads, the elongated version must be used for the cable gland in the middle.
Installation specifications and tightening torques can be found in the installation instructions.
For further information please use our online catalogue: catalog.weidmueller.com

HQ cable glands

Cable gland especially for heavy-duty connectors of the HQ series, available in plastic, brass and as brass EMC version.

Technical data

Material	Polyamide 6
Seal insert	TPE
Temperature range	-40 °C ... 130 °C
Protection class	IP68
Note	

Ordering data

Type	Thread	KB	SW	Qty.	Order No.
Plastic					
VG 16 HQ K68 4-6.5	PG 16	4-6.5	27	1	**2715990000**
VG 16 HQ K68 6.5-9.5	PG 16	6.5-9.5	27	1	**1273890000**
VG 16 HQ K68 9-13	PG 16	9-13	27	1	**1016070000**
VG 16 HQ K68 11.5-15.5	PG 16	11.5-15.5	27	1	**1016080000**
brass					
VG 21 HQ MS68 9-13	PG 21	9-13	30	1	**1016090000**
VG 21 HQ MS68 11.5-15.5	PG 21	11.5-15.5	30	1	**1016100000**
VG 21 HQ MS68 14-18	PG 21	14-18	30	1	**1016110000**
EMC					
VG 21 HQ EMV68 11-15.5	PG 21	11-15.5	30	1	**1016120000**
VG 21 HQ EMV68 14-18	PG 21	14-18	30	1	**1016130000**
only for angled HQ base enclosure (order number 1003110000)					
VG16 HQ K68 9-12SH	PG 16	9-12	30	1	**1045530000**
VG16 HQ K68 11,5-15,5SH	PG 16	11.5-15.5	30	1	**1045540000**

Note

Installation specifications and tightening torques can be found in the installation instructions.
For further information please use our online catalogue: catalog.weidmueller.com.

Overview: Klippon® cable glands and selection tool

ATEX / IECEx certified cable glands

Cable Gland Type	Outer Elastomeric Seal	Inner Elastomeric Seal	Lead Option	Armour Clamp	Certification	IP Rating	Page No.
KDSU	YES	YES	NO	Universal	Ex d / Ex e	IP66, IP68	D.27
KDSW	YES	YES	YES	Steel wire	Ex d / Ex e	IP66, IP68	D.29
KDSX	YES	YES	NO	Braided	Ex d / Ex e	IP66, IP68	D.32
KUB	YES	Compound	NO	Universal	Ex d	IP66, IP68	On request
KSG	YES	NO	NO	No	Ex d / Ex e	IP66, IP68	D.33

General

Health & Safety

When Weidmüller cable glands and the accessories are used and installed as prescribed within the data sheet provided, they will not cause any danger or hazard to the health or safety of persons, animals or property. The products should be installed by suitably trained/skilled personnel and in full accordance with the relevant legislative regulations and the accepted code of practice for the industry concerned.

Warning

Weidmüller cable glands and accessories should not be used within any application other than those specified for each product, unless Weidmüller issue a statement in writing that the product is suitable for the specified application. For further information on each product, we refer you to the specific Assembly Instructions and General Arrangement drawings, which are available on request. Weidmueller takes no responsibility for any damage, unjury or other consequential loss caused where the glands are not installed or used according to our Assembly Instructions.

Installation in hazardous area applications

If cable glands and accessories are installed in hazardous area applications, international and national standards of the Explosion Protection have to be considered.

The KDSU type glands provide a universal armour clamp for steel wire, steel tape, screened or braided cables. An electrical bond between the cable armour and the gland is ensured. The gland can also be used to terminate un-armoured cables. In addition, the gland is fitted with two separate seals to seal the outer and inner cable insulation.
When choosing the gland with a neoprene sealing a temperature range from -35 °C to +90 °C will be achieved. Whereas the gland with silicone sealing ensures a temperature range from -60 °C to +180 °C.
With both sealing materials an IP rating of IP68 to 25 metres (30 min. at 2.5 bar) is maintained. The KDSU is approved for explosion protection type of pressure-resistant encapsulation Ex d and increased safety Ex e.

Structure of the part description

Order key	[Type]	[a]	[b]	[c]	[d]	[e]	[f]	[ggg]
Example article description	KDSU	M20	B	S	0	SC	1	G16

Meaning

[Type] = Gland type (KDSU)
[a] = Entry thread (M20-M75)
[b] = Material (B = brass)
[c] = Seal material (S = Silicone, N = Neoprene)
[d] = Continuity for lead sheath (L = yes, 0 = no)
[e] = Plating (SC = self-coloured, NI = Nickel)
[f] = Cable outer sheath (1 = Reduced, 2 = Standard)
[ggg] = Gland size (G16-G75)



Note Refer to page D.22 Selection Guide Klippon® Cable Glands to determine the suitable order number

Dimensions

Gland Size	Entry thread	Entry thread Length	Max Outer Diameter	Max Length	Gland Seal Range						Armour Acceptance Range	Shroud Size
					Cable Inner Sheath [C]		Cable Outer Sheath [D]					
							Standard [f] = 2		Reduced [f] = 1			
[ggg]	[a]	[B]	[A]		Min	Max	Min	Max	Min	Max		
G16	M20	16	28.0	78.0	3.4	8.4	9.0	13.5	6.7	10.3	0.15 - 1.25	L24
G20S	M20	16	28.0	78.0	7.2	11.7	11.5	16.0	9.4	12.5	0.15 - 1.25	L24
G20	M20	16	33.0	78.0	9.4	14.0	15.5	21.1	12.0	17.6	0.15 - 1.25	EL30
G25	M25	16	41.4	90.0	13.5	20.0	20.3	27.4	16.8	23.9	0.15 - 1.60	EL38
G32	M32	16	50.6	105.0	19.5	26.3	26.7	34.0	23.2	30.5	0.15 - 2.00	EL46
G40	M40	16	60.5	113.0	23.0	32.2	33.0	40.6	28.6	36.2	0.20 - 2.00	EL55
G50S	M50	16	71.5	125.0	28.1	38.2	39.4	46.7	34.8	42.4	0.30 - 2.50	EL65
G50	M50	16	71.5	125.0	33.1	44.1	45.7	53.2	41.1	48.5	0.30 - 2.50	EL65
G63S	M63	19	88.0	125.0	39.2	50.1	52.1	59.5	47.5	54.8	0.30 - 2.50	EL80
G63	M63	19	88.0	125.0	46.7	56.0	58.4	65.8	53.8	61.2	0.30 - 2.50	EL80
G75S	M75	19	99.0	131.0	52.1	62.0	64.8	72.2	60.2	68.0	0.30 - 2.50	EL90
G75	M75	19	99.0	131.0	58.0	68.0	71.1	78.0	66.5	73.4	0.30 - 2.50	EL90
		Dimensions in mm										

Important Notes

- The gland size does not necessarily equate to the entry thread size.
- In some cases several gland sizes can be chosen due to overlapping inner as well as outer cable diameters. Due to the wide range of armoured cables available, it is necessary to select the correct clamping range. This is achieved by taking the inner and outer clamping range values to determine the best fit (as close as possible to the Min/Max values average).
- All cable glands have a 1.5 mm pitch.
- For Flameproof Ex d applications the female thread into which the gland is to be fitted must achieve an engagement of at least 5 full threads in compliance with clause 5.3 of EN/IEC 60079-1.
- Where KDSU glands are fitted into non-metallic Increased Safety Ex e enclosures they must be included within the earth circuit of the system.
- Fully assembly instructions are supplied with the glands. The instructions must be read prior to installation and adhered to in full.
- When the gland is used to terminate un-armoured cables, the gland is suitable only for fixed installation.

Klippon® KDSW Cable Glands

The KDSW glands provide an armour clamp for steel wire, steel tape and lead sheathed cables. An electrical bond between the cable armour and the gland is ensured. In addition, the gland is fitted with two separate sealings to seal the outer and inner cable insulation.
When choosing the gland with a neoprene sealing a temperature range from -35 °C to +90 °C will be achieved, whereas the gland with silicone sealing ensures a temperature range from -60 °C to +180 °C.
With both sealing materials an IP rating of IP66 and IP68 to 25 metres (30 min at 2.5 bar) is maintained. The KDSW gland is approved for Flameproof Ex d and Increased Safety Ex e applications.

Structure of the part description

Order key	[Type]	[a]	[b]	[c]	[d]	[e]	[f]	[ggg]
Example article description	KDSW	M20	B	S	L	SC	1	G16

Meaning

[Type] = Gland type (KDSW)
[a] = Entry thread (M20-M75)
[b] = Material (B = brass)
[c] = Seal material (S = Silicone, N = Neoprene)
[d] = Continuity for lead sheath (L = yes, O = no)
[e] = Plating (SC = self-coloured, NI = Nickel)
[f] = Cable outer sheath (1 = Reduced, 2 = Standard)
[ggg] = Gland size (G16-G75)



Note Refer to page D.22 Selection Guide Klippon® Cable Glands to determine the suitable order number

Dimensions

Gland Size	Entry thread	Entry thread Length	Max Outer Diameter	Max Length	Gland Seal Range						Armour Acceptance Range	Shroud Size
					Cable Inner Sheath [C]		Cable Outer Sheath [D]					
							Standard [f] = 2		Reduced [f] = 1			
[ggg]	[a]	[B]	[A]		Min	Max	Min	Max	Min	Max		
G16	M20	16	26.5	58.0	4.0	8.4	8.4	13.5	4.9	10.0	0.90	L24
G20S	M20	16	26.5	58.0	8.0	11.7	11.5	16.0	9.4	12.5	0.90 - 1.25	L24
G20	M20	16	33.0	58.0	6.7*	14.0	15.5	21.1	12.0	17.6	0.90 - 1.25	L30
G25	M25	16	41.4	58.0	13.0	20.0	20.3	27.4	16.8	23.9	1.25 - 1.60	L38
G32	M32	16	50.6	65.0	19.0	26.3	26.7	34.0	23.2	30.5	1.60 - 2.00	L46
G40	M40	16	60.5	72.0	25.0	32.2	33.0	40.6	28.6	36.2	1.60 - 2.00	L55
G50S	M50	16	71.5	73.0	31.5	38.2	39.4	46.7	34.8	42.4	2.00 - 2.50	L65
G50	M50	16	71.5	73.0	36.5	44.1	45.7	53.2	41.1	48.5	2.00 - 2.50	L65
G63S	M63	19	88.0	76.0	42.5	50.1	52.1	59.5	47.5	54.8	2.50	L80
G63	M63	19	88.0	76.0	49.5	56.0	58.4	65.8	53.8	61.2	2.50	L80
G75S	M75	19	99.0	82.0	54.5	62.0	64.8	72.2	60.2	68.0	2.50	L90
G75	M75	19	99.0	82.0	60.5	68.0	71.1	78.0	66.5	73.4	2.5	L90

Dimensions in mm

Important Notes

- The gland size does not necessarily equate to the entry thread size.
- In some cases several gland sizes can be chosen due to overlapping inner as well as outer cable diameters. Due to the wide range of armoured cables available, it is necessary to select the correct clamping range. This is achieved by taking the inner and outer clamping range values to determine the best fit (as close as possible to the Min/Max values average).
- All cable glands have a 1.5 mm pitch.
- For Flameproof Ex d applications the female thread into which the gland is to be fitted must achieve an engagement of at least 5 full threads in compliance with clause 5.3 of EN/IEC 60079-1.
- Where KDSW glands are fitted into non-metallic Increased Safety Ex e enclosures they must be included within the earth circuit of the system.
- Fully assembly instructions are supplied with the glands. The instructions must be read prior to installation and adhered to in full.
- When the gland is used to terminate un-armoured cables, the gland is suitable only for fixed installation.
- * KDSW gland size G20 with silicone seal , the silicone inner seal only seals to a minimum of 9,3 mm and NOT 6.7 mm.

The KDSX glands provide an armour clamp for braided cables. An electrical bond between the cable armour and the gland is ensured. In addition, the gland is fitted with two separate sealings to seal the outer and inner cable insulation.
The gland maintains a temperature range from -60 °C to +180 °C. With both sealing materials an IP rating of IP66 and IP68 to 25 metres (30 min at 2.5 bar) is maintained. The KDSX gland is approved for Flameproof Ex d and Increased Safety Ex e applications.

Structure of the part description

Order key	[Type]	[a]	[b]	[c]	[d]	[e]	[f]	[ggg]
Example article description	KDSX	M20	B	S	O	SC	1	G16

Meaning

[Type] = Gland type (KDSX)
[a] = Entry thread (M20-M75)
[b] = Material (B = brass)
[c] = Seal material (S = Silicone)
[d] = Continuity for lead sheath (L = yes, O = no)
[e] = Plating (SC = self-coloured, NI = Nickel)
[f] = Cable outer sheath (1 = Reduced, 2 = Standard)
[ggg] = Gland size (G16-G75)



Note Refer to page D.22 Selection Guide Klippon® Cable Glands to determine the suitable order number

Dimensions

Gland Size	Entry thread	Entry thread Length	Max Outer Diameter	Max Length	Gland Seal Range						Armour Acceptance Range	Shroud Size
					Cable Inner Sheath [C]		Cable Outer Sheath [D]					
							Standard [f] = 2		Reduced [f] = 1			
[ggg]	[a]	[B]	[A]		Min	Max	Min	Max	Min	Max		
G16	M20	16	26.5	58.0	4.0	8.4	8.4	13.5	4.9	10.0	0.15 - 0.35	L24
G20S	M20	16	26.5	58.0	8.0	11.7	11.5	16.0	9.4	12.5	0.15 - 0.35	L24
G20	M20	16	33.0	58.0	6.7*	14.0	15.5	21.1	12.0	17.6	0.15 - 0.50	L30
G25	M25	16	41.4	58.0	13.0	20.0	20.3	27.4	16.8	23.9	0.15 - 0.50	L38
G32	M32	16	50.6	65.0	19.0	26.3	26.7	34.0	23.2	30.5	0.15 - 0.55	L46
G40	M40	16	60.5	72.0	25.0	32.2	33.0	40.6	28.6	36.2	0.20 - 0.60	L55
G50S	M50	16	71.5	73.0	31.5	38.2	39.4	46.7	34.8	42.4	0.20 - 0.60	L65
G50	M50	16	71.5	73.0	36.5	44.1	45.7	53.2	41.1	48.5	0.30 - 0.80	L65
G63S	M63	19	88.0	76.0	42.5	50.1	52.1	59.5	47.5	54.8	0.30 - 0.80	L80
G63	M63	19	88.0	76.0	49.5	56.0	58.4	65.8	53.8	61.2	0.30 - 0.80	L80
G75S	M75	19	99.0	82.0	54.5	62.0	64.8	72.2	60.2	68.0	0.30 - 1.00	L90
G75	M75	19	99.0	82.0	60.5	68.0	71.1	78.0	66.5	73.4	0.30 - 1.00	L90

Dimensions in mm

Important Notes

- The gland size does not necessarily equate to the entry thread size.
- In some cases several gland sizes can be chosen due to overlapping inner as well as outer cable diameters. Due to the wide range of armoured cables available, it is necessary to select the correct clamping range. This is achieved by taking the inner and outer clamping range values to determine the best fit (as close as possible to the Min/Max values average).
- All cable glands have a 1.5 mm pitch.
- For Flameproof Ex d applications the female thread into which the gland is to be fitted must achieve an engagement of at least 5 full threads in compliance with clause 5.3 of EN/IEC 60079-1.
- Where KDSX glands are fitted into non-metallic Increased Safety Ex e enclosures they must be included within the earth circuit of the system.
- Fully assembly instructions are supplied with the glands. The instructions must be read prior to installation and adhered to in full.
- When the gland is used to terminate un-armoured cables, the gland is suitable only for fixed installation.
- * KDSX gland size G20 with silicone seal , the silicone inner seal only seals to a minimum of 9,3 mm and NOT 6.7 mm.

The KSG gland is designed to terminate un-armoured cables. When choosing the gland with a neoprene sealing a temperature range from -35 °C to +90 °C will be achieved, whereas the gland with silicone sealing ensures a temperature range from -60 °C to +180 °C. With both sealing materials an IP rating of IP66 and IP68 to 25 metres (30 min. at 2.5 bar) is maintained. The KSG type gland is approved for Flameproof Ex d and Increased Safety Ex e applications.

Structure of the part description

Order key	[Type]	[a]	[b]	[c]	[d]	[e]	[f]	[ggg]
Example article description	KSG	M20	B	S	0	SC	2	G16

Meaning

[Type] = Gland type (KSG)
[a] = Entry thread (M20-M90)
[b] = Material (B = brass)
[c] = Seal material (S = Silicone, N = Neoprene)
[d] = Continuity for lead sheath (L = yes, 0 = no)
[e] = Plating (SC = self-coloured, NI = Nickel)
[f] = Cable outer sheath (2 = Standard)
[ggg] = Gland size (G16-G90)



Note Refer to page D.22 Selection Guide Klippon® Cable Glands to determine the suitable order number

Dimensions

Gland Size [ggg]	Entry thread [a]	Entry thread Length [B]	Max Outer Diameter [A]	Max Length	Gland Seal Range: Cable Outer Sheath [D]: Standard [f] = 2		Shroud Size
					Min	Max	
G16	M20	16	28.0	33.0	4.0	8.4	L24
G20S	M20	16	28.0	33.0	7.2	11.7	L24
G20	M20	16	33.0	33.0	9.6	14.0	L30
G25	M25	16	41.4	33.0	13.5	20.0	L38
G32	M32	16	50.6	33.0	19.5	26.3	L46
G40	M40	16	60.5	37.0	23.0	32.2	L55
G50S	M50	16	71.5	37.0	28.2	38.2	L65
G50	M50	16	71.5	37.0	33.2	44.1	L65
G63S	M63	19	88.0	37.0	39.3	50.1	L80
G63	M63	19	88.0	37.0	46.7	56.0	L80
G75S	M75	19	99.0	37.0	52.3	62.0	L90
G75	M75	19	99.0	37.0	58.1	69.0	L90
		Dimensions in mm					

Important Notes

- The gland size does not necessarily equate to the entry thread size.
- In some cases several gland sizes can be chosen due to overlapping inner as well as outer cable diameters. Due to the wide range of armoured cables available, it is necessary to select the correct clamping range. This is achieved by taking the inner and outer clamping range values to determine the best fit (as close as possible to the Min/Max values average).
- All cable glands have a 1.5 mm pitch.
- For Flameproof Ex d applications the female thread into which the gland is to be fitted must achieve an engagement of at least 5 full threads in compliance with clause 5.3 of EN/IEC 60079-1.
- Where KSG glands are fitted into non-metallic Increased Safety Ex e enclosures they must be included within the earth circuit of the system.
- Fully assembly instructions are supplied with the glands. The instructions must be read prior to installation and adhered to in full.
- When the gland is used to terminate un-armoured cables, the gland is suitable only for fixed installation.

The KUB gland provide an armour clamp for steel tape, steel wire and braided cables. An electrical bond between the cable armour and the gland is ensured. The gland can also be used to terminate unarmoured cables. Additionally, the gland provides a single pull resistant seal on the outer sheath of any cable. After clamping the cable armour onto the cone, the cable has to be filled with the provided compound to seal the free spaces between the single conductors.
The gland maintains a temperature range from -60 °C to +135 °C. When filled, the gland fulfills an IP rating of IP68 to 100 metres (30 Min. at 10 bar). The KUB gland is only suitable for pressure-resistant Ex d encapsulation, and is available on request.

Structure of the part description

Order key	[Type]	[a]	[b]	[c]	[d]	[e]	[f]	[ggg]
Example article description	KUB	M20	B	S	0	SC	1	G16

Meaning

[Type] = Gland type (KUB)
[a] = Entry thread (M20-M75)
[b] = Material (B = brass)
[c] = Seal material (S = Silicone)
[d] = Continuity for lead sheath (L = yes, 0 = no)
[e] = Plating (SC = self-coloured, NI = Nickel)
[f] = Cable outer sheath (1 = Reduced, 2 = Standard)
[ggg] = Gland size (G16-G75)



Note Refer to page D.22 Selection Guide Klippon® Cable Glands to determine the suitable order number

Dimensions

Gland Size [ggg]	Entry thread [a]	Entry thread Length [B]	Max Outer Diameter [A]	Max Length	Gland Seal Range							Armour Acceptance Range	Shroud Size
					Cable Inner Sheath [C]			Cable Outer Sheath [D]					
								Standard [f] = 2		Reduced [f] = 1			
					X	Y	Z	Min	Max	Min	Max		
G16	M20	16	28.0	72.0	7	9.0	11.7	9.0	13.5	6.7	10.3	0.15 - 1.25	L24
G20S	M20	16	28.0	72.0	8	10.4	11.7	11.5	16.0	9.4	12.5	0.15 - 1.25	L24
G20	M20	16	33.0	73.0	14	12.5	14.0	15.5	21.1	12.0	17.6	0.15 - 1.25	EL30
G25	M25	16	41.4	83.0	25	17.8	20.0	20.3	27.4	16.8	23.9	0.15 - 1.60	EL38
G32	M32	16	50.6	103.0	50	23.5	26.3	26.7	34.0	23.2	30.5	0.15 - 2.00	EL46
G40	M40	16	60.5	105.0	80	28.8	32.2	33.0	40.6	28.6	36.2	0.20 - 2.00	EL55
G50S	M50	16	71.5	115.0	100	34.2	38.2	39.4	46.7	34.8	42.4	0.30 - 2.50	EL65
G50	M50	16	71.5	115.0	100	39.4	44.1	45.7	53.2	41.1	48.5	0.30 - 2.50	EL65
G63S	M63	19	88.0	115.0	120	44.8	50.1	52.1	59.5	47.5	54.8	0.30 - 2.50	EL80
G63	M63	19	88.0	115.0	120	50.0	56.0	58.4	65.8	53.8	61.2	0.30 - 2.50	EL80
G75S	M75	19	99.0	122.0	140	55.4	62.0	64.8	72.2	60.2	68.0	0.30 - 2.50	EL90
G75	M75	19	99.0	122.0	140	60.8	68.0	71.1	78.0	66.5	73.4	0.30 - 2.50	EL90

Dimensions in mm

Important Notes

- The gland size does not necessarily equate to the entry thread size.
- In some cases several gland sizes can be chosen due to overlapping inner as well as outer cable diameters. Due to the wide range of armoured cables available, it is necessary to select the correct clamping range. This is achieved by taking the inner and outer clamping range values to determine the best fit (as close as possible to the Min/Max values average).
- X = Maximum numbers of cores
- Y = Maximum over cores
- Z = Maximum inner sheath
- All cable glands have a 1.5 mm pitch.
- For Flameproof Ex d applications the female thread into which the gland is to be fitted must achieve an engagement of at least 5 full threads in compliance with clause 5.3 of EN/IEC 60079-1.
- Where KUB glands are fitted into non-metallic Increased Safety Ex e enclosures they must be included within the earth circuit of the system
- Fully assembly instructions are supplied with the glands. The instructions must be read prior to installation and adhered to in full.
- When the gland is used to terminate un-armoured cables, the gland is suitable only for fixed installation.

Selection Guide Klippon® Cable Glands

Purpose: Generation of the article description

By selecting the suitable cable gland different factors have to be considered, such as
- The environment of the application
- The conditions inside the enclosure
- The construction of the cable

By using the Selection Guide Klippon® Cable Glands the article description will be generated following the step by step process to create the 7 character order key. From this the order number can be identified.

The order key consists out of the following attributes:

Order key	[Type]	[a]	[b]	[c]	[d]	[e]	[f]	[ggg]
Example Article Description	KDSU	M20	B	S	0	SC	1	G16

Meaning	[Type]	=	Gland type (KDSU, KDSW, KDSX, KSG, KUB)
	[a]	=	Entry thread (M20-M75)
	[b]	=	Material (B = brass)
	[c]	=	Seal material (S=Silicone, N=Neoprene)
	[d]	=	Continuity for lead sheath (L = yes, 0 = no)
	[e]	=	Plating (SC = self-coloured, NI = nickel-plated
	[f]	=	Cable outer sheath (1 = Reduced, 2 = Standard)
	[ggg]	=	Gland size (G16-G75)

Application example

Within an Ex d application on an Off-Shore platform a suitable cable gland for the termination into an enclosure is required.
Following details about the application are given:

- The enclosure will be used for the control of a motor circuit breaker
- The enclosure has a volume of 1.3 dm^3 and is installed outdoor.
- The application is in the field, a place in which an explosive atmosphere is likely to occur in normal operation, occasionally (Zone 1)
- The surrounding atmosphere of the enclosure consists Ethylene (gas group IIB)
- The enclosure operates in a temperature range of -40 °C bis +45 °C
- The armour of the cable is unknown, no lead sheathed cable
- The cable outer sheath diameter is 10 mm
- The cable inner sheath diameter is 8 mm

Based on the information in the above shown example case the article description will be determined on the following pages.

1. Selection of the cable gland type [type] and continuity for lead sheath [d]

Order key	[Type]	[a]	[b]	[c]	[d]	[e]	[f]	[ggg]
Example Article Description								

1a) Selection of the cable gland type in regard to the ignition protection type

[Type]	Ignition Protecion Type
KDSU	Ex d / Ex e
KDSW	Ex d / Ex e
KDSX	Ex d / Ex e
KSG	Ex d / Ex e
KUB	Ex d

Because it is an Ex d application all cable gland types (marked in blue) can come into consideration.
For Ex d applications the following questionnaire according to the IEC 60079-14 standard has to be passed to find out if a barrier gland ([Type]=KUB) or if a cable gland with a sealing ring ([Type]=KDSU,KDSW,KDSX) has to be used.



By passing this questionnaire with the given information of the example case the orange marked way has to be followed and the result is that a cable gland with sealing ring has to be used. Consequently the blue marked cable gland types below can come into consideration.

Gland type	Type of sealing
KDSU	Sealing ring
KDSW	Sealing ring
KDSX	Sealing ring
KSG	Sealing ring
KUB	Compound

1b) Selection of the cable gland type in regard to the continuity for lead sheath

[Type]	[d]	Continuity for lead sheath
KDSU	0	No
KDSW	L / 0	Yes
KDSX	0	No
KSG	0	No
KUB	0	No

In the example case a cable without lead sheath is to be terminated, therefore the option to clamp a lead sheathed cable is not needed.
Consequently is
[d] = 0
All four gland types marked in blue can be used.

1c) Selection of the cable gland type in regard to the type of armour

[Type]	Armour
KDSU	Universal
KDSW	Steel wire, steel tape
KDSX	Braided
KSG	No armour
KUB	Universal

Because the type of armour of the cable is unknown, the cable gland type KDSU has to be selected.
Consequently is
[Type] = KDSU

The generated information has to be filled into the order key below:

Order key	[Type]	[a]	[b]	[c]	[d]	[e]	[f]	[ggg]
Example Article Description	KDSU				0			

2. Selection of the material [b], the sealing material [c] and the plating [e] of the cable gland

Order key	[Type]	[a]	[b]	[c]	[d]	[e]	[f]	[ggg]
Example Article Description	**KDSU**				**0**			

2a) Selection of the material [b]

All cable gland types are made from brass "b". Other materials can also be provided upon request.
Consequently is
[b] = B

2b) Selection of the sealing material [c] based on the required temperature range

The cable glands can be ordered with either a neoprene seal "N" or a silicone seal "S".
Glands with a neoprene seal can be used in a temperature range from -35 °C to +90 °C, whereas glands with silicone seal maintain a temperature range from -60 °C to +180 °C. (KUB glands are certified to a temperature of -60 °C to +135 °C).

[Type]	[c]	Seal material
KDSU	N,**S**	Neoprene, Silicone
KDSW	N,S	Neoprene (with continuity for lead sheath), Silicone
KDSX	S	Silicone
KSG	N,S	Neoprene, Silicone
KUB	N	Silicone (-60 °C to +135 °C)

Because the enclosure in the example case operates in a temperature range of -40 °C bis +45 °C, a cable gland with a silicone seal has to be used.
Consequently is
[c] = „S" (Silicone)

2c) Selection of the plating [e]

All cable glands can be provided either with nickel plated surface "NI" or with self-coloured surface "SC".

In the example case the enclosure is used outdoor, therefore it can come into contact with water in form of rain, so that a cable gland with nickel plated surface as protection against corrosion and wear has to be selected. Consequently is [e] = „NI"

The generated information has to be filled into the order key below:

Order key	[Type]	[a]	[b]	[c]	[d]	[e]	[f]	[ggg]
Example Article Description	**KDSU**		**B**	**S**	**0**	**NI**		

3. Selection of the entry thread [a], the cable outer sheath variant [f] and the gland size [ggg]

Order key	[Type]	[a]	[b]	[c]	[d]	[e]	[f]	[ggg]
Example Article Description	**KDSU**		B	**S**	0	NI		

The suitable gland size [ggg] will be selected based on the inner and outer sheath diameters of the cable. Thereby the entry thread size [a] and the cable outer sheath variant [f] result.

In the example case the following diameters are given:

Cable Outer Sheath: 10 mm (By looking into the below shown dimensions chart of the KDSU the orange marked clamping ranges (Cable Outer Sheath [D]) can be selected).
Cable Inner Sheath: 8 mm (By looking into the below shown dimensions chart of the KDSU the orange marked clamping ranges (Cable Inner Sheath [C]) can be selected).

Dimensions

Gland Size	Entry thread	Entry thread Length	Max Outer Diameter	Max Length	Gland Seal Range						Armour Acceptance Range	Shroud Size
					Cable Inner Sheath [C]		Cable Outer Sheath [D]					
							Standard [f]=2		Reduced [f]=1			
[ggg]		[B]	[A]		Min	Max	Min	Max	Min	Max		
G16	M20	16	28.0	78.0	3.4	8.4	9.0	13.5	6.7	10.3	0.15 - 1.25	L24
G20S	M20	16	28.0	78.0	7.2	11.7	11.5	16.0	9.4	12.5	0.15 - 1.25	L24
G20	M20	16	33.0	78.0	9.4	14.0	15.5	21.1	12.0	17.6	0.15 - 1.25	EL30
G25	M25	16	41.4	90.0	13.5	20.0	20.3	27.4	16.8	23.9	0.15 - 1.60	EL38
G32	M32	16	50.6	105.0	19.5	26.3	26.7	34.0	23.2	30.5	0.15 - 2.00	EL46
G40	M40	16	60.5	113.0	23.0	32.2	33.0	40.6	28.6	36.2	0.20 - 2.00	EL55
G50S	M50	16	71.5	125.0	28.1	38.2	39.4	46.7	34.8	42.4	0.30 - 2.50	EL65
G50	M50	16	71.5	125.0	33.1	44.1	45.7	53.2	41.1	48.5	0.30 - 2.50	EL65
G63S	M63	19	88.0	125.0	39.2	50.1	52.1	59.5	47.5	54.8	0.30 - 2.50	EL80
G63	M63	19	88.0	125.0	46.7	56.0	58.4	65.8	53.8	61.2	0.30 - 2.50	EL80
G75S	M75	19	99.0	131.0	52.1	62.0	64.8	72.2	60.2	68.0	0.30 - 2.50	EL90
G75	M75	19	99.0	131.0	58.0	68.0	71.1	78.0	66.5	73.4	0.30 - 2.50	EL90
		All dimensions in mm										

By the selection of the inner [C] resp. outer [D] clamping range, a range should be used where the diameter of the cable outer and inner sheath are as near as possible to the average of the Min/Max Values. In doing so, the reduced cable outer sheath with the gland size G20S and the entry thread of M20 has to be selected.

Consequently is

[f]=1
[ggg]=G20S
[a]=M20

The generated information has to be filled into the order key below:

	[Type]	[a]	[b]	[c]	[d]	[e]	[f]	[ggg]
Order key	KDSU	M20	B	S	0	NI	1	G20S
Article description								

Resulting from the complete article description the relating order number (brown marked) can be determined.

Extract from table KDSU "Nickel-plated brass gland with silicone sealing" on page D.28

Order No.	Description	[Type]	[a]	[b]	[c]	[d]	[e]	[f]	[ggg]	Qty.
0930001221	KDSU M20 BS 0 NI 1 G16	KDSU	M20	B	S	0	NI	1	G16	20
0930001222	KDSU M20 BS 0 NI 2 G16	KDSU	M20	B	S	0	NI	2	G16	20
0930011223	KDSU M20 BS 0 NI 1 G20S	KDSU	M20	B	S	0	NI	1	G20S	20
0930011224	KDSU M20 BS 0 NI 2 G20S	KDSU	M20	B	S	0	NI	2	G20S	20
0930021221	KDSU M20 BS 0 NI 1 G20	KDSU	M20	B	S	0	NI	1	G20	20
...	...	...	...	...	...	...	...	...	...	...

Klippon® cable glands – Nickel–plated Brass – Ex e, Ex d, IP68 for armoured and non-armoured cables

All-purpose cable gland for cables and lines with single-wire armouring, metal-foil armouring and braided armouring. Non-armoured cables and lines can also be connected.



Technical data

Material	Brass, nickel-plated
O-Ring / Seal insert	NBR / CR
Temperature range	-35 °C...90 °C
Degree of protection	IP66, IP68 - 2.5 bar
Water depth	25 m (30 Min.)
Type of armouring	Single-wire armouring, Metal foil armouring, Braided armouring
Marking	ATEX: II 2G, Ex db IIC Gb, Ex eb IIC Gb, II 1D, Ex ta IIIC Da, IECEx: Ex db IIC Gb, Ex eb IIC Gb, Ex ta IIIC Da
Certificate no. (ATEX / IECEx / EAC)	SIRA 05ATEX1285X / IECEx SIR 05.0067X / RUC-DE.IT08.B.00594
Note	Length "L" depends on the cable diameter used. Cable glands made of brass with natural surface are available in the online catalogue (catalog.weidmueller.com).

Ordering data

Type	Thread	D1 outer cable Ø	D2 inner cable Ø	Cable armour	L/L1	SW	SUHB	Qty.	Order No.
metric, nickel-plated brass									
KDSU M20 BN O NI 1 G16	M 20	6.7-10.3	3.40-8.40	0.1-1.25	78 / 16	24	L24	20	**1083280000**
KDSU M20 BN O NI 2 G16	M 20	9-13.5	3.40-8.40	0.1-1.25	78 / 16	24	L24	20	**1911380000**
KDSU M20 BN O NI 1 G20S	M 20	9.4-12.5	7.20-11.70	0.1-1.25	78 / 16	24	L24	20	**1083290000**
KDSU M20 BN O NI 2 G20S	M 20	11.5-16	7.20-11.70	0.1-1.25	78 / 16	24	L24	20	**1911390000**
KDSU M20 BN O NI 1 G20	M 20	12-17.6	9.40-14.00	0.1-1.25	78 / 16	30	EL30	20	**1083320000**
KDSU M20 BN O NI 2 G20	M 20	15.5-21.1	9.40-14.00	0.1-1.25	78 / 16	30	EL30	20	**1911400000**
KDSU M25 BN O NI 1 G25	M 25	16.8-23.9	13.50-20.00	0.1-1.6	90 / 16	38	EL38	20	**1083330000**
KDSU M25 BN O NI 2 G25	M 25	20.3-27.4	13.50-20.00	0.1-1.6	90 / 16	38	EL38	20	**1911420000**
KDSU M32 BN O NI 1 G32	M 32	23.2-30.5	19.50-26.30	0.1-2	105 / 16	46	EL46	10	**1083340000**
KDSU M32 BN O NI 2 G32	M 32	26.7-34	19.50-26.30	0.1-2	105 / 16	46	EL46	10	**1911430000**
KDSU M40 BN O NI 1 G40	M 40	28.6-36.2	23.00-32.20	0.1-2	113 / 16	55	EL55	10	**1083350000**
KDSU M40 BN O NI 2 G40	M 40	33-40.6	23.00-32.20	0.1-2	113 / 16	55	EL55	10	**1911440000**
KDSU M50 BN O NI 1 G50	M 50	41.1-48.5	33.10-44.10	0.1-2.5	125 / 16	65	EL65	1	**1083370000**
KDSU M50 BN O NI 2 G50	M 50	45.7-53.2	33.10-44.10	0.1-2.5	125 / 16	65	EL65	1	**1911460000**
KDSU M50 BN O NI 1 G50S	M 50	34.8-42.4	28.10-38.20	0.1-2.5	125 / 16	65	EL65	1	**1083360000**
KDSU M50 BN O NI 2 G50S	M 50	39.4-46.7	28.10-38.20	0.1-2.5	125 / 16	65	EL65	1	**1911450000**
KDSU M63 BN O NI 1 G63S	M 63	47.5-54.8	39.20-50.10	0.1-2.5	125 / 19	80	EL80	1	**1083380000**
KDSU M63 BN O NI 2 G63S	M 63	52.1-59.5	39.20-50.10	0.1-2.5	125 / 19	80	EL80	1	**1911480000**
KDSU M63 BN O NI 1 G63	M 63	53.8-61.2	46.70-56.00	0.1-2.5	125 / 16	80	EL80	1	**1083390000**
KDSU M63 BN O NI 2 G63	M 63	58.4-65.8	46.70-56.00	0.1-2.5	125 / 19	80	EL80	1	**1911490000**
KDSU M75 BN O NI 1 G75S	M 75	60.2-68	52.10-62.00	0.1-2.5	131 / 19	90	EL90	1	**1083400000**
KDSU M75 BN O NI 2 G75S	M 75	64.8-72.2	52.10-62.00	0.1-2.5	131 / 19	90	EL90	1	**1083410000**
KDSU M75 BN O NI 1 G75	M 75	66.5-73.4	58.00-68.00	0.1-2.5	131 / 19	90	EL90	1	**1083420000**
KDSU M75 BN O NI 2 G75	M 75	71.1-78	58.00-68.00	0.1-2.5	131 / 19	90	EL90	1	**1083430000**

Note

- All cable glands have a thread pitch of 1.5 mm.
- In the case of Ex d applications, the inner threads used for cable glands must meet the requirements of section 5.3 of EN/IEC 60079-1. In the screwed in position, at least 5 threads must be engaged.
- If the cable glands are installed in non-metallic Ex e connection equipment, these must be connected to the protective earth of the system.
- The connection cable must be laid securely and inflexibly to rule out tensile stress.
- Installation specifications and tightening torques can be found in the installation instructions. For further information please use our online catalogue: catalog.weidmueller.com.

Klippon® cable glands – Nickel–plated Brass – Ex e, Ex d, IP68 for armoured and non-armoured cables

All-purpose cable gland for cables and lines with single-wire armouring, metal-foil armouring and braided armouring. Non-armoured cables and lines can also be connected.



Technical data

Material	Brass, nickel-plated
O-Ring / Seal insert	Silicone / Silicone
Temperature range	-60 °C...180 °C
Degree of protection	IP66, IP68 - 2.5 bar
Water depth	25 m (30 Min.)
Type of armouring	Single-wire armouring, Metal foil armouring, Braided armouring
Marking	ATEX: II 2G, Ex db IIC Gb, Ex eb IIC Gb, II 1D, Ex ta IIIC Da, IECEx: Ex db IIC Gb, Ex eb IIC Gb, Ex ta IIIC Da
Certificate no. (ATEX / IECEx / EAC)	SIRA 05ATEX1285X / IECEx SIR 05.0067X / RUC-DE.IT08.B.00594
Note	Length "L" depends on the cable diameter used. Cable glands made of brass with natural surface are available in the online catalogue (catalog.weidmueller.com).

Ordering data

Type	Thread	D1 outer cable Ø	D2 inner cable Ø	Cable armour	L/L1	SW	SUHB	Qty.	Order No.
metric, nickel-plated brass									
KDSU M20 BS O NI 1 G16	M 20	6.7-10.3	3.40-8.40	0.1-1.25	78 / 16	24	L24	20	**0930001221**
KDSU M20 BS O NI 2 G16	M 20	9-13.5	3.40-8.40	0.1-1.25	78 / 16	24	L24	20	**0930001222**
KDSU M20 BS O NI 1 G20	M 20	12-17.6	9.40-14.00	0.1-1.25	78 / 16	30	EL30	20	**0930021221**
KDSU M20 BS O NI 2 G20	M 20	15.5-21.1	9.40-14.00	0.1-1.25	78 / 16	30	EL30	20	**0930021222**
KDSU M20 BS O NI 1 G20S	M 20	9.4-12.5	7.20-11.70	0.1-1.25	78 / 16	24	L24	20	**0930011223**
KDSU M20 BS O NI 2 G20S	M 20	11.5-16	7.20-11.70	0.1-1.25	78 / 16	24	L24	20	**0930011224**
KDSU M25 BS O NI 1 G25	M 25	16.8-23.9	13.50-20.00	0.1-1.6	90 / 16	38	EL38	20	**0930031221**
KDSU M25 BS O NI 2 G25	M 25	20.3-27.4	13.50-20.00	0.1-1.6	90 / 16	38	EL38	1	**0930031222**
KDSU M32 BS O NI 1 G32	M 32	23.2-30.5	19.50-26.30	0.1-2	105 / 16	46	EL46	10	**0930041221**
KDSU M32 BS O NI 2 G32	M 32	26.7-34	19.50-26.30	0.1-2	105 / 16	46	EL46	10	**0930041222**
KDSU M40 BS O NI 1 G40	M 40	28.6-36.2	23.00-32.20	0.1-2	113 / 16	55	EL55	10	**1136990000**
KDSU M40 BS O NI 2 G40	M 40	33-40.6	23.00-32.20	0.1-2	113 / 16	55	EL55	10	**0930051222**
KDSU M50 BS O NI 1 G50	M 50	41.1-48.5	33.10-44.10	0.1-2.5	125 / 16	65	EL65	1	**1137010000**
KDSU M50 BS O NI 2 G50	M 50	45.7-53.2	33.10-44.10	0.1-2.5	125 / 16	65	EL65	1	**1137020000**
KDSU M50 BS O NI 1 G50S	M 50	34.8-42.4	28.10-38.20	0.1-2.5	125 / 16	65	EL65	1	**1137000000**
KDSU M50 BS O NI 2 G50S	M 50	39.4-46.7	28.10-38.20	0.1-2.5	125 / 16	65	EL65	1	**0930061224**
KDSU M63 BS O NI 1 G63	M 63	53.8-61.2	46.70-56.00	0.1-2.5	125 / 19	80	EL80	1	**1137050000**
KDSU M63 BS O NI 2 G63	M 63	58.4-65.8	46.70-56.00	0.1-2.5	125 / 19	80	EL80	1	**0930091222**
KDSU M63 BS O NI 1 G63S	M 63	47.5-54.8	39.20-50.10	0.1-2.5	125 / 19	80	EL80	1	**1137030000**
KDSU M63 BS O NI 2 G63S	M 63	52.1-59.5	39.20-50.10	0.1-2.5	125 / 19	80	EL80	1	**1137040000**
KDSU M75 BS O NI 1 G75	M 75	66.5-73.4	58.00-68.00	0.1-2.5	131 / 19	90	EL90	1	**1137080000**
KDSU M75 BS O NI 2 G75	M 75	71.1-78	58.00-68.00	0.1-2.5	131 / 19	90	EL90	1	**1137090000**
KDSU M75 BS O NI 1 G75S	M 75	60.2-68	52.10-62.00	0.1-2.5	131 / 19	90	EL90	1	**1137060000**
KDSU M75 BS O NI 2 G75S	M 75	64.8-72.2	52.10-62.00	0.1-2.5	131 / 19	90	EL90	1	**1137070000**

Note

- All cable glands have a thread pitch of 1.5 mm.
- In the case of Ex d applications, the inner threads used for cable glands must meet the requirements of section 5.3 of EN/IEC 60079-1. In the screwed in position, at least 5 threads must be engaged.
- If the cable glands are installed in non-metallic Ex e connection equipment, these must be connected to the protective earth of the system.
- The connection cable must be laid securely and inflexibly to rule out tensile stress.
- Installation specifications and tightening torques can be found in the installation instructions. For further information please use our online catalogue: catalog.weidmueller.com.

Klippon® cable glands – Nickel–plated Brass – Ex e, Ex d, IP66 / IP68 for armoured cables

Cable gland for cables and lines with single-wire armouring.



Technical data

Material	Brass, nickel-plated
Seal insert	CR
Temperature range	-35 °C...90 °C
Protection class	IP54
Protection degree with GWDR	IP66, IP68 - 2.5 bar
Water depth	25 m (30 Min.)
Type of armouring	Single-wire armouring
Marking	ATEX: II 2G, Ex db IIC Gb, Ex eb IIC Gb, II 1D, Ex ta IIIC Da, IECEx: Ex db IIC Gb, Ex eb IIC Gb, Ex ta IIIC Da
Certificate no. (ATEX / IECEx / EAC)	SIRA 05ATEX1286X / IECEx SIR 05.0067X / RUC-DE.IT08.B.00594
Note	Length "L" depends on the cable diameter used. IP protection without GWDR is IP54. To achieve IP66 / IP68 protection, a nylon GWDR must be ordered separately. Cable glands made of brass with natural surface are available in the online catalogue (catalog.weidmueller.com).

Ordering data

Type	Thread	D1 outer cable Ø	D2 inner cable Ø	Cable armour	L/L1	SW	SUHB	Qty.	Order No.
metric, nickel-plated brass									
KDSW M20 BN 0 NI 1 G16	M 20	4.9-10.3	3.50-8.40	0.9	58 / 16	24	L24	20	**1075030000**
KDSW M20 BN 0 NI 2 G16	M 20	8.4-13.5	3.50-8.40	0.9	58 / 16	24	L24	20	**1075040000**
KDSW M20 BN 0 NI 1 G20	M 20	12-17.6	6.70-14.00	0.9-1.25	58 / 16	30	L30	20	**1075070000**
KDSW M20 BN 0 NI 2 G20	M 20	15.5-21.1	6.70-14.00	0.9-1.25	58 / 16	30	L30	20	**1075080000**
KDSW M20 BN 0 NI 1 G20S	M 20	9.4-12.5	8.00-11.70	0.9-1.25	58 / 16	30	L24	20	**1075050000**
KDSW M20 BN 0 NI 2 G20S	M 20	11.5-16	8.00-11.70	0.9-1.25	58 / 16	24	L24	20	**1075060000**
KDSW M25 BN 0 NI 1 G25	M 25	16.8-23.9	13.00-20.00	1.25-1.6	58 / 16	38	L38	20	**1075090000**
KDSW M25 BN 0 NI 2 G25	M 25	20.3-27.4	13.00-20.00	1.25-1.6	58 / 16	38	L38	20	**1075110000**
KDSW M32 BN 0 NI 1 G32	M 32	23.2-30.5	19.00-26.30	1.6-2	65 / 16	46	L46	10	**1075120000**
KDSW M32 BN 0 NI 2 G32	M 32	26.7-34	19.00-26.30	1.6-2	65 / 16	46	L46	10	**1075130000**
KDSW M40 BN 0 NI 1 G40	M 40	28.6-36.2	25.00-32.20	1.6-2	72 / 16	55	L55	10	**1075140000**
KDSW M40 BN 0 NI 2 G40	M 40	33-40.6	25.00-32.20	1.6-2	72 / 16	55	L55	10	**1075150000**
KDSW M50 BN 0 NI 1 G50	M 50	41.1-48.5	36.50-44.10	2-2.5	73 / 16	65	L65	1	**1075180000**
KDSW M50 BN 0 NI 2 G50	M 50	45.7-53.2	36.50-44.10	2-2.5	73 / 16	65	L65	1	**1075190000**
KDSW M50 BN 0 NI 1 G50S	M 50	34.8-42.4	31.50-38.20	2-2.5	73 / 16	65	L65	1	**1075160000**
KDSW M50 BN 0 NI 2 G50S	M 50	39.4-46.7	31.50-38.20	2-2.5	73 / 16	65	L65	1	**1075170000**
KDSW M63 BN 0 NI 1 G63	M 63	53.8-61.2	49.50-56.00	2.5	76 / 19	80	L80	1	**1075230000**
KDSW M63 BN 0 NI 2 G63	M 63	58.4-65.8	49.50-56.00	2.5	76 / 19	80	L80	1	**1075240000**
KDSW M63 BN 0 NI 1 G63S	M 63	47.5-54.8	42.50-50.10	2.5	76 / 19	80	L80	1	**1075210000**
KDSW M63 BN 0 NI 2 G63S	M 63	52.1-59.5	42.50-50.10	2.5	76 / 19	80	L80	1	**1075220000**
KDSW M75 BN 0 NI 1 G75	M 75	66.5-73.4	60.50-68.00	2.5	82 / 19	90	L90	1	**1075270000**
KDSW M75 BN 0 NI 2 G75	M 75	71.1-78	60.50-68.00	2.5	82 / 19	90	L90	1	**1075280000**
KDSW M75 BN 0 NI 1 G75S	M 75	60.2-68	54.50-62.00	2.5	82 / 19	90	L90	1	**1075250000**
KDSW M75 BN 0 NI 2 G75S	M 75	64.8-72.2	54.50-62.00	2.5	82 / 19	90	L90	1	**1075260000**

Note

- All cable glands have a thread pitch of 1.5 mm.
- In the case of Ex d applications, the inner threads used for cable glands must meet the requirements of section 5.3 of EN/IEC 60079-1. In the screwed in position, at least 5 threads must be engaged.
- If the cable glands are installed in non-metallic Ex e connection equipment, these must be connected to the protective earth of the system.
- The connection cable must be laid securely and inflexibly to rule out tensile stress.
- Installation specifications and tightening torques can be found in the installation instructions. For further information please use our online catalogue: catalog.weidmueller.com.

Klippon® cable glands – Nickel–plated Brass – Ex e, Ex d, IP66 / IP68 for armoured cables

Cable gland for cables and lines with single-wire armouring.



Technical data

Material	Brass, nickel-plated
Seal insert	Silicone
Temperature range	-60 °C...180 °C
Protection class	IP54
Protection degree with GWDR	IP66, IP68 - 2.5 bar
Water depth	25 m (30 Min.)
Type of armouring	Single-wire armouring
Marking	ATEX: II 2G, Ex db IIC Gb, Ex eb IIC Gb, II 1D, Ex ta IIIC Da, IECEx: Ex db IIC Gb, Ex eb IIC Gb, Ex ta IIIC Da
Certificate no. (ATEX / IECEx / EAC)	SIRA 05ATEX1286X / IECEx SIR 05.0067X / RUC-DE.IT08.B.00594
Note	Length "L" depends on the cable diameter used. IP protection without GWDR is IP54. To achieve IP66 / IP68 protection, a nylon GWDR must be ordered separately. Cable glands made of brass with natural surface are available in the online catalogue (catalog.weidmueller.com).

Ordering data

Type	Thread	D1 outer cable Ø	D2 inner cable Ø	Cable armour	L/L1	SW	SUHB	Qty.	Order No.
metric, nickel-plated brass									
KDSW M20 BS O NI 1 G16	M 20	4.9-10.3	3.50-8.40	0.9	58 / 16	24	L24	20	**1136410000**
KDSW M20 BS O NI 2 G16	M 20	8.4-13.5	3.50-8.40	0.9	58 / 16	24	L24	20	**1136420000**
KDSW M20 BS O NI 1 G20	M 20	12-17.6	9.30-14.00	0.9-1.25	58 / 16	30	L30	20	**1136450000**
KDSW M20 BS O NI 2 G20	M 20	15.5-21.1	9.30-14.00	0.9-1.25	58 / 16	30	L30	20	**1136460000**
KDSW M20 BS O NI 1 G20S	M 20	9.4-12.5	8.00-11.70	0.9-1.25	58 / 16	30	L24	20	**1136430000**
KDSW M20 BS O NI 2 G20S	M 20	11.5-16	8.00-11.70	0.9-1.25	58 / 16	24	L24	20	**1136440000**
KDSW M25 BS O NI 1 G25	M 25	16.8-23.9	13.00-20.00	1.25-1.6	58 / 16	38	L38	20	**1136470000**
KDSW M25 BS O NI 2 G25	M 25	20.3-27.4	13.00-20.00	1.25-1.6	58 / 16	38	L38	20	**1136480000**
KDSW M32 BS O NI 1 G32	M 32	23.2-30.5	19.00-26.30	1.6-2	65 / 16	46	L46	10	**1136490000**
KDSW M32 BS O NI 2 G32	M 32	26.7-34	19.00-26.30	1.6-2	65 / 16	46	L46	10	**1136510000**
KDSW M40 BS O NI 1 G40	M 40	28.6-36.2	25.00-32.20	1.6-2	72 / 16	55	L55	10	**1136520000**
KDSW M40 BS O NI 2 G40	M 40	33-40.6	25.00-32.20	1.6-2	72 / 16	55	L55	10	**1136530000**
KDSW M50 BS O NI 1 G50	M 50	41.1-48.5	36.50-44.10	2-2.5	73 / 16	65	L65	1	**1136560000**
KDSW M50 BS O NI 2 G50	M 50	45.7-53.2	36.50-44.10	2-2.5	73 / 16	65	L65	1	**1136570000**
KDSW M50 BS O NI 1 G50S	M 50	34.8-42.4	31.50-38.20	2-2.5	73 / 16	65	L65	1	**1136540000**
KDSW M50 BS O NI 2 G50S	M 50	39.4-46.7	31.50-38.20	2-2.5	73 / 16	65	L65	1	**1136550000**
KDSW M63 BS O NI 1 G63	M 63	53.8-61.2	49.50-56.00	2.5	76 / 19	80	L80	1	**1136600000**
KDSW M63 BS O NI 2 G63	M 63	58.4-65.8	49.50-56.00	2.5	76 / 19	80	L80	1	**1136610000**
KDSW M63 BS O NI 1 G63S	M 63	47.5-54.8	42.50-50.10	2.5	76 / 19	80	L80	1	**1136580000**
KDSW M63 BS O NI 2 G63S	M 63	52.1-59.5	42.50-50.10	2.5	76 / 19	80	L80	1	**1136590000**
KDSW M75 BS O NI 1 G75	M 75	66.5-73.4	60.50-68.00	2.5	82 / 19	90	L90	1	**1136640000**
KDSW M75 BS O NI 2 G75	M 75	71.1-78	60.50-68.00	2.5	82 / 19	90	L90	1	**1136650000**
KDSW M75 BS O NI 1 G75S	M 75	60.2-68	54.50-62.00	2.5	82 / 19	90	L90	1	**1136620000**
KDSW M75 BS O NI 2 G75S	M 75	64.8-72.2	54.50-62.00	2.5	82 / 19	90	L90	1	**1136630000**

Note

- All cable glands have a thread pitch of 1.5 mm.
- In the case of Ex d applications, the inner threads used for cable glands must meet the requirements of section 5.3 of EN/IEC 60079-1. In the screwed in position, at least 5 threads must be engaged.
- If the cable glands are installed in non-metallic Ex e connection equipment, these must be connected to the protective earth of the system.
- The connection cable must be laid securely and inflexibly to rule out tensile stress.
- Installation specifications and tightening torques can be found in the installation instructions. For further information please use our online catalogue: catalog.weidmueller.com.

Klippon® cable glands – Nickel–plated Brass – Ex e, Ex d, IP66 / IP68 for armoured cables

Cable gland for cables and lines with single-wire armouring and lead-sheath armouring.



Technical data

Material	Brass, nickel-plated
Seal insert	CR
Temperature range	-35 °C...90 °C
Protection class	IP54
Protection degree with GWDR	IP66, IP68 - 2.5 bar
Water depth	25 m (30 Min.)
Type of armouring	Single-wire armouring, Lead sheath armouring
Marking	ATEX: II 2G, Ex db IIC Gb, Ex eb IIC Gb, II 1D, Ex ta IIIC Da, IECEx: Ex db IIC Gb, Ex eb IIC Gb, Ex ta IIIC Da
Certificate no. (ATEX / IECEx / EAC)	SIRA 05ATEX1286X / IECEx SIR 05.0067X / RUC-DE.IT08.B.00594
Note	Length "L" depends on the cable diameter used. IP protection without GWDR is IP54. To achieve IP66 / IP68 protection, a nylon GWDR must be ordered separately. Cable glands made of brass with natural surface are available in the online catalogue (catalog.weidmueller.com).

Ordering data

Type	Thread	D1 outer cable Ø	D2 inner cable Ø	Cable armour	L/L1	SW	SUHB	Qty.	Order No.
metric, nickel-plated brass									
KDSW M20 BN L NI 1 G16	M 20	4.9-10.3	3.50-8.40	0.9	58 / 16	24	L24	20	**1074660000**
KDSW M20 BN L NI 2 G16	M 20	8.4-13.5	3.50-8.40	0.9	58 / 16	24	L24	20	**1074690000**
KDSW M20 BN L NI 1 G20	M 20	12-17.6	6.70-14.00	0.9-1.25	58 / 16	30	L30	20	**1074760000**
KDSW M20 BN L NI 2 G20	M 20	15.5-21.1	6.70-14.00	0.9-1.25	58 / 16	30	L30	20	**1074780000**
KDSW M20 BN L NI 1 G20S	M 20	9.4-12.5	8.00-11.70	0.9-1.25	58 / 16	24	L24	20	**1074720000**
KDSW M20 BN L NI 2 G20S	M 20	11.5-16	8.00-11.70	0.9-1.25	58 / 16	24	L24	20	**1074740000**
KDSW M25 BN L NI 1 G25	M 25	16.8-23.9	13.00-20.00	1.25-1.6	58 / 16	38	L38	20	**1074810000**
KDSW M25 BN L NI 2 G25	M 25	20.3-27.4	13.00-20.00	1.25-1.6	58 / 16	38	L38	20	**1074830000**
KDSW M32 BN L NI 1 G32	M 32	23.2-30.5	19.00-26.30	1.6-2	65 / 16	46	L46	10	**1074850000**
KDSW M32 BN L NI 2 G32	M 32	26.7-34	19.00-26.30	1.6-2	65 / 16	46	L46	10	**1074860000**
KDSW M40 BN L NI 1 G40	M 40	28.6-36.2	25.00-32.20	1.6-2	72 / 16	55	L55	10	**1074870000**
KDSW M40 BN L NI 2 G40	M 40	33-40.6	25.00-32.20	1.6-2	72 / 16	55	L55	10	**1074880000**
KDSW M50 BN L NI 1 G50	M 50	41.4-48.5	36.50-44.10	2-2.5	73 / 16	65	L65	1	**1074920000**
KDSW M50 BN L NI 2 G50	M 50	45.7-53.2	36.50-44.10	2-2.5	73 / 16	65	L65	1	**1074930000**
KDSW M50 BN L NI 1 G50S	M 50	34.8-42.4	31.50-38.20	2-2.5	73 / 16	65	L65	1	**1074890000**
KDSW M50 BN L NI 2 G50S	M 50	39.4-46.7	31.50-38.20	2-2.5	73 / 16	65	L65	1	**1074910000**
KDSW M63 BN L NI 1 G63	M 63	53.8-61.2	49.50-56.00	2.5	76 / 19	80	L80	1	**1074960000**
KDSW M63 BN L NI 2 G63	M 63	58.4-65.8	49.50-56.00	2.5	76 / 19	80	L80	1	**1074970000**
KDSW M63 BN L NI 1 G63S	M 63	47.5-54.8	42.50-50.10	2.5	76 / 19	80	L80	1	**1074940000**
KDSW M63 BN L NI 2 G63S	M 63	52.1-59.5	42.50-50.10	2.5	76 / 19	80	L80	1	**1074950000**
KDSW M75 BN L NI 1 G75	M 75	66.5-73.4	60.50-68.00	2.5	82 / 19	90	L90	1	**1075010000**
KDSW M75 BN L NI 2 G75	M 75	71.1-78	60.50-68.00	2.5	82 / 19	90	L90	1	**1075020000**
KDSW M75 BN L NI 1 G75S	M 75	60.2-68	54.50-62.00	2.5	82 / 19	90	L90	1	**1074980000**
KDSW M75 BN L NI 2 G75S	M 75	64.8-72.2	54.50-62.00	2.5	82 / 19	90	L90	1	**1074990000**

Note

- All cable glands have a thread pitch of 1.5 mm.
- In the case of Ex d applications, the inner threads used for cable glands must meet the requirements of section 5.3 of EN/IEC 60079-1. In the screwed in position, at least 5 threads must be engaged.
- If the cable glands are installed in non-metallic Ex e connection equipment, these must be connected to the protective earth of the system.
- The connection cable must be laid securely and inflexibly to rule out tensile stress.
- Installation specifications and tightening torques can be found in the installation instructions. For further information please use our online catalogue: catalog.weidmueller.com.

Klippon® cable glands – Nickel–plated Brass – Ex e, Ex d, IP66 / IP68 for armoured cables

Cable gland for cables and lines with braided armouring.



Technical data

Material	Brass, nickel-plated
Seal insert	Silicone
Temperature range	-60 °C...180 °C
Protection class	IP54
Protection degree with GWDR	IP66, IP68 - 2.5 bar
Water depth	25 m (30 Min.)
Type of armouring	Braided armouring
Marking	ATEX: II 2G, Ex db IIC Gb, Ex eb IIC Gb, II 1D, Ex ta IIIC Da, IECEx: Ex db IIC Gb, Ex eb IIC Gb, Ex ta IIIC Da
Certificate no. (ATEX / IECEx / EAC)	SIRA 05ATEX1286X / IECEx SIR 05.0067X / RUC-DE.IT08.B.00594
Note	Length "L" depends on the cable diameter used. IP protection without GWDR is IP54. To achieve IP66 / IP68 protection, a nylon GWDR must be ordered separately. Cable glands made of brass with natural surface are available in the online catalogue (catalog.weidmueller.com).

Ordering data

Type	Thread	D1 outer cable Ø	D2 inner cable Ø	Cable armour	L/L1	SW	SUHB	Qty.	Order No.
metric, nickel-plated brass									
KDSX M20 BS O NI 1 G16	M 20	4.9-10.3	3.50-8.40	0.15-0.35	58 / 16	24	L24	20	**1135910000**
KDSX M20 BS O NI 2 G16	M 20	8.4-13.5	3.50-8.40	0.15-0.35	58 / 16	24	L24	20	**1135920000**
KDSX M20 BS O NI 1 G20	M 20	12-17.6	9.30-14.00	0.15-0.5	58 / 16	30	L30	20	**1135950000**
KDSX M20 BS O NI 2 G20	M 20	15.5-21.1	9.30-14.00	0.15-0.5	58 / 16	30	L30	20	**1135960000**
KDSX M20 BS O NI 1 G20S	M 20	9.4-12.5	8.00-11.70	0.15-0.35	58 / 16	24	L24	20	**1135930000**
KDSX M20 BS O NI 2 G20S	M 20	11.5-16	8.00-11.70	0.15-0.35	58 / 16	24	L24	20	**1135940000**
KDSX M25 BS O NI 1 G25	M 25	16.8-23.9	13.00-20.00	0.15-0.5	58 / 16	38	L38	20	**1135970000**
KDSX M25 BS O NI 2 G25	M 25	20.3-27.4	13.00-20.00	0.15-0.5	58 / 16	38	L38	20	**1135980000**
KDSX M32 BS O NI 1 G32	M 32	23.2-30.5	19.00-26.30	0.15-0.55	65 / 16	46	L46	10	**1135990000**
KDSX M32 BS O NI 2 G32	M 32	26.7-34	19.00-26.30	0.15-0.55	65 / 16	46	L46	10	**1136000000**
KDSX M40 BS O NI 1 G40	M 40	28.6-36.2	25.00-32.20	0.2-0.6	72 / 16	55	L55	10	**1136010000**
KDSX M40 BS O NI 2 G40	M 40	33-40.6	25.00-32.20	0.2-0.6	72 / 16	55	L55	10	**1136020000**
KDSX M50 BS O NI 1 G50	M 50	41.1-48.5	36.50-44.10	0.5-0.8	73 / 16	65	L65	1	**1136050000**
KDSX M50 BS O NI 2 G50	M 50	45.7-53.2	36.50-44.10	0.5-0.8	73 / 16	65	L65	1	**1136060000**
KDSX M50 BS O NI 1 G50S	M 50	34.8-42.4	31.50-38.20	0.2-0.6	73 / 16	65	L65	1	**1136030000**
KDSX M50 BS O NI 2 G50S	M 50	39.4-46.7	31.50-38.20	0.2-0.6	73 / 16	65	L65	1	**1136040000**
KDSX M63 BS O NI 1 G63	M 63	53.8-61.2	49.50-56.00	0.5-0.8	76 / 19	80	L80	1	**1136090000**
KDSX M63 BS O NI 2 G63	M 63	58.4-65.8	49.50-56.00	0.5-0.8	76 / 19	80	L80	1	**1136110000**
KDSX M63 BS O NI 1 G63S	M 63	47.5-54.8	42.50-50.10	0.5-0.8	76 / 19	80	L80	1	**1136070000**
KDSX M63 BS O NI 2 G63S	M 63	52.1-59.5	42.50-50.10	0.5-0.8	76 / 19	80	L80	1	**1136080000**
KDSX M75 BS O NI 1 G75	M 75	66.5-73.4	60.50-68.00	0.5-1	82 / 19	90	L90	1	**1136140000**
KDSX M75 BS O NI 2 G75	M 75	71.1-78	60.50-68.00	0.5-1	82 / 19	90	L90	1	**1136150000**
KDSX M75 BS O NI 1 G75S	M 75	60.2-68	54.50-62.00	0.5-1	82 / 19	90	L90	1	**1136120000**
KDSX M75 BS O NI 2 G75S	M 75	64.8-72.2	54.50-62.00	0.5-1	82 / 19	90	L90	1	**1136130000**

Note

- All cable glands have a thread pitch of 1.5 mm.
- In the case of Ex d applications, the inner threads used for cable glands must meet the requirements of section 5.3 of EN/IEC 60079-1. In the screwed in position, at least 5 threads must be engaged.
- If the cable glands are installed in non-metallic Ex e connection equipment, these must be connected to the protective earth of the system.
- The connection cable must be laid securely and inflexibly to rule out tensile stress.
- Installation specifications and tightening torques can be found in the installation instructions. For further information please use our online catalogue: catalog.weidmueller.com.

Klippon® cable glands – Nickel–plated Brass – Ex e, Ex d, IP66 / IP68 for non-armoured cables

Cable gland exclusively for non-armoured cables and lines.



Technical data

Material	Brass, nickel-plated
O-ring / Seal insert	CR / CR
Temperature range	-35 °C...90 °C
Degree of protection	IP66, IP68 - 2.5 bar
Water depth	25 m (30 Min.)
Marking	ATEX: II 2GD, Ex db IIC Gb, Ex ta IIIC Da and/or II 2 GD, Ex eb IIC Gb, Ex ta IIIC Da, IECEx: Ex db IIC Gb, Ex eb IIC Gb, Ex ta IIIC Da
Certificate no. (ATEX / IECEx / EAC)	SIRA 05ATEX1287X / IECEx SIR 05.0067X / RUC-DE.IT08.B.00594
Note	Length "L" depends on the cable diameter used. Cable glands made of brass with natural surface are available in the online catalogue (catalog.weidmueller.com).

Ordering data

Type	Thread	KB	L/L1	SW	SUHB	Qty.	Order No.
metric, nickel-plated brass							
KSG M20 BN O NI 2 G16	M 20	4-8.4	33 / 16	25	L24	20	**1911510000**
KSG M20 BN O NI 2 G20S	M 20	7.2-11.7	33 / 16	25	L24	20	**1911540000**
KSG M20 BN O NI 2 G20	M 20	9.6-14	33 / 16	30	L30	20	**1911560000**
KSG M25 BN O NI 2 G25	M 25	13.5-20	33 / 16	38	L38	20	**1911570000**
KSG M32 BN O NI 2 G32	M 32	19.5-26.3	33 / 16	46	L46	10	**1911580000**
KSG M40 BN O NI 2 G40	M 40	23-32.2	37 / 16	55	L55	10	**1911590000**
KSG M50 BN O NI 2 G50S	M 50	28.1-38.2	37 / 16	65	L65	1	**1911600000**
KSG M50 BN O NI 2 G50	M 50	33.1-44.1	37 / 16	65	L65	1	**1911610000**
KSG M63 BN O NI 2 G63S	M 63	39.2-50.1	37 / 19	80	L80	1	**1911620000**
KSG M63 BN O NI 2 G63	M 63	46.7-56	37 / 19	80	L80	1	**1911630000**
KSG M75 BN O NI 2 G75	M 75	58-68	37 / 19	90	L90	1	**1075360000**
KSG M75 BN O NI 2 G75S	M 75	52.1-62	37 / 19	90	L90	1	**1075350000**

Note

- All cable glands have a thread pitch of 1.5 mm.
- In the case of Ex d applications, the inner threads used for cable glands must meet the requirements of section 5.3 of EN/IEC 60079-1. In the screwed in position, at least 5 threads must be engaged.
- If the cable glands are installed in non-metallic Ex e connection equipment, these must be connected to the protective earth of the system.
- The connection cable must be laid securely and inflexibly to rule out tensile stress.
- Installation specifications and tightening torques can be found in the installation instructions. For further information please use our online catalogue: catalog.weidmueller.com.

Klippon® cable glands – Brass – Ex e, Ex d, IP66 / IP68 for non-armoured cables

Cable gland exclusively for non-armoured cables and lines.



Technical data

Material	Brass, nickel-plated
O-ring / Seal insert	Silicone / Silicone
Temperature range	-60 °C...180 °C
Degree of protection	IP66, IP68 - 2.5 bar
Water depth	25 m (30 Min.)
Marking	ATEX: II 2GD, Ex db IIC Gb, Ex ta IIIC Da and/or II 2 GD, Ex eb IIC Gb, Ex ta IIIC Da, IECEx: Ex db IIC Gb, Ex eb IIC Gb, Ex ta IIIC Da
Certificate no. (ATEX / IECEx / EAC)	SIRA 05ATEX1287X / IECEx SIR 05.0067X / RUC-DE.IT08.B.00594
Note	Length "L" depends on the cable diameter used. Cable glands made of brass with natural surface are available in the online catalogue (catalog.weidmueller.com).

Ordering data

Type	Thread	KB	L/L1	SW	SUHB	Qty.	Order No.
metric, nickel-plated brass							
KSG M20 BS O NI 2 G16	M 20	4-8.4	33 / 16	25	L24	20	**0930481222**
KSG M20 BS O NI 2 G20	M 20	9.6-14	33 / 16	25	L30	20	**0930501222**
KSG M20 BS O NI 2 G20S	M 20	7.2-11.7	33 / 16	25	L24	20	**0930491224**
KSG M25 BS O NI 2 G25	M 25	13.5-20	33 / 16	38	L38	20	**0930511222**
KSG M32 BS O NI 2 G32	M 32	19.5-26.3	33 / 16	46	L46	10	**0930521222**
KSG M40 BS O NI 2 G40	M 40	23-32.2	37 / 16	55	L55	10	**0930531222**
KSG M50 BS O NI 2 G50	M 50	33.1-44.1	37 / 16	65	L65	1	**1136670000**
KSG M50 BS O NI 2 G50S	M 50	28.1-38.2	37 / 16	65	L65	1	**1136660000**
KSG M63 BS O NI 2 G63	M 63	46.7-56	37 / 19	80	L80	1	**1136690000**
KSG M63 BS O NI 2 G63S	M 63	39.2-50.1	37 / 19	80	L80	1	**1136680000**
KSG M75 BS O NI 2 G75	M 75	58-68	37 / 19	90	L90	1	**1136710000**
KSG M75 BS O NI 2 G75S	M 75	52.1-62	37 / 19	90	L90	1	**1136700000**

Note

- All cable glands have a thread pitch of 1.5 mm.
- In the case of Ex d applications, the inner threads used for cable glands must meet the requirements of section 5.3 of EN/IEC 60079-1. In the screwed in position, at least 5 threads must be engaged.
- If the cable glands are installed in non-metallic Ex e connection equipment, these must be connected to the protective earth of the system.
- The connection cable must be laid securely and inflexibly to rule out tensile stress.
- Installation specifications and tightening torques can be found in the installation instructions. For further information please use our online catalogue: catalog.weidmueller.com.

Ex cable glands – Brass – Nickel plated – Ex e, Ex d, IP 66 / IP 68 for non-armoured cables

Cable gland made from brass exclusively for non-armoured cables and lines. This Ex e/d approved screw connection has multiply divisible seal inserts (onion rings) to cover the greatest possible clamping range.



Technical data

Material	Brass, nickel-plated
O-ring / Seal insert	NBR / CR
Temperature range	-40 °C...100 °C
Degree of protection	IP66, IP68
Marking	Ex d IIC Gb, Ex e IIC Gb, Ex tb IIIC Db IP66/68
Note	Length "L" depends on the cable diameter used. Cable glands made of brass with natural surface are available in the online catalogue (catalog.weidmueller.com).

Ordering data

Type	Thread	KB	L/L1	SW	Qty.	Order No.
VG M16 EXE MS	M 16	3-12	46 / 16	22	50	**1460040000**
VG M20 EXE MS	M 20	3-12	43 / 16	22	50	**1460050000**
VG M25 EXE MS	M 25	10-18	45.5 / 16	28	20	**1460070000**
VG M32 EXE MS	M 32	14-24	49 / 16	35	20	**1460080000**
VG M40 EXE MS	M 40	22-32	59 / 18	45	10	**1460090000**
VG M50 EXE MS	M 50	35-44	61.5 / 18	64	5	**1460100000**
VG M63 EXE MS	M 63	46-56	69.5 / 18	80	5	**1460110000**

Note Installation specifications and tightening torques can be found in the installation instructions.
For further information please use our online catalogue: catalog.weidmueller.com.

Safeguard processes in potentially explosive atmospheres

Ex cable glands for safe devices as per EN 60079-0:2012 + A11 : 2013

The environmental conditions in many industry and explosion-proof applications pose a real challenge for the system components. Dust, vibrations, moisture and extreme temperatures all have an impact on the installed devices and the cable glands must also be able to withstand these stresses too.

Ex cable glands from Weidmüller guarantee process reliability in demanding environments. They are designed such that they can be used universally in any enclosure series. They are also just as easy to use in both high and low-temperature environments.

With impact resistance of 7 Joules, the explosion-proof polyamide cable glands offer extremely high levels of protection against external influences such as shocks or impacts. Together with their suitability for use in an extended temperature range and their proven conformity with current standards, these cable glands ensure safe and reliable functioning in a wide range of applications.

Your special advantages:
Impact and temperature resistant: The cable glands for use in areas at risk of explosion can withstand extreme temperature conditions. They are impact-resistant up to 7 Joules and can be used in any Weidmüller enclosures, guaranteeing versatile applicability with full standard conformity.

In process-intensive industries such as petrochemistry, energy production, machine construction, motor and drive technology and device components which are subjected to extremely high stresses. The cable glands can withstand even the harshest environmental conditions. Guarantee impact-resistance of up to 7 Joules over an extended temperature range.

Flexible application
Available in 8 standard sizes from M12 to M63 (additional thread types on request) and with 14 different clamping ranges, the new range of cable glands is suitable for an extremely wide range of applications.

Resistant to high temperatures
The cable glands have an operating temperature range of –40 °C to +70 °C with a chloroprene seal, and a range of as wide as –60 °C to +70 °C with a silicone seal.



Extremely impact-resistant
With impact resistance of 7 Joules, the explosion-proof cable glands offer extremely high levels of protection against external influences such as shocks or impacts, in accordance with EN 60079-0:2012 + A11 : 2013.



Comprehensive approvals
Whether for Ex e or Ex i applications:
The plastic cable glands comply consistently with EN 60079-0:2012 + A11 : 2013 and are approved in accordance with ATEX, IECEx, EAC, and DNV GL.

Ex cable glands – Plastic – Ex e, Ex i, IP66 / IP68, 7J, –40°C – +70°C

Plastic cable gland for Ex applications with integrated strain relief, especially for Ex e and Ex i applications with chloroprene seal and 7 Joule impact resistance. Complete with integral membrane seal for clean transportation and storage.



Technical data

Material	Polyamide 6
Temperature range	-40 °C...70 °C
Seal insert	CR
Protection class	IP54, IP66, IP67, IP68 - 5 bar (30 min.)
Impact resistance	7 joules in acc. with IEC 60079-0
Marking	Ex eb IIC Gb, Ex tb IIIC Db IP66/68
Note	Length "L" depends on the cable diameter used.

Ordering data

Type	Thread	KB	L/L1	SW	Qty.	Order No.
Ex e, deep black						
VG M12 EXE 4-6,5 CR7J G4	M 12	4-6.5 mm	22 / 10 mm	15 mm	100	**2721930000**
VG M16 EXE 5-8 CR7J G4	M 16	5-8 mm	26 / 10 mm	19 mm	50	**2721940000**
VG M16 EXE 6-10 CR7J G4	M 16	6-10 mm	29.5 / 10 mm	22 mm	50	**2721950000**
VG M20 EXE 7-12 CR7J G4	M 20	7-12 mm	30 / 10 mm	24 mm	50	**2721960000**
VG M20 EXE 7-13 CR7J G4	M 20	7-13 mm	33 / 10 mm	25 mm	50	**2721970000**
VG M20 EXE 11-14 CR7J G4	M 20	11-14 mm	30 / 10 mm	27 mm	50	**2721980000**
VG M25 EXE 12-17 CR7J G4	M 25	12-17 mm	34 / 10 mm	29 mm	50	**2721990000**
VG M25 EXE 14-18 CR7J G4	M 25	14-18 mm	35 / 10 mm	33 mm	25	**2722000000**
VG M32 EXE 16-21 CR7J G4	M 32	16-21 mm	42 / 10 mm	36 mm	25	**2722010000**
VG M32 EXE 19-25 CR7J G4	M 32	19-25 mm	40.5 / 15 mm	42 mm	20	**2722020000**
VG M40 EXE 20-28 CR7J G4	M 40	20-28 mm	46 / 10 mm	46 mm	15	**2722030000**
VG M40 EXE 23-32 CR7J G4	M 40	23-32 mm	50 / 18 mm	53 mm	10	**2722040000**
VG M50 EXE 31-38 CR7J G4	M 50	31-38 mm	54 / 18 mm	60 mm	10	**2722050000**
VG M63 EXE 35-44 CR7J G4	M 63	35-44 mm	54 / 18 mm	65 mm	10	**2722060000**
Ex i, light blue, deep black						
VG M12 EXI 4-6,5 CR7J G4	M 12	4-6.5 mm	22 / 10 mm	15 mm	100	**2722210000**
VG M16 EXI 5-8 CR7J G4	M 16	5-8 mm	26 / 10 mm	19 mm	50	**2722220000**
VG M16 EXI 6-10 CR7J G4	M 16	6-10 mm	29.5 / 10 mm	22 mm	50	**2722230000**
VG M20 EXI 7-12 CR7J G4	M 20	7-12 mm	30 / 10 mm	24 mm	50	**2722240000**
VG M20 EXI 7-13 CR7J G4	M 20	7-13 mm	33 / 10 mm	25 mm	50	**2722250000**
VG M20 EXI 11-14 CR7J G4	M 20	11-14 mm	30 / 10 mm	27 mm	50	**2722260000**
VG M25 EXI 12-17 CR7J G4	M 25	12-17 mm	34 / 10 mm	29 mm	50	**2722270000**
VG M25 EXI 14-18 CR7J G4	M 25	14-18 mm	35 / 10 mm	33 mm	25	**2722280000**
VG M32 EXI 16-21 CR7J G4	M 32	16-21 mm	42 / 10 mm	36 mm	25	**2722290000**
VG M32 EXI 19-25 CR7J G4	M 32	19-25 mm	40.5 / 15 mm	42 mm	20	**2722300000**
VG M40 EXI 20-28 CR7J G4	M 40	20-28 mm	46 / 10 mm	46 mm	15	**2722310000**
VG M40 EXI 23-32 CR7J G4	M 40	23-32 mm	50 / 18 mm	53 mm	10	**2722320000**
VG M50 EXI 31-38 CR7J G4	M 50	31-38 mm	54 / 18 mm	60 mm	10	**2722330000**
VG M63 EXI 35-44 CR7J G4	M 63	35-44 mm	54 / 18 mm	65 mm	10	**2722340000**
Note	Installation specifications and tightening torques can be found in the installation instructions. For further information please use our online catalogue: catalog.weidmueller.com					

Ex cable glands – Plastic – Ex e, Ex i, IP66 / IP68, 7J, –60°C – +70°C

Plastic cable gland for Ex applications with integrated strain relief, especially for Ex e and Ex i applications with silicone seal and 7 Joule impact resistance. Complete with integral membrane seal for clean transportation and storage.



Technical data

Material	Polyamide 6
Temperature range	-60 °C...70 °C
Seal insert	Silicone
Protection class	IP54, IP66, IP67, IP68 - 5 bar (30 min.)
Impact resistance	7 joules in acc. with IEC 60079-0
Marking	Ex eb IIC Gb, Ex tb IIIC Db IP66/68
Note	Length "L" depends on the cable diameter used.

Ordering data

Type	Thread	KB	L/L1	SW	Qty.	Order No.
Ex e, deep black						
VG M12 EXE 4-6,5 SI7J G4	M 12	4-6.5 mm	22 / 10 mm	15 mm	100	**2722070000**
VG M16 EXE 5-8 SI7J G4	M 16	5-8 mm	26 / 10 mm	19 mm	50	**2722080000**
VG M16 EXE 6-10 SI7J G4	M 16	6-10 mm	29.5 / 10 mm	22 mm	50	**2722090000**
VG M20 EXE 7-12 SI7J G4	M 20	7-12 mm	30 / 10 mm	24 mm	50	**2722100000**
VG M20 EXE 7-13 SI7J G4	M 20	7-13 mm	33 / 10 mm	25 mm	50	**2722110000**
VG M20 EXE 11-14 SI7J G4	M 20	11-14 mm	30 / 10 mm	27 mm	50	**2722120000**
VG M25 EXE 12-17 SI7J G4	M 25	12-17 mm	34 / 10 mm	29 mm	50	**2722130000**
VG M25 EXE 14-18 SI7J G4	M 25	14-18 mm	35 / 10 mm	33 mm	25	**2722140000**
VG M32 EXE 16-21 SI7J G4	M 32	16-21 mm	42 / 10 mm	36 mm	25	**2722150000**
VG M32 EXE 19-25 SI7J G4	M 32	19-25 mm	40.5 / 15 mm	42 mm	20	**2722160000**
VG M40 EXE 20-28 SI7J G4	M 40	20-28 mm	46 / 10 mm	46 mm	15	**2722170000**
VG M40 EXE 23-32 SI7J G4	M 40	23-32 mm	50 / 18 mm	53 mm	10	**2722180000**
VG M50 EXE 31-38 SI7J G4	M 50	31-38 mm	54 / 18 mm	60 mm	10	**2722190000**
VG M63 EXE 35-44 SI7J G4	M 63	35-44 mm	54 / 18 mm	65 mm	10	**2722200000**
Ex i, light blue, deep black						
VG M12 EXI 4-6,5 SI7J G4	M 12	4-6.5 mm	22 / 10 mm	15 mm	100	**2722350000**
VG M16 EXI 5-8 SI7J G4	M 16	5-8 mm	26 / 10 mm	19 mm	50	**2722360000**
VG M16 EXI 6-10 SI7J G4	M 16	6-10 mm	29.5 / 10 mm	22 mm	50	**2722370000**
VG M20 EXI 7-12 SI7J G4	M 20	7-12 mm	30 / 10 mm	24 mm	50	**2722380000**
VG M20 EXI 7-13 SI7J G4	M 20	7-13 mm	33 / 10 mm	25 mm	50	**2722390000**
VG M20 EXI 11-14 SI7J G4	M 20	11-14 mm	30 / 10 mm	27 mm	50	**2722400000**
VG M25 EXI 12-17 SI7J G4	M 25	12-17 mm	34 / 10 mm	29 mm	50	**2722410000**
VG M25 EXI 14-18 SI7J G4	M 25	14-18 mm	35 / 10 mm	33 mm	25	**2722420000**
VG M32 EXI 16-21 SI7J G4	M 32	16-21 mm	42 / 10 mm	36 mm	25	**2722430000**
VG M32 EXI 19-25 SI7J G4	M 32	19-25 mm	40.5 / 15 mm	42 mm	20	**2722440000**
VG M40 EXI 20-28 SI7J G4	M 40	20-28 mm	46 / 10 mm	46 mm	15	**2722450000**
VG M40 EXI 23-32 SI7J G4	M 40	23-32 mm	50 / 18 mm	53 mm	10	**2722460000**
VG M50 EXI 31-38 SI7J G4	M 50	31-38 mm	54 / 18 mm	60 mm	10	**2722470000**
VG M63 EXI 35-44 SI7J G4	M 63	35-44 mm	54 / 18 mm	65 mm	10	**2722480000**
Note	Installation specifications and tightening torques can be found in the installation instructions. For further information please use our online catalogue: catalog.weidmueller.com					

Lock nuts – Plastic 7035

For fastening cable glands and accessories if no threaded hole is available. With circumferential collar to prevent damage to the substrate during installation.



Technical data

Material / Colour	Polyamid 6 (PA6 - GF30) / Light Grey / RAL 7035
Temperature range	-40 °C...100 °C
Flammability rating	V-2
Note	

Ordering data

Type	Thread	S1	SW	Qty.	Order No.
metric					
SKMU M12 - K GR	M 12	5.00	18	100	**1772440000**
SKMU M16 - K GR	M 16	5.00	22	100	**1772450000**
SKMU M20 - K GR	M 20	6.00	26	100	**1772460000**
SKMU M25 - K GR	M 25	6.00	32	100	**1772470000**
SKMU M32 - K GR	M 32	7.00	41	100	**1772480000**
SKMU M40 - K GR	M 40	7.00	50	50	**1772490000**
SKMU M50 - K GR	M 50	8.00	60	10	**1772500000**
SKMU M63 - K GR	M 63	8.00	75	10	**1772510000**
PG					
SKMU PG7-K GR	PG 7	5.00	19	100	**1697440000**
SKMU PG9-K GR	PG 9	5.00	22	100	**1697450000**
SKMU PG11-K GR	PG 11	5.00	24	100	**1697460000**
SKMU PG 13,5-K GR	PG 13.5	6.00	27	100	**1697470000**
SKMU PG16-K GR	PG 16	6.00	30	100	**1697480000**
SKMU PG21-K GR	PG 21	7.00	36	100	**1698220000**
SKMU PG29-K GR	PG 29	7.00	46	50	**1698230000**
SKMU PG36-K GR	PG 36	8.00	60	25	**1698240000**
SKMU PG42-K GR	PG 42	8.00	65	25	**1698250000**
SKMU PG48-K GR	PG 48	8.00	70	25	**1719090000**
Note	Further versions on request.				

Lock nuts – Plastic 9005

Lock nuts with collar for preventing enclosure damage on installation. These are used to secure plastic cable glands and blanking plugs - recommended for Ex e and Ex i plastic cable glands.



Technical data

Material / Colour	Polyamid 6 (PA6 - GF30) / Deep black / RAL 9005
Temperature range	-40 °C...100 °C
Flammability rating	V-2
Note	Accessories for Ex cable glands are not subject to approval.

Ordering data

Type	Thread	S1	SW	Qty.	Order No.
metric					
SKMU M12 K SW	M 12	5.00	18	100	**1806540000**
SKMU M16 K SW	M 16	5.00	22	100	**1736920000**
SKMU M20 K SW	M 20	6.00	26	100	**1736930000**
SKMU M25 K SW	M 25	6.00	32	25	**1736940000**
SKMU M32 K SW	M 32	7.00	41	100	**1736950000**
SKMU M40 K SW	M 40	7.00	50	10	**1736960000**
SKMU M50 K SW	M 50	8.00	60	5	**1736970000**
SKMU M63 K SW	M 63	8.00	75	5	**1736980000**
PG					
SKMU PG7-K SW	PG 7	5.00	19	100	**1719100000**
SKMU PG9-K SW	PG 9	5.00	22	50	**1719110000**
SKMU PG11-K SW	PG 11	5.00	24	50	**1719120000**
SKMU PG13,5-K SW	PG 13.5	6.00	27	50	**1719130000**
SKMU PG16-K SW	PG 16	6.00	30	100	**1719140000**
SKMU PG21-K SW	PG 21	7.00	36	100	**1719150000**
SKMU PG29-K SW	PG 29	7.00	46	20	**1719160000**
SKMU PG36-K SW	PG 36	8.00	60	10	**1719170000**
SKMU PG42-K SW	PG 42	8.00	65	25	**1719180000**
SKMU PG48-K SW	PG 48	8.00	70	25	**1719190000**
Note	Further versions on request.				

Lock nuts – Brass – nickel-plated

For fastening cable glands and accessories if no threaded hole is available. Recommended when working with Ex applications.



Technical data

Material	Brass, nickel-plated
Note	

Ordering data

Type	Thread	S1	SW	Qty.	Order No.
metric					
SKMU M12 MS	M 12	2.8	14	100	**1772360000**
SKMU M16 MS	M 16	2.8	19	100	**1736990000**
SKMU M20 MS	M 20	3	24	100	**1737000000**
SKMU M25 MS	M 25	3	28	100	**1737010000**
SKMU M32 MS	M 32	4	36	100	**1737020000**
SKMU M40 MS	M 40	4.5	44	50	**1737030000**
SKMU M50 MS	M 50	5	54	25	**1737040000**
SKMU M63 MS	M 63	6	70	25	**1737050000**
SKMU M75 MS	M 75	8	85	5	**1737060000**
PG					
SKMU PG7-MS	PG 7	2.8	15	100	**1694070000**
SKMU PG9-MS	PG 9	2.8	18	100	**1694080000**
SKMU PG11-MS	PG 11	3	21	100	**1694090000**
SKMU PG13,5-MS	PG 13.5	3	23	100	**1694100000**
SKMU PG16-MS	PG 16	3	26	100	**1694110000**
SKMU PG21-MS	PG 21	3.5	32	100	**1719200000**
SKMU PG29-MS	PG 29	4	41	50	**1719210000**
SKMU PG36-MS	PG 36	5	51	50	**1719220000**
SKMU PG42-MS	PG 42	5	60	25	**1719230000**
SKMU PG48-MS	PG 48	5.5	64	10	**1719240000**
Note	Further versions on request.				

Lock nuts – Brass – natural

For fastening cable glands and accessories if no threaded hole is available. Recommended when working with Ex applications.



Technical data

Material	Brass
Note	

Ordering data

Type	Thread	S1	SW	Qty.	Order No.
metric					
SKMU M16 MS SC	M 16	4	22	50	**0930640001**
SKMU M20 MS SC	M 20	4	24	50	**0930640002**
SKMU M25 MS SC	M 25	4	30	25	**0930640003**
SKMU M32 MS SC	M 32	4	40	20	**0930640004**
SKMU M40 MS SC	M 40	4.5	50	10	**0930640005**
SKMU M50 MS SC	M 50	5	65	5	**0930640006**
SKMU M63 MS SC	M 63	6.5	75	5	**0930640007**
SKMU M75 MS SC	M 75	7	90	5	**0930640008**
Note					

Lock nuts – Brass – EMC

For fastening cable glands and accessories if no threaded hole is available. Specially equipped with 6 edges which contact the enclosure when the lock nut is tightened.



Technical data

Material	Brass, nickel-plated
Note	

Ordering data

Type	Thread	S1	SW	Qty.	Order No.
metric					
SKMU EMV M12	M 12	3.6	15	100	**1777610000**
SKMU EMV M16	M 16	3.6	19	100	**1777620000**
SKMU EMV M20	M 20	3.6	24	100	**1777630000**
SKMU EMV M25	M 25	3.6	30	50	**1777640000**
SKMU EMV M32	M 32	4.1	36	50	**1777650000**
SKMU EMV M40	M 40	4.6	46	10	**1777660000**
SKMU EMV M50	M 50	4.6	60	10	**1777670000**
SKMU EMV M63	M 63	6.6	70	10	**1777680000**
PG					
SKMU EMV PG7	PG 7	4.7	15	20	**1718900000**
SKMU EMV PG9	PG 9	4.7	18	20	**1718910000**
SKMU EMV PG11	PG 11	4.7	21	20	**1718920000**
SKMU EMV PG13,5	PG 13.5	4.7	23	10	**1718930000**
SKMU EMV PG16	PG 16	4.7	26	10	**1718940000**
SKMU EMV PG21	PG 21	5.2	32	10	**1718950000**
SKMU EMV PG29	PG 29	5.7	41	15	**1718960000**
SKMU EMV PG 36	PG 36	4.6	51	1	**1777710000**
SKMU EMV PG 42	PG 42	4.6	58	1	**1777700000**
SKMU EMV PG 48	PG 48	5.6	64	1	**1777690000**

Note Further versions on request.

Flat IP washer – Standard – Polyethylene

For better sealing of the connection thread of a cable gland or accessory.



Technical data

Material / Colour	Polyethylene / Transparent
Temperature range	-30 °C...90 °C
Note	

Ordering data

Type	Thread	D1	D2	S	Qty.	Order No.
metric						
GWDR M12-PO	M 12	16.00	12.00	2.00	50	**1777920000**
GWDR M16-PO	M 16	20.00	16.00	2.00	50	**1777930000**
GWDR M20-PO	M 20	24.00	20.00	2.00	100	**1777940000**
GWDR M25-PO	M 25	29.00	25.00	2.00	50	**1777950000**
GWDR M32-PO	M 32	36.00	32.00	2.00	50	**1777960000**
GWDR M40-PO	M 40	45.00	40.00	2.00	50	**1777970000**
GWDR M50-PO	M 50	56.00	50.00	2.00	50	**1777980000**
GWDR M63-PO	M 63	70.00	63.00	2.00	50	**1777990000**
PG						
GWDR PG7-PO	PG 7	16.50	12.50	2.00	100	**1719440000**
GWDR PG9-PO	PG 9	19.00	15.20	2.00	100	**1719450000**
GWDR PG11-PO	PG 11	22.50	18.60	2.00	100	**1719460000**
GWDR PG13,5-PO	PG 13.5	25.00	20.40	2.00	100	**1719470000**
GWDR PG16-PO	PG 16	27.00	22.50	2.00	100	**1719480000**
GWDR PG21-PO	PG 21	33.50	28.30	3.00	100	**1719490000**
GWDR PG29-PO	PG 29	43.50	37.00	3.00	50	**1719500000**
GWDR PG36-PO	PG 36	55.00	47.00	3.00	50	**1719510000**
GWDR PG42-PO	PG 42	63.00	54.00	3.00	10	**1719520000**
GWDR PG48-PO	PG 48	69.00	59.30	3.00	5	**1719530000**
Note	Further versions on request.					

Flat IP washer – Standard – Neoprene

For better sealing of the connection thread of a cable gland or accessory.



Technical data

Material / Colour	Neoprene / Deep black / RAL 9005
Temperature range	-40 °C...100 °C
Note	

Ordering data

Type	Thread	D1	D2	S	Qty.	Order No.
metric						
GWDR M12-NP	M 12	18.00	12.00	1.20	50	**1913320000**
GWDR M16-NP	M 16	22.00	16.00	1.20	50	**1736230000**
GWDR M20-NP	M 20	24.00	20.00	1.20	50	**1736240000**
GWDR M25-NP	M 25	30.00	25.00	1.50	100	**1736250000**
GWDR M32-NP	M 32	42.00	32.00	1.50	50	**1736260000**
GWDR M40-NP	M 40	52.00	40.00	1.50	20	**1736270000**
GWDR M50-NP	M 50	63.00	50.00	1.50	20	**1736280000**
GWDR M63-NP	M 63	77.00	63.00	2.00	10	**1736290000**
PG						
GWDR PG7-NP	PG 7	17.00	11.60	1.20	100	**1719540000**
GWDR PG9-NP	PG 9	21.00	14.00	1.20	100	**1719550000**
GWDR PG11-NP	PG 11	24.00	17.00	1.20	100	**1719560000**
GWDR PG13,5-NP	PG 13.5	27.00	19.50	1.20	100	**1719570000**
GWDR PG16-NP	PG 16	30.00	22.50	1.20	100	**1719580000**
GWDR PG21-NP	PG 21	35.00	28.30	1.50	100	**1719590000**
GWDR PG29-NP	PG 29	45.00	37.00	1.50	50	**1719600000**
GWDR PG36-NP	PG 36	60.00	47.00	1.50	20	**1719610000**
GWDR PG42-NP	PG 42	65.00	54.00	1.50	10	**1719620000**
GWDR PG48-NP	PG 48	71.00	59.30	1.50	5	**1719630000**
Note	Further versions on request.					

Flat IP washer – Standard – Nylon

For better sealing of the connection thread of a cable gland or accessory.



Technical data

Material / Colour	Nylon 6 / traffic red / RAL 3020
Temperature range	-40 °C...135 °C
Note	

Ordering data

Type	Thread	D1	D2	S	Qty.	Order No.
metric						
KSWN M16	M 16	25.00	16.50	2.00	25	**1076630000**
KSWN M20	M 20	29.40	20.70	2.00	25	**0930730002**
KSWN M25	M 25	38.10	25.70	2.00	25	**1076640000**
KSWN M32	M 32	42.50	32.50	2.00	25	**1076650000**
KSWN M40	M 40	52.00	40.50	2.00	25	**0899780000**
KSWN M50	M 50	65.00	50.50	2.00	25	**0900660000**
KSWN M63	M 63	79.40	63.50	2.00	25	**1076660000**
KSWN M75	M 75	90.50	75.50	2.00	25	**1076670000**
Note						

Flat IP washer – Standard – Vulcanised fibre

For better sealing of the connection thread of a cable gland or accessory.



Technical data

Material / Colour	Vulcanized fibre / brown-red / RAL 3011
Temperature range	-40 °C...95 °C
Note	

Ordering data

Type	Thread	D1	D2	S	Qty.	Order No.
metric						
KSWF M16	M 16	25.00	16.50	1.50	25	**1076680000**
KSWF M20	M 20	29.40	20.70	1.50	25	**0899750000**
KSWF M25	M 25	38.10	25.70	1.50	25	**0899770000**
KSWF M32	M 32	42.50	32.50	1.50	25	**1076690000**
KSWF M40	M 40	52.00	40.50	1.50	25	**1076710000**
KSWF M50	M 50	65.00	50.50	1.50	25	**1076720000**
KSWF M63	M 63	79.40	63.50	1.50	25	**1076730000**
KSWF M75	M 75	90.50	75.50	1.50	25	**1076740000**
Note						

Accessories – Earth tags – Brass

Earth tags are best used when a cable shielding is being tightened onto the cable gland, and when it has the same potential as another cable gland on the enclosure.



Technical data

Material	Brass, nickel-plated
Note	

Ordering data

Type	Thread	A	B	C	D1	D2	Qty.	Order No.
metric, nickel-plated brass								
EA-RING MS/M 16	M 16	48.75	30.00	13.00	24.5	6.75	20	**1736480000**
EA-RING MS/M 20	M 20	53.8	33.00	13.00	28.6	7.00	20	**1736490000**
EA-RING MS/M 25	M 25	61.5	36.00	17.00	34	10.50	20	**1736500000**
EA-RING MS/M 32	M 32	73	41.00	22.00	42	12.20	20	**1736510000**
EA-RING MS/M 40	M 40	86.5	44.50	30.00	54	13.50	10	**1736520000**
EA-RING MS/M 50	M 50	111.5	58.00	40.00	67	13.50	10	**1736530000**
EA-RING MS/M 63	M 63	125.5	67.00	40.00	77	13.50	10	**1736540000**
EA-RING MS/M 75	M 75	137.5	73.00	40.00	89	13.50	10	**1736550000**
metric, brass natural								
EA-RING MS/M16 SC	M 16	50.8	31.80	12.80	25.4	6.90	20	**0930710001**
EA-RING MS/M20 SC	M 20	54	33.00	12.80	28.6	6.90	20	**0930710002**
EA-RING MS/M25 SC	M 25	60.2	36.50	12.80	34.8	6.90	20	**0930710003**
EA-RING MS/M32 SC	M 32	74.6	42.50	22.30	44.6	11.80	20	**0930710004**
EA-RING MS/M40 SC	M 40	86.7	45.40	31.70	53	13.50	10	**0930710005**
EA-RING MS/M50 SC	M 50	111	58.10	41.30	65.2	13.50	10	**0930710006**
EA-RING MS/M63 SC	M 63	128.7	66.80	41.30	82.6	13.50	10	**0930710007**
EA-RING MS/M75 SC	M 75	141.3	73.00	41.30	95.3	13.50	10	**0930710008**
Note	Further versions on request.							

Accessories – Shrouds – Silicone

The cover shroud a cable gland before and after the installation. It also protects against external environmental influences.



Technical data

Material / Colour	Silicone / blue-grey / RAL 7031
Temperature range	-60 °C...200 °C
Hardness (IRHD)	60
Note	

Ordering data

Type	A	B	D1	D2	S	Qty.	Order No.
metric							
KSP L24 S	123	70.00	25.00	28	1.50	10	**0930700001**
KSP L30 S	130	75.00	30.00	33	1.50	10	**0930700002**
KSP L38 S	130	75.00	37.00	40	1.50	10	**0930700003**
KSP L46 S	130	75.00	46.00	49	1.50	10	**0930700004**
KSP L55 S	150	85.00	55.00	58	1.50	10	**0930700005**
KSP L65 S	150	85.00	65.00	68	1.50	10	**0930700006**
KSP L80 S	150	85.00	80.00	84	2.00	10	**0930700007**
KSP L90 S	165	95.00	90.00	94	2.00	10	**0930700008**
KSP L 104 S	210	120.00	104.00	108	2.00	10	**1193940000**
KSP L114 S	210	120.00	114.00	118	2.00	10	**1192790000**
Note							

Accessories – Shrouds – PVC

The cover shroud a cable gland before and after the installation. It also protects against external environmental influences.



Technical data

Material / Colour	PVC / Deep black / RAL 9005
Temperature range	-25 °C...70 °C
Hardness (Shore A)	65
Note	

Ordering data

Type	A	B	D1	D2	S	Qty.	Order No.
metric							
KSP L24	123	70.00	25.00	29	2.00	10	**1736570000**
KSP L30	130	75.00	30.00	34	2.00	10	**1736580000**
KSP L38	130	75.00	37.00	41	2.00	10	**1736590000**
KSP L46	130	75.00	46.00	50	2.00	10	**1736600000**
KSP L55	150	85.00	55.00	59	2.00	10	**1736610000**
KSP L65	150	85.00	65.00	69	2.00	10	**1736620000**
KSP L80	150	85.00	80.00	84	2.00	10	**1736630000**
KSP L90	165	95.00	90.00	94	2.00	10	**1736640000**
KSP EL30	130	80.00	30.00	34	2.00	10	**1736670000**
KSP EL38	175	95.00	37.00	41	2.00	10	**1736680000**
KSP EL46	205	105.00	46.00	50	2.00	10	**1076750000**
KSP EL55	220	115.00	55.00	59	2.00	10	**1076760000**
KSP EL65	265	125.00	65.00	69	2.00	10	**1076770000**
KSP EL80	280	130.00	80.00	84	2.00	10	**1076780000**
KSP EL90	280	140.00	90.00	94	2.00	10	**1076790000**
Note	*These shrouds have been specially designed for the Klippon® KDSU and Klippon® KUB cable glands.						

Accessories – Serrated washers, Stainless steel

Serrated stainless-steel washers to prevent mounted cable glands from loosening. Can also be used to roughen painted or passivated surfaces.



Technical data

Material	Stainless steel 1.4404 (316L)
Note	

Ordering data

Type	Thread	D1	D2	Qty.	Order No.
metric					
SZS M16	M 16	25.5	17.30	50	**1736300000**
SZS M20	M 20	32.4	21.30	10	**1736310000**
SZS M25	M 25	37.4	25.30	10	**1736320000**
SZS M32	M 32	48	33.00	10	**1736330000**
SZS M40	M 40	60	41.00	5	**1736340000**
SZS M50	M 50	71	51.00	5	**1736350000**
SZS M63	M 63	87	64.00	5	**1736360000**
Note					

Blanking plugs – Plastic

Plastic blanking plug with cross-head is used to seal surplus threaded holes and to maintain the IP protection degree.



Technical data

Material / Colour	Polyamid 6 (PA6 - GF30) / Light Grey / RAL 7035
Temperature range	-40 °C...100 °C
Protection class	IP54
Flammability rating	V-2
Note	Optional sealing ring.

Ordering data

Type	Thread	L	L1	Head Ø	Qty.	Order No.
metric						
VP M12 K54	M 12	5.5	6	15.00	100	**1776930000**
VP M16 K54	M 16	5.5	7	20.00	100	**1776920000**
VP M20 K54	M 20	6.5	7	24.00	100	**1776910000**
VP M25 K54	M 25	7	10	30.00	100	**1776900000**
VP M32 K54	M 32	7	11	37.00	50	**1776940000**
VP M40 K54	M 40	7	13	46.00	25	**1776950000**
VP M50 K54	M 50	8.5	14	56.00	10	**1776960000**
VP M63 K54	M 63	8.5	15	69.50	50	**1776970000**
PG						
VP 7-K54	PG 7	8	6	15.00	100	**1719250000**
VP 9-K54	PG 9	9.5	5	19.00	100	**0294760000**
VP 11-K54	PG 11	10	6.5	22.00	100	**0294860000**
VP 13,5-K54	PG 13.5	10	5	25.00	100	**0294960000**
VP 16-K54	PG 16	10	5	27.00	100	**0295060000**
VP 21-K54	PG 21	12	8	33.00	50	**0295160000**
VP 29-K54	PG 29	11.5	8	44.00	25	**0501160000**
VP 36-K54	PG 36	14	10	55.00	10	**0501260000**
VP 42-K54	PG 42	14	10	62.00	5	**0501360000**
VP 48-K54	PG 48	16	12	69.00	5	**1719260000**
Note	Other versions available on request. The blanking plugs must be tightened "hand-tight" with the screwdriver.					

Blanking plugs – Brass – Nickel-plated

Brass blanking plug with cross-head is used to seal surplus threaded holes and to maintain the IP protection degree.



Technical data

Material	Brass, nickel-plated
O-Ring	NBR
Temperature range	-40 °C...100 °C
Protection class	IP68 - 5 bar (30 min.)

Note

Ordering data

Type	Thread	L	L1	Head Ø	Qty.	Order No.
metric						
VP M12-MS65	M 12	7.5	5	14.00	100	**1777720000**
VP M16-MS65	M 16	8	5	18.00	100	**1777730000**
VP M20-MS65	M 20	9.5	6	22.00	100	**1777740000**
VP M25-MS65	M 25	11	7	28.00	100	**1777750000**
VP M32-MS65	M 32	12	8	35.00	50	**1777760000**
VP M40-MS65	M 40	13	8	44.00	50	**1777770000**
VP M50-MS65	M 50	15	9	54.00	25	**1777780000**
VP M63-MS65	M 63	16	10	67.00	10	**1777790000**
PG						
VP 7-MS65	PG 7	7.5	5	15.00	100	**0521600000**
VP 9-MS65	PG 9	8	5	18.00	100	**0294700000**
VP 11-MS65	PG 11	8	5	22.00	100	**0294800000**
VP 13,5-MS65	PG 13.5	9	6	24.00	100	**0294900000**
VP 16-MS65	PG 16	9	6	26.00	100	**0295000000**
VP 21-MS65	PG 21	10	6	32.00	50	**0295100000**
VP 29-MS65	PG 29	12	8	40.00	50	**0501100000**
VP 36-MS65	PG 36	15	9	50.00	25	**0501200000**
VP 42-MS65	PG 42	16	10	57.00	25	**0501300000**
VP 48-MS65	PG 48	16	10	64.00	10	**1719270000**

Note Other versions available on request. The blanking plugs must be tightened "hand-tight" with the screwdriver.

Blanking plugs – Plastic – Ex e

Blanking plug with cross-head is used to seal surplus threaded holes and to maintain the IP protection degree – especially for Ex-e Ex applications.



Technical data

Material / Colour	Polyamide / Deep black / RAL 9005
Temperature range	-20 °C...80 °C
Protection class	IP54, IP66
Protection degree with GWDR	IP66, IP68
UL 94 flammability rating	V-2
Marking	Ex e II, Ex tD
Note	Optional sealing ring.

Ordering data

Type	Thread	L	L1	SW	Qty.	Order No.
metric						
VP M16-EXE SW	M 16	19	15	19	100	**1737070000**
VP M20-EXE SW	M 20	19	15	23	100	**1737080000**
VP M25-EXE SW	M 25	20	15	28	100	**1737090000**
VP M32-EXE SW	M 32	20.5	15	36	100	**1737100000**
VP M40-EXE SW	M 40	20.5	15	44	20	**1737110000**
VP M50-EXE SW	M 50	21	15	54	5	**1737120000**
VP M63-EXE SW	M 63	23.5	15	67	5	**1737130000**

Note Installation specifications and tightening torques can be found in the installation instructions.
For further information please use our online catalogue: catalog.weidmueller.com.

Blanking plugs – Brass – Ex e, Ex d

Blanking plug is used for sealing surplus threaded holes to ensure the IP protection degree - especially for Ex-e and Ex-d applications.



Technical data

Material	Brass, nickel-plated
O-Ring	NBR
Temperature range	-40 °C...100 °C
Protection class	IP54, IP64, IP68
Marking	II 2 GD, Ex d IIC, Ex e II, Ex tD
Note	

Ordering data

Type	Thread	L	L1	SW	Qty.	Order No.
metric						
VP M16 EXE MS	M 16	15	12	18	50	**1210890000**
VP M20 EXE MS	M 20	15	12	23	50	**1210900000**
VP M25 EXE MS	M 25	15.5	12	29	25	**1210910000**
VP M32 EXE MS	M 32	16	12	39	10	**1210920000**
VP M40 EXE MS	M 40	19	15	45	10	**1210930000**
VP M50 EXE MS	M 50	20	15	58	5	**1210940000**
VP M63 EXE MS	M 63	26	19	70	5	**1210950000**

Note

Installation specifications and tightening torques can be found in the installation instructions.
For further information please use our online catalogue: catalog.weidmueller.com.

Blanking plugs – Brass and Stainless steel – Ex e, Ex d, IP66 / IP68

The KSPMH is a mushroom-shaped blanking plug with a hexagon socket. It is used to seal unused threaded holes so that cable glands can be inserted in the future. The KSPMH is approved for pressure-resistant Ex d encapsulations and increased safety Ex e applications.



Technical data

O-Ring	Silicone
Temperature range	-60 °C...200 °C
Protection class	IP66, IP68 (100 m / 168 h)
Marking	Ex d IIC Gb, Ex e IIC Gb, Ex tb IIIC Db
Note	

Ordering data

Type	Thread	L	L1	Qty.	Order No.
brass					
KSPMH M16 BSC	M 16	20.5	16	20	**1477740000**
KSPMH M20 BSC	M 20	21	16	20	**1477750000**
KSPMH M25 BSC	M 25	21	16	20	**1477770000**
KSPMH M32 BSC	M 32	21	16	10	**1477780000**
KSPMH M40 BSC	M 40	21.5	16	10	**1477790000**
KSPMH M50 BSC	M 50	21.5	16	1	**1477800000**
KSPMH M63 BSC	M 63	22	16	1	**1477810000**
KSPMH M75 BSC	M 75	22	16	1	**1477830000**
Stainless steel					
KSPMH M16 SSC	M 16	20.5	16	20	**1477820000**
KSPMH M20 SSC	M 20	21	16	20	**1477840000**
KSPMH M25 SSC	M 25	21	16	20	**1477870000**
KSPMH M32 SSC	M 32	21	16	10	**1477890000**
KSPMH M40 SSC	M 40	21.5	16	10	**1477910000**
KSPMH M50 SSC	M 50	21.5	16	1	**1477930000**
KSPMH M63 SSC	M 63	22	16	1	**1477950000**
KSPMH M75 SSC	M 75	22	16	1	**1477980000**

Note

Installation specifications and tightening torques can be found in the installation instructions.
For further information please use our online catalogue: catalog.weidmueller.com.

Blanking plugs – Plastic – Ex e, IP66

For secure connection of unused screw-in threads or through-hole in enclosures. For Ex e applications with an impact resistance of 7 Joule in accordance with IEC 60079-0.



Technical data

Material / Colour	Polyamide 6 / Deep black / RAL 9005
O-Ring	Silicone
Temperature range	-60 °C...70 °C
Protection class	IP54, IP66, IP67, IP68 - 5 bar (30 min.)
Impact resistance	7 joules in acc. with IEC 60079-0
Marking	Ex eb IIC Gb, Ex tb IIIC Db IP66/68
Note	

Ordering data

Type	Thread	L	L1	SW	Qty.	Order No.
VP M12 EX SI 7J	M 12	15	10	15	100	**2066710000**
VP M16 EX SI 7J	M 16	16.3	12	19	100	**2066720000**
VP M20 EX SI 7J	M 20	17	11	23	100	**2066730000**
VP M25 EX SI 7J	M 25	15.8	10	28	100	**2066740000**
VP M32 EX SI 7J	M 32	22.8	15	36	100	**2066750000**
VP M40 EX SI 7J	M 40	26.5	18	46	20	**2066760000**
VP M50 EX SI 7J	M 50	27.5	18	55	20	**2066770000**
VP M63 EX SI 7J	M 63	27.5	18	69	20	**2066940000**

Note

Installation specifications and tightening torques can be found in the installation instructions.
For further information please use our online catalogue: catalog.weidmueller.com.

Compensation elements – Plastic – DAE

The DAE pressure-compensation element provides good ventilation for the enclosure and prevents moisture build-up. At the same time it maintains the high IP69k protection level. The membrane repels water and oil.



Technical data

Material / Colour	Polyamide 6 / Deep black / RAL 9005
O-Ring	NBR
Temperature range	-40 °C...105 °C
Protection class	IP66, IP68 (1 m / 60 min), IP69K
Air flow	0.8 l/min at 0.1 bar ΔP, up to 7.6 l/min at 1bar ΔP
Water inlet point	> 1.5 bar
UL 94 flammability rating	V-2
Note	

Ordering data

Type	Thread	L	L1	SW	Qty.	Order No.
metric						
DAE M12 PA LONG	M 12	17.4	10	17	10	**1868570000**
DAE M12 PA SHORT	M 12	13.4	6	17	10	**1868560000**
Note	Light grey version - RAL 7035 - on request.					

Compensation elements – Stainless steel – DAE

The DAE pressure-compensation element provides good ventilation for the enclosure and prevents moisture build-up. At the same time it maintains the high IP69k protection level. The membrane repels water and oil.



Technical data

Material	Stainless steel 1.4305 (303)
O-Ring	NBR
Temperature range	-40 °C...105 °C
Protection class	IP66, IP68 (1 m / 60 min), IP69K
Air flow	0.4 l/min at 0.1 bar ΔP, up to 5.0 l/min at 1bar ΔP
Water inlet point	> 1.5 bar
Note	

Ordering data

Type	Thread	L	L1	SW	Qty.	Order No.
metric						
DAE M12 SS	M 12	21.1	10	17	10	**1868550000**
Note						

Breather drains – Klippon® BDX

The BDX compensating element is used for ventilating the enclosure and preventing a buildup of moisture, particularly in Ex applications.



Technical data

Material	Brass / Stainless steel 1.4404 (316L)
Protection class	IP66
Impact resistance	7 J ATEX version
Filter	Bronze insert (90% copper, 10% tin)
Air flow	0.25 l / 1 h
Sealing	Silicone / O-Ring
Temperature range	-60 °C...200 °C
Colour	Natural
Note	

Ordering data

Type	Material	Thread	L / L1	SW	*Diameter	Qty.	Order No.
KLIPPON BDX M20 B	Brass	M 20	22 / 10	27	26.20	1	**2519520000**
KLIPPON BDX M20 S	Stainless steel 1.4404 (316L)	M 20	22 / 10	27	26.20	1	**2519550000**
KLIPPON BDX M20X15 S	Stainless steel 1.4404 (316L)	M 20	22 / 15	27	26.20	1	**2519570000**
KLIPPON BDX M25 S	Stainless steel 1.4404 (316L)	M 25	22 / 10	32	31.00	1	**2519590000**

Note

- The breather-drain is only to be fitted on the bottom side of the enclosure, aligned vertically with the thread upwards, and at the lowest point to permit proper drainage.
- The water flow rate has been tested by a water filled empty enclosure (no pressure or heat producing internal components). The water flow rate can slightly differ by influences from operational parameter and environmental conditions.
- Installation specifications and torques can be found in the installation instructions.
- For further information please use our online catalogue: catalog.weidmueller.com.

Cable entry system

Cable entry system	Cable Management – Cable Entry System – Cabtite	E.2
	Cable grommets	E.4
	Cable entry frames	E.5
	Divisible cable gland and accessories	E.7

Flexible and safe insertion of pre-assembled cables

Cabtite – the new modular system cable entry system

Managing pre-assembled cables is challenging for many plant manufacturers, especially when the cables run through cabinet or enclosure walls. A flexible cable entry system speeds up installation, facilitates service, and minimises downtime.

With the Cabtite cable entry system, maximal flexibility and time savings in cable management can be achieved. Assembled and unassembled cables in control cabinets, enclosures and machines are securely sealed and protected against tensile stress. The modular design consisting of a frame or cable gland, snap-in inlays and sealing elements allows quick configuration of cable entry cut-outs – without tools and with reliable sealing in IP66 according to DIN EN 60529.

Your special advantages:

- Maximum flexibility and time savings
- High IP protection class (IP66) as well NEMA 4x and 12
- Integrated strain relief acc. to DIN EN 62444
- Installation safety through simple handling with acoustic feedback
- Preservation of the manufacturer's guarantee for pre-assembled cables
- Fast adaptation of cable management in the event of system changes, service and maintenance cases

Use our online catalogue to find additional product details, technical information and additional services:
www.weidmueller.com/Cabtite

Handling-Video:
Cabtite Cable Entry System
Frame Solution
weidmueller.com/handling-cabtite-fs

Handling-Video:
Handling – Cabtite Cable Entry System
separable retrofit Cable Gland Solution
weidmueller.com/handling-cabtite-cgs

Individual assembly
Whether with frames or with separable cable glands with inlay and sealing elements: the basic modular components guarantee maximal flexibility and a wide range of variants.



High reliability
One click informs the user about the correct installation and guarantees error-free operation. The foamed-in seals guarantee high IP and NEMA protection.

No loss of warranty
Due to the cut-in sealing elements, the cables and wires are precisely encased. Existing connectors do not have to be dismantled – and the manufacturer's warranty is maintained.

Cabtite SE - Sealing element small

Cable grommets for ASI cables

The Cabtite SE sealing elements are used in the Cabtite FR frame or in the separable cable gland Cabtite CGS. The conical design allows easy installation, reliably seals gaps and provides strain relief in accordance with DIN EN 62444. For installation, the sealing elements are pressed from the inside to the outside into the snap-in inlays previously fitted in the frame or, in the case of the Cabtite CGS divisible cable gland, are placed between the cable gland half-shells. Various sealing elements with different cable diameters and geometries are available.

Technical data

Material	TPE
Halogen / Silicone	No / No
Operating temperature, min.	Light Grey: -40 °C; Deep black: -40 °C
Operating temperature, max.	Light Grey: 90 °C; Deep black: 120 °C
UL 94 flammability rating	Light Grey: V-0; Deep black: HB
Note	

Ordering data

Type	Clamping range	Qty.	Deep black	Light Grey
			Order No.	Order No.
Individual sealing elements				
CABTITE SE 1.5-2 SML	1.5...2 mm	10	**2584780000**	**2583360000**
CABTITE SE 2-3 SML	2...3 mm	10	**2584760000**	**2583380000**
CABTITE SE 3-4 SML	3...4 mm	10	**2584730000**	**2583400000**
CABTITE SE 4-5 SML	4...5 mm	10	**2584680000**	**2583440000**
CABTITE SE 5-6 SML	5...6 mm	10	**2584710000**	**2583450000**
CABTITE SE 6-7 SML	6...7 mm	10	**2584690000**	**2583460000**
CABTITE SE 7-8 SML	7...8 mm	10	**2584670000**	**2584660000**
CABTITE SE 8-9 SML	8...9 mm	10	**2584330000**	**2584650000**
CABTITE SE 9-10 SML	9...10 mm	10	**2584080000**	**2584630000**
CABTITE SE 10-11 SML	10...11 mm	10	**2584060000**	**2584610000**
CABTITE SE 11-12 SML	11...12 mm	10	**2584040000**	**2584600000**
CABTITE SE 12-13 SML	12...13 mm	10	**2584020000**	**2584590000**
CABTITE SE 13-14 SML	13...14 mm	10	**2584000000**	**2584570000**
CABTITE SE 14-15 SML	14...15 mm	10	**2583980000**	**2584560000**
CABTITE SE 15-16 SML	15...16 mm	10	**2583960000**	**2584550000**
Special geometry ASI				
CABTITE SE 1/ASI SML		10	**2583530000**	**2584810000**
CABTITE SE 2/ASI SML		10	**2583520000**	**2584800000**
Multiple sealing element				
CABTITE SE 2/4-5 SML	4...5 mm	10	**2583620000**	**2584900000**
CABTITE SE 2/5-6 SML	5...6 mm	10	**2583610000**	**2584890000**
CABTITE SE 2/7 SML	7...8 mm	10	**2583550000**	**2584830000**
CABTITE SE 2/8 SML	8...9 mm	10	**2583540000**	**2584820000**
CABTITE SE 3/5-6 SML	5...6 mm	10	**2652280000**	**2652290000**
CABTITE SE 4/2-3 SML	2...3 mm	10	**2583590000**	**2584870000**
CABTITE SE 4/3-4 SML	3...4 mm	10	**2583580000**	**2584860000**
CABTITE SE 4/4-5 SML	4...5 mm	10	**2583560000**	**2584840000**
Cone sealing element				
CABTITE CSE 2-11 SML	2...11 mm	10	**2583510000**	
Blind plugs				
CABTITE BSE SML		10	**2584790000**	**2583350000**
Note				

Cabtite SE - sealing elements large

Blanking plugs

Cone sealing element

The Cabtite SE sealing elements in large design are identical in construction to those in small design.However, they can accommodate cables with a larger outer diameter.

Technical data

Material	TPE
Halogen / Silicone	No / No
Operating temperature, min.	Deep black: -40 °C; Light Grey: -40 °C
Operating temperature, max.	Deep black: 120 °C; Light Grey: 90 °C
UL 94 flammability rating	Deep black: HB; Light Grey: V-0
Note	

Ordering data

Type	Clamping range	Qty.	Deep black	Light Grey
			Order No.	Order No.
Individual sealing elements				
CABTITE SE 14-15 LRG	14...15 mm	10	**2583880000**	**2584510000**
CABTITE SE 15-16 LRG	15...16 mm	10	**2583860000**	**2584500000**
CABTITE SE 16-17 LRG	16...17 mm	10	**2583850000**	**2584490000**
CABTITE SE 17-18 LRG	17...18 mm	10	**2583840000**	**2584480000**
CABTITE SE 18-19 LRG	18...19 mm	10	**2583830000**	**2584470000**
CABTITE SE 19-20 LRG	19...20 mm	10	**2583810000**	**2584460000**
CABTITE SE 20-21 LRG	20...21 mm	10	**2583790000**	**2584450000**
CABTITE SE 21-22 LRG	21...22 mm	10	**2583770000**	**2584440000**
CABTITE SE 22-23 LRG	22...23 mm	10	**2583750000**	**2584430000**
CABTITE SE 23-24 LRG	23...24 mm	10	**2583730000**	**2584420000**
CABTITE SE 24-25 LRG	24...25 mm	10	**2583710000**	**2584410000**
CABTITE SE 25-26 LRG	25...26 mm	10	**2583700000**	**2584400000**
CABTITE SE 26-27 LRG	26...27 mm	10	**2583690000**	**2584390000**
CABTITE SE 27-28 LRG	27...28 mm	10	**2583680000**	**2584370000**
CABTITE SE 28-29 LRG	28...29 mm	10	**2583670000**	**2584350000**
CABTITE SE 29-30 LRG	29...30 mm	10	**2583660000**	**2584380000**
CABTITE SE 30-31 LRG	30...31 mm	10	**2583650000**	**2584360000**
CABTITE SE 31-32 LRG	31...32 mm	10	**2583640000**	**2584340000**
CABTITE SE 32-33 LRG	32...33 mm	10	**2583630000**	**2584920000**
CABTITE SE 33-34 LRG	33...34 mm	10	**2595510000**	**2584910000**
CABTITE SE 34-35 LRG	34...35 mm	10	**2595520000**	**2595530000**
Cone sealing element				
CABTITE CSE 7-24 LRG	7...24 mm	10	**2583500000**	
Blind plugs				
CABTITE BSE LRG		10	**2583900000**	**2584520000**
Note				

Cabtite FR - CABTITE FR 4-1 BK SET



Possible combinations

The one-piece frame, consisting of a dimensionally stable, fibreglass-reinforced plastic, is quick and easy to assemble and available in four different sizes. The foamed, captive seal guarantees a high degree of impermeability to IP66, even with painted or rough surfaces. The frame sets contain the appropriate Rastinlays to realize the individual configuration (see above a or b) of small and large sealing elements. The sealing elements are not included in the frame set and must be selected to match the cable diameter.

Technical data

Material	Polyamide, glass fibre-reinforced
Colour	Deep black
Operating temperature	-40...120 °C
Protection class / Protection class (UL)	IP54, IP65, IP66 / Type 12, Type 4x
UL 94 flammability rating	V-0
Note	

Ordering data

Type	Qty.	Order No.
Set		
CABTITE FR 4-1 BK SET	1	**2583780000**
Single frame (without snap-in inlay)		
CABTITE FR 4-1 BK	1	**2583490000**
Note The individual frames do not contain any Rastinlays or sealing elements.		

Accessories

Product type	Type	Qty.	Order No.
Locking frame (inside)	CABTITE FRL 4-1 BK	10	**2584260000**
Operating tool	CABTITE TOOL ATSE PA	1	**2637360000**
Mounting screw set	CABTITE SC M5X25 SET	1	**2635120000**
Note			

Dimensioned drawing



Cabtite FR - CABTITE FR 10/6 BK SET



Possible combinations

The one-piece frame, consisting of a dimensionally stable, fibreglass-reinforced plastic, is quick and easy to assemble and available in four different sizes. The foamed, captive seal guarantees a high degree of impermeability to IP66, even with painted or rough surfaces. The frame sets contain the appropriate Rastinlays to realize the individual configuration (see above a or b) of small and large sealing elements. The sealing elements are not included in the frame set and must be selected to match the cable diameter.

Technical data

Material	Polyamide, glass fibre-reinforced
Colour	Deep black
Operating temperature	-40...120 °C
Protection class / Protection class (UL)	IP54, IP65, IP66 / Type 12, Type 4x
UL 94 flammability rating	V-0
Note	

Ordering data

Type	Qty.	Order No.
Set		
CABTITE FR 10/6 BK SET	1	**2583760000**
Single frame (without snap-in inlay)		
CABTITE FR 10/6 BK	1	**2583480000**
Note The individual frames do not contain any Rastinlays or sealing elements.		

Accessories

Product type	Type	Qty.	Order No.
Locking frame (inside)	CABTITE FRL 10/6 BK	10	**2584240000**
Operating tool	CABTITE TOOL ATSE PA	1	**2637360000**
Mounting screw set	CABTITE SC M5X25 SET	1	**2635120000**
Note			

Dimensioned drawing



Cabtite FR - CABTITE FR 16/8 BK SET



Possible combinations

The one-piece frame, consisting of a dimensionally stable, fibreglass-reinforced plastic, is quick and easy to assemble and available in four different sizes. The foamed, captive seal guarantees a high degree of impermeability to IP66, even with painted or rough surfaces. The frame sets contain the appropriate Rastinlays to realize the individual configuration (see above a, b or c) of small and large sealing elements. The sealing elements are not included in the frame set and must be selected to match the cable diameters.

Technical data

Material	Polyamide, glass fibre-reinforced
Colour	Deep black
Operating temperature	-40...120 °C
Protection class / Protection class (UL)	IP54, IP65, IP66 / Type 12, Type 4x
UL 94 flammability rating	V-0
Note	

Ordering data

Type	Qty.	Order No.
Set		
CABTITE FR 16/8 BK SET	1	**2583740000**
Single frame (without snap-in inlay)		
CABTITE FR 16/8 BK	1	**2583470000**
Note The individual frames do not contain any Rastinlays or sealing elements.		

Accessories

Product type	Type	Qty.	Order No.
Locking frame (inside)	CABTITE FRL 16/8 BK	10	**2584220000**
Operating tool	CABTITE TOOL ATSE PA	1	**2637360000**
Mounting screw set	CABTITE SC M5X25 SET	1	**2635120000**
Note			

Dimensioned drawing



Cabtite FR - CABTITE FR 24/10 BK SET



Possible combinations

The one-piece frame, consisting of a dimensionally stable, fibreglass-reinforced plastic, is quick and easy to assemble and available in four different sizes. The foamed, captive seal guarantees a high degree of impermeability to IP66, even with painted or rough surfaces. The frame sets contain the appropriate Rastinlays to realize the individual configuration (see above a, b or c) of small and large sealing elements. The sealing elements are not included in the frame set and must be selected to match the cable diameters.

Technical data

Material	Polyamide, glass fibre-reinforced
Colour	Deep black
Operating temperature	-40...120 °C
Protection class / Protection class (UL)	IP54, IP65, IP66 / Type 12, Type 4x
UL 94 flammability rating	V-0
Note	

Ordering data

Type	Qty.	Order No.
Set		
CABTITE FR 24/10 BK SET	1	**2583720000**
Single frame (without snap-in inlay)		
CABTITE FR 24/10 BK	1	**2583800000**
Note The individual frames do not contain any Rastinlays or sealing elements.		

Accessories

Product type	Type	Qty.	Order No.
Locking frame (inside)	CABTITE FRL 24/10 BK	10	**2584210000**
Operating tool	CABTITE TOOL ATSE PA	1	**2637360000**
Mounting screw set	CABTITE SC M5X25 SET	1	**2635120000**
Note			

Dimensioned drawing



Cabtite CGD - separable cable gland

Spare counter nut

For metric through holes from M20 to M63, the Cabtite cable entry system offers separable cable glands for cables with and without plugs. In case of maintenance or changes in the system, pre-assembled cables with diameters from 2 to 35 mm can be quickly and safely inserted into switch cabinets or housings. After inserting the sealing elements (Cabtite SE), the two halves of the cable gland are simply snapped together. A likewise separable lock nut on the inside of the cabinet ensures a secure and firm hold.

Technical data

Material	Polyamide, glass fibre-reinforced
Colour	Deep black
Operating temperature	-40...120 °C
Protection class / Protection class (UL)	IP54, IP65, IP66 /
UL 94 flammability rating	V-0
Note	

Ordering data

Type	Qty.	Order No.
Divisible cable gland*		
CABTITE CGS M20 BK	10	**2584200000**
CABTITE CGS M25 BK	10	**2584180000**
CABTITE CGS M32 BK	10	**2584160000**
CABTITE CGS M40 BK	5	**2584150000**
CABTITE CGS M50 BK	5	**2584130000**
CABTITE CGS M63 BK	5	**2584120000**
Articulated locknut		
CABTITE LNS M20 BK	10	**2584110000**
CABTITE LNS M25 BK	10	**2584090000**
CABTITE LNS M32 BK	10	**2584070000**
CABTITE LNS M40 BK	5	**2584050000**
CABTITE LNS M50 BK	5	**2584030000**
CABTITE LNS M63 BK	5	**2584010000**
Rastinly for M40-M63**		
CABTITE GI X BK	5	**2584290000**
Note	*The cable glands are supplied with a locknut. **The snap-in insert is required to install 4 small sealing elements in the cable gland.	

Dimensioned drawing



Cabtite GI - Rastinlay

The insertable snap-in inlay allows the frame openings/cable glands to be configured as required for the small or large sealing elements used. Thus the Cabtite cable entry system can be variably configured for different requirements (cables, lines, hoses, pneumatic and hydraulic lines).

Technical data

Material	Polyamide, glass fibre-reinforced
Colour	Deep black
Operating temperature	-40...120 °C
Protection class / Protection class (UL)	IP54, IP65, IP66 /
UL 94 flammability rating	V-0
Note	

Ordering data

Type	Qty.	Order No.
CABTITE GI I BK	5	**2584320000**
CABTITE GI T BK	5	**2584300000**
CABTITE GI H BK	5	**2584270000**
Rastinly for M40-M63**		
CABTITE GI X BK	5	**2584290000**
Note	**The locking inlay is required to install 4 small sealing elements in the cable gland.	

Dimensioned drawing



Cabtite CR - Cable support strips (EMC)

In combination with a large number of different shield connection clamps (KLBÜ), the shield connection rails enable practical, uncomplicated and fast shielding of cables.

Technical data

Material	Steel, galvanized
Colour	silver

Note

Ordering data

Type	Qty.	Order No.
CABTITE CR 4-1 EMV	10	2583950000
CABTITE CR 10/6 EMV	10	2583930000
CABTITE CR 16/8 EMV	10	2583910000
CABTITE CR 24/10 EMV	10	2583890000

Note

Dimensioned drawing



Cabtite BP - Blanking plug

The blind plugs are used for the safe closing of unneeded cable passages in the sealing elements.

Technical data

Material	Polyamide
Colour	red
Operating temperature	-60...100 °C

Note

Ordering data

Type	Qty.	Order No.
CABTITE BP 2MM PA	50	2652300000
CABTITE BP 3MM PA	50	2652310000
CABTITE BP 4MM PA	50	2652320000
CABTITE BP 5MM PA	50	2652330000
CABTITE BP 6MM PA	50	2652340000
CABTITE BP 7MM PA	50	2652350000
CABTITE BP 8MM PA	50	2652360000
CABTITE BP 9MM PA	50	2652370000
CABTITE BP 10MM PA	50	2652380000
CABTITE BP 12MM PA	50	2652400000
CABTITE BP 13MM PA	50	2652410000
CABTITE BP 14MM PA	50	2652420000
CABTITE BP 17MM PA	50	2652430000
CABTITE BP 20MM PA	50	2652440000
CABTITE BP 21MM PA	50	2652450000
CABTITE BP 25MM PA	50	2652460000
CABTITE BP 28MM PA	50	2652470000
CABTITE BP 35MM PA	50	2652480000

Note

Tools

Tools	Overview	F.2

Tools

At Weidmüller, we have been developing and manufacturing quality tools to meet the most stringent requirements for over 30 years. When we develop new solutions, we always keep our goal in mind: to make your job easier, optimise processes and help protect the long-term productivity of your business.

The best conditions for this can be created by using perfectly coordinated products and tools from a single source. Our range includes professional manual tools for cutting, stripping, crimping, testing and screwing. The assortment is supplemented by tool sets that sensibly and efficiently combine tools and matching accessories. Our machines simplify continually recurring tasks and save valuable time.

Your special advantages:

- Increased safety thanks to the tool certification service
- Flexibility in form and function
- High level of efficiency thanks to sophisticated ergonomics and multiple actions per work process
- Profitable interplay between products and tools from a single source



Stripping tools
Thanks to the exact adaptation to the insulation and wire cross-section, our professional stripping tools guarantee defect-free processing with consistently reliable stripping results. With its wide range of stripping tools, Weidmüller satisfies all the criteria for professional cable processing.

Cable gland tools
The Weidmüller cable gland tools are suitable for an extremely wide range of cable glands. They enable you to tighten or loosen several rows of connections without deforming the cable glands.

Screwdrivers
Weidmüller screwdrivers allow for the perfect handling of all grip sizes. They ensure maximum torques and optimal transfer of the axial force. Available in all standard dimensions.



Cutting tools
Weidmüller is a specialist in the cutting of copper and aluminium cables. The range of products extends from cutting tools with direct force application for small cross-sections to cutting tools for large diameters.

Service and support

Service and support	Our expertise for your requirements	V.2
	Benefit from optimum support when using our products	V.4

Our expertise for your requirements
Service connects - worldwide

Automation technology functions are becoming more complex in a globally-oriented world facing ambitious targets in terms of energy efficiency and smart production. We are your equal partners for the best connections in Industrial Connectivity. Our worldwide network of industrial managers for machine construction, process automation, energy and traffic engineering and for device manufacturers know the challenges you face and can support you in your specific applications.

Training course on technologies, applications and the detailed functionality of our products is available to you locally or at our headquarter in Germany. Our personal support can answer any questions reliably and expertly. Our online services are available 365 day a year around the clock to provide answers to your questions on our products - from user documentation through software to planning tools.

In short: Weidmüller's global service combines our expertise with your requirements.

Professional advice on planning
Our global network of industrial managers has extensive experience in automation technology and electrical connectivity. This expertise allows us to assist you with advice and planning support in order to work with you on resolving the everyday challenges of your applications.

Technology and application training
Industrial automation is moving towards smart production. It faces the challenges of new technologies and applications. Our varied range of training courses develops this knowledge further or provides more in-depth information on the handling of our products and solutions. Our seminars are modular and can be customised. We can train you and your employees in our academy, on your premises if you wish or online in our webinars at any time.

Customised installation
The challenges for the future are reducing costs and increasing efficiency. This requires intelligent, individual solutions which are tailored to your requirements. We can offer a highly qualified customer-specific production service in our application centre. Whether you need modified products, pre-assembled terminal rails or complete small cabinets: we produce the solutions developed for your application quickly and flexibly.

Online support and downloads

Exactly the right help and information on our solutions and products

If our products are used in your automation technology applications, you need the best possible individual support, from planning through installation to operation.

For every stage of your application, we can offer the right tools and information for our products and solutions. Up-to-date, uncomplicated, comprehensive and around the clock via our service portal at www.weidmueller.com/service.

Fast access to our support and services is available via Weidmüller webcodes. Simply select the service you want on the right hand side, then enter the webcode made up of five digits with a preceding hashtag into the search field in the top right corner of www.weidmueller.com and it will bring up the details you need.

Online and personal support

From planning through installation to operation, we can provide exactly the right help and information for each step of your application based on our solutions and products: up-to-date, uncomplicated and comprehensive, around the clock, online or in person.

Visit our website
for more information

www.weidmueller.com/service

Let's connect.

Engineering Support

As a developer, you need simple processes and system-wide tools. We support you in your development environment with comprehensive data, software tools and interfaces, product selection guides and development samples.

Technical data and downloads

Download all the documents and software relating to our products by simply entering the item number. You can also view our Online Catalogue and research the technical properties of our products.

Commercial support

Integrate our product data into your commercial sytem using standardised interfaces or familiarise yourself with the wide range of products in our technical catalogues.

Engineering data
Webcode #01219

Find downloads
Webcode #11379

Electronic catalogue in BMECat format and other formats
Webcode #11378

Product software
Webcode #01212

Products in the Online Catalogue
Webcode #01217

Access our Webshop
Webcode #11382

Whitepaper for device connectivity
Webcode #11359

Security Advisory Board
Webcode #11424

Technical catalogue in PDF Format
Webcode #01218

Engineering software
Webcode #11377



Product Change Notification
Webcode #11425

Product configurators, product selection guides and samples
Webcode #01214

More offers in online support and downloads

Not found what you are looking for? We have even more to offer you in online support and downloads.

Approvals, certificates and declaration of conformity
Webcode #11374

Here you will find information on the CE declaration of conformity, on RoHS and REACH and other company related certificates and approvals.

Technical appendix

Technical appendix	Directive 1999/92/EC	W.2
	ATEX directive 2014/34/EU	W.5
	IECEx scheme	W.6
	Hazardous areas guide	W.7
	IP class of protection	W.10
	Guidelines for selecting cable glands	W.12
	Ratings plate of an empty enclosure	W.14
	Type label for enclosure assemblies	W.15

Directive 1999/92/EC

Article 137 of the European Community Formation Treaty set out the minimum standards in order to improve workers' health and safety, this can also be put at risk by explosive atmospheres. An explosive atmosphere is a mixture of air and flammable gasses, vapours, mists or dust under atmospheric conditions where, following successful ignition, the burning process will propagate throughout the whole unburned mixture.

The directive 1999/92/EC was transferred into national law. Compliance with the minimum standards contained in this directive does not guarantee that all relevant national laws are met. It is possible for local regulators to introduce more stringent requirements.

The employer is required, according to the directive 1999/92/EC, to take measures to ensure the health and safety of the employees. One measure is the division of the area into zones where explosive atmospheres could be present.

Unless the risk analysis conducted by the employer indicates otherwise, all areas where an explosive atmosphere may be present must be equipped with devices and protective systems that meet the relevant category of the ATEX directive 2014/34/EU.
In particular in these zones the following categories of equipment should be used, as long as they are suitable for use with gases, vapours, mists or dusts:

- In Zone 0 or Zone 20: category 1 devices
- In Zone 1 or Zone 21: category 1 or category 2 devices
- In Zone 2 or Zone 22: category 1, category 2 or category 3 devices

Zoning according to the directive 1999/92/EC
Explosion risk areas are classified into zones according to likelihood of explosive atmospheres occurring and their persistence.

Zone 0
An area which has a potentially explosive atmosphere that is a mixture of air and **flammable gases, vapours or mists**. The mixture is either permanently present or frequently present over long periods of time.

Zone 1
An area in which during normal operations a potentially explosive atmosphere of air and **flammable gases, vapours or mists** can occasionally form.

Zone 2
An area for which during normal operations there is at most only a short-term occurrence of a potentially explosive atmosphere of mixtures of air and **flammables gases, vapours or mists**.

Zone 20
An area where a potentially explosive atmosphere is present in the form of a **flammable dust** cloud in the air. This cloud is either permanently present or frequently present over long periods of time.

Zone 21
An area where, during normal operations, a potentially explosive atmosphere in the form of a **flammable dust** cloud in the air can occasionally form.

Zone 22
An area where, during normal operations, a potentially explosive atmosphere in the form of a **flammable dust** cloud in the air is not normally present or only present for a short time.

For the risk assessment and as well as the zoning concept described above, Ex devices themselves can be considered in an alternative process which uses the equipment protection level (EPL). These protective levels determine the internal ignition risk of a device where the sort of applied protection does not play a role.

The system of EPL classifications (Equipment Protection Level) is shown below.

Firedamp (methane) risk mines (Group I)

EPL Ma
Equipment for installation in mining applications, offering a „very high" level of protection and which do not constitute a source of ignition during normal operation, or in the event of rarely occurring faults.

EPL Mb
Equipment for installation in a mine with a high level of rotection. Has sufficient safety to ensure that there is no source of ignition in the period of time between the outbreak of gas and the time the equipment is switched off.

Gases (Group II)

EPL Ga
Equipment for explosive-risk gas atmospheres with a very high level of protection. No source of ignition is present during normal operation or when errors occur that cannot be necessarily expected on a regular basis.

EPL Gb
Equipment for explosive-risk gas atmospheres with a high level of protection. No source of ignition is present during normal operation or when errors occur that cannot be necessarily expected on a regular basis.

EPL Gc
Equipment for explosive-risk gas atmospheres with an elevated level of protection. No source of ignition is present during normal operation and it can have additional safeguards to ensure that none is present during faults which happen regularly (e. g. failure of a lamp).

Dust (Group III)

EPL Da
Equipment for combustible dust atmospheres with a very high level of protection. No source of ignition is present during normal operation or in very rare faults.

EPL Db
Equipment for combustible dust atmospheres with a high level of protection. No source of ignition is present during normal operation or when errors occur that cannot be necessarily expected on a regular basis.

EPL Dc
Equipment for combustible dust atmospheres with an elevated level of protection. No source of ignition is present during normal operation and it can have additional safeguards to ensure that none is present during faults which happen regularly (e. g. failure of a lamp).

Order your own guide for explosive risk zones
Article number: 2654330000

Classification of explosive groups

Electrical devices for groups II and III are classified further as a function of the properties of the explosive atmosphere for which they are intended.

The danger of the atmosphere increases from IIA(IIIA) to IIC(IIIC) so that all equipment certified for use in IIC(IIIC) areas may also be used in IIA(IIIA) and IIB(IIIB) areas.

Classification of explosive groups

Group	Material, e.g.	Ignition energy	Group	Material
IIA	Propane	266 µJ	IIA	Flammable fluff
IIB	Ethylene	85 µJ	IIB	Non-conductive dust
IIC	Hydrogen	19 µJ	IIC	Conductive dust

Classification of zones and equipment categories

Combustible ingredients	Explosive atmospheres	Zone division	EPL safety level	Identification	
				Equipment group	Device category
Gas, mist, vapours/fumes (G / Gas)	permanent, long-term	Zone 0	Ga	II	1G
	occasionally	Zone 1	Gb	II	2G
	unlikely, short-term	Zone 2	Gc	II	3G
Dusts (D / Dust)	permanent, long-term	Zone 20	Da	II	1D
	occasionally	Zone 21	Db	II	2D
	unlikely, short-term	Zone 22	Dc	II	3D

ATEX directive 2014/34/EU

Article 96 of the Treaty on the Foundation of the European Union and Decision no. 768/2008/EU and Federal Gazette 96/309-356 govern the standardisation of legal regulations in the Member States. The ATEX directive 2014/34/EU sets out the basic requirements for health and safety protection as a directive following the new concept. It is aimed at manufacturers of equipment and components designed for used in potentially explosive atmosphere areas.

This directive had to be adopted without deviation into national law.
For Germany, this took the form of the passing of the Explosion Protection Ordinance (2015 ExVo 2015) of the Product Safety Act (ProdSG). It applies to all industrial potentially explosive areas, including mines, and also covers protection from dust-ignited explosions.

This directive sets out the requirements for the products depending on their equipment group and category. This is the category as set down by the directive 1999/92/EC applicable for each appropriate zone.

To prove conformity with the basic health and safety regulations, harmonised standards are used. If the requirements as laid out in the Official Journal of the EU are met, then it will be in compliance with the standard requirements for conformity (presumption of conformity). Various, mostly equivalent, protection types have been standardised harmoniously.

This conformity assessment process of the directives sets out different procedures. For device category 3, the manufacturer can perform the conformity assessment itself. For devices of categories 1 and 2, this conformity check must be carried out at a notified body in the form of a EC type-examination. In addition, quality assurance must be monitored for the devices of categories 1, 2 and 3.

Weidmüller has devices and components in its product range. Empty enclosures are components and are certified at the factory as such. Installing certified components does not create a certified equipment. To do this, additional tests must be carried out.

Weidmüller offers customer-specific devices available as certified solutions. The production of assembled enclosures is monitored by a notified body.

IECEx scheme

The IECEx scheme is an international certification scheme for products which meet the requirements of the international standards, e.g. the technical committee TC31's IEC standards.

The certificates awarded in this scheme are published on the IECEx website (www.iecex.com) as an electronic certificate. They can be viewed online and printed out.

A Certificate of Conformity (CoC) refers to a test report (Ex Test Report ExTR) and on an assessment of the quality assessment report from the manufacturer (QAR).

The standards used for the production of the test report correspond almost entirely to the harmonised standards in Europe. Recent EN standards were initially adopted as IEC standards.

Protection concepts

The zoning described above provides the basis for the selection of the type of ignition protection. So, as an example, in the ATEX applicable areas, only ignition protection devices meeting Ex ia for Zone 0 (highest probability of an explosive atmosphere being present) are allowed.

Increased safety Ex e
No sparks and a surface temperature limited to a safe level



Increased safety is for products where there are no sparks produced during normal operation or in case of a failure. The surface temperature of the relevant parts is limited to a value below the ignition temperature. Increased safety is achieved by reducing the current load and raising the isolation properties and by maintaining clearance and creepage distances above the value in an industrial application. The highest voltage permitted for this protection scheme is 11 kV (D.C. or A.C. rms).

This protection scheme is usually used for distribution cabinets..

Intrinsically safe Ex i
Limited to a safe level of ignition energy



Intrinsic safety is for products where electrical energy which flows into the product, or is stored in the product, is not sufficient to ignite the surrounding explosive atmosphere. This also applies in fault conditions. The methods that achieve intrinsic safety mean that it is important that not only the devices installed in direct contact with the explosive atmosphere are constructed correctly, but also the electrical devices to which they are connected.

Intrinsically safe equipment and intrinsically safe parts of the associated equipment are divided into protection levels: ia (for zones 0, 1, and 2), ib (for zones 1 and 2), and ic (only for zone 2).

A typical application area are control and display circuits with low voltage and current.

Pressure-resistant Ex d encapsulation
Limits the explosion to the inside of the enclosure



Pressure-resistant encapsulated enclosures are designed for devices where sparks are generated or which have hot surfaces which are a source of ignition during normal operation. Similarly, industrial components for use in potentially explosive atmospheres are often made suitable by encapsulating them in a pressure-resistant enclosure which otherwise could not be used.

The surrounding possibly explosive atmosphere can enter the enclosure and will produce an internal explosion during the equipment's lifespan.

The enclosure must therefore be stable enough to ensure that it is not deformed or destroyed by the pressure created. All connections of the enclosure are sized so that they cannot transmit an explosion from inside to the surrounding atmosphere. These connections are known as ignition gaps.

Area classification



Gas groups

IIA	e.g. Propane
IIB	e.g. Etyhlene
IIC	e.g. Hydrogen

Equipment group acc. to directive 2014/34/EU		**Equipment category** acc. to directive 2014/34/EU		**Classification of hazardous areas** acc. to directive 1999/92/EG	**Group** acc. to IEC/EN 60079-0	**Combustible materials**	**Equipment protection level** (EPL acc. to IEC/EN 60079-0)
I	Mining	M1	very high level of protection; remain functional at occurrence of Ex-atmosphere		I	Methane, Carbon dust	Ma
I		M2	high level of protection; de-energized at occurrence of Ex-atmosphere		I		Mb
II	Other industries (except mining)	1	very high level of protection; save even in an event of rare incidents	0	II	Gases, Vapours, Mists (G)	Ga
II		2	high level of protection; save even in an event of predictable failures	1	II		Gb
II		3	normal level of protection; save during normal operation	2	II		Gc
II	Other industries (except mining)	1	very high level of protection; save even in an event of rare incidents	20	III	Dust (D)	Da
II		2	high level of protection; save even in an event of predictable failures	21	III		Db
II		3	normal level of protection; save during normal operation	22	III		Dc



Dust groups

IIIA	Combustible flyings
IIIB	Non-conductive dust
IIIC	Conductive dust

Types of Protection

Types of protection for electrical equipment in explosive gas atmospheres

Type of protection	Symbol	Main application	Norm
increased safety	eb	junction boxes, control stations for installing Ex-components (with a different type of protection), squirrel-cage motors, light fittings	IEC 60079-7 EN 60079-7 ISA 60079-7
flameproof enclosures	db	switchgears, control stations, indicating equipment, control systems, motors, transformers, heating equipment, light fittings	IEC 60079-1 EN 60079-1 ISA 60079-1
pressurized enclosures	pxb pyb pzc	switchgear and control cabinets, analysers, large motors	IEC 60079-2 EN 60079-2 ISA 60079-2
intrinsic safety	ia ib ic	instrumentation technology, fieldbus technology, sensors, actuators [Ex ib] = associated electrical apparatus – installation in the safe area	IEC 60079-11 EN 60079-11 ISA 60079-11
		intrinsically safe systems	IEC 60079-25 EN 60079-25
		FISCO: fieldbus intrinsically-safe concept	IEC 60079-27 EN 60079-27 ISA 60079-27
oil immersion	ob	transformers, starting resistors	IEC 60079-6 EN 60079-6 ISA 60079-6
powder filling	qb	sensors, display units, electronic ballasts, transmitters	IEC 60079-5 EN 60079-5 ISA 60079-5
encapsu-lation	ma mb mc	switchgear with small capacity, control and signalling units, display units, sensors	IEC 60079-18 EN 60079-18 ISA 60079-18
type of protection "n"	nAc nCc nRc	all electrical equipment for Zone 2 nA = non-sparking device nC = sparking devices and components nL = energy limited apparatus nR = restricted breathing enclosures	IEC 60079-15 EN 60079-15 ISA 60079-15
optical radiation	op_a op_b op_c	op is = inherently safe optical radiation op pr = protected optical radiation op sh = optical radiation interlock	IEC 60079-28 EN 60079-28

Types of protection for electrical equipment in explosive dust atmospheres

Type of protection	Symbol	Main application	Norm
protection by enclosures	ta tb tc	switchgear, control stations, junction boxes, control boxes, motors, light fittings	IEC 60079-31 EN 60079-31 ISA 60079-31
pressuri-zation	pb pc	switchgear and control cabinets, motors	IEC 60079-2 EN 60079-2 ISA 60079-2
intrinsic safety	ia ib ic	instrumentation technology, fieldbus technology, sensors, actuators [Ex ib] = associated electrical apparatus – installation in the safe area	IEC 60079-11 EN 60079-11 ISA 60079-11
encapsu-lation	ma mb mc	switchgear with small capacity, control and signalling units, display units, sensors	IEC 60079-18 EN 60079-18 ISA 60079-18

Temperature class

Classification of the maximum surface temperatures into temperature classes for eletrical equipment of group II

Temperature class ATEX/IECEx	Temperature class NEC/UL (AEx)	Maximum surface temperature	
T1	T1	450 °C	842 °F
T2	T2	300 °C	572 °F
	T2A	280 °C	536 °F
	T2B	260 °C	500 °F
	T2C	230 °C	446 °F
	T2D	215 °C	419 °F
T3	T3	200 °C	392 °F
	T3A	180 °C	356 °F
	T3B	165 °C	329 °F
	T3C	160 °C	320 °F
T4	T4	135 °C	275 °F
	T4A	120 °C	248 °F
T5	T5	100 °C	212 °F
T6	T6	85 °C	185 °F
IEC/DIN EN 60079-0	NEC500ff	°C	°F

Certifications worldwide

IP class of protection to DIN EN 60529

The ingress protection class or IP rating is indicated by a code consisting of the two letters IP and two digits representing the class of protection.

Example: **I P 6 5**

2nd digit: protection from liquids

1st digit: protection from solid bodies

Protection against intrusion of external particle matter (1st digit)

Code digit		
0		No protection
1		Protection against ingress of large solid bodies with diameter > 50 mm. (Protection to prevent dangerous parts being touched with the back of the hand.)
2		Protection against ingress of large solid bodies with diameter > 12.5 mm. (Protection to prevent dangerous parts being touched with the fingers.)
3		Protection against ingress of large solid bodies with diameter > 2.5 mm. (Protection to prevent dangerous parts being touched with a tool.)
4		Protection against ingress of large solid bodies with diameter > 1 mm. (Protection to prevent dangerous parts being touched with a piece of wire.)
5		Protection against harmful deposits of dust, which cannot enter in an amount sufficient to interfere with satisfactory operation.
6		Complete protection against ingress of dust.

Protection against penetration of liquids (2nd digit)

Code digit		
0		No protection
1		Protection against drops of condensed water falling vertically.
2		Protection against drops of liquid falling at an angle of 15° with respect to the vertical.
3		Protection against drops of liquid falling at an angle of 60° with respect to the vertical.
4		Protection against liquids splashed from any direction.
5		Protection against water jets projected by a nozzle from any direction.
6		Protection against water from heavy sea on ships'decks.
7		Protection against immersion in water under defined conditions of pressure and time.
8		Protection against indefinite immersion in water under defined conditions of pressure (which must be agreed between manufacturer and user and must be more adverse than number 7).

Definition of the protection degrees according to NEMA, UL and CSA

Type	NEMA	UL	CSA
Designation	National Electrical Manufacturers Association NEMA 250-1991	Underwriters Laboratories Inc. UL 50 und UL 508	Canadian Standards Association CSA-C22.2 No. 94-M91
Type 1	Enclosure predominately for indoor use. Protection against penetration by solid foreign bodies.	Enclosure predominately for indoor use. Protection against penetration by solid foreign bodies.	Enclosure for general use. Protection against accidental contact with live components.
Type 2	Enclosure predominately for indoor use. Protection against penetration by solid foreign bodies and water.	Enclosure predominately for indoor use. Protection against penetration by solid foreign bodies and water.	Enclosure for indoor use. Protection against non-corrosive drops/splashes of liquid and foreign bodies.
Type 3	Enclosure predominately for indoor use. Protection against penetration by rainfall and dust as well as damage due to ice formation.	Enclosure predominately for indoor use. Protection against penetration by rainfall and dust as well as damage due to ice formation.	Enclosure for indoor or outdoor use. Protection against penetration by rainfall and snow as well as damage due to ice formation.
Type 3R	Enclosure predominately for indoor use. Protection against rain and snow as damage due to ice-formation.	Enclosure predominately for indoor use. Protection against rain and snow as damage due to ice-formation.	Enclosure for indoor or outdoor use. Protection against penetration by rainfall and snow as well as damage due to ice formation.
Type 3S	Enclosure predominately for indoor use. Protection against rain, snow and foreign bodies. External mechanisms can be operated despite ice accumulation.	Enclosure predominately for indoor use. Protection against rain, snow and foreign bodies. External mechanisms can be operated despite ice accumulation.	Enclosure for indoor or outdoor use. Protection against rain, snow and foreign bodies. External mechanisms can be operated despite ice accumulation.
Type 4	Enclosure for indoor or outdoor use. Protection against rain, foreign bodies, splashing water and hose water as well as damage due to ice-formation on the outside of the enclosure.	Enclosure for indoor or outdoor use. Protection against rain, foreign bodies, splashing water and hose water as well as damage due to ice-formation on the outside of the enclosure.	Enclosure for indoor or outdoor use. Protection against rain, snow, foreign bodies, splashing water and hose water as well as damage due to ice-formation on the outside of the enclosure.
Type 4X	Enclosure for indoor or outdoor use. Protection against corrosion, rain, foreign bodies, splashing water and hose water as well as damage due to ice-formation on the outside of the enclosure.	Enclosure for indoor or outdoor use. Protection against corrosion, rain, foreign bodies, splashing water and hose water as well as damage due to ice-formation on the outside of the enclosure.	Enclosure for indoor or outdoor use. Protection against rain, foreign bodies, splashing water and hose water as well as damage due to ice-formation on the outside of the enclosure.
Type 6	Enclosure for indoor or outdoor use. Protection against hose water as well as against penetration by water during immersion; protection damage due to ice formation on the outside of the enclosure.	Enclosure for indoor or outdoor use. Protection against hose water as well as against penetration by water during immersion; protection damage due to ice formation on the outside of the enclosure.	Enclosure for indoor or outdoor use. Protection against penetration by water during immersion; protection damage due to ice formation on the outside of the enclosure.
Type 12	Enclosure for indoor use. Protection against dust accumulation, foreign bodies and non-corrosive drops of liquids.	Enclosure for indoor use. Protection against dust accumulation, foreign bodies and non-corrosive drops of liquids.	Enclosure for indoor or outdoor use. Protection against a build-up of dust, fibres and foreign bodies as well as against non-corrosive liquid drips, without pre-formed openings.
Type 13	Enclosure for indoor use. Protection against dust build-up, splashing water, oil, and non-corrosive coolants.	Enclosure for indoor use. Protection against dust build-up, splashing water, oil, and non-corrosive coolants.	Enclosure for indoor or outdoor use. Protection against a build-up of dust, fibres and foreign bodies as well as against non-corrosive liquid sprays including oil and coolants.

Guidelines for selecting cable glands

The sizes quoted were based on stranded cables. Please note the clamping range for the cable gland you have selected.

Cross-section	No. of conductors	Cable ø approx. mm	Metric cable glands								PG							
0.5 mm²	2	5.7 - 8.7	12	16	20						9							
AWG 20	3	6.0 - 9.0	12	16	20						9							
	4	6.7 - 9.7	12	16	20						9	11						
	5	7.2 - 10.2		16	20						9	11	13.5	16				
	6	7.6 - 10.6		16	20						9	11	13.5	16				
	7	8.0 - 10.6		16	20						9	11	13.5	16				
	8	9.4 - 12.8		16	20	25					9	11	13.5	16				
	10	9.4 - 12.8		16	20	25					9	11	13.5	16				
	12	9.7 - 12.9		16	20	25					9	11	13.5	16				
	14	10.2 - 13.4			20	25						11	13.5	16				
	16	10.7 - 13.9			20	25						11	13.5	16				
	21	12.3 - 15.1			20	25							13.5	16	21			
	24	13.5 - 16.7				25	32						13.5	16	21			
	30	14.3 - 17.5				25	32							16	21			
	35	16.0 - 18.6				25	32								21			
	40	16.6 - 19.2				25	32	40							21			
	52	19.2 - 21.6					32	40							21	29		
	61	20.3 - 23.1					32	40							21	29		
	80	22.9 - 25.7					32	40								29	36	
	100	26.4 - 29.6						40	50							29	36	
0.75 mm²	2	6.8 - 9.8	12	16	20						9	11						
AWG 18	3	7.2 - 9.7	12	16	20						9	11						
	4	7.9 - 10.3	12	16	20						9	11						
	5	8.9 - 10.9		16	20						9	11	13.5	16				
	6	8.9 - 12.3		16	20	25					9	11	13.5	16				
	7	9.6 - 12.3		16	20	25					9	11	13.5	16				
	8	10.4 - 13.8			20	25						11	13.5	16				
	9	10.7 - 13.9			20	25						11	13.5	16				
	10	10.4 - 13.8			20	25						11	13.5	16				
	12	10.7 - 13.9			20	25						11	13.5	16				
	15	12.3 - 13.5			20	25							13.5	16				
	18	13.0 - 16.2				25	32						13.5	16	21			
	21	13.6 - 16.8				25	32						13.5	16	21			
	25	15.9 - 18.5				25	32								21	29		
	32	17.1 - 19.7				25	32								21	29		
	40	19.0 - 21.4					32	40							21	29		
	50	21.3 - 24.1					32	40							21	29		
	61	22.6 - 25.4						40							21	29	36	
	80	26.1 - 29.3						40	50							29	36	
	100	29.4 - 33.0						40	50								36	
1 mm²	2	7.1 - 10.1	12	16	20						9	11						
AWG 16-18	3	7.5 - 10.1	12	16	20						9	11						
	4	8.4 - 10.7		16	20						9	11	13.5					
	5	9.2 - 11.4		16	20	25					9	11	13.5	16				
	6	9.2 - 12.6		16	20	25					9	11	13.5	16				
	7	9.2 - 12.6		16	20	25					9	11	13.5	16				
	8	11.0 - 14.4			20	25						11	13.5	16	21			
	9	11.8 - 15.2			20	25	32					11	13.5	16	21			
	10	11.0 - 14.4			20	25	32					11	13.5	16	21			
	12	11.8 - 14.6			20	25	32					11	13.5	16	21			
	14	12.4 - 15.2			20	25	32						13.5	16	21			
	16	13.0 - 16.2				25	32						13.5	16	21			
	18	13.7 - 16.9				25	32						13.5	16	21			
	20	14.4 - 17.6				25	32	40						16	21			
	24	16.5 - 19.1				25	32	40							21	29		
	25	16.9 - 19.5				25	32	40							21	29		
	34	19.4 - 21.8					32	40							21	29		
	48	22.0 - 24.8						40							21	29		
	56	23.2 - 26.0						40	50						21	29	36	
	61	24.5 - 27.2						40	50							29	36	
	80	27.7 - 30.9						40	50								36	
	100	31.8 - 35.2						40	50	63							36	42

Cross-section	No. of conductors	Cable ø approx. mm	Metric cable glands								PG							
1.5 mm²	2	8.0 - 11.0	12	16	20						9	11	13.5	16				
AWG 16	3	8.7 - 11.0		16	20	25					9	11	13.5	16				
	4	9.7 - 11.8		16	20	25					9	11	13.5	16				
	5	10.8 - 13.0			20	25						11	13.5	16				
	6	10.8 - 14.2			20	25						11	13.5	16				
	7	10.8 - 14.2			20	25						11	13.5	16				
	8	13.2 - 16.6				25	32						13.5	16	21			
	11	13.6 - 16.8				25	32						13.5	16	21			
	12	17.6 - 16.8				25	32						13.5	16	21			
	14	14.4 - 17.6				25	32							16	21			
	16	15.8 - 18.4				25	32							16	21			
	18	16.6 - 19.2				25	32								21	29		
	20	17.4 - 20.0				25	32	40							21	29		
	25	20.2 - 23.0					32	40							21	29		
	32	23.8 - 24.5						40								29	36	
	34	22.6 - 25.4						40								29	36	
	42	25.8 - 29.0						40	50							29	36	
	50	27.0 - 30.2						40	50							29	36	
	56	27.8 - 31.0						40	50							29	36	
	61	28.6 - 31.8						40	50								36	
	80	33.0 - 36.4							50	63							36	42
	90	34.6 - 37.6							50	63							36	42
	100	37.8 - 41.4							50	63								42
2.5 mm²	2	9.8 - 12.8		16	20	25					9	11	13.5	16				
AWG 12-14	3	10.6 - 13.4			20	25						11	13.5	16				
	4	11.7 - 14.4			20	25						11	13.5	16				
	5	13.0 - 16.4			20	25	32						13.5	16	21			
	6	13.3 - 16.7				25	32						13.5	16	21			
	7	13.3 - 16.7				25	32						13.5	16	21			
	8	17.4 - 20.8				25	32	40							21	29		
	11	18.0 - 20.6				25	32	40							21	29		
	16	20.6 - 23.4					32	40							21	29		
	18	21.7 - 24.5						40								29	36	
	25	26.4 - 29.6						40	50							29	36	
	34	31.3 - 33.1						40	50								36	42
	50	37.0 - 39.4							50	63								42
	61	39.0 - 41.5							50	63								42
4 mm²	2	10.7 - 14.1			20	25						11	13.5	16	21			
AWG 10-12	4	13.0 - 16.4				25	32						13.5	16	21			
	5	14.3 - 17.7				25	32							16	21			
	7	16.2 - 19.6				25	32								21	29	36	
	11	ca. 24.5						40								29	36	

Note:
The values can differ between manufacturers. These figures should be considered as rough guidelines.

Ratings plate of an Ex-certified empty enclosure

1 Number of the notified body

2 Part No.

3 Part designation

4 Ex marking

5 Equipment group

6 Device category

7 • G Gas (gas)
• D flammable dust

8 Explosion protection type

9 IP ingress protection class (DIN EN 60529)

10 EC type-examination certificate

11 Year of manufacture

12 Name and address of manufacturer



Type label for enclosure assemblies

1 Certification conditions and logo

2 Name and address of manufacturer

3 Approval number

4 Part designation

5 Part No.

6 Serial number

7 Year of Contruction

8 IP ingress protection class

9 Ambient temperature

10 Approval number

11 Ex marking
Example:



Weidmüller

Weidmüller Interface GmbH & Co. KG **2**
Klingenbergstr. 16 – D 32758 Detmold

c UL us **1**
LISTED
Juncition Box for HAZ. LOC.
E223792
3

4 Type: Klippon TB MH 303020
5 P/N: 9876543219
6 S/N: XA-DE-A-0000
7 Year of Construction: 2018

8 IP 66 NEMA TYPE: 4x

Rated voltage: 600 [V] Cable size: 4 [mm²]
Rated current: 21 [A] **9** T amb: - 20 °C ... + 55 °C

11 Class I Zone 1 AEx e IIC T4 Gb

W A R N I N G - DO NOT OPEN WHEN ENERGIZED

Weidmüller

Weidmüller Interface GmbH & Co. KG **2**
Klingenbergstr. 16 – D 32758 Detmold

CE **1**
0344

4 Type: Klippon TB MH 303020
5 P/N: 9876543219
6 S/N: XA-DE-A-0000
7 Year of Construction: 2018

8 IP 66

Rated voltage: 600 [V] Cable size: 4 [mm²]
Rated current: 21 [A] **9** T amb: - 20 °C ... + 55 °C

10 IBExU14ATEX1050
11 II 2G Ex eb IIC T4 Gb

10 IECEx IBE 14.0013
11 Ex eb IIC T4 Gb

W A R N I N G - DO NOT OPEN WHEN ENERGIZED

Index

Index	Index Type	X.2
	Index Order No.	X.11
	Addresses worldwide	X.20

Type	Order No.	Page
A		
ADAP EX M20-M16	1737560000	C.153
ADAP EX M20-M16	1737560000	C.154
ADAP EX M20-M16	1737560000	C.155
ADAP EX M20-M16	1737560000	C.156
B		
BK 4/E	7906080000	C.116
C		
CABTITE BP 10MM PA	2652380000	E.8
CABTITE BP 12MM PA	2652400000	E.8
CABTITE BP 13MM PA	2652410000	E.8
CABTITE BP 14MM PA	2652420000	E.8
CABTITE BP 17MM PA	2652430000	E.8
CABTITE BP 20MM PA	2652440000	E.8
CABTITE BP 21MM PA	2652450000	E.8
CABTITE BP 25MM PA	2652460000	E.8
CABTITE BP 28MM PA	2652470000	E.8
CABTITE BP 2MM PA	2652300000	E.8
CABTITE BP 35MM PA	2652480000	E.8
CABTITE BP 3MM PA	2652310000	E.8
CABTITE BP 4MM PA	2652320000	E.8
CABTITE BP 5MM PA	2652330000	E.8
CABTITE BP 6MM PA	2652340000	E.8
CABTITE BP 7MM PA	2652350000	E.8
CABTITE BP 8MM PA	2652360000	E.8
CABTITE BP 9MM PA	2652370000	E.8
CABTITE BSE LRG BK	2583900000	E.4
CABTITE BSE LRG GY	2584520000	E.4
CABTITE BSE SML BK	2584790000	E.4
CABTITE BSE SML GY	2583350000	E.4
CABTITE CGS M20 BK	2584200000	E.7
CABTITE CGS M25 BK	2584180000	E.7
CABTITE CGS M32 BK	2584160000	E.7
CABTITE CGS M40 BK	2584150000	E.7
CABTITE CGS M50 BK	2584130000	E.7
CABTITE CGS M63 BK	2584120000	E.7
CABTITE CR 10/6 EMV	2583930000	E.8
CABTITE CR 16/8 EMV	2583910000	E.8
CABTITE CR 24/10 EMV	2583890000	E.8
CABTITE CR 4/1 EMV	2583950000	E.8
CABTITE CSE 2-11 SML BK	2583510000	E.4
CABTITE CSE 7-24 LRG BK	2583500000	E.4
CABTITE FR 10/6 BK	2583480000	E.5
CABTITE FR 10/6 BK SET	2583760000	E.5
CABTITE FR 16/8 BK	2583470000	E.6
CABTITE FR 16/8 BK SET	2583740000	E.6
CABTITE FR 24/10 BK	2583800000	E.6
CABTITE FR 24/10 BK SET	2583720000	E.6
CABTITE FR 4-1 BK	2583490000	E.5
CABTITE FR 4-1 BK SET	2583780000	E.5
CABTITE FRL 10/6 BK	2584240000	E.5
CABTITE FRL 16/8 BK	2584220000	E.6
CABTITE FRL 24/10 BK	2584210000	E.6
CABTITE FRL 4-1 BK	2584260000	E.5
CABTITE GI H BK	2584270000	E.7
CABTITE GI I BK	2584320000	E.7
CABTITE GI T BK	2584300000	E.7
CABTITE GI X BK	2584290000	E.7
CABTITE LNS M20 BK	2584110000	E.7
CABTITE LNS M25 BK	2584090000	E.7
CABTITE LNS M32 BK	2584070000	E.7
CABTITE LNS M40 BK	2584050000	E.7
CABTITE LNS M50 BK	2584030000	E.7
CABTITE LNS M63 BK	2584010000	E.7
CABTITE SC M5X25 SET	2635120000	E.5
CABTITE SC M5X25 SET	2635120000	E.6
CABTITE SE 1.5-2 SML BK	2584780000	E.4
CABTITE SE 1.5-2 SML GY	2583360000	E.4
CABTITE SE 1/ASI SML BK	2583530000	E.4
CABTITE SE 1/ASI SML GY	2584810000	E.4
CABTITE SE 10-11 SML BK	2584060000	E.4
CABTITE SE 10-11 SML GY	2584610000	E.4
CABTITE SE 11-12 SML BK	2584040000	E.4
CABTITE SE 11-12 SML GY	2584600000	E.4
CABTITE SE 12-13 SML BK	2584020000	E.4
CABTITE SE 12-13 SML GY	2584590000	E.4
CABTITE SE 13-14 SML BK	2584000000	E.4
CABTITE SE 13-14 SML GY	2584570000	E.4
CABTITE SE 14-15 LRG BK	2583880000	E.4
CABTITE SE 14-15 LRG GY	2584510000	E.4
CABTITE SE 14-15 SML BK	2583980000	E.4
CABTITE SE 14-15 SML GY	2584560000	E.4
CABTITE SE 15-16 LRG BK	2583860000	E.4
CABTITE SE 15-16 LRG GY	2584500000	E.4
CABTITE SE 15-16 SML BK	2583960000	E.4
CABTITE SE 15-16 SML GY	2584550000	E.4
CABTITE SE 16-17 LRG BK	2583850000	E.4
CABTITE SE 16-17 LRG GY	2584490000	E.4
CABTITE SE 17-18 LRG BK	2583840000	E.4
CABTITE SE 17-18 LRG GY	2584480000	E.4
CABTITE SE 18-19 LRG BK	2583830000	E.4
CABTITE SE 18-19 LRG GY	2584470000	E.4
CABTITE SE 19-20 LRG BK	2583810000	E.4
CABTITE SE 19-20 LRG GY	2584460000	E.4
CABTITE SE 2-3 SML BK	2584760000	E.4
CABTITE SE 2-3 SML GY	2583380000	E.4
CABTITE SE 2/4-5 SML BK	2583620000	E.4
CABTITE SE 2/4-5 SML GY	2584900000	E.4
CABTITE SE 2/5-6 SML BK	2583610000	E.4
CABTITE SE 2/5-6 SML GY	2584890000	E.4
CABTITE SE 2/7 SML BK	2583550000	E.4
CABTITE SE 2/7 SML GY	2584830000	E.4
CABTITE SE 2/8 SML BK	2583540000	E.4
CABTITE SE 2/8 SML GY	2584820000	E.4
CABTITE SE 2/ASI SML BK	2583520000	E.4
CABTITE SE 2/ASI SML GY	2584800000	E.4
CABTITE SE 20-21 LRG BK	2583790000	E.4
CABTITE SE 20-21 LRG GY	2584450000	E.4
CABTITE SE 21-22 LRG BK	2583770000	E.4
CABTITE SE 21-22 LRG GY	2584440000	E.4
CABTITE SE 22-23 LRG BK	2583750000	E.4
CABTITE SE 22-23 LRG GY	2584430000	E.4
CABTITE SE 23-24 LRG BK	2583730000	E.4
CABTITE SE 23-24 LRG GY	2584420000	E.4
CABTITE SE 24-25 LRG BK	2583710000	E.4
CABTITE SE 24-25 LRG GY	2584410000	E.4
CABTITE SE 25-26 LRG BK	2583700000	E.4
CABTITE SE 25-26 LRG GY	2584400000	E.4
CABTITE SE 26-27 LRG BK	2583690000	E.4
CABTITE SE 26-27 LRG GY	2584390000	E.4
CABTITE SE 27-28 LRG BK	2583680000	E.4
CABTITE SE 27-28 LRG GY	2584370000	E.4
CABTITE SE 28-29 LRG BK	2583670000	E.4
CABTITE SE 28-29 LRG GY	2584350000	E.4
CABTITE SE 29-30 LRG BK	2583660000	E.4
CABTITE SE 29-30 LRG GY	2584380000	E.4
CABTITE SE 3-4 SML BK	2584730000	E.4
CABTITE SE 3-4 SML GY	2583400000	E.4
CABTITE SE 3/5-6 SML BK	2652280000	E.4
CABTITE SE 3/5-6 SML GY	2652290000	E.4
CABTITE SE 30-31 LRG BK	2583650000	E.4
CABTITE SE 30-31 LRG GY	2584360000	E.4
CABTITE SE 31-32 LRG BK	2583640000	E.4
CABTITE SE 31-32 LRG GY	2584340000	E.4
CABTITE SE 32-33 LRG BK	2583630000	E.4
CABTITE SE 32-33 LRG GY	2584920000	E.4
CABTITE SE 33-34 LRG BK	2595510000	E.4
CABTITE SE 33-34 LRG GY	2584910000	E.4
CABTITE SE 34-35 LRG BK	2595520000	E.4
CABTITE SE 34-35 LRG GY	2595530000	E.4
CABTITE SE 4-5 SML BK	2584680000	E.4
CABTITE SE 4-5 SML GY	2583440000	E.4
CABTITE SE 4/2-3 SML BK	2583590000	E.4
CABTITE SE 4/2-3 SML GY	2584870000	E.4
CABTITE SE 4/3-4 SML BK	2583580000	E.4
CABTITE SE 4/3-4 SML GY	2584860000	E.4
CABTITE SE 4/4-5 SML BK	2583560000	E.4
CABTITE SE 4/4-5 SML GY	2584840000	E.4
CABTITE SE 5-6 SML BK	2584710000	E.4
CABTITE SE 5-6 SML GY	2583450000	E.4
CABTITE SE 6-7 SML BK	2584690000	E.4
CABTITE SE 6-7 SML GY	2583460000	E.4
CABTITE SE 7-8 SML BK	2584670000	E.4
CABTITE SE 7-8 SML GY	2584660000	E.4
CABTITE SE 8-9 SML BK	2584330000	E.4
CABTITE SE 8-9 SML GY	2584650000	E.4
CABTITE SE 9-10 SML BK	2584080000	E.4
CABTITE SE 9-10 SML GY	2584630000	E.4
CABTITE TOOL ATSE PA	2637360000	E.5
CABTITE TOOL ATSE PA	2637360000	E.6
D		
DAE M12 PA LONG	1868570000	C.52
DAE M12 PA LONG	1868570000	C.53
DAE M12 PA LONG	1868570000	C.54
DAE M12 PA LONG	1868570000	C.55
DAE M12 PA LONG	1868570000	C.56
DAE M12 PA LONG	1868570000	C.57
DAE M12 PA LONG	1868570000	C.58
DAE M12 PA LONG	1868570000	C.59
DAE M12 PA LONG	1868570000	C.60
DAE M12 PA LONG	1868570000	C.61
DAE M12 PA LONG	1868570000	C.62
DAE M12 PA LONG	1868570000	C.68
DAE M12 PA LONG	1868570000	C.69
DAE M12 PA LONG	1868570000	C.70
DAE M12 PA LONG	1868570000	C.71
DAE M12 PA LONG	1868570000	C.72
DAE M12 PA LONG	1868570000	C.73
DAE M12 PA LONG	1868570000	C.74
DAE M12 PA LONG	1868570000	C.75
DAE M12 PA LONG	1868570000	C.96
DAE M12 PA LONG	1868570000	C.97
DAE M12 PA LONG	1868570000	C.98
DAE M12 PA LONG	1868570000	C.99
DAE M12 PA LONG	1868570000	C.100
DAE M12 PA LONG	1868570000	C.101
DAE M12 PA LONG	1868570000	C.102
DAE M12 PA LONG	1868570000	C.103
DAE M12 PA LONG	1868570000	C.104
DAE M12 PA LONG	1868570000	C.105
DAE M12 PA LONG	1868570000	C.106
DAE M12 PA LONG	1868570000	C.107
DAE M12 PA LONG	1868570000	C.108
DAE M12 PA LONG	1868570000	C.109
DAE M12 PA LONG	1868570000	C.110
DAE M12 PA LONG	1868570000	C.111
DAE M12 PA LONG	1868570000	C.112
DAE M12 PA LONG	1868570000	C.113
DAE M12 PA LONG	1868570000	C.114
DAE M12 PA LONG	1868570000	C.132
DAE M12 PA LONG	1868570000	C.133
DAE M12 PA LONG	1868570000	C.134
DAE M12 PA LONG	1868570000	C.135
DAE M12 PA LONG	1868570000	C.136
DAE M12 PA LONG	1868570000	C.137
DAE M12 PA LONG	1868570000	C.138
DAE M12 PA LONG	1868570000	C.139
DAE M12 PA LONG	1868570000	C.140
DAE M12 PA LONG	1868570000	C.141
DAE M12 PA LONG	1868570000	C.142
DAE M12 PA LONG	1868570000	C.143
DAE M12 PA LONG	1868570000	C.144
DAE M12 PA LONG	1868570000	C.145
DAE M12 PA LONG	1868570000	C.146
DAE M12 PA LONG	1868570000	C.147
DAE M12 PA LONG	1868570000	C.148
DAE M12 PA LONG	1868570000	C.170
DAE M12 PA LONG	1868570000	C.171
DAE M12 PA LONG	1868570000	C.172
DAE M12 PA LONG	1868570000	C.173
DAE M12 PA LONG	1868570000	C.174
DAE M12 PA LONG	1868570000	C.178
DAE M12 PA LONG	1868570000	C.179
DAE M12 PA LONG	1868570000	C.180
DAE M12 PA LONG	1868570000	C.181
DAE M12 PA LONG	1868570000	C.182
DAE M12 PA LONG	1868570000	C.183
DAE M12 PA LONG	1868570000	C.185
DAE M12 PA LONG	1868570000	C.186
DAE M12 PA LONG	1868570000	C.187
DAE M12 PA LONG	1868570000	D.59
DAE M12 PA SHORT	1868560000	D.59
DAE M12 SS	1868550000	C.52
DAE M12 SS	1868550000	C.53
DAE M12 SS	1868550000	C.54
DAE M12 SS	1868550000	C.55
DAE M12 SS	1868550000	C.56
DAE M12 SS	1868550000	C.57
DAE M12 SS	1868550000	C.58
DAE M12 SS	1868550000	C.59
DAE M12 SS	1868550000	C.60
DAE M12 SS	1868550000	C.61
DAE M12 SS	1868550000	C.62
DAE M12 SS	1868550000	C.68
DAE M12 SS	1868550000	C.69
DAE M12 SS	1868550000	C.70
DAE M12 SS	1868550000	C.71
DAE M12 SS	1868550000	C.72
DAE M12 SS	1868550000	C.73
DAE M12 SS	1868550000	C.74
DAE M12 SS	1868550000	C.75
DAE M12 SS	1868550000	C.96
DAE M12 SS	1868550000	C.97
DAE M12 SS	1868550000	C.98
DAE M12 SS	1868550000	C.99
DAE M12 SS	1868550000	C.100
DAE M12 SS	1868550000	C.101
DAE M12 SS	1868550000	C.102
DAE M12 SS	1868550000	C.103
DAE M12 SS	1868550000	C.104
DAE M12 SS	1868550000	C.105
DAE M12 SS	1868550000	C.106
DAE M12 SS	1868550000	C.107
DAE M12 SS	1868550000	C.108
DAE M12 SS	1868550000	C.109
DAE M12 SS	1868550000	C.110
DAE M12 SS	1868550000	C.111
DAE M12 SS	1868550000	C.112
DAE M12 SS	1868550000	C.113
DAE M12 SS	1868550000	C.114
DAE M12 SS	1868550000	C.132
DAE M12 SS	1868550000	C.133
DAE M12 SS	1868550000	C.134
DAE M12 SS	1868550000	C.135
DAE M12 SS	1868550000	C.136
DAE M12 SS	1868550000	C.137
DAE M12 SS	1868550000	C.138
DAE M12 SS	1868550000	C.139
DAE M12 SS	1868550000	C.140
DAE M12 SS	1868550000	C.141
DAE M12 SS	1868550000	C.142
DAE M12 SS	1868550000	C.143
DAE M12 SS	1868550000	C.144
DAE M12 SS	1868550000	C.145
DAE M12 SS	1868550000	C.146
DAE M12 SS	1868550000	C.147
DAE M12 SS	1868550000	C.148
DAE M12 SS	1868550000	C.170
DAE M12 SS	1868550000	C.171
DAE M12 SS	1868550000	C.172
DAE M12 SS	1868550000	C.173
DAE M12 SS	1868550000	C.174
DAE M12 SS	1868550000	C.178
DAE M12 SS	1868550000	C.179
DAE M12 SS	1868550000	C.180
DAE M12 SS	1868550000	C.181
DAE M12 SS	1868550000	C.182
DAE M12 SS	1868550000	C.183
DAE M12 SS	1868550000	C.185
DAE M12 SS	1868550000	C.186
DAE M12 SS	1868550000	C.187
DAE M12 SS	1868550000	D.60
DESC M6X14 KTB SET	1253230000	C.15
DESC M6X14 KTB SET	1253230000	C.16
DESC M6X14 KTB SET	1253230000	C.17
DESC M6X14 KTB SET	1253230000	C.18
DESC M6X14 KTB SET	1253230000	C.19
DESC M6X14 KTB SET	1253230000	C.20
DESC M6X14 KTB SET	1253230000	C.21
DESC M6X14 KTB SET	1253230000	C.22
DESC M6X14 KTB SET	1253230000	C.23
DESC M6X14 KTB SET	1253230000	C.24
DESC M6X14 KTB SET	1253230000	C.25
DESC M6X14 KTB SET	1253230000	C.26
DESC M6X14 KTB SET	1253230000	C.27
DESC M6X14 KTB SET	1253230000	C.28
DESC M6X14 KTB SET	1253230000	C.29
DESC M6X14 KTB SET	1253230000	C.30
DESC M6X14 KTB SET	1253230000	C.31
DESC M6X14 KTB SET	1253230000	C.32
DESC M6X14 KTB SET	1253230000	C.33
DESC M6X14 KTB SET	1253230000	C.34
DESC M6X14 KTB SET	1253230000	C.35
DESC M6X14 KTB SET	1253230000	C.36
DESC M6X14 KTB SET	1253230000	C.44
DESC M6X14 KTB SET	1253230000	C.45
DESC M6X14 KTB SET	1253230000	C.46
DESC M6X14 KTB SET	1253230000	C.47
DOHA KTB A4 S2 R	1252730000	C.26
DOHA KTB A4 S2 R	1252730000	C.27
DOHA KTB A4 S2 R	1252730000	C.28
DOHA KTB A4 S2 R	1252730000	C.29
DOHA KTB A4 S2 R	1252730000	C.30
DOHA KTB A4 S2 R	1252730000	C.31
DOHA KTB A4 S2 R	1252730000	C.32
DOHA KTB A4 S2 R	1252730000	C.33
DOHA KTB A4 S2 R	1252730000	C.34
DOHA KTB A4 S2 R	1252730000	C.35
DOHA KTB A4 S2 R	1252730000	C.36
DOHA KTB A4 S2 R	1252730000	C.47
DOHA KTB A5 S2 R	1252750000	C.24
DOHA KTB A5 S2 R	1252750000	C.25
DOHA KTB A5 S2 R	1252750000	C.26
DOHA KTB A5 S2 R	1252750000	C.27
DOHA KTB A5 S2 R	1252750000	C.28
DOHA KTB A5 S2 R	1252750000	C.29
DOHA KTB A5 S2 R	1252750000	C.30
DOHA KTB A5 S2 R	1252750000	C.31
DOHA KTB A5 S2 R	1252750000	C.32
DOHA KTB A5 S2 R	1252750000	C.33
DOHA KTB A5 S2 R	1252750000	C.34
DOHA KTB A5 S2 R	1252750000	C.35
DOHA KTB A5 S2 R	1252750000	C.36
DOHA KTB A6 S2 R	1252780000	C.16
DOHA KTB A6 S2 R	1252780000	C.17
DOHA KTB A6 S2 R	1252780000	C.18
DOHA KTB A6 S2 R	1252780000	C.19
DOHA KTB A6 S2 R	1252780000	C.20
DOHA KTB A6 S2 R	1252780000	C.21
DOHA KTB A6 S2 R	1252780000	C.22
DOHA KTB A6 S2 R	1252780000	C.23
DOHA KTB A6 S2 R	1252780000	C.24
DOHA KTB A6 S2 R	1252780000	C.25
DOHA KTB A6 S2 R	1252780000	C.26
DOHA KTB A6 S2 R	1252780000	C.27
DOHA KTB A6 S2 R	1252780000	C.28
DOHA KTB A6 S2 R	1252780000	C.29
DOHA KTB A6 S2 R	1252780000	C.30
DOHA KTB A6 S2 R	1252780000	C.31
DOHA KTB A6 S2 R	1252780000	C.32
DOHA KTB A6 S2 R	1252780000	C.33
DOHA KTB A6 S2 R	1252780000	C.34
DOHA KTB A6 S2 R	1252780000	C.35
DOHA KTB A6 S2 R	1252780000	C.36
DOHA KTB A6 S2 R	1252780000	C.45
DOHA KTB A6 S2 R	1252780000	C.46
DOHA KTB A6 S2 R	1252780000	C.47
E		
EA-RING MS/M 16	1736480000	D.49
EA-RING MS/M 20	1736490000	D.49
EA-RING MS/M 25	1736500000	D.49
EA-RING MS/M 32	1736510000	D.49
EA-RING MS/M 40	1736520000	D.49
EA-RING MS/M 50	1736530000	D.49
EA-RING MS/M 63	1736540000	D.49
EA-RING MS/M 75	1736550000	D.49
EA-RING MS/M16 SC	0930710001	D.49

Type	Order No.	Page
EA-RING MS/M20 SC	0930710002	D.49
EA-RING MS/M25 SC	0930710003	D.49
EA-RING MS/M32 SC	0930710004	D.49
EA-RING MS/M40 SC	0930710005	D.49
EA-RING MS/M50 SC	0930710006	D.49
EA-RING MS/M63 SC	0930710007	D.49
EA-RING MS/M75 SC	0930710008	D.49

F

FKSC M4X6 D8/SW2	1567480000	C.170
FKSC M4X6 D8/SW2	1567480000	C.171
FKSC M4X6 D8/SW2	1567480000	C.172
FKSC M4X6 D8/SW2	1567480000	C.173
FKSC M4X6 D8/SW2	1567480000	C.174
FKSC M4X6 D8/SW2	1567480000	C.178
FKSC M4X6 D8/SW2	1567480000	C.179
FKSC M4X6 D8/SW2	1567480000	C.180
FKSC M4X6 D8/SW2	1567480000	C.181
FKSC M4X6 D8/SW2	1567480000	C.182
FKSC M4X6 D8/SW2	1567480000	C.183
FKSC M4X6 D8/SW2	1567480000	C.185
FKSC M4X6 D8/SW2	1567480000	C.186
FKSC M4X6 D8/SW2	1567480000	C.187
FKSC M6X8 D9/SW3	0642600000	C.15
FKSC M6X8 D9/SW3	0642600000	C.16
FKSC M6X8 D9/SW3	0642600000	C.17
FKSC M6X8 D9/SW3	0642600000	C.18
FKSC M6X8 D9/SW3	0642600000	C.19
FKSC M6X8 D9/SW3	0642600000	C.20
FKSC M6X8 D9/SW3	0642600000	C.21
FKSC M6X8 D9/SW3	0642600000	C.22
FKSC M6X8 D9/SW3	0642600000	C.23
FKSC M6X8 D9/SW3	0642600000	C.24
FKSC M6X8 D9/SW3	0642600000	C.25
FKSC M6X8 D9/SW3	0642600000	C.26
FKSC M6X8 D9/SW3	0642600000	C.27
FKSC M6X8 D9/SW3	0642600000	C.28
FKSC M6X8 D9/SW3	0642600000	C.29
FKSC M6X8 D9/SW3	0642600000	C.30
FKSC M6X8 D9/SW3	0642600000	C.31
FKSC M6X8 D9/SW3	0642600000	C.32
FKSC M6X8 D9/SW3	0642600000	C.33
FKSC M6X8 D9/SW3	0642600000	C.34
FKSC M6X8 D9/SW3	0642600000	C.35
FKSC M6X8 D9/SW3	0642600000	C.36
FKSC M6X8 D9/SW3	0642600000	C.44
FKSC M6X8 D9/SW3	0642600000	C.45
FKSC M6X8 D9/SW3	0642600000	C.46
FKSC M6X8 D9/SW3	0642600000	C.47
FKSC M6X8 D9/SW3	0642600000	C.132
FKSC M6X8 D9/SW3	0642600000	C.133
FKSC M6X8 D9/SW3	0642600000	C.134
FKSC M6X8 D9/SW3	0642600000	C.135
FKSC M6X8 D9/SW3	0642600000	C.136
FKSC M6X8 D9/SW3	0642600000	C.137
FKSC M6X8 D9/SW3	0642600000	C.138
FKSC M6X8 D9/SW3	0642600000	C.139
FKSC M6X8 D9/SW3	0642600000	C.140
FKSC M6X8 D9/SW3	0642600000	C.141
FKSC M6X8 D9/SW3	0642600000	C.142
FKSC M6X8 D9/SW3	0642600000	C.143
FKSC M6X8 D9/SW3	0642600000	C.144
FKSC M6X8 D9/SW3	0642600000	C.145
FKSC M6X8 D9/SW3	0642600000	C.146
FKSC M6X8 D9/SW3	0642600000	C.147
FKSC M6X8 D9/SW3	0642600000	C.148
FPC 20/20/13 7035	9535690000	C.184
FPC 20/20/13 7035	9535690000	C.185
FPC 20/20/13 TRSP	9535680000	C.184
FPC 20/20/13 TRSP	9535680000	C.185
FPC 20/30/13 7035	9535710000	C.184
FPC 20/30/13 7035	9535710000	C.185
FPC 20/30/13 TRSP	9535700000	C.184
FPC 20/30/13 TRSP	9535700000	C.185
FPC 20/40/13 7035	9535730000	C.184
FPC 20/40/13 7035	9535730000	C.186
FPC 20/40/13 TRSP	9535720000	C.184
FPC 20/40/13 TRSP	9535720000	C.186
FPC 30/30/13 7035	9535750000	C.184
FPC 30/30/13 7035	9535750000	C.186
FPC 30/30/13 TRSP	9535740000	C.184
FPC 30/30/13 TRSP	9535740000	C.186
FPC 30/40/13 7035	9535770000	C.184
FPC 30/40/13 7035	9535770000	C.187
FPC 30/40/13 TRSP	9535760000	C.184
FPC 30/40/13 TRSP	9535760000	C.187
FPC 40/60/13 7035	9535810000	C.184
FPC 40/60/13 7035	9535810000	C.187
FPC 40/60/13 TRSP	9535820000	C.184
FPC 40/60/13 TRSP	9535820000	C.187

G

GFSC M5x10 TX20 SET	1274150000	C.15
GFSC M5x10 TX20 SET	1274150000	C.16
GFSC M5x10 TX20 SET	1274150000	C.17
GFSC M5x10 TX20 SET	1274150000	C.18
GFSC M5x10 TX20 SET	1274150000	C.19
GFSC M5x10 TX20 SET	1274150000	C.20
GFSC M5x10 TX20 SET	1274150000	C.21
GFSC M5x10 TX20 SET	1274150000	C.22
GFSC M5x10 TX20 SET	1274150000	C.23
GFSC M5x10 TX20 SET	1274150000	C.24
GFSC M5x10 TX20 SET	1274150000	C.25
GFSC M5x10 TX20 SET	1274150000	C.26
GFSC M5x10 TX20 SET	1274150000	C.27
GFSC M5x10 TX20 SET	1274150000	C.28
GFSC M5x10 TX20 SET	1274150000	C.29
GFSC M5x10 TX20 SET	1274150000	C.30
GFSC M5x10 TX20 SET	1274150000	C.31
GFSC M5x10 TX20 SET	1274150000	C.32
GFSC M5x10 TX20 SET	1274150000	C.33
GFSC M5x10 TX20 SET	1274150000	C.34
GFSC M5x10 TX20 SET	1274150000	C.35
GFSC M5x10 TX20 SET	1274150000	C.36
GFSC M5x10 TX20 SET	1274150000	C.52
GFSC M5x10 TX20 SET	1274150000	C.53
GFSC M5x10 TX20 SET	1274150000	C.54
GFSC M5x10 TX20 SET	1274150000	C.55
GFSC M5x10 TX20 SET	1274150000	C.56
GFSC M5x10 TX20 SET	1274150000	C.57
GFSC M5x10 TX20 SET	1274150000	C.58
GFSC M5x10 TX20 SET	1274150000	C.59
GFSC M5x10 TX20 SET	1274150000	C.60
GFSC M5x10 TX20 SET	1274150000	C.61
GFSC M5x10 TX20 SET	1274150000	C.62
GWDR M12-NP	1913320000	D.46
GWDR M12-PO	1777920000	D.45
GWDR M16-NP	1736230000	D.46
GWDR M16-PO	1777930000	D.45
GWDR M20-NP	1736240000	D.46
GWDR M20-PO	1777940000	D.45
GWDR M25-NP	1736250000	D.46
GWDR M25-PO	1777950000	D.45
GWDR M32-NP	1736260000	D.46
GWDR M32-PO	1777960000	D.45
GWDR M40-NP	1736270000	D.46
GWDR M40-PO	1777970000	D.45
GWDR M50-NP	1736280000	D.46
GWDR M50-PO	1777980000	D.45
GWDR M63-NP	1736290000	D.46
GWDR M63-PO	1777990000	D.45
GWDR PG11-NP	1719560000	D.46
GWDR PG11-PO	1719460000	D.45
GWDR PG13,5-NP	1719570000	D.46
GWDR PG13,5-PO	1719470000	D.45
GWDR PG16-NP	1719580000	D.46
GWDR PG16-PO	1719480000	D.45
GWDR PG21-NP	1719590000	D.46
GWDR PG21-PO	1719490000	D.45
GWDR PG29-NP	1719600000	D.46
GWDR PG29-PO	1719500000	D.45
GWDR PG36-NP	1719610000	D.46
GWDR PG36-PO	1719510000	D.45
GWDR PG42-NP	1719620000	D.46
GWDR PG42-PO	1719520000	D.45
GWDR PG48-NP	1719630000	D.46
GWDR PG48-PO	1719530000	D.45
GWDR PG7-NP	1719540000	D.46
GWDR PG7-PO	1719440000	D.45
GWDR PG9-NP	1719550000	D.46
GWDR PG9-PO	1719450000	D.45

H

HG FPC	9535990000	C.185
HG FPC	9535990000	C.186
HG FPC	9535990000	C.187
HG K+POK	1580360000	C.100
HG K+POK	1580360000	C.102
HG K+POK	1580360000	C.104
HG K+POK	1580360000	C.106
HG K+POK	1580360000	C.107
HG K+POK	1580360000	C.108
HG K+POK	1580360000	C.109
HG K+POK	1580360000	C.110
HG K+POK	1580360000	C.111
HG K+POK	1580360000	C.112
HG K+POK	1580360000	C.113
HG K+POK	1580360000	C.114
HG MPC	9535590000	C.178
HG MPC	9535590000	C.179
HG MPC	9535590000	C.180
HG MPC	9535590000	C.181
HG MPC	9535590000	C.182
HG MPC	9535590000	C.183

K

KDSU M20 BN O NI 1 G16	1083280000	D.27
KDSU M20 BN O NI 1 G20	1083320000	D.27
KDSU M20 BN O NI 1 G20S	1083290000	D.27
KDSU M20 BN O NI 2 G16	1911380000	D.27
KDSU M20 BN O NI 2 G20	1911400000	D.27
KDSU M20 BN O NI 2 G20S	1911390000	D.27
KDSU M20 BS O NI 1 G16	0930001221	D.26
KDSU M20 BS O NI 1 G16	0930001221	D.28
KDSU M20 BS O NI 1 G20	0930021221	D.26
KDSU M20 BS O NI 1 G20	0930021221	D.28
KDSU M20 BS O NI 1 G20S	0930011223	D.26
KDSU M20 BS O NI 1 G20S	0930011223	D.28
KDSU M20 BS O NI 2 G16	0930001222	D.26
KDSU M20 BS O NI 2 G16	0930001222	D.28
KDSU M20 BS O NI 2 G20	0930021222	D.28
KDSU M20 BS O NI 2 G20S	0930011224	D.26
KDSU M20 BS O NI 2 G20S	0930011224	D.28
KDSU M25 BN O NI 1 G25	1083330000	D.27
KDSU M25 BN O NI 2 G25	1911420000	D.27
KDSU M25 BS O NI 1 G25	0930031221	D.28
KDSU M25 BS O NI 2 G25	0930031222	D.28
KDSU M32 BN O NI 1 G32	1083340000	D.27
KDSU M32 BN O NI 2 G32	1911430000	D.27
KDSU M32 BS O NI 1 G32	0930041221	D.28
KDSU M32 BS O NI 2 G32	0930041222	D.28
KDSU M40 BN O NI 1 G40	1083350000	D.27
KDSU M40 BN O NI 2 G40	1911440000	D.27
KDSU M40 BS O NI 1 G40	1136990000	D.28
KDSU M40 BS O NI 2 G40	0930051222	D.28
KDSU M50 BN O NI 1 G50	1083370000	D.27
KDSU M50 BN O NI 1 G50S	1083360000	D.27
KDSU M50 BN O NI 2 G50	1911460000	D.27
KDSU M50 BN O NI 2 G50S	1911450000	D.27
KDSU M50 BS O NI 1 G50	1137010000	D.28
KDSU M50 BS O NI 1 G50S	1137000000	D.28
KDSU M50 BS O NI 2 G50	1137020000	D.28
KDSU M50 BS O NI 2 G50S	0930061224	D.28
KDSU M63 BN O NI 1 G63	1083390000	D.27
KDSU M63 BN O NI 1 G63S	1083380000	D.27
KDSU M63 BN O NI 2 G63	1911490000	D.27
KDSU M63 BN O NI 2 G63S	1911480000	D.27
KDSU M63 BS O NI 1 G63	1137050000	D.28
KDSU M63 BS O NI 1 G63S	1137030000	D.28
KDSU M63 BS O NI 2 G63	0930091222	D.28
KDSU M63 BS O NI 2 G63S	1137040000	D.28
KDSU M75 BN O NI 1 G75	1083420000	D.27
KDSU M75 BN O NI 1 G75S	1083400000	D.27
KDSU M75 BN O NI 2 G75	1083430000	D.27
KDSU M75 BN O NI 2 G75S	1083410000	D.27
KDSU M75 BS O NI 1 G75	1137080000	D.28
KDSU M75 BS O NI 1 G75S	1137060000	D.28
KDSU M75 BS O NI 2 G75	1137090000	D.28
KDSU M75 BS O NI 2 G75S	1137070000	D.28
KDSW M20 BN L NI 1 G16	1074660000	D.31
KDSW M20 BN L NI 1 G20	1074760000	D.31
KDSW M20 BN L NI 1 G20S	1074720000	D.31
KDSW M20 BN L NI 2 G16	1074690000	D.31
KDSW M20 BN L NI 2 G20	1074780000	D.31
KDSW M20 BN L NI 2 G20S	1074740000	D.31
KDSW M20 BN O NI 1 G16	1075030000	D.29
KDSW M20 BN O NI 1 G20	1075070000	D.29
KDSW M20 BN O NI 1 G20S	1075050000	D.29
KDSW M20 BN O NI 2 G16	1075040000	D.29
KDSW M20 BN O NI 2 G20	1075080000	D.29
KDSW M20 BN O NI 2 G20S	1075060000	D.29
KDSW M20 BS O NI 1 G16	1136410000	D.30
KDSW M20 BS O NI 1 G20	1136450000	D.30
KDSW M20 BS O NI 1 G20S	1136430000	D.30
KDSW M20 BS O NI 2 G16	1136420000	D.30
KDSW M20 BS O NI 2 G20	1136460000	D.30
KDSW M20 BS O NI 2 G20S	1136440000	D.30
KDSW M25 BN L NI 1 G25	1074810000	D.31
KDSW M25 BN L NI 2 G25	1074830000	D.31
KDSW M25 BN O NI 1 G25	1075090000	D.29
KDSW M25 BN O NI 2 G25	1075110000	D.29
KDSW M25 BS O NI 1 G25	1136470000	D.30
KDSW M25 BS O NI 2 G25	1136480000	D.30
KDSW M32 BN L NI 1 G32	1074850000	D.31
KDSW M32 BN L NI 2 G32	1074860000	D.31
KDSW M32 BN O NI 1 G32	1075120000	D.29
KDSW M32 BN O NI 2 G32	1075130000	D.29
KDSW M32 BS O NI 1 G32	1136490000	D.30
KDSW M32 BS O NI 2 G32	1136510000	D.30
KDSW M40 BN L NI 1 G40	1074870000	D.31
KDSW M40 BN L NI 2 G40	1074880000	D.31
KDSW M40 BN O NI 1 G40	1075140000	D.29
KDSW M40 BN O NI 2 G40	1075150000	D.29
KDSW M40 BS O NI 1 G40	1136520000	D.30
KDSW M40 BS O NI 2 G40	1136530000	D.30
KDSW M50 BN L NI 1 G50	1074920000	D.31
KDSW M50 BN L NI 1 G50S	1074890000	D.31
KDSW M50 BN L NI 2 G50	1074930000	D.31
KDSW M50 BN L NI 2 G50S	1074910000	D.31
KDSW M50 BN O NI 1 G50	1075180000	D.29
KDSW M50 BN O NI 1 G50S	1075160000	D.29
KDSW M50 BN O NI 2 G50	1075190000	D.29
KDSW M50 BN O NI 2 G50S	1075170000	D.29
KDSW M50 BS O NI 1 G50	1136560000	D.30
KDSW M50 BS O NI 1 G50S	1136540000	D.30
KDSW M50 BS O NI 2 G50	1136570000	D.30
KDSW M50 BS O NI 2 G50S	1136550000	D.30
KDSW M63 BN L NI 1 G63	1074960000	D.31
KDSW M63 BN L NI 1 G63S	1074940000	D.31
KDSW M63 BN L NI 2 G63	1074970000	D.31
KDSW M63 BN L NI 2 G63S	1074950000	D.31
KDSW M63 BN O NI 1 G63	1075230000	D.29
KDSW M63 BN O NI 1 G63S	1075210000	D.29
KDSW M63 BN O NI 2 G63	1075240000	D.29
KDSW M63 BN O NI 2 G63S	1075220000	D.29
KDSW M63 BS O NI 1 G63	1136600000	D.30
KDSW M63 BS O NI 1 G63S	1136580000	D.30
KDSW M63 BS O NI 2 G63	1136610000	D.30
KDSW M63 BS O NI 2 G63S	1136590000	D.30
KDSW M75 BN L NI 1 G75	1075010000	D.31
KDSW M75 BN L NI 1 G75S	1074980000	D.31
KDSW M75 BN L NI 2 G75	1075020000	D.31
KDSW M75 BN L NI 2 G75S	1074990000	D.31
KDSW M75 BN O NI 1 G75	1075270000	D.29
KDSW M75 BN O NI 1 G75S	1075250000	D.29
KDSW M75 BN O NI 2 G75	1075280000	D.29
KDSW M75 BN O NI 2 G75S	1075260000	D.29
KDSW M75 BS O NI 1 G75	1136640000	D.30
KDSW M75 BS O NI 1 G75S	1136620000	D.30
KDSW M75 BS O NI 2 G75	1136650000	D.30
KDSW M75 BS O NI 2 G75S	1136630000	D.30
KDSX M20 BS O NI 1 G16	1135910000	D.32
KDSX M20 BS O NI 1 G20	1135950000	D.32
KDSX M20 BS O NI 1 G20S	1135930000	D.32
KDSX M20 BS O NI 2 G16	1135920000	D.32
KDSX M20 BS O NI 2 G20	1135960000	D.32
KDSX M20 BS O NI 2 G20S	1135940000	D.32
KDSX M25 BS O NI 1 G25	1135970000	D.32
KDSX M25 BS O NI 2 G25	1135980000	D.32
KDSX M32 BS O NI 1 G32	1135990000	D.32
KDSX M32 BS O NI 2 G32	1136000000	D.32
KDSX M40 BS O NI 1 G40	1136010000	D.32
KDSX M40 BS O NI 2 G40	1136020000	D.32
KDSX M50 BS O NI 1 G50	1136050000	D.32
KDSX M50 BS O NI 1 G50S	1136030000	D.32
KDSX M50 BS O NI 2 G50	1136060000	D.32
KDSX M50 BS O NI 2 G50S	1136040000	D.32
KDSX M63 BS O NI 1 G63	1136090000	D.32
KDSX M63 BS O NI 1 G63S	1136070000	D.32
KDSX M63 BS O NI 2 G63	1136110000	D.32
KDSX M63 BS O NI 2 G63S	1136080000	D.32
KDSX M75 BS O NI 1 G75	1136140000	D.32
KDSX M75 BS O NI 1 G75S	1136120000	D.32
KDSX M75 BS O NI 2 G75	1136150000	D.32
KDSX M75 BS O NI 2 G75S	1136130000	D.32
KEBI QL 302015 S2B0	2470690000	C.50
KEBI QL 302015 S2B0	2470690000	C.52
KEBI QL 302015 S2B1	2470800000	C.50
KEBI QL 302015 S2B1	2470800000	C.52
KEBI QL 303015 S2B0	2470700000	C.50
KEBI QL 303015 S2B0	2470700000	C.53
KEBI QL 303015 S2B1	2470810000	C.50
KEBI QL 303015 S2B1	2470810000	C.53
KEBI QL 303022 S2B0	2470710000	C.50
KEBI QL 303022 S2B0	2470710000	C.54
KEBI QL 303022 S2B1	2470820000	C.50
KEBI QL 303022 S2B1	2470820000	C.54
KEBI QL 403015 S2B0	2470720000	C.50
KEBI QL 403015 S2B0	2470720000	C.55
KEBI QL 403015 S2B1	2470830000	C.50
KEBI QL 403015 S2B1	2470830000	C.55
KEBI QL 403022 S2B0	2470730000	C.50
KEBI QL 403022 S2B0	2470730000	C.56
KEBI QL 403022 S2B1	2470840000	C.50
KEBI QL 403022 S2B1	2470840000	C.56
KEBI QL 404022 S2B0	2470740000	C.50
KEBI QL 404022 S2B0	2470740000	C.57
KEBI QL 404022 S2B1	2470850000	C.50
KEBI QL 404022 S2B1	2470850000	C.57
KEBI QL 504022 S2B0	2470750000	C.50
KEBI QL 504022 S2B0	2470750000	C.58
KEBI QL 504022 S2B1	2470860000	C.50
KEBI QL 504022 S2B1	2470860000	C.58
KEBI QL 505022 S2B0	2470760000	C.50
KEBI QL 505022 S2B0	2470760000	C.59
KEBI QL 505022 S2B1	2470870000	C.50
KEBI QL 505022 S2B1	2470870000	C.59
KEBI QL 604022 S2B0	2470770000	C.50
KEBI QL 604022 S2B0	2470770000	C.60
KEBI QL 604022 S2B1	2470880000	C.50
KEBI QL 604022 S2B1	2470880000	C.60
KEBI QL 606022 S2B0	2470780000	C.50
KEBI QL 606022 S2B0	2470780000	C.61
KEBI QL 606022 S2B1	2470890000	C.50
KEBI QL 606022 S2B1	2470890000	C.61
KEBI QL 806022 S2B0	2470790000	C.50
KEBI QL 806022 S2B0	2470790000	C.62
KEBI QL 806022 S2B1	2470900000	C.50
KEBI QL 806022 S2B1	2470900000	C.62
KEBI-KTBI MF S2 SET	1289180000	C.52
KEBI-KTBI MF S2 SET	1289180000	C.53
KEBI-KTBI MF S2 SET	1289180000	C.54
KEBI-KTBI MF S2 SET	1289180000	C.55
KEBI-KTBI MF S2 SET	1289180000	C.56
KEBI-KTBI MF S2 SET	1289180000	C.57
KEBI-KTBI MF S2 SET	1289180000	C.58
KEBI-KTBI MF S2 SET	1289180000	C.59
KEBI-KTBI MF S2 SET	1289180000	C.60
KEBI-KTBI MF S2 SET	1289180000	C.61
KEBI-KTBI MF S2 SET	1289180000	C.62
KEBI-KTBI MOPL 3020 MSZN	1309690000	C.52
KEBI-KTBI MOPL 3020 S2N	1309700000	C.52

Type	Order No.	Page
KEB-KTBI MOPL 3030 MSZN	1310410000	C.53
KEB-KTBI MOPL 3030 MSZN	1310410000	C.54
KEB-KTBI MOPL 3030 S2N	1310320000	C.53
KEB-KTBI MOPL 3030 S2N	1310320000	C.54
KEB-KTBI MOPL 4030 MSZN	1310420000	C.55
KEB-KTBI MOPL 4030 MSZN	1310420000	C.56
KEB-KTBI MOPL 4030 S2N	1310330000	C.55
KEB-KTBI MOPL 4030 S2N	1310330000	C.56
KEB-KTBI MOPL 4040 MSZN	1310430000	C.57
KEB-KTBI MOPL 4040 S2N	1310340000	C.57
KEB-KTBI MOPL 5040 MSZN	1310440000	C.58
KEB-KTBI MOPL 5040 S2N	1310350000	C.58
KEB-KTBI MOPL 5050 MSZN	1310450000	C.59
KEB-KTBI MOPL 5050 S2N	1310360000	C.59
KEB-KTBI MOPL 6040 MSZN	1310460000	C.60
KEB-KTBI MOPL 6040 S2N	1310370000	C.60
KEB-KTBI MOPL 6060 MSZN	1310470000	C.61
KEB-KTBI MOPL 6060 S2N	1310380000	C.61
KEB-KTBI MOPL 8060 MSZN	1310480000	C.62
KEB-KTBI MOPL 8060 S2N	1310390000	C.62
KL SET 10A4 S	8000004145	C.150
KL SET 10A4 S	8000004145	C.153
KL SET 12W4 S	8000003444	C.116
KL SET 12W4 S	8000003444	C.150
KL SET 12W4 S	8000003444	C.155
KL SET 13A4 S	8000004134	C.116
KL SET 14Z2.5 S	8000004133	C.116
KL SET 18A4 S	8000004146	C.150
KL SET 18A4 S	8000004146	C.154
KL SET 18W4 S	8000004140	C.116
KL SET 21A4 S	8000004137	C.116
KL SET 24Z2.5 S	8000004136	C.116
KL SET 32W4 S	8000004142	C.116
KL SET 32W4 S	8000004142	C.150
KL SET 32W4 S	8000004142	C.156
KL SET 38Z2.5 S	8000004143	C.116
KL SET 38Z2.5 S	8000004143	C.150
KL SET 38Z2.5 S	8000004143	C.156
KL SET 4Z4 S	8000004139	C.116
KL SET 5W4 S	8000004138	C.116
KL SET 5Z2.5 S	8000004130	C.116
KL SET 6A4 S	8000004144	C.150
KL SET 6A4 S	8000004144	C.152
KL SET KLIPPON POK1 BK4	8000004365	C.150
KL SET KLIPPON POK1 BK4	8000004365	C.152
KL SET KLIPPON POK2 BK6	8000004366	C.150
KL SET KLIPPON POK2 BK6	8000004366	C.153
KL SET KLIPPON POK3BK12	8000004367	C.150
KL SET KLIPPON POK3BK12	8000004367	C.154
KLIPPON BDX M20 B	2519520000	C.44
KLIPPON BDX M20 B	2519520000	C.45
KLIPPON BDX M20 B	2519520000	C.46
KLIPPON BDX M20 B	2519520000	C.47
KLIPPON BDX M20 B	2519520000	C.78
KLIPPON BDX M20 B	2519520000	C.79
KLIPPON BDX M20 B	2519520000	C.80
KLIPPON BDX M20 B	2519520000	C.81
KLIPPON BDX M20 B	2519520000	D.61
KLIPPON BDX M20 S	2519550000	C.44
KLIPPON BDX M20 S	2519550000	C.45
KLIPPON BDX M20 S	2519550000	C.46
KLIPPON BDX M20 S	2519550000	C.47
KLIPPON BDX M20 S	2519550000	C.68
KLIPPON BDX M20 S	2519550000	C.69
KLIPPON BDX M20 S	2519550000	C.70
KLIPPON BDX M20 S	2519550000	C.71
KLIPPON BDX M20 S	2519550000	C.72
KLIPPON BDX M20 S	2519550000	C.73
KLIPPON BDX M20 S	2519550000	C.74
KLIPPON BDX M20 S	2519550000	C.75
KLIPPON BDX M20 S	2519550000	C.78
KLIPPON BDX M20 S	2519550000	C.79
KLIPPON BDX M20 S	2519550000	C.80
KLIPPON BDX M20 S	2519550000	C.81
KLIPPON BDX M20 S	2519550000	D.61
KLIPPON BDX M20X15 S	2519570000	C.132
KLIPPON BDX M20X15 S	2519570000	C.133
KLIPPON BDX M20X15 S	2519570000	C.134
KLIPPON BDX M20X15 S	2519570000	C.135
KLIPPON BDX M20X15 S	2519570000	C.136
KLIPPON BDX M20X15 S	2519570000	C.137
KLIPPON BDX M20X15 S	2519570000	C.138
KLIPPON BDX M20X15 S	2519570000	C.139
KLIPPON BDX M20X15 S	2519570000	C.140
KLIPPON BDX M20X15 S	2519570000	C.141
KLIPPON BDX M20X15 S	2519570000	C.142
KLIPPON BDX M20X15 S	2519570000	C.143
KLIPPON BDX M20X15 S	2519570000	C.144
KLIPPON BDX M20X15 S	2519570000	C.145
KLIPPON BDX M20X15 S	2519570000	C.146
KLIPPON BDX M20X15 S	2519570000	C.147
KLIPPON BDX M20X15 S	2519570000	C.148
KLIPPON BDX M20X15 S	2519570000	D.61
KLIPPON BDX M25 S	2519590000	D.61
KLIPPON COPL 080806	1390910000	C.132
KLIPPON COPL 081106	1390920000	C.133
KLIPPON COPL 081606	1390930000	C.134
KLIPPON COPL 081906	1390940000	C.135
KLIPPON COPL 082306	1390950000	C.136

Type	Order No.	Page
KLIPPON COPL 121209	1390970000	C.137
KLIPPON COPL 122209	1390980000	C.138
KLIPPON COPL 161609	1390990000	C.139
KLIPPON COPL 162609	1391000000	C.140
KLIPPON COPL 163609	1391010000	C.141
KLIPPON COPL 165609	1391020000	C.142
KLIPPON COPL 252512/16	1391030000	C.143
KLIPPON COPL 252512/16	1391030000	C.144
KLIPPON COPL 254012/16	1391040000	C.145
KLIPPON COPL 254012/16	1391040000	C.146
KLIPPON COPL 256012	1391050000	C.147
KLIPPON COPL 404012	1391070000	C.148
KLIPPON CS K41-1	1537470000	C.122
KLIPPON CS K41-1	1537480000	C.122
KLIPPON CS K41-1	1537490000	C.123
KLIPPON CS K41-1	1537500000	C.123
KLIPPON CS K41-4	1537510000	C.123
KLIPPON CS K41-4	1537520000	C.124
KLIPPON CS K41-4	1537530000	C.124
KLIPPON CS K51-2	1537540000	C.125
KLIPPON CS K51-2	1537550000	C.125
KLIPPON CS K51-2	1537570000	C.125
KLIPPON CS K51-4	1537580000	C.126
KLIPPON CS POK 121209-2	1537070000	C.162
KLIPPON CS POK 121209-2	1537080000	C.162
KLIPPON CS POK 121209-2	1537090000	C.163
KLIPPON CS POK 121209-2	1537100000	C.163
KLIPPON CS POK 121209-4	1537110000	C.163
KLIPPON CS POK 121209-4	1537120000	C.164
KLIPPON CS POK 121209-4	1537130000	C.164
KLIPPON CS POK 122209-2	1537140000	C.165
KLIPPON CS POK 122209-2	1537150000	C.165
KLIPPON CS POK 122209-2	1537170000	C.165
KLIPPON CS POK 122209-4	1537180000	C.166
KLIPPON CS STB 1-1	1537200000	C.86
KLIPPON CS STB 1-1	1537210000	C.86
KLIPPON CS STB 1-1	1537220000	C.87
KLIPPON CS STB 1-1	1537230000	C.87
KLIPPON CS STB 1-2	1537240000	C.87
KLIPPON CS STB 1-2	1537250000	C.88
KLIPPON CS STB 1-2	1537280000	C.88
KLIPPON CS STB 1-2	1537290000	C.89
KLIPPON CS STB 2.1-2	1537300000	C.89
KLIPPON CS STB 2.1-2	1537310000	C.89
KLIPPON CS STB 2.1-2	1537320000	C.90
KLIPPON CS STB 2.1-6	1537330000	C.90
KLIPPON CS STB 2.1-7	1537340000	C.91
KLIPPON CS STB 2.1-7	1537370000	C.91
KLIPPON K MF KIT 16	9529080000	C.108
KLIPPON K MF KIT 16	9529080000	C.111
KLIPPON K MF KIT 16	9529080000	C.113
KLIPPON K MF KIT 25	9527590000	C.107
KLIPPON K MF KIT 25	9527590000	C.109
KLIPPON K MF KIT 25	9527590000	C.110
KLIPPON K MF KIT 25	9527590000	C.112
KLIPPON K MF KIT 25	9527590000	C.114
KLIPPON K0	0573200000	C.94
KLIPPON K0	0573200000	C.96
KLIPPON K0 RAL7001	9529090000	C.94
KLIPPON K0 RAL7001	9529090000	C.96
KLIPPON K0 VMQ	1939760000	C.94
KLIPPON K0 VMQ	1939760000	C.96
KLIPPON K0 VMQ RAL7001	1937920000	C.94
KLIPPON K0 VMQ RAL7001	1937920000	C.96
KLIPPON K01	1565240000	C.94
KLIPPON K01	1565240000	C.97
KLIPPON K01	1565240000	C.116
KLIPPON K01 1M16AB CSS	8000004184	C.116
KLIPPON K01 RAL7001	9529100000	C.94
KLIPPON K01 RAL7001	9529100000	C.97
KLIPPON K01 VMQ	1939540000	C.94
KLIPPON K01 VMQ	1939540000	C.97
KLIPPON K01 VMQ RAL7001	1937850000	C.94
KLIPPON K01 VMQ RAL7001	1937850000	C.97
KLIPPON K02	1565250000	C.94
KLIPPON K02	1565250000	C.98
KLIPPON K02 RAL7001	9529110000	C.94
KLIPPON K02 RAL7001	9529110000	C.98
KLIPPON K02 VMQ	1939550000	C.94
KLIPPON K02 VMQ	1939550000	C.98
KLIPPON K02 VMQ RAL7001	1937840000	C.94
KLIPPON K02 VMQ RAL7001	1937840000	C.98
KLIPPON K1	0342000000	C.94
KLIPPON K1	0342000000	C.99
KLIPPON K1	0342000000	C.116
KLIPPON K1 1,5M16AB CSS	8000004147	C.116
KLIPPON K1 1M20AB CSS	8000004148	C.116
KLIPPON K1 EX	9526840000	C.94
KLIPPON K1 EX RAL7001	1329630000	C.94
KLIPPON K1 M16BCSS EX	8000004202	C.116
KLIPPON K1 M20BCSS EX	8000004203	C.116
KLIPPON K1 RAL7001	9529120000	C.94
KLIPPON K1 RAL7001	9529120000	C.99
KLIPPON K1 VMQ	1939560000	C.94
KLIPPON K1 VMQ	1939560000	C.99
KLIPPON K1 VMQ RAL7001	1937630000	C.94
KLIPPON K1 VMQ RAL7001	1937630000	C.99
KLIPPON K11	0573300000	C.94
KLIPPON K11	0573300000	C.100

Type	Order No.	Page
KLIPPON K11	0573300000	C.116
KLIPPON K11 2M16AB CSS	8000004149	C.116
KLIPPON K11 2M20AB CSS	8000004150	C.116
KLIPPON K11 EX	9526850000	C.94
KLIPPON K11 EX RAL7001	1329640000	C.94
KLIPPON K11 M16ACSS EX	8000004207	C.116
KLIPPON K11 M16ZCSS EX	8000004204	C.116
KLIPPON K11 M20ACSS EX	8000004209	C.116
KLIPPON K11 M20ZCSS EX	8000004208	C.116
KLIPPON K11 RAL7001	9529130000	C.94
KLIPPON K11 RAL7001	9529130000	C.100
KLIPPON K11 VMQ	1939570000	C.94
KLIPPON K11 VMQ	1939570000	C.100
KLIPPON K11 VMQ RAL7001	1937910000	C.94
KLIPPON K11 VMQ RAL7001	1937910000	C.100
KLIPPON K2	0342100000	C.94
KLIPPON K2	0342100000	C.101
KLIPPON K2	0342100000	C.116
KLIPPON K2 2M20AB CSS	8000004151	C.116
KLIPPON K2 EX	9526860000	C.94
KLIPPON K2 EX RAL7001	1329650000	C.94
KLIPPON K2 M20BCSS EX	8000004210	C.116
KLIPPON K2 RAL7001	9529140000	C.94
KLIPPON K2 RAL7001	9529140000	C.101
KLIPPON K2 VMQ	1939580000	C.94
KLIPPON K2 VMQ	1939580000	C.101
KLIPPON K2 VMQ RAL7001	1937930000	C.94
KLIPPON K2 VMQ RAL7001	1937930000	C.101
KLIPPON K21	0573400000	C.94
KLIPPON K21	0573400000	C.102
KLIPPON K21	0573400000	C.116
KLIPPON K21 3M16AB CSS	8000004152	C.116
KLIPPON K21 EX	9526870000	C.94
KLIPPON K21 EX RAL7001	1328120000	C.94
KLIPPON K21 M16ACSS EX	8000004212	C.116
KLIPPON K21 M16ZCSS EX	8000004211	C.116
KLIPPON K21 RAL7001	9529150000	C.94
KLIPPON K21 RAL7001	9529150000	C.102
KLIPPON K21 VMQ	1939590000	C.94
KLIPPON K21 VMQ	1939590000	C.102
KLIPPON K21 VMQ RAL7001	1937830000	C.94
KLIPPON K21 VMQ RAL7001	1937830000	C.102
KLIPPON K3	0342200000	C.94
KLIPPON K3	0342200000	C.103
KLIPPON K3	0342200000	C.116
KLIPPON K3 4M20AB CSS	8000004153	C.116
KLIPPON K3 EX	9526880000	C.94
KLIPPON K3 EX RAL7001	1329670000	C.94
KLIPPON K3 M20BCSS EX	8000004213	C.116
KLIPPON K3 RAL7001	9529160000	C.94
KLIPPON K3 RAL7001	9529160000	C.103
KLIPPON K3 VMQ	1939600000	C.94
KLIPPON K3 VMQ	1939600000	C.103
KLIPPON K3 VMQ RAL7001	1937900000	C.94
KLIPPON K3 VMQ RAL7001	1937900000	C.103
KLIPPON K31	0573500000	C.94
KLIPPON K31	0573500000	C.104
KLIPPON K31	0573500000	C.116
KLIPPON K31 4M20AB CSS	8000004154	C.116
KLIPPON K31 EX	9526890000	C.94
KLIPPON K31 EX RAL7001	1329680000	C.94
KLIPPON K31 M20ZCSS EX	8000004214	C.116
KLIPPON K31 RAL7001	9529170000	C.94
KLIPPON K31 RAL7001	9529170000	C.104
KLIPPON K31 VMQ	1939610000	C.94
KLIPPON K31 VMQ	1939610000	C.104
KLIPPON K31 VMQ RAL7001	1937820000	C.94
KLIPPON K31 VMQ RAL7001	1937820000	C.104
KLIPPON K32	1565260000	C.94
KLIPPON K32	1565260000	C.105
KLIPPON K32 EX	9526900000	C.94
KLIPPON K32 EX RAL7001	1329690000	C.94
KLIPPON K32 RAL7001	9529180000	C.94
KLIPPON K32 RAL7001	9529180000	C.105
KLIPPON K32 VMQ	1939620000	C.94
KLIPPON K32 VMQ	1939620000	C.105
KLIPPON K32 VMQ RAL7001	1937810000	C.94
KLIPPON K32 VMQ RAL7001	1937810000	C.105
KLIPPON K4	0342300000	C.94
KLIPPON K4	0342300000	C.106
KLIPPON K4	0342300000	C.116
KLIPPON K4 2M20AB CSS	8000004155	C.116
KLIPPON K4 EX	9526910000	C.94
KLIPPON K4 EX RAL7001	1329700000	C.94
KLIPPON K4 RAL7001	9529190000	C.94
KLIPPON K4 RAL7001	9529190000	C.106
KLIPPON K4 VMQ	1939630000	C.94
KLIPPON K4 VMQ	1939630000	C.106
KLIPPON K4 VMQ RAL7001	1937890000	C.94
KLIPPON K4 VMQ RAL7001	1937890000	C.106
KLIPPON K41	1565270000	C.94
KLIPPON K41	1565270000	C.107
KLIPPON K41	1565270000	C.116
KLIPPON K41 2M25AB CSS	8000003446	C.116
KLIPPON K41 3M20AB CSS	8000003447	C.116
KLIPPON K41 EX	9526920000	C.94
KLIPPON K41 EX RAL7001	1329710000	C.94
KLIPPON K41 M20WCSS EX	8000003591	C.116
KLIPPON K41 M25WCSS EX	8000003589	C.116

Type	Order No.	Page
KLIPPON K41 RAL7001	9529200000	C.94
KLIPPON K41 RAL7001	9529200000	C.107
KLIPPON K41 VMQ	1939640000	C.94
KLIPPON K41 VMQ	1939640000	C.107
KLIPPON K41 VMQ RAL7001	1937800000	C.94
KLIPPON K41 VMQ RAL7001	1937800000	C.107
KLIPPON K5	0342400000	C.94
KLIPPON K5	0342400000	C.108
KLIPPON K5	0342400000	C.116
KLIPPON K5 4M20AB CSS	8000004158	C.116
KLIPPON K5 4M20WCSS EX	8000004218	C.116
KLIPPON K5 4M20ZCSS EX	8000004219	C.116
KLIPPON K5 EX	9526930000	C.94
KLIPPON K5 EX RAL7001	1329720000	C.94
KLIPPON K5 RAL7001	9529210000	C.94
KLIPPON K5 RAL7001	9529210000	C.108
KLIPPON K5 VMQ	1939650000	C.94
KLIPPON K5 VMQ	1939650000	C.108
KLIPPON K5 VMQ RAL7001	1937860000	C.94
KLIPPON K5 VMQ RAL7001	1937860000	C.108
KLIPPON K51	1565280000	C.94
KLIPPON K51	1565280000	C.109
KLIPPON K51 EX	9526940000	C.94
KLIPPON K51 EX RAL7001	1328130000	C.94
KLIPPON K51 RAL7001	9529220000	C.94
KLIPPON K51 RAL7001	9529220000	C.109
KLIPPON K51 VMQ	1939660000	C.94
KLIPPON K51 VMQ	1939660000	C.109
KLIPPON K51 VMQ RAL7001	1937750000	C.94
KLIPPON K51 VMQ RAL7001	1937750000	C.109
KLIPPON K52	1565290000	C.94
KLIPPON K52	1565290000	C.110
KLIPPON K52	1565290000	C.116
KLIPPON K52 EX	9526950000	C.94
KLIPPON K52 EX RAL7001	1329730000	C.94
KLIPPON K52 M20WCSS EX	8000004220	C.116
KLIPPON K52 M20ZCSS EX	8000004221	C.116
KLIPPON K52 RAL7001	9529230000	C.94
KLIPPON K52 RAL7001	9529230000	C.110
KLIPPON K52 VMQ	1939670000	C.94
KLIPPON K52 VMQ	1939670000	C.110
KLIPPON K52 VMQ RAL7001	1937740000	C.94
KLIPPON K52 VMQ RAL7001	1937740000	C.110
KLIPPON K6	0342500000	C.94
KLIPPON K6	0342500000	C.111
KLIPPON K6 EX	9526960000	C.94
KLIPPON K6 EX RAL7001	1329740000	C.94
KLIPPON K6 RAL7001	9529240000	C.94
KLIPPON K6 RAL7001	9529240000	C.111
KLIPPON K6 VMQ	1939690000	C.94
KLIPPON K6 VMQ	1939690000	C.111
KLIPPON K6 VMQ RAL7001	1937870000	C.94
KLIPPON K6 VMQ RAL7001	1937870000	C.111
KLIPPON K61	0573600000	C.94
KLIPPON K61	0573600000	C.112
KLIPPON K61 EX	9526970000	C.94
KLIPPON K61 EX RAL7001	1328140000	C.94
KLIPPON K61 RAL7001	9529250000	C.94
KLIPPON K61 RAL7001	9529250000	C.112
KLIPPON K61 VMQ	1939700000	C.94
KLIPPON K61 VMQ	1939700000	C.112
KLIPPON K61 VMQ RAL7001	1937730000	C.94
KLIPPON K61 VMQ RAL7001	1937730000	C.112
KLIPPON K7	0342600000	C.94
KLIPPON K7	0342600000	C.113
KLIPPON K7 EX	9526980000	C.94
KLIPPON K7 EX RAL7001	1329750000	C.94
KLIPPON K7 RAL7001	9529260000	C.94
KLIPPON K7 RAL7001	9529260000	C.113
KLIPPON K7 VMQ	1939710000	C.94
KLIPPON K7 VMQ	1939710000	C.113
KLIPPON K7 VMQ RAL7001	1937880000	C.94
KLIPPON K7 VMQ RAL7001	1937880000	C.113
KLIPPON K71	0573700000	C.94
KLIPPON K71	0573700000	C.114
KLIPPON K71 EX	9526990000	C.94
KLIPPON K71 EX RAL7001	1329770000	C.94
KLIPPON K71 RAL7001	9529270000	C.94
KLIPPON K71 RAL7001	9529270000	C.114
KLIPPON K71 VMQ	1939730000	C.94
KLIPPON K71 VMQ	1939730000	C.114
KLIPPON K71 VMQ RAL7001	1937720000	C.94
KLIPPON K71 VMQ RAL7001	1937720000	C.114
KLIPPON POK 080806	1305810000	C.130
KLIPPON POK 080806	1305810000	C.132
KLIPPON POK 080806	1305810000	C.150
KLIPPON POK 080806 EX	1306000000	C.130
KLIPPON POK 080806 EX	1306000000	C.132
KLIPPON POK 081106	1305820000	C.130
KLIPPON POK 081106	1305820000	C.133
KLIPPON POK 081106	1305820000	C.150
KLIPPON POK 081106 EX	1306010000	C.130
KLIPPON POK 081106 EX	1306010000	C.133
KLIPPON POK 081606	1305830000	C.130
KLIPPON POK 081606	1305830000	C.134
KLIPPON POK 081606	1305830000	C.150
KLIPPON POK 081606 EX	1306020000	C.130
KLIPPON POK 081606 EX	1306020000	C.134
KLIPPON POK 081906	1305840000	C.130

Type	Order No.	Page
KLIPPON POK 081906	1305840000	C.135
KLIPPON POK 081906 EX	1306030000	C.130
KLIPPON POK 081906 EX	1306030000	C.135
KLIPPON POK 082306	1305850000	C.130
KLIPPON POK 082306	1305850000	C.136
KLIPPON POK 082306 EX	1306040000	C.130
KLIPPON POK 082306 EX	1306040000	C.136
KLIPPON POK 121209	1305870000	C.130
KLIPPON POK 121209	1305870000	C.137
KLIPPON POK 121209	1305870000	C.150
KLIPPON POK 121209 EX	1306050000	C.130
KLIPPON POK 121209 EX	1306050000	C.137
KLIPPON POK 122209	1305880000	C.130
KLIPPON POK 122209	1305880000	C.138
KLIPPON POK 122209 EX	1306070000	C.130
KLIPPON POK 122209 EX	1306070000	C.138
KLIPPON POK 161609	1305890000	C.130
KLIPPON POK 161609	1305890000	C.139
KLIPPON POK 161609	1305890000	C.150
KLIPPON POK 161609 EX	1306080000	C.130
KLIPPON POK 161609 EX	1306080000	C.139
KLIPPON POK 162609	1305900000	C.130
KLIPPON POK 162609	1305900000	C.140
KLIPPON POK 162609 EX	1306090000	C.130
KLIPPON POK 162609 EX	1306090000	C.140
KLIPPON POK 163609	1305910000	C.130
KLIPPON POK 163609	1305910000	C.141
KLIPPON POK 163609 EX	1306100000	C.130
KLIPPON POK 163609 EX	1306100000	C.141
KLIPPON POK 165609	1305920000	C.130
KLIPPON POK 165609	1305920000	C.142
KLIPPON POK 165609 EX	1306110000	C.130
KLIPPON POK 165609 EX	1306110000	C.142
KLIPPON POK 252512	1305930000	C.130
KLIPPON POK 252512	1305930000	C.143
KLIPPON POK 252512 EX	1306120000	C.130
KLIPPON POK 252512 EX	1306120000	C.143
KLIPPON POK 252516	1305980000	C.130
KLIPPON POK 252516	1305980000	C.144
KLIPPON POK 252516 EX	1306170000	C.130
KLIPPON POK 252516 EX	1306170000	C.144
KLIPPON POK 254012	1305940000	C.130
KLIPPON POK 254012	1305940000	C.145
KLIPPON POK 254012 EX	1306130000	C.130
KLIPPON POK 254012 EX	1306130000	C.145
KLIPPON POK 254016	1305990000	C.130
KLIPPON POK 254016	1305990000	C.146
KLIPPON POK 254016 EX	1306180000	C.130
KLIPPON POK 254016 EX	1306180000	C.146
KLIPPON POK 256012	1305950000	C.130
KLIPPON POK 256012	1305950000	C.147
KLIPPON POK 256012 EX	1306140000	C.130
KLIPPON POK 256012 EX	1306140000	C.147
KLIPPON POK 404012	1305970000	C.130
KLIPPON POK 404012	1305970000	C.148
KLIPPON POK 404012 EX	1306150000	C.130
KLIPPON POK 404012 EX	1306150000	C.148
KLIPPON POK1 2M16AB CSS	8000004160	C.150
KLIPPON POK1 2M16AB CSS	8000004160	C.152
KLIPPON POK1 M16ACSS EX	8000004223	C.150
KLIPPON POK1 M16ACSS EX	8000004223	C.152
KLIPPON POK1 M16BCSS EX	8000004222	C.150
KLIPPON POK1 M16BCSS EX	8000004222	C.152
KLIPPON POK2 2M20AB CSS	8000004161	C.150
KLIPPON POK2 2M20AB CSS	8000004161	C.153
KLIPPON POK2 M20ACSS EX	8000004225	C.150
KLIPPON POK2 M20ACSS EX	8000004225	C.153
KLIPPON POK2 M20BCSS EX	8000004224	C.150
KLIPPON POK2 M20BCSS EX	8000004224	C.153
KLIPPON POK3 4M20AB CSS	8000004162	C.150
KLIPPON POK3 4M20AB CSS	8000004162	C.154
KLIPPON POK3 M20ACSS EX	8000004228	C.150
KLIPPON POK3 M20ACSS EX	8000004228	C.154
KLIPPON POK3 M20BCSS EX	8000004226	C.150
KLIPPON POK3 M20BCSS EX	8000004226	C.154
KLIPPON POK4 3M20AB CSS	8000003448	C.150
KLIPPON POK4 3M20AB CSS	8000003448	C.155
KLIPPON POK4 M20WCSS EX	8000003593	C.150
KLIPPON POK4 M20WCSS EX	8000003593	C.155
KLIPPON POK4 M20ZCSS EX	8000003594	C.150
KLIPPON POK4 M20ZCSS EX	8000003594	C.155
KLIPPON POK51 4M20ABCSS	8000004164	C.150
KLIPPON POK51 4M20ABCSS	8000004164	C.156
KLIPPON POK51 M20WCSS E	8000004229	C.150
KLIPPON POK51 M20WCSS E	8000004229	C.156
KLIPPON POK51 M20ZCSS E	8000004230	C.150
KLIPPON POK51 M20ZCSS E	8000004230	C.156
KLIPPON QL KEY	2473930000	C.52
KLIPPON QL KEY	2473930000	C.53
KLIPPON QL KEY	2473930000	C.54
KLIPPON QL KEY	2473930000	C.55
KLIPPON QL KEY	2473930000	C.56
KLIPPON QL KEY	2473930000	C.57
KLIPPON QL KEY	2473930000	C.58
KLIPPON QL KEY	2473930000	C.59
KLIPPON QL KEY	2473930000	C.60
KLIPPON QL KEY	2473930000	C.61
KLIPPON QL KEY	2473930000	C.62
KLIPPON STB 1 MS HT	1024970000	C.66

Type	Order No.	Page
KLIPPON STB 1 MS HT	1024970000	C.68
KLIPPON STB 1 SS	1002690000	C.66
KLIPPON STB 1 SS	1002690000	C.68
KLIPPON STB 1 SS	1002690000	C.78
KLIPPON STB 1 SS E	1058810000	C.66
KLIPPON STB 1 SS E	1058810000	C.68
KLIPPON STB 1.1 MS HT	1024980000	C.66
KLIPPON STB 1.1 MS HT	1024980000	C.69
KLIPPON STB 1.1 SS	1002750000	C.66
KLIPPON STB 1.1 SS	1002750000	C.69
KLIPPON STB 1.1 SS E	1058820000	C.66
KLIPPON STB 1.1 SS E	1058820000	C.69
KLIPPON STB 2 MS HT	1024990000	C.66
KLIPPON STB 2 MS HT	1024990000	C.70
KLIPPON STB 2 SS	1002740000	C.66
KLIPPON STB 2 SS	1002740000	C.70
KLIPPON STB 2 SS	1002740000	C.79
KLIPPON STB 2 SS E	1058830000	C.66
KLIPPON STB 2 SS E	1058830000	C.70
KLIPPON STB 2.1 MS HT	1025010000	C.66
KLIPPON STB 2.1 MS HT	1025010000	C.71
KLIPPON STB 2.1 SS	1002730000	C.66
KLIPPON STB 2.1 SS	1002730000	C.71
KLIPPON STB 2.1 SS E	1058840000	C.66
KLIPPON STB 2.1 SS E	1058840000	C.71
KLIPPON STB 3 MS HT	1025020000	C.66
KLIPPON STB 3 MS HT	1025020000	C.72
KLIPPON STB 3 SS	1002720000	C.66
KLIPPON STB 3 SS	1002720000	C.72
KLIPPON STB 3 SS	1002720000	C.80
KLIPPON STB 3 SS E	1058850000	C.66
KLIPPON STB 3 SS E	1058850000	C.72
KLIPPON STB 4 MS HT	1025030000	C.66
KLIPPON STB 4 MS HT	1025030000	C.73
KLIPPON STB 4 SS	1002710000	C.66
KLIPPON STB 4 SS	1002710000	C.73
KLIPPON STB 4 SS	1002710000	C.81
KLIPPON STB 4 SS E	1058860000	C.66
KLIPPON STB 4 SS E	1058860000	C.73
KLIPPON STB 5 MS HT	1025040000	C.66
KLIPPON STB 5 MS HT	1025040000	C.74
KLIPPON STB 5 SS	1002700000	C.66
KLIPPON STB 5 SS	1002700000	C.74
KLIPPON STB 5 SS E	1058880000	C.66
KLIPPON STB 5 SS E	1058880000	C.74
KLIPPON STB 6 MS HT	1025050000	C.66
KLIPPON STB 6 MS HT	1025050000	C.75
KLIPPON STB 6 SS	1002760000	C.66
KLIPPON STB 6 SS	1002760000	C.75
KLIPPON STB 6 SS E	1058870000	C.66
KLIPPON STB 6 SS E	1058870000	C.75
KSG M20 BN O NI 2 G16	1911510000	D.33
KSG M20 BN O NI 2 G20	1911560000	D.33
KSG M20 BN O NI 2 G20S	1911540000	D.33
KSG M20 BS O NI 2 G16	0930481222	D.34
KSG M20 BS O NI 2 G20	0930501222	D.34
KSG M20 BS O NI 2 G20S	0930491224	D.34
KSG M25 BN O NI 2 G25	1911570000	D.33
KSG M25 BS O NI 2 G25	0930511222	D.34
KSG M32 BN O NI 2 G32	1911580000	D.33
KSG M32 BS O NI 2 G32	0930521222	D.34
KSG M40 BN O NI 2 G40	1911590000	D.33
KSG M40 BS O NI 2 G40	0930531222	D.34
KSG M50 BN O NI 2 G50	1911610000	D.33
KSG M50 BN O NI 2 G50S	1911600000	D.33
KSG M50 BS O NI 2 G50	1136670000	D.34
KSG M50 BS O NI 2 G50S	1136660000	D.34
KSG M63 BN O NI 2 G63	1911630000	D.33
KSG M63 BN O NI 2 G63S	1911620000	D.33
KSG M63 BS O NI 2 G63	1136690000	D.34
KSG M63 BS O NI 2 G63S	1136680000	D.34
KSG M75 BN O NI 2 G75	1075360000	D.33
KSG M75 BN O NI 2 G75S	1075350000	D.33
KSG M75 BS O NI 2 G75	1136710000	D.34
KSG M75 BS O NI 2 G75S	1136700000	D.34
KSP EL30	1736670000	D.51
KSP EL38	1736680000	D.51
KSP EL46	1076750000	D.51
KSP EL55	1076760000	D.51
KSP EL65	1076770000	D.51
KSP EL80	1076780000	D.51
KSP EL90	1076790000	D.51
KSP L 104 S	1193940000	D.50
KSP L114 S	1192790000	D.50
KSP L24	1736570000	D.51
KSP L24 S	0930700001	D.50
KSP L30	1736580000	D.51
KSP L30 S	0930700002	D.50
KSP L38	1736590000	D.51
KSP L38 S	0930700003	D.50
KSP L46	1736600000	D.51
KSP L46 S	0930700004	D.50
KSP L55	1736610000	D.51
KSP L55 S	0930700005	D.50
KSP L65	1736620000	D.51
KSP L65 S	0930700006	D.50
KSP L80	1736630000	D.51
KSP L80 S	0930700007	D.50
KSP L90	1736640000	D.51

Type	Order No.	Page
KSP L90 S	0930700008	D.50
KSPMH M16 BSC	1477740000	D.57
KSPMH M16 SSC	1477820000	C.44
KSPMH M16 SSC	1477820000	C.78
KSPMH M16 SSC	1477820000	D.57
KSPMH M20 BSC	1477750000	D.57
KSPMH M20 SSC	1477840000	C.44
KSPMH M20 SSC	1477840000	C.45
KSPMH M20 SSC	1477840000	C.46
KSPMH M20 SSC	1477840000	C.47
KSPMH M20 SSC	1477840000	C.79
KSPMH M20 SSC	1477840000	C.80
KSPMH M20 SSC	1477840000	D.57
KSPMH M25 BSC	1477770000	D.57
KSPMH M25 SSC	1477870000	C.47
KSPMH M25 SSC	1477870000	C.81
KSPMH M25 SSC	1477870000	D.57
KSPMH M32 BSC	1477780000	D.57
KSPMH M32 SSC	1477890000	C.45
KSPMH M32 SSC	1477890000	C.46
KSPMH M32 SSC	1477890000	D.57
KSPMH M40 BSC	1477790000	D.57
KSPMH M40 SSC	1477910000	C.47
KSPMH M40 SSC	1477910000	D.57
KSPMH M50 BSC	1477800000	D.57
KSPMH M50 SSC	1477930000	D.57
KSPMH M63 BSC	1477810000	D.57
KSPMH M63 SSC	1477950000	D.57
KSPMH M75 BSC	1477830000	D.57
KSPMH M75 SSC	1477980000	D.57
KSWF M16	1076680000	D.48
KSWF M20	0899750000	D.48
KSWF M25	0899770000	D.48
KSWF M32	1076690000	D.48
KSWF M40	1076710000	D.48
KSWF M50	1076720000	D.48
KSWF M63	1076730000	D.48
KSWF M75	1076740000	D.48
KSWN M16	1076630000	D.47
KSWN M20	0930730002	D.47
KSWN M25	1076640000	D.47
KSWN M32	1076650000	D.47
KSWN M40	0899780000	D.47
KSWN M50	0900660000	D.47
KSWN M63	1076660000	D.47
KSWN M75	1076670000	D.47
KTB FS 221513 S4E0	1195650000	C.40
KTB FS 221513 S4E1	1195660000	C.40
KTB FS 221513 S4E2	1195670000	C.40
KTB FS 221513 S4E3	1195680000	C.40
KTB FS 221513 S4E4	1195690000	C.40
KTB FS 262615 S4E0	1195700000	C.40
KTB FS 262615 S4E1	1195710000	C.40
KTB FS 262615 S4E2	1195720000	C.40
KTB FS 262615 S4E3	1195730000	C.40
KTB FS 262615 S4E4	1195740000	C.40
KTB FS 262620 S4E0	1195750000	C.40
KTB FS 262620 S4E1	1195760000	C.40
KTB FS 262620 S4E2	1195770000	C.40
KTB FS 262620 S4E3	1195780000	C.40
KTB FS 262620 S4E4	1195790000	C.40
KTB FS 303015 S4E0	1195800000	C.40
KTB FS 303015 S4E1	1195810000	C.40
KTB FS 303015 S4E2	1195820000	C.40
KTB FS 303015 S4E3	1195830000	C.40
KTB FS 303015 S4E4	1195840000	C.40
KTB FS 303020 S4E0	1195850000	C.40
KTB FS 303020 S4E1	1195860000	C.40
KTB FS 303020 S4E2	1195870000	C.40
KTB FS 303020 S4E3	1195880000	C.40
KTB FS 303020 S4E4	1195890000	C.40
KTB FS 352615 S4E0	1195900000	C.40
KTB FS 352615 S4E1	1195910000	C.40
KTB FS 352615 S4E2	1195920000	C.40
KTB FS 352615 S4E3	1195930000	C.40
KTB FS 352615 S4E4	1195940000	C.40
KTB FS 352620 S4E0	1195950000	C.40
KTB FS 352620 S4E1	1195960000	C.40
KTB FS 352620 S4E2	1195970000	C.40
KTB FS 352620 S4E3	1195980000	C.40
KTB FS 352620 S4E4	1195990000	C.40
KTB FS 403015 S4E0	1196000000	C.40
KTB FS 403015 S4E1	1196010000	C.40
KTB FS 403015 S4E2	1196020000	C.40
KTB FS 403015 S4E3	1196030000	C.40
KTB FS 403015 S4E4	1196040000	C.40
KTB FS 403020 S4E0	1196050000	C.40
KTB FS 403020 S4E1	1196060000	C.40
KTB FS 403020 S4E2	1196070000	C.40
KTB FS 403020 S4E3	1196080000	C.40
KTB FS 403020 S4E4	1196090000	C.40
KTB FS 453815 S4E0	1196100000	C.40
KTB FS 453815 S4E1	1196110000	C.40
KTB FS 453815 S4E2	1196120000	C.40
KTB FS 453815 S4E3	1196130000	C.40
KTB FS 453815 S4E4	1196140000	C.40
KTB FS 453820 S4E0	1196150000	C.40
KTB FS 453820 S4E1	1196160000	C.40
KTB FS 453820 S4E2	1196170000	C.40

Type	Order No.	Page
KTB FS 453820 S4E3	1196180000	C.40
KTB FS 453820 S4E4	1196190000	C.40
KTB FS 484815 S4E0	1196200000	C.40
KTB FS 484815 S4E1	1196210000	C.40
KTB FS 484815 S4E2	1196220000	C.40
KTB FS 484815 S4E3	1196230000	C.40
KTB FS 484815 S4E4	1196240000	C.40
KTB FS 484820 S4E0	1196250000	C.40
KTB FS 484820 S4E1	1196260000	C.40
KTB FS 484820 S4E2	1196270000	C.40
KTB FS 484820 S4E3	1196280000	C.40
KTB FS 484820 S4E4	1196290000	C.40
KTB FS 553515 S4E0	1196300000	C.40
KTB FS 553515 S4E1	1196310000	C.40
KTB FS 553515 S4E2	1196320000	C.40
KTB FS 553515 S4E3	1196330000	C.40
KTB FS 553515 S4E4	1196340000	C.40
KTB FS 553520 S4E0	1196350000	C.40
KTB FS 553520 S4E1	1196360000	C.40
KTB FS 553520 S4E2	1196370000	C.40
KTB FS 553520 S4E3	1196380000	C.40
KTB FS 553520 S4E4	1196390000	C.40
KTB FS 624515 S4E0	1196400000	C.40
KTB FS 624515 S4E1	1196410000	C.40
KTB FS 624515 S4E2	1196420000	C.40
KTB FS 624515 S4E3	1196430000	C.40
KTB FS 624515 S4E4	1196440000	C.40
KTB FS 624520 S4E0	1196450000	C.40
KTB FS 624520 S4E1	1196460000	C.40
KTB FS 624520 S4E2	1196470000	C.40
KTB FS 624520 S4E3	1196480000	C.40
KTB FS 624520 S4E4	1196490000	C.40
KTB FS 765015 S4E0	1196500000	C.40
KTB FS 765015 S4E1	1196510000	C.40
KTB FS 765015 S4E2	1196520000	C.40
KTB FS 765015 S4E3	1196530000	C.40
KTB FS 765015 S4E4	1196540000	C.40
KTB FS 765020 S4E0	1196550000	C.40
KTB FS 765020 S4E1	1196560000	C.40
KTB FS 765020 S4E2	1196570000	C.40
KTB FS 765020 S4E3	1196580000	C.40
KTB FS 765020 S4E4	1196590000	C.40
KTB FS 916115 S4E0	1196600000	C.40
KTB FS 916115 S4E1	1196610000	C.40
KTB FS 916115 S4E2	1196620000	C.40
KTB FS 916115 S4E3	1196630000	C.40
KTB FS 916115 S4E4	1196640000	C.40
KTB FS 916120 S4E0	1196650000	C.40
KTB FS 916120 S4E1	1196660000	C.40
KTB FS 916120 S4E2	1196670000	C.40
KTB FS 916120 S4E3	1196680000	C.40
KTB FS 916120 S4E4	1196690000	C.40
KTB FS 987420 S4E0	1196700000	C.40
KTB FS 987420 S4E1	1196710000	C.40
KTB FS 987420 S4E2	1196720000	C.40
KTB FS 987420 S4E3	1196730000	C.40
KTB FS 987420 S4E4	1196740000	C.40
KTB GP 221513 AB S4	1280890000	C.44
KTB GP 221513 AB S4 6MM	1256270000	C.15
KTB GP 221513 AB S4 6MM	1256270000	C.44
KTB GP 221513 AB S4 PE	2022770000	C.15
KTB GP 221513 CD S4 6MM	1256280000	C.15
KTB GP 221513 CD S4 PE	2022900000	C.15
KTB GP 262615 AB S4	1280910000	C.45
KTB GP 262615 AB S4 6MM	1256290000	C.16
KTB GP 262615 AB S4 6MM	1256290000	C.45
KTB GP 262615 AB S4 PE	2022930000	C.16
KTB GP 262615 CD S4 6MM	1256310000	C.16
KTB GP 262615 CD S4 PE	2023090000	C.16
KTB GP 262620 AB S4 6MM	1256320000	C.17
KTB GP 262620 AB S4 PE	2023100000	C.17
KTB GP 262620 CD S4 6MM	1256330000	C.17
KTB GP 262620 CD S4 PE	2023110000	C.17
KTB GP 303015 AB S4 6MM	1256340000	C.18
KTB GP 303015 AB S4 PE	2023120000	C.18
KTB GP 303015 CD S4 6MM	1256350000	C.18
KTB GP 303015 CD S4 PE	2023130000	C.18
KTB GP 303020 AB S4	1280970000	C.46
KTB GP 303020 AB S4 6MM	1256360000	C.19
KTB GP 303020 AB S4 6MM	1256360000	C.46
KTB GP 303020 AB S4 PE	2023140000	C.19
KTB GP 303020 CD S4 6MM	1256370000	C.19
KTB GP 303020 CD S4 PE	2023150000	C.19
KTB GP 352615 AB S4 6MM	1256380000	C.20
KTB GP 352615 AB S4 PE	2023160000	C.20
KTB GP 352615 CD S4 6MM	1256390000	C.20
KTB GP 352615 DC S4 PE	2023210000	C.20
KTB GP 352620 AB S4 6MM	1256410000	C.21
KTB GP 352620 AB S4 PE	2023230000	C.21
KTB GP 352620 CD S4 6MM	1256420000	C.21
KTB GP 352620 CD S4 PE	2023280000	C.21
KTB GP 403015 AB S4 6MM	1256430000	C.22
KTB GP 403015 AB S4 PE	2023320000	C.22
KTB GP 403015 CD S4 6MM	1256440000	C.22
KTB GP 403015 CD S4 PE	2023330000	C.22
KTB GP 403020 AB S4 6MM	1256450000	C.23
KTB GP 403020 AB S4 PE	2023450000	C.23
KTB GP 403020 CD S4 6MM	1256470000	C.23
KTB GP 403020 CD S4 PE	2023480000	C.23

Type	Order No.	Page
KTB GP 453815 AB S4 6MM	1256480000	C.24
KTB GP 453815 AB S4 PE	2023490000	C.24
KTB GP 453815 CD S4 6MM	1256490000	C.24
KTB GP 453815 CD S4 PE	2023500000	C.24
KTB GP 453820 AB S4 6MM	1256510000	C.25
KTB GP 453820 AB S4 PE	2023510000	C.25
KTB GP 453820 CD S4 6MM	1256520000	C.25
KTB GP 453820 CD S4 PE	2023520000	C.25
KTB GP 484815 AB S4 6MM	1256530000	C.26
KTB GP 484815 AB S4 PE	2023530000	C.26
KTB GP 484815 CD S4 6MM	1256540000	C.26
KTB GP 484815 CD S4 PE	2023540000	C.26
KTB GP 484820 AB S4	1281130000	C.47
KTB GP 484820 AB S4 6MM	1256550000	C.27
KTB GP 484820 AB S4 6MM	1256550000	C.47
KTB GP 484820 AB S4 PE	2023580000	C.27
KTB GP 484820 CD S4 6MM	1256560000	C.27
KTB GP 484820 CD S4 PE	2023620000	C.27
KTB GP 553515 AB S4 6MM	1256570000	C.28
KTB GP 553515 AB S4 PE	2023660000	C.28
KTB GP 553515 CD S4 6MM	1256580000	C.28
KTB GP 553515 CD S4 PE	2023670000	C.28
KTB GP 553520 AB S4 6MM	1256590000	C.29
KTB GP 553520 AB S4 PE	2023740000	C.29
KTB GP 553520 CD S4 6MM	1256610000	C.29
KTB GP 553520 CD S4 PE	2023790000	C.29
KTB GP 624515 AB S4 6MM	1256620000	C.30
KTB GP 624515 AB S4 PE	2023820000	C.30
KTB GP 624515 CD S4 6MM	1256630000	C.30
KTB GP 624515 CD S4 PE	2023870000	C.30
KTB GP 624520 AB S4 6MM	1256640000	C.31
KTB GP 624520 AB S4 PE	2023880000	C.31
KTB GP 624520 CD S4 6MM	1256650000	C.31
KTB GP 624520 CD S4 PE	2023930000	C.31
KTB GP 765015 AB S4 6MM	1256660000	C.32
KTB GP 765015 AB S4 PE	2024040000	C.32
KTB GP 765015 CD S4 6MM	1256670000	C.32
KTB GP 765015 CD S4 PE	2024090000	C.32
KTB GP 765020 AB S4 6MM	1256680000	C.33
KTB GP 765020 AB S4 PE	2024100000	C.33
KTB GP 765020 CD S4 6MM	1256690000	C.33
KTB GP 765020 CD S4 PE	2024140000	C.33
KTB GP 916115 AB S4 6MM	1256710000	C.34
KTB GP 916115 AB S4 PE	2024150000	C.34
KTB GP 916115 CD S4 6MM	1256720000	C.34
KTB GP 916115 CD S4 PE	2024300000	C.34
KTB GP 916120 AB S4 6MM	1256730000	C.35
KTB GP 916120 AB S4 PE	2024470000	C.35
KTB GP 916120 CD S4 6MM	1256740000	C.35
KTB GP 916120 CD S4 PE	2024490000	C.35
KTB GP 987420 AB S4 6MM	1256750000	C.36
KTB GP 987420 AB S4 PE	2024560000	C.36
KTB GP 987420 CD S4 6MM	1256760000	C.36
KTB GP 987420 CD S4 PE	2024590000	C.36
KTB MH 221513 Exia	8000028398	C.42
KTB MH 221513 Exia	8000028398	C.44
KTB MH 221513 S4E0	1194550000	C.12
KTB MH 221513 S4E0	1194550000	C.15
KTB MH 221513 S4E1	1194560000	C.12
KTB MH 221513 S4E1	1194560000	C.15
KTB MH 221513 S4E1	1194560000	C.44
KTB MH 221513 S4E2	1194570000	C.12
KTB MH 221513 S4E2	1194570000	C.15
KTB MH 221513 S4E3	1194580000	C.12
KTB MH 221513 S4E3	1194580000	C.15
KTB MH 221513 S4E4	1194590000	C.12
KTB MH 221513 S4E4	1194590000	C.15
KTB MH 262615 Exia	8000028399	C.42
KTB MH 262615 Exia	8000028399	C.45
KTB MH 262615 S4E0	1194600000	C.12
KTB MH 262615 S4E0	1194600000	C.16
KTB MH 262615 S4E1	1194610000	C.12
KTB MH 262615 S4E1	1194610000	C.16
KTB MH 262615 S4E1	1194610000	C.45
KTB MH 262615 S4E2	1194620000	C.12
KTB MH 262615 S4E2	1194620000	C.16
KTB MH 262615 S4E3	1194630000	C.12
KTB MH 262615 S4E3	1194630000	C.16
KTB MH 262615 S4E4	1194640000	C.12
KTB MH 262615 S4E4	1194640000	C.16
KTB MH 262620 S4E0	1194650000	C.12
KTB MH 262620 S4E0	1194650000	C.17
KTB MH 262620 S4E1	1194660000	C.12
KTB MH 262620 S4E1	1194660000	C.17
KTB MH 262620 S4E2	1194670000	C.12
KTB MH 262620 S4E2	1194670000	C.17
KTB MH 262620 S4E3	1194680000	C.12
KTB MH 262620 S4E3	1194680000	C.17
KTB MH 262620 S4E4	1194690000	C.12
KTB MH 262620 S4E4	1194690000	C.17
KTB MH 303015 S4E0	1194700000	C.12
KTB MH 303015 S4E0	1194700000	C.18
KTB MH 303015 S4E1	1194710000	C.12
KTB MH 303015 S4E1	1194710000	C.18
KTB MH 303015 S4E2	1194720000	C.12
KTB MH 303015 S4E2	1194720000	C.18
KTB MH 303015 S4E3	1194730000	C.12
KTB MH 303015 S4E3	1194730000	C.18
KTB MH 303015 S4E4	1194740000	C.12

Type	Order No.	Page
KTB MH 303015 S4E4	1194740000	C.18
KTB MH 303020 S4E0	1194750000	C.12
KTB MH 303020 S4E0	1194750000	C.19
KTB MH 303020 S4E1	1194760000	C.12
KTB MH 303020 S4E1	1194760000	C.19
KTB MH 303020 S4E2	1194770000	C.12
KTB MH 303020 S4E2	1194770000	C.19
KTB MH 303020 S4E3	1194780000	C.12
KTB MH 303020 S4E3	1194780000	C.19
KTB MH 303020 S4E4	1194790000	C.12
KTB MH 303020 S4E4	1194790000	C.19
KTB MH 352615 S4E0	1194800000	C.12
KTB MH 352615 S4E0	1194800000	C.20
KTB MH 352615 S4E1	1194810000	C.12
KTB MH 352615 S4E1	1194810000	C.20
KTB MH 352615 S4E2	1194820000	C.12
KTB MH 352615 S4E2	1194820000	C.20
KTB MH 352615 S4E3	1194830000	C.12
KTB MH 352615 S4E3	1194830000	C.20
KTB MH 352615 S4E4	1194840000	C.12
KTB MH 352615 S4E4	1194840000	C.20
KTB MH 352620 S4E0	1194850000	C.12
KTB MH 352620 S4E0	1194850000	C.21
KTB MH 352620 S4E1	1194860000	C.12
KTB MH 352620 S4E1	1194860000	C.21
KTB MH 352620 S4E2	1194870000	C.12
KTB MH 352620 S4E2	1194870000	C.21
KTB MH 352620 S4E3	1194880000	C.12
KTB MH 352620 S4E3	1194880000	C.21
KTB MH 352620 S4E4	1194890000	C.12
KTB MH 352620 S4E4	1194890000	C.21
KTB MH 403015 S4E0	1194900000	C.12
KTB MH 403015 S4E0	1194900000	C.22
KTB MH 403015 S4E1	1194910000	C.12
KTB MH 403015 S4E1	1194910000	C.22
KTB MH 403015 S4E2	1194920000	C.12
KTB MH 403015 S4E2	1194920000	C.22
KTB MH 403015 S4E3	1194930000	C.12
KTB MH 403015 S4E3	1194930000	C.22
KTB MH 403015 S4E4	1194940000	C.12
KTB MH 403015 S4E4	1194940000	C.22
KTB MH 403020 S4E0	1194950000	C.12
KTB MH 403020 S4E0	1194950000	C.23
KTB MH 403020 S4E1	1194960000	C.12
KTB MH 403020 S4E1	1194960000	C.23
KTB MH 403020 S4E2	1194970000	C.12
KTB MH 403020 S4E2	1194970000	C.23
KTB MH 403020 S4E3	1194980000	C.12
KTB MH 403020 S4E3	1194980000	C.23
KTB MH 403020 S4E4	1194990000	C.12
KTB MH 403020 S4E4	1194990000	C.23
KTB MH 453815 S4E0	1195000000	C.12
KTB MH 453815 S4E0	1195000000	C.24
KTB MH 453815 S4E1	1195010000	C.12
KTB MH 453815 S4E1	1195010000	C.24
KTB MH 453815 S4E2	1195020000	C.12
KTB MH 453815 S4E2	1195020000	C.24
KTB MH 453815 S4E3	1195030000	C.12
KTB MH 453815 S4E3	1195030000	C.24
KTB MH 453815 S4E4	1195040000	C.12
KTB MH 453815 S4E4	1195040000	C.24
KTB MH 453820 S4E0	1195050000	C.12
KTB MH 453820 S4E0	1195050000	C.25
KTB MH 453820 S4E1	1195060000	C.12
KTB MH 453820 S4E1	1195060000	C.25
KTB MH 453820 S4E2	1195070000	C.12
KTB MH 453820 S4E2	1195070000	C.25
KTB MH 453820 S4E3	1195080000	C.12
KTB MH 453820 S4E3	1195080000	C.25
KTB MH 453820 S4E4	1195090000	C.12
KTB MH 453820 S4E4	1195090000	C.25
KTB MH 484815 S4E0	1195100000	C.12
KTB MH 484815 S4E0	1195100000	C.26
KTB MH 484815 S4E1	1195110000	C.12
KTB MH 484815 S4E1	1195110000	C.26
KTB MH 484815 S4E2	1195120000	C.12
KTB MH 484815 S4E2	1195120000	C.26
KTB MH 484815 S4E3	1195130000	C.12
KTB MH 484815 S4E3	1195130000	C.26
KTB MH 484815 S4E4	1195140000	C.12
KTB MH 484815 S4E4	1195140000	C.26
KTB MH 484820 S4E0	1195150000	C.12
KTB MH 484820 S4E0	1195150000	C.27
KTB MH 484820 S4E1	1195160000	C.12
KTB MH 484820 S4E1	1195160000	C.27
KTB MH 484820 S4E2	1195170000	C.12
KTB MH 484820 S4E2	1195170000	C.27
KTB MH 484820 S4E3	1195180000	C.12
KTB MH 484820 S4E3	1195180000	C.27
KTB MH 484820 S4E4	1195190000	C.12
KTB MH 484820 S4E4	1195190000	C.27
KTB MH 553515 S4E0	1195200000	C.12
KTB MH 553515 S4E0	1195200000	C.28
KTB MH 553515 S4E1	1195210000	C.12
KTB MH 553515 S4E1	1195210000	C.28
KTB MH 553515 S4E2	1195220000	C.12
KTB MH 553515 S4E2	1195220000	C.28
KTB MH 553515 S4E3	1195230000	C.12
KTB MH 553515 S4E3	1195230000	C.28

Type	Order No.	Page
KTB MH 553515 S4E4	1195240000	C.12
KTB MH 553515 S4E4	1195240000	C.28
KTB MH 553520 S4E0	1195250000	C.12
KTB MH 553520 S4E0	1195250000	C.29
KTB MH 553520 S4E1	1195260000	C.12
KTB MH 553520 S4E1	1195260000	C.29
KTB MH 553520 S4E2	1195270000	C.12
KTB MH 553520 S4E2	1195270000	C.29
KTB MH 553520 S4E3	1195280000	C.12
KTB MH 553520 S4E3	1195280000	C.29
KTB MH 553520 S4E4	1195290000	C.12
KTB MH 553520 S4E4	1195290000	C.29
KTB MH 624515 S4E0	1195300000	C.12
KTB MH 624515 S4E0	1195300000	C.30
KTB MH 624515 S4E1	1195310000	C.12
KTB MH 624515 S4E1	1195310000	C.30
KTB MH 624515 S4E2	1195320000	C.12
KTB MH 624515 S4E2	1195320000	C.30
KTB MH 624515 S4E3	1195330000	C.12
KTB MH 624515 S4E3	1195330000	C.30
KTB MH 624515 S4E4	1195340000	C.12
KTB MH 624515 S4E4	1195340000	C.30
KTB MH 624520 S4E0	1195350000	C.12
KTB MH 624520 S4E0	1195350000	C.31
KTB MH 624520 S4E1	1195360000	C.12
KTB MH 624520 S4E1	1195360000	C.31
KTB MH 624520 S4E2	1195370000	C.12
KTB MH 624520 S4E2	1195370000	C.31
KTB MH 624520 S4E3	1195380000	C.12
KTB MH 624520 S4E3	1195380000	C.31
KTB MH 624520 S4E4	1195390000	C.12
KTB MH 624520 S4E4	1195390000	C.31
KTB MH 765015 S4E0	1195400000	C.12
KTB MH 765015 S4E0	1195400000	C.32
KTB MH 765015 S4E1	1195410000	C.12
KTB MH 765015 S4E1	1195410000	C.32
KTB MH 765015 S4E2	1195420000	C.12
KTB MH 765015 S4E2	1195420000	C.32
KTB MH 765015 S4E3	1195430000	C.12
KTB MH 765015 S4E3	1195430000	C.32
KTB MH 765015 S4E4	1195440000	C.12
KTB MH 765015 S4E4	1195440000	C.32
KTB MH 765020 S4E0	1195450000	C.12
KTB MH 765020 S4E0	1195450000	C.33
KTB MH 765020 S4E1	1195460000	C.12
KTB MH 765020 S4E1	1195460000	C.33
KTB MH 765020 S4E2	1195470000	C.12
KTB MH 765020 S4E2	1195470000	C.33
KTB MH 765020 S4E3	1195480000	C.12
KTB MH 765020 S4E3	1195480000	C.33
KTB MH 765020 S4E4	1195490000	C.12
KTB MH 765020 S4E4	1195490000	C.33
KTB MH 916115 S4E0	1195500000	C.12
KTB MH 916115 S4E0	1195500000	C.34
KTB MH 916115 S4E1	1195510000	C.12
KTB MH 916115 S4E1	1195510000	C.34
KTB MH 916115 S4E2	1195520000	C.12
KTB MH 916115 S4E2	1195520000	C.34
KTB MH 916115 S4E3	1195530000	C.12
KTB MH 916115 S4E3	1195530000	C.34
KTB MH 916115 S4E4	1195540000	C.12
KTB MH 916115 S4E4	1195540000	C.34
KTB MH 916120 S4E0	1195550000	C.12
KTB MH 916120 S4E0	1195550000	C.35
KTB MH 916120 S4E1	1195560000	C.12
KTB MH 916120 S4E1	1195560000	C.35
KTB MH 916120 S4E2	1195570000	C.12
KTB MH 916120 S4E2	1195570000	C.35
KTB MH 916120 S4E3	1195580000	C.12
KTB MH 916120 S4E3	1195580000	C.35
KTB MH 916120 S4E4	1195590000	C.12
KTB MH 916120 S4E4	1195590000	C.35
KTB MH 987420 S4E0	1195600000	C.12
KTB MH 987420 S4E0	1195600000	C.36
KTB MH 987420 S4E1	1195610000	C.12
KTB MH 987420 S4E1	1195610000	C.36
KTB MH 987420 S4E2	1195620000	C.12
KTB MH 987420 S4E2	1195620000	C.36
KTB MH 987420 S4E3	1195630000	C.12
KTB MH 987420 S4E3	1195630000	C.36
KTB MH 987420 S4E4	1195640000	C.12
KTB MH 987420 S4E4	1195640000	C.36
KTB MOPL 2215 MSZN	1193930000	C.15
KTB MOPL 2215 MSZN H	2022050000	C.15
KTB MOPL 2215 S2N	1193810000	C.15
KTB MOPL 2215 S2N	1193810000	C.44
KTB MOPL 2215 S2N H	1257650000	C.15
KTB MOPL 2626 MSZN	1193950000	C.16
KTB MOPL 2626 MSZN	1193950000	C.17
KTB MOPL 2626 MSZN H	2022060000	C.16
KTB MOPL 2626 MSZN H	2022060000	C.17
KTB MOPL 2626 S2N	1193820000	C.16
KTB MOPL 2626 S2N	1193820000	C.17
KTB MOPL 2626 S2N	1193820000	C.45
KTB MOPL 2626 S2N H	1257660000	C.16
KTB MOPL 2626 S2N H	1257660000	C.17
KTB MOPL 3030 MSZN	1193960000	C.18
KTB MOPL 3030 MSZN	1193960000	C.19
KTB MOPL 3030 MSZN H	2022190000	C.18

Type	Order No.	Page
KTB MOPL 3030 MSZN H	2022190000	C.19
KTB MOPL 3030 S2N	1193830000	C.18
KTB MOPL 3030 S2N	1193830000	C.19
KTB MOPL 3030 S2N	1193830000	C.46
KTB MOPL 3030 S2N H	1257670000	C.18
KTB MOPL 3030 S2N H	1257670000	C.19
KTB MOPL 3526 MSZN	1193970000	C.20
KTB MOPL 3526 MSZN	1193970000	C.21
KTB MOPL 3526 MSZN H	2022310000	C.20
KTB MOPL 3526 MSZN H	2022310000	C.21
KTB MOPL 3526 S2N	1193840000	C.20
KTB MOPL 3526 S2N	1193840000	C.21
KTB MOPL 3526 S2N H	1257680000	C.20
KTB MOPL 3526 S2N H	1257680000	C.21
KTB MOPL 4030 MSZN	1193980000	C.22
KTB MOPL 4030 MSZN	1193980000	C.23
KTB MOPL 4030 MSZN H	2022420000	C.22
KTB MOPL 4030 MSZN H	2022420000	C.23
KTB MOPL 4030 S2N	1193850000	C.22
KTB MOPL 4030 S2N	1193850000	C.23
KTB MOPL 4030 S2N H	1257690000	C.22
KTB MOPL 4030 S2N H	1257690000	C.23
KTB MOPL 4538 MSZN	1193990000	C.24
KTB MOPL 4538 MSZN	1193990000	C.25
KTB MOPL 4538 MSZN H	2022590000	C.24
KTB MOPL 4538 MSZN H	2022590000	C.25
KTB MOPL 4538 S2N	1193860000	C.24
KTB MOPL 4538 S2N	1193860000	C.25
KTB MOPL 4538 S2N H	1257700000	C.24
KTB MOPL 4538 S2N H	1257700000	C.25
KTB MOPL 4848 MSZN	1194000000	C.26
KTB MOPL 4848 MSZN	1194000000	C.27
KTB MOPL 4848 MSZN H	2022610000	C.26
KTB MOPL 4848 MSZN H	2022610000	C.27
KTB MOPL 4848 S2N	1193870000	C.26
KTB MOPL 4848 S2N	1193870000	C.27
KTB MOPL 4848 S2N	1193870000	C.47
KTB MOPL 4848 S2N H	1257710000	C.26
KTB MOPL 4848 S2N H	1257710000	C.27
KTB MOPL 5535 MSZN	1194010000	C.28
KTB MOPL 5535 MSZN	1194010000	C.29
KTB MOPL 5535 MSZN H	2022650000	C.28
KTB MOPL 5535 MSZN H	2022650000	C.29
KTB MOPL 5535 S2N	1193880000	C.28
KTB MOPL 5535 S2N	1193880000	C.29
KTB MOPL 5535 S2N H	1257720000	C.28
KTB MOPL 5535 S2N H	1257720000	C.29
KTB MOPL 6245 MSZN	1194020000	C.30
KTB MOPL 6245 MSZN	1194020000	C.31
KTB MOPL 6245 MSZN H	2022670000	C.30
KTB MOPL 6245 MSZN H	2022670000	C.31
KTB MOPL 6245 S2N	1193890000	C.30
KTB MOPL 6245 S2N	1193890000	C.31
KTB MOPL 6245 S2N H	1257740000	C.30
KTB MOPL 6245 S2N H	1257740000	C.31
KTB MOPL 7650 MSZN	1194030000	C.32
KTB MOPL 7650 MSZN	1194030000	C.33
KTB MOPL 7650 MSZN H	2022680000	C.32
KTB MOPL 7650 MSZN H	2022680000	C.33
KTB MOPL 7650 S2N	1193900000	C.32
KTB MOPL 7650 S2N	1193900000	C.33
KTB MOPL 7650 S2N H	1257750000	C.32
KTB MOPL 7650 S2N H	1257750000	C.33
KTB MOPL 9161 MSZN	1194040000	C.34
KTB MOPL 9161 MSZN	1194040000	C.35
KTB MOPL 9161 MSZN H	2022740000	C.34
KTB MOPL 9161 MSZN H	2022740000	C.35
KTB MOPL 9161 S2N	1193910000	C.34
KTB MOPL 9161 S2N	1193910000	C.35
KTB MOPL 9161 S2N H	1257760000	C.34
KTB MOPL 9161 S2N H	1257760000	C.35
KTB MOPL 9874 MSZN	1194050000	C.36
KTB MOPL 9874 MSZN H	2022760000	C.36
KTB MOPL 9874 S2N	1193920000	C.36
KTB MOPL 9874 S2N H	1257770000	C.36
KTB QL 221513 S4E0	1199850000	C.38
KTB QL 221513 S4E1	1199860000	C.38
KTB QL 221513 S4E2	1199870000	C.38
KTB QL 221513 S4E3	1199880000	C.38
KTB QL 221513 S4E4	1199890000	C.38
KTB QL 262615 S4E0	1199900000	C.38
KTB QL 262615 S4E1	1199910000	C.38
KTB QL 262615 S4E2	1199920000	C.38
KTB QL 262615 S4E3	1199930000	C.38
KTB QL 262615 S4E4	1199940000	C.38
KTB QL 262620 S4E0	1199950000	C.38
KTB QL 262620 S4E1	1199960000	C.38
KTB QL 262620 S4E2	1199970000	C.38
KTB QL 262620 S4E3	1199980000	C.38
KTB QL 262620 S4E4	1199990000	C.38
KTB QL 303015 S4E0	1200010000	C.38
KTB QL 303015 S4E1	1200020000	C.38
KTB QL 303015 S4E2	1200030000	C.38
KTB QL 303015 S4E3	1200040000	C.38
KTB QL 303015 S4E4	1200050000	C.38
KTB QL 303020 EXE	8000028400	C.42
KTB QL 303020 EXE	8000028400	C.46
KTB QL 303020 S4E0	1200060000	C.38
KTB QL 303020 S4E1	1200070000	C.38

Type	Order No.	Page
KTB QL 303020 S4E1	1200070000	C.46
KTB QL 303020 S4E2	1200080000	C.38
KTB QL 303020 S4E3	1200090000	C.38
KTB QL 303020 S4E4	1200100000	C.38
KTB QL 352615 S4E0	1200110000	C.38
KTB QL 352615 S4E1	1200120000	C.38
KTB QL 352615 S4E2	1200130000	C.38
KTB QL 352615 S4E3	1200140000	C.38
KTB QL 352615 S4E4	1200150000	C.38
KTB QL 352620 S4E0	1200160000	C.38
KTB QL 352620 S4E1	1200170000	C.38
KTB QL 352620 S4E2	1200180000	C.38
KTB QL 352620 S4E3	1200190000	C.38
KTB QL 352620 S4E4	1200210000	C.38
KTB QL 403015 S4E0	1200220000	C.38
KTB QL 403015 S4E1	1200230000	C.38
KTB QL 403015 S4E2	1200240000	C.38
KTB QL 403015 S4E3	1200250000	C.38
KTB QL 403015 S4E4	1200260000	C.38
KTB QL 403020 S4E0	1200270000	C.38
KTB QL 403020 S4E1	1200280000	C.38
KTB QL 403020 S4E2	1200290000	C.38
KTB QL 403020 S4E3	1200310000	C.38
KTB QL 403020 S4E4	1200320000	C.38
KTB QL 453815 S4E0	1200330000	C.38
KTB QL 453815 S4E1	1200340000	C.38
KTB QL 453815 S4E2	1200350000	C.38
KTB QL 453815 S4E3	1200360000	C.38
KTB QL 453815 S4E4	1200370000	C.38
KTB QL 453820 S4E0	1200380000	C.38
KTB QL 453820 S4E1	1200390000	C.38
KTB QL 453820 S4E2	1200410000	C.38
KTB QL 453820 S4E3	1200420000	C.38
KTB QL 453820 S4E4	1200430000	C.38
KTB QL 484815 S4E0	1200440000	C.38
KTB QL 484815 S4E1	1200450000	C.38
KTB QL 484815 S4E2	1200460000	C.38
KTB QL 484815 S4E3	1200470000	C.38
KTB QL 484815 S4E4	1200480000	C.38
KTB QL 484820 Exe	8000028401	C.42
KTB QL 484820 Exe	8000028401	C.47
KTB QL 484820 S4E0	1200490000	C.38
KTB QL 484820 S4E1	1200510000	C.38
KTB QL 484820 S4E1	1200510000	C.47
KTB QL 484820 S4E2	1200520000	C.38
KTB QL 484820 S4E3	1200530000	C.38
KTB QL 484820 S4E4	1200540000	C.38
KTB QL 553515 S4E0	1200550000	C.38
KTB QL 553515 S4E1	1200560000	C.38
KTB QL 553515 S4E2	1200570000	C.38
KTB QL 553515 S4E3	1200580000	C.38
KTB QL 553515 S4E4	1200590000	C.38
KTB QL 553520 S4E0	1200610000	C.38
KTB QL 553520 S4E1	1200620000	C.38
KTB QL 553520 S4E2	1200630000	C.38
KTB QL 553520 S4E3	1200640000	C.38
KTB QL 553520 S4E4	1200650000	C.38
KTB QL 624515 S4E0	1200660000	C.38
KTB QL 624515 S4E1	1200670000	C.38
KTB QL 624515 S4E2	1200680000	C.38
KTB QL 624515 S4E3	1200690000	C.38
KTB QL 624515 S4E4	1200710000	C.38
KTB QL 624520 S4E0	1200720000	C.38
KTB QL 624520 S4E1	1200730000	C.38
KTB QL 624520 S4E2	1200740000	C.38
KTB QL 624520 S4E3	1200750000	C.38
KTB QL 624520 S4E4	1200760000	C.38
KTB QL 765015 S4E0	1200770000	C.38
KTB QL 765015 S4E1	1200780000	C.38
KTB QL 765015 S4E2	1200790000	C.38
KTB QL 765015 S4E3	1200810000	C.38
KTB QL 765015 S4E4	1200820000	C.38
KTB QL 765020 S4E0	1200830000	C.38
KTB QL 765020 S4E1	1200840000	C.38
KTB QL 765020 S4E2	1200850000	C.38
KTB QL 765020 S4E3	1200860000	C.38
KTB QL 765020 S4E4	1200870000	C.38
KTB QL 916115 S4E0	1200880000	C.38
KTB QL 916115 S4E1	1200890000	C.38
KTB QL 916115 S4E2	1200910000	C.38
KTB QL 916115 S4E3	1200920000	C.38
KTB QL 916115 S4E4	1200930000	C.38
KTB QL 916120 S4E0	1200940000	C.38
KTB QL 916120 S4E1	1200950000	C.38
KTB QL 916120 S4E2	1200960000	C.38
KTB QL 916120 S4E3	1200970000	C.38
KTB QL 916120 S4E4	1200980000	C.38
KTB QL 987420 S4E0	1200990000	C.38
KTB QL 987420 S4E1	1201010000	C.38
KTB QL 987420 S4E2	1201020000	C.38
KTB QL 987420 S4E3	1201030000	C.38
KTB QL 987420 S4E4	1201040000	C.38
KTB QLL S2 SLS	1191600000	C.52
KTB QLL S2 SLS	1191600000	C.53
KTB QLL S2 SLS	1191600000	C.54
KTB QLL S2 SLS	1191600000	C.55
KTB QLL S2 SLS	1191600000	C.56
KTB QLL S2 SLS	1191600000	C.57
KTB QLL S2 SLS	1191600000	C.58

Type	Order No.	Page
KTB QLL S2 SLS	1191600000	C.59
KTB QLL S2 SLS	1191600000	C.60
KTB QLL S2 SLS	1191600000	C.61
KTB QLL S2 SLS	1191600000	C.62
KTB RNHD 221513 R	1281360000	C.15
KTB RNHD 221513 R	1281360000	C.44
KTB RNHD 221513 S4E R	1314090000	C.15
KTB RNHD 262615 R	1281370000	C.16
KTB RNHD 262615 R	1281370000	C.45
KTB RNHD 262615 S4E R	1314100000	C.16
KTB RNHD 262620 R	1281380000	C.17
KTB RNHD 262620 S4E R	1314110000	C.17
KTB RNHD 303015 R	1281390000	C.18
KTB RNHD 303015 S4E R	1314120000	C.18
KTB RNHD 303020 R	1281400000	C.19
KTB RNHD 303020 R	1281400000	C.46
KTB RNHD 303020 S4E R	1314130000	C.19
KTB RNHD 352615 R	1281410000	C.20
KTB RNHD 352615 S4E R	1314140000	C.20
KTB RNHD 352620 R	1281420000	C.21
KTB RNHD 352620 S4E R	1314150000	C.21
KTB RNHD 403015 R	1281430000	C.22
KTB RNHD 403015 S4E R	1314170000	C.22
KTB RNHD 403020 R	1281440000	C.23
KTB RNHD 403020 S4E R	1314180000	C.23
KTB RNHD 453815 R	1281450000	C.24
KTB RNHD 453815 S4E R	1314190000	C.24
KTB RNHD 453820 R	1281460000	C.25
KTB RNHD 453820 S4E R	1314200000	C.25
KTB RNHD 484815 R	1281470000	C.26
KTB RNHD 484815 S4E R	1314220000	C.26
KTB RNHD 484820 R	1281480000	C.27
KTB RNHD 484820 R	1281480000	C.47
KTB RNHD 484820 S4E R	1314230000	C.27
KTB RNHD 553515 R	1281490000	C.28
KTB RNHD 553515 S4E R	1314240000	C.28
KTB RNHD 553520 R	1281500000	C.29
KTB RNHD 553520 S4E R	1314250000	C.29
KTB RNHD 624515 R	1281510000	C.30
KTB RNHD 624515 S4E R	1314270000	C.30
KTB RNHD 624520 R	1281520000	C.31
KTB RNHD 624520 S4E R	1314280000	C.31
KTB RNHD 765015 R	1281530000	C.32
KTB RNHD 765015 S4E R	1314290000	C.32
KTB RNHD 765020 R	1281540000	C.33
KTB RNHD 765020 S4E R	1314300000	C.33
KTB RNHD 916115 R	1281550000	C.34
KTB RNHD 916115 S4E R	1314320000	C.34
KTB RNHD 916120 R	1281570000	C.35
KTB RNHD 916120 S4E R	1314330000	C.35
KTB RNHD 987420 R	1281580000	C.36
KTB RNHD 987420 S4E R	1314340000	C.36
KV 11-M	1656390000	D.10
KV 13-M	1656400000	D.10
KV 16-M	1656410000	D.10
KV 21-M	1656420000	D.10
KV 29-M	1656430000	D.10

M

MF FPC	9536040000	C.185
MF FPC	9536040000	C.186
MF FPC	9536040000	C.187
MF MPC	9535600000	C.178
MF MPC	9535600000	C.179
MF MPC	9535600000	C.180
MF MPC	9535600000	C.181
MF MPC	9535600000	C.182
MF MPC	9535600000	C.183
MF POK BIG	9510910000	C.137
MF POK BIG	9510910000	C.138
MF POK BIG	9510910000	C.139
MF POK BIG	9510910000	C.140
MF POK BIG	9510910000	C.141
MF POK BIG	9510910000	C.142
MF POK BIG	9510910000	C.143
MF POK BIG	9510910000	C.144
MF POK BIG	9510910000	C.145
MF POK BIG	9510910000	C.146
MF POK BIG	9510910000	C.147
MF POK BIG	9510910000	C.148
MF POK SMALL	9510900000	C.132
MF POK SMALL	9510900000	C.133
MF POK SMALL	9510900000	C.134
MF POK SMALL	9510900000	C.135
MF POK SMALL	9510900000	C.136
MF TBF	0360800000	C.170
MF TBF	0360800000	C.171
MF TBF	0360800000	C.172
MF TBF	0360800000	C.173
MF TBF	0360800000	C.174
MOPL K1 N FE	1905280000	C.99
MOPL K11 STAHL	3073000000	C.100
MOPL K2 N FE	1905270000	C.101
MOPL K21 STAHL	3073020000	C.102
MOPL K3 BKVARIO SET	8000004497	C.116
MOPL K3 N FE	1898210000	C.103
MOPL K31 STAHL	3073040000	C.104
MOPL K32 STAHL	3073050000	C.105

Type	Order No.	Page
MOPL K4 STAHL	3073060000	C.106
MOPL K41 STAHL	3073070000	C.107
MOPL K5 STAHL	3073080000	C.108
MOPL K51 STAHL	3073090000	C.109
MOPL K52 STAHL	3073100000	C.110
MOPL K6 STAHL	3073110000	C.111
MOPL K61 STAHL	3073120000	C.112
MOPL K7 STAHL	3073130000	C.113
MOPL K71 STAHL	3073140000	C.114
MOPL SET BK12 S	8000004135	C.116
MOPL SET BK4 S	8000004129	C.116
MOPL SET BK6 S	8000004132	C.116
MP FPC 20/20	9535920000	C.185
MP FPC 20/30	9535930000	C.185
MP FPC 20/40	9535940000	C.186
MP FPC 30/30	9535950000	C.186
MP FPC 30/40	9535960000	C.187
MP FPC 40/60	9535980000	C.187
MP MPC 07/12	9535540000	C.178
MP MPC 12/12	9535550000	C.179
MP MPC 12/17	9535560000	C.179
MP MPC 12/17	9535560000	C.180
MP MPC 17/17	9535570000	C.181
MP MPC 17/17	9535570000	C.182
MP MPC 17/25	9535580000	C.182
MP MPC 17/25	9535580000	C.183
MP TBF 19/15	9502720000	C.170
MP TBF 30/19	3018950000	C.170
MP TBF 30/30	9502730000	C.171
MP TBF 37/30	9502740000	C.171
MP TBF 49/30	9500960000	C.172
MP TBF 56/30	9500950000	C.172
MP TBF 60/30	9502750000	C.173
MP TBF 60/37	9502910000	C.174
MP TBF 60/60	9502920000	C.174
MPC 07/12/07 7035	9535170000	C.176
MPC 07/12/07 7035	9535170000	C.178
MPC 07/12/07 TRSP	9535180000	C.176
MPC 07/12/07 TRSP	9535180000	C.178
MPC 07/12/10 7035	9535190000	C.176
MPC 07/12/10 TRSP	9535200000	C.176
MPC 07/12/12 7035	9535210000	C.176
MPC 07/12/12 7035	9535210000	C.178
MPC 07/12/12 TRSP	9535220000	C.176
MPC 07/12/12 TRSP	9535220000	C.178
MPC 12/12/07 7035	9535230000	C.176
MPC 12/12/07 7035	9535230000	C.179
MPC 12/12/07 TRSP	9535240000	C.176
MPC 12/12/07 TRSP	9535240000	C.179
MPC 12/12/10 7035	9535250000	C.176
MPC 12/12/10 TRSP	9535260000	C.176
MPC 12/12/12 7035	9535270000	C.176
MPC 12/12/12 TRSP	9535280000	C.176
MPC 12/17/07 7035	9535290000	C.176
MPC 12/17/07 7035	9535290000	C.179
MPC 12/17/07 TRSP	9535300000	C.176
MPC 12/17/07 TRSP	9535300000	C.179
MPC 12/17/10 7035	9535310000	C.176
MPC 12/17/10 7035	9535310000	C.180
MPC 12/17/10 TRSP	9535320000	C.176
MPC 12/17/10 TRSP	9535320000	C.180
MPC 12/17/12 7035	9535330000	C.176
MPC 12/17/12 7035	9535330000	C.180
MPC 12/17/12 TRSP	9535340000	C.176
MPC 12/17/12 TRSP	9535340000	C.180
MPC 12/17/15 7035	9535350000	C.176
MPC 12/17/15 TRSP	9535360000	C.176
MPC 17/17/07 7035	9535370000	C.176
MPC 17/17/07 7035	9535370000	C.181
MPC 17/17/07 TRSP	9535380000	C.176
MPC 17/17/07 TRSP	9535380000	C.181
MPC 17/17/10 7035	9535390000	C.176
MPC 17/17/10 TRSP	9535400000	C.176
MPC 17/17/12 7035	9535410000	C.176
MPC 17/17/15 7035	9535430000	C.176
MPC 17/17/15 7035	9535430000	C.182
MPC 17/17/15 TRSP	9535440000	C.176
MPC 17/17/15 TRSP	9535440000	C.182
MPC 17/25/07 7035	9535450000	C.176
MPC 17/25/07 7035	9535450000	C.182
MPC 17/25/10 7035	9535470000	C.176
MPC 17/25/10 7035	9535470000	C.183
MPC 17/25/10 TRSP	9535480000	C.176
MPC 17/25/10 TRSP	9535480000	C.183
MPC 17/25/15 7035	9535490000	C.176
MPC 17/25/15 7035	9535490000	C.183
MPC 17/25/15 TRSP	9535500000	C.176
MPC 17/25/15 TRSP	9535500000	C.183

P

PEBZ M10 BR SET	1277220000	C.106
PEBZ M10 BR SET	1277220000	C.107
PEBZ M10 BR SET	1277220000	C.108
PEBZ M10 BR SET	1277220000	C.109
PEBZ M10 BR SET	1277220000	C.110
PEBZ M10 BR SET	1277220000	C.111
PEBZ M10 BR SET	1277220000	C.112
PEBZ M10 BR SET	1277220000	C.113

Type	Order No.	Page
PEBZ M10 BR SET	1277220000	C.114
PEBZ M10 BR SET	1277220000	C.132
PEBZ M10 BR SET	1277220000	C.133
PEBZ M10 BR SET	1277220000	C.134
PEBZ M10 BR SET	1277220000	C.135
PEBZ M10 BR SET	1277220000	C.136
PEBZ M10 BR SET	1277220000	C.137
PEBZ M10 BR SET	1277220000	C.138
PEBZ M10 BR SET	1277220000	C.139
PEBZ M10 BR SET	1277220000	C.140
PEBZ M10 BR SET	1277220000	C.141
PEBZ M10 BR SET	1277220000	C.142
PEBZ M10 BR SET	1277220000	C.143
PEBZ M10 BR SET	1277220000	C.144
PEBZ M10 BR SET	1277220000	C.145
PEBZ M10 BR SET	1277220000	C.146
PEBZ M10 BR SET	1277220000	C.147
PEBZ M10 BR SET	1277220000	C.148
PEBZ M10 BR SET	1277220000	C.170
PEBZ M10 BR SET	1277220000	C.171
PEBZ M10 BR SET	1277220000	C.172
PEBZ M10 BR SET	1277220000	C.173
PEBZ M10 BR SET	1277220000	C.174
PEBZ M10 BR SET	1277220000	C.178
PEBZ M10 BR SET	1277220000	C.179
PEBZ M10 BR SET	1277220000	C.180
PEBZ M10 BR SET	1277220000	C.181
PEBZ M10 BR SET	1277220000	C.182
PEBZ M10 BR SET	1277220000	C.183
PEBZ M10 BR SET	1277220000	C.185
PEBZ M10 BR SET	1277220000	C.186
PEBZ M10 BR SET	1277220000	C.187
PEBZ M10 KTB S4 SET	1192690000	C.15
PEBZ M10 KTB S4 SET	1192690000	C.16
PEBZ M10 KTB S4 SET	1192690000	C.17
PEBZ M10 KTB S4 SET	1192690000	C.18
PEBZ M10 KTB S4 SET	1192690000	C.19
PEBZ M10 KTB S4 SET	1192690000	C.20
PEBZ M10 KTB S4 SET	1192690000	C.21
PEBZ M10 KTB S4 SET	1192690000	C.22
PEBZ M10 KTB S4 SET	1192690000	C.23
PEBZ M10 KTB S4 SET	1192690000	C.24
PEBZ M10 KTB S4 SET	1192690000	C.25
PEBZ M10 KTB S4 SET	1192690000	C.26
PEBZ M10 KTB S4 SET	1192690000	C.27
PEBZ M10 KTB S4 SET	1192690000	C.28
PEBZ M10 KTB S4 SET	1192690000	C.29
PEBZ M10 KTB S4 SET	1192690000	C.30
PEBZ M10 KTB S4 SET	1192690000	C.31
PEBZ M10 KTB S4 SET	1192690000	C.32
PEBZ M10 KTB S4 SET	1192690000	C.33
PEBZ M10 KTB S4 SET	1192690000	C.34
PEBZ M10 KTB S4 SET	1192690000	C.35
PEBZ M10 KTB S4 SET	1192690000	C.36
PEBZ M10 KTB S4 SET	1192690000	C.44
PEBZ M10 KTB S4 SET	1192690000	C.45
PEBZ M10 KTB S4 SET	1192690000	C.46
PEBZ M10 KTB S4 SET	1192690000	C.47
PEBZ M10 S4 SET	1283440000	C.106
PEBZ M10 S4 SET	1283440000	C.107
PEBZ M10 S4 SET	1283440000	C.108
PEBZ M10 S4 SET	1283440000	C.109
PEBZ M10 S4 SET	1283440000	C.110
PEBZ M10 S4 SET	1283440000	C.111
PEBZ M10 S4 SET	1283440000	C.112
PEBZ M10 S4 SET	1283440000	C.113
PEBZ M10 S4 SET	1283440000	C.114
PEBZ M10 S4 SET	1283440000	C.132
PEBZ M10 S4 SET	1283440000	C.133
PEBZ M10 S4 SET	1283440000	C.134
PEBZ M10 S4 SET	1283440000	C.135
PEBZ M10 S4 SET	1283440000	C.136
PEBZ M10 S4 SET	1283440000	C.137
PEBZ M10 S4 SET	1283440000	C.138
PEBZ M10 S4 SET	1283440000	C.139
PEBZ M10 S4 SET	1283440000	C.140
PEBZ M10 S4 SET	1283440000	C.141
PEBZ M10 S4 SET	1283440000	C.142
PEBZ M10 S4 SET	1283440000	C.143
PEBZ M10 S4 SET	1283440000	C.144
PEBZ M10 S4 SET	1283440000	C.145
PEBZ M10 S4 SET	1283440000	C.146
PEBZ M10 S4 SET	1283440000	C.147
PEBZ M10 S4 SET	1283440000	C.148
PEBZ M10 S4 SET	1283440000	C.170
PEBZ M10 S4 SET	1283440000	C.171
PEBZ M10 S4 SET	1283440000	C.172
PEBZ M10 S4 SET	1283440000	C.173
PEBZ M10 S4 SET	1283440000	C.174
PEBZ M10 S4 SET	1283440000	C.178
PEBZ M10 S4 SET	1283440000	C.179
PEBZ M10 S4 SET	1283440000	C.180
PEBZ M10 S4 SET	1283440000	C.181
PEBZ M10 S4 SET	1283440000	C.182
PEBZ M10 S4 SET	1283440000	C.183
PEBZ M10 S4 SET	1283440000	C.185
PEBZ M10 S4 SET	1283440000	C.186
PEBZ M10 S4 SET	1283440000	C.187
PEBZ M6 BR SET	1277250000	C.99

Type	Order No.	Page
PEBZ M6 BR SET	1277250000	C.100
PEBZ M6 BR SET	1277250000	C.101
PEBZ M6 BR SET	1277250000	C.102
PEBZ M6 BR SET	1277250000	C.103
PEBZ M6 BR SET	1277250000	C.104
PEBZ M6 BR SET	1277250000	C.105
PEBZ M6 BR SET	1277250000	C.106
PEBZ M6 BR SET	1277250000	C.107
PEBZ M6 BR SET	1277250000	C.108
PEBZ M6 BR SET	1277250000	C.109
PEBZ M6 BR SET	1277250000	C.110
PEBZ M6 BR SET	1277250000	C.111
PEBZ M6 BR SET	1277250000	C.112
PEBZ M6 BR SET	1277250000	C.113
PEBZ M6 BR SET	1277250000	C.114
PEBZ M6 BR SET	1277250000	C.132
PEBZ M6 BR SET	1277250000	C.133
PEBZ M6 BR SET	1277250000	C.134
PEBZ M6 BR SET	1277250000	C.135
PEBZ M6 BR SET	1277250000	C.136
PEBZ M6 BR SET	1277250000	C.137
PEBZ M6 BR SET	1277250000	C.138
PEBZ M6 BR SET	1277250000	C.139
PEBZ M6 BR SET	1277250000	C.140
PEBZ M6 BR SET	1277250000	C.141
PEBZ M6 BR SET	1277250000	C.142
PEBZ M6 BR SET	1277250000	C.143
PEBZ M6 BR SET	1277250000	C.144
PEBZ M6 BR SET	1277250000	C.145
PEBZ M6 BR SET	1277250000	C.146
PEBZ M6 BR SET	1277250000	C.147
PEBZ M6 BR SET	1277250000	C.148
PEBZ M6 BR SET	1277250000	C.170
PEBZ M6 BR SET	1277250000	C.171
PEBZ M6 BR SET	1277250000	C.172
PEBZ M6 BR SET	1277250000	C.173
PEBZ M6 BR SET	1277250000	C.174
PEBZ M6 BR SET	1277250000	C.178
PEBZ M6 BR SET	1277250000	C.179
PEBZ M6 BR SET	1277250000	C.180
PEBZ M6 BR SET	1277250000	C.181
PEBZ M6 BR SET	1277250000	C.182
PEBZ M6 BR SET	1277250000	C.183
PEBZ M6 BR SET	1277250000	C.185
PEBZ M6 BR SET	1277250000	C.186
PEBZ M6 BR SET	1277250000	C.187
PEBZ M6 S4 SET	1283430000	C.99
PEBZ M6 S4 SET	1283430000	C.100
PEBZ M6 S4 SET	1283430000	C.101
PEBZ M6 S4 SET	1283430000	C.102
PEBZ M6 S4 SET	1283430000	C.103
PEBZ M6 S4 SET	1283430000	C.104
PEBZ M6 S4 SET	1283430000	C.105
PEBZ M6 S4 SET	1283430000	C.106
PEBZ M6 S4 SET	1283430000	C.107
PEBZ M6 S4 SET	1283430000	C.108
PEBZ M6 S4 SET	1283430000	C.109
PEBZ M6 S4 SET	1283430000	C.110
PEBZ M6 S4 SET	1283430000	C.111
PEBZ M6 S4 SET	1283430000	C.112
PEBZ M6 S4 SET	1283430000	C.113
PEBZ M6 S4 SET	1283430000	C.114
PEBZ M6 S4 SET	1283430000	C.132
PEBZ M6 S4 SET	1283430000	C.133
PEBZ M6 S4 SET	1283430000	C.134
PEBZ M6 S4 SET	1283430000	C.135
PEBZ M6 S4 SET	1283430000	C.136
PEBZ M6 S4 SET	1283430000	C.137
PEBZ M6 S4 SET	1283430000	C.138
PEBZ M6 S4 SET	1283430000	C.139
PEBZ M6 S4 SET	1283430000	C.140
PEBZ M6 S4 SET	1283430000	C.141
PEBZ M6 S4 SET	1283430000	C.142
PEBZ M6 S4 SET	1283430000	C.143
PEBZ M6 S4 SET	1283430000	C.144
PEBZ M6 S4 SET	1283430000	C.145
PEBZ M6 S4 SET	1283430000	C.146
PEBZ M6 S4 SET	1283430000	C.147
PEBZ M6 S4 SET	1283430000	C.148
PEBZ M6 S4 SET	1283430000	C.170
PEBZ M6 S4 SET	1283430000	C.171
PEBZ M6 S4 SET	1283430000	C.172
PEBZ M6 S4 SET	1283430000	C.173
PEBZ M6 S4 SET	1283430000	C.174
PEBZ M6 S4 SET	1283430000	C.178
PEBZ M6 S4 SET	1283430000	C.179
PEBZ M6 S4 SET	1283430000	C.180
PEBZ M6 S4 SET	1283430000	C.181
PEBZ M6 S4 SET	1283430000	C.182
PEBZ M6 S4 SET	1283430000	C.183
PEBZ M6 S4 SET	1283430000	C.185
PEBZ M6 S4 SET	1283430000	C.186
PEBZ M6 S4 SET	1283430000	C.187
PECD WIRE 6/200/D6 SET	2475490000	C.44
PECD WIRE 6/200/D6 SET	2475490000	C.45
PECD WIRE 6/200/D6 SET	2475490000	C.46
PECD WIRE 6/200/D6 SET	2475490000	C.47
PECD WIRE 6/200/D6 SET	2475490000	C.78
PECD WIRE 6/200/D6 SET	2475490000	C.79
PECD WIRE 6/200/D6 SET	2475490000	C.80
PECD WIRE 6/200/D6 SET	2475490000	C.81
POK MOPL 0808	9510570000	C.132
POK MOPL 0808 MINI	1534280000	C.132
POK MOPL 0811	9510580000	C.133
POK MOPL 0811 MINI	1534290000	C.133
POK MOPL 0816	9510680000	C.134
POK MOPL 0816 MINI	1534310000	C.134
POK MOPL 0819	9510690000	C.135
POK MOPL 0819 MINI	1534320000	C.135
POK MOPL 0823 MINI	1534330000	C.136
POK MOPL 1212	9510590000	C.137
POK MOPL 1212 MINI	1534340000	C.137
POK MOPL 1222	9510600000	C.138
POK MOPL 1222 MINI	1534350000	C.138
POK MOPL 1616	9510610000	C.139
POK MOPL 1616 MINI	1534360000	C.139
POK MOPL 1626	9510620000	C.140
POK MOPL 1626 MINI	1534370000	C.140
POK MOPL 1636	9510630000	C.141
POK MOPL 1636 MINI	1534380000	C.141
POK MOPL 1656	9510710000	C.142
POK MOPL 1656 MINI	1534390000	C.142
POK MOPL 2525	9510640000	C.143
POK MOPL 2525	9510640000	C.144
POK MOPL 2525 MINI	1534410000	C.143
POK MOPL 2525 MINI	1534410000	C.144
POK MOPL 2540	9510650000	C.145
POK MOPL 2540	9510650000	C.146
POK MOPL 2540 MINI	1534420000	C.145
POK MOPL 2540 MINI	1534420000	C.146
POK MOPL 2560	9510660000	C.147
POK MOPL 2560 MINI	1534430000	C.147
POK MOPL 4040	9510670000	C.148
POK MOPL 4040 MINI	1534440000	C.148
S		
SD FIXING SET	1285200000	C.15
SD FIXING SET	1285200000	C.16
SD FIXING SET	1285200000	C.17
SD FIXING SET	1285200000	C.18
SD FIXING SET	1285200000	C.19
SD FIXING SET	1285200000	C.20
SD FIXING SET	1285200000	C.21
SD FIXING SET	1285200000	C.22
SD FIXING SET	1285200000	C.23
SD FIXING SET	1285200000	C.24
SD FIXING SET	1285200000	C.25
SD FIXING SET	1285200000	C.26
SD FIXING SET	1285200000	C.27
SD FIXING SET	1285200000	C.28
SD FIXING SET	1285200000	C.29
SD FIXING SET	1285200000	C.30
SD FIXING SET	1285200000	C.31
SD FIXING SET	1285200000	C.32
SD FIXING SET	1285200000	C.33
SD FIXING SET	1285200000	C.34
SD FIXING SET	1285200000	C.35
SD FIXING SET	1285200000	C.36
SD TH20	9009160000	C.96
SD TH20	9009160000	C.97
SD TH20	9009160000	C.98
SD TH20	9009160000	C.99
SD TH20	9009160000	C.100
SD TH20	9009160000	C.101
SD TH20	9009160000	C.102
SD TH20	9009160000	C.103
SD TH20	9009160000	C.104
SD TH20	9009160000	C.105
SD TH20	9009160000	C.106
SD TH20	9009160000	C.107
SD TH20	9009160000	C.108
SD TH20	9009160000	C.109
SD TH20	9009160000	C.110
SD TH20	9009160000	C.111
SD TH20	9009160000	C.112
SD TH20	9009160000	C.113
SD TH20	9009160000	C.114
SFNS5 VKMU M5 SW15	0433500000	C.68
SFNS5 VKMU M5 SW15	0433500000	C.69
SFNS5 VKMU M5 SW15	0433500000	C.70
SFNS5 VKMU M5 SW15	0433500000	C.71
SFNS5 VKMU M5 SW15	0433500000	C.72
SFNS5 VKMU M5 SW15	0433500000	C.73
SFNS5 VKMU M5 SW15	0433500000	C.74
SFNS5 VKMU M5 SW15	0433500000	C.75
SKMU EMV M12	1777610000	D.44
SKMU EMV M16	1777620000	D.44
SKMU EMV M20	1777630000	D.44
SKMU EMV M25	1777640000	D.44
SKMU EMV M32	1777650000	D.44
SKMU EMV M40	1777660000	D.44
SKMU EMV M50	1777670000	D.44
SKMU EMV M63	1777680000	D.44
SKMU EMV PG 36	1777710000	D.44
SKMU EMV PG 42	1777700000	D.44
SKMU EMV PG 48	1777690000	D.44
SKMU EMV PG11	1718920000	D.44
SKMU EMV PG13,5	1718930000	D.44
SKMU EMV PG16	1718940000	D.44
SKMU EMV PG21	1718950000	D.44
SKMU EMV PG29	1718960000	D.44
SKMU EMV PG7	1718900000	D.44
SKMU EMV PG9	1718910000	D.44
SKMU M12 - K GR	1772440000	D.40
SKMU M12 K SW	1806540000	D.41
SKMU M12 MS	1772360000	D.42
SKMU M16 - K GR	1772450000	D.40
SKMU M16 K SW	1736920000	D.41
SKMU M16 MS	1736990000	C.44
SKMU M16 MS	1736990000	C.78
SKMU M16 MS	1736990000	D.42
SKMU M16 MS SC	0930640001	D.43
SKMU M20 - K GR	1772460000	D.40
SKMU M20 K SW	1736930000	C.79
SKMU M20 K SW	1736930000	C.80
SKMU M20 K SW	1736930000	D.41
SKMU M20 MS	1737000000	C.44
SKMU M20 MS	1737000000	C.45
SKMU M20 MS	1737000000	C.46
SKMU M20 MS	1737000000	C.47
SKMU M20 MS	1737000000	C.79
SKMU M20 MS	1737000000	C.80
SKMU M20 MS	1737000000	D.42
SKMU M20 MS SC	0930640002	D.43
SKMU M25 - K GR	1772470000	D.40
SKMU M25 K SW	1736940000	C.81
SKMU M25 K SW	1736940000	D.41
SKMU M25 MS	1737010000	C.47
SKMU M25 MS	1737010000	C.81
SKMU M25 MS	1737010000	D.42
SKMU M25 MS SC	0930640003	D.43
SKMU M32 - K GR	1772480000	D.40
SKMU M32 K SW	1736950000	D.41
SKMU M32 MS	1737020000	C.45
SKMU M32 MS	1737020000	C.46
SKMU M32 MS	1737020000	D.42
SKMU M32 MS SC	0930640004	D.43
SKMU M40 - K GR	1772490000	D.40
SKMU M40 K SW	1736960000	D.41
SKMU M40 MS	1737030000	C.47
SKMU M40 MS	1737030000	D.42
SKMU M40 MS SC	0930640005	D.43
SKMU M50 - K GR	1772500000	D.40
SKMU M50 K SW	1736970000	D.41
SKMU M50 MS	1737040000	D.42
SKMU M50 MS SC	0930640006	D.43
SKMU M63 - K GR	1772510000	D.40
SKMU M63 K SW	1736980000	D.41
SKMU M63 MS	1737050000	D.42
SKMU M63 MS SC	0930640007	D.43
SKMU M75 MS	1737060000	D.42
SKMU M75 MS SC	0930640008	D.43
SKMU PG 13,5-K GR	1697470000	D.40
SKMU PG11-K GR	1697460000	D.40
SKMU PG11-K SW	1719120000	D.41
SKMU PG11-MS	1694090000	D.42
SKMU PG13,5-K SW	1719130000	D.41
SKMU PG13,5-MS	1694100000	D.42
SKMU PG16-K GR	1697480000	D.40
SKMU PG16-K SW	1719140000	D.41
SKMU PG16-MS	1694110000	D.42
SKMU PG21-K GR	1698220000	D.40
SKMU PG21-K SW	1719150000	D.41
SKMU PG21-MS	1719200000	D.42
SKMU PG29-K GR	1698230000	D.40
SKMU PG29-K SW	1719160000	D.41
SKMU PG29-MS	1719210000	D.42
SKMU PG36-K GR	1698240000	D.40
SKMU PG36-K SW	1719170000	D.41
SKMU PG36-MS	1719220000	D.42
SKMU PG42-K GR	1698250000	D.40
SKMU PG42-K SW	1719180000	D.41
SKMU PG42-MS	1719230000	D.42
SKMU PG48-K GR	1719090000	D.40
SKMU PG48-K SW	1719190000	D.41
SKMU PG48-MS	1719240000	D.42
SKMU PG7-K GR	1697440000	D.40
SKMU PG7-K SW	1719100000	D.41
SKMU PG7-MS	1694070000	D.42
SKMU PG9-K GR	1697450000	D.40
SKMU PG9-K SW	1719110000	D.41
SKMU PG9-MS	1694080000	D.42
SP M6 10 S2	0935110000	C.15
SP M6 10 S2	0935110000	C.16
SP M6 10 S2	0935110000	C.17
SP M6 10 S2	0935110000	C.18
SP M6 10 S2	0935110000	C.19
SP M6 10 S2	0935110000	C.20
SP M6 10 S2	0935110000	C.21
SP M6 10 S2	0935110000	C.22
SP M6 10 S2	0935110000	C.23
SP M6 10 S2	0935110000	C.24
SP M6 10 S2	0935110000	C.25
SP M6 10 S2	0935110000	C.26
SP M6 10 S2	0935110000	C.27
SP M6 10 S2	0935110000	C.28
SP M6 10 S2	0935110000	C.29
SP M6 10 S2	0935110000	C.30
SP M6 10 S2	0935110000	C.31
SP M6 10 S2	0935110000	C.32
SP M6 10 S2	0935110000	C.33
SP M6 10 S2	0935110000	C.34
SP M6 10 S2	0935110000	C.35
SP M6 10 S2	0935110000	C.36
SP M6 10 S2	0935110000	C.52
SP M6 10 S2	0935110000	C.53
SP M6 10 S2	0935110000	C.54
SP M6 10 S2	0935110000	C.55
SP M6 10 S2	0935110000	C.56
SP M6 10 S2	0935110000	C.57
SP M6 10 S2	0935110000	C.58
SP M6 10 S2	0935110000	C.59
SP M6 10 S2	0935110000	C.60
SP M6 10 S2	0935110000	C.61
SP M6 10 S2	0935110000	C.62
SP M6 15 MSZN	3896100000	C.52
SP M6 15 MSZN	3896100000	C.53
SP M6 15 MSZN	3896100000	C.54
SP M6 15 MSZN	3896100000	C.55
SP M6 15 MSZN	3896100000	C.56
SP M6 15 MSZN	3896100000	C.57
SP M6 15 MSZN	3896100000	C.58
SP M6 15 MSZN	3896100000	C.59
SP M6 15 MSZN	3896100000	C.60
SP M6 15 MSZN	3896100000	C.61
SP M6 15 MSZN	3896100000	C.62
SP M6 15 S2	0935120000	C.15
SP M6 15 S2	0935120000	C.16
SP M6 15 S2	0935120000	C.17
SP M6 15 S2	0935120000	C.18
SP M6 15 S2	0935120000	C.19
SP M6 15 S2	0935120000	C.20
SP M6 15 S2	0935120000	C.21
SP M6 15 S2	0935120000	C.22
SP M6 15 S2	0935120000	C.23
SP M6 15 S2	0935120000	C.24
SP M6 15 S2	0935120000	C.25
SP M6 15 S2	0935120000	C.26
SP M6 15 S2	0935120000	C.27
SP M6 15 S2	0935120000	C.28
SP M6 15 S2	0935120000	C.29
SP M6 15 S2	0935120000	C.30
SP M6 15 S2	0935120000	C.31
SP M6 15 S2	0935120000	C.32
SP M6 15 S2	0935120000	C.33
SP M6 15 S2	0935120000	C.34
SP M6 15 S2	0935120000	C.35
SP M6 15 S2	0935120000	C.36
SP M6 15 S2	0935120000	C.52
SP M6 15 S2	0935120000	C.53
SP M6 15 S2	0935120000	C.54
SP M6 15 S2	0935120000	C.55
SP M6 15 S2	0935120000	C.56
SP M6 15 S2	0935120000	C.57
SP M6 15 S2	0935120000	C.58
SP M6 15 S2	0935120000	C.59
SP M6 15 S2	0935120000	C.60
SP M6 15 S2	0935120000	C.61
SP M6 15 S2	0935120000	C.62
SP M6 20 MSZN	3896200000	C.52
SP M6 20 MSZN	3896200000	C.53
SP M6 20 MSZN	3896200000	C.54
SP M6 20 MSZN	3896200000	C.55
SP M6 20 MSZN	3896200000	C.56
SP M6 20 MSZN	3896200000	C.57
SP M6 20 MSZN	3896200000	C.58
SP M6 20 MSZN	3896200000	C.59
SP M6 20 MSZN	3896200000	C.60
SP M6 20 MSZN	3896200000	C.61
SP M6 20 MSZN	3896200000	C.62
SP M6 20 S2	0935130000	C.15
SP M6 20 S2	0935130000	C.16
SP M6 20 S2	0935130000	C.17
SP M6 20 S2	0935130000	C.18
SP M6 20 S2	0935130000	C.19
SP M6 20 S2	0935130000	C.20
SP M6 20 S2	0935130000	C.21
SP M6 20 S2	0935130000	C.22
SP M6 20 S2	0935130000	C.23
SP M6 20 S2	0935130000	C.24
SP M6 20 S2	0935130000	C.25
SP M6 20 S2	0935130000	C.26
SP M6 20 S2	0935130000	C.27
SP M6 20 S2	0935130000	C.28
SP M6 20 S2	0935130000	C.29
SP M6 20 S2	0935130000	C.30
SP M6 20 S2	0935130000	C.31
SP M6 20 S2	0935130000	C.32
SP M6 20 S2	0935130000	C.33
SP M6 20 S2	0935130000	C.34
SP M6 20 S2	0935130000	C.35
SP M6 20 S2	0935130000	C.36
SP M6 20 S2	0935130000	C.52
SP M6 20 S2	0935130000	C.53
SP M6 20 S2	0935130000	C.54

Type	Order No.	Page
SP M6 20 S2	0935130000	C.55
SP M6 20 S2	0935130000	C.56
SP M6 20 S2	0935130000	C.57
SP M6 20 S2	0935130000	C.58
SP M6 20 S2	0935130000	C.59
SP M6 20 S2	0935130000	C.60
SP M6 20 S2	0935130000	C.61
SP M6 20 S2	0935130000	C.62
SP M6 30 MSZN	3896300000	C.52
SP M6 30 MSZN	3896300000	C.53
SP M6 30 MSZN	3896300000	C.54
SP M6 30 MSZN	3896300000	C.55
SP M6 30 MSZN	3896300000	C.56
SP M6 30 MSZN	3896300000	C.57
SP M6 30 MSZN	3896300000	C.58
SP M6 30 MSZN	3896300000	C.59
SP M6 30 MSZN	3896300000	C.60
SP M6 30 MSZN	3896300000	C.61
SP M6 30 MSZN	3896300000	C.62
SP M6 30 S2	0935140000	C.15
SP M6 30 S2	0935140000	C.16
SP M6 30 S2	0935140000	C.17
SP M6 30 S2	0935140000	C.18
SP M6 30 S2	0935140000	C.19
SP M6 30 S2	0935140000	C.20
SP M6 30 S2	0935140000	C.21
SP M6 30 S2	0935140000	C.22
SP M6 30 S2	0935140000	C.23
SP M6 30 S2	0935140000	C.24
SP M6 30 S2	0935140000	C.25
SP M6 30 S2	0935140000	C.26
SP M6 30 S2	0935140000	C.27
SP M6 30 S2	0935140000	C.28
SP M6 30 S2	0935140000	C.29
SP M6 30 S2	0935140000	C.30
SP M6 30 S2	0935140000	C.31
SP M6 30 S2	0935140000	C.32
SP M6 30 S2	0935140000	C.33
SP M6 30 S2	0935140000	C.34
SP M6 30 S2	0935140000	C.35
SP M6 30 S2	0935140000	C.36
SP M6 30 S2	0935140000	C.52
SP M6 30 S2	0935140000	C.53
SP M6 30 S2	0935140000	C.54
SP M6 30 S2	0935140000	C.55
SP M6 30 S2	0935140000	C.56
SP M6 30 S2	0935140000	C.57
SP M6 30 S2	0935140000	C.58
SP M6 30 S2	0935140000	C.59
SP M6 30 S2	0935140000	C.60
SP M6 30 S2	0935140000	C.61
SP M6 30 S2	0935140000	C.62
STB 1 EXIA	8000028394	C.76
STB 1 EXIA	8000028394	C.78
STB 2 Exe	8000028395	C.76
STB 2 Exe	8000028395	C.79
STB 3 Exe	8000028396	C.76
STB 3 Exe	8000028396	C.80
STB 4 Exe	8000028397	C.76
STB 4 Exe	8000028397	C.81
SZS M16	1736300000	D.52
SZS M20	1736310000	D.52
SZS M25	1736320000	D.52
SZS M32	1736330000	D.52
SZS M40	1736340000	D.52
SZS M50	1736350000	D.52
SZS M63	1736360000	D.52

T

TBF 19/15/14 7035	0360100000	C.168
TBF 19/15/14 7035	0360100000	C.170
TBF 19/15/14 TRSP	0500500000	C.168
TBF 19/15/14 TRSP	0500500000	C.170
TBF 30/19/18 7035	0360200000	C.168
TBF 30/19/18 7035	0360200000	C.170
TBF 30/19/18 TRSP	0500600000	C.168
TBF 30/19/18 TRSP	0500600000	C.170
TBF 30/30/18 7035	0360300000	C.168
TBF 30/30/18 7035	0360300000	C.171
TBF 30/30/18 TRSP	0500700000	C.168
TBF 30/30/18 TRSP	0500700000	C.171
TBF 37/30/18 7035	0360400000	C.168
TBF 37/30/18 7035	0360400000	C.171
TBF 37/30/18 TRSP	0500800000	C.168
TBF 37/30/18 TRSP	0500800000	C.171
TBF 49/30/18 7035	9502800000	C.168
TBF 49/30/18 7035	9502800000	C.172
TBF 49/30/21 TRSP	9502840000	C.168
TBF 49/30/21 TRSP	9502840000	C.172
TBF 56/30/18 7035	9502810000	C.168
TBF 56/30/18 7035	9502810000	C.172
TBF 56/30/21 TRSP	9502850000	C.168
TBF 56/30/21 TRSP	9502850000	C.172
TBF 60/30/18 7035	0360500000	C.168
TBF 60/30/18 7035	0360500000	C.173
TBF 60/30/21 TRSP	0500900000	C.168
TBF 60/30/21 TRSP	0500900000	C.173
TBF 60/37/18 7035	9502820000	C.168
TBF 60/37/18 7035	9502820000	C.174
TBF 60/37/21 TRSP	9502860000	C.168
TBF 60/37/21 TRSP	9502860000	C.174
TBF 60/60/18 7035	9502830000	C.168
TBF 60/60/18 7035	9502830000	C.174
TBF 60/60/21 TRSP	9502870000	C.168
TBF 60/60/21 TRSP	9502870000	C.174
TPSD FIXING SET KTB	1252190000	C.15
TPSD FIXING SET KTB	1252190000	C.16
TPSD FIXING SET KTB	1252190000	C.17
TPSD FIXING SET KTB	1252190000	C.18
TPSD FIXING SET KTB	1252190000	C.19
TPSD FIXING SET KTB	1252190000	C.20
TPSD FIXING SET KTB	1252190000	C.21
TPSD FIXING SET KTB	1252190000	C.22
TPSD FIXING SET KTB	1252190000	C.23
TPSD FIXING SET KTB	1252190000	C.24
TPSD FIXING SET KTB	1252190000	C.25
TPSD FIXING SET KTB	1252190000	C.26
TPSD FIXING SET KTB	1252190000	C.27
TPSD FIXING SET KTB	1252190000	C.28
TPSD FIXING SET KTB	1252190000	C.29
TPSD FIXING SET KTB	1252190000	C.30
TPSD FIXING SET KTB	1252190000	C.31
TPSD FIXING SET KTB	1252190000	C.32
TPSD FIXING SET KTB	1252190000	C.33
TPSD FIXING SET KTB	1252190000	C.34
TPSD FIXING SET KTB	1252190000	C.35
TPSD FIXING SET KTB	1252190000	C.36
TPSDHA KTB 100X25 S2 2R	1257640000	C.16
TPSDHA KTB 100X25 S2 2R	1257640000	C.17
TPSDHA KTB 100X25 S2 2R	1257640000	C.18
TPSDHA KTB 100X25 S2 2R	1257640000	C.19
TPSDHA KTB 100X25 S2 2R	1257640000	C.20
TPSDHA KTB 100X25 S2 2R	1257640000	C.21
TPSDHA KTB 100X25 S2 2R	1257640000	C.22
TPSDHA KTB 100X25 S2 2R	1257640000	C.23
TPSDHA KTB 100X25 S2 2R	1257640000	C.24
TPSDHA KTB 100X25 S2 2R	1257640000	C.25
TPSDHA KTB 100X25 S2 2R	1257640000	C.26
TPSDHA KTB 100X25 S2 2R	1257640000	C.27
TPSDHA KTB 100X25 S2 2R	1257640000	C.28
TPSDHA KTB 100X25 S2 2R	1257640000	C.29
TPSDHA KTB 100X25 S2 2R	1257640000	C.30
TPSDHA KTB 100X25 S2 2R	1257640000	C.31
TPSDHA KTB 100X25 S2 2R	1257640000	C.32
TPSDHA KTB 100X25 S2 2R	1257640000	C.33
TPSDHA KTB 100X25 S2 2R	1257640000	C.34
TPSDHA KTB 100X25 S2 2R	1257640000	C.35
TPSDHA KTB 100X25 S2 2R	1257640000	C.36
TPSDHA KTB 100X25 S2 2R	1257640000	C.45
TPSDHA KTB 100X25 S2 2R	1257640000	C.46
TPSDHA KTB 100X25 S2 2R	1257640000	C.47
TPSDHA KTB 130X50 S2 R	1283450000	C.16
TPSDHA KTB 130X50 S2 R	1283450000	C.17
TPSDHA KTB 130X50 S2 R	1283450000	C.18
TPSDHA KTB 130X50 S2 R	1283450000	C.19
TPSDHA KTB 130X50 S2 R	1283450000	C.20
TPSDHA KTB 130X50 S2 R	1283450000	C.21
TPSDHA KTB 130X50 S2 R	1283450000	C.22
TPSDHA KTB 130X50 S2 R	1283450000	C.23
TPSDHA KTB 130X50 S2 R	1283450000	C.24
TPSDHA KTB 130X50 S2 R	1283450000	C.25
TPSDHA KTB 130X50 S2 R	1283450000	C.26
TPSDHA KTB 130X50 S2 R	1283450000	C.27
TPSDHA KTB 130X50 S2 R	1283450000	C.28
TPSDHA KTB 130X50 S2 R	1283450000	C.29
TPSDHA KTB 130X50 S2 R	1283450000	C.30
TPSDHA KTB 130X50 S2 R	1283450000	C.31
TPSDHA KTB 130X50 S2 R	1283450000	C.32
TPSDHA KTB 130X50 S2 R	1283450000	C.33
TPSDHA KTB 130X50 S2 R	1283450000	C.34
TPSDHA KTB 130X50 S2 R	1283450000	C.35
TPSDHA KTB 130X50 S2 R	1283450000	C.36
TPSDHA KTB 130X50 S2 R	1283450000	C.45
TPSDHA KTB 130X50 S2 R	1283450000	C.46
TPSDHA KTB 130X50 S2 R	1283450000	C.47
TPSDHA KTB 70X70M3 S2 R	1279320000	C.15
TPSDHA KTB 70X70M3 S2 R	1279320000	C.16
TPSDHA KTB 70X70M3 S2 R	1279320000	C.17
TPSDHA KTB 70X70M3 S2 R	1279320000	C.18
TPSDHA KTB 70X70M3 S2 R	1279320000	C.19
TPSDHA KTB 70X70M3 S2 R	1279320000	C.20
TPSDHA KTB 70X70M3 S2 R	1279320000	C.21
TPSDHA KTB 70X70M3 S2 R	1279320000	C.22
TPSDHA KTB 70X70M3 S2 R	1279320000	C.23
TPSDHA KTB 70X70M3 S2 R	1279320000	C.24
TPSDHA KTB 70X70M3 S2 R	1279320000	C.25
TPSDHA KTB 70X70M3 S2 R	1279320000	C.26
TPSDHA KTB 70X70M3 S2 R	1279320000	C.27
TPSDHA KTB 70X70M3 S2 R	1279320000	C.28
TPSDHA KTB 70X70M3 S2 R	1279320000	C.29
TPSDHA KTB 70X70M3 S2 R	1279320000	C.30
TPSDHA KTB 70X70M3 S2 R	1279320000	C.31
TPSDHA KTB 70X70M3 S2 R	1279320000	C.32
TPSDHA KTB 70X70M3 S2 R	1279320000	C.33
TPSDHA KTB 70X70M3 S2 R	1279320000	C.34
TPSDHA KTB 70X70M3 S2 R	1279320000	C.35
TPSDHA KTB 70X70M3 S2 R	1279320000	C.36
TPSDHA KTB 70X70M3 S2 R	1279320000	C.44
TPSDHA KTB 70X70M3 S2 R	1279320000	C.45
TPSDHA KTB 70X70M3 S2 R	1279320000	C.46
TPSDHA KTB 70X70M3 S2 R	1279320000	C.47
TS 35x105_MPC_12	8000037603	C.178
TS 35x105_MPC_12	8000037603	C.179
TS 35x105_MPC_12	8000037603	C.181
TS15 114 Klippon K21 CSS	1910020000	C.102
TS15 114 Klippon K21 CSS	1910020000	C.116
TS15 147 Klippon POK3 CSS	1928080000	C.150
TS15 147 Klippon POK3 CSS	1928080000	C.154
TS15 155 Klippon K3 CSS	1910030000	C.103
TS15 155 Klippon K3 CSS	1910030000	C.116
TS15 164 Klippon K31 CSS	1910040000	C.104
TS15 164 Klippon K31 CSS	1910040000	C.116
TS15 60 KLippon K1 CSS	1909980000	C.99
TS15 60 KLippon K1 CSS	1909980000	C.116
TS15 64 Klippon K11	1909990000	C.100
TS15 64 Klippon K11	1909990000	C.116
TS15 68 Klippon POK1 CSS	1928060000	C.150
TS15 68 Klippon POK1 CSS	1928060000	C.152
TS15 90 KLippon K2 CSS	1910010000	C.101
TS15 90 KLippon K2 CSS	1910010000	C.116
TS15 98 Klippon POK2 CSS	1928070000	C.150
TS15 98 Klippon POK2 CSS	1928070000	C.153
TS15X5 ST FPC 20 VER	8000037604	C.185
TS15X5 ST FPC 20 VER	8000037604	C.186
TS15X5 ST MPC0712 VER	8000037599	C.178
TS15X5 ST MPC1217 VER	8000037598	C.178
TS15X5 ST MPC1217 VER	8000037598	C.179
TS15X5 ST MPC1217 VER	8000037598	C.180
TS15X5 ST POK 0808	8000003889	C.132
TS15X5 ST POK 0811	8000003890	C.133
TS15X5 ST POK 0811	8000003890	C.137
TS15X5 ST POK 0816	8000003891	C.134
TS15X5 ST POK 0819	8000003892	C.135
TS15X5 ST POK 0823	8000032382	C.136
TS35 105 Klippon K41/POK4	1910070000	C.107
TS35 105 Klippon K41/POK4	1910070000	C.116
TS35 105 Klippon K41/POK4	1910070000	C.150
TS35 105 Klippon K41/POK4	1910070000	C.155
TS35 64 Klippon K4K11	1910060000	C.106
TS35 64 Klippon K4K11	1910060000	C.116
TS35 MPC 1717 VER	8000037605	C.179
TS35 MPC 1717 VER	8000037605	C.180
TS35 MPC 1717 VER	8000037605	C.181
TS35/140 Klippon K52 POK51	1910100000	C.110
TS35/140 Klippon K52 POK51	1910100000	C.116
TS35/140 Klippon K52 POK51	1910100000	C.150
TS35/140 Klippon K52 POK51	1910100000	C.156
TS35/148 KLIPPON K5 CSS	1910080000	C.108
TS35/148 KLIPPON K5 CSS	1910080000	C.116
TS35/172 KLIPPON K6 CSS	1910110000	C.111
TS35/203 KLIPPON K51POK5	1910090000	C.109
TS35/243 KLIPPON K61POK6	1910120000	C.112
TS35/260 KLIPPON K71 CSS	1910140000	C.114
TS35/324 KLIPPON K7 CSS	1910130000	C.113
TS35X7.5 ST FPC 20 HOR	8000037557	C.185
TS35X7.5 ST FPC 20 VER	8000037558	C.185
TS35X7.5 ST FPC 20 VER	8000037558	C.186
TS35X7.5 ST FPC 30 HOR	8000037559	C.185
TS35X7.5 ST FPC 30 VER	8000037561	C.187
TS35X7.5 ST FPC 40 HOR	8000037560	C.186
TS35X7.5 ST FPC 40 HOR	8000037560	C.187
TS35X7.5 ST FPC 40 VER	8000037562	C.187
TS35X7.5 ST FPC 60 HOR	8000037563	C.187
TS35X7.5 ST K52	8000003908	C.139
TS35X7.5 ST KEBI 30 VER	8000037556	C.52
TS35X7.5 ST KEBI 30 VER	8000037556	C.53
TS35X7.5 ST KEBI 30 VER	8000037556	C.54
TS35X7.5 ST KEBI 40 VER	8000037555	C.55
TS35X7.5 ST KEBI 40 VER	8000037555	C.56
TS35X7.5 ST KEBI 40 VER	8000037555	C.57
TS35X7.5 ST KEBI 50 VER	8000037554	C.58
TS35X7.5 ST KEBI 50 VER	8000037554	C.59
TS35X7.5 ST KEBI 60 VER	8000037553	C.60
TS35X7.5 ST KEBI 60 VER	8000037553	C.61
TS35X7.5 ST KEBI 80 VER	8000037552	C.62
TS35X7.5 ST KTB2215 HOR	8000006720	C.15
TS35X7.5 ST KTB2215 VER	8000006708	C.15
TS35X7.5 ST KTB2626 VER	8000006709	C.16
TS35X7.5 ST KTB2626 VER	8000006709	C.17
TS35X7.5 ST KTB3030 HOR	8000006722	C.18
TS35X7.5 ST KTB3030 HOR	8000006722	C.19
TS35X7.5 ST KTB3030 VER	8000006710	C.18
TS35X7.5 ST KTB3030 VER	8000006710	C.19
TS35X7.5 ST KTB3526 HOR	8000006721	C.16
TS35X7.5 ST KTB3526 HOR	8000006721	C.17
TS35X7.5 ST KTB3526 HOR	8000006721	C.20
TS35X7.5 ST KTB3526 HOR	8000006721	C.21
TS35X7.5 ST KTB3526 VER	8000006711	C.20
TS35X7.5 ST KTB3526 VER	8000006711	C.21
TS35X7.5 ST KTB4030 HOR	8000006723	C.22
TS35X7.5 ST KTB4030 HOR	8000006723	C.23
TS35X7.5 ST KTB4030 VER	8000006712	C.22
TS35X7.5 ST KTB4030 VER	8000006712	C.23
TS35X7.5 ST KTB4538 HOR	8000006724	C.24
TS35X7.5 ST KTB4538 HOR	8000006724	C.25
TS35X7.5 ST KTB4538 VER	8000006713	C.24
TS35X7.5 ST KTB4538 VER	8000006713	C.25
TS35X7.5 ST KTB4848 HOR	8000006725	C.26
TS35X7.5 ST KTB4848 HOR	8000006725	C.27
TS35X7.5 ST KTB4848 VER	8000006714	C.26
TS35X7.5 ST KTB4848 VER	8000006714	C.27
TS35X7.5 ST KTB5535 HOR	8000006726	C.28
TS35X7.5 ST KTB5535 HOR	8000006726	C.29
TS35X7.5 ST KTB5535 VER	8000006715	C.28
TS35X7.5 ST KTB5535 VER	8000006715	C.29
TS35X7.5 ST KTB6245 HOR	8000006727	C.30
TS35X7.5 ST KTB6245 HOR	8000006727	C.31
TS35X7.5 ST KTB6245 VER	8000006716	C.30
TS35X7.5 ST KTB6245 VER	8000006716	C.31
TS35X7.5 ST KTB7650 HOR	8000006728	C.32
TS35X7.5 ST KTB7650 HOR	8000006728	C.33
TS35X7.5 ST KTB7650 VER	8000006717	C.32
TS35X7.5 ST KTB7650 VER	8000006717	C.33
TS35X7.5 ST KTB9161 HOR	8000006729	C.34
TS35X7.5 ST KTB9161 HOR	8000006729	C.35
TS35X7.5 ST KTB9161 VER	8000006718	C.34
TS35X7.5 ST KTB9161 VER	8000006718	C.35
TS35X7.5 ST KTB9874 HOR	8000006730	C.36
TS35X7.5 ST KTB9874 VER	8000006719	C.36
TS35X7.5 ST MPC1725 HOR	8000037601	C.182
TS35X7.5 ST MPC1725 HOR	8000037601	C.183
TS35X7.5 ST MPC1725 VER	8000037600	C.182
TS35X7.5 ST MPC1725 VER	8000037600	C.183
TS35X7.5 ST POK 1222	8000037568	C.138
TS35X7.5 ST POK 1626	8000003909	C.140
TS35X7.5 ST POK 1636	8000003910	C.141
TS35X7.5 ST POK 1656	8000003911	C.142
TS35X7.5 ST POK 2525	8000003912	C.143
TS35X7.5 ST POK 2525	8000003912	C.144
TS35X7.5 ST POK 2560	8000003914	C.147
TS35X7.5 ST POK 4040	8000003913	C.145
TS35X7.5 ST POK 4040	8000003913	C.146
TS35X7.5 ST POK 4040	8000003913	C.148
TS35X7.5 ST STB 1.1 STB 2	8683740000	C.68
TS35X7.5 ST STB 1.1 STB 2	8683740000	C.69
TS35X7.5 ST STB 1.1 STB 2	8683740000	C.70
TS35X7.5 ST STB 2.1 STB 3	1567660000	C.71
TS35X7.5 ST STB 2.1 STB 3	1567660000	C.72
TS35X7.5 ST STB 4 STB 6	8563410000	C.73
TS35X7.5 ST STB 4 STB 6	8563410000	C.74
TS35X7.5 ST STB 4 STB 6	8563410000	C.75
TS35X7.5 ST STB 5	8803610000	C.73
TS35X7.5 ST STB 5	8803610000	C.74
TS35X7.5 ST STB 5	8803610000	C.75

V

VG 11-K68	1568990000	D.6
VG 11-K68 SKS	1720490000	D.7
VG 11-MS68	1569080000	D.8
VG 11-SS 68 KB 5-10	1009760000	D.13
VG 13,5-MS68	1569090000	D.8
VG 13.5-K68	1569000000	D.6
VG 13.5-K68 SKS	1720500000	D.7
VG 16-K68	1569010000	D.6
VG 16-K68 SKS	1720510000	D.7
VG 16-MS68	1569100000	D.8
VG 16-SS 68 KB 10-14	1009780000	D.13
VG 21-K68	1569020000	D.6
VG 21-K68 SKS	1720520000	D.7
VG 21-MS68	1569110000	D.8
VG 21-SS 68 KB 13-18	1009790000	D.13
VG 29-K68	1569030000	D.6
VG 29-MS68	1569120000	D.8
VG 29-SS 68 KB 18-25	1009800000	D.13
VG 36-K68	1569040000	D.6
VG 36-MS68	1569130000	D.8
VG 36-SS 68 KB 22-32	1009810000	D.13
VG 42-K68	1569050000	D.6
VG 42-MS68	1569140000	D.8
VG 48-K68	1718770000	D.6
VG 48-MS68	1718790000	D.8
VG 7-K68	1568970000	D.6
VG 7-K68 SKS	1720470000	D.7
VG 7-MS68	1569060000	D.8
VG 7-SS 68 KB 3-6.5	1009740000	D.13
VG 9-K68	1568980000	D.6
VG 9-K68 SKS	1720480000	D.7
VG 9-MS68	1569070000	D.8
VG 9-SS 68 KB 4-8	1009750000	D.13
VG H M20 MS	1921720000	D.10
VG H M25 MS	1921740000	D.10
VG H M32 MS	1921760000	D.10
VG H M40 MS	1921770000	D.10
VG M12 - MS 68	1772200000	D.8
VG M12 EMV-4 MS 3-6.5	2435070000	D.11
VG M12 EXE 4-6,5 CR7J G4	2721930000	D.38
VG M12 EXE 4-6,5 SI7J G4	2722070000	D.39
VG M12 EXI 4-6,5 CR7J G4	2722210000	D.38
VG M12 EXI 4-6,5 SI7J G4	2722350000	D.39
VG M12-1/K68	1772280000	D.6
VG M12-K68 SKS	1776700000	D.7
VG M16 - K 68	1772290000	D.6
VG M16 - MS 68	1772210000	D.8
VG M16 EMV-4 MS 5-10	2435140000	D.11

Type	Order No.	Page
VG M16 EXE 5-8 CR7J G4	2721940000	D.38
VG M16 EXE 5-8 SI7J G4	2722080000	C.152
VG M16 EXE 5-8 SI7J G4	2722080000	D.39
VG M16 EXE 6-10 CR7J G4	2721950000	D.38
VG M16 EXE 6-10 SI7J G4	2722090000	C.152
VG M16 EXE 6-10 SI7J G4	2722090000	D.39
VG M16 EXE MS	1460040000	C.44
VG M16 EXE MS	1460040000	C.78
VG M16 EXE MS	1460040000	C.152
VG M16 EXI 5-8 CR7J G4	2722220000	D.38
VG M16 EXI 5-8 SI7J G4	2722360000	D.39
VG M16 EXI 6-10 CR7J G4	2722230000	D.38
VG M16 EXI 6-10 SI7J G4	2722370000	D.39
VG M16-1/K68	1909860000	D.6
VG M16-1/MS68	1909910000	D.8
VG M16-K68 SKS	1776710000	D.7
VG M20 - MS 68	1772220000	D.8
VG M20 EMV-4 MS 6-12	2435150000	D.11
VG M20 EMV-4 MS 8-14	2435160000	D.11
VG M20 EXE 11-14 CR7J G4	2721980000	D.38
VG M20 EXE 11-14 SI7J G4	2722120000	C.153
VG M20 EXE 11-14 SI7J G4	2722120000	C.154
VG M20 EXE 11-14 SI7J G4	2722120000	C.155
VG M20 EXE 11-14 SI7J G4	2722120000	C.156
VG M20 EXE 11-14 SI7J G4	2722120000	D.39
VG M20 EXE 7-12 CR7J G4	2721960000	D.38
VG M20 EXE 7-12 SI7J G4	2722100000	D.39
VG M20 EXE 7-13 CR7J G4	2721970000	D.38
VG M20 EXE 7-13 SI7J G4	2722110000	C.153
VG M20 EXE 7-13 SI7J G4	2722110000	C.154
VG M20 EXE 7-13 SI7J G4	2722110000	C.155
VG M20 EXE 7-13 SI7J G4	2722110000	C.156
VG M20 EXE 7-13 SI7J G4	2722110000	D.39
VG M20 EXE MS	1460050000	C.44
VG M20 EXE MS	1460050000	C.45
VG M20 EXE MS	1460050000	C.46
VG M20 EXE MS	1460050000	C.47
VG M20 EXE MS	1460050000	C.79
VG M20 EXE MS	1460050000	C.80
VG M20 EXE MS	1460050000	C.153
VG M20 EXE MS	1460050000	C.154
VG M20 EXE MS	1460050000	C.155
VG M20 EXE MS	1460050000	C.156
VG M20 EXI 11-14 CR7J G4	2722260000	D.38
VG M20 EXI 11-14 SI7J G4	2722400000	D.39
VG M20 EXI 7-12 CR7J G4	2722240000	D.38
VG M20 EXI 7-12 SI7J G4	2722380000	D.39
VG M20 EXI 7-13 CR7J G4	2722250000	D.38
VG M20 EXI 7-13 SI7J G4	2722390000	D.39
VG M20-1/K68	1772300000	D.6
VG M20-K68 SKS 10-14	1776720000	D.7
VG M20-K68 SKS 6-12	1778860000	D.7
VG M25 - K 68	1772310000	D.6
VG M25 - MS 68	1772230000	D.8
VG M25 EMV-4 MS 10-18	2435170000	D.11
VG M25 EXE 12-17 CR7J G4	2721990000	D.38
VG M25 EXE 12-17 SI7J G4	2722130000	D.39
VG M25 EXE 14-18 CR7J G4	2722000000	D.38
VG M25 EXE 14-18 SI7J G4	2722140000	D.39
VG M25 EXE MS	1460070000	C.47
VG M25 EXE MS	1460070000	C.81
VG M25 EXI 12-17 CR7J G4	2722270000	D.38
VG M25 EXI 12-17 SI7J G4	2722410000	D.39
VG M25 EXI 14-18 CR7J G4	2722280000	D.38
VG M25 EXI 14-18 SI7J G4	2722420000	D.39
VG M25-1/K68	1909870000	D.6
VG M25-1/MS68	1909920000	D.8
VG M25-K68 SKS	1776730000	D.7
VG M32 - K 68	1772320000	D.6
VG M32 - MS 68	1772240000	D.8
VG M32 EMV-4 MS 16-25	2435180000	D.11
VG M32 EXE 16-21 CR7J G4	2722010000	D.38
VG M32 EXE 16-21 SI7J G4	2722150000	D.39
VG M32 EXE 19-25 CR7J G4	2722020000	D.38
VG M32 EXE 19-25 SI7J G4	2722160000	D.39
VG M32 EXE MS	1460080000	C.45
VG M32 EXE MS	1460080000	C.46
VG M32 EXI 16-21 CR7J G4	2722290000	D.38
VG M32 EXI 16-21 SI7J G4	2722430000	D.39
VG M32 EXI 19-25 CR7J G4	2722300000	D.38
VG M32 EXI 19-25 SI7J G4	2722440000	D.39
VG M32-1/K68	1909880000	D.6
VG M32-1/MS68	1909930000	D.8
VG M40 - K 68	1772330000	D.6
VG M40 - MS 68	1772250000	D.8
VG M40 EMV-4 MS 22-32	2435190000	D.11
VG M40 EXE 20-28 CR7J G4	2722030000	D.38
VG M40 EXE 20-28 SI7J G4	2722170000	D.39
VG M40 EXE 23-32 CR7J G4	2722040000	D.38
VG M40 EXE 23-32 SI7J G4	2722180000	D.39
VG M40 EXE MS	1460090000	C.47
VG M40 EXI 20-28 CR7J G4	2722310000	D.38
VG M40 EXI 20-28 SI7J G4	2722450000	D.39
VG M40 EXI 23-32 CR7J G4	2722320000	D.38
VG M40 EXI 23-32 SI7J G4	2722460000	D.39
VG M40-1/K68	1909890000	D.6
VG M40-1/MS68	1909940000	D.8
VG M50 - K 68	1772340000	D.6
VG M50 - MS 68	1772260000	D.8

Type	Order No.	Page
VG M50 EMV-4 MS 30-38	2435200000	D.11
VG M50 EXE 31-38 CR7J G4	2722050000	D.38
VG M50 EXE 31-38 SI7J G4	2722190000	D.39
VG M50 EXI 31-38 CR7J G4	2722330000	D.38
VG M50 EXI 31-38 SI7J G4	2722470000	D.39
VG M50-1/MS68	1909950000	D.8
VG M63 - MS 68	1772270000	D.8
VG M63 EMV-4 MS 34-44	2435210000	D.11
VG M63 EXE 35-44 CR7J G4	2722060000	D.38
VG M63 EXE 35-44 SI7J G4	2722200000	D.39
VG M63 EXI 35-44 CR7J G4	2722340000	D.38
VG M63 EXI 35-44 SI7J G4	2722480000	D.39
VG M63-1/K68	1772350000	D.6
VGM12-SS 68 KB 3-6.5	1009840000	D.13
VGM16-SS 68 KB 4-8	1009850000	D.13
VGM20-SS 68 KB 6-12	1009860000	D.13
VGM25-MS68 11-20 BG	1193600000	D.9
VGM25-MS68 EMC 11-20SET	1463720000	D.12
VGM25-SS 68 KB 10-14	1009870000	D.13
VGM25-SS68 11-20 BG	1193570000	D.14
VGM32-MS68 15-25 BG	1193610000	D.9
VGM32-MS68 EMC 15-25SET	1463730000	D.12
VGM32-SS 68 KB 13-18	1009880000	D.13
VGM32-SS68 15-25 BG	1193580000	D.14
VGM40-MS68 20-32 BG	1193620000	D.9
VGM40-SS 68 KB 18-25	1009890000	D.13
VGM40-SS68 20-32 BG	1193590000	D.14
VGM40/1-MS68 20-32 BG	1205890000	D.9
VGM40/1-SS68 20-32 BG	1205920000	D.14
VGM50-SS 68 KB 22-32	1009900000	D.13
VGM63-SS 68 KB 34-44	1009910000	D.13
VP 11-K54	0294860000	D.53
VP 11-MS65	0294800000	D.54
VP 13,5-K54	0294960000	D.53
VP 13,5-MS65	0294900000	D.54
VP 16-K54	0295060000	D.53
VP 16-MS65	0295000000	D.54
VP 21-K54	0295160000	D.53
VP 21-MS65	0295100000	D.54
VP 29-K54	0501160000	D.53
VP 29-MS65	0501100000	D.54
VP 36-K54	0501260000	D.53
VP 36-MS65	0501200000	D.54
VP 42-K54	0501360000	D.53
VP 42-MS65	0501300000	D.54
VP 48-K54	1719260000	D.53
VP 48-MS65	1719270000	D.54
VP 7-K54	1719250000	D.53
VP 7-MS65	0521600000	D.54
VP 9-K54	0294760000	D.53
VP 9-MS65	0294700000	D.54
VP M12 EX SI 7J	2066710000	D.58
VP M12 K54	1776930000	D.53
VP M12-MS65	1777720000	D.54
VP M16 EX SI 7J	2066720000	C.152
VP M16 EX SI 7J	2066720000	D.58
VP M16 EXE MS	1210890000	C.152
VP M16 EXE MS	1210890000	D.56
VP M16 K54	1776920000	D.53
VP M16-EXE SW	1737070000	D.55
VP M16-MS65	1777730000	D.54
VP M20 EX SI 7J	2066730000	C.153
VP M20 EX SI 7J	2066730000	C.154
VP M20 EX SI 7J	2066730000	C.155
VP M20 EX SI 7J	2066730000	C.156
VP M20 EX SI 7J	2066730000	D.58
VP M20 EXE MS	1210900000	C.153
VP M20 EXE MS	1210900000	C.154
VP M20 EXE MS	1210900000	C.155
VP M20 EXE MS	1210900000	D.56
VP M20 K54	1776910000	D.53
VP M20-EXE SW	1737080000	D.55
VP M20-MS65	1777740000	D.54
VP M25 EX SI 7J	2066740000	D.58
VP M25 EXE MS	1210910000	D.56
VP M25 K54	1776900000	D.53
VP M25-EXE SW	1737090000	D.55
VP M25-MS65	1777750000	D.54
VP M32 EX SI 7J	2066750000	D.58
VP M32 EXE MS	1210920000	D.56
VP M32 K54	1776940000	D.53
VP M32-EXE SW	1737100000	D.55
VP M32-MS65	1777760000	D.54
VP M40 EX SI 7J	2066760000	D.58
VP M40 EXE MS	1210930000	D.56
VP M40 K54	1776950000	D.53
VP M40-EXE SW	1737110000	D.55
VP M40-MS65	1777770000	D.54
VP M50 EX SI 7J	2066770000	D.58
VP M50 EXE MS	1210940000	D.56
VP M50 K54	1776960000	D.53
VP M50-EXE SW	1737120000	D.55
VP M50-MS65	1777780000	D.54
VP M63 EX SI 7J	2066940000	D.58
VP M63 EXE MS	1210950000	D.56
VP M63 K54	1776970000	D.53
VP M63-EXE SW	1737130000	D.55
VP M63-MS65	1777790000	D.54

W

Type	Order No.	Page
WDU 4	1020100000	C.46
WDU 4	1020100000	C.47
WDU 4	1020100000	C.79
WDU 4	1020100000	C.80
WDU 4	1020100000	C.81
WDU 4 BL	1020180000	C.44
WDU 4 BL	1020180000	C.45
WDU 4 BL	1020180000	C.78
WPE 4	1010100000	C.46
WPE 4	1010100000	C.47
WPE 4	1010100000	C.80
WPE 4	1010100000	C.81

X

Order No.	Type	Page
0290000000		
0294700000	VP 9-MS65	D.54
0294760000	VP 9-K54	D.53
0294800000	VP 11-MS65	D.54
0294860000	VP 11-K54	D.53
0294900000	VP 13,5-MS65	D.54
0294960000	VP 13,5-K54	D.53
0295000000	VP 16-MS65	D.54
0295060000	VP 16-K54	D.53
0295100000	VP 21-MS65	D.54
0295160000	VP 21-K54	D.53
0340000000		
0342000000	KLIPPON K1	C.94
0342000000	KLIPPON K1	C.99
0342000000	KLIPPON K1	C.116
0342100000	KLIPPON K2	C.94
0342100000	KLIPPON K2	C.101
0342100000	KLIPPON K2	C.116
0342200000	KLIPPON K3	C.94
0342200000	KLIPPON K3	C.103
0342200000	KLIPPON K3	C.116
0342300000	KLIPPON K4	C.94
0342300000	KLIPPON K4	C.106
0342300000	KLIPPON K4	C.116
0342400000	KLIPPON K5	C.94
0342400000	KLIPPON K5	C.108
0342400000	KLIPPON K5	C.116
0342500000	KLIPPON K6	C.94
0342500000	KLIPPON K6	C.111
0342600000	KLIPPON K7	C.94
0342600000	KLIPPON K7	C.113
0360000000		
0360100000	TBF 19/15/14 7035	C.168
0360100000	TBF 19/15/14 7035	C.170
0360200000	TBF 30/19/18 7035	C.168
0360200000	TBF 30/19/18 7035	C.170
0360300000	TBF 30/30/18 7035	C.168
0360300000	TBF 30/30/18 7035	C.171
0360400000	TBF 37/30/18 7035	C.168
0360400000	TBF 37/30/18 7035	C.171
0360500000	TBF 60/30/18 7035	C.168
0360500000	TBF 60/30/18 7035	C.173
0360800000	MF TBF	C.170
0360800000	MF TBF	C.171
0360800000	MF TBF	C.172
0360800000	MF TBF	C.173
0360800000	MF TBF	C.174
0430000000		
0433500000	SFNS5 VKMU M5 SW15	C.68
0433500000	SFNS5 VKMU M5 SW15	C.69
0433500000	SFNS5 VKMU M5 SW15	C.70
0433500000	SFNS5 VKMU M5 SW15	C.71
0433500000	SFNS5 VKMU M5 SW15	C.72
0433500000	SFNS5 VKMU M5 SW15	C.73
0433500000	SFNS5 VKMU M5 SW15	C.74
0433500000	SFNS5 VKMU M5 SW15	C.75
0500000000		
0500500000	TBF 19/15/14 TRSP	C.168
0500500000	TBF 19/15/14 TRSP	C.170
0500600000	TBF 30/19/18 TRSP	C.168
0500600000	TBF 30/19/18 TRSP	C.170
0500700000	TBF 30/30/18 TRSP	C.168
0500700000	TBF 30/30/18 TRSP	C.171
0500800000	TBF 37/30/18 TRSP	C.168
0500800000	TBF 37/30/18 TRSP	C.171
0500900000	TBF 60/30/21 TRSP	C.168
0500900000	TBF 60/30/21 TRSP	C.173
0501100000	VP 29-MS65	D.54
0501160000	VP 29-K54	D.53
0501200000	VP 36-MS65	D.54
0501260000	VP 36-K54	D.53
0501300000	VP 42-MS65	D.54
0501360000	VP 42-K54	D.53
0520000000		
0521600000	VP 7-MS65	D.54
0570000000		
0573200000	KLIPPON K0	C.94
0573200000	KLIPPON K0	C.96
0573300000	KLIPPON K11	C.94
0573300000	KLIPPON K11	C.100
0573300000	KLIPPON K11	C.116
0573400000	KLIPPON K21	C.94
0573400000	KLIPPON K21	C.102
0573400000	KLIPPON K21	C.116
0573500000	KLIPPON K31	C.94
0573500000	KLIPPON K31	C.104
0573500000	KLIPPON K31	C.116
0573600000	KLIPPON K61	C.94
0573600000	KLIPPON K61	C.112
0573700000	KLIPPON K71	C.94
0573700000	KLIPPON K71	C.114
0640000000		
0642600000	FKSC M6X8 D9/SW3	C.15
0642600000	FKSC M6X8 D9/SW3	C.16
0642600000	FKSC M6X8 D9/SW3	C.17
0642600000	FKSC M6X8 D9/SW3	C.18
0642600000	FKSC M6X8 D9/SW3	C.19
0642600000	FKSC M6X8 D9/SW3	C.20
0642600000	FKSC M6X8 D9/SW3	C.21
0642600000	FKSC M6X8 D9/SW3	C.22
0642600000	FKSC M6X8 D9/SW3	C.23
0642600000	FKSC M6X8 D9/SW3	C.24
0642600000	FKSC M6X8 D9/SW3	C.25
0642600000	FKSC M6X8 D9/SW3	C.26
0642600000	FKSC M6X8 D9/SW3	C.27
0642600000	FKSC M6X8 D9/SW3	C.28
0642600000	FKSC M6X8 D9/SW3	C.29
0642600000	FKSC M6X8 D9/SW3	C.30
0642600000	FKSC M6X8 D9/SW3	C.31
0642600000	FKSC M6X8 D9/SW3	C.32
0642600000	FKSC M6X8 D9/SW3	C.33
0642600000	FKSC M6X8 D9/SW3	C.34
0642600000	FKSC M6X8 D9/SW3	C.35
0642600000	FKSC M6X8 D9/SW3	C.36
0642600000	FKSC M6X8 D9/SW3	C.44
0642600000	FKSC M6X8 D9/SW3	C.45
0642600000	FKSC M6X8 D9/SW3	C.46
0642600000	FKSC M6X8 D9/SW3	C.47
0642600000	FKSC M6X8 D9/SW3	C.132
0642600000	FKSC M6X8 D9/SW3	C.133
0642600000	FKSC M6X8 D9/SW3	C.134
0642600000	FKSC M6X8 D9/SW3	C.135
0642600000	FKSC M6X8 D9/SW3	C.136
0642600000	FKSC M6X8 D9/SW3	C.137
0642600000	FKSC M6X8 D9/SW3	C.138
0642600000	FKSC M6X8 D9/SW3	C.139
0642600000	FKSC M6X8 D9/SW3	C.140
0642600000	FKSC M6X8 D9/SW3	C.141
0642600000	FKSC M6X8 D9/SW3	C.142
0642600000	FKSC M6X8 D9/SW3	C.143
0642600000	FKSC M6X8 D9/SW3	C.144
0642600000	FKSC M6X8 D9/SW3	C.145
0642600000	FKSC M6X8 D9/SW3	C.146
0642600000	FKSC M6X8 D9/SW3	C.147
0642600000	FKSC M6X8 D9/SW3	C.148
0890000000		
0899750000	KSWF M20	D.48
0899770000	KSWF M25	D.48
0899780000	KSWN M40	D.47
0900000000		
0900660000	KSWN M50	D.47
0930000000		
0930001221	KDSU M20 BS O NI 1 G16	D.26
0930001221	KDSU M20 BS O NI 1 G16	D.28
0930001222	KDSU M20 BS O NI 2 G16	D.26
0930001222	KDSU M20 BS O NI 2 G16	D.28
0930011223	KDSU M20 BS O NI 1 G20S	D.26
0930011223	KDSU M20 BS O NI 1 G20S	D.28
0930011224	KDSU M20 BS O NI 2 G20S	D.26
0930011224	KDSU M20 BS O NI 2 G20S	D.28
0930021221	KDSU M20 BS O NI 1 G20	D.26
0930021221	KDSU M20 BS O NI 1 G20	D.28
0930021222	KDSU M20 BS O NI 2 G20	D.28
0930031221	KDSU M25 BS O NI 1 G25	D.28
0930031222	KDSU M25 BS O NI 2 G25	D.28
0930041221	KDSU M32 BS O NI 1 G32	D.28
0930041222	KDSU M32 BS O NI 2 G32	D.28
0930051222	KDSU M40 BS O NI 2 G40	D.28
0930061224	KDSU M50 BS O NI 2 G50S	D.28
0930091222	KDSU M63 BS O NI 2 G63	D.28
0930481222	KSG M20 BS O NI 2 G16	D.34
0930491224	KSG M20 BS O NI 2 G20S	D.34
0930501222	KSG M20 BS O NI 2 G20	D.34
0930511222	KSG M25 BS O NI 2 G25	D.34
0930521222	KSG M32 BS O NI 2 G32	D.34
0930531222	KSG M40 BS O NI 2 G40	D.34
0930640001	SKMU M16 MS SC	D.43
0930640002	SKMU M20 MS SC	D.43
0930640003	SKMU M25 MS SC	D.43
0930640004	SKMU M32 MS SC	D.43
0930640005	SKMU M40 MS SC	D.43
0930640006	SKMU M50 MS SC	D.43
0930640007	SKMU M63 MS SC	D.43
0930640008	SKMU M75 MS SC	D.43
0930700001	KSP L24 S	D.50
0930700002	KSP L30 S	D.50
0930700003	KSP L38 S	D.50
0930700004	KSP L46 S	D.50
0930700005	KSP L55 S	D.50
0930700006	KSP L65 S	D.50
0930700007	KSP L80 S	D.50
0930700008	KSP L90 S	D.50
0930710001	EA-RING MS/M16 SC	D.49
0930710002	EA-RING MS/M20 SC	D.49
0930710003	EA-RING MS/M25 SC	D.49
0930710004	EA-RING MS/M32 SC	D.49
0930710005	EA-RING MS/M40 SC	D.49
0930710006	EA-RING MS/M50 SC	D.49
0930710007	EA-RING MS/M63 SC	D.49
0930710008	EA-RING MS/M75 SC	D.49
0930730002	KSWN M20	D.47
0935110000	SP M6 10 S2	C.15
0935110000	SP M6 10 S2	C.16
0935110000	SP M6 10 S2	C.17
0935110000	SP M6 10 S2	C.18
0935110000	SP M6 10 S2	C.19
0935110000	SP M6 10 S2	C.20
0935110000	SP M6 10 S2	C.21
0935110000	SP M6 10 S2	C.22
0935110000	SP M6 10 S2	C.23
0935110000	SP M6 10 S2	C.24
0935110000	SP M6 10 S2	C.25
0935110000	SP M6 10 S2	C.26
0935110000	SP M6 10 S2	C.27
0935110000	SP M6 10 S2	C.28
0935110000	SP M6 10 S2	C.29
0935110000	SP M6 10 S2	C.30
0935110000	SP M6 10 S2	C.31
0935110000	SP M6 10 S2	C.32
0935110000	SP M6 10 S2	C.33
0935110000	SP M6 10 S2	C.34
0935110000	SP M6 10 S2	C.35
0935110000	SP M6 10 S2	C.36
0935110000	SP M6 10 S2	C.52
0935110000	SP M6 10 S2	C.53
0935110000	SP M6 10 S2	C.54
0935110000	SP M6 10 S2	C.55
0935110000	SP M6 10 S2	C.56
0935110000	SP M6 10 S2	C.57
0935110000	SP M6 10 S2	C.58
0935110000	SP M6 10 S2	C.59
0935110000	SP M6 10 S2	C.60
0935110000	SP M6 10 S2	C.61
0935110000	SP M6 10 S2	C.62
0935120000	SP M6 15 S2	C.15
0935120000	SP M6 15 S2	C.16
0935120000	SP M6 15 S2	C.17
0935120000	SP M6 15 S2	C.18
0935120000	SP M6 15 S2	C.19
0935120000	SP M6 15 S2	C.20
0935120000	SP M6 15 S2	C.21
0935120000	SP M6 15 S2	C.22
0935120000	SP M6 15 S2	C.23
0935120000	SP M6 15 S2	C.24
0935120000	SP M6 15 S2	C.25
0935120000	SP M6 15 S2	C.26
0935120000	SP M6 15 S2	C.27
0935120000	SP M6 15 S2	C.28
0935120000	SP M6 15 S2	C.29
0935120000	SP M6 15 S2	C.30
0935120000	SP M6 15 S2	C.31
0935120000	SP M6 15 S2	C.32
0935120000	SP M6 15 S2	C.33
0935120000	SP M6 15 S2	C.34
0935120000	SP M6 15 S2	C.35
0935120000	SP M6 15 S2	C.36
0935120000	SP M6 15 S2	C.52
0935120000	SP M6 15 S2	C.53
0935120000	SP M6 15 S2	C.54
0935120000	SP M6 15 S2	C.55
0935120000	SP M6 15 S2	C.56
0935120000	SP M6 15 S2	C.57
0935120000	SP M6 15 S2	C.58
0935120000	SP M6 15 S2	C.59
0935120000	SP M6 15 S2	C.60
0935120000	SP M6 15 S2	C.61
0935120000	SP M6 15 S2	C.62
0935130000	SP M6 20 S2	C.15
0935130000	SP M6 20 S2	C.16
0935130000	SP M6 20 S2	C.17
0935130000	SP M6 20 S2	C.18
0935130000	SP M6 20 S2	C.19
0935130000	SP M6 20 S2	C.20
0935130000	SP M6 20 S2	C.21
0935130000	SP M6 20 S2	C.22
0935130000	SP M6 20 S2	C.23
0935130000	SP M6 20 S2	C.24
0935130000	SP M6 20 S2	C.25
0935130000	SP M6 20 S2	C.26
0935130000	SP M6 20 S2	C.27
0935130000	SP M6 20 S2	C.28
0935130000	SP M6 20 S2	C.29
0935130000	SP M6 20 S2	C.30
0935130000	SP M6 20 S2	C.31
0935130000	SP M6 20 S2	C.32
0935130000	SP M6 20 S2	C.33
0935130000	SP M6 20 S2	C.34
0935130000	SP M6 20 S2	C.35
0935130000	SP M6 20 S2	C.36
0935130000	SP M6 20 S2	C.52
0935130000	SP M6 20 S2	C.53
0935130000	SP M6 20 S2	C.54
0935130000	SP M6 20 S2	C.55
0935130000	SP M6 20 S2	C.56
0935130000	SP M6 20 S2	C.57
0935130000	SP M6 20 S2	C.58
0935130000	SP M6 20 S2	C.59
0935130000	SP M6 20 S2	C.60
0935130000	SP M6 20 S2	C.61
0935130000	SP M6 20 S2	C.62
0935140000	SP M6 30 S2	C.15
0935140000	SP M6 30 S2	C.16
0935140000	SP M6 30 S2	C.17
0935140000	SP M6 30 S2	C.18
0935140000	SP M6 30 S2	C.19
0935140000	SP M6 30 S2	C.20
0935140000	SP M6 30 S2	C.21
0935140000	SP M6 30 S2	C.22
0935140000	SP M6 30 S2	C.23
0935140000	SP M6 30 S2	C.24
0935140000	SP M6 30 S2	C.25
0935140000	SP M6 30 S2	C.26
0935140000	SP M6 30 S2	C.27
0935140000	SP M6 30 S2	C.28
0935140000	SP M6 30 S2	C.29
0935140000	SP M6 30 S2	C.30
0935140000	SP M6 30 S2	C.31
0935140000	SP M6 30 S2	C.32
0935140000	SP M6 30 S2	C.33
0935140000	SP M6 30 S2	C.34
0935140000	SP M6 30 S2	C.35
0935140000	SP M6 30 S2	C.36
0935140000	SP M6 30 S2	C.52
0935140000	SP M6 30 S2	C.53
0935140000	SP M6 30 S2	C.54
0935140000	SP M6 30 S2	C.55
0935140000	SP M6 30 S2	C.56
0935140000	SP M6 30 S2	C.57
0935140000	SP M6 30 S2	C.58
0935140000	SP M6 30 S2	C.59
0935140000	SP M6 30 S2	C.60
0935140000	SP M6 30 S2	C.61
0935140000	SP M6 30 S2	C.62
1000000000		
1002690000	KLIPPON STB 1 SS	C.66
1002690000	KLIPPON STB 1 SS	C.68
1002690000	KLIPPON STB 1 SS	C.78
1002700000	KLIPPON STB 5 SS	C.66
1002700000	KLIPPON STB 5 SS	C.74
1002710000	KLIPPON STB 4 SS	C.66
1002710000	KLIPPON STB 4 SS	C.73
1002710000	KLIPPON STB 4 SS	C.81
1002720000	KLIPPON STB 3 SS	C.66
1002720000	KLIPPON STB 3 SS	C.72
1002720000	KLIPPON STB 3 SS	C.80
1002730000	KLIPPON STB 2.1 SS	C.66
1002730000	KLIPPON STB 2.1 SS	C.71
1002740000	KLIPPON STB 2 SS	C.66
1002740000	KLIPPON STB 2 SS	C.70
1002740000	KLIPPON STB 2 SS	C.79
1002750000	KLIPPON STB 1.1 SS	C.66
1002750000	KLIPPON STB 1.1 SS	C.69
1002760000	KLIPPON STB 6 SS	C.66
1002760000	KLIPPON STB 6 SS	C.75
1009740000	VG 7-SS 68 KB 3-6.5	D.13
1009750000	VG 9-SS 68 KB 4-8	D.13
1009760000	VG 11-SS 68 KB 5-10	D.13
1009780000	VG 16-SS 68 KB 10-14	D.13
1009790000	VG 21-SS 68 KB 13-18	D.13
1009800000	VG 29-SS 68 KB 18-25	D.13
1009810000	VG 36-SS 68 KB 22-32	D.13
1009840000	VGM12-SS 68 KB 3-6.5	D.13
1009850000	VGM16-SS 68 KB 4-8	D.13
1009860000	VGM20-SS 68 KB 6-12	D.13
1009870000	VGM25-SS 68 KB 10-14	D.13
1009880000	VGM32-SS 68 KB 13-18	D.13
1009890000	VGM40-SS 68 KB 18-25	D.13
1009900000	VGM50-SS 68 KB 22-32	D.13
1009910000	VGM63-SS 68 KB 34-44	D.13
1010000000		
1010100000	WPE 4	C.46
1010100000	WPE 4	C.47
1010100000	WPE 4	C.80
1010100000	WPE 4	C.81
1020000000		
1020100000	WDU 4	C.46
1020100000	WDU 4	C.47
1020100000	WDU 4	C.79
1020100000	WDU 4	C.80

Order No.	Type	Page
1020100000	WDU 4	C.81
1020180000	WDU 4 BL	C.44
1020180000	WDU 4 BL	C.45
1020180000	WDU 4 BL	C.78
1024970000	KLIPPON STB 1 MS HT	C.66
1024970000	KLIPPON STB 1 MS HT	C.68
1024980000	KLIPPON STB 1.1 MS HT	C.66
1024980000	KLIPPON STB 1.1 MS HT	C.69
1024990000	KLIPPON STB 2 MS HT	C.66
1024990000	KLIPPON STB 2 MS HT	C.70
1025010000	KLIPPON STB 2.1 MS HT	C.66
1025010000	KLIPPON STB 2.1 MS HT	C.71
1025020000	KLIPPON STB 3 MS HT	C.66
1025020000	KLIPPON STB 3 MS HT	C.72
1025030000	KLIPPON STB 4 MS HT	C.66
1025030000	KLIPPON STB 4 MS HT	C.73
1025040000	KLIPPON STB 5 MS HT	C.66
1025040000	KLIPPON STB 5 MS HT	C.74
1025050000	KLIPPON STB 6 MS HT	C.66
1025050000	KLIPPON STB 6 MS HT	C.75

1050000000

1058810000	KLIPPON STB 1 SS E	C.66
1058810000	KLIPPON STB 1 SS E	C.68
1058820000	KLIPPON STB 1.1 SS E	C.66
1058820000	KLIPPON STB 1.1 SS E	C.69
1058830000	KLIPPON STB 2 SS E	C.66
1058830000	KLIPPON STB 2 SS E	C.70
1058840000	KLIPPON STB 2.1 SS E	C.66
1058840000	KLIPPON STB 2.1 SS E	C.71
1058850000	KLIPPON STB 3 SS E	C.66
1058850000	KLIPPON STB 3 SS E	C.72
1058860000	KLIPPON STB 4 SS E	C.66
1058860000	KLIPPON STB 4 SS E	C.73
1058870000	KLIPPON STB 6 SS E	C.66
1058870000	KLIPPON STB 6 SS E	C.75
1058880000	KLIPPON STB 5 SS E	C.66
1058880000	KLIPPON STB 5 SS E	C.74

1070000000

1074660000	KDSW M20 BN L NI 1 G16	D.31
1074690000	KDSW M20 BN L NI 2 G16	D.31
1074720000	KDSW M20 BN L NI 1 G20S	D.31
1074740000	KDSW M20 BN L NI 2 G20S	D.31
1074760000	KDSW M20 BN L NI 1 G20	D.31
1074780000	KDSW M20 BN L NI 2 G20	D.31
1074810000	KDSW M25 BN L NI 1 G25	D.31
1074830000	KDSW M25 BN L NI 2 G25	D.31
1074850000	KDSW M32 BN L NI 1 G32	D.31
1074860000	KDSW M32 BN L NI 2 G32	D.31
1074870000	KDSW M40 BN L NI 1 G40	D.31
1074880000	KDSW M40 BN L NI 2 G40	D.31
1074890000	KDSW M50 BN L NI 1 G50S	D.31
1074910000	KDSW M50 BN L NI 2 G50S	D.31
1074920000	KDSW M50 BN L NI 1 G50	D.31
1074930000	KDSW M50 BN L NI 2 G50	D.31
1074940000	KDSW M63 BN L NI 1 G63S	D.31
1074950000	KDSW M63 BN L NI 2 G63S	D.31
1074960000	KDSW M63 BN L NI 1 G63	D.31
1074970000	KDSW M63 BN L NI 2 G63	D.31
1074980000	KDSW M75 BN L NI 1 G75S	D.31
1074990000	KDSW M75 BN L NI 2 G75S	D.31
1075010000	KDSW M75 BN L NI 1 G75	D.31
1075020000	KDSW M75 BN L NI 2 G75	D.31
1075030000	KDSW M20 BN O NI 1 G16	D.29
1075040000	KDSW M20 BN O NI 2 G16	D.29
1075050000	KDSW M20 BN O NI 1 G20S	D.29
1075060000	KDSW M20 BN O NI 2 G20S	D.29
1075070000	KDSW M20 BN O NI 1 G20	D.29
1075080000	KDSW M20 BN O NI 2 G20	D.29
1075090000	KDSW M25 BN O NI 1 G25	D.29
1075110000	KDSW M25 BN O NI 2 G25	D.29
1075120000	KDSW M32 BN O NI 1 G32	D.29
1075130000	KDSW M32 BN O NI 2 G32	D.29
1075140000	KDSW M40 BN O NI 1 G40	D.29
1075150000	KDSW M40 BN O NI 2 G40	D.29
1075160000	KDSW M50 BN O NI 1 G50S	D.29
1075170000	KDSW M50 BN O NI 2 G50S	D.29
1075180000	KDSW M50 BN O NI 1 G50	D.29
1075190000	KDSW M50 BN O NI 2 G50	D.29
1075210000	KDSW M63 BN O NI 1 G63S	D.29
1075220000	KDSW M63 BN O NI 2 G63S	D.29
1075230000	KDSW M63 BN O NI 1 G63	D.29
1075240000	KDSW M63 BN O NI 2 G63	D.29
1075250000	KDSW M75 BN O NI 1 G75S	D.29
1075260000	KDSW M75 BN O NI 2 G75S	D.29
1075270000	KDSW M75 BN O NI 1 G75	D.29
1075280000	KDSW M75 BN O NI 2 G75	D.29
1075350000	KSG M75 BN O NI 2 G75S	D.33
1075360000	KSG M75 BN O NI 2 G75	D.33
1076630000	KSWN M16	D.47
1076640000	KSWN M25	D.47
1076650000	KSWN M32	D.47
1076660000	KSWN M63	D.47
1076670000	KSWN M75	D.47
1076680000	KSWF M16	D.48
1076690000	KSWF M32	D.48

Order No.	Type	Page
1076710000	KSWF M40	D.48
1076720000	KSWF M50	D.48
1076730000	KSWF M63	D.48
1076740000	KSWF M75	D.48
1076750000	KSP EL46	D.51
1076760000	KSP EL55	D.51
1076770000	KSP EL65	D.51
1076780000	KSP EL80	D.51
1076790000	KSP EL90	D.51

1080000000

1083280000	KDSU M20 BN O NI 1 G16	D.27
1083290000	KDSU M20 BN O NI 1 G20S	D.27
1083320000	KDSU M20 BN O NI 1 G20	D.27
1083330000	KDSU M25 BN O NI 1 G25	D.27
1083340000	KDSU M32 BN O NI 1 G32	D.27
1083350000	KDSU M40 BN O NI 1 G40	D.27
1083360000	KDSU M50 BN O NI 1 G50S	D.27
1083370000	KDSU M50 BN O NI 1 G50	D.27
1083380000	KDSU M63 BN O NI 1 G63S	D.27
1083390000	KDSU M63 BN O NI 1 G63	D.27
1083400000	KDSU M75 BN O NI 1 G75S	D.27
1083410000	KDSU M75 BN O NI 2 G75S	D.27
1083420000	KDSU M75 BN O NI 1 G75	D.27
1083430000	KDSU M75 BN O NI 2 G75	D.27

1130000000

1135910000	KDSX M20 BS O NI 1 G16	D.32
1135920000	KDSX M20 BS O NI 2 G16	D.32
1135930000	KDSX M20 BS O NI 1 G20S	D.32
1135940000	KDSX M20 BS O NI 2 G20S	D.32
1135950000	KDSX M20 BS O NI 1 G20	D.32
1135960000	KDSX M20 BS O NI 2 G20	D.32
1135970000	KDSX M25 BS O NI 1 G25	D.32
1135980000	KDSX M25 BS O NI 2 G25	D.32
1135990000	KDSX M32 BS O NI 1 G32	D.32
1136000000	KDSX M32 BS O NI 2 G32	D.32
1136010000	KDSX M40 BS O NI 1 G40	D.32
1136020000	KDSX M40 BS O NI 2 G40	D.32
1136030000	KDSX M50 BS O NI 1 G50S	D.32
1136040000	KDSX M50 BS O NI 2 G50S	D.32
1136050000	KDSX M50 BS O NI 1 G50	D.32
1136060000	KDSX M50 BS O NI 2 G50	D.32
1136070000	KDSX M63 BS O NI 1 G63S	D.32
1136080000	KDSX M63 BS O NI 2 G63S	D.32
1136090000	KDSX M63 BS O NI 1 G63	D.32
1136110000	KDSX M63 BS O NI 2 G63	D.32
1136120000	KDSX M75 BS O NI 1 G75S	D.32
1136130000	KDSX M75 BS O NI 2 G75S	D.32
1136140000	KDSX M75 BS O NI 1 G75	D.32
1136150000	KDSX M75 BS O NI 2 G75	D.32
1136410000	KDSW M20 BS O NI 1 G16	D.30
1136420000	KDSW M20 BS O NI 2 G16	D.30
1136430000	KDSW M20 BS O NI 1 G20S	D.30
1136440000	KDSW M20 BS O NI 2 G20S	D.30
1136450000	KDSW M20 BS O NI 1 G20	D.30
1136460000	KDSW M20 BS O NI 2 G20	D.30
1136470000	KDSW M25 BS O NI 1 G25	D.30
1136480000	KDSW M25 BS O NI 2 G25	D.30
1136490000	KDSW M32 BS O NI 1 G32	D.30
1136510000	KDSW M32 BS O NI 2 G32	D.30
1136520000	KDSW M40 BS O NI 1 G40	D.30
1136530000	KDSW M40 BS O NI 2 G40	D.30
1136540000	KDSW M50 BS O NI 1 G50S	D.30
1136550000	KDSW M50 BS O NI 2 G50S	D.30
1136560000	KDSW M50 BS O NI 1 G50	D.30
1136570000	KDSW M50 BS O NI 2 G50	D.30
1136580000	KDSW M63 BS O NI 1 G63S	D.30
1136590000	KDSW M63 BS O NI 2 G63S	D.30
1136600000	KDSW M63 BS O NI 1 G63	D.30
1136610000	KDSW M63 BS O NI 2 G63	D.30
1136620000	KDSW M75 BS O NI 1 G75S	D.30
1136630000	KDSW M75 BS O NI 2 G75S	D.30
1136640000	KDSW M75 BS O NI 1 G75	D.30
1136650000	KDSW M75 BS O NI 2 G75	D.30
1136660000	KSG M50 BS O NI 2 G50S	D.34
1136670000	KSG M50 BS O NI 2 G50	D.34
1136680000	KSG M63 BS O NI 2 G63S	D.34
1136690000	KSG M63 BS O NI 2 G63	D.34
1136700000	KSG M75 BS O NI 2 G75S	D.34
1136710000	KSG M75 BS O NI 2 G75	D.34
1136990000	KDSU M40 BS O NI 1 G40	D.28
1137000000	KDSU M50 BS O NI 1 G50S	D.28
1137010000	KDSU M50 BS O NI 1 G50	D.28
1137020000	KDSU M50 BS O NI 2 G50	D.28
1137030000	KDSU M63 BS O NI 1 G63S	D.28
1137040000	KDSU M63 BS O NI 2 G63S	D.28
1137050000	KDSU M63 BS O NI 1 G63	D.28
1137060000	KDSU M75 BS O NI 1 G75S	D.28
1137070000	KDSU M75 BS O NI 2 G75S	D.28
1137080000	KDSU M75 BS O NI 1 G75	D.28
1137090000	KDSU M75 BS O NI 2 G75	D.28

1190000000

1191600000	KTB QLL S2 SLS	C.52
1191600000	KTB QLL S2 SLS	C.53

Order No.	Type	Page
1191600000	KTB QLL S2 SLS	C.54
1191600000	KTB QLL S2 SLS	C.55
1191600000	KTB QLL S2 SLS	C.56
1191600000	KTB QLL S2 SLS	C.57
1191600000	KTB QLL S2 SLS	C.58
1191600000	KTB QLL S2 SLS	C.59
1191600000	KTB QLL S2 SLS	C.60
1191600000	KTB QLL S2 SLS	C.61
1191600000	KTB QLL S2 SLS	C.62
1192690000	PEBZ M10 KTB S4 SET	C.15
1192690000	PEBZ M10 KTB S4 SET	C.16
1192690000	PEBZ M10 KTB S4 SET	C.17
1192690000	PEBZ M10 KTB S4 SET	C.18
1192690000	PEBZ M10 KTB S4 SET	C.19
1192690000	PEBZ M10 KTB S4 SET	C.20
1192690000	PEBZ M10 KTB S4 SET	C.21
1192690000	PEBZ M10 KTB S4 SET	C.22
1192690000	PEBZ M10 KTB S4 SET	C.23
1192690000	PEBZ M10 KTB S4 SET	C.24
1192690000	PEBZ M10 KTB S4 SET	C.25
1192690000	PEBZ M10 KTB S4 SET	C.26
1192690000	PEBZ M10 KTB S4 SET	C.27
1192690000	PEBZ M10 KTB S4 SET	C.28
1192690000	PEBZ M10 KTB S4 SET	C.29
1192690000	PEBZ M10 KTB S4 SET	C.30
1192690000	PEBZ M10 KTB S4 SET	C.31
1192690000	PEBZ M10 KTB S4 SET	C.32
1192690000	PEBZ M10 KTB S4 SET	C.33
1192690000	PEBZ M10 KTB S4 SET	C.34
1192690000	PEBZ M10 KTB S4 SET	C.35
1192690000	PEBZ M10 KTB S4 SET	C.36
1192690000	PEBZ M10 KTB S4 SET	C.44
1192690000	PEBZ M10 KTB S4 SET	C.45
1192690000	PEBZ M10 KTB S4 SET	C.46
1192690000	PEBZ M10 KTB S4 SET	C.47
1192790000	KSP L114 S	D.50
1193570000	VGM25-SS68 11-20 BG	D.14
1193580000	VGM32-SS68 15-25 BG	D.14
1193590000	VGM40-SS68 20-32 BG	D.14
1193600000	VGM25-MS68 11-20 BG	D.9
1193610000	VGM32-MS68 15-25 BG	D.9
1193620000	VGM40-MS68 20-32 BG	D.9
1193810000	KTB MOPL 2215 S2N	C.15
1193810000	KTB MOPL 2215 S2N	C.44
1193820000	KTB MOPL 2626 S2N	C.16
1193820000	KTB MOPL 2626 S2N	C.17
1193820000	KTB MOPL 2626 S2N	C.45
1193830000	KTB MOPL 3030 S2N	C.18
1193830000	KTB MOPL 3030 S2N	C.19
1193830000	KTB MOPL 3030 S2N	C.46
1193840000	KTB MOPL 3526 S2N	C.20
1193840000	KTB MOPL 3526 S2N	C.21
1193850000	KTB MOPL 4030 S2N	C.22
1193850000	KTB MOPL 4030 S2N	C.23
1193860000	KTB MOPL 4538 S2N	C.24
1193860000	KTB MOPL 4538 S2N	C.25
1193870000	KTB MOPL 4848 S2N	C.26
1193870000	KTB MOPL 4848 S2N	C.27
1193870000	KTB MOPL 4848 S2N	C.47
1193880000	KTB MOPL 5535 S2N	C.28
1193880000	KTB MOPL 5535 S2N	C.29
1193890000	KTB MOPL 6245 S2N	C.30
1193890000	KTB MOPL 6245 S2N	C.31
1193900000	KTB MOPL 7650 S2N	C.32
1193900000	KTB MOPL 7650 S2N	C.33
1193910000	KTB MOPL 9161 S2N	C.34
1193910000	KTB MOPL 9161 S2N	C.35
1193920000	KTB MOPL 9874 S2N	C.36
1193930000	KTB MOPL 2215 MSZN	C.15
1193940000	KSP L 104 S	D.50
1193950000	KTB MOPL 2626 MSZN	C.16
1193950000	KTB MOPL 2626 MSZN	C.17
1193960000	KTB MOPL 3030 MSZN	C.18
1193960000	KTB MOPL 3030 MSZN	C.19
1193970000	KTB MOPL 3526 MSZN	C.20
1193970000	KTB MOPL 3526 MSZN	C.21
1193980000	KTB MOPL 4030 MSZN	C.22
1193980000	KTB MOPL 4030 MSZN	C.23
1193990000	KTB MOPL 4538 MSZN	C.24
1193990000	KTB MOPL 4538 MSZN	C.25
1194000000	KTB MOPL 4848 MSZN	C.26
1194000000	KTB MOPL 4848 MSZN	C.27
1194010000	KTB MOPL 5535 MSZN	C.28
1194010000	KTB MOPL 5535 MSZN	C.29
1194020000	KTB MOPL 6245 MSZN	C.30
1194020000	KTB MOPL 6245 MSZN	C.31
1194030000	KTB MOPL 7650 MSZN	C.32
1194030000	KTB MOPL 7650 MSZN	C.33
1194040000	KTB MOPL 9161 MSZN	C.34
1194040000	KTB MOPL 9161 MSZN	C.35
1194050000	KTB MOPL 9874 MSZN	C.36
1194550000	KTB MH 221513 S4E0	C.12
1194550000	KTB MH 221513 S4E0	C.15
1194560000	KTB MH 221513 S4E1	C.12
1194560000	KTB MH 221513 S4E1	C.15
1194560000	KTB MH 221513 S4E1	C.44
1194570000	KTB MH 221513 S4E2	C.12
1194570000	KTB MH 221513 S4E2	C.15
1194580000	KTB MH 221513 S4E3	C.12

Order No.	Type	Page
1194580000	KTB MH 221513 S4E3	C.15
1194590000	KTB MH 221513 S4E4	C.12
1194590000	KTB MH 221513 S4E4	C.15
1194600000	KTB MH 262615 S4E0	C.12
1194600000	KTB MH 262615 S4E0	C.16
1194610000	KTB MH 262615 S4E1	C.12
1194610000	KTB MH 262615 S4E1	C.16
1194610000	KTB MH 262615 S4E1	C.45
1194620000	KTB MH 262615 S4E2	C.12
1194620000	KTB MH 262615 S4E2	C.16
1194630000	KTB MH 262615 S4E3	C.12
1194630000	KTB MH 262615 S4E3	C.16
1194640000	KTB MH 262615 S4E4	C.12
1194640000	KTB MH 262615 S4E4	C.16
1194650000	KTB MH 262620 S4E0	C.12
1194650000	KTB MH 262620 S4E0	C.17
1194660000	KTB MH 262620 S4E1	C.12
1194660000	KTB MH 262620 S4E1	C.17
1194670000	KTB MH 262620 S4E2	C.12
1194670000	KTB MH 262620 S4E2	C.17
1194680000	KTB MH 262620 S4E3	C.12
1194680000	KTB MH 262620 S4E3	C.17
1194690000	KTB MH 262620 S4E4	C.12
1194690000	KTB MH 262620 S4E4	C.17
1194700000	KTB MH 303015 S4E0	C.12
1194700000	KTB MH 303015 S4E0	C.18
1194710000	KTB MH 303015 S4E1	C.12
1194710000	KTB MH 303015 S4E1	C.18
1194720000	KTB MH 303015 S4E2	C.12
1194720000	KTB MH 303015 S4E2	C.18
1194730000	KTB MH 303015 S4E3	C.12
1194730000	KTB MH 303015 S4E3	C.18
1194740000	KTB MH 303015 S4E4	C.12
1194740000	KTB MH 303015 S4E4	C.18
1194750000	KTB MH 303020 S4E0	C.12
1194750000	KTB MH 303020 S4E0	C.19
1194760000	KTB MH 303020 S4E1	C.12
1194760000	KTB MH 303020 S4E1	C.19
1194770000	KTB MH 303020 S4E2	C.12
1194770000	KTB MH 303020 S4E2	C.19
1194780000	KTB MH 303020 S4E3	C.12
1194780000	KTB MH 303020 S4E3	C.19
1194790000	KTB MH 303020 S4E4	C.12
1194790000	KTB MH 303020 S4E4	C.19
1194800000	KTB MH 352615 S4E0	C.12
1194800000	KTB MH 352615 S4E0	C.20
1194810000	KTB MH 352615 S4E1	C.12
1194810000	KTB MH 352615 S4E1	C.20
1194820000	KTB MH 352615 S4E2	C.12
1194820000	KTB MH 352615 S4E2	C.20
1194830000	KTB MH 352615 S4E3	C.12
1194830000	KTB MH 352615 S4E3	C.20
1194840000	KTB MH 352615 S4E4	C.12
1194840000	KTB MH 352615 S4E4	C.20
1194850000	KTB MH 352620 S4E0	C.12
1194850000	KTB MH 352620 S4E0	C.21
1194860000	KTB MH 352620 S4E1	C.12
1194860000	KTB MH 352620 S4E1	C.21
1194870000	KTB MH 352620 S4E2	C.12
1194870000	KTB MH 352620 S4E2	C.21
1194880000	KTB MH 352620 S4E3	C.12
1194880000	KTB MH 352620 S4E3	C.21
1194890000	KTB MH 352620 S4E4	C.12
1194890000	KTB MH 352620 S4E4	C.21
1194900000	KTB MH 403015 S4E0	C.12
1194900000	KTB MH 403015 S4E0	C.22
1194910000	KTB MH 403015 S4E1	C.12
1194910000	KTB MH 403015 S4E1	C.22
1194920000	KTB MH 403015 S4E2	C.12
1194920000	KTB MH 403015 S4E2	C.22
1194930000	KTB MH 403015 S4E3	C.12
1194930000	KTB MH 403015 S4E3	C.22
1194940000	KTB MH 403015 S4E4	C.12
1194940000	KTB MH 403015 S4E4	C.22
1194950000	KTB MH 403020 S4E0	C.12
1194950000	KTB MH 403020 S4E0	C.23
1194960000	KTB MH 403020 S4E1	C.12
1194960000	KTB MH 403020 S4E1	C.23
1194970000	KTB MH 403020 S4E2	C.12
1194970000	KTB MH 403020 S4E2	C.23
1194980000	KTB MH 403020 S4E3	C.12
1194980000	KTB MH 403020 S4E3	C.23
1194990000	KTB MH 403020 S4E4	C.12
1194990000	KTB MH 403020 S4E4	C.23
1195000000	KTB MH 453815 S4E0	C.12
1195000000	KTB MH 453815 S4E0	C.24
1195010000	KTB MH 453815 S4E1	C.12
1195010000	KTB MH 453815 S4E1	C.24
1195020000	KTB MH 453815 S4E2	C.12
1195020000	KTB MH 453815 S4E2	C.24
1195030000	KTB MH 453815 S4E3	C.12
1195030000	KTB MH 453815 S4E3	C.24
1195040000	KTB MH 453815 S4E4	C.12
1195040000	KTB MH 453815 S4E4	C.24
1195050000	KTB MH 453820 S4E0	C.12
1195050000	KTB MH 453820 S4E0	C.25
1195060000	KTB MH 453820 S4E1	C.12
1195060000	KTB MH 453820 S4E1	C.25
1195070000	KTB MH 453820 S4E2	C.12

Order No.	Type	Page
1195070000	KTB MH 453820 S4E2	C.25
1195080000	KTB MH 453820 S4E3	C.12
1195080000	KTB MH 453820 S4E3	C.25
1195090000	KTB MH 453820 S4E4	C.12
1195090000	KTB MH 453820 S4E4	C.25
1195100000	KTB MH 484815 S4E0	C.12
1195100000	KTB MH 484815 S4E0	C.26
1195110000	KTB MH 484815 S4E1	C.12
1195110000	KTB MH 484815 S4E1	C.26
1195120000	KTB MH 484815 S4E2	C.12
1195120000	KTB MH 484815 S4E2	C.26
1195130000	KTB MH 484815 S4E3	C.12
1195130000	KTB MH 484815 S4E3	C.26
1195140000	KTB MH 484815 S4E4	C.12
1195140000	KTB MH 484815 S4E4	C.26
1195150000	KTB MH 484820 S4E0	C.12
1195150000	KTB MH 484820 S4E0	C.27
1195160000	KTB MH 484820 S4E1	C.12
1195160000	KTB MH 484820 S4E1	C.27
1195170000	KTB MH 484820 S4E2	C.12
1195170000	KTB MH 484820 S4E2	C.27
1195180000	KTB MH 484820 S4E3	C.12
1195180000	KTB MH 484820 S4E3	C.27
1195190000	KTB MH 484820 S4E4	C.12
1195190000	KTB MH 484820 S4E4	C.27
1195200000	KTB MH 553515 S4E0	C.12
1195200000	KTB MH 553515 S4E0	C.28
1195210000	KTB MH 553515 S4E1	C.12
1195210000	KTB MH 553515 S4E1	C.28
1195220000	KTB MH 553515 S4E2	C.12
1195220000	KTB MH 553515 S4E2	C.28
1195230000	KTB MH 553515 S4E3	C.12
1195230000	KTB MH 553515 S4E3	C.28
1195240000	KTB MH 553515 S4E4	C.12
1195240000	KTB MH 553515 S4E4	C.28
1195250000	KTB MH 553520 S4E0	C.12
1195250000	KTB MH 553520 S4E0	C.29
1195260000	KTB MH 553520 S4E1	C.12
1195260000	KTB MH 553520 S4E1	C.29
1195270000	KTB MH 553520 S4E2	C.12
1195270000	KTB MH 553520 S4E2	C.29
1195280000	KTB MH 553520 S4E3	C.12
1195280000	KTB MH 553520 S4E3	C.29
1195290000	KTB MH 553520 S4E4	C.12
1195290000	KTB MH 553520 S4E4	C.29
1195300000	KTB MH 624515 S4E0	C.12
1195300000	KTB MH 624515 S4E0	C.30
1195310000	KTB MH 624515 S4E1	C.12
1195310000	KTB MH 624515 S4E1	C.30
1195320000	KTB MH 624515 S4E2	C.12
1195320000	KTB MH 624515 S4E2	C.30
1195330000	KTB MH 624515 S4E3	C.12
1195330000	KTB MH 624515 S4E3	C.30
1195340000	KTB MH 624515 S4E4	C.12
1195340000	KTB MH 624515 S4E4	C.30
1195350000	KTB MH 624520 S4E0	C.12
1195350000	KTB MH 624520 S4E0	C.31
1195360000	KTB MH 624520 S4E1	C.12
1195360000	KTB MH 624520 S4E1	C.31
1195370000	KTB MH 624520 S4E2	C.12
1195370000	KTB MH 624520 S4E2	C.31
1195380000	KTB MH 624520 S4E3	C.12
1195380000	KTB MH 624520 S4E3	C.31
1195390000	KTB MH 624520 S4E4	C.12
1195390000	KTB MH 624520 S4E4	C.31
1195400000	KTB MH 765015 S4E0	C.12
1195400000	KTB MH 765015 S4E0	C.32
1195410000	KTB MH 765015 S4E1	C.12
1195410000	KTB MH 765015 S4E1	C.32
1195420000	KTB MH 765015 S4E2	C.12
1195420000	KTB MH 765015 S4E2	C.32
1195430000	KTB MH 765015 S4E3	C.12
1195430000	KTB MH 765015 S4E3	C.32
1195440000	KTB MH 765015 S4E4	C.12
1195440000	KTB MH 765015 S4E4	C.32
1195450000	KTB MH 765020 S4E0	C.12
1195450000	KTB MH 765020 S4E0	C.33
1195460000	KTB MH 765020 S4E1	C.12
1195460000	KTB MH 765020 S4E1	C.33
1195470000	KTB MH 765020 S4E2	C.12
1195470000	KTB MH 765020 S4E2	C.33
1195480000	KTB MH 765020 S4E3	C.12
1195480000	KTB MH 765020 S4E3	C.33
1195490000	KTB MH 765020 S4E4	C.12
1195490000	KTB MH 765020 S4E4	C.33
1195500000	KTB MH 916115 S4E0	C.12
1195500000	KTB MH 916115 S4E0	C.34
1195510000	KTB MH 916115 S4E1	C.12
1195510000	KTB MH 916115 S4E1	C.34
1195520000	KTB MH 916115 S4E2	C.12
1195520000	KTB MH 916115 S4E2	C.34
1195530000	KTB MH 916115 S4E3	C.12
1195530000	KTB MH 916115 S4E3	C.34
1195540000	KTB MH 916115 S4E4	C.12
1195540000	KTB MH 916115 S4E4	C.34
1195550000	KTB MH 916120 S4E0	C.12
1195550000	KTB MH 916120 S4E0	C.35
1195560000	KTB MH 916120 S4E1	C.12
1195560000	KTB MH 916120 S4E1	C.35

Order No.	Type	Page
1195570000	KTB MH 916120 S4E2	C.12
1195570000	KTB MH 916120 S4E2	C.35
1195580000	KTB MH 916120 S4E3	C.12
1195580000	KTB MH 916120 S4E3	C.35
1195590000	KTB MH 916120 S4E4	C.12
1195590000	KTB MH 916120 S4E4	C.35
1195600000	KTB MH 987420 S4E0	C.12
1195600000	KTB MH 987420 S4E0	C.36
1195610000	KTB MH 987420 S4E1	C.12
1195610000	KTB MH 987420 S4E1	C.36
1195620000	KTB MH 987420 S4E2	C.12
1195620000	KTB MH 987420 S4E2	C.36
1195630000	KTB MH 987420 S4E3	C.12
1195630000	KTB MH 987420 S4E3	C.36
1195640000	KTB MH 987420 S4E4	C.12
1195640000	KTB MH 987420 S4E4	C.36
1195650000	KTB FS 221513 S4E0	C.40
1195660000	KTB FS 221513 S4E1	C.40
1195670000	KTB FS 221513 S4E2	C.40
1195680000	KTB FS 221513 S4E3	C.40
1195690000	KTB FS 221513 S4E4	C.40
1195700000	KTB FS 262615 S4E0	C.40
1195710000	KTB FS 262615 S4E1	C.40
1195720000	KTB FS 262615 S4E2	C.40
1195730000	KTB FS 262615 S4E3	C.40
1195740000	KTB FS 262615 S4E4	C.40
1195750000	KTB FS 262620 S4E0	C.40
1195760000	KTB FS 262620 S4E1	C.40
1195770000	KTB FS 262620 S4E2	C.40
1195780000	KTB FS 262620 S4E3	C.40
1195790000	KTB FS 262620 S4E4	C.40
1195800000	KTB FS 303015 S4E0	C.40
1195810000	KTB FS 303015 S4E1	C.40
1195820000	KTB FS 303015 S4E2	C.40
1195830000	KTB FS 303015 S4E3	C.40
1195840000	KTB FS 303015 S4E4	C.40
1195850000	KTB FS 303020 S4E0	C.40
1195860000	KTB FS 303020 S4E1	C.40
1195870000	KTB FS 303020 S4E2	C.40
1195880000	KTB FS 303020 S4E3	C.40
1195890000	KTB FS 303020 S4E4	C.40
1195900000	KTB FS 352615 S4E0	C.40
1195910000	KTB FS 352615 S4E1	C.40
1195920000	KTB FS 352615 S4E2	C.40
1195930000	KTB FS 352615 S4E3	C.40
1195940000	KTB FS 352615 S4E4	C.40
1195950000	KTB FS 352620 S4E0	C.40
1195960000	KTB FS 352620 S4E1	C.40
1195970000	KTB FS 352620 S4E2	C.40
1195980000	KTB FS 352620 S4E3	C.40
1195990000	KTB FS 352620 S4E4	C.40
1196000000	KTB FS 403015 S4E0	C.40
1196010000	KTB FS 403015 S4E1	C.40
1196020000	KTB FS 403015 S4E2	C.40
1196030000	KTB FS 403015 S4E3	C.40
1196040000	KTB FS 403015 S4E4	C.40
1196050000	KTB FS 403020 S4E0	C.40
1196060000	KTB FS 403020 S4E1	C.40
1196070000	KTB FS 403020 S4E2	C.40
1196080000	KTB FS 403020 S4E3	C.40
1196090000	KTB FS 403020 S4E4	C.40
1196100000	KTB FS 453815 S4E0	C.40
1196110000	KTB FS 453815 S4E1	C.40
1196120000	KTB FS 453815 S4E2	C.40
1196130000	KTB FS 453815 S4E3	C.40
1196140000	KTB FS 453815 S4E4	C.40
1196150000	KTB FS 453820 S4E0	C.40
1196160000	KTB FS 453820 S4E1	C.40
1196170000	KTB FS 453820 S4E2	C.40
1196180000	KTB FS 453820 S4E3	C.40
1196190000	KTB FS 453820 S4E4	C.40
1196200000	KTB FS 484815 S4E0	C.40
1196210000	KTB FS 484815 S4E1	C.40
1196220000	KTB FS 484815 S4E2	C.40
1196230000	KTB FS 484815 S4E3	C.40
1196240000	KTB FS 484815 S4E4	C.40
1196250000	KTB FS 484820 S4E0	C.40
1196260000	KTB FS 484820 S4E1	C.40
1196270000	KTB FS 484820 S4E2	C.40
1196280000	KTB FS 484820 S4E3	C.40
1196290000	KTB FS 484820 S4E4	C.40
1196300000	KTB FS 553515 S4E0	C.40
1196310000	KTB FS 553515 S4E1	C.40
1196320000	KTB FS 553515 S4E2	C.40
1196330000	KTB FS 553515 S4E3	C.40
1196340000	KTB FS 553515 S4E4	C.40
1196350000	KTB FS 553520 S4E0	C.40
1196360000	KTB FS 553520 S4E1	C.40
1196370000	KTB FS 553520 S4E2	C.40
1196380000	KTB FS 553520 S4E3	C.40
1196390000	KTB FS 553520 S4E4	C.40
1196400000	KTB FS 624515 S4E0	C.40
1196410000	KTB FS 624515 S4E1	C.40
1196420000	KTB FS 624515 S4E2	C.40
1196430000	KTB FS 624515 S4E3	C.40
1196440000	KTB FS 624515 S4E4	C.40
1196450000	KTB FS 624520 S4E0	C.40
1196460000	KTB FS 624520 S4E1	C.40
1196470000	KTB FS 624520 S4E2	C.40

Order No.	Type	Page
1196480000	KTB FS 624520 S4E3	C.40
1196490000	KTB FS 624520 S4E4	C.40
1196500000	KTB FS 765015 S4E0	C.40
1196510000	KTB FS 765015 S4E1	C.40
1196520000	KTB FS 765015 S4E2	C.40
1196530000	KTB FS 765015 S4E3	C.40
1196540000	KTB FS 765015 S4E4	C.40
1196550000	KTB FS 765020 S4E0	C.40
1196560000	KTB FS 765020 S4E1	C.40
1196570000	KTB FS 765020 S4E2	C.40
1196580000	KTB FS 765020 S4E3	C.40
1196590000	KTB FS 765020 S4E4	C.40
1196600000	KTB FS 916115 S4E0	C.40
1196610000	KTB FS 916115 S4E1	C.40
1196620000	KTB FS 916115 S4E2	C.40
1196630000	KTB FS 916115 S4E3	C.40
1196640000	KTB FS 916115 S4E4	C.40
1196650000	KTB FS 916120 S4E0	C.40
1196660000	KTB FS 916120 S4E1	C.40
1196670000	KTB FS 916120 S4E2	C.40
1196680000	KTB FS 916120 S4E3	C.40
1196690000	KTB FS 916120 S4E4	C.40
1196700000	KTB FS 987420 S4E0	C.40
1196710000	KTB FS 987420 S4E1	C.40
1196720000	KTB FS 987420 S4E2	C.40
1196730000	KTB FS 987420 S4E3	C.40
1196740000	KTB FS 987420 S4E4	C.40
1199850000	KTB QL 221513 S4E0	C.38
1199860000	KTB QL 221513 S4E1	C.38
1199870000	KTB QL 221513 S4E2	C.38
1199880000	KTB QL 221513 S4E3	C.38
1199890000	KTB QL 221513 S4E4	C.38
1199900000	KTB QL 262615 S4E0	C.38
1199910000	KTB QL 262615 S4E1	C.38
1199920000	KTB QL 262615 S4E2	C.38
1199930000	KTB QL 262615 S4E3	C.38
1199940000	KTB QL 262615 S4E4	C.38
1199950000	KTB QL 262620 S4E0	C.38
1199960000	KTB QL 262620 S4E1	C.38
1199970000	KTB QL 262620 S4E2	C.38
1199980000	KTB QL 262620 S4E3	C.38
1199990000	KTB QL 262620 S4E4	C.38

1200000000

1200010000	KTB QL 303015 S4E0	C.38
1200020000	KTB QL 303015 S4E1	C.38
1200030000	KTB QL 303015 S4E2	C.38
1200040000	KTB QL 303015 S4E3	C.38
1200050000	KTB QL 303015 S4E4	C.38
1200060000	KTB QL 303020 S4E0	C.38
1200070000	KTB QL 303020 S4E1	C.38
1200070000	KTB QL 303020 S4E1	C.46
1200080000	KTB QL 303020 S4E2	C.38
1200090000	KTB QL 303020 S4E3	C.38
1200100000	KTB QL 303020 S4E4	C.38
1200110000	KTB QL 352615 S4E0	C.38
1200120000	KTB QL 352615 S4E1	C.38
1200130000	KTB QL 352615 S4E2	C.38
1200140000	KTB QL 352615 S4E3	C.38
1200150000	KTB QL 352615 S4E4	C.38
1200160000	KTB QL 352620 S4E0	C.38
1200170000	KTB QL 352620 S4E1	C.38
1200180000	KTB QL 352620 S4E2	C.38
1200190000	KTB QL 352620 S4E3	C.38
1200210000	KTB QL 352620 S4E4	C.38
1200220000	KTB QL 403015 S4E0	C.38
1200230000	KTB QL 403015 S4E1	C.38
1200240000	KTB QL 403015 S4E2	C.38
1200250000	KTB QL 403015 S4E3	C.38
1200260000	KTB QL 403015 S4E4	C.38
1200270000	KTB QL 403020 S4E0	C.38
1200280000	KTB QL 403020 S4E1	C.38
1200290000	KTB QL 403020 S4E2	C.38
1200310000	KTB QL 403020 S4E3	C.38
1200320000	KTB QL 403020 S4E4	C.38
1200330000	KTB QL 453815 S4E0	C.38
1200340000	KTB QL 453815 S4E1	C.38
1200350000	KTB QL 453815 S4E2	C.38
1200360000	KTB QL 453815 S4E3	C.38
1200370000	KTB QL 453815 S4E4	C.38
1200380000	KTB QL 453820 S4E0	C.38
1200390000	KTB QL 453820 S4E1	C.38
1200410000	KTB QL 453820 S4E2	C.38
1200420000	KTB QL 453820 S4E3	C.38
1200430000	KTB QL 453820 S4E4	C.38
1200440000	KTB QL 484815 S4E0	C.38
1200450000	KTB QL 484815 S4E1	C.38
1200460000	KTB QL 484815 S4E2	C.38
1200470000	KTB QL 484815 S4E3	C.38
1200480000	KTB QL 484815 S4E4	C.38
1200490000	KTB QL 484820 S4E0	C.38
1200510000	KTB QL 484820 S4E1	C.38
1200510000	KTB QL 484820 S4E1	C.47
1200520000	KTB QL 484820 S4E2	C.38
1200530000	KTB QL 484820 S4E3	C.38
1200540000	KTB QL 484820 S4E4	C.38
1200550000	KTB QL 553515 S4E0	C.38
1200560000	KTB QL 553515 S4E1	C.38

Order No.	Type	Page
1200570000	KTB QL 553515 S4E2	C.38
1200580000	KTB QL 553515 S4E3	C.38
1200590000	KTB QL 553515 S4E4	C.38
1200610000	KTB QL 553520 S4E0	C.38
1200620000	KTB QL 553520 S4E1	C.38
1200630000	KTB QL 553520 S4E2	C.38
1200640000	KTB QL 553520 S4E3	C.38
1200650000	KTB QL 553520 S4E4	C.38
1200660000	KTB QL 624515 S4E0	C.38
1200670000	KTB QL 624515 S4E1	C.38
1200680000	KTB QL 624515 S4E2	C.38
1200690000	KTB QL 624515 S4E3	C.38
1200710000	KTB QL 624515 S4E4	C.38
1200720000	KTB QL 624520 S4E0	C.38
1200730000	KTB QL 624520 S4E1	C.38
1200740000	KTB QL 624520 S4E2	C.38
1200750000	KTB QL 624520 S4E3	C.38
1200760000	KTB QL 624520 S4E4	C.38
1200770000	KTB QL 765015 S4E0	C.38
1200780000	KTB QL 765015 S4E1	C.38
1200790000	KTB QL 765015 S4E2	C.38
1200810000	KTB QL 765015 S4E3	C.38
1200820000	KTB QL 765015 S4E4	C.38
1200830000	KTB QL 765020 S4E0	C.38
1200840000	KTB QL 765020 S4E1	C.38
1200850000	KTB QL 765020 S4E2	C.38
1200860000	KTB QL 765020 S4E3	C.38
1200870000	KTB QL 765020 S4E4	C.38
1200880000	KTB QL 916115 S4E0	C.38
1200890000	KTB QL 916115 S4E1	C.38
1200910000	KTB QL 916115 S4E2	C.38
1200920000	KTB QL 916115 S4E3	C.38
1200930000	KTB QL 916115 S4E4	C.38
1200940000	KTB QL 916120 S4E0	C.38
1200950000	KTB QL 916120 S4E1	C.38
1200960000	KTB QL 916120 S4E2	C.38
1200970000	KTB QL 916120 S4E3	C.38
1200980000	KTB QL 916120 S4E4	C.38
1200990000	KTB QL 987420 S4E0	C.38
1201010000	KTB QL 987420 S4E1	C.38
1201020000	KTB QL 987420 S4E2	C.38
1201030000	KTB QL 987420 S4E3	C.38
1201040000	KTB QL 987420 S4E4	C.38
1205890000	VGM40/1-MS68 20-32 BG	D.9
1205920000	VGM40/1-SS68 20-32 BG	D.14

1210000000

1210890000	VP M16 EXE MS	C.152
1210890000	VP M16 EXE MS	D.56
1210900000	VP M20 EXE MS	C.153
1210900000	VP M20 EXE MS	C.154
1210900000	VP M20 EXE MS	C.155
1210900000	VP M20 EXE MS	D.56
1210910000	VP M25 EXE MS	D.56
1210920000	VP M32 EXE MS	D.56
1210930000	VP M40 EXE MS	D.56
1210940000	VP M50 EXE MS	D.56
1210950000	VP M63 EXE MS	D.56

1250000000

1252190000	TPSD FIXING SET KTB	C.15
1252190000	TPSD FIXING SET KTB	C.16
1252190000	TPSD FIXING SET KTB	C.17
1252190000	TPSD FIXING SET KTB	C.18
1252190000	TPSD FIXING SET KTB	C.19
1252190000	TPSD FIXING SET KTB	C.20
1252190000	TPSD FIXING SET KTB	C.21
1252190000	TPSD FIXING SET KTB	C.22
1252190000	TPSD FIXING SET KTB	C.23
1252190000	TPSD FIXING SET KTB	C.24
1252190000	TPSD FIXING SET KTB	C.25
1252190000	TPSD FIXING SET KTB	C.26
1252190000	TPSD FIXING SET KTB	C.27
1252190000	TPSD FIXING SET KTB	C.28
1252190000	TPSD FIXING SET KTB	C.29
1252190000	TPSD FIXING SET KTB	C.30
1252190000	TPSD FIXING SET KTB	C.31
1252190000	TPSD FIXING SET KTB	C.32
1252190000	TPSD FIXING SET KTB	C.33
1252190000	TPSD FIXING SET KTB	C.34
1252190000	TPSD FIXING SET KTB	C.35
1252190000	TPSD FIXING SET KTB	C.36
1252730000	DOHA KTB A4 S2 R	C.26
1252730000	DOHA KTB A4 S2 R	C.27
1252730000	DOHA KTB A4 S2 R	C.28
1252730000	DOHA KTB A4 S2 R	C.29
1252730000	DOHA KTB A4 S2 R	C.30
1252730000	DOHA KTB A4 S2 R	C.31
1252730000	DOHA KTB A4 S2 R	C.32
1252730000	DOHA KTB A4 S2 R	C.33
1252730000	DOHA KTB A4 S2 R	C.34
1252730000	DOHA KTB A4 S2 R	C.35
1252730000	DOHA KTB A4 S2 R	C.36
1252730000	DOHA KTB A4 S2 R	C.47
1252750000	DOHA KTB A5 S2 R	C.24
1252750000	DOHA KTB A5 S2 R	C.25
1252750000	DOHA KTB A5 S2 R	C.26

Order No.	Type	Page
1252750000	DOHA KTB A5 S2 R	C.27
1252750000	DOHA KTB A5 S2 R	C.28
1252750000	DOHA KTB A5 S2 R	C.29
1252750000	DOHA KTB A5 S2 R	C.30
1252750000	DOHA KTB A5 S2 R	C.31
1252750000	DOHA KTB A5 S2 R	C.32
1252750000	DOHA KTB A5 S2 R	C.33
1252750000	DOHA KTB A5 S2 R	C.34
1252750000	DOHA KTB A5 S2 R	C.35
1252750000	DOHA KTB A5 S2 R	C.36
1252780000	DOHA KTB A6 S2 R	C.16
1252780000	DOHA KTB A6 S2 R	C.17
1252780000	DOHA KTB A6 S2 R	C.18
1252780000	DOHA KTB A6 S2 R	C.19
1252780000	DOHA KTB A6 S2 R	C.20
1252780000	DOHA KTB A6 S2 R	C.21
1252780000	DOHA KTB A6 S2 R	C.22
1252780000	DOHA KTB A6 S2 R	C.23
1252780000	DOHA KTB A6 S2 R	C.24
1252780000	DOHA KTB A6 S2 R	C.25
1252780000	DOHA KTB A6 S2 R	C.26
1252780000	DOHA KTB A6 S2 R	C.27
1252780000	DOHA KTB A6 S2 R	C.28
1252780000	DOHA KTB A6 S2 R	C.29
1252780000	DOHA KTB A6 S2 R	C.30
1252780000	DOHA KTB A6 S2 R	C.31
1252780000	DOHA KTB A6 S2 R	C.32
1252780000	DOHA KTB A6 S2 R	C.33
1252780000	DOHA KTB A6 S2 R	C.34
1252780000	DOHA KTB A6 S2 R	C.35
1252780000	DOHA KTB A6 S2 R	C.36
1252780000	DOHA KTB A6 S2 R	C.45
1252780000	DOHA KTB A6 S2 R	C.46
1252780000	DOHA KTB A6 S2 R	C.47
1253230000	DESC M6X14 KTB SET	C.15
1253230000	DESC M6X14 KTB SET	C.16
1253230000	DESC M6X14 KTB SET	C.17
1253230000	DESC M6X14 KTB SET	C.18
1253230000	DESC M6X14 KTB SET	C.19
1253230000	DESC M6X14 KTB SET	C.20
1253230000	DESC M6X14 KTB SET	C.21
1253230000	DESC M6X14 KTB SET	C.22
1253230000	DESC M6X14 KTB SET	C.23
1253230000	DESC M6X14 KTB SET	C.24
1253230000	DESC M6X14 KTB SET	C.25
1253230000	DESC M6X14 KTB SET	C.26
1253230000	DESC M6X14 KTB SET	C.27
1253230000	DESC M6X14 KTB SET	C.28
1253230000	DESC M6X14 KTB SET	C.29
1253230000	DESC M6X14 KTB SET	C.30
1253230000	DESC M6X14 KTB SET	C.31
1253230000	DESC M6X14 KTB SET	C.32
1253230000	DESC M6X14 KTB SET	C.33
1253230000	DESC M6X14 KTB SET	C.34
1253230000	DESC M6X14 KTB SET	C.35
1253230000	DESC M6X14 KTB SET	C.36
1253230000	DESC M6X14 KTB SET	C.44
1253230000	DESC M6X14 KTB SET	C.45
1253230000	DESC M6X14 KTB SET	C.46
1253230000	DESC M6X14 KTB SET	C.47
1256270000	KTB GP 221513 AB S4 6MM	C.15
1256270000	KTB GP 221513 AB S4 6MM	C.44
1256280000	KTB GP 221513 CD S4 6MM	C.15
1256290000	KTB GP 262615 AB S4 6MM	C.16
1256290000	KTB GP 262615 AB S4 6MM	C.45
1256310000	KTB GP 262615 CD S4 6MM	C.16
1256320000	KTB GP 262620 AB S4 6MM	C.17
1256330000	KTB GP 262620 CD S4 6MM	C.17
1256340000	KTB GP 303015 AB S4 6MM	C.18
1256350000	KTB GP 303015 CD S4 6MM	C.18
1256360000	KTB GP 303020 AB S4 6MM	C.19
1256360000	KTB GP 303020 AB S4 6MM	C.46
1256370000	KTB GP 303020 CD S4 6MM	C.19
1256380000	KTB GP 352615 AB S4 6MM	C.20
1256390000	KTB GP 352615 CD S4 6MM	C.20
1256410000	KTB GP 352620 AB S4 6MM	C.21
1256420000	KTB GP 352620 CD S4 6MM	C.21
1256430000	KTB GP 403015 AB S4 6MM	C.22
1256440000	KTB GP 403015 CD S4 6MM	C.22
1256450000	KTB GP 403020 AB S4 6MM	C.23
1256470000	KTB GP 403020 CD S4 6MM	C.23
1256480000	KTB GP 453815 AB S4 6MM	C.24
1256490000	KTB GP 453815 CD S4 6MM	C.24
1256510000	KTB GP 453820 AB S4 6MM	C.25
1256520000	KTB GP 453820 CD S4 6MM	C.25
1256530000	KTB GP 484815 AB S4 6MM	C.26
1256540000	KTB GP 484815 CD S4 6MM	C.26
1256550000	KTB GP 484820 AB S4 6MM	C.27
1256550000	KTB GP 484820 AB S4 6MM	C.47
1256560000	KTB GP 484820 CD S4 6MM	C.27
1256570000	KTB GP 553515 AB S4 6MM	C.28
1256580000	KTB GP 553515 CD S4 6MM	C.28
1256590000	KTB GP 553520 AB S4 6MM	C.29
1256610000	KTB GP 553520 CD S4 6MM	C.29
1256620000	KTB GP 624515 AB S4 6MM	C.30
1256630000	KTB GP 624515 CD S4 6MM	C.30
1256640000	KTB GP 624520 AB S4 6MM	C.31
1256650000	KTB GP 624520 CD S4 6MM	C.31
1256660000	KTB GP 765015 AB S4 6MM	C.32

Order No.	Type	Page
1256670000	KTB GP 765015 CD S4 6MM	C.32
1256680000	KTB GP 765020 AB S4 6MM	C.33
1256690000	KTB GP 765020 CD S4 6MM	C.33
1256710000	KTB GP 916115 AB S4 6MM	C.34
1256720000	KTB GP 916115 CD S4 6MM	C.34
1256730000	KTB GP 916120 AB S4 6MM	C.35
1256740000	KTB GP 916120 CD S4 6MM	C.35
1256750000	KTB GP 987420 AB S4 6MM	C.36
1256760000	KTB GP 987420 CD S4 6MM	C.36
1257640000	TPSDHA KTB 100X25 S2 2R	C.16
1257640000	TPSDHA KTB 100X25 S2 2R	C.17
1257640000	TPSDHA KTB 100X25 S2 2R	C.18
1257640000	TPSDHA KTB 100X25 S2 2R	C.19
1257640000	TPSDHA KTB 100X25 S2 2R	C.20
1257640000	TPSDHA KTB 100X25 S2 2R	C.21
1257640000	TPSDHA KTB 100X25 S2 2R	C.22
1257640000	TPSDHA KTB 100X25 S2 2R	C.23
1257640000	TPSDHA KTB 100X25 S2 2R	C.24
1257640000	TPSDHA KTB 100X25 S2 2R	C.25
1257640000	TPSDHA KTB 100X25 S2 2R	C.26
1257640000	TPSDHA KTB 100X25 S2 2R	C.27
1257640000	TPSDHA KTB 100X25 S2 2R	C.28
1257640000	TPSDHA KTB 100X25 S2 2R	C.29
1257640000	TPSDHA KTB 100X25 S2 2R	C.30
1257640000	TPSDHA KTB 100X25 S2 2R	C.31
1257640000	TPSDHA KTB 100X25 S2 2R	C.32
1257640000	TPSDHA KTB 100X25 S2 2R	C.33
1257640000	TPSDHA KTB 100X25 S2 2R	C.34
1257640000	TPSDHA KTB 100X25 S2 2R	C.35
1257640000	TPSDHA KTB 100X25 S2 2R	C.36
1257640000	TPSDHA KTB 100X25 S2 2R	C.45
1257640000	TPSDHA KTB 100X25 S2 2R	C.46
1257640000	TPSDHA KTB 100X25 S2 2R	C.47
1257650000	KTB MOPL 2215 S2N H	C.15
1257660000	KTB MOPL 2626 S2N H	C.16
1257660000	KTB MOPL 2626 S2N H	C.17
1257670000	KTB MOPL 3030 S2N H	C.18
1257670000	KTB MOPL 3030 S2N H	C.19
1257680000	KTB MOPL 3526 S2N H	C.20
1257680000	KTB MOPL 3526 S2N H	C.21
1257690000	KTB MOPL 4030 S2N H	C.22
1257690000	KTB MOPL 4030 S2N H	C.23
1257700000	KTB MOPL 4538 S2N H	C.24
1257700000	KTB MOPL 4538 S2N H	C.25
1257710000	KTB MOPL 4848 S2N H	C.26
1257710000	KTB MOPL 4848 S2N H	C.27
1257720000	KTB MOPL 5535 S2N H	C.28
1257720000	KTB MOPL 5535 S2N H	C.29
1257740000	KTB MOPL 6245 S2N H	C.30
1257740000	KTB MOPL 6245 S2N H	C.31
1257750000	KTB MOPL 7650 S2N H	C.32
1257750000	KTB MOPL 7650 S2N H	C.33
1257760000	KTB MOPL 9161 S2N H	C.34
1257760000	KTB MOPL 9161 S2N H	C.35
1257770000	KTB MOPL 9874 S2N H	C.36

1270000000

Order No.	Type	Page
1274150000	GFSC M5x10 TX20 SET	C.15
1274150000	GFSC M5x10 TX20 SET	C.16
1274150000	GFSC M5x10 TX20 SET	C.17
1274150000	GFSC M5x10 TX20 SET	C.18
1274150000	GFSC M5x10 TX20 SET	C.19
1274150000	GFSC M5x10 TX20 SET	C.20
1274150000	GFSC M5x10 TX20 SET	C.21
1274150000	GFSC M5x10 TX20 SET	C.22
1274150000	GFSC M5x10 TX20 SET	C.23
1274150000	GFSC M5x10 TX20 SET	C.24
1274150000	GFSC M5x10 TX20 SET	C.25
1274150000	GFSC M5x10 TX20 SET	C.26
1274150000	GFSC M5x10 TX20 SET	C.27
1274150000	GFSC M5x10 TX20 SET	C.28
1274150000	GFSC M5x10 TX20 SET	C.29
1274150000	GFSC M5x10 TX20 SET	C.30
1274150000	GFSC M5x10 TX20 SET	C.31
1274150000	GFSC M5x10 TX20 SET	C.32
1274150000	GFSC M5x10 TX20 SET	C.33
1274150000	GFSC M5x10 TX20 SET	C.34
1274150000	GFSC M5x10 TX20 SET	C.35
1274150000	GFSC M5x10 TX20 SET	C.36
1274150000	GFSC M5x10 TX20 SET	C.52
1274150000	GFSC M5x10 TX20 SET	C.53
1274150000	GFSC M5x10 TX20 SET	C.54
1274150000	GFSC M5x10 TX20 SET	C.55
1274150000	GFSC M5x10 TX20 SET	C.56
1274150000	GFSC M5x10 TX20 SET	C.57
1274150000	GFSC M5x10 TX20 SET	C.58
1274150000	GFSC M5x10 TX20 SET	C.59
1274150000	GFSC M5x10 TX20 SET	C.60
1274150000	GFSC M5x10 TX20 SET	C.61
1274150000	GFSC M5x10 TX20 SET	C.62
1277220000	PEBZ M10 BR SET	C.106
1277220000	PEBZ M10 BR SET	C.107
1277220000	PEBZ M10 BR SET	C.108
1277220000	PEBZ M10 BR SET	C.109
1277220000	PEBZ M10 BR SET	C.110
1277220000	PEBZ M10 BR SET	C.111
1277220000	PEBZ M10 BR SET	C.112
1277220000	PEBZ M10 BR SET	C.113

Order No.	Type	Page
1277220000	PEBZ M10 BR SET	C.114
1277220000	PEBZ M10 BR SET	C.132
1277220000	PEBZ M10 BR SET	C.133
1277220000	PEBZ M10 BR SET	C.134
1277220000	PEBZ M10 BR SET	C.135
1277220000	PEBZ M10 BR SET	C.136
1277220000	PEBZ M10 BR SET	C.137
1277220000	PEBZ M10 BR SET	C.138
1277220000	PEBZ M10 BR SET	C.139
1277220000	PEBZ M10 BR SET	C.140
1277220000	PEBZ M10 BR SET	C.141
1277220000	PEBZ M10 BR SET	C.142
1277220000	PEBZ M10 BR SET	C.143
1277220000	PEBZ M10 BR SET	C.144
1277220000	PEBZ M10 BR SET	C.145
1277220000	PEBZ M10 BR SET	C.146
1277220000	PEBZ M10 BR SET	C.147
1277220000	PEBZ M10 BR SET	C.148
1277220000	PEBZ M10 BR SET	C.170
1277220000	PEBZ M10 BR SET	C.171
1277220000	PEBZ M10 BR SET	C.172
1277220000	PEBZ M10 BR SET	C.173
1277220000	PEBZ M10 BR SET	C.174
1277220000	PEBZ M10 BR SET	C.178
1277220000	PEBZ M10 BR SET	C.179
1277220000	PEBZ M10 BR SET	C.180
1277220000	PEBZ M10 BR SET	C.181
1277220000	PEBZ M10 BR SET	C.182
1277220000	PEBZ M10 BR SET	C.183
1277220000	PEBZ M10 BR SET	C.185
1277220000	PEBZ M10 BR SET	C.186
1277220000	PEBZ M10 BR SET	C.187
1277250000	PEBZ M6 BR SET	C.99
1277250000	PEBZ M6 BR SET	C.100
1277250000	PEBZ M6 BR SET	C.101
1277250000	PEBZ M6 BR SET	C.102
1277250000	PEBZ M6 BR SET	C.103
1277250000	PEBZ M6 BR SET	C.104
1277250000	PEBZ M6 BR SET	C.105
1277250000	PEBZ M6 BR SET	C.106
1277250000	PEBZ M6 BR SET	C.107
1277250000	PEBZ M6 BR SET	C.108
1277250000	PEBZ M6 BR SET	C.109
1277250000	PEBZ M6 BR SET	C.110
1277250000	PEBZ M6 BR SET	C.111
1277250000	PEBZ M6 BR SET	C.112
1277250000	PEBZ M6 BR SET	C.113
1277250000	PEBZ M6 BR SET	C.114
1277250000	PEBZ M6 BR SET	C.132
1277250000	PEBZ M6 BR SET	C.133
1277250000	PEBZ M6 BR SET	C.134
1277250000	PEBZ M6 BR SET	C.135
1277250000	PEBZ M6 BR SET	C.136
1277250000	PEBZ M6 BR SET	C.137
1277250000	PEBZ M6 BR SET	C.138
1277250000	PEBZ M6 BR SET	C.139
1277250000	PEBZ M6 BR SET	C.140
1277250000	PEBZ M6 BR SET	C.141
1277250000	PEBZ M6 BR SET	C.142
1277250000	PEBZ M6 BR SET	C.143
1277250000	PEBZ M6 BR SET	C.144
1277250000	PEBZ M6 BR SET	C.145
1277250000	PEBZ M6 BR SET	C.146
1277250000	PEBZ M6 BR SET	C.147
1277250000	PEBZ M6 BR SET	C.148
1277250000	PEBZ M6 BR SET	C.170
1277250000	PEBZ M6 BR SET	C.171
1277250000	PEBZ M6 BR SET	C.172
1277250000	PEBZ M6 BR SET	C.173
1277250000	PEBZ M6 BR SET	C.174
1277250000	PEBZ M6 BR SET	C.178
1277250000	PEBZ M6 BR SET	C.179
1277250000	PEBZ M6 BR SET	C.180
1277250000	PEBZ M6 BR SET	C.181
1277250000	PEBZ M6 BR SET	C.182
1277250000	PEBZ M6 BR SET	C.183
1277250000	PEBZ M6 BR SET	C.185
1277250000	PEBZ M6 BR SET	C.186
1277250000	PEBZ M6 BR SET	C.187
1279320000	TPSDHA KTB 70X70M3 S2 R	C.15
1279320000	TPSDHA KTB 70X70M3 S2 R	C.16
1279320000	TPSDHA KTB 70X70M3 S2 R	C.17
1279320000	TPSDHA KTB 70X70M3 S2 R	C.18
1279320000	TPSDHA KTB 70X70M3 S2 R	C.19
1279320000	TPSDHA KTB 70X70M3 S2 R	C.20
1279320000	TPSDHA KTB 70X70M3 S2 R	C.21
1279320000	TPSDHA KTB 70X70M3 S2 R	C.22
1279320000	TPSDHA KTB 70X70M3 S2 R	C.23
1279320000	TPSDHA KTB 70X70M3 S2 R	C.24
1279320000	TPSDHA KTB 70X70M3 S2 R	C.25
1279320000	TPSDHA KTB 70X70M3 S2 R	C.26
1279320000	TPSDHA KTB 70X70M3 S2 R	C.27
1279320000	TPSDHA KTB 70X70M3 S2 R	C.28
1279320000	TPSDHA KTB 70X70M3 S2 R	C.29
1279320000	TPSDHA KTB 70X70M3 S2 R	C.30
1279320000	TPSDHA KTB 70X70M3 S2 R	C.31
1279320000	TPSDHA KTB 70X70M3 S2 R	C.32
1279320000	TPSDHA KTB 70X70M3 S2 R	C.33
1279320000	TPSDHA KTB 70X70M3 S2 R	C.34

Order No.	Type	Page
1279320000	TPSDHA KTB 70X70M3 S2 R	C.35
1279320000	TPSDHA KTB 70X70M3 S2 R	C.36
1279320000	TPSDHA KTB 70X70M3 S2 R	C.44
1279320000	TPSDHA KTB 70X70M3 S2 R	C.45
1279320000	TPSDHA KTB 70X70M3 S2 R	C.46
1279320000	TPSDHA KTB 70X70M3 S2 R	C.47

1280000000

Order No.	Type	Page
1280890000	KTB GP 221513 AB S4	C.44
1280910000	KTB GP 262615 AB S4	C.45
1280970000	KTB GP 303020 AB S4	C.46
1281130000	KTB GP 484820 AB S4	C.47
1281360000	KTB RNHD 221513 R	C.15
1281360000	KTB RNHD 221513 R	C.44
1281370000	KTB RNHD 262615 R	C.16
1281370000	KTB RNHD 262615 R	C.45
1281380000	KTB RNHD 262620 R	C.17
1281390000	KTB RNHD 303015 R	C.18
1281400000	KTB RNHD 303020 R	C.19
1281400000	KTB RNHD 303020 R	C.46
1281410000	KTB RNHD 352615 R	C.20
1281420000	KTB RNHD 352620 R	C.21
1281430000	KTB RNHD 403015 R	C.22
1281440000	KTB RNHD 403020 R	C.23
1281450000	KTB RNHD 453815 R	C.24
1281460000	KTB RNHD 453820 R	C.25
1281470000	KTB RNHD 484815 R	C.26
1281480000	KTB RNHD 484820 R	C.27
1281480000	KTB RNHD 484820 R	C.47
1281490000	KTB RNHD 553515 R	C.28
1281500000	KTB RNHD 553520 R	C.29
1281510000	KTB RNHD 624515 R	C.30
1281520000	KTB RNHD 624520 R	C.31
1281530000	KTB RNHD 765015 R	C.32
1281540000	KTB RNHD 765020 R	C.33
1281550000	KTB RNHD 916115 R	C.34
1281570000	KTB RNHD 916120 R	C.35
1281580000	KTB RNHD 987420 R	C.36
1283430000	PEBZ M6 S4 SET	C.99
1283430000	PEBZ M6 S4 SET	C.100
1283430000	PEBZ M6 S4 SET	C.101
1283430000	PEBZ M6 S4 SET	C.102
1283430000	PEBZ M6 S4 SET	C.103
1283430000	PEBZ M6 S4 SET	C.104
1283430000	PEBZ M6 S4 SET	C.105
1283430000	PEBZ M6 S4 SET	C.106
1283430000	PEBZ M6 S4 SET	C.107
1283430000	PEBZ M6 S4 SET	C.108
1283430000	PEBZ M6 S4 SET	C.109
1283430000	PEBZ M6 S4 SET	C.110
1283430000	PEBZ M6 S4 SET	C.111
1283430000	PEBZ M6 S4 SET	C.112
1283430000	PEBZ M6 S4 SET	C.113
1283430000	PEBZ M6 S4 SET	C.114
1283430000	PEBZ M6 S4 SET	C.132
1283430000	PEBZ M6 S4 SET	C.133
1283430000	PEBZ M6 S4 SET	C.134
1283430000	PEBZ M6 S4 SET	C.135
1283430000	PEBZ M6 S4 SET	C.136
1283430000	PEBZ M6 S4 SET	C.137
1283430000	PEBZ M6 S4 SET	C.138
1283430000	PEBZ M6 S4 SET	C.139
1283430000	PEBZ M6 S4 SET	C.140
1283430000	PEBZ M6 S4 SET	C.141
1283430000	PEBZ M6 S4 SET	C.142
1283430000	PEBZ M6 S4 SET	C.143
1283430000	PEBZ M6 S4 SET	C.144
1283430000	PEBZ M6 S4 SET	C.145
1283430000	PEBZ M6 S4 SET	C.146
1283430000	PEBZ M6 S4 SET	C.147
1283430000	PEBZ M6 S4 SET	C.148
1283430000	PEBZ M6 S4 SET	C.170
1283430000	PEBZ M6 S4 SET	C.171
1283430000	PEBZ M6 S4 SET	C.172
1283430000	PEBZ M6 S4 SET	C.173
1283430000	PEBZ M6 S4 SET	C.174
1283430000	PEBZ M6 S4 SET	C.178
1283430000	PEBZ M6 S4 SET	C.179
1283430000	PEBZ M6 S4 SET	C.180
1283430000	PEBZ M6 S4 SET	C.181
1283430000	PEBZ M6 S4 SET	C.182
1283430000	PEBZ M6 S4 SET	C.183
1283430000	PEBZ M6 S4 SET	C.185
1283430000	PEBZ M6 S4 SET	C.186
1283430000	PEBZ M6 S4 SET	C.187
1283440000	PEBZ M10 S4 SET	C.106
1283440000	PEBZ M10 S4 SET	C.107
1283440000	PEBZ M10 S4 SET	C.108
1283440000	PEBZ M10 S4 SET	C.109
1283440000	PEBZ M10 S4 SET	C.110
1283440000	PEBZ M10 S4 SET	C.111
1283440000	PEBZ M10 S4 SET	C.112
1283440000	PEBZ M10 S4 SET	C.113
1283440000	PEBZ M10 S4 SET	C.114
1283440000	PEBZ M10 S4 SET	C.132
1283440000	PEBZ M10 S4 SET	C.133
1283440000	PEBZ M10 S4 SET	C.134
1283440000	PEBZ M10 S4 SET	C.135

Order No.	Type	Page
1283440000	PEBZ M10 S4 SET	C.136
1283440000	PEBZ M10 S4 SET	C.137
1283440000	PEBZ M10 S4 SET	C.138
1283440000	PEBZ M10 S4 SET	C.139
1283440000	PEBZ M10 S4 SET	C.140
1283440000	PEBZ M10 S4 SET	C.141
1283440000	PEBZ M10 S4 SET	C.142
1283440000	PEBZ M10 S4 SET	C.143
1283440000	PEBZ M10 S4 SET	C.144
1283440000	PEBZ M10 S4 SET	C.145
1283440000	PEBZ M10 S4 SET	C.146
1283440000	PEBZ M10 S4 SET	C.147
1283440000	PEBZ M10 S4 SET	C.148
1283440000	PEBZ M10 S4 SET	C.170
1283440000	PEBZ M10 S4 SET	C.171
1283440000	PEBZ M10 S4 SET	C.172
1283440000	PEBZ M10 S4 SET	C.173
1283440000	PEBZ M10 S4 SET	C.174
1283440000	PEBZ M10 S4 SET	C.178
1283440000	PEBZ M10 S4 SET	C.179
1283440000	PEBZ M10 S4 SET	C.180
1283440000	PEBZ M10 S4 SET	C.181
1283440000	PEBZ M10 S4 SET	C.182
1283440000	PEBZ M10 S4 SET	C.183
1283440000	PEBZ M10 S4 SET	C.185
1283440000	PEBZ M10 S4 SET	C.186
1283440000	PEBZ M10 S4 SET	C.187
1283450000	TPSDHA KTB 130X50 S2 R	C.16
1283450000	TPSDHA KTB 130X50 S2 R	C.17
1283450000	TPSDHA KTB 130X50 S2 R	C.18
1283450000	TPSDHA KTB 130X50 S2 R	C.19
1283450000	TPSDHA KTB 130X50 S2 R	C.20
1283450000	TPSDHA KTB 130X50 S2 R	C.21
1283450000	TPSDHA KTB 130X50 S2 R	C.22
1283450000	TPSDHA KTB 130X50 S2 R	C.23
1283450000	TPSDHA KTB 130X50 S2 R	C.24
1283450000	TPSDHA KTB 130X50 S2 R	C.25
1283450000	TPSDHA KTB 130X50 S2 R	C.26
1283450000	TPSDHA KTB 130X50 S2 R	C.27
1283450000	TPSDHA KTB 130X50 S2 R	C.28
1283450000	TPSDHA KTB 130X50 S2 R	C.29
1283450000	TPSDHA KTB 130X50 S2 R	C.30
1283450000	TPSDHA KTB 130X50 S2 R	C.31
1283450000	TPSDHA KTB 130X50 S2 R	C.32
1283450000	TPSDHA KTB 130X50 S2 R	C.33
1283450000	TPSDHA KTB 130X50 S2 R	C.34
1283450000	TPSDHA KTB 130X50 S2 R	C.35
1283450000	TPSDHA KTB 130X50 S2 R	C.36
1283450000	TPSDHA KTB 130X50 S2 R	C.45
1283450000	TPSDHA KTB 130X50 S2 R	C.46
1283450000	TPSDHA KTB 130X50 S2 R	C.47
1285200000	SD FIXING SET	C.15
1285200000	SD FIXING SET	C.16
1285200000	SD FIXING SET	C.17
1285200000	SD FIXING SET	C.18
1285200000	SD FIXING SET	C.19
1285200000	SD FIXING SET	C.20
1285200000	SD FIXING SET	C.21
1285200000	SD FIXING SET	C.22
1285200000	SD FIXING SET	C.23
1285200000	SD FIXING SET	C.24
1285200000	SD FIXING SET	C.25
1285200000	SD FIXING SET	C.26
1285200000	SD FIXING SET	C.27
1285200000	SD FIXING SET	C.28
1285200000	SD FIXING SET	C.29
1285200000	SD FIXING SET	C.30
1285200000	SD FIXING SET	C.31
1285200000	SD FIXING SET	C.32
1285200000	SD FIXING SET	C.33
1285200000	SD FIXING SET	C.34
1285200000	SD FIXING SET	C.35
1285200000	SD FIXING SET	C.36
1289180000	KEBI-KTBI MF S2 SET	C.52
1289180000	KEBI-KTBI MF S2 SET	C.53
1289180000	KEBI-KTBI MF S2 SET	C.54
1289180000	KEBI-KTBI MF S2 SET	C.55
1289180000	KEBI-KTBI MF S2 SET	C.56
1289180000	KEBI-KTBI MF S2 SET	C.57
1289180000	KEBI-KTBI MF S2 SET	C.58
1289180000	KEBI-KTBI MF S2 SET	C.59
1289180000	KEBI-KTBI MF S2 SET	C.60
1289180000	KEBI-KTBI MF S2 SET	C.61
1289180000	KEBI-KTBI MF S2 SET	C.62

1300000000

Order No.	Type	Page
1305810000	KLIPPON POK 080806	C.130
1305810000	KLIPPON POK 080806	C.132
1305810000	KLIPPON POK 080806	C.150
1305820000	KLIPPON POK 081106	C.130
1305820000	KLIPPON POK 081106	C.133
1305820000	KLIPPON POK 081106	C.150
1305830000	KLIPPON POK 081606	C.130
1305830000	KLIPPON POK 081606	C.134
1305830000	KLIPPON POK 081606	C.150
1305840000	KLIPPON POK 081906	C.130
1305840000	KLIPPON POK 081906	C.135
1305850000	KLIPPON POK 082306	C.130
1305850000	KLIPPON POK 082306	C.136
1305870000	KLIPPON POK 121209	C.130
1305870000	KLIPPON POK 121209	C.137
1305870000	KLIPPON POK 121209	C.150
1305880000	KLIPPON POK 122209	C.130
1305880000	KLIPPON POK 122209	C.138
1305890000	KLIPPON POK 161609	C.130
1305890000	KLIPPON POK 161609	C.139
1305890000	KLIPPON POK 161609	C.150
1305900000	KLIPPON POK 162609	C.130
1305900000	KLIPPON POK 162609	C.140
1305910000	KLIPPON POK 163609	C.130
1305910000	KLIPPON POK 163609	C.141
1305920000	KLIPPON POK 165609	C.130
1305920000	KLIPPON POK 165609	C.142
1305930000	KLIPPON POK 252512	C.130
1305930000	KLIPPON POK 252512	C.143
1305940000	KLIPPON POK 254012	C.130
1305940000	KLIPPON POK 254012	C.145
1305950000	KLIPPON POK 256012	C.130
1305950000	KLIPPON POK 256012	C.147
1305970000	KLIPPON POK 404012	C.130
1305970000	KLIPPON POK 404012	C.148
1305980000	KLIPPON POK 252516	C.130
1305980000	KLIPPON POK 252516	C.144
1305990000	KLIPPON POK 254016	C.130
1305990000	KLIPPON POK 254016	C.146
1306000000	KLIPPON POK 080806 EX	C.130
1306000000	KLIPPON POK 080806 EX	C.132
1306010000	KLIPPON POK 081106 EX	C.130
1306010000	KLIPPON POK 081106 EX	C.133
1306020000	KLIPPON POK 081606 EX	C.130
1306020000	KLIPPON POK 081606 EX	C.134
1306030000	KLIPPON POK 081906 EX	C.130
1306030000	KLIPPON POK 081906 EX	C.135
1306040000	KLIPPON POK 082306 EX	C.130
1306040000	KLIPPON POK 082306 EX	C.136
1306050000	KLIPPON POK 121209 EX	C.130
1306050000	KLIPPON POK 121209 EX	C.137
1306070000	KLIPPON POK 122209 EX	C.130
1306070000	KLIPPON POK 122209 EX	C.138
1306080000	KLIPPON POK 161609 EX	C.130
1306080000	KLIPPON POK 161609 EX	C.139
1306090000	KLIPPON POK 162609 EX	C.130
1306090000	KLIPPON POK 162609 EX	C.140
1306100000	KLIPPON POK 163609 EX	C.130
1306100000	KLIPPON POK 163609 EX	C.141
1306110000	KLIPPON POK 165609 EX	C.130
1306110000	KLIPPON POK 165609 EX	C.142
1306120000	KLIPPON POK 252512 EX	C.130
1306120000	KLIPPON POK 252512 EX	C.143
1306130000	KLIPPON POK 254012 EX	C.130
1306130000	KLIPPON POK 254012 EX	C.145
1306140000	KLIPPON POK 256012 EX	C.130
1306140000	KLIPPON POK 256012 EX	C.147
1306150000	KLIPPON POK 404012 EX	C.130
1306150000	KLIPPON POK 404012 EX	C.148
1306170000	KLIPPON POK 252516 EX	C.130
1306170000	KLIPPON POK 252516 EX	C.144
1306180000	KLIPPON POK 254016 EX	C.130
1306180000	KLIPPON POK 254016 EX	C.146
1309690000	KEBI-KTBI MOPL 3020 MSZN	C.52
1309700000	KEBI-KTBI MOPL 3020 S2N	C.52

1310000000

Order No.	Type	Page
1310320000	KEBI-KTBI MOPL 3030 S2N	C.53
1310320000	KEBI-KTBI MOPL 3030 S2N	C.54
1310330000	KEBI-KTBI MOPL 4030 S2N	C.55
1310330000	KEBI-KTBI MOPL 4030 S2N	C.56
1310340000	KEBI-KTBI MOPL 4040 S2N	C.57
1310350000	KEBI-KTBI MOPL 5040 S2N	C.58
1310360000	KEBI-KTBI MOPL 5050 S2N	C.59
1310370000	KEBI-KTBI MOPL 6040 S2N	C.60
1310380000	KEBI-KTBI MOPL 6060 S2N	C.61
1310390000	KEBI-KTBI MOPL 8060 S2N	C.62
1310410000	KEBI-KTBI MOPL 3030 MSZN	C.53
1310410000	KEBI-KTBI MOPL 3030 MSZN	C.54
1310420000	KEBI-KTBI MOPL 4030 MSZN	C.55
1310420000	KEBI-KTBI MOPL 4030 MSZN	C.56
1310430000	KEBI-KTBI MOPL 4040 MSZN	C.57
1310440000	KEBI-KTBI MOPL 5040 MSZN	C.58
1310450000	KEBI-KTBI MOPL 5050 MSZN	C.59
1310460000	KEBI-KTBI MOPL 6040 MSZN	C.60
1310470000	KEBI-KTBI MOPL 6060 MSZN	C.61
1310480000	KEBI-KTBI MOPL 8060 MSZN	C.62
1314090000	KTB RNHD 221513 S4E R	C.15
1314100000	KTB RNHD 262615 S4E R	C.16
1314110000	KTB RNHD 262620 S4E R	C.17
1314120000	KTB RNHD 303015 S4E R	C.18
1314130000	KTB RNHD 303020 S4E R	C.19
1314140000	KTB RNHD 352615 S4E R	C.20
1314150000	KTB RNHD 352620 S4E R	C.21
1314170000	KTB RNHD 403015 S4E R	C.22
1314180000	KTB RNHD 403020 S4E R	C.23
1314190000	KTB RNHD 453815 S4E R	C.24
1314200000	KTB RNHD 453820 S4E R	C.25
1314220000	KTB RNHD 484815 S4E R	C.26
1314230000	KTB RNHD 484820 S4E R	C.27
1314240000	KTB RNHD 553515 S4E R	C.28
1314250000	KTB RNHD 553520 S4E R	C.29
1314270000	KTB RNHD 624515 S4E R	C.30
1314280000	KTB RNHD 624520 S4E R	C.31
1314290000	KTB RNHD 765015 S4E R	C.32
1314300000	KTB RNHD 765020 S4E R	C.33
1314320000	KTB RNHD 916115 S4E R	C.34
1314330000	KTB RNHD 916120 S4E R	C.35
1314340000	KTB RNHD 987420 S4E R	C.36

1320000000

Order No.	Type	Page
1328120000	KLIPPON K21 EX RAL7001	C.94
1328130000	KLIPPON K51 EX RAL7001	C.94
1328140000	KLIPPON K61 EX RAL7001	C.94
1329630000	KLIPPON K1 EX RAL7001	C.94
1329640000	KLIPPON K11 EX RAL7001	C.94
1329650000	KLIPPON K2 EX RAL7001	C.94
1329670000	KLIPPON K3 EX RAL7001	C.94
1329680000	KLIPPON K31 EX RAL7001	C.94
1329690000	KLIPPON K32 EX RAL7001	C.94
1329700000	KLIPPON K4 EX RAL7001	C.94
1329710000	KLIPPON K41 EX RAL7001	C.94
1329720000	KLIPPON K5 EX RAL7001	C.94
1329730000	KLIPPON K52 EX RAL7001	C.94
1329740000	KLIPPON K6 EX RAL7001	C.94
1329750000	KLIPPON K7 EX RAL7001	C.94
1329770000	KLIPPON K71 EX RAL7001	C.94

1390000000

Order No.	Type	Page
1390910000	KLIPPON COPL 080806	C.132
1390920000	KLIPPON COPL 081106	C.133
1390930000	KLIPPON COPL 081606	C.134
1390940000	KLIPPON COPL 081906	C.135
1390950000	KLIPPON COPL 082306	C.136
1390970000	KLIPPON COPL 121209	C.137
1390980000	KLIPPON COPL 122209	C.138
1390990000	KLIPPON COPL 161609	C.139
1391000000	KLIPPON COPL 162609	C.140
1391010000	KLIPPON COPL 163609	C.141
1391020000	KLIPPON COPL 165609	C.142
1391030000	KLIPPON COPL 252512/16	C.143
1391030000	KLIPPON COPL 252512/16	C.144
1391040000	KLIPPON COPL 254012/16	C.145
1391040000	KLIPPON COPL 254012/16	C.146
1391050000	KLIPPON COPL 256012	C.147
1391070000	KLIPPON COPL 404012	C.148

1460000000

Order No.	Type	Page
1460040000	VG M16 EXE MS	C.44
1460040000	VG M16 EXE MS	C.78
1460040000	VG M16 EXE MS	C.152
1460050000	VG M20 EXE MS	C.44
1460050000	VG M20 EXE MS	C.45
1460050000	VG M20 EXE MS	C.46
1460050000	VG M20 EXE MS	C.47
1460050000	VG M20 EXE MS	C.79
1460050000	VG M20 EXE MS	C.80
1460050000	VG M20 EXE MS	C.153
1460050000	VG M20 EXE MS	C.154
1460050000	VG M20 EXE MS	C.155
1460050000	VG M20 EXE MS	C.156
1460070000	VG M25 EXE MS	C.47
1460070000	VG M25 EXE MS	C.81
1460080000	VG M32 EXE MS	C.45
1460080000	VG M32 EXE MS	C.46
1460090000	VG M40 EXE MS	C.47
1463720000	VGM25-MS68 EMC 11-20SET	D.12
1463730000	VGM32-MS68 EMC 15-25SET	D.12

1470000000

Order No.	Type	Page
1477740000	KSPMH M16 BSC	D.57
1477750000	KSPMH M20 BSC	D.57
1477770000	KSPMH M25 BSC	D.57
1477780000	KSPMH M32 BSC	D.57
1477790000	KSPMH M40 BSC	D.57
1477800000	KSPMH M50 BSC	D.57
1477810000	KSPMH M63 BSC	D.57
1477820000	KSPMH M16 SSC	C.44
1477820000	KSPMH M16 SSC	C.78
1477820000	KSPMH M16 SSC	D.57
1477830000	KSPMH M75 BSC	D.57
1477840000	KSPMH M20 SSC	C.44
1477840000	KSPMH M20 SSC	C.45
1477840000	KSPMH M20 SSC	C.46
1477840000	KSPMH M20 SSC	C.47
1477840000	KSPMH M20 SSC	C.79
1477840000	KSPMH M20 SSC	C.80
1477840000	KSPMH M20 SSC	D.57
1477870000	KSPMH M25 SSC	C.47
1477870000	KSPMH M25 SSC	C.81
1477870000	KSPMH M25 SSC	D.57
1477890000	KSPMH M32 SSC	C.45
1477890000	KSPMH M32 SSC	C.46
1477890000	KSPMH M32 SSC	D.57
1477910000	KSPMH M40 SSC	C.47
1477910000	KSPMH M40 SSC	D.57
1477930000	KSPMH M50 SSC	D.57
1477950000	KSPMH M63 SSC	D.57
1477980000	KSPMH M75 SSC	D.57

1530000000

Order No.	Type	Page
1534280000	POK MOPL 0808 MINI	C.132
1534290000	POK MOPL 0811 MINI	C.133
1534310000	POK MOPL 0816 MINI	C.134
1534320000	POK MOPL 0819 MINI	C.135
1534330000	POK MOPL 0823 MINI	C.136
1534340000	POK MOPL 1212 MINI	C.137
1534350000	POK MOPL 1222 MINI	C.138
1534360000	POK MOPL 1616 MINI	C.139
1534370000	POK MOPL 1626 MINI	C.140
1534380000	POK MOPL 1636 MINI	C.141
1534390000	POK MOPL 1656 MINI	C.142
1534410000	POK MOPL 2525 MINI	C.143
1534410000	POK MOPL 2525 MINI	C.144
1534420000	POK MOPL 2540 MINI	C.145
1534420000	POK MOPL 2540 MINI	C.146
1534430000	POK MOPL 2560 MINI	C.147
1534440000	POK MOPL 4040 MINI	C.148
1537070000	KLIPPON CS POK 121209-2	C.162
1537080000	KLIPPON CS POK 121209-2	C.162
1537090000	KLIPPON CS POK 121209-2	C.163
1537100000	KLIPPON CS POK 121209-2	C.163
1537110000	KLIPPON CS POK 121209-4	C.163
1537120000	KLIPPON CS POK 121209-4	C.164
1537130000	KLIPPON CS POK 121209-4	C.164
1537140000	KLIPPON CS POK 122209-2	C.165
1537150000	KLIPPON CS POK 122209-2	C.165
1537170000	KLIPPON CS POK 122209-2	C.165
1537180000	KLIPPON CS POK 122209-4	C.166
1537200000	KLIPPON CS STB 1-1	C.86
1537210000	KLIPPON CS STB 1-1	C.86
1537220000	KLIPPON CS STB 1-1	C.87
1537230000	KLIPPON CS STB 1-1	C.87
1537240000	KLIPPON CS STB 1-2	C.87
1537250000	KLIPPON CS STB 1-2	C.88
1537280000	KLIPPON CS STB 1-2	C.88
1537290000	KLIPPON CS STB 1-2	C.89
1537300000	KLIPPON CS STB 2.1-2	C.89
1537310000	KLIPPON CS STB 2.1-2	C.89
1537320000	KLIPPON CS STB 2.1-2	C.90
1537330000	KLIPPON CS STB 2.1-6	C.90
1537340000	KLIPPON CS STB 2.1-7	C.91
1537370000	KLIPPON CS STB 2.1-7	C.91
1537470000	KLIPPON CS K41-1	C.122
1537480000	KLIPPON CS K41-1	C.122
1537490000	KLIPPON CS K41-1	C.123
1537500000	KLIPPON CS K41-1	C.123
1537510000	KLIPPON CS K41-4	C.123
1537520000	KLIPPON CS K41-4	C.124
1537530000	KLIPPON CS K41-4	C.124
1537540000	KLIPPON CS K51-2	C.125
1537550000	KLIPPON CS K51-2	C.125
1537570000	KLIPPON CS K51-2	C.125
1537580000	KLIPPON CS K51-4	C.126

1560000000

Order No.	Type	Page
1565240000	KLIPPON K01	C.94
1565240000	KLIPPON K01	C.97
1565240000	KLIPPON K01	C.116
1565250000	KLIPPON K02	C.94
1565250000	KLIPPON K02	C.98
1565260000	KLIPPON K32	C.94
1565260000	KLIPPON K32	C.105
1565270000	KLIPPON K41	C.94
1565270000	KLIPPON K41	C.107
1565270000	KLIPPON K41	C.116
1565280000	KLIPPON K51	C.94
1565280000	KLIPPON K51	C.109
1565290000	KLIPPON K52	C.94
1565290000	KLIPPON K52	C.110
1565290000	KLIPPON K52	C.116
1567480000	FKSC M4X6 D8/SW2	C.170
1567480000	FKSC M4X6 D8/SW2	C.171
1567480000	FKSC M4X6 D8/SW2	C.172
1567480000	FKSC M4X6 D8/SW2	C.173
1567480000	FKSC M4X6 D8/SW2	C.174
1567480000	FKSC M4X6 D8/SW2	C.178
1567480000	FKSC M4X6 D8/SW2	C.179
1567480000	FKSC M4X6 D8/SW2	C.180
1567480000	FKSC M4X6 D8/SW2	C.181
1567480000	FKSC M4X6 D8/SW2	C.182
1567480000	FKSC M4X6 D8/SW2	C.183
1567480000	FKSC M4X6 D8/SW2	C.185
1567480000	FKSC M4X6 D8/SW2	C.186
1567480000	FKSC M4X6 D8/SW2	C.187
1567660000	TS35X7.5 ST STB 2.1 STB 3	C.71
1567660000	TS35X7.5 ST STB 2.1 STB 3	C.72
1568970000	VG 7-K68	D.6
1568980000	VG 9-K68	D.6
1568990000	VG 11-K68	D.6
1569000000	VG 13.5-K68	D.6
1569010000	VG 16-K68	D.6

Order No.	Type	Page
1569020000	VG 21-K68	D.6
1569030000	VG 29-K68	D.6
1569040000	VG 36-K68	D.6
1569050000	VG 42-K68	D.6
1569060000	VG 7-MS68	D.8
1569070000	VG 9-MS68	D.8
1569080000	VG 11-MS68	D.8
1569090000	VG 13,5-MS68	D.8
1569100000	VG 16-MS68	D.8
1569110000	VG 21-MS68	D.8
1569120000	VG 29-MS68	D.8
1569130000	VG 36-MS68	D.8
1569140000	VG 42-MS68	D.8

1580000000

1580360000	HG K+POK	C.100
1580360000	HG K+POK	C.102
1580360000	HG K+POK	C.104
1580360000	HG K+POK	C.106
1580360000	HG K+POK	C.107
1580360000	HG K+POK	C.108
1580360000	HG K+POK	C.109
1580360000	HG K+POK	C.110
1580360000	HG K+POK	C.111
1580360000	HG K+POK	C.112
1580360000	HG K+POK	C.113
1580360000	HG K+POK	C.114

1650000000

1656390000	KV 11-M	D.10
1656400000	KV 13-M	D.10
1656410000	KV 16-M	D.10
1656420000	KV 21-M	D.10
1656430000	KV 29-M	D.10

1690000000

1694070000	SKMU PG7-MS	D.42
1694080000	SKMU PG9-MS	D.42
1694090000	SKMU PG11-MS	D.42
1694100000	SKMU PG13,5-MS	D.42
1694110000	SKMU PG16-MS	D.42
1697440000	SKMU PG7-K GR	D.40
1697450000	SKMU PG9-K GR	D.40
1697460000	SKMU PG11-K GR	D.40
1697470000	SKMU PG 13,5-K GR	D.40
1697480000	SKMU PG16-K GR	D.40
1698220000	SKMU PG21-K GR	D.40
1698230000	SKMU PG29-K GR	D.40
1698240000	SKMU PG36-K GR	D.40
1698250000	SKMU PG42-K GR	D.40

1710000000

1718770000	VG 48-K68	D.6
1718790000	VG 48-MS68	D.8
1718900000	SKMU EMV PG7	D.44
1718910000	SKMU EMV PG9	D.44
1718920000	SKMU EMV PG11	D.44
1718930000	SKMU EMV PG13,5	D.44
1718940000	SKMU EMV PG16	D.44
1718950000	SKMU EMV PG21	D.44
1718960000	SKMU EMV PG29	D.44
1719090000	SKMU PG48-K GR	D.40
1719100000	SKMU PG7-K SW	D.41
1719110000	SKMU PG9-K SW	D.41
1719120000	SKMU PG11-K SW	D.41
1719130000	SKMU PG13,5-K SW	D.41
1719140000	SKMU PG16-K SW	D.41
1719150000	SKMU PG21-K SW	D.41
1719160000	SKMU PG29-K SW	D.41
1719170000	SKMU PG36-K SW	D.41
1719180000	SKMU PG42-K SW	D.41
1719190000	SKMU PG48-K SW	D.41
1719200000	SKMU PG21-MS	D.42
1719210000	SKMU PG29-MS	D.42
1719220000	SKMU PG36-MS	D.42
1719230000	SKMU PG42-MS	D.42
1719240000	SKMU PG48-MS	D.42
1719250000	VP 7-K54	D.53
1719260000	VP 48-K54	D.53
1719270000	VP 48-MS65	D.54
1719440000	GWDR PG7-P0	D.45
1719450000	GWDR PG9-P0	D.45
1719460000	GWDR PG11-P0	D.45
1719470000	GWDR PG13,5-P0	D.45
1719480000	GWDR PG16-P0	D.45
1719490000	GWDR PG21-P0	D.45
1719500000	GWDR PG29-P0	D.45
1719510000	GWDR PG36-P0	D.45
1719520000	GWDR PG42-P0	D.45
1719530000	GWDR PG48-P0	D.45
1719540000	GWDR PG7-NP	D.46
1719550000	GWDR PG9-NP	D.46
1719560000	GWDR PG11-NP	D.46
1719570000	GWDR PG13,5-NP	D.46
1719580000	GWDR PG16-NP	D.46

Order No.	Type	Page
1719590000	GWDR PG21-NP	D.46
1719600000	GWDR PG29-NP	D.46
1719610000	GWDR PG36-NP	D.46
1719620000	GWDR PG42-NP	D.46
1719630000	GWDR PG48-NP	D.46

1720000000

1720470000	VG 7-K68 SKS	D.7
1720480000	VG 9-K68 SKS	D.7
1720490000	VG 11-K68 SKS	D.7
1720500000	VG 13.5-K68 SKS	D.7
1720510000	VG 16-K68 SKS	D.7
1720520000	VG 21-K68 SKS	D.7

1730000000

1736230000	GWDR M16-NP	D.46
1736240000	GWDR M20-NP	D.46
1736250000	GWDR M25-NP	D.46
1736260000	GWDR M32-NP	D.46
1736270000	GWDR M40-NP	D.46
1736280000	GWDR M50-NP	D.46
1736290000	GWDR M63-NP	D.46
1736300000	SZS M16	D.52
1736310000	SZS M20	D.52
1736320000	SZS M25	D.52
1736330000	SZS M32	D.52
1736340000	SZS M40	D.52
1736350000	SZS M50	D.52
1736360000	SZS M63	D.52
1736480000	EA-RING MS/M 16	D.49
1736490000	EA-RING MS/M 20	D.49
1736500000	EA-RING MS/M 25	D.49
1736510000	EA-RING MS/M 32	D.49
1736520000	EA-RING MS/M 40	D.49
1736530000	EA-RING MS/M 50	D.49
1736540000	EA-RING MS/M 63	D.49
1736550000	EA-RING MS/M 75	D.49
1736570000	KSP L24	D.51
1736580000	KSP L30	D.51
1736590000	KSP L38	D.51
1736600000	KSP L46	D.51
1736610000	KSP L55	D.51
1736620000	KSP L65	D.51
1736630000	KSP L80	D.51
1736640000	KSP L90	D.51
1736670000	KSP EL30	D.51
1736680000	KSP EL38	D.51
1736920000	SKMU M16 K SW	D.41
1736930000	SKMU M20 K SW	C.79
1736930000	SKMU M20 K SW	C.80
1736930000	SKMU M20 K SW	D.41
1736940000	SKMU M25 K SW	C.81
1736940000	SKMU M25 K SW	D.41
1736950000	SKMU M32 K SW	D.41
1736960000	SKMU M40 K SW	D.41
1736970000	SKMU M50 K SW	D.41
1736980000	SKMU M63 K SW	D.41
1736990000	SKMU M16 MS	C.44
1736990000	SKMU M16 MS	C.78
1736990000	SKMU M16 MS	D.42
1737000000	SKMU M20 MS	C.44
1737000000	SKMU M20 MS	C.45
1737000000	SKMU M20 MS	C.46
1737000000	SKMU M20 MS	C.47
1737000000	SKMU M20 MS	C.79
1737000000	SKMU M20 MS	C.80
1737000000	SKMU M20 MS	D.42
1737010000	SKMU M25 MS	C.47
1737010000	SKMU M25 MS	C.81
1737010000	SKMU M25 MS	D.42
1737020000	SKMU M32 MS	C.45
1737020000	SKMU M32 MS	C.46
1737020000	SKMU M32 MS	D.42
1737030000	SKMU M40 MS	C.47
1737030000	SKMU M40 MS	D.42
1737040000	SKMU M50 MS	D.42
1737050000	SKMU M63 MS	D.42
1737060000	SKMU M75 MS	D.42
1737070000	VP M16-EXE SW	D.55
1737080000	VP M20-EXE SW	D.55
1737090000	VP M25-EXE SW	D.55
1737100000	VP M32-EXE SW	D.55
1737110000	VP M40-EXE SW	D.55
1737120000	VP M50-EXE SW	D.55
1737130000	VP M63-EXE SW	D.55
1737560000	ADAP EX M20-M16	C.153
1737560000	ADAP EX M20-M16	C.154
1737560000	ADAP EX M20-M16	C.155
1737560000	ADAP EX M20-M16	C.156

1770000000

1772200000	VG M12 - MS 68	D.8
1772210000	VG M16 - MS 68	D.8
1772220000	VG M20 - MS 68	D.8
1772230000	VG M25 - MS 68	D.8
1772240000	VG M32 - MS 68	D.8

Order No.	Type	Page
1772250000	VG M40 - MS 68	D.8
1772260000	VG M50 - MS 68	D.8
1772270000	VG M63 - MS 68	D.8
1772280000	VG M12-1/K68	D.6
1772290000	VG M16 - K 68	D.6
1772300000	VG M20-1/K68	D.6
1772310000	VG M25 - K 68	D.6
1772320000	VG M32 - K 68	D.6
1772330000	VG M40 - K 68	D.6
1772340000	VG M50 - K 68	D.6
1772350000	VG M63-1/K68	D.6
1772360000	SKMU M12 MS	D.42
1772440000	SKMU M12 - K GR	D.40
1772450000	SKMU M16 - K GR	D.40
1772460000	SKMU M20 - K GR	D.40
1772470000	SKMU M25 - K GR	D.40
1772480000	SKMU M32 - K GR	D.40
1772490000	SKMU M40 - K GR	D.40
1772500000	SKMU M50 - K GR	D.40
1772510000	SKMU M63 - K GR	D.40
1776700000	VG M12-K68 SKS	D.7
1776710000	VG M16-K68 SKS	D.7
1776720000	VG M20-K68 SKS 10-14	D.7
1776730000	VG M25-K68 SKS	D.7
1776900000	VP M25 K54	D.53
1776910000	VP M20 K54	D.53
1776920000	VP M16 K54	D.53
1776930000	VP M12 K54	D.53
1776940000	VP M32 K54	D.53
1776950000	VP M40 K54	D.53
1776960000	VP M50 K54	D.53
1776970000	VP M63 K54	D.53
1777610000	SKMU EMV M12	D.44
1777620000	SKMU EMV M16	D.44
1777630000	SKMU EMV M20	D.44
1777640000	SKMU EMV M25	D.44
1777650000	SKMU EMV M32	D.44
1777660000	SKMU EMV M40	D.44
1777670000	SKMU EMV M50	D.44
1777680000	SKMU EMV M63	D.44
1777690000	SKMU EMV PG 48	D.44
1777700000	SKMU EMV PG 42	D.44
1777710000	SKMU EMV PG 36	D.44
1777720000	VP M12-MS65	D.54
1777730000	VP M16-MS65	D.54
1777740000	VP M20-MS65	D.54
1777750000	VP M25-MS65	D.54
1777760000	VP M32-MS65	D.54
1777770000	VP M40-MS65	D.54
1777780000	VP M50-MS65	D.54
1777790000	VP M63-MS65	D.54
1777920000	GWDR M12-P0	D.45
1777930000	GWDR M16-P0	D.45
1777940000	GWDR M20-P0	D.45
1777950000	GWDR M25-P0	D.45
1777960000	GWDR M32-P0	D.45
1777970000	GWDR M40-P0	D.45
1777980000	GWDR M50-P0	D.45
1777990000	GWDR M63-P0	D.45
1778860000	VG M20-K68 SKS 6-12	D.7

1800000000

1806540000	SKMU M12 K SW	D.41

1860000000

1868550000	DAE M12 SS	C.52
1868550000	DAE M12 SS	C.53
1868550000	DAE M12 SS	C.54
1868550000	DAE M12 SS	C.55
1868550000	DAE M12 SS	C.56
1868550000	DAE M12 SS	C.57
1868550000	DAE M12 SS	C.58
1868550000	DAE M12 SS	C.59
1868550000	DAE M12 SS	C.62
1868550000	DAE M12 SS	C.63
1868550000	DAE M12 SS	C.64
1868550000	DAE M12 SS	C.65
1868550000	DAE M12 SS	C.66
1868550000	DAE M12 SS	C.67
1868550000	DAE M12 SS	C.68
1868550000	DAE M12 SS	C.69
1868550000	DAE M12 SS	C.70
1868550000	DAE M12 SS	C.71
1868550000	DAE M12 SS	C.72
1868550000	DAE M12 SS	C.73
1868550000	DAE M12 SS	C.74
1868550000	DAE M12 SS	C.75
1868550000	DAE M12 SS	C.96
1868550000	DAE M12 SS	C.97
1868550000	DAE M12 SS	C.98
1868550000	DAE M12 SS	C.99
1868550000	DAE M12 SS	C.100
1868550000	DAE M12 SS	C.101
1868550000	DAE M12 SS	C.102
1868550000	DAE M12 SS	C.103
1868550000	DAE M12 SS	C.104
1868550000	DAE M12 SS	C.105
1868550000	DAE M12 SS	C.106
1868550000	DAE M12 SS	C.107
1868550000	DAE M12 SS	C.108

Order No.	Type	Page
1868550000	DAE M12 SS	C.109
1868550000	DAE M12 SS	C.110
1868550000	DAE M12 SS	C.111
1868550000	DAE M12 SS	C.112
1868550000	DAE M12 SS	C.113
1868550000	DAE M12 SS	C.114
1868550000	DAE M12 SS	C.132
1868550000	DAE M12 SS	C.133
1868550000	DAE M12 SS	C.134
1868550000	DAE M12 SS	C.135
1868550000	DAE M12 SS	C.136
1868550000	DAE M12 SS	C.137
1868550000	DAE M12 SS	C.138
1868550000	DAE M12 SS	C.139
1868550000	DAE M12 SS	C.140
1868550000	DAE M12 SS	C.141
1868550000	DAE M12 SS	C.142
1868550000	DAE M12 SS	C.143
1868550000	DAE M12 SS	C.144
1868550000	DAE M12 SS	C.145
1868550000	DAE M12 SS	C.146
1868550000	DAE M12 SS	C.147
1868550000	DAE M12 SS	C.148
1868550000	DAE M12 SS	C.170
1868550000	DAE M12 SS	C.171
1868550000	DAE M12 SS	C.172
1868550000	DAE M12 SS	C.173
1868550000	DAE M12 SS	C.174
1868550000	DAE M12 SS	C.178
1868550000	DAE M12 SS	C.179
1868550000	DAE M12 SS	C.180
1868550000	DAE M12 SS	C.181
1868550000	DAE M12 SS	C.182
1868550000	DAE M12 SS	C.183
1868550000	DAE M12 SS	C.185
1868550000	DAE M12 SS	C.186
1868550000	DAE M12 SS	C.187
1868550000	DAE M12 SS	D.60
1868560000	DAE M12 PA SHORT	D.59
1868570000	DAE M12 PA LONG	C.52
1868570000	DAE M12 PA LONG	C.53
1868570000	DAE M12 PA LONG	C.54
1868570000	DAE M12 PA LONG	C.55
1868570000	DAE M12 PA LONG	C.56
1868570000	DAE M12 PA LONG	C.57
1868570000	DAE M12 PA LONG	C.58
1868570000	DAE M12 PA LONG	C.59
1868570000	DAE M12 PA LONG	C.60
1868570000	DAE M12 PA LONG	C.61
1868570000	DAE M12 PA LONG	C.62
1868570000	DAE M12 PA LONG	C.68
1868570000	DAE M12 PA LONG	C.69
1868570000	DAE M12 PA LONG	C.70
1868570000	DAE M12 PA LONG	C.71
1868570000	DAE M12 PA LONG	C.72
1868570000	DAE M12 PA LONG	C.73
1868570000	DAE M12 PA LONG	C.74
1868570000	DAE M12 PA LONG	C.75
1868570000	DAE M12 PA LONG	C.96
1868570000	DAE M12 PA LONG	C.97
1868570000	DAE M12 PA LONG	C.98
1868570000	DAE M12 PA LONG	C.99
1868570000	DAE M12 PA LONG	C.100
1868570000	DAE M12 PA LONG	C.101
1868570000	DAE M12 PA LONG	C.102
1868570000	DAE M12 PA LONG	C.103
1868570000	DAE M12 PA LONG	C.104
1868570000	DAE M12 PA LONG	C.105
1868570000	DAE M12 PA LONG	C.106
1868570000	DAE M12 PA LONG	C.107
1868570000	DAE M12 PA LONG	C.108
1868570000	DAE M12 PA LONG	C.109
1868570000	DAE M12 PA LONG	C.110
1868570000	DAE M12 PA LONG	C.111
1868570000	DAE M12 PA LONG	C.112
1868570000	DAE M12 PA LONG	C.113
1868570000	DAE M12 PA LONG	C.114
1868570000	DAE M12 PA LONG	C.132
1868570000	DAE M12 PA LONG	C.133
1868570000	DAE M12 PA LONG	C.134
1868570000	DAE M12 PA LONG	C.135
1868570000	DAE M12 PA LONG	C.136
1868570000	DAE M12 PA LONG	C.137
1868570000	DAE M12 PA LONG	C.138
1868570000	DAE M12 PA LONG	C.139
1868570000	DAE M12 PA LONG	C.140
1868570000	DAE M12 PA LONG	C.141
1868570000	DAE M12 PA LONG	C.142
1868570000	DAE M12 PA LONG	C.143
1868570000	DAE M12 PA LONG	C.144
1868570000	DAE M12 PA LONG	C.145
1868570000	DAE M12 PA LONG	C.146
1868570000	DAE M12 PA LONG	C.147
1868570000	DAE M12 PA LONG	C.148
1868570000	DAE M12 PA LONG	C.170
1868570000	DAE M12 PA LONG	C.171
1868570000	DAE M12 PA LONG	C.172
1868570000	DAE M12 PA LONG	C.173
1868570000	DAE M12 PA LONG	C.174

Order No.	Type	Page
1868570000	DAE M12 PA LONG	C.178
1868570000	DAE M12 PA LONG	C.179
1868570000	DAE M12 PA LONG	C.180
1868570000	DAE M12 PA LONG	C.181
1868570000	DAE M12 PA LONG	C.182
1868570000	DAE M12 PA LONG	C.183
1868570000	DAE M12 PA LONG	C.185
1868570000	DAE M12 PA LONG	C.186
1868570000	DAE M12 PA LONG	C.187
1868570000	DAE M12 PA LONG	D.59

1890000000

1898210000	MOPL K3 N FE	C.103

1900000000

1905270000	MOPL K2 N FE	C.101
1905280000	MOPL K1 N FE	C.99
1909860000	VG M16-1/K68	D.6
1909870000	VG M25-1/K68	D.6
1909880000	VG M32-1/K68	D.6
1909890000	VG M40-1/K68	D.6
1909910000	VG M16-1/MS68	D.8
1909920000	VG M25-1/MS68	D.8
1909930000	VG M32-1/MS68	D.8
1909940000	VG M40-1/MS68	D.8
1909950000	VG M50-1/MS68	D.8
1909980000	TS15 60 KLippon K1 CSS	C.99
1909980000	TS15 60 KLippon K1 CSS	C.116
1909990000	TS15 64 Klippon K11	C.100
1909990000	TS15 64 Klippon K11	C.116

1910000000

1910010000	TS15 90 KLippon K2 CSS	C.101
1910010000	TS15 90 KLippon K2 CSS	C.116
1910020000	TS15 114 Klippon K21 CSS	C.102
1910020000	TS15 114 Klippon K21 CSS	C.116
1910030000	TS15 155 Klippon K3 CSS	C.103
1910030000	TS15 155 Klippon K3 CSS	C.116
1910040000	TS15 164 Klippon K31 CSS	C.104
1910040000	TS15 164 Klippon K31 CSS	C.116
1910060000	TS35 64 Klippon K4K11	C.106
1910060000	TS35 64 Klippon K4K11	C.116
1910070000	TS35 105 Klippon K41/POK4	C.107
1910070000	TS35 105 Klippon K41/POK4	C.116
1910070000	TS35 105 Klippon K41/POK4	C.150
1910070000	TS35 105 Klippon K41/POK4	C.155
1910080000	TS35/148 KLIPPON K5 CSS	C.108
1910080000	TS35/148 KLIPPON K5 CSS	C.116
1910090000	TS35/203 KLIPPON K51POK5	C.109
1910100000	TS35/140 Klippon K52 POK51	C.110
1910100000	TS35/140 Klippon K52 POK51	C.116
1910100000	TS35/140 Klippon K52 POK51	C.150
1910100000	TS35/140 Klippon K52 POK51	C.156
1910110000	TS35/172 KLIPPON K6 CSS	C.111
1910120000	TS35/243 KLIPPON K61POK6	C.112
1910130000	TS35/324 KLIPPON K7 CSS	C.113
1910140000	TS35/260 KLIPPON K71 CSS	C.114
1911380000	KDSU M20 BN O NI 2 G16	D.27
1911390000	KDSU M20 BN O NI 2 G20S	D.27
1911400000	KDSU M20 BN O NI 2 G20	D.27
1911420000	KDSU M25 BN O NI 2 G25	D.27
1911430000	KDSU M32 BN O NI 2 G32	D.27
1911440000	KDSU M40 BN O NI 2 G40	D.27
1911450000	KDSU M50 BN O NI 2 G50S	D.27
1911460000	KDSU M50 BN O NI 2 G50	D.27
1911480000	KDSU M63 BN O NI 2 G63S	D.27
1911490000	KDSU M63 BN O NI 2 G63	D.27
1911510000	KSG M20 BN O NI 2 G16	D.33
1911540000	KSG M20 BN O NI 2 G20S	D.33
1911560000	KSG M20 BN O NI 2 G20	D.33
1911570000	KSG M25 BN O NI 2 G25	D.33
1911580000	KSG M32 BN O NI 2 G32	D.33
1911590000	KSG M40 BN O NI 2 G40	D.33
1911600000	KSG M50 BN O NI 2 G50S	D.33
1911610000	KSG M50 BN O NI 2 G50	D.33
1911620000	KSG M63 BN O NI 2 G63S	D.33
1911630000	KSG M63 BN O NI 2 G63	D.33
1913320000	GWDR M12-NP	D.46

1920000000

1921720000	VG H M20 MS	D.10
1921740000	VG H M25 MS	D.10
1921760000	VG H M32 MS	D.10
1921770000	VG H M40 MS	D.10
1928060000	TS15 68 Klippon POK1 CSS	C.150
1928060000	TS15 68 Klippon POK1 CSS	C.152
1928070000	TS15 98 Klippon POK2 CSS	C.150
1928070000	TS15 98 Klippon POK2 CSS	C.153
1928080000	TS15 147 Klippon POK3 CSS	C.150
1928080000	TS15 147 Klippon POK3 CSS	C.154

1930000000

1937630000	KLIPPON K1 VMQ RAL7001	C.94
1937630000	KLIPPON K1 VMQ RAL7001	C.99

Order No.	Type	Page
1937720000	KLIPPON K71 VMQ RAL7001	C.94
1937720000	KLIPPON K71 VMQ RAL7001	C.114
1937730000	KLIPPON K61 VMQ RAL7001	C.94
1937730000	KLIPPON K61 VMQ RAL7001	C.112
1937740000	KLIPPON K52 VMQ RAL7001	C.94
1937740000	KLIPPON K52 VMQ RAL7001	C.110
1937750000	KLIPPON K51 VMQ RAL7001	C.94
1937750000	KLIPPON K51 VMQ RAL7001	C.109
1937800000	KLIPPON K41 VMQ RAL7001	C.94
1937800000	KLIPPON K41 VMQ RAL7001	C.107
1937810000	KLIPPON K32 VMQ RAL7001	C.94
1937810000	KLIPPON K32 VMQ RAL7001	C.105
1937820000	KLIPPON K31 VMQ RAL7001	C.94
1937820000	KLIPPON K31 VMQ RAL7001	C.104
1937830000	KLIPPON K21 VMQ RAL7001	C.94
1937830000	KLIPPON K21 VMQ RAL7001	C.102
1937840000	KLIPPON K02 VMQ RAL7001	C.94
1937840000	KLIPPON K02 VMQ RAL7001	C.98
1937850000	KLIPPON K01 VMQ RAL7001	C.94
1937850000	KLIPPON K01 VMQ RAL7001	C.97
1937860000	KLIPPON K5 VMQ RAL7001	C.94
1937860000	KLIPPON K5 VMQ RAL7001	C.108
1937870000	KLIPPON K6 VMQ RAL7001	C.94
1937870000	KLIPPON K6 VMQ RAL7001	C.111
1937880000	KLIPPON K7 VMQ RAL7001	C.94
1937880000	KLIPPON K7 VMQ RAL7001	C.113
1937890000	KLIPPON K4 VMQ RAL7001	C.94
1937890000	KLIPPON K4 VMQ RAL7001	C.106
1937900000	KLIPPON K3 VMQ RAL7001	C.94
1937900000	KLIPPON K3 VMQ RAL7001	C.103
1937910000	KLIPPON K11 VMQ RAL7001	C.94
1937910000	KLIPPON K11 VMQ RAL7001	C.100
1937920000	KLIPPON K0 VMQ RAL7001	C.94
1937920000	KLIPPON K0 VMQ RAL7001	C.96
1937930000	KLIPPON K2 VMQ RAL7001	C.94
1937930000	KLIPPON K2 VMQ RAL7001	C.101
1939540000	KLIPPON K01 VMQ	C.94
1939540000	KLIPPON K01 VMQ	C.97
1939550000	KLIPPON K02 VMQ	C.94
1939550000	KLIPPON K02 VMQ	C.98
1939560000	KLIPPON K1 VMQ	C.94
1939560000	KLIPPON K1 VMQ	C.99
1939570000	KLIPPON K11 VMQ	C.94
1939570000	KLIPPON K11 VMQ	C.100
1939580000	KLIPPON K2 VMQ	C.94
1939580000	KLIPPON K2 VMQ	C.101
1939590000	KLIPPON K21 VMQ	C.94
1939590000	KLIPPON K21 VMQ	C.102
1939600000	KLIPPON K3 VMQ	C.94
1939600000	KLIPPON K3 VMQ	C.103
1939610000	KLIPPON K31 VMQ	C.94
1939610000	KLIPPON K31 VMQ	C.104
1939620000	KLIPPON K32 VMQ	C.94
1939620000	KLIPPON K32 VMQ	C.105
1939630000	KLIPPON K4 VMQ	C.94
1939630000	KLIPPON K4 VMQ	C.106
1939640000	KLIPPON K41 VMQ	C.94
1939640000	KLIPPON K41 VMQ	C.107
1939650000	KLIPPON K5 VMQ	C.94
1939650000	KLIPPON K5 VMQ	C.108
1939660000	KLIPPON K51 VMQ	C.94
1939660000	KLIPPON K51 VMQ	C.109
1939670000	KLIPPON K52 VMQ	C.94
1939670000	KLIPPON K52 VMQ	C.110
1939690000	KLIPPON K6 VMQ	C.94
1939690000	KLIPPON K6 VMQ	C.111
1939700000	KLIPPON K61 VMQ	C.94
1939700000	KLIPPON K61 VMQ	C.112
1939710000	KLIPPON K7 VMQ	C.94
1939710000	KLIPPON K7 VMQ	C.113
1939730000	KLIPPON K71 VMQ	C.94
1939730000	KLIPPON K71 VMQ	C.114
1939760000	KLIPPON K0 VMQ	C.94
1939760000	KLIPPON K0 VMQ	C.96

2020000000

2022050000	KTB MOPL 2215 MSZN H	C.15
2022060000	KTB MOPL 2626 MSZN H	C.16
2022060000	KTB MOPL 2626 MSZN H	C.17
2022190000	KTB MOPL 3030 MSZN H	C.18
2022190000	KTB MOPL 3030 MSZN H	C.19
2022310000	KTB MOPL 3526 MSZN H	C.20
2022310000	KTB MOPL 3526 MSZN H	C.21
2022420000	KTB MOPL 4030 MSZN H	C.22
2022420000	KTB MOPL 4030 MSZN H	C.23
2022590000	KTB MOPL 4538 MSZN H	C.24
2022590000	KTB MOPL 4538 MSZN H	C.25
2022610000	KTB MOPL 4848 MSZN H	C.26
2022610000	KTB MOPL 4848 MSZN H	C.27
2022650000	KTB MOPL 5535 MSZN H	C.28
2022650000	KTB MOPL 5535 MSZN H	C.29
2022670000	KTB MOPL 6245 MSZN H	C.30
2022670000	KTB MOPL 6245 MSZN H	C.31
2022680000	KTB MOPL 7650 MSZN H	C.32
2022680000	KTB MOPL 7650 MSZN H	C.33
2022740000	KTB MOPL 9161 MSZN H	C.34
2022740000	KTB MOPL 9161 MSZN H	C.35
2022760000	KTB MOPL 9874 MSZN H	C.36

Order No.	Type	Page
2022770000	KTB GP 221513 AB S4 PE	C.15
2022900000	KTB GP 221513 CD S4 PE	C.15
2022930000	KTB GP 262615 AB S4 PE	C.16
2023090000	KTB GP 262615 CD S4 PE	C.16
2023100000	KTB GP 262620 AB S4 PE	C.17
2023110000	KTB GP 262620 CD S4 PE	C.17
2023120000	KTB GP 303015 AB S4 PE	C.18
2023130000	KTB GP 303015 CD S4 PE	C.18
2023140000	KTB GP 303020 AB S4 PE	C.19
2023150000	KTB GP 303020 CD S4 PE	C.19
2023160000	KTB GP 352615 AB S4 PE	C.20
2023210000	KTB GP 352615 DC S4 PE	C.20
2023230000	KTB GP 352620 AB S4 PE	C.21
2023280000	KTB GP 352620 CD S4 PE	C.21
2023320000	KTB GP 403015 AB S4 PE	C.22
2023330000	KTB GP 403015 CD S4 PE	C.22
2023450000	KTB GP 403020 AB S4 PE	C.23
2023480000	KTB GP 403020 CD S4 PE	C.23
2023490000	KTB GP 453815 AB S4 PE	C.24
2023500000	KTB GP 453815 CD S4 PE	C.24
2023510000	KTB GP 453820 AB S4 PE	C.25
2023520000	KTB GP 453820 CD S4 PE	C.25
2023530000	KTB GP 484815 AB S4 PE	C.26
2023540000	KTB GP 484815 CD S4 PE	C.26
2023580000	KTB GP 484820 AB S4 PE	C.27
2023620000	KTB GP 484820 CD S4 PE	C.27
2023660000	KTB GP 553515 AB S4 PE	C.28
2023670000	KTB GP 553515 CD S4 PE	C.28
2023740000	KTB GP 553520 AB S4 PE	C.29
2023790000	KTB GP 553520 CD S4 PE	C.29
2023820000	KTB GP 624515 AB S4 PE	C.30
2023870000	KTB GP 624515 CD S4 PE	C.30
2023880000	KTB GP 624520 AB S4 PE	C.31
2023930000	KTB GP 624520 CD S4 PE	C.31
2024040000	KTB GP 765015 AB S4 PE	C.32
2024090000	KTB GP 765015 CD S4 PE	C.32
2024100000	KTB GP 765020 AB S4 PE	C.33
2024140000	KTB GP 765020 CD S4 PE	C.33
2024150000	KTB GP 916115 AB S4 PE	C.34
2024300000	KTB GP 916115 CD S4 PE	C.34
2024470000	KTB GP 916120 AB S4 PE	C.35
2024490000	KTB GP 916120 CD S4 PE	C.35
2024560000	KTB GP 987420 AB S4 PE	C.36
2024590000	KTB GP 987420 CD S4 PE	C.36

2060000000

2066710000	VP M12 EX SI 7J	D.58
2066720000	VP M16 EX SI 7J	C.152
2066720000	VP M16 EX SI 7J	D.58
2066730000	VP M20 EX SI 7J	C.153
2066730000	VP M20 EX SI 7J	C.154
2066730000	VP M20 EX SI 7J	C.155
2066730000	VP M20 EX SI 7J	C.156
2066730000	VP M20 EX SI 7J	D.58
2066740000	VP M25 EX SI 7J	D.58
2066750000	VP M32 EX SI 7J	D.58
2066760000	VP M40 EX SI 7J	D.58
2066770000	VP M50 EX SI 7J	D.58
2066940000	VP M63 EX SI 7J	D.58

2430000000

2435070000	VG M12 EMV-4 MS 3-6.5	D.11
2435140000	VG M16 EMV-4 MS 5-10	D.11
2435150000	VG M20 EMV-4 MS 6-12	D.11
2435160000	VG M20 EMV-4 MS 8-14	D.11
2435170000	VG M25 EMV-4 MS 10-18	D.11
2435180000	VG M32 EMV-4 MS 16-25	D.11
2435190000	VG M40 EMV-4 MS 22-32	D.11
2435200000	VG M50 EMV-4 MS 30-38	D.11
2435210000	VG M63 EMV-4 MS 34-44	D.11

2470000000

2470690000	KEBI QL 302015 S2B0	C.50
2470690000	KEBI QL 302015 S2B0	C.52
2470700000	KEBI QL 303015 S2B0	C.50
2470700000	KEBI QL 303015 S2B0	C.53
2470710000	KEBI QL 303022 S2B0	C.50
2470710000	KEBI QL 303022 S2B0	C.54
2470720000	KEBI QL 403015 S2B0	C.50
2470720000	KEBI QL 403015 S2B0	C.55
2470730000	KEBI QL 403022 S2B0	C.50
2470730000	KEBI QL 403022 S2B0	C.56
2470740000	KEBI QL 404022 S2B0	C.50
2470740000	KEBI QL 404022 S2B0	C.57
2470750000	KEBI QL 504022 S2B0	C.50
2470750000	KEBI QL 504022 S2B0	C.58
2470760000	KEBI QL 505022 S2B0	C.50
2470760000	KEBI QL 505022 S2B0	C.59
2470770000	KEBI QL 604022 S2B0	C.50
2470770000	KEBI QL 604022 S2B0	C.60
2470780000	KEBI QL 606022 S2B0	C.50
2470780000	KEBI QL 606022 S2B0	C.61
2470790000	KEBI QL 806022 S2B0	C.50
2470790000	KEBI QL 806022 S2B0	C.62
2470800000	KEBI QL 302015 S2B1	C.50
2470800000	KEBI QL 302015 S2B1	C.52

Order No.	Type	Page
2470810000	KEBI QL 303015 S2B1	C.50
2470810000	KEBI QL 303015 S2B1	C.53
2470820000	KEBI QL 303022 S2B1	C.50
2470820000	KEBI QL 303022 S2B1	C.54
2470830000	KEBI QL 403015 S2B1	C.50
2470830000	KEBI QL 403015 S2B1	C.55
2470840000	KEBI QL 403022 S2B1	C.50
2470840000	KEBI QL 403022 S2B1	C.56
2470850000	KEBI QL 404022 S2B1	C.50
2470850000	KEBI QL 404022 S2B1	C.57
2470860000	KEBI QL 504022 S2B1	C.50
2470860000	KEBI QL 504022 S2B1	C.58
2470870000	KEBI QL 505022 S2B1	C.50
2470870000	KEBI QL 505022 S2B1	C.59
2470880000	KEBI QL 604022 S2B1	C.50
2470880000	KEBI QL 604022 S2B1	C.60
2470890000	KEBI QL 606022 S2B1	C.50
2470890000	KEBI QL 606022 S2B1	C.61
2470900000	KEBI QL 806022 S2B1	C.50
2470900000	KEBI QL 806022 S2B1	C.62
2473930000	KLIPPON QL KEY	C.52
2473930000	KLIPPON QL KEY	C.53
2473930000	KLIPPON QL KEY	C.54
2473930000	KLIPPON QL KEY	C.55
2473930000	KLIPPON QL KEY	C.56
2473930000	KLIPPON QL KEY	C.57
2473930000	KLIPPON QL KEY	C.58
2473930000	KLIPPON QL KEY	C.59
2473930000	KLIPPON QL KEY	C.60
2473930000	KLIPPON QL KEY	C.61
2473930000	KLIPPON QL KEY	C.62
2475490000	PECD WIRE 6/200/D6 SET	C.44
2475490000	PECD WIRE 6/200/D6 SET	C.45
2475490000	PECD WIRE 6/200/D6 SET	C.46
2475490000	PECD WIRE 6/200/D6 SET	C.47
2475490000	PECD WIRE 6/200/D6 SET	C.78
2475490000	PECD WIRE 6/200/D6 SET	C.79
2475490000	PECD WIRE 6/200/D6 SET	C.80
2475490000	PECD WIRE 6/200/D6 SET	C.81

2510000000

2519520000	KLIPPON BDX M20 B	C.44
2519520000	KLIPPON BDX M20 B	C.45
2519520000	KLIPPON BDX M20 B	C.46
2519520000	KLIPPON BDX M20 B	C.47
2519520000	KLIPPON BDX M20 B	C.78
2519520000	KLIPPON BDX M20 B	C.79
2519520000	KLIPPON BDX M20 B	C.80
2519520000	KLIPPON BDX M20 B	C.81
2519520000	KLIPPON BDX M20 B	D.61
2519550000	KLIPPON BDX M20 S	C.44
2519550000	KLIPPON BDX M20 S	C.45
2519550000	KLIPPON BDX M20 S	C.46
2519550000	KLIPPON BDX M20 S	C.47
2519550000	KLIPPON BDX M20 S	C.68
2519550000	KLIPPON BDX M20 S	C.69
2519550000	KLIPPON BDX M20 S	C.70
2519550000	KLIPPON BDX M20 S	C.71
2519550000	KLIPPON BDX M20 S	C.72
2519550000	KLIPPON BDX M20 S	C.73
2519550000	KLIPPON BDX M20 S	C.74
2519550000	KLIPPON BDX M20 S	C.75
2519550000	KLIPPON BDX M20 S	C.78
2519550000	KLIPPON BDX M20 S	C.79
2519550000	KLIPPON BDX M20 S	C.80
2519550000	KLIPPON BDX M20 S	C.81
2519550000	KLIPPON BDX M20 S	D.61
2519570000	KLIPPON BDX M20X15 S	C.132
2519570000	KLIPPON BDX M20X15 S	C.133
2519570000	KLIPPON BDX M20X15 S	C.134
2519570000	KLIPPON BDX M20X15 S	C.135
2519570000	KLIPPON BDX M20X15 S	C.136
2519570000	KLIPPON BDX M20X15 S	C.137
2519570000	KLIPPON BDX M20X15 S	C.138
2519570000	KLIPPON BDX M20X15 S	C.139
2519570000	KLIPPON BDX M20X15 S	C.140
2519570000	KLIPPON BDX M20X15 S	C.141
2519570000	KLIPPON BDX M20X15 S	C.142
2519570000	KLIPPON BDX M20X15 S	C.143
2519570000	KLIPPON BDX M20X15 S	C.144
2519570000	KLIPPON BDX M20X15 S	C.145
2519570000	KLIPPON BDX M20X15 S	C.146
2519570000	KLIPPON BDX M20X15 S	C.147
2519570000	KLIPPON BDX M20X15 S	C.148
2519570000	KLIPPON BDX M20X15 S	D.61
2519590000	KLIPPON BDX M25 S	D.61

2580000000

2583350000	CABTITE BSE SML GY	E.4
2583360000	CABTITE SE 1.5-2 SML GY	E.4
2583380000	CABTITE SE 2-3 SML GY	E.4
2583400000	CABTITE SE 3-4 SML GY	E.4
2583440000	CABTITE SE 4-5 SML GY	E.4
2583450000	CABTITE SE 5-6 SML GY	E.4
2583460000	CABTITE SE 6-7 SML GY	E.4
2583470000	CABTITE FR 16/8 BK	E.6
2583480000	CABTITE FR 10/6 BK	E.5

Order No.	Type	Page
2583490000	CABTITE FR 4-1 BK	E.5
2583500000	CABTITE CSE 7-24 LRG BK	E.4
2583510000	CABTITE CSE 2-11 SML BK	E.4
2583520000	CABTITE SE 2/ASI SML BK	E.4
2583530000	CABTITE SE 1/ASI SML BK	E.4
2583540000	CABTITE SE 2/8 SML BK	E.4
2583550000	CABTITE SE 2/7 SML BK	E.4
2583560000	CABTITE SE 4/4-5 SML BK	E.4
2583580000	CABTITE SE 4/3-4 SML BK	E.4
2583590000	CABTITE SE 4/2-3 SML BK	E.4
2583610000	CABTITE SE 2/5-6 SML BK	E.4
2583620000	CABTITE SE 2/4-5 SML BK	E.4
2583630000	CABTITE SE 32-33 LRG BK	E.4
2583640000	CABTITE SE 31-32 LRG BK	E.4
2583650000	CABTITE SE 30-31 LRG BK	E.4
2583660000	CABTITE SE 29-30 LRG BK	E.4
2583670000	CABTITE SE 28-29 LRG BK	E.4
2583680000	CABTITE SE 27-28 LRG BK	E.4
2583690000	CABTITE SE 26-27 LRG BK	E.4
2583700000	CABTITE SE 25-26 LRG BK	E.4
2583710000	CABTITE SE 24-25 LRG BK	E.4
2583720000	CABTITE FR 24/10 BK SET	E.6
2583730000	CABTITE SE 23-24 LRG BK	E.4
2583740000	CABTITE FR 16/8 BK SET	E.6
2583750000	CABTITE SE 22-23 LRG BK	E.4
2583760000	CABTITE FR 10/6 BK SET	E.5
2583770000	CABTITE SE 21-22 LRG BK	E.4
2583780000	CABTITE FR 4-1 BK SET	E.5
2583790000	CABTITE SE 20-21 LRG BK	E.4
2583800000	CABTITE FR 24/10 BK	E.6
2583810000	CABTITE SE 19-20 LRG BK	E.4
2583830000	CABTITE SE 18-19 LRG BK	E.4
2583840000	CABTITE SE 17-18 LRG BK	E.4
2583850000	CABTITE SE 16-17 LRG BK	E.4
2583860000	CABTITE SE 15-16 LRG BK	E.4
2583880000	CABTITE SE 14-15 LRG BK	E.4
2583890000	CABTITE CR 24/10 EMV	E.8
2583900000	CABTITE BSE LRG BK	E.4
2583910000	CABTITE CR 16/8 EMV	E.8
2583930000	CABTITE CR 10/6 EMV	E.8
2583950000	CABTITE CR 4/1 EMV	E.8
2583960000	CABTITE SE 15-16 SML BK	E.4
2583980000	CABTITE SE 14-15 SML BK	E.4
2584000000	CABTITE SE 13-14 SML BK	E.4
2584010000	CABTITE LNS M63 BK	E.7
2584020000	CABTITE SE 12-13 SML BK	E.4
2584030000	CABTITE LNS M50 BK	E.7
2584040000	CABTITE SE 11-12 SML BK	E.4
2584050000	CABTITE LNS M40 BK	E.7
2584060000	CABTITE SE 10-11 SML BK	E.4
2584070000	CABTITE LNS M32 BK	E.7
2584080000	CABTITE SE 9-10 SML BK	E.4
2584090000	CABTITE LNS M25 BK	E.7
2584110000	CABTITE LNS M20 BK	E.7
2584120000	CABTITE CGS M63 BK	E.7
2584130000	CABTITE CGS M50 BK	E.7
2584150000	CABTITE CGS M40 BK	E.7
2584160000	CABTITE CGS M32 BK	E.7
2584180000	CABTITE CGS M25 BK	E.7
2584200000	CABTITE CGS M20 BK	E.7
2584210000	CABTITE FRL 24/10 BK	E.6
2584220000	CABTITE FRL 16/8 BK	E.6
2584240000	CABTITE FRL 10/6 BK	E.5
2584260000	CABTITE FRL 4-1 BK	E.5
2584270000	CABTITE GI H BK	E.7
2584290000	CABTITE GI X BK	E.7
2584300000	CABTITE GI T BK	E.7
2584320000	CABTITE GI I BK	E.7
2584330000	CABTITE SE 8-9 SML BK	E.4
2584340000	CABTITE SE 31-32 LRG GY	E.4
2584350000	CABTITE SE 28-29 LRG GY	E.4
2584360000	CABTITE SE 30-31 LRG GY	E.4
2584370000	CABTITE SE 27-28 LRG GY	E.4
2584380000	CABTITE SE 29-30 LRG GY	E.4
2584390000	CABTITE SE 26-27 LRG GY	E.4
2584400000	CABTITE SE 25-26 LRG GY	E.4
2584410000	CABTITE SE 24-25 LRG GY	E.4
2584420000	CABTITE SE 23-24 LRG GY	E.4
2584430000	CABTITE SE 22-23 LRG GY	E.4
2584440000	CABTITE SE 21-22 LRG GY	E.4
2584450000	CABTITE SE 20-21 LRG GY	E.4
2584460000	CABTITE SE 19-20 LRG GY	E.4
2584470000	CABTITE SE 18-19 LRG GY	E.4
2584480000	CABTITE SE 17-18 LRG GY	E.4
2584490000	CABTITE SE 16-17 LRG GY	E.4
2584500000	CABTITE SE 15-16 LRG GY	E.4
2584510000	CABTITE SE 14-15 LRG GY	E.4
2584520000	CABTITE BSE LRG GY	E.4
2584550000	CABTITE SE 15-16 SML GY	E.4
2584560000	CABTITE SE 14-15 SML GY	E.4
2584570000	CABTITE SE 13-14 SML GY	E.4
2584590000	CABTITE SE 12-13 SML GY	E.4
2584600000	CABTITE SE 11-12 SML GY	E.4
2584610000	CABTITE SE 10-11 SML GY	E.4
2584630000	CABTITE SE 9-10 SML GY	E.4
2584650000	CABTITE SE 8-9 SML GY	E.4
2584660000	CABTITE SE 7-8 SML GY	E.4
2584670000	CABTITE SE 7-8 SML BK	E.4
2584680000	CABTITE SE 4-5 SML BK	E.4

Order No.	Type	Page
2584690000	CABTITE SE 6-7 SML BK	E.4
2584710000	CABTITE SE 5-6 SML BK	E.4
2584730000	CABTITE SE 3-4 SML BK	E.4
2584760000	CABTITE SE 2-3 SML BK	E.4
2584780000	CABTITE SE 1.5-2 SML BK	E.4
2584790000	CABTITE BSE SML BK	E.4
2584800000	CABTITE SE 2/ASI SML GY	E.4
2584810000	CABTITE SE 1/ASI SML GY	E.4
2584820000	CABTITE SE 2/8 SML GY	E.4
2584830000	CABTITE SE 2/7 SML GY	E.4
2584840000	CABTITE SE 4/4-5 SML GY	E.4
2584860000	CABTITE SE 4/3-4 SML GY	E.4
2584870000	CABTITE SE 4/2-3 SML GY	E.4
2584890000	CABTITE SE 2/5-6 SML GY	E.4
2584900000	CABTITE SE 2/4-5 SML GY	E.4
2584910000	CABTITE SE 33-34 LRG GY	E.4
2584920000	CABTITE SE 32-33 LRG GY	E.4

2590000000

2595510000	CABTITE SE 33-34 LRG BK	E.4
2595520000	CABTITE SE 34-35 LRG BK	E.4
2595530000	CABTITE SE 34-35 LRG GY	E.4

2630000000

2635120000	CABTITE SC M5X25 SET	E.5
2635120000	CABTITE SC M5X25 SET	E.6
2637360000	CABTITE TOOL ATSE PA	E.5
2637360000	CABTITE TOOL ATSE PA	E.6

2650000000

2652280000	CABTITE SE 3/5-6 SML BK	E.4
2652290000	CABTITE SE 3/5-6 SML GY	E.4
2652300000	CABTITE BP 2MM PA	E.8
2652310000	CABTITE BP 3MM PA	E.8
2652320000	CABTITE BP 4MM PA	E.8
2652330000	CABTITE BP 5MM PA	E.8
2652340000	CABTITE BP 6MM PA	E.8
2652350000	CABTITE BP 7MM PA	E.8
2652360000	CABTITE BP 8MM PA	E.8
2652370000	CABTITE BP 9MM PA	E.8
2652380000	CABTITE BP 10MM PA	E.8
2652400000	CABTITE BP 12MM PA	E.8
2652410000	CABTITE BP 13MM PA	E.8
2652420000	CABTITE BP 14MM PA	E.8
2652430000	CABTITE BP 17MM PA	E.8
2652440000	CABTITE BP 20MM PA	E.8
2652450000	CABTITE BP 21MM PA	E.8
2652460000	CABTITE BP 25MM PA	E.8
2652470000	CABTITE BP 28MM PA	E.8
2652480000	CABTITE BP 35MM PA	E.8

2720000000

2721930000	VG M12 EXE 4-6,5 CR7J G4	D.38
2721940000	VG M16 EXE 5-8 CR7J G4	D.38
2721950000	VG M16 EXE 6-10 CR7J G4	D.38
2721960000	VG M20 EXE 7-12 CR7J G4	D.38
2721970000	VG M20 EXE 7-13 CR7J G4	D.38
2721980000	VG M20 EXE 11-14 CR7J G4	D.38
2721990000	VG M25 EXE 12-17 CR7J G4	D.38
2722000000	VG M25 EXE 14-18 CR7J G4	D.38
2722010000	VG M32 EXE 16-21 CR7J G4	D.38
2722020000	VG M32 EXE 19-25 CR7J G4	D.38
2722030000	VG M40 EXE 20-28 CR7J G4	D.38
2722040000	VG M40 EXE 23-32 CR7J G4	D.38
2722050000	VG M50 EXE 31-38 CR7J G4	D.38
2722060000	VG M63 EXE 35-44 CR7J G4	D.38
2722070000	VG M12 EXE 4-6,5 SI7J G4	D.39
2722080000	VG M16 EXE 5-8 SI7J G4	C.152
2722080000	VG M16 EXE 5-8 SI7J G4	D.39
2722090000	VG M16 EXE 6-10 SI7J G4	C.152
2722090000	VG M16 EXE 6-10 SI7J G4	D.39
2722100000	VG M20 EXE 7-12 SI7J G4	D.39
2722110000	VG M20 EXE 7-13 SI7J G4	C.153
2722110000	VG M20 EXE 7-13 SI7J G4	C.154
2722110000	VG M20 EXE 7-13 SI7J G4	C.155
2722110000	VG M20 EXE 7-13 SI7J G4	C.156
2722110000	VG M20 EXE 7-13 SI7J G4	D.39
2722120000	VG M20 EXE 11-14 SI7J G4	C.153
2722120000	VG M20 EXE 11-14 SI7J G4	C.154
2722120000	VG M20 EXE 11-14 SI7J G4	C.155
2722120000	VG M20 EXE 11-14 SI7J G4	C.156
2722120000	VG M20 EXE 11-14 SI7J G4	D.39
2722130000	VG M25 EXE 12-17 SI7J G4	D.39
2722140000	VG M25 EXE 14-18 SI7J G4	D.39
2722150000	VG M32 EXE 16-21 SI7J G4	D.39
2722160000	VG M32 EXE 19-25 SI7J G4	D.39
2722170000	VG M40 EXE 20-28 SI7J G4	D.39
2722180000	VG M40 EXE 23-32 SI7J G4	D.39
2722190000	VG M50 EXE 31-38 SI7J G4	D.39
2722200000	VG M63 EXE 35-44 SI7J G4	D.39
2722210000	VG M12 EXI 4-6,5 CR7J G4	D.38
2722220000	VG M16 EXI 5-8 CR7J G4	D.38
2722230000	VG M16 EXI 6-10 CR7J G4	D.38
2722240000	VG M20 EXI 7-12 CR7J G4	D.38
2722250000	VG M20 EXI 7-13 CR7J G4	D.38

Order No.	Type	Page
2722260000	VG M20 EXI 11-14 CR7J G4	D.38
2722270000	VG M25 EXI 12-17 CR7J G4	D.38
2722280000	VG M25 EXI 14-18 CR7J G4	D.38
2722290000	VG M32 EXI 16-21 CR7J G4	D.38
2722300000	VG M32 EXI 19-25 CR7J G4	D.38
2722310000	VG M40 EXI 20-28 CR7J G4	D.38
2722320000	VG M40 EXI 23-32 CR7J G4	D.38
2722330000	VG M50 EXI 31-38 CR7J G4	D.38
2722340000	VG M63 EXI 35-44 CR7J G4	D.38
2722350000	VG M12 EXI 4-6,5 SI7J G4	D.39
2722360000	VG M16 EXI 5-8 SI7J G4	D.39
2722370000	VG M16 EXI 6-10 SI7J G4	D.39
2722380000	VG M20 EXI 7-12 SI7J G4	D.39
2722390000	VG M20 EXI 7-13 SI7J G4	D.39
2722400000	VG M20 EXI 11-14 SI7J G4	D.39
2722410000	VG M25 EXI 12-17 SI7J G4	D.39
2722420000	VG M25 EXI 14-18 SI7J G4	D.39
2722430000	VG M32 EXI 16-21 SI7J G4	D.39
2722440000	VG M32 EXI 19-25 SI7J G4	D.39
2722450000	VG M40 EXI 20-28 SI7J G4	D.39
2722460000	VG M40 EXI 23-32 SI7J G4	D.39
2722470000	VG M50 EXI 31-38 SI7J G4	D.39
2722480000	VG M63 EXI 35-44 SI7J G4	D.39

3010000000

3018950000	MP TBF 30/19	C.170

3070000000

3073000000	MOPL K11 STAHL	C.100
3073020000	MOPL K21 STAHL	C.102
3073040000	MOPL K31 STAHL	C.104
3073050000	MOPL K32 STAHL	C.105
3073060000	MOPL K4 STAHL	C.106
3073070000	MOPL K41 STAHL	C.107
3073080000	MOPL K5 STAHL	C.108
3073090000	MOPL K51 STAHL	C.109
3073100000	MOPL K52 STAHL	C.110
3073110000	MOPL K6 STAHL	C.111
3073120000	MOPL K61 STAHL	C.112
3073130000	MOPL K7 STAHL	C.113
3073140000	MOPL K71 STAHL	C.114

3890000000

3896100000	SP M6 15 MSZN	C.52
3896100000	SP M6 15 MSZN	C.53
3896100000	SP M6 15 MSZN	C.54
3896100000	SP M6 15 MSZN	C.55
3896100000	SP M6 15 MSZN	C.56
3896100000	SP M6 15 MSZN	C.57
3896100000	SP M6 15 MSZN	C.58
3896100000	SP M6 15 MSZN	C.59
3896100000	SP M6 15 MSZN	C.60
3896100000	SP M6 15 MSZN	C.61
3896100000	SP M6 15 MSZN	C.62
3896200000	SP M6 20 MSZN	C.52
3896200000	SP M6 20 MSZN	C.53
3896200000	SP M6 20 MSZN	C.54
3896200000	SP M6 20 MSZN	C.55
3896200000	SP M6 20 MSZN	C.56
3896200000	SP M6 20 MSZN	C.57
3896200000	SP M6 20 MSZN	C.58
3896200000	SP M6 20 MSZN	C.59
3896200000	SP M6 20 MSZN	C.60
3896200000	SP M6 20 MSZN	C.61
3896200000	SP M6 20 MSZN	C.62
3896300000	SP M6 30 MSZN	C.52
3896300000	SP M6 30 MSZN	C.53
3896300000	SP M6 30 MSZN	C.54
3896300000	SP M6 30 MSZN	C.55
3896300000	SP M6 30 MSZN	C.56
3896300000	SP M6 30 MSZN	C.57
3896300000	SP M6 30 MSZN	C.58
3896300000	SP M6 30 MSZN	C.59
3896300000	SP M6 30 MSZN	C.60
3896300000	SP M6 30 MSZN	C.61
3896300000	SP M6 30 MSZN	C.62

7900000000

7906080000	BK 4/E	C.116

8000000000

8000003444	KL SET 12W4 S	C.116
8000003444	KL SET 12W4 S	C.150
8000003444	KL SET 12W4 S	C.155
8000003446	KLIPPON K41 2M25AB CSS	C.116
8000003447	KLIPPON K41 3M20AB CSS	C.116
8000003448	KLIPPON POK4 3M20AB CSS	C.150
8000003448	KLIPPON POK4 3M20AB CSS	C.155
8000003589	KLIPPON K41 M25WCSS EX	C.116
8000003591	KLIPPON K41 M20WCSS EX	C.116
8000003593	KLIPPON POK4 M20WCSS EX	C.150
8000003593	KLIPPON POK4 M20WCSS EX	C.155
8000003594	KLIPPON POK4 M20ZCSS EX	C.150
8000003594	KLIPPON POK4 M20ZCSS EX	C.155

Order No.	Type	Page
8000003889	TS15X5 ST POK 0808	C.132
8000003890	TS15X5 ST POK 0811	C.133
8000003890	TS15X5 ST POK 0811	C.137
8000003891	TS15X5 ST POK 0816	C.134
8000003892	TS15X5 ST POK 0819	C.135
8000003908	TS35X7.5 ST K52	C.139
8000003909	TS35X7.5 ST POK 1626	C.140
8000003910	TS35X7.5 ST POK 1636	C.141
8000003911	TS35X7.5 ST POK 1656	C.142
8000003912	TS35X7.5 ST POK 2525	C.143
8000003912	TS35X7.5 ST POK 2525	C.144
8000003913	TS35X7.5 ST POK 4040	C.145
8000003913	TS35X7.5 ST POK 4040	C.146
8000003913	TS35X7.5 ST POK 4040	C.148
8000003914	TS35X7.5 ST POK 2560	C.147
8000004129	MOPL SET BK4 S	C.116
8000004130	KL SET 5Z2.5 S	C.116
8000004132	MOPL SET BK6 S	C.116
8000004133	KL SET 14Z2.5 S	C.116
8000004134	KL SET 13A4 S	C.116
8000004135	MOPL SET BK12 S	C.116
8000004136	KL SET 24Z2.5 S	C.116
8000004137	KL SET 21A4 S	C.116
8000004138	KL SET 5W4 S	C.116
8000004139	KL SET 4Z4 S	C.116
8000004140	KL SET 18W4 S	C.116
8000004142	KL SET 32W4 S	C.116
8000004142	KL SET 32W4 S	C.150
8000004142	KL SET 32W4 S	C.156
8000004143	KL SET 38Z2.5 S	C.116
8000004143	KL SET 38Z2.5 S	C.150
8000004143	KL SET 38Z2.5 S	C.156
8000004144	KL SET 6A4 S	C.150
8000004144	KL SET 6A4 S	C.152
8000004145	KL SET 10A4 S	C.150
8000004145	KL SET 10A4 S	C.153
8000004146	KL SET 18A4 S	C.150
8000004146	KL SET 18A4 S	C.154
8000004147	KLIPPON K1 1,5M16AB CSS	C.116
8000004148	KLIPPON K1 1M20AB CSS	C.116
8000004149	KLIPPON K11 2M16AB CSS	C.116
8000004150	KLIPPON K11 2M20AB CSS	C.116
8000004151	KLIPPON K2 2M20AB CSS	C.116
8000004152	KLIPPON K21 3M16AB CSS	C.116
8000004153	KLIPPON K3 4M20AB CSS	C.116
8000004154	KLIPPON K31 4M20AB CSS	C.116
8000004155	KLIPPON K4 2M20AB CSS	C.116
8000004158	KLIPPON K5 4M20AB CSS	C.116
8000004160	KLIPPON POK1 2M16AB CSS	C.150
8000004160	KLIPPON POK1 2M16AB CSS	C.152
8000004161	KLIPPON POK2 2M20AB CSS	C.150
8000004161	KLIPPON POK2 2M20AB CSS	C.153
8000004162	KLIPPON POK3 4M20AB CSS	C.150
8000004162	KLIPPON POK3 4M20AB CSS	C.154
8000004164	KLIPPON POK51 4M20ABCSS	C.150
8000004164	KLIPPON POK51 4M20ABCSS	C.156
8000004184	KLIPPON K01 1M16AB CSS	C.116
8000004202	KLIPPON K1 M16BCSS EX	C.116
8000004203	KLIPPON K1 M20BCSS EX	C.116
8000004204	KLIPPON K11 M16ZCSS EX	C.116
8000004207	KLIPPON K11 M16ACSS EX	C.116
8000004208	KLIPPON K11 M20ZCSS EX	C.116
8000004209	KLIPPON K11 M20ACSS EX	C.116
8000004210	KLIPPON K2 M20BCSS EX	C.116
8000004211	KLIPPON K21 M16ZCSS EX	C.116
8000004212	KLIPPON K21 M16ACSS EX	C.116
8000004213	KLIPPON K3 M20BCSS EX	C.116
8000004214	KLIPPON K31 M20ZCSS EX	C.116
8000004218	KLIPPON K5 4M20WCSS EX	C.116
8000004219	KLIPPON K5 4M20ZCSS EX	C.116
8000004220	KLIPPON K52 M20WCSS EX	C.116
8000004221	KLIPPON K52 M20ZCSS EX	C.116
8000004222	KLIPPON POK1 M16BCSS EX	C.150
8000004222	KLIPPON POK1 M16BCSS EX	C.152
8000004223	KLIPPON POK1 M16ACSS EX	C.150
8000004223	KLIPPON POK1 M16ACSS EX	C.152
8000004224	KLIPPON POK2 M20BCSS EX	C.150
8000004224	KLIPPON POK2 M20BCSS EX	C.153
8000004225	KLIPPON POK2 M20ACSS EX	C.150
8000004225	KLIPPON POK2 M20ACSS EX	C.153
8000004226	KLIPPON POK3 M20BCSS EX	C.150
8000004226	KLIPPON POK3 M20BCSS EX	C.154
8000004228	KLIPPON POK3 M20ACSS EX	C.150
8000004228	KLIPPON POK3 M20ACSS EX	C.154
8000004229	KLIPPON POK51 M20WCSS E	C.150
8000004229	KLIPPON POK51 M20WCSS E	C.156
8000004230	KLIPPON POK51 M20ZCSS E	C.150
8000004230	KLIPPON POK51 M20ZCSS E	C.156
8000004365	KL SET KLIPPON POK1 BK4	C.150
8000004365	KL SET KLIPPON POK1 BK4	C.152
8000004366	KL SET KLIPPON POK2 BK6	C.150
8000004366	KL SET KLIPPON POK2 BK6	C.153
8000004367	KL SET KLIPPON POK3BK12	C.150
8000004367	KL SET KLIPPON POK3BK12	C.154
8000004497	MOPL K3 BKVARIO SET	C.116
8000006708	TS35X7.5 ST KTB2215 VER	C.15
8000006709	TS35X7.5 ST KTB2626 VER	C.16
8000006709	TS35X7.5 ST KTB2626 VER	C.17
8000006710	TS35X7.5 ST KTB3030 VER	C.18

Order No.	Type	Page
8000006710	TS35X7.5 ST KTB3030 VER	C.19
8000006711	TS35X7.5 ST KTB3526 VER	C.20
8000006711	TS35X7.5 ST KTB3526 VER	C.21
8000006712	TS35X7.5 ST KTB4030 VER	C.22
8000006712	TS35X7.5 ST KTB4030 VER	C.23
8000006713	TS35X7.5 ST KTB4538 VER	C.24
8000006713	TS35X7.5 ST KTB4538 VER	C.25
8000006714	TS35X7.5 ST KTB4848 VER	C.26
8000006714	TS35X7.5 ST KTB4848 VER	C.27
8000006715	TS35X7.5 ST KTB5535 VER	C.28
8000006715	TS35X7.5 ST KTB5535 VER	C.29
8000006716	TS35X7.5 ST KTB6245 VER	C.30
8000006716	TS35X7.5 ST KTB6245 VER	C.31
8000006717	TS35X7.5 ST KTB7650 VER	C.32
8000006717	TS35X7.5 ST KTB7650 VER	C.33
8000006718	TS35X7.5 ST KTB9161 VER	C.34
8000006718	TS35X7.5 ST KTB9161 VER	C.35
8000006719	TS35X7.5 ST KTB9874 VER	C.36
8000006720	TS35X7.5 ST KTB2215 HOR	C.15
8000006721	TS35X7.5 ST KTB3526 HOR	C.16
8000006721	TS35X7.5 ST KTB3526 HOR	C.17
8000006721	TS35X7.5 ST KTB3526 HOR	C.20
8000006721	TS35X7.5 ST KTB3526 HOR	C.21
8000006722	TS35X7.5 ST KTB3030 HOR	C.18
8000006722	TS35X7.5 ST KTB3030 HOR	C.19
8000006723	TS35X7.5 ST KTB4030 HOR	C.22
8000006723	TS35X7.5 ST KTB4030 HOR	C.23
8000006724	TS35X7.5 ST KTB4538 HOR	C.24
8000006724	TS35X7.5 ST KTB4538 HOR	C.25
8000006725	TS35X7.5 ST KTB4848 HOR	C.26
8000006725	TS35X7.5 ST KTB4848 HOR	C.27
8000006726	TS35X7.5 ST KTB5535 HOR	C.28
8000006726	TS35X7.5 ST KTB5535 HOR	C.29
8000006727	TS35X7.5 ST KTB6245 HOR	C.30
8000006727	TS35X7.5 ST KTB6245 HOR	C.31
8000006728	TS35X7.5 ST KTB7650 HOR	C.32
8000006728	TS35X7.5 ST KTB7650 HOR	C.33
8000006729	TS35X7.5 ST KTB9161 HOR	C.34
8000006729	TS35X7.5 ST KTB9161 HOR	C.35
8000006730	TS35X7.5 ST KTB9874 HOR	C.36
8000028394	STB 1 EXIA	C.76
8000028394	STB 1 EXIA	C.78
8000028395	STB 2 Exe	C.76
8000028395	STB 2 Exe	C.79
8000028396	STB 3 Exe	C.76
8000028396	STB 3 Exe	C.80
8000028397	STB 4 Exe	C.76
8000028397	STB 4 Exe	C.81
8000028398	KTB MH 221513 Exia	C.42
8000028398	KTB MH 221513 Exia	C.44
8000028399	KTB MH 262615 Exia	C.42
8000028399	KTB MH 262615 Exia	C.45
8000028400	KTB QL 303020 EXE	C.42
8000028400	KTB QL 303020 EXE	C.46
8000028401	KTB QL 484820 Exe	C.42
8000028401	KTB QL 484820 Exe	C.47
8000032382	TS15X5 ST POK 0823	C.136
8000037552	TS35X7.5 ST KEBI 80 VER	C.62
8000037553	TS35X7.5 ST KEBI 60 VER	C.60
8000037553	TS35X7.5 ST KEBI 60 VER	C.61
8000037554	TS35X7.5 ST KEBI 50 VER	C.58
8000037554	TS35X7.5 ST KEBI 50 VER	C.59
8000037555	TS35X7.5 ST KEBI 40 VER	C.55
8000037555	TS35X7.5 ST KEBI 40 VER	C.56
8000037555	TS35X7.5 ST KEBI 40 VER	C.57
8000037556	TS35X7.5 ST KEBI 30 VER	C.52
8000037556	TS35X7.5 ST KEBI 30 VER	C.53
8000037556	TS35X7.5 ST KEBI 30 VER	C.54
8000037557	TS35X7.5 ST FPC 20 HOR	C.185
8000037558	TS35X7.5 ST FPC 20 VER	C.185
8000037558	TS35X7.5 ST FPC 20 VER	C.186
8000037559	TS35X7.5 ST FPC 30 HOR	C.185
8000037560	TS35X7.5 ST FPC 40 HOR	C.186
8000037560	TS35X7.5 ST FPC 40 HOR	C.187
8000037561	TS35X7.5 ST FPC 30 VER	C.187
8000037562	TS35X7.5 ST FPC 40 VER	C.187
8000037563	TS35X7.5 ST FPC 60 HOR	C.187
8000037568	TS35X7.5 ST POK 1222	C.138
8000037598	TS15X5 ST MPC1217 VER	C.178
8000037598	TS15X5 ST MPC1217 VER	C.179
8000037598	TS15X5 ST MPC1217 VER	C.180
8000037599	TS15X5 ST MPC0712 VER	C.178
8000037600	TS35X7.5 ST MPC1725 VER	C.182
8000037600	TS35X7.5 ST MPC1725 VER	C.183
8000037601	TS35X7.5 ST MPC1725 HOR	C.182
8000037601	TS35X7.5 ST MPC1725 HOR	C.183
8000037603	TS 35x105_MPC_12	C.178
8000037603	TS 35x105_MPC_12	C.179
8000037603	TS 35x105_MPC_12	C.181
8000037604	TS15X5 ST FPC 20 VER	C.185
8000037604	TS15X5 ST FPC 20 VER	C.186
8000037605	TS35 MPC 1717 VER	C.179
8000037605	TS35 MPC 1717 VER	C.180
8000037605	TS35 MPC 1717 VER	C.181

8560000000

8563410000	TS35X7.5 ST STB 4 STB 6	C.73
8563410000	TS35X7.5 ST STB 4 STB 6	C.74
8563410000	TS35X7.5 ST STB 4 STB 6	C.75

8680000000

8683740000	TS35X7.5 ST STB 1.1 STB 2	C.68
8683740000	TS35X7.5 ST STB 1.1 STB 2	C.69
8683740000	TS35X7.5 ST STB 1.1 STB 2	C.70

8800000000

8803610000	TS35X7.5 ST STB 5	C.73
8803610000	TS35X7.5 ST STB 5	C.74
8803610000	TS35X7.5 ST STB 5	C.75

9000000000

9009160000	SD TH20	C.96
9009160000	SD TH20	C.97
9009160000	SD TH20	C.98
9009160000	SD TH20	C.99
9009160000	SD TH20	C.100
9009160000	SD TH20	C.101
9009160000	SD TH20	C.102
9009160000	SD TH20	C.103
9009160000	SD TH20	C.104
9009160000	SD TH20	C.105
9009160000	SD TH20	C.106
9009160000	SD TH20	C.107
9009160000	SD TH20	C.108
9009160000	SD TH20	C.109
9009160000	SD TH20	C.110
9009160000	SD TH20	C.111
9009160000	SD TH20	C.112
9009160000	SD TH20	C.113
9009160000	SD TH20	C.114

9500000000

9500950000	MP TBF 56/30	C.172
9500960000	MP TBF 49/30	C.172
9502720000	MP TBF 19/15	C.170
9502730000	MP TBF 30/30	C.171
9502740000	MP TBF 37/30	C.171
9502750000	MP TBF 60/30	C.173
9502800000	TBF 49/30/18 7035	C.168
9502800000	TBF 49/30/18 7035	C.172
9502810000	TBF 56/30/18 7035	C.168
9502810000	TBF 56/30/18 7035	C.172
9502820000	TBF 60/37/18 7035	C.168
9502820000	TBF 60/37/18 7035	C.174
9502830000	TBF 60/60/18 7035	C.168
9502830000	TBF 60/60/18 7035	C.174
9502840000	TBF 49/30/21 TRSP	C.168
9502840000	TBF 49/30/21 TRSP	C.172
9502850000	TBF 56/30/21 TRSP	C.168
9502850000	TBF 56/30/21 TRSP	C.172
9502860000	TBF 60/37/21 TRSP	C.168
9502860000	TBF 60/37/21 TRSP	C.174
9502870000	TBF 60/60/21 TRSP	C.168
9502870000	TBF 60/60/21 TRSP	C.174
9502910000	MP TBF 60/37	C.174
9502920000	MP TBF 60/60	C.174

9510000000

9510570000	POK MOPL 0808	C.132
9510580000	POK MOPL 0811	C.133
9510590000	POK MOPL 1212	C.137
9510600000	POK MOPL 1222	C.138
9510610000	POK MOPL 1616	C.139
9510620000	POK MOPL 1626	C.140
9510630000	POK MOPL 1636	C.141
9510640000	POK MOPL 2525	C.143
9510640000	POK MOPL 2525	C.144
9510650000	POK MOPL 2540	C.145
9510650000	POK MOPL 2540	C.146
9510660000	POK MOPL 2560	C.147
9510670000	POK MOPL 4040	C.148
9510680000	POK MOPL 0816	C.134
9510690000	POK MOPL 0819	C.135
9510710000	POK MOPL 1656	C.142
9510900000	MF POK SMALL	C.132
9510900000	MF POK SMALL	C.133
9510900000	MF POK SMALL	C.134
9510900000	MF POK SMALL	C.135
9510900000	MF POK SMALL	C.136
9510910000	MF POK BIG	C.137
9510910000	MF POK BIG	C.138
9510910000	MF POK BIG	C.139
9510910000	MF POK BIG	C.140
9510910000	MF POK BIG	C.141
9510910000	MF POK BIG	C.142
9510910000	MF POK BIG	C.143
9510910000	MF POK BIG	C.144
9510910000	MF POK BIG	C.145
9510910000	MF POK BIG	C.146
9510910000	MF POK BIG	C.147
9510910000	MF POK BIG	C.148

9520000000

9526840000	KLIPPON K1 EX	C.94
9526850000	KLIPPON K11 EX	C.94
9526860000	KLIPPON K2 EX	C.94
9526870000	KLIPPON K21 EX	C.94
9526880000	KLIPPON K3 EX	C.94
9526890000	KLIPPON K31 EX	C.94
9526900000	KLIPPON K32 EX	C.94
9526910000	KLIPPON K4 EX	C.94
9526920000	KLIPPON K41 EX	C.94
9526930000	KLIPPON K5 EX	C.94
9526940000	KLIPPON K51 EX	C.94
9526950000	KLIPPON K52 EX	C.94
9526960000	KLIPPON K6 EX	C.94
9526970000	KLIPPON K61 EX	C.94
9526980000	KLIPPON K7 EX	C.94
9526990000	KLIPPON K71 EX	C.94
9527590000	KLIPPON K MF KIT 25	C.107
9527590000	KLIPPON K MF KIT 25	C.109
9527590000	KLIPPON K MF KIT 25	C.110
9527590000	KLIPPON K MF KIT 25	C.112
9527590000	KLIPPON K MF KIT 25	C.114
9529080000	KLIPPON K MF KIT 16	C.108
9529080000	KLIPPON K MF KIT 16	C.111
9529080000	KLIPPON K MF KIT 16	C.113
9529090000	KLIPPON K0 RAL7001	C.94
9529090000	KLIPPON K0 RAL7001	C.96
9529100000	KLIPPON K01 RAL7001	C.94
9529100000	KLIPPON K01 RAL7001	C.97
9529110000	KLIPPON K02 RAL7001	C.94
9529110000	KLIPPON K02 RAL7001	C.98
9529120000	KLIPPON K1 RAL7001	C.94
9529120000	KLIPPON K1 RAL7001	C.99
9529130000	KLIPPON K11 RAL7001	C.94
9529130000	KLIPPON K11 RAL7001	C.100
9529140000	KLIPPON K2 RAL7001	C.94
9529140000	KLIPPON K2 RAL7001	C.101
9529150000	KLIPPON K21 RAL7001	C.94
9529150000	KLIPPON K21 RAL7001	C.102
9529160000	KLIPPON K3 RAL7001	C.94
9529160000	KLIPPON K3 RAL7001	C.103
9529170000	KLIPPON K31 RAL7001	C.94
9529170000	KLIPPON K31 RAL7001	C.104
9529180000	KLIPPON K32 RAL7001	C.94
9529180000	KLIPPON K32 RAL7001	C.105
9529190000	KLIPPON K4 RAL7001	C.94
9529190000	KLIPPON K4 RAL7001	C.106
9529200000	KLIPPON K41 RAL7001	C.94
9529200000	KLIPPON K41 RAL7001	C.107
9529210000	KLIPPON K5 RAL7001	C.94
9529210000	KLIPPON K5 RAL7001	C.108
9529220000	KLIPPON K51 RAL7001	C.94
9529220000	KLIPPON K51 RAL7001	C.109
9529230000	KLIPPON K52 RAL7001	C.94
9529230000	KLIPPON K52 RAL7001	C.110
9529240000	KLIPPON K6 RAL7001	C.94
9529240000	KLIPPON K6 RAL7001	C.111
9529250000	KLIPPON K61 RAL7001	C.94
9529250000	KLIPPON K61 RAL7001	C.112
9529260000	KLIPPON K7 RAL7001	C.94
9529260000	KLIPPON K7 RAL7001	C.113
9529270000	KLIPPON K71 RAL7001	C.94
9529270000	KLIPPON K71 RAL7001	C.114

9530000000

9535170000	MPC 07/12/07 7035	C.176
9535170000	MPC 07/12/07 7035	C.178
9535180000	MPC 07/12/07 TRSP	C.176
9535180000	MPC 07/12/07 TRSP	C.178
9535190000	MPC 07/12/10 7035	C.176
9535200000	MPC 07/12/10 TRSP	C.176
9535210000	MPC 07/12/12 7035	C.176
9535210000	MPC 07/12/12 7035	C.178
9535220000	MPC 07/12/12 TRSP	C.176
9535220000	MPC 07/12/12 TRSP	C.178
9535230000	MPC 12/12/07 7035	C.176
9535230000	MPC 12/12/07 7035	C.179
9535240000	MPC 12/12/07 TRSP	C.176
9535240000	MPC 12/12/07 TRSP	C.179
9535250000	MPC 12/12/10 7035	C.176
9535260000	MPC 12/12/10 TRSP	C.176
9535270000	MPC 12/12/12 7035	C.176
9535280000	MPC 12/12/12 TRSP	C.176
9535290000	MPC 12/17/07 7035	C.176
9535290000	MPC 12/17/07 7035	C.179
9535300000	MPC 12/17/07 TRSP	C.176
9535300000	MPC 12/17/07 TRSP	C.179
9535310000	MPC 12/17/10 7035	C.176
9535310000	MPC 12/17/10 7035	C.180
9535320000	MPC 12/17/10 TRSP	C.176
9535320000	MPC 12/17/10 TRSP	C.180
9535330000	MPC 12/17/12 7035	C.176
9535330000	MPC 12/17/12 7035	C.180
9535340000	MPC 12/17/12 TRSP	C.176
9535340000	MPC 12/17/12 TRSP	C.180
9535350000	MPC 12/17/15 7035	C.176
9535360000	MPC 12/17/15 TRSP	C.176
9535370000	MPC 17/17/07 7035	C.176
9535370000	MPC 17/17/07 7035	C.181
9535380000	MPC 17/17/07 TRSP	C.176
9535380000	MPC 17/17/07 TRSP	C.181
9535390000	MPC 17/17/10 7035	C.176
9535400000	MPC 17/17/10 TRSP	C.176
9535410000	MPC 17/17/12 7035	C.176
9535430000	MPC 17/17/15 7035	C.176
9535430000	MPC 17/17/15 7035	C.182
9535440000	MPC 17/17/15 TRSP	C.176
9535440000	MPC 17/17/15 TRSP	C.182
9535450000	MPC 17/25/07 7035	C.176
9535450000	MPC 17/25/07 7035	C.182
9535470000	MPC 17/25/10 7035	C.176
9535470000	MPC 17/25/10 7035	C.183
9535480000	MPC 17/25/10 TRSP	C.176
9535480000	MPC 17/25/10 TRSP	C.183
9535490000	MPC 17/25/15 7035	C.176
9535490000	MPC 17/25/15 7035	C.183
9535500000	MPC 17/25/15 TRSP	C.176
9535500000	MPC 17/25/15 TRSP	C.183
9535540000	MP MPC 07/12	C.178
9535550000	MP MPC 12/12	C.179
9535560000	MP MPC 12/17	C.179
9535560000	MP MPC 12/17	C.180
9535570000	MP MPC 17/17	C.181
9535570000	MP MPC 17/17	C.182
9535580000	MP MPC 17/25	C.182
9535580000	MP MPC 17/25	C.183
9535590000	HG MPC	C.178
9535590000	HG MPC	C.179
9535590000	HG MPC	C.180
9535590000	HG MPC	C.181
9535590000	HG MPC	C.182
9535590000	HG MPC	C.183
9535600000	MF MPC	C.178
9535600000	MF MPC	C.179
9535600000	MF MPC	C.180
9535600000	MF MPC	C.181
9535600000	MF MPC	C.182
9535600000	MF MPC	C.183
9535680000	FPC 20/20/13 TRSP	C.184
9535680000	FPC 20/20/13 TRSP	C.185
9535690000	FPC 20/20/13 7035	C.184
9535690000	FPC 20/20/13 7035	C.185
9535700000	FPC 20/30/13 TRSP	C.184
9535700000	FPC 20/30/13 TRSP	C.185
9535710000	FPC 20/30/13 7035	C.184
9535710000	FPC 20/30/13 7035	C.185
9535720000	FPC 20/40/13 TRSP	C.184
9535720000	FPC 20/40/13 TRSP	C.186
9535730000	FPC 20/40/13 7035	C.184
9535730000	FPC 20/40/13 7035	C.186
9535740000	FPC 30/30/13 TRSP	C.184
9535740000	FPC 30/30/13 TRSP	C.186
9535750000	FPC 30/30/13 7035	C.184
9535750000	FPC 30/30/13 7035	C.186
9535760000	FPC 30/40/13 TRSP	C.184
9535760000	FPC 30/40/13 TRSP	C.187
9535770000	FPC 30/40/13 7035	C.184
9535770000	FPC 30/40/13 7035	C.187
9535810000	FPC 40/60/13 7035	C.184
9535810000	FPC 40/60/13 7035	C.187
9535820000	FPC 40/60/13 TRSP	C.184
9535820000	FPC 40/60/13 TRSP	C.187
9535920000	MP FPC 20/20	C.185
9535930000	MP FPC 20/30	C.185
9535940000	MP FPC 20/40	C.186
9535950000	MP FPC 30/30	C.186
9535960000	MP FPC 30/40	C.187
9535980000	MP FPC 40/60	C.187
9535990000	HG FPC	C.185
9535990000	HG FPC	C.186
9535990000	HG FPC	C.187
9536040000	MF FPC	C.185
9536040000	MF FPC	C.186
9536040000	MF FPC	C.187

X

Addresses worldwide

Let's connect.



You can find all Weidmüller addresses and your local contact on the internet at: www.weidmueller.com/countries

Let's connect.


Sales company
Representation abroad
Distributors
UA
RU
KZ
TR
AZ
TN
IL
AE
IN
CN
HK
TW
KR
JP
TH
PH
VN
MY
SG
ID
MU
ZA
AU
NZ

We cannot guarantee that there are no mistakes in the publications or software provided by us to the customer for the purpose of making orders. We try our best to quickly correct errors in our printed media.

All orders are based on our general terms of delivery, which can be reviewed on the websites of our group companies where you place your order. On demand we can also send the general terms of delivery to you.

Weidmüller – Your partner in Industrial Connectivity

As experienced experts we support our customers and partners around the world with products, solutions and services in the industrial environment of power, signal and data. We are at home in their industries and markets and know the technological challenges of tomorrow. We are therefore continuously developing innovative, sustainable and useful solutions for their individual needs. Together we set standards in Industrial Connectivity.

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
32758 Detmold, Germany
T +49 5231 14-0
F +49 5231 14-292083
www.weidmueller.com

Personal support can
be found on our website:
www.weidmueller.com/contact

Made in Germany

4 050118 752533

Order number: 2712630000/03/2020/SMM

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Enclosures, Boxes & Cases ***category:***

Click to view products by Weidmuller ***manufacturer:***

Other Similar products are found below :

585-R-WH-PK M-10-PLATED 60566-01-000 HPL-9VB BATT DOOR M18-PLTD M-21-PLATED 63310-01-000 6711GSKT 71884-29-028 LH45-100 Black 72868-510-000 CNS-0000 Black 72883-510-000 CNS-0101 Black 72906-510-000 CNS-0407 Black 73092-510-000 CNM-0101 Black 73105-510-000 CNL-0101 Black 73395-510-039 CNS-0006 Bone 74016-510-000 CNL-0006 Black 74257-510-000 CNL-0004 MDC-1183-PLAIN-ALUM MDC-1183-PTD MDC-13104-PTD MDC-321-PTD MDC-973-PTD 76 77153-01-028 FLX6030 83535-01-508 90026-501-000 PS36-200 116-508 120-407 120-910 127-908 130-008 1301170079 1322GSKTEP 1325GSKT3 138-PLAIN 1434-1210 EAS-500 (BLACK ANO) 1804RP-RB-PK 190-005 2202307 KAB3321 BLACK KAB3421 2697466 S52213 2901123 2901699 A0645271 A20P20 2106-IR PERF-850-PLN