

Klippon K (aluminium empty enclosure) KLIPPON K51 RAL7001

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The Klippon® brand has long stood for competence and quality in housings – particularly when turnkey, customer-specific solutions for standard industrial applications and applications in explosive risk zones are concerned.

Improved products that meet all application requirements: this was Weidmüller's aim when modernising and upgrading the Klippon® K enclosure series. No matter what kind of application the customer is planning; Weidmüller is able to provide a wide range of aluminium enclosures precisely fitting the customer's requirements.

- Available in two surface finishes: natural and powder-coated (RAL 7001)
- Available with moulded silicone or chloroprene gasket as standard
- Uniform Torx slotted screw head for 19 enclosure sizes
- Mounting holes outside of the gasket area
- High IP protection classes: IP66, IP67 and IP68
- Impact resistance of up to 7 (10) Joules
- The enclosures are approved according ATEX, IECEx, GOST Ex, GOST, cULus, Russian Maritime Register and Germanischer Lloyd as well as the empty enclosure standard.
- Alloy is resistant to salt water
- Standardised distributor enclosures with threaded holes and a variety of terminal configurations

General ordering data

| | |
|------------|--|
| Type | KLIPPON K51 RAL7001 |
| Order No. | 9529220000 |
| Version | Klippon K (aluminium empty enclosure), Empty enclosure, Aluminium enclosure, Height: 120 mm, Width: 220 mm, Depth: 81 mm, Material: Aluminium AISi12, Powder-coated, textured, Silver grey |
| GTIN (EAN) | 4008190918118 |
| Qty. | 1 pc(s). |

Klippon K (aluminium empty enclosure) KLIPPON K51 RAL7001

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|----------------------------|---------|-----------------------------|------------|
| Width | 220 mm | Width (inches) | 8.661 inch |
| Height | 120 mm | Height (inches) | 4.724 inch |
| Depth | 81 mm | Depth (inches) | 3.189 inch |
| Mounting dimension - width | 204 mm | Mounting dimension - height | 82 mm |
| Weight | 1,280 g | Net weight | 1,399 g |

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Cable glands, left

| | | | |
|-----|---|-----|---|
| M12 | 6 | M16 | 3 |
| M20 | 2 | M25 | 1 |
| M32 | 1 | | |

Cable glands, right

| | | | |
|-----|---|-----|---|
| M12 | 6 | M16 | 3 |
| M20 | 2 | M25 | 1 |
| M32 | 1 | | |

Cable glands, top/bottom

| | | | |
|-----|----|-----|----|
| M12 | 23 | M16 | 14 |
| M20 | 8 | M25 | 5 |
| M32 | 3 | M40 | 3 |

Certificate numbers enclosure

| | | | |
|-----------------------------|------------|----------------------------|--------------|
| Certificate No. (GERMLLOYD) | TAE00002SM | Certificate No. (MARITREG) | 14.40040.250 |
| Certificate no. (cULus) | E197061 | | |

General information

| | | | |
|-----------------------------|--|---------------------------------|--|
| Areas of use | Process industry, Transportation, Marine engineering, Packaging industry, Harbour facilities, Machine construction | Material thickness | 4.5 mm |
| Material thickness of cover | 4 mm | Material thickness of enclosure | 4.5 mm |
| Material | Aluminium AlSi12 | Seal material | Chloroprene |
| Surface finish | Powder-coated, textured | Operating temperature, min. | -40 °C |
| Operating temperature, max. | 80 °C | Impact resistance | 10.00 J |
| Protection degree | IP66, IP67, IP68 | Note: protection class | IP68 (t=72h, h=1m) |
| Enclosure attachment | Holes 6 mm | Lid attachment | M6 torx stainless steel screws with slot |
| Integral fixing | Threaded holes M5 | | |

horizontal assembly

| | | | |
|-----------------|------|-----------------------------|------|
| WDU 10 / ZDU 10 | 1x15 | WDU 2,5 / ZDU 2,5 / IDU 2,5 | 1x31 |
| WDU 4 / ZDU 4 | 1x26 | WDU 6 / ZDU 6 | 1x19 |

Klippon K (aluminium empty enclosure) KLIPPON K51 RAL7001

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

vertical assembly

WDU 2,5 / ZDU 2,5 / IDU 2,5

*

WDU 4 / ZDU 4

*

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC000058 | ETIM 4.0 | EC000058 |
| ETIM 5.0 | EC000058 | ETIM 6.0 | EC000261 |
| UNSPSC | 31-26-15-02 | eClass 5.1 | 27-14-91-07 |
| eClass 6.2 | 27-14-91-07 | eClass 7.1 | 27-14-91-07 |
| eClass 8.1 | 27-14-91-07 | eClass 9.0 | 27-18-01-01 |
| eClass 9.1 | 27-18-92-90 | | |

Approvals

Approvals



ROHS

Conform

Downloads

| | |
|---|--|
| Approval/Certificate/Document of Conformity | EU Declaration of Conformity - Klippon K Empty Enclosures - DoC DE PS2410 160412 001ISS01 |
| Brochure/Catalogue | MB KLIPPON ENCL.TECN EN CAT 5 ENCL 17/18 EN FL RAILWAY 2014 EN |
| Engineering Data | EPLAN, WSCAD |
| Engineering Data | STEP |
| Tender specification | Klippon K51 RAL7001_9529220000_DE Klippon K51 RAL7001_9529220000_EN |
| User Documentation | MB KLIPPON ENCL.TECN DE Assembly guidelines - empty enclosures |

**Klippon K (aluminium empty enclosure)
KLIPPON K51 RAL7001**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings**Dimensioned drawing**

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Enclosures, Boxes, & Cases](#) category:

Click to view products by [Weidmuller](#) manufacturer:

Other Similar products are found below :

[CR-425 PAINTED](#) [585-R-WH-PK](#) [M-10-PLATED](#) [60221-01](#) [60566-01-000](#) [HPL-9VB BATT DOOR](#) [M-16-LID-PLATED](#) [M18-PLTD](#) [M-21-LID-PLATED](#) [M-21-PLATED](#) [M-23-PLATED](#) [CU-281-MB](#) [6711GSKT](#) [71884-29-028](#) [LH45-100 Black](#) [7200B](#) [72868-510-000](#) [CNS-0000 Black](#) [72883-510-000](#) [CNS-0101 Black](#) [72906-510-000](#) [CNS-0407 Black](#) [73091-510-000](#) [CNM-0000-BLACK Kit](#) [73092-510-000](#) [CNM-0101 Black](#) [73108-510-000](#) [CNL-0303 Black](#) [73395-510-039](#) [CNS-0006 Bone](#) [74257-510-000](#) [CNL-0004](#) [MDC-1183-PLAIN-ALUM](#) [MDC-1183-PTD](#) [MDC-13104-PLAIN-ALUM](#) [MDC-211 - PAINTED IVORY/BEIGE](#) [MDC-321-PTD](#) [MDC-432-PLAIN-ALUM](#) [MDC-973-PTD](#) [76](#) [77153-01-028](#) [FLX6030](#) [83535-01-508](#) [PS-11296-G](#) [PS-11298-B](#) [116-508](#) [120-407](#) [120-412](#) [120-909](#) [120-455](#) [R272-100-000](#) [120-910](#) [R501-001-010](#) [R508-080-000](#) [R508-160-000](#) [R530-120-000](#) [R530-122-000](#) [R530-200-000](#) [R531-160-000](#) [R531-200-000](#) [R582-080-100](#)