VT SF 6/21 MC NE BL VO



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com



Similar to illustration

SlimFix are conductor and cable markers with a spacesaving design. The markers can be fitted even after the conductor has been installed. They consist of halogenfree material and comply with flammability rating V0/V2. SlimFix is an acknowledged and accredited marker type for traffic engineering applications. The SF tool allows easy installation, even in case of small markers.

Advantages:

- Halogen-free material
- Flammability rating V0/V2
- Approved and accredited markers for traffic engineering applications, etc.
- Has to be fixed with cable ties if the conductor crosssection is larger than 16.0 mm²
- Markers in proven MultiCard format



General ordering data

Version	SlimFix, Conductor and cable markers, 5.8 - 7.8
	mm, 21 x 8.4 mm, blue
Order No.	<u>1730560002</u>
Туре	VT SF 6/21 MC NE BL VO
GTIN (EAN)	4008190954628
Qty.	160 pc(s).
compatible printer	<u>2438520000 2438510000</u>

Technical data

VT SF 6/21 MC NE BL VO



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Depth	8.5 mm	Depth (inches)	0.335 inch
Height	21 mm	Height (inches)	0.827 inch
Net weight	1.006 g	Width	8.4 mm
Width (inches)	0.331 inch		
Temperatures			
Operating temperature range	-50120 °C		
General data			
Colour	blue	Halogen	No
Material	Polyamide 66	Number of markers per combination	1 MultiCard = Conductor and cable markers
Operating temperature range	-50120 °C	Operating temperature range, max.	120 °C
Operating temperature range, min.	-50 °C	Recommended industries	Transportation, Machinery
Size of labelling field	21 x 8.4 mm	Type of printing	neutral
UL 94 flammability rating	V-0	Width	8.4 mm
Conductor and cable marke	rs		
	-	Conductor O.D. may	7.8 mm
Conductor O.D.	5.8 - 7.8 mm	Conductor O.D., max.	7.8 mm
Conductor O.D. Conductor O.D., min.	5.8 - 7.8 mm 5.8 mm	Conductor cross-section, max.	16 mm²
Conductor O.D.	5.8 - 7.8 mm		
Conductor O.D. Conductor O.D., min. Conductor cross-section, min.	5.8 - 7.8 mm 5.8 mm 10 mm ²	Conductor cross-section, max.	16 mm²
Conductor O.D. Conductor O.D., min. Conductor cross-section, min. Halogen Classifications	5.8 - 7.8 mm 5.8 mm 10 mm ² No	Conductor cross-section, max. Cross-section for connected wire	16 mm ² 10 - 16 mm ²
Conductor O.D. Conductor O.D., min. Conductor cross-section, min. Halogen Classifications ETIM 6.0	5.8 - 7.8 mm 5.8 mm 10 mm ² No EC001530	Conductor cross-section, max. Cross-section for connected wire ETIM 7.0	16 mm ² 10 - 16 mm ² EC001530
Conductor O.D. Conductor O.D., min. Conductor cross-section, min. Halogen Classifications ETIM 6.0 ECLASS 9.0	5.8 - 7.8 mm 5.8 mm 10 mm ² No EC001530 27-40-04-01	Conductor cross-section, max. Cross-section for connected wire ETIM 7.0 ECLASS 9.1	16 mm ² 10 - 16 mm ² EC001530 27-40-04-01
Conductor O.D. Conductor O.D., min. Conductor cross-section, min. Halogen Classifications ETIM 6.0	5.8 - 7.8 mm 5.8 mm 10 mm ² No EC001530	Conductor cross-section, max. Cross-section for connected wire ETIM 7.0	16 mm ² 10 - 16 mm ² EC001530
Conductor O.D. Conductor O.D., min. Conductor cross-section, min. Halogen Classifications ETIM 6.0 ECLASS 9.0	5.8 - 7.8 mm 5.8 mm 10 mm ² No EC001530 27-40-04-01	Conductor cross-section, max. Cross-section for connected wire ETIM 7.0 ECLASS 9.1	16 mm ² 10 - 16 mm ² EC001530 27-40-04-01
Conductor O.D. Conductor O.D., min. Conductor cross-section, min. Halogen Classifications ETIM 6.0 ECLASS 9.0 ECLASS 10.0	5.8 - 7.8 mm 5.8 mm 10 mm ² No EC001530 27-40-04-01	Conductor cross-section, max. Cross-section for connected wire ETIM 7.0 ECLASS 9.1	16 mm ² 10 - 16 mm ² EC001530 27-40-04-01
Conductor O.D. Conductor O.D., min. Conductor cross-section, min. Halogen Classifications ETIM 6.0 ECLASS 9.0 ECLASS 10.0 Approvals	5.8 - 7.8 mm 5.8 mm 10 mm ² No EC001530 27-40-04-01 27-40-04-01	Conductor cross-section, max. Cross-section for connected wire ETIM 7.0 ECLASS 9.1	16 mm ² 10 - 16 mm ² EC001530 27-40-04-01
Conductor O.D. Conductor O.D., min. Conductor cross-section, min. Halogen Classifications ETIM 6.0 ECLASS 9.0 ECLASS 10.0 Approvals ROHS	5.8 - 7.8 mm 5.8 mm 10 mm ² No EC001530 27-40-04-01 27-40-04-01	Conductor cross-section, max. Cross-section for connected wire ETIM 7.0 ECLASS 9.1	16 mm ² 10 - 16 mm ² EC001530 27-40-04-01

VT SF 6/21 MC NE BL VO

Drawings



Weidmüller Interface GmbH & Co. KG Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Labels & Markers category:

Click to view products by Weidmuller manufacturer:

Other Similar products are found below :

89078GBEST 89082GBESR 89082GBEST PCL025-4 5761-2SF 58400 586R734H02 M1.040.0000.6 CRS-CM5M CRS-M18M CS1836-000 CS8626-000 CU6337-000 CU6342-000 CU6343-000 CWD01-0 CWD012-0 CWD012-7 CWD015-3 CWD015-7 CWD02-0 CWD02-3 CWD02-4 CWD02-6 CWD02-8 CWD02-A CWD02-D CWD02-H CWD02-K CWD02-L CWD02-M CWD02-P CWD02-Q CWD02-R CWD02-U CWD02-W CWD02-Y CWD03-+ CWD03-0 CWD03-P CWD06-0 CWD06-8 CWD06-9 CWD06-L CWD06-N CWD09-0 CWD09-5 CWD09-7 6806810001 CZ2857-000