



#### ALL APN ■ AND UPC ● CODE NUMBERS SHOWN ARE PRECEDED BY THE MANUFACTURER APN OR UPC I.D. NUMBER ■ 9337103 & ● 037103.

Weller products have been serving the scientifc, industrial and do-it-yourself markets since 1945. The Australian plant at Albury/Wodonga manufactures a full range of soldering and desoldering tools and aids that are designed to comply with Australian standards and the requirements of local conditions. Industry demands that soldering tools are extremely efficient with minimal maintenance. The technology gained in meeting these requirements has been incorporated throughout the consumer products as well.

#### **BENEFITS:**

- Iron is ready to use from new. No tip preparation by the purchaser required.
   Good thermal conductivity with corrosion protection for longer life.
- 3. Heats up quickly. Rugged long life element.
- 4. Minimal deterioration over long periods.
- 5. User comfort even after long periods of use.
- 6. The right iron available for the right job to give the best results.
- 7. Safe to use.



#### **Marksman Soldering Irons (Line Voltage)**

All irons blister packaged on hang-up card. SP250D also with stand. SP15D & SP25D - Nickel Plated. SP40D, SP80D, SP120D, SP175D & SP250D Iron plated.

	Material Number	Description Watt / Volt / Hertz	APN/UPC	Shelf Pack
SP15D (15 watt)	SP15D	15 Watt / 240 Volt / 50 Hertz	<b>473686</b>	3
	Letter Market	Pencil grip. Light duty soldering iron. 210mm long. 400°C tip temperature. Replaceable screw-in tip. Recommended Use: Electronic or transistor kit work. Printed circuit board work where a fine tip is required.		
SP25DAU (25 watt)	SP25DAU	25 Watt / 240 Volt / 50 Hertz	<b>475901</b>	3
Weller materiasis		Pencil grip. 210mm long. 400°C tip temperature. Replaceable screw-in tip. Recommended Use: Light home and hobby iron suitable for printed circuit board work, light electrical soldering. SP25DK for Woodburning.		
SP40DAU (40 watt)	SP40DAU	40 Watt / 240 Volt / 50 Hertz	<b>475925</b>	3
		Pencil grip. Weighs only 56g. 209mm long. Replaceable 6.35mm (diameter) tip. <b>Recommended Use:</b> Suitable for general home soldering of electrical wiring and connections.		
SP80DAU (80 watt)	SP80DAU	80 Watt / 240 Volt / 50 Hertz	<b>475932</b>	3
		Pencil grip. Weighs only 113g. 238mm long. Replaceable 9.52mm (diameter) tip. Recommended Use: Medium wattage iron for electrical soldering. Suitable for light alloy or metal soldering. SPG80D for leadlight soldering.		
SP120DAU (120 watt)	SP120DAU	120 Watt / 240 Volt / 50 Hertz	<b>474539</b>	3
		Medium duty soldering iron. Weighs only 283g. 289mm long. Replaceable 12.70mm (diameter) tip. Recommended Use: Heavy electrical connections and light sheetmetal work.		
SP175DAU (175 watt)	SP175DAU	175 Watt / 240 Volt / 50 Hertz	<b>474676</b>	3
		Heavy duty soldering iron. Weighs 435g. 317mm long. Replaceable 15.87mm (diameter) tip. Recommended Use: Suitable for very heavy cable and medium gauge sheetmetal. eg.: guttering.		
SP250D (250 watt)	SP250D	250 Watt / 240 Volt / 50 Hertz	<b>476625</b>	3
		Heavy duty soldering iron. Weighs 510g. 350mm long. Replaceable 20mm (diameter) tip. Recommended Use: Heavy sheetmetal assembly.		
FEATURES:				
Pre-tinned tip.     Electroplated copper tips.     Ceramic filled element.     Stainess Steel metal components.     Stay cool handle material and design.				
6. A range of 10 wattage sizes and kits.				,

7. Fully approved by Electrical Authority.



ALL APN ■ AND UPC • CODE NUMBERS SHOWN ARE PRECEDED BY THE MANUFACTURER APN OR UPC I.D. NUMBER ■ 9337103 & • 037103.

## Marksman Soldering Irons (Line Voltage)





WHK30AU



- 15 piece set, including 12 tips, ideal for wood burning, sculpting, adding accents, stencil cutting, pattern transfers, hot knife cutting, embossing and branding
- 30 Watt short barrel Woodburning Iron
- Set contains 6 Woodburning tips, Hot Knife Tip with Blade Chuck, Pattern Transfer Tip, 3 Branding Tips, Iron Stand and complete Project Book
- Boxed in plastic presentation case

SPG80DAU







WLC80D

TB100AU

## Temperature Controlled Irons - Magnastat®

W60D	60 Watt - (Temp. controlled)	<u>^</u>	<b>474089</b>	3
W100D	100 Watt - (Temp. controlled)		<b>474263</b>	3
T0056107599	W201D 230V Magnastat® Tool		4003019029563	

- Industrial Soldering Pencils, ideal for electronic work
- Magnastat Controlled

#### **Therma-Boost Soldering Tool**

	_		
TB100AU	30W-130W/230V	■ 002121	5

 Therma-Boost trigger gives added bursts of power when needed (130W Therma-Boost, 30W Std) Kit includes Therma-Boost heat tool, six multiple use tips, stand and instructions

## **Woodburning Tips**





## Woodburning Tips (for SPW25DK)

MT5	Conical (2 per card)	<b>303020</b>	1
MT8	Chisel (2 per card)	<b>478063</b>	1
МТ9	Knife edge (2 per card)	<b>478070</b>	1

#### **Tips for Marksman Irons**



MT05AU	Tip 2mm/3/32 Spade - SP15D 2 Per Card	■ 472795	1
MT10	Tip 6mm/1/4 Chisel - SP40D 2 Per Card	<b>473617</b>	1
MTG30	Tip 13mm/1/2 Chisel - SP120D	<b>477905</b>	1
MTG40	Tip 16mm/5/8 Chisel - SP175D	<b>478674</b>	1
MT50	Tip 19mm/3/4 Chisel - SP250D	<b>480156</b>	1

## **Tips for SP25D Marksman Iron**



MT1	Tip 4mm/5/32 Cone 2 Per Card	<b>472177</b>	1
MT2	Tip 4mm/5/32 S/driver 36•50 2 Per Card	<b>472412</b>	1
МТЗ	Tip 4mm/5/32 Chisel 2 Per Card	<b>472504</b>	1

#### **Iron Plated Tips for Marksman Irons**





MTG20	Straight Tip 10mm/3/8 S/driver - SP80D	<b>476595</b>	1
MTG21	Straight Tip 6mm/1/4 S/driver - SP80D	<b>476601</b>	1
MTG22	Beading Tip	■ 300869	1

ALL APN ■ AND UPC ● CODE NUMBERS SHOWN ARE PRECEDED BY THE MANUFACTURER APN OR UPC I.D. NUMBER ■ 9337103 & ● 037103.

### **Magnastat Controlled Station**



Material Number	Description	APN/UPC	Shelf Pack
WTCPTD	Soldering Station	<b>476441</b>	1

#### Consists of:

- TC202DT2 230V Power Unit
- TC201B 42 Watt 24V Pencil
- PH1201 Stand
- 1.6mm 700°F/371°C tip
- Soldering Tips PT Series available (refer Cooper Tools Electronic Catalogue)

#### **Temperature Controlled Station**



T0056806599	WHS40 Soldering Station - 40W/230V	4003019418107	1
T0056828599	WHS40D Soldering Station - 40W/240V - Digital	4003019412952	1

- 3.5mm straight nickel tip
- Ergonomic contoured handle Hot-iron holder

- Tip-cleaning sponge
  40W, 18V low voltage
  Connector for iron lead
  LED optical
- Temperature control dial (200°C-450°C)
  Mains 230V
- Meets Australian and European safety and approval CE

T0054311399	2mm Tip	
T0054311599	3.5mm Tip	

## **Electronically Controlled Station**



WES51D	Soldering Station	■ 339661	1

An economical soldering station with High-End Performance. Ideal for continuous production soldering.

- Analogue temperature controlTemperature lockout

- Automatic shut off
   Slim comfortable pencil reduced operator fatigue
   Temperature range 150°C-450°C
   Max. power output 50W

- Assembled in Australia
   Soldering station consists of:
   WES51DPU 230V Power Unit
   PES51 50 Watt 24V Pencil
   PH50 Holder

- Soldering Tips ET Series available (refer Cooper Tools Electronic Catalogue)

## **Pyropens**



WPA2	Piezo ignition (self) lighting	■ 590437	1
Kit includes:  • 1 x WPT-2 sold  • 1 x WHC-52 hof  • Metal kit box See Cooper Tools			
			_

WSTA3	Soldering, hot blow and torch flame	<b>472283</b>	1
	facilities		

- Kit includes:
   1 x soldering tip
   1 x hot blow tip
- Torch ejector tightening barMetal Kit box.

See Cooper Tools Electronic Catalogue for Tool Selection.

WSTA6	Jnr pocket size with auto ignition	5012535052657	1
-------	------------------------------------	---------------	---

- Fitted with pocket clip
  Suitable for soldering and hot blow applications
  1 x WPT-01 tip

See Cooper Tools Electronic Catalogue for Tool Selection

WSTA5	Jumbo. (self igniting)	■ 370701	1
WOIAJ	Julibo, (Seli julililia)	<b>370701</b>	

- Soldering temperature range 250°-500°C
   1 x 72-01-02 tip
   1 x hot blow tip
   Torch ejector with tightening bar

Metal Kit box.
See Cooper Tools Electronic Catalogue for Tool Selection.



ALL APN ■ AND UPC • CODE NUMBERS SHOWN ARE PRECEDED BY THE MANUFACTURER APN OR UPC I.D. NUMBER ■ 9337103 & • 037103.

#### **Weller Portasol**



Material Number	Description	APN/UPC	Shelf Pack
P1C	Port. Cord/1 refill gas pow. Soldering tool Carded	• 593368	6


- Does not require cords, batteries or cartridges
- Patented soldering tool has a catalytic converter that provides a powerful yet safe flameless combustion
- Refills with butane fuel Weller® BR2000
- Tank holds gas for 90 minute operation
- Ideal for a wide variety of soldering and desoldering jobs at work or at home
- Develops 850°F/454°C



Port. Cord/1 refill gas pow. Soldering tool Carded P1KC • 593382 4

- Safety cut off switch when cap replaced
- Flint-spark ignitor in cap
- Packed in a rugged plastic case
- Adjustable temperature control regulates the power (the equivalent of 10-60 watts) to quickly heat the
- Kit contains Portasol® P1 soldering tool, 3/32"/2.4mm iron-plated soldering tip, hot knife accessory, hot blower accessory, blow torch accessory, cleaning sponge and safety stand

• 169372



#### TIPS FOR P1C and P1KC

T1AU	1.0mm (1/32") Soldering Tip	• 593412	5
T2AU	2.4mm (3/32") Soldering Tip	• 593429	5
T3AU	3.2mm (1/8") Soldering Tip	• 593436	5
T4AU	4.8mm (3/16") Soldering Tip	• 593443	5
T5AU	Blow Torch Tip	• 593450	5
T6AU	Hot Blower Tip	• 593467	5
T7AU	Hot Knife Tip	• 593399	5

#### **Butane Soldering**



PSI100K Butane Powered Soldering Iron • 06097	6 6
---	-----

- Piezo Ignition Self Lighting
- Kit includes:
- 1 x soldering, hot blow and cutting tip
- Torch flame facility
- Equivalent to 10 to 60 Watts.
- Tip includes:

P2KC

PSI-6, PSI-8, PSI-9, PSI-10

Refer to Electronic Catalogue for Tip Selection Chart.

Full range of PSI Tips are available.



P2KC	<b>Butane Powered Soldering Iron</b>

Multi-purpose Heat tool

- Soldering Iron Blow Torch
- **Hot Air Tool**
- Hot Knife

Piezo Ignition, Cordless and totally portable.
Refills in 20 secs with standard quality butane lighter fuel.

- Adjustable temperature control 15-75 watts
- Anti-static
- Catalytic combustion provides safe flameless combustion
- Iron plated tips
- Kit includes tips PPT12, PPT10, PPT9, PPT5.





#### **TIPS FOR P2KC**

PPT5	Double Flat Tip 1.0mm	5099681780054	1
PPT6	Double Flat Tip 2.4mm	5099681780061	1
PPT7	Double Flat Tip 3.2mm	5099681780078	1
PPT8	Double Flat Tip 4.8mm	5099681780085	1
PPT9	Hot Blower Tip	5099681780092	1
PPT10	Hot Knife Tip	5099681780108	1




ALL APN ■ AND UPC ● CODE NUMBERS SHOWN ARE PRECEDED BY THE MANUFACTURER APN OR UPC I.D. NUMBER ■ 9337103 & ● 037103.

### **Dual Heat Battery Powered Cordless Soldering Tool**







- Dual Heat gives two different working temperatures 454°C and 510°C
- Long lasting iron plated conical shape tip
- Solders up to 180 solder joints per battery charge
- Heating element in tip for super-fast heat-up, heats to working temperature in only 15 seconds
- LED work light illuminates your work in low light
- Ideal for field work where electricity is not available
- Perfect tool for light duty soldering jobs where portable is necessary



BP10	Conical Soldering Tip	• 215442	1
BP11	Chisel Soldering Tip	• 215688	1

#### **Blow Torch**



ML100	Butane Powered Magna Lite	• 212559	8
	Blow Torch		

- Applications include heat shrinking of tubing, fusing rope ends, un-freezing locks, camping, rist aid, laboratory work and boating, etc.
  Piezo electronic ignition system for reliable ignition every time
  Blue LED light illuminates work in dark conditions
  Adjustable flame height
  Refillable with Weller BR200 butane

- Nozzle cover prevents accidental ignition
- Keyring lanyard

- Handy portable torch for industrial maintenance, tool and die shops, automotive repairs, etc.
- Applications include soldering, brazing, heat shrink tubing, frozen locks, fusing rope ends, camping, boating, labs and more
  Waterproof Piezo electronic ignition system for fast and reliable ignition every time
  Adjustable flame height and length, and level of heat output (up to 1,300°C/2,400°F)
  Flame lock-on allows hands-free operation

- Up to 60 minutes continuous use

## **Magna-Lite Butane Soldering Iron**



#### ML500MP

Magna-Lite Butane Soldering Iron

• 220912

- Applications include soldering, heat shrink tubing, electrical, electronics, field service repair
- Waterproof piezo ignition for fast, reliable ignition Adjustable flame height
- Temperature adjustable from 400°C to 510°C 30 minute run time

- Also operates as a torch when soldering tip is removed Refills with standard butane gas (Weller BR200)

### **Portable Soldering Iron**



#### WPSI12V

12 Volt Portable Soldering Iron

**329471** 

- 42 Watt Battery Powered, with temperature control Powered by a 12 Volt, 7.2 amp hour sealed lead acidity battery
- Fitted with an automotive cigarette lighter plug for direct connection to other 12 Volt power sources 21 types of PT series tips available in 315°C,

- S71'C & 427'C
  Battery life of 2-8 hours dependant on usage
  Fluoro yellow carry pack with high visability
  reflective strip, carry strap & soldering tool stand
  3 stage automative battery charger included

NB: Butane Gas: The WELLER BR200 is suitable for P1-C, P-1KC & PP1K, ML100.

### **Butane Gas**





**BR200** 

**Butane Gas Refiller 200gms** 

**473600** 

12

## **Soldering Stands**



PH1260	suits SP15D, SP25D, SP40D	<b>474010</b>	1
PH12100	suits W100D, SP80D	<b>474027</b>	1



ALL APN ■ AND UPC • CODE NUMBERS SHOWN ARE PRECEDED BY THE MANUFACTURER APN OR UPC I.D. NUMBER ■ 9337103 & • 037103.

## Solder



Material Number			Shelf Pack
RC40AU	60/40 Alloy Rosin Core 1.6mm	<b>473853</b>	10

## **De-Soldering Pump**



WDS	De-soldering Pump	■ 332167	50

- High Suction Power
- Ideal for PC Board Repairing
- Lightweight
- · Easy to clean cylinder

## **Weller Cable Ties**





Available in black and natural.

Most popular sizes from
100mm to 550mm.

Packs of 25 or 100 pieces.
The black cable ties are
UV resistant, which prolongs useful life
under sunshine/outdoor applications.



WA350 - Weller Cable Ties Assortment Pack -Resealable Container

	Quantity	Colour	Size	Tensile Strength
ı	x 100	Natural	100mm x 2.5mm Ties	8kg
ı	x 100	Coloured	100mm x 2.5mm Ties	8kg
ı	x 50	Natural	200mm x 4.8mm Ties	18kg
ı	x 50	Coloured	200mm x 4.8mm Ties	18kg
ı	x 50	Coloured	280mm x 4.8mm Ties	22kg

Material Number	Description	Pack Qty	APN/UPC	Shelf Pack
WB425	Black 100mm x 2.5mm	25	<b>485009</b>	50
WB4100	Black 100mm x 2.5mm	100	<b>485061</b>	50
WN425	Natural 100mm x 2.5mm	25	■ 485207	50
WN4100	Natural 100mm x 2.5mm	100	■ 485269	50
WB625	Black 150mm x 3.6mm	25	<b>485016</b>	50
WB6100	Black 150mm x 3.6mm	100	<b>485078</b>	50
WN625	Natural 150mm x 3.6mm	25	<b>485214</b>	50
WN6100	Natural 150mm x 3.6mm	100	■ 485276	50
WB825	Black 200mm x 4.8mm	25	■ 485023	50
WB8100	Black 200mm x 4.8mm	100	■ 485085	50
WN825	Natural 200mm x 4.8mm	25	■ 485221	50
WN8100	Natural 200mm x 4.8mm	100	■ 485283	50
WB1225	Black 300mm x 4.8mm	25	<b>485030</b>	50
WB12100	Black 300mm x 4.8mm	100	■ 485092	50
WN1225	Natural 300mm x 4.8mm	25	■ 485238	50
WN12100	Natural 300mm x 4.8mm	100	■ 485290	50
WB1425	Black 370mm x 4.8mm	25	■ 485047	50
WB14100	Black 370mm x 4.8mm	100	<b>485108</b>	50
WN1425	Natural 370mm x 4.8mm	25	■ 485245	240
WN14100	Natural 370mm x 4.8mm	100	■ 485306	50
WB1525	Black 380mm x 7.6mm HD	25	■ 485252	150
WB15100	Black 380mm x 7.6mm HD	100	<b>485313</b>	40
WA350	350 piece Cable Tie Assortment	350	<b>485405</b>	25
WB5100HD	Black 120mm x 4.8mm HD	100	<b>485122</b>	50
WB12100HD	Black 300mm x 7.6mm HD	100	<b>485139</b>	50
WB18100HD	Black 450mm x 8.0mm HD	100	■ 485146	35
WB22100HD	Black 550mm x 8.0m HD	100	<b>485153</b>	25

## 8 Piece 1000V Insulated Screwdriver Set





SD8SET 8 Piece Screwdriver Set 4003019117222

Consists of:
Phillips® PH 1 x 100 / PH 2 x 100
Pozidrive PZ 1 x 100 / PZ 2 x 100
Slotted 2,5 x 80 / 4,0 x 100 / 6,5 x 150
Main Tester 140

- Insulated according Norm 1000V 06 IEC 60900:2004
- VDE / GS certificated
- Co-moulded handles for maximum comfort
- Blades made of 8660 steel

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Weller manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160